


## Technical data sheet Starter battery

Battery type	12V 90Ah +R LB4	Product code	CGA0820

Specification		
Nominal voltage	12 V	
Capacity (C20)	90 Ah at 25°C to 10,5V	
Reserve capacity	159 min	
(25A discharge)		
Cold cranking current (EN -18°C)	760 A	
Cold cranking current (DIN -18°C)	540 A	
Weight	20.2 kg ± 5%	
Technology	Flooded/SLI	

Overall dimensions	
Length	315 +0/-2 mm
Width	175 +0/-2 mm
Height	175 <sub>+0</sub> /-з mm
Base hold-down	B13
Layout	0
Terminal type	1
Container material	PP
Box color	Black
Lid color	Black

Electrolyte		
Electrolyte type	H <sub>2</sub> SO <sub>4</sub>	
Electrolyte spec density at 25°C	$1.28 \pm 0.01 \text{ g/cm}3$	



Cell properties		
Grid prod. technology	Punched	
+ grid alloy	PbCa	
+ strip / grid thickness	0.9 / 1.3 mm	
(-) grid	CE-	
Grid prod. technology	Expanded	
- grid alloy	PbCa	
- strip / grid thickness	0.75 / 1.25 mm	
Separator		
Туре	PE	
Thickness	1.0 - 1.2 mm	

5 notches
FRONT (B)

Terminal type	Key characteristics	
1	- Maintenance free	
• 19,5 • 17,9 • 17,9 • 17,9 • 17,9 • 17,9 • 17,9 • 19,5	- Wide range of application  - Universal EN design  - Lid type: K2 with push in plug	





Fabricado en C.E. según las normas ISO 9001 – ISO 14001 e I.P.P.C.

Date: 01/01/2020