

Tutorial of Class and Object (Basic)

Based on the tutorial of "2020S-Java-A" designed by teaching group in SUSTech

Designed by ZHU Yueming

Improved by WANG Wei

Modified (mainly change to markdown file) by ZHU Yueming in 2021. March. 29th

Minor changes by Yida Tao. Oct. 21 2022.

Objectives

- Learn how to define a Java class and create its object
- Learn how to define and use instance variables
- Learn how to define and use instance methods
- Learn how to use get and set methods
- Learn how to use `ArrayList` and make the object as its element.

Before Exercise

Attribute and Method

Step 1: How to define a circle on a 2-dimensional plane?

A circle has three attributes including the **radius**, the **x coordinate** and the **y coordinate**.

We can define a class named `Circle`, in which there are three private attributes.

```
public class Circle {  
    private double radius;  
    private double x;  
    private double y;  
}
```

Step 2: Define the methods of a circle.

Define three public methods for computing the area, perimeter and printing the position of the circle.

```
public class Circle {  
    private double radius;  
    private double x;  
    private double y;  
}
```

```
    public double area() {
        return radius*radius*Math.PI;
    }
    public double perimeter () {
        return 2*Math.PI*radius;
    }
    public void position() {
        System.out.printf("Position of the cricle is (%.1f,%.1f)\n",x,y);
    }
}
```

Step 3: How to use the class Circle?

Create another class named `CircleTest` in *the same package*, in which there is a `main` method to be used.

In the `main` method, we can create an object of `Circle` by using the statement as follows:

```
Circle c1=new Circle();
```

After that, we want to know the perimeter, area and position about the `c1`, so we need to invoke the method of `c1`.

```
public class CircleTest {
    public static void main(String[] args) {
        Circle c1=new Circle();
        System.out.printf("The area of c1 is %.2f\n", c1.area());
        System.out.printf("The perimeter of c1 is %.2f\n", c1.perimeter());
        c1.position();
    }
}
```

When we run the program, the result would be as follows:

```
The area of c1 is 0.00
The perimeter of c1 is 0.00
Position of the circle is (0.0,0.0)
```

Getter and Setter

Step 4: Set and get the values of the attributes

If we set or get the radius of a circle object in `main` method directly, it would lead to an error because of its private privilege.

In addition, the radius of a circle should not contain a negative number, how can we set the restriction?

```
public static void main(String[] args) {
    Circle c1=new Circle();
    System.out.printf("The area of c1 is %.2f\n", c1.area());
    System.out.printf("The perimeter of c1 is %.2f\n", c1.perimeter());
    c1.position();
    c1.radius=-1;
    System.out.println(c1.radius);
}
```

We can define several **public** methods in class **Circle** for getting or setting the class variables, and we can check the validity of input value in the **set** method.

```
public class Circle {
    private double radius;
    private double x;
    private double y;

    public double area() {
        return radius*radius*Math.PI;
    }
    public double perimeter () {
        return 2*Math.PI*radius;
    }
    public void position() {
        System.out.printf("Position of the cricle is (%.1f,%.1f)\n",x,y);
    }
    public double getRadius() {
        return radius;
    }
    public void setRadius(double radius) {
        if (radius > 0) {
            this.radius = radius;
        }
    }
    public double getX() {
        return x;
    }
    public void setX(double x) {
        this.x = x;
    }
    public double getY() {
        return y;
    }
    public void setY(double y) {
        this.y = y;
    }
}
```

After that, we can access the attributes by the `get` and `set` methods.

```
public static void main(String[] args) {  
    Circle c1=new Circle();  
    c1.setRadius(5);  
    System.out.println(c1.getRadius());  
  
    System.out.printf("The area of c1 is %.2f\n", c1.area());  
    System.out.printf("The perimeter of c1 is %.2f\n", c1.perimeter());  
    c1.position();  
}
```

Sample output:

```
5.0  
The area of c1 is 78.54  
The perimeter of c1 is 31.42  
Position of the circle is (0.0,0.0)
```

ArrayList

Step 5: How to manage multiple circle objects ?

We can use an array or an `ArrayList` to manage them.

In the `main` method, create an `ArrayList` with a `Circle` element type, to store multiple objects of `Circle`. Add the following code at the end of `main` method.

```
ArrayList<Circle> circleList=new ArrayList<Circle>();  
circleList.add(c1);  
System.out.printf("Radius of %d circle is %.2f: \n", 1 ,  
    circleList.get(0).getRadius());
```

Sample output:

```
5.0  
The area of c1 is 78.54  
The perimeter of c1 is 31.42  
Position of the circle is (0.0,0.0)  
Radius of 1  
circle is 5.00:
```

Step 6: Add more circles to the ArrayList

Add the following code at the end of `main` method.

```
for(int i=1;i<5;i++) {
    circleList.add(new Circle());
    circleList.get(i).setRadius(i);
    circleList.get(i).setX(Math.random()*5);
    circleList.get(i).setY(Math.random()*5);
}

System.out.println("---Begin to print the circle list---");
for(int i=0;i<5;i++) {
    System.out.printf("The area of %d circle is %.2f\n",
        i+1, circleList.get(i).area());
    System.out.printf("The perimeter is %.2f\n",
        circleList.get(i).perimeter());
}
```

Sample output:

```
5.0 The area of c1 is 78.54
The perimeter of c1 is 31.42
Position of the circle is (0.0,0.0)
Radius of 1 circle is 5.00:
---Begin to print the circle list--
The area of 1 circle is 78.54
The perimeter is 31.42
The area of 2 circle is 3.14
The perimeter is 6.28
The area of 3 circle is 12.57
The perimeter is 12.57
The area of 4 circle is 28.27
The perimeter is 18.85
The area of 5 circle is 50.27
The perimeter is 25.1
```

Exercise

Exercise 1 : User

Declare a class named `User`. The class contains:

- Private data fields:

```
String account;
```

```
String password;
```

```
double money;
```

- Implement a public method named **introduce()** to print the user account and his account balance.
- Implement a public method **withdraw(double value)**. It withdraws the money from the user account *if the password is correct*.
- Implement a public method **deposit(double value)**. It deposits the money to the user account.
- Implement the **getter** and **setter** methods for each private field of the class **User**.

In the same package, we create a class named **UserTest**, which has a main method.

```
public class UserTest {  
    public static void main(String[] args) {  
        User user =new User();  
  
        user.setUser("Lucy");  
        user.setPassword("123456");  
        user.setMoney(1000);  
        user.introduce();  
  
        user.withdraw(2000);  
        user.withdraw(500);  
        user.deposit(1000);  
  
        user.introduce();  
    }  
}
```

Sample Output:

```
Lucy's account has a balance of 1000.00 dollar  
Plan to withdraw 2000.00 dollar, but no sufficient balance  
Plan to withdraw 500.00 dollar, okay  
Please input your password:  
123  
password error,there are 2 times left to try  
Please input your password:  
123456  
Withdraw 500.00 dollar and balance is 500.00 dollar  
Got 1000.00 as income,balance is 1500.00 dollar  
Lucy's account has a balance of 1500.00 dollar
```

Exercise 2 : Food

Design a class named **Food**. The class contains:

- Private data fields:

int **id** ;

String **name**;

String **type**;

int **size**;

double **price**;

- Implement a public method `showInformation()` to print all the information of this particular food object.
- Implement the **getter** and **setter** method for each private field of Food.

In **FoodTest** class, create four objects of Food as follows:

Object Name	id	name	type	size	price
pizza1	1	pizza	Seafood	11	12
pizza2	2	pizza	Beef	9	10
Fried rice	3	fried rice	Seafood	5	12
Noodles	4	noodles	Beef	6	14

Create an `ArrayList<Food>` to add those four Food objects, and then show the information of them as follows by iterating the `ArrayList<Food>` and invoke `showInformation()` of each food object.

```

-----Menu-----
[id] 1  [type] Seafood  [name] pizza    [size] 11 (Inches) 12.00 $
[id] 2  [type] Beef    [name] pizza    [size] 9 (Inches) 10.00 $
[id] 3  [type] Seafood [name] fried rice [size] 5 (Inches) 12.00 $
[id] 4  [type] Beef    [name] noodles  [size] 6 (Inches) 14.00 $
-----Menu-----

```

Exercise 3: Combining Food and User

Design a class named **SoftOpening**. The class contains no data fields, yet it has several methods:

- Implement a public static method named `generateMenu()` to generate 4 object of Food and add them to the `ArrayList<Food>`.
- Implement a public static method named `getMenu(ArrayList<Food> foodList)` to print the items in the `ArrayList<Food>` as designed.
- Implement a public static method named `generateUser()` to generated a user whose account and money is get by using the Scanner object 'in'.
- Implement a public static method named `userConsume(ArrayList<Food> foodList, User user)` to invoke the `getMenu()`, ask user to select the foods in the Menu, count the cost and invoke the expense of the user.

- Invoke the method `introduce()` of the User object to show his/hers balance.

Statements in `main` method:

```
ArrayList<Food> foodList = generateMenu();
User user = generateUser();
user.introduce();
userConsume(foodList,user);
user.introduce();
```

Sample Output:

```
Generate a user, please input name: Alice
Balance($):100
Alice's account has a balance of 100.00 dollar
-----Menu-----
[id] 1  [type] Seafood    [name] pizza    [size] 11 (Inches) 12.00 $
[id] 2  [type] Beef      [name] pizza    [size] 9 (Inches) 10.00 $
[id] 3  [type] Seafood    [name] fried rice [size] 5 (Inches) 12.00 $
[id] 4  [type] Beef      [name] noodles  [size] 6 (Inches) 14.00 $
-----Menu-----
Please input the foodID and the number you want, to exit input 0
Food id (input 0 to end select):1
Number of this food:1
Food id (input 0 to end select):2
Number of this food:2
Food id (input 0 to end select):0
Select end
Plan to withdraw 32.00 dollar, okay
Please input your password:
123456
Withdraw 32.00 dollar and balance is 68.00 dollar
Alice's account has a balance of 68.00 dollar
```