Lab Questions: Lab Session 3

Deadline: 06.09.2017 11:59pm SGT

Complete all assignments below. Create a script file <yourMatricNo_Lab3>.py and use this script to save your answers (write the commands, not what the console displays after executing your commands) to those questions below that are marked with an asterisk *. These questions are 6 and 10. Once you are done with it, submit the file via iNTU.

Important!!! Please name the files according to the requirements, and upload each file separately and not in a Zip file or similar. The submission system closes at the deadline. Hence after that, you will get no marks for your solution.

- 1. Using the range function, create the following lists:
 - (a) [3, 4, 5, 6]
 - (b) [18, 16, 14, 12]
 - (c) [50, 45, 40, 35, 30, 5, 10, 15, 20, 25, 30]
- 2. Using the linspace function from the NumPy module (consider it is already imported as np), create the following vectors:
 - (a) [4, 6, 8]
 - (b) [-3, -6, -9, -12, -15]
 - (c) [9, 7, 5]
- 3. Create the following vectors twice, using linspace from the NumPy module (consider it is already imported as np) and using the range function:
 - (a) [1, 2, 3, 4, 5, 5, 4, 3, 2, 1]
 - (b) [4, 5, 4, 5, 4, 5, 4, 5, 4, 5]
- 4. Create a variable myEnd which stores a random integer in the range from 40 to 60 included. Then, using the range function, create a list myList filled with increasing integers (with a step of 3), starting from 1 and not exceeding myend.
- 5. Write an expression that refers to only the odd-numbered elements in a list (starting the counting from 0), regardless of the length of the list in other words, we would like to get elements located at index [1357...]. Test your expression on lists that have both an odd and even number of elements.
- 6. * Assume you are given two lists myList1 and myList2, both of unknown sizes.
 - (a) Using only methods from lists, remove the last element from myList1, remove the first element from myList2, concatenante these two new lists while adding a string element 'Hello' in between.
 - (b) Same question, without using any list method.
- 7. Consider that you have access to an array myArray that can have any length.

- (a) Write assignment statements that would store the first half of the array in one array variable fhalf and the second half in another array variable shalf. Make sure that your assignment statements are general, and work whether myArray has an even or odd number of elements (hint: use a rounding function).
- (b) Assign the first element of fhalf to 100. What happens to myArray? How would you answer to question (a) if you wanted to avoid this effect?
- 8. Create two variables rows and cols that are two random integers in the range from 1 to 5 included. Create a matrix (two dimension array) of all zeros with the dimensions given by the values of rows and cols.
- 9. Create a 5×3 matrix myMat (a two dimension array) filled of random values in [0,1). Then, replace the second row of myMat with zeros using a single command. Finally, again using a single command, apply the function $f(x) = 2^x + 1$ to all elements of the matrix.
- 10. * Assume you are given a variable myMat that contains a square matrix of an unknown dimension. Create a new square matrix myRandMat that is of the same dimension as myMat, but filled with random values in [0,1). Compute the square matrix myNewMat defined by:

$$\texttt{myNewMat} = (2 \cdot \texttt{myMat} + (\texttt{myRandMat})^2)$$

- 11. Create a three-dimensional matrix mat3d consisting of all ones and get its dimension.
- 12. Create the following vector C:

$$C = [0.7 \ 1.9 \ 3.1 \ 4.3 \ 5.5 \ 6.7 \ 7.9 \ 9.1 \ 10.3 \ 11.5 \ 12.7 \ 13.9 \ 15.1 \ 16.3 \ 17.5]$$

Then use reshape function from the NumPy module to create the following matrix D from the vector C (search for information on the reshape function by typing the command help(np.reshape) for example):

$$D = \begin{pmatrix} 0.7 & 1.9 & 3.1 & 4.3 & 5.5 \\ 6.7 & 7.9 & 9.1 & 10.3 & 11.5 \\ 12.7 & 13.9 & 15.1 & 16.3 & 17.5 \end{pmatrix}$$