

## Getting a datagram from source to dest.


IP datagram:

misc fields	source IP addr	dest IP addr	data
-------------	----------------	--------------	------

- datagram remains **unchanged**, as it travels source to destination
- addr fields of interest here

forwarding table in A

Dest. Net.	next router	Nhops
223.1.1		1
223.1.2	223.1.1.4	2
223.1.3	223.1.1.4	2



Network Layer 4-46


## Getting a datagram from source to dest.

forwarding table in A

Dest. Net.	next router	Nhops
223.1.1		1
223.1.2	223.1.1.4	2
223.1.3	223.1.1.4	2

Starting at A, send IP datagram addressed to B:

- look up net. address of B in forwarding table
- find B is on same net. as A
- link layer will send datagram directly to B inside link-layer frame
  - B and A are directly connected



Network Layer 4-47

## Getting a datagram from source to dest.


misc fields	223.1.1.1	223.1.2.3	data
-------------	-----------	-----------	------

Starting at A, dest. E:

- look up network address of E in forwarding table
- E on *different* network
  - A, E not directly attached
- routing table: next hop router to E is 223.1.1.4
- link layer sends datagram to router 223.1.1.4 inside link-layer frame
- datagram arrives at 223.1.1.4
- continued....

forwarding table in A

Dest. Net.	next router	Nhops
223.1.1		1
223.1.2	223.1.1.4	2
223.1.3	223.1.1.4	2



Network Layer 4-48

## Getting a datagram from source to dest.


misc fields	223.1.1.1	223.1.2.3	data
-------------	-----------	-----------	------

Arriving at 223.1.4, destined for 223.1.2.2

- look up network address of E in router's forwarding table
- E on same network as router's interface 223.1.2.9
  - router, E directly attached
- link layer sends datagram to 223.1.2.3 inside link-layer frame via interface 223.1.2.9
- datagram arrives at 223.1.2.3!!! (hooray!)

forwarding table in router

Dest. Net.	router	Nhops	interface
223.1.1	-	1	223.1.1.4
223.1.2	-	1	223.1.2.9
223.1.3	-	1	223.1.3.27



Network Layer 4-49