




Linked List


List



List

<http://www.gograph.com/vector-clip-art/queue.html>

List



Already bought
Eggs, Rice, Bread, Juice

Oh I forgot
Salmon

Ordered List – Unordered List

To Buy :

1. Bread
2. Milk
3. Eggs
4. Fruit
5. Rice
6. Pasta
7. Butter
8. Juice

Unordered List

Scores :

- | | |
|----------|----|
| 1. Bruce | 2 |
| 2. Tom | 3 |
| 3. Ben | 5 |
| 4. Max | 7 |
| 5. Tim | 7 |
| 6. Marry | 8 |
| 7. Ron | 9 |
| 8. Harry | 10 |

Ordered List
Ascending Order

$$98n^5 - 4n^4 + n^3 - 8n^2 + 5n + 7$$

Ordered List
Decending Order

Logical ADT : ขึ้นกับ application

1. Data : ของมีลำดับ มีปลาย หัว head และ/หรือ ท้าย tail Data Implementation ?
Python List
2. Methods : ขึ้นกับ และ list เป็น ordered list หรือไม่

Unordered List / Ordered List

- `List()` สร้าง empty list
- `isEmpty()` returns boolean ว่า empty list หรือไม่
- `size()` returns จำนวนของใน list
- `search(item)` returns ว่ามี item ใน list หรือไม่
- `index(item)` returns index ของ item กำหนดให้ item อยู่ใน list

unordered list

- `append(item)` adds item ท้าย list ไม่ Returns คิดว่า item ไม่มีอยู่ก่อนใน list
- `insert(pos,item)` adds item ที่ index pos ไม่ Returns คิดว่า item ไม่มีอยู่ก่อนใน list

ordered list

`add(item)` adds item เข้า list ตามลำดับ ไม่ Returns

- `remove(item)` removes & return item คิดว่า item มีอยู่ใน list
- `pop()` removes & return item ตัวสุดท้าย list_size >= 1
- `pop(pos)` removes & return item ตัวที่ index = pos list_size >= 1

List Implementation : C Sequential (Implicit) Array, Python List



A B C D


Problem : fix positions

C : Sequential Array


Python : List

insert **i** ? : shift out

head




head




delete : shift in

head



head



Linked List


Problem : Fix Positions

List


Unfix Positions

Linked List


ลำดับ order?



C List
Implicit (Sequential) Array (C)




Python : List



node

head 3



Logical linked list


Logical คือในความคิดของเรา

เช่น link แทนด้วยลูกศร แทนการเชื่อมโยงกัน


physical (implementation) โครงสร้างที่ใช้ในการสร้างจริง


เช่น link อาจใช้ pointer หรือ index ของ array

Solve Inserting Expensive Shifting Problem



Solve Deleting Expensive Shifting Problem





Linked List

Data :

1. data
 2. next (link)
 3. head
 4. tail ?
- node class
- list class




Node Class / List Class

1. Data :

 init () : constructor ให้ค่าตั้งต้น
 ↑ ↑
2 underscores 2 underscores

Node Class



```
p = node('A', None)
```

```
class node:

    def __init__(self, data, next = None):

        self.data = data

        if next is None:
            self.next = None
        else:
            self.next = next

    def __str__(self):
        return str(self.data)
```

List Class

class list:

```
""" unordered singly linked list
    with head
"""
```

```
def __init__(self):  
    self.head = None
```

```
""" unordered singly linked list
    with head & tail
"""
```

```
def __init__(self):  
    self.head = self.tail = None
```

```
def __init__(self, head = None):
```


```
""" unordered singly linked list
    can set default list
    with head, tail & size
    """
```

```
if head == None:
```

```
self.head = self.tail = None
```

```
self.size = 0
```

else:



```
self.head = head
```

```
t = self.head
```

```
self.size = 1
```

```
while t.next != None: # locating tail & find size
```

```
t = t.next
```

```
self.size += 1
```


```
self.tail = t
```



Methods

1. `__init__()` : ให้ค่าตั้งต้น
2. `size()`:
3. `isEmpty()`:
4. `append ()` : add at the end
5. `__str__()`:
6. `addHead()` : ให้ค่าตั้งต้น
7. `remove(item)`:
8. `removeTail()`:
9. `removeHead()` :
10. `isIn(item)`: / `search(item)`
11. . . .

Creating a List



`node('A', None)`

`class list:`

```
""" unordered singly linked list
with head """
```

```
def __init__(self):
    self.head = None
```

```
def append(self, data):
```

```
    """ add at the end of list """
```

```
    p = node(data)
```

```
    if self.head == None: # null list
        self.head = p
```

```
    else:
```

```
        t = self.head
```

```
        while t.next != None :
```

```
            t = t.next
```

```
        t.next = p
```

`class node:`

```
def __init__(self, data, next = None):
```


```
    self.data = data
```

```
    if next == None:
```

```
        self.next = None
```


```
    else:
```

```
        self.next = next
```



Insert After

`insertAfter('i', q)`




insert node data
after a node pointed by q

Why insert after ?
Can you insert before ?


Delete After

`deleteAfter(q)`

delete a node
after a node pointed by q



Design how to call.





```

    p is not None:
while p != None:
    print(p.data)
    p = p.next
}

```

Linked List VS Sequential Array



Sequential Array


- Insertion / Deletion Shifting Problem.
- Random Access.
- C array : Automatic Allocation.
Python List array : Dynamic Allocation
- Lifetime : C-array, Python List
 - from defined until its scope finishes.
- Only keeps data.

Linked List


- Solved.
- Sequential Access.
- Node : Dynamic Allocation.
- Node Lifetime : from allocated (C : malloc()/new, python: instantiate obj) until C: deallocated by free()/delete, Python : no reference.
- Need spaces for links.

Dummy Node


To insert & delete at 1st position change head ie. make special case.




“Dummy Node” solves the problem.




Empty List has a dummy node.



Head & Tail Nodes




Circular List




Why ptr to tail ? Why not ptr to head?

Doubly VS Singly Linked List



Doubly Circular List




Linked Stack



Check if it support every operations.

Linked Queue




Can switch front & rear ?

Linked Queue




front rear



How do they link?


Support every operations ?




enQueue ?
(insert)


deQueue ?
(delete)

Every operations ?





Lab : Riffle Shuffle



Lift up to 2 packets.

- Riffle Shuffle each node of each packet from the top.
- put the rest at the back of the result packet.

- Polynomial Expression
- Multilists
- Radix Sort

How about ... ?

$$A = 5x^3 + 4x^2 - 7x + 10$$

+

$$B = x^3 + 2x - 8$$

$$C = 6x^3 + 4x^2 - 5x + 2$$

$$5x^{85} + 7x + 1$$

+

$$x^{76} - 8$$

What data structure will you use?


Array?

Array?

Sparse -> Linked List
(has lots of 0 data)

Multilists

1. class หนึ่งๆ มีใครลงบ้าง 2. นร. คนหนึ่งๆ ลง class ไດบ้าง



Radix Sort

input: 64 8 216 512 27 729 0 1 343 125

0 1 512 343 64 125 216 27 8 729

0 1 2 3 4 5 6 7 8 9

8 729

1 216 27

0 512 125 343 64

0 1 2 3 4 5 6 7 8 9

64

27

8

1

0

125

216

343

512





729

0 1 2 3 4 5 6 7 8 9

output: 0 1 8 27 64 125 216 343 512 729

Radix Sort

input:



output: 0 1 8 27 64 125 216 343 512 729