


PIN	FUNCT	PIN	FUNCT
1	BP	40	BP
2	S1	39	S2
3	5B,5C	38	"LO BAT"
4	DP4	37	4G
5	4E	36	4F
6	4D	35	4A
7	4C	34	4B
8	DP3	33	COLON 2
9	3E	32	3G
10	3D	31	3F
11	3C	30	3A
12	DP2	29	3B
13	2E	28	COLON 1
14	2D	27	2G
15	2C	26	2F
16	DP1	25	2A
17	1E	24	2B
18	1D	23	1G
19	1C	22	1F
20	1B	21	1A

- NOTES:
1. DISPLAY TYPE: TN, REFLECTIVE, POSITIVE IMAGE (BLACK CHARACTERS - LIGHT BACKGROUND).
 2. OPERATING TEMP: -40 TO +113 DEG C.
 3. FIRST OPTICAL MINIMA - WIDE FIELD OF VIEW.
 4. STATIC DRIVE
 5. FRONT POLARIZER TO BE VERTICAL TO BE COMPATIBLE WITH POLARIZED SUNGLASSES.
 6. VIEW ANGLE: 1:30
 7. RoHS COMPLIANT.

 LXD LIQUID CRYSTAL DISPLAYS www.lxdinc.com	7300 ACC BLVD. RALEIGH, NC. 27617 (919) 600-6440 (800) 786-8710		DESCRIPTION 4.5X1 DIGITS	
	INFORMATION CONTAINED HEREIN IS PROPRIETARY TO LXD, AND MAY NOT BE USED OR DISCLOSED WITHOUT THE WRITTEN PERMISSION OF LXD		PART NUMBER H0049B	
	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE: MM ±0.25 INCH ±0.01		DRAWING 2414	REV A
	DRAWN RRN	DATE 08-11-2011	SHEET 1 OF 1	

A	ADDED RoHS, PART NUMBER WAS H0049A	04/24/2009	GBH
REV	DESCRIPTION	DATE	BY
REVISIONS			

DO NOT SCALE