

# Database Questions and Answers – Relational Algebra

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Relational Algebra”.

1. Relational Algebra is a \_\_\_\_\_ query language that takes two relations as input and produces another relation as an output of the query.

- a) Relational
- b) Structural
- c) Procedural
- d) Fundamental

[View Answer](#)

Answer: c

Explanation: This language has fundamental and other operations which are used on relations.

advertisement

2. Which of the following is a fundamental operation in relational algebra?

- a) Set intersection
- b) Natural join
- c) Assignment
- d) None of the mentioned

[View Answer](#)

Answer: d

Explanation: The fundamental operations are select, project, union, set difference, Cartesian product, and rename.

3. Which of the following is used to denote the selection operation in relational algebra?

- a) Pi (Greek)
- b) Sigma (Greek)
- c) Lambda (Greek)
- d) Omega (Greek)

[View Answer](#)

Answer: b

Explanation: The select operation selects tuples that satisfy a given predicate.

4. For select operation the \_\_\_\_\_ appear in the subscript and the \_\_\_\_\_ argument appears in the paranthesis after the sigma.

- a) Predicates, relation
- b) Relation, Predicates
- c) Operation, Predicates
- d) Relation, Operation

[View Answer](#)

Answer: a

Explanation: None.

advertisement

5. The \_\_\_\_\_ operation, denoted by  $-$ , allows us to find tuples that are in one relation but are not in another.

- a) Union
- b) Set-difference
- c) Difference
- d) Intersection

[View Answer](#)

Answer: b

Explanation: The expression  $r - s$  produces a relation containing those tuples in  $r$  but not in  $s$ .

6. Which is a unary operation:

- a) Selection operation
- b) Primitive operation
- c) Projection operation
- d) Generalized selection

[View Answer](#)

Answer: d

Explanation: Generalization Selection takes only one argument for operation.

7. Which is a join condition contains an equality operator:

- a) Equijoins
- b) Cartesian
- c) Natural
- d) Left

[View Answer](#)

Answer: a

Explanation: None.

advertisement

8. In precedence of set operators, the expression is evaluated from

- a) Left to left
- b) Left to right
- c) Right to left
- d) From user specification

[View Answer](#)

Answer: b

Explanation: The expression is evaluated from left to right according to the precedence.

9. Which of the following is not outer join?

- a) Left outer join
- b) Right outer join
- c) Full outer join

d) All of the mentioned

View Answer

Answer: d

Explanation: The FULL OUTER JOIN keyword combines the result of both LEFT and RIGHT joins.

10. The assignment operator is denoted by

a) ->

b) <-

c) =

d) ==

View Answer

Answer: b

Explanation: The result of the expression to the right of the  $\leftarrow$  is assigned to the relation variable on the left of the  $\leftarrow$ .

advertisement

### Sanfoundry Global Education & Learning Series – Database Management System.

To practice all areas of Database Management System, [here is complete set on 1000+ Multiple Choice Questions and Answers on Database Management System](#).

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our social networks below and stay updated with latest contests, videos, internships and jobs!

[Telegram](#) | [Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

# Database Questions and Answers – Tuple Relational Calculus and Domain Relational Calculus

[« Prev](#)[Next »](#)

This set of Database test focuses on “Tuple Relational Calculus and Domain Relational Calculus”.

1. Find the ID, name, dept name, salary for instructors whose salary is greater than \$80,000 .

- a)  $\{t \mid t \in \text{instructor} \wedge t[\text{salary}] > 80000\}$
- b)  $\exists t \in r (Q(t))$
- c)  $\{t \mid \exists s \in \text{instructor} (t[\text{ID}] = s[\text{ID}] \wedge s[\text{salary}] > 80000)\}$
- d) None of the mentioned

[View Answer](#)

Answer: a

Explanation: This expression is in tuple relational format.

2. A query in the tuple relational calculus is expressed as:

- a)  $\{t \mid P() \mid t\}$
- b)  $\{P(t) \mid t\}$
- c)  $\{t \mid P(t)\}$
- d) All of the mentioned

[View Answer](#)

^

Answer: c

Explanation: The tuple relational calculus, is a nonprocedural query language. It describes the desired information without giving a specific procedure for obtaining that information.

advertisement

3.

```
{t | ∃ s ∈ instructor (t[name] = s[name]
∧ ∃ u ∈ department (u[dept name] = s[dept name]
∧ u[building] = "Watson"))}
```

Which of the following best describes the query?

- a) Finds the names of all instructors whose department is in the Watson building
- b) Finds the names of all department is in the Watson building
- c) Finds the name of the department whose instructor and building is Watson
- d) Returns the building name of all the departments

[View Answer](#)

Answer: a

Explanation: This query has two "there exists" clauses in our tuple-relational-calculus expression, connected by and ( $\wedge$ ).

advertisement



4. Which of the following symbol is used in the place of except?

- a)  $\wedge$
- b)  $\vee$
- c)  $\neg$
- d)  $\sim$

[View Answer](#)

Answer: c

Explanation: The query  $\neg P$  negates the value of P.

5. "Find all students who have taken all courses offered in the Biology department." The expressions that matches this sentence is :

- a)  $\exists t \in r(Q(t))$
- b)  $\forall t \in r(Q(t))$
- c)  $\neg t \in r(Q(t))$
- d)  $\sim t \in r(Q(t))$

[View Answer](#)

Answer: b

Explanation:  $\forall$  is used denote "for all" in SQL.

6. Which of the following is the comparison operator in tuple relational calculus

- a)  $\Rightarrow$
- b)  $=$
- c)  $\epsilon$
- d) All of the mentioned

[View Answer](#)

Answer: b

Explanation: The comparison operators are ( $<$ ,  $\leq$ ,  $=$ ,  $\neq$ ,  $>$ ,  $\geq$ ).

7. An expression in the domain relational calculus is of the form

- a)  $\{P(x_1, x_2, \dots, x_n) \mid \langle x_1, x_2, \dots, x_n \rangle\}$
- b)  $\{x_1, x_2, \dots, x_n \mid \langle x_1, x_2, \dots, x_n \rangle\}$
- c)  $\{x_1, x_2, \dots, x_n \mid x_1, x_2, \dots, x_n\}$
- d)  $\{\langle x_1, x_2, \dots, x_n \rangle \mid P(x_1, x_2, \dots, x_n)\}$

[View Answer](#)



Answer: d

Explanation: Here  $x_1, x_2, \dots, x_n$  represent domain variables. P represents a formula composed of atoms, as was the case in the tuple relational calculus.

advertisement

8. Find the names of all instructors in the Physics department together with the course id of all courses they teach:

a)

$$\{ \langle c \rangle \mid \exists s (\langle c, a, s, y, b, r, t \rangle \in \text{section} \wedge s = \text{"Fall"} \wedge y = \text{"2009"} \vee \exists u (\langle c, a, s, y, b, r, t \rangle \in \text{section} \wedge s = \text{"Spring"} \wedge y = \text{"2010"}) \}$$

b)

$$\{ \langle n, c \rangle \mid \exists i, a (\langle i, c, a, s, y \rangle \in \text{teaches} \wedge \exists d, s (\langle i, n, d, s \rangle \in \text{instructor} \wedge d = \text{"Physics"})) \}$$

c)

$$\{ \langle n \rangle \mid \exists i, d, s (\langle i, n, d, s \rangle \in \text{instructor} \wedge s > 80000) \}$$

d)

$$\{ \langle i, n, d, s \rangle \mid \langle i, n, d, s \rangle \in \text{instructor} \wedge s > 80000 \}$$

[View Answer](#)

Answer: b

Explanation: None.

9. In domain relational calculus "there exist" can be expressed as

- a)  $(P1(x))$
- b)  $(P1(x)) \exists x$
- c)  $\forall x (P1(x))$
- d)  $\exists x (P1(x))$

[View Answer](#)

Answer: d

Explanation:  $\exists$  is used to denote "some" values in relational calculus.

advertisement

10. A set of possible data values is called

- a) Attribute
- b) Degree
- c) Tuple
- d) Domain

[View Answer](#)

Answer: d

Explanation: None.



**Sanfoundry Global Education & Learning Series – Database Management System.**

# Database Questions and Answers – Modification of Database

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Modification of Database”.

1. A Delete command operates on \_\_\_\_\_ relation.

- a) One
- b) Two
- c) Several
- d) Null

[View Answer](#)

Answer: a

Explanation: Delete can delete from only one table at a time.



advertisement

2.

Delete from r where P;

The above command

- a) Deletes a particular tuple from the relation
- b) Deletes the relation
- c) Clears all entries from the relation
- d) All of the mentioned

[View Answer](#)

Answer: a

Explanation: Here P gives the condition for deleting specific rows.

3. Which one of the following deletes all the entries but keeps the structure of the relation.

- a) Delete from r where P;
- b) Delete from instructor where dept name= 'Finance';
- c) Delete from instructor where salary between 13000 and 15000;
- d) Delete from instructor;

[View Answer](#)

Answer: d

Explanation: Absence of condition deletes all rows.



4. Which of the following is used to insert a tuple from another relation?

- a)

```
INSERT INTO course (course id, title, dept name, credits)
VALUES ('CS-437', 'DATABASE Systems', 'Comp. Sci.', 4);
```

b)

advertisement

```
INSERT INTO instructor
SELECT ID, name, dept name, 18000
FROM student
WHERE dept name = 'Music' AND tot cred > 144;
```

c)

```
INSERT INTO course VALUES ('CS-437', 'DATABASE Systems', 'Comp. Sci.', 4);
```

d) Not possible

[View Answer](#)

Answer: b

Explanation: Using select statement in insert will include rows which are the result of the selection.

5. Which of the following deletes all tuples in the instructor relation for those instructors associated with a department located in the Watson building which is in department relation. ^

a)

```
DELETE FROM instructor
WHERE dept_name IN 'Watson';
```

b)

advertisement

```
DELETE FROM department
WHERE building='Watson';
```

c)

```
DELETE FROM instructor
WHERE dept_name IN (SELECT dept_name
                    FROM department
                    WHERE building = 'Watson');
```

d) None of the mentioned

[View Answer](#)

Answer: c

Explanation: The query must include building=watson condition to filter the tuples.

6.

```
UPDATE instructor
____ salary= salary * 1.05;
```

Fill in with correct keyword to update the instructor relation.

- a) Where
- b) Set
- c) In
- d) Select

View Answer

Answer: b

Explanation: Set is used to update the particular value.

7. \_\_\_\_\_ are useful in SQL update statements, where they can be used in the set clause.

- a) Multiple queries
- b) Sub queries
- c) Update
- d) Scalar subqueries

View Answer

Answer: d

Explanation: None.

advertisement

8. The problem of ordering the update in multiple updates is avoided using

- a) Set
- b) Where
- c) Case

^

d) When

View Answer

Answer: c

Explanation: The case statements can add the order of updating tuples.

9. Which of the following is the correct format for case statements.

a)

```
CASE
WHEN pred1 ... result1
WHEN pred2 ... result2
. . .
WHEN predn ... resultn
ELSE result0
END
```

b)

```
CASE
WHEN pred1 THEN result1
WHEN pred2 THEN result2
. . .
WHEN predn THEN resultn
ELSE result0
END
```

c)

```
CASE
WHEN pred1 THEN result1
WHEN pred2 THEN result2
. . .
WHEN predn THEN resultn
ELSE result0
```

d) All of the mentioned

View Answer

Answer: b

Explanation: None.





10. Which of the following relation updates all instructors with salary over \$100,000 receive a 3 percent raise, whereas all others receive a 5 percent raise.

a)

```
UPDATE instructor
SET salary = salary * 1.03
WHERE salary > 100000;
UPDATE instructor
SET salary = salary * 1.05
WHERE salary <= 100000;
```

b)

```
UPDATE instructor
SET salary = salary * 1.05
WHERE salary < (SELECT avg (salary)
FROM instructor);
```

c)

```
UPDATE instructor
SET salary = CASE
WHEN salary <= 100000 THEN salary * 1.03
ELSE salary * 1.05
END
```

d) None of the mentioned


View Answer

Answer: a

Explanation: The order of the two update statements is important. If we changed the order of the two statements, an instructor with a salary just under \$100,000 would receive an over 8 percent raise. SQL provides a case construct that we can use to perform both the updates with a single update statement, avoiding the problem with the order of updates.

### Sanfoundry Global Education & Learning Series – Database Management System.

To practice all areas of Database Management System, [here is complete set on 1000+ Multiple Choice Questions and Answers on Database Management System](#).

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our so  networks below and stay updated with latest contests, videos, internships and jobs!

[Telegram](#) | [Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

- « [Prev - Database Questions and Answers – Aggregate Functions and Nested Subqueries – 2](#)  
» [Next - Database Questions and Answers – Join Expressions](#)

Join Sanfoundry@YouTube

## Advanced C Programming - Introduction (+5 Tricky Code with Solution) | San...



### Recommended Posts:

1. [C Programming Examples on Arrays](#)
2. [RDBMS Questions and Answers](#)
3. [Java Programming Examples on Arrays](#)
4. [C Programming Examples on Strings](#)
5. [C Programming Examples on File Handling](#)
6. [Python Programming Examples on Stacks & Queues](#)
7. [Database Management System Questions and Answers](#)
8. [Oracle Database Questions and Answers](#)
9. [MySQL Database Questions and Answers](#)
10. [Database Questions and Answers – Integrity Constraints](#)
11. [Database Questions and Answers – Database Design Process](#)
12. [SQL Server Questions and Answers – Modifying Data – 1](#)
13. [Database Questions and Answers – SQL Basics and SQL Data Definition](#)
14. [Database Questions and Answers – Relational Database and Database Schema](#)
15. [Database Questions and Answers – Implementation of Isolation Levels](#)
16. [Database Questions and Answers – Triggers](#)
17. [Database Questions and Answers – Functions and Procedures](#)
18. [Database Questions and Answers – Functional-Dependency Theory](#)
19. [Database Questions and Answers – Aggregate Functions and Nested Subqueries – 1](#)
20. [Database Questions and Answers – Authorizations](#)

advertisement





[Manish Bhojasia](#), a technology veteran with 20+ years @ Cisco & Wipro, is Founder and CTO at Sanfoundry. He is Linux Kernel Developer & SAN Architect and is passionate about competency developments in these areas. He lives in Bangalore and delivers focused training sessions to IT professionals in Linux Kernel, Linux Debugging, Linux Device Drivers, Linux Networking, Linux Storage, Advanced C Programming, SAN Storage Technologies, SCSI Internals & Storage Protocols such as iSCSI & Fiber Channel. Stay connected with him @ [LinkedIn](#) |

[Youtube](#) | [Instagram](#) | [Facebook](#) | [Twitter](#)

### Subscribe Sanfoundry Newsletter and Posts

Subscribe

[About](#) | [Certifications](#) | [Internships](#) | [Jobs](#) | [Privacy Policy](#) | [Terms](#) | [Copyright](#) | [Contact](#)



© 2011-2021 Sanfoundry. All Rights Reserved.



# Database Questions and Answers – Views

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Views”.

1. Which of the following creates a virtual relation for storing the query?

- a) Function
- b) View
- c) Procedure
- d) None of the mentioned

[View Answer](#)

Answer: b

Explanation: Any such relation that is not part of the logical model, but is made visible to a user as a virtual relation, is called a view.

advertisement



2. Which of the following is the syntax for views where v is view name?

- a) Create view v as "query name";
- b) Create "query expression" as view;
- c) Create view v as "query expression";
- d) Create view "query expression";

View Answer

Answer: c

Explanation: <query expression> is any legal query expression. The view name is represented by v.

3.

```
SELECT course_id
FROM physics_fall_2009
WHERE building= 'Watson';
```

Here the tuples are selected from the view. Which one denotes the view.

- a) Course\_id
- b) Watson
- c) Building
- d) physics\_fall\_2009

View Answer

Answer: c

Explanation: View names may appear in a query any place where a relation name may appear. ^

4. Materialised views make sure that

- a) View definition is kept stable
- b) View definition is kept up-to-date

- c) View definition is verified for error
- d) View is deleted after specified time

View Answer

Answer: b

Explanation: None.

5. Updating the value of the view

- a) Will affect the relation from which it is defined
- b) Will not change the view definition
- c) Will not affect the relation from which it is defined
- d) Cannot determine

View Answer

Answer: a

Explanation: None.

advertisement

6. SQL view is said to be updatable (that is, inserts, updates or deletes can be applied on the view) if which of the following conditions are satisfied by the query defining the view?

- a) The from clause has only one database relation
- b) The query does not have a group by or having clause
- c) The select clause contains only attribute names of the relation and does not have ..., expressions, aggregates, or distinct specification
- d) All of the mentioned

View Answer

Answer: d

Explanation: All of the conditions must be satisfied to update the view in sql.

7. Which of the following is used at the end of the view to reject the tuples which do not satisfy the condition in where clause?

- a) With
- b) Check
- c) With check
- d) All of the mentioned

View Answer

Answer: c

Explanation: Views can be defined with a with check option clause at the end of the view definition; then, if a tuple inserted into the view does not satisfy the view's where clause condition, the insertion is rejected by the database system.

8. Consider the two relations instructor and department

Instructor:

ID	Name	Dept_name	Salary
1001	Ted	Finance	10000
1002	Bob	Music	20000
1003	Ron	Physics	50000

Department:

Dept_name	Building	Budget
Biology	Watson	40000
Chemistry	Painter	30000
Music	Taylor	50000

Which of the following is used to create view for these relations together?

a)

```
CREATE VIEW instructor_info AS  
SELECT ID, name, building
```

```
FROM instructor, department
WHERE instructor.dept name= department.dept name;
```

b)

advertisement

```
CREATE VIEW instructor_info
SELECT ID, name, building
FROM instructor, department;
```

c)

```
CREATE VIEW instructor_info AS
SELECT ID, name, building
FROM instructor;
```

d)

```
CREATE VIEW instructor_info AS
SELECT ID, name, building
FROM department;
```

[View Answer](#)

Answer: a

Explanation: None.





9. For the view Create view instructor\_info as

```
SELECT ID, name, building
FROM instructor, department
WHERE instructor.dept name= department.dept name;
```

If we insert tuple into the view as insert into instructor\_info values ('69987', 'White', 'Taylor');

What will be the values of the other attributes in instructor and department relations?

- a) Default value
- b) Null
- c) Error statement
- d) 0

[View Answer](#)

Answer: b

Explanation: The values take null if there is no constraint in the attribute else it is an Erroneous statement.

advertisement

10.

```
CREATE VIEW faculty AS
SELECT ID, name, dept name
FROM instructor;
```

Find the error in this query.

- a) Instructor
- b) Select

- c) View ...as
- d) None of the mentioned

View Answer

Answer: d

Explanation: Syntax is – create view v as <query expression>;.

### Sanfoundry Global Education & Learning Series – Database Management System.

To practice all areas of Database Management System, [here is complete set on 1000+ Multiple Choice Questions and Answers on Database Management System](#).

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our social networks below and stay updated with latest contests, videos, internships and jobs!

[Telegram](#) | [Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

« [Prev - Database Questions and Answers – Join Expressions](#)

» [Next - Database Questions and Answers – Transactions](#)

Join Sanfoundry@YouTube

Advanced C Programming - Introduction (+5 Trick...



### Recommended Posts:

1. [Machine Drawing Questions and Answers](#)
2. [Civil Engineering Drawing and Estimates Questions and Answers](#)
3. [Java Programming Examples on Utility Classes](#)
4. [Genetic Engineering Questions and Answers](#)
5. [MongoDB Questions and Answers](#)
6. [C# Programming Examples on Files](#)
7. [SQL Server Questions and Answers](#)
8. [RDBMS Questions and Answers](#)
9. [C# Programming Examples on LINQ](#)



# Database Questions and Answers – Extended E-R Features

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Extended E-R Features”.

1. The entity set person is classified as student and employee. This process is called \_\_\_\_\_
- a) Generalization
  - b) Specialization
  - c) Inheritance
  - d) Constraint generalization

[View Answer](#)

Answer: b

Explanation: The process of designating subgroupings within an entity set is called specialization ^

advertisement

2. Which relationship is used to represent a specialization entity?

- a) ISA
- b) AIS
- c) ONIS
- d) WHOIS

View Answer

Answer: a

Explanation: In terms of an E-R diagram, specialization is depicted by a hollow arrow-head pointing from the specialized entity to the other entity.

3. The refinement from an initial entity set into successive levels of entity subgroupings represents a \_\_\_\_\_ design process in which distinctions are made explicit.

- a) Hierarchy
- b) Bottom-up
- c) Top-down
- d) Radical

View Answer

Answer: c

Explanation: The design process may also proceed in a bottom-up manner, in which multiple entity sets are synthesized into a higher-level entity set on the basis of common features.

4. There are similarities between the instructor entity set and the secretary entity set in the set that they have several attributes that are conceptually the same across the two entity sets: name, the identifier, name, and salary attributes. This process is called

- a) Commonality
- b) Specialization

- c) Generalization
- d) Similarity

View Answer

Answer: c

Explanation: Generalization is used to emphasize the similarities among lower-level entity sets and to hide the differences.

advertisement

5. If an entity set is a lower-level entity set in more than one ISA relationship, then the entity set has
- a) Hierarchy
  - b) Multilevel inheritance
  - c) Single inheritance
  - d) Multiple inheritance

View Answer

Answer: d

Explanation: The attributes of the higher-level entity sets are said to be inherited by the lower-level entity sets.

6. A \_\_\_\_\_ constraint requires that an entity belong to no more than one lower-level entity set.
- a) Disjointness
  - b) Uniqueness
  - c) Special

## d) Relational

[View Answer](#)

Answer: a

Explanation: For example, student entity can satisfy only one condition for the student type attribute; an entity can be either a graduate student or an undergraduate student, but cannot be both.

7. Consider the employee work-team example, and assume that certain employees participate in more than one work team. A given employee may therefore appear in more than one of the team entity sets that are lower level entity sets of employee. Thus, the generalization is \_\_\_\_\_


- a) Overlapping
- b) Disjointness
- c) Uniqueness
- d) Relational

[View Answer](#)

Answer: a

Explanation: In overlapping generalizations, the same entity may belong to more than one lower-level entity set within a single generalization.

advertisement

8. The completeness constraint may be one of the following: Total generalization or specialization, Partial generalization or specialization. Which is the default? 

- a) Total
- b) Partial

- c) Should be specified
- d) Cannot be determined

View Answer

Answer: b

Explanation: Partial generalization or specialization – Some higher-level entities may not belong to any lower-level entity set.

9. Functional dependencies are a generalization of

- a) Key dependencies
- b) Relation dependencies
- c) Database dependencies
- d) None of the mentioned

View Answer

Answer: a

Explanation: The subclasses are combined to form the superclass.

10. Which of the following is another name for a weak entity?

- a) Child
- b) Owner
- c) Dominant
- d) All of the mentioned

View Answer

Answer: a

Explanation: A parent may be called as a strong entity.

advertisement



## Sanfoundry Global Education & Learning Series – Database Management System.

To practice all areas of Database Management System, [here is complete set on 1000+ Multiple Choice Questions and Answers on Database Management System.](#)

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our social networks below and stay updated with latest contests, videos, internships and jobs!

[Telegram](#) | [Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

« [Prev - Database Questions and Answers – Entity-Relationship Design Issues](#)

» [Next - Database Questions and Answers – Querying database part-1 DDL](#)

Join Sanfoundry@YouTube

Advanced C Programming - Introduction (+5 Tricky Code with Solution) | San...



## Recommended Posts:

1. [Master of Computer Applications Questions and Answers](#)
2. [C++ Programming Questions and Answers](#)
3. [Bachelor of Computer Applications Questions and Answers](#)
4. [Java Programming Examples on Arrays](#)
5. [Java Programming Examples](#)
6. [Java Programming Questions and Answers](#)
7. [Object Oriented Programming using C++ Questions and Answers](#)
8. [RDBMS Questions and Answers](#)
9. [C# Programming Examples](#)
10. [C# Programming Examples on LINQ](#)
11. [Python Programming Questions and Answers](#)
12. [C Programming Examples on File Handling](#)
13. [C# Programming Examples on Strings](#)
14. [Java Programming Examples on Classes](#)





15. [C# Programming Examples on Networking](#)
16. [Java Programming Examples on Inheritance](#)
17. [MySQL Database Questions and Answers](#)
18. [C# Programming Examples on Inheritance](#)
19. [Database Management System Questions and Answers](#)
20. [Oracle Database Questions and Answers](#)

advertisement



[Manish Bhojasia](#), a technology veteran with 20+ years @ Cisco & Wipro, is Founder and CTO at Sanfoundry. He is Linux Kernel Developer & SAN Architect and is passionate about competency developments in these areas. He lives in Bangalore and delivers focused training sessions to IT professionals in Linux Kernel, Linux Debugging, Linux Device Drivers, Linux Networking, Linux Storage, Advanced C Programming, SAN Storage Technologies, SCSI Internals & Storage Protocols such as iSCSI & Fiber Channel. Stay connected with him @ [LinkedIn](#) |

[Youtube](#) | [Instagram](#) | [Facebook](#) | [Twitter](#)

Subscribe Sanfoundry Newsletter and Posts

Subscribe

[About](#) | [Certifications](#) | [Internships](#) | [Jobs](#) | [Privacy Policy](#) | [Terms](#) | [Copyright](#) | [Contact](#)



© 2011-2021 Sanfoundry. All Rights Reserved.



# Database Questions & Answers – Normal Forms

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Normal Forms”.

1. In the \_\_\_\_\_ normal form, a composite attribute is converted to individual attributes.

- a) First
- b) Second
- c) Third
- d) Fourth

[View Answer](#)

Answer: a

Explanation: The first normal form is used to eliminate the duplicate information.

advertisement

^

2. A table on the many side of a one to many or many to many relationship must:

- a) Be in Second Normal Form (2NF)
- b) Be in Third Normal Form (3NF)
- c) Have a single attribute key
- d) Have a composite key

[View Answer](#)

Answer: d

Explanation: The relation in second normal form is also in first normal form and no partial dependencies on any column in primary key.

3. Tables in second normal form (2NF):

- a) Eliminate all hidden dependencies
- b) Eliminate the possibility of a insertion anomalies
- c) Have a composite key
- d) Have all non key fields depend on the whole primary key

[View Answer](#)

Answer: a

Explanation: The relation in second normal form is also in first normal form and no partial dependencies on any column in primary key.

4. Which-one of the following statements about normal forms is FALSE?

- a) BCNF is stricter than 3 NF
- b) Lossless, dependency -preserving decomposition into 3 NF is always possible
- c) Loss less, dependency – preserving decomposition into BCNF is always possible
- d) Any relation with two attributes is BCNF

[View Answer](#)



Answer: c

Explanation: We say that the decomposition is a lossless decomposition if there is no loss of information by replacing  $r(R)$  with two relation schemas  $r_1(R_1)$  and  $r_2(R_2)$ .

5. Functional Dependencies are the types of constraints that are based on\_\_\_\_\_

- a) Key
- b) Key revisited
- c) Superset key
- d) None of the mentioned

[View Answer](#)

Answer: a

Explanation: Key is the basic element needed for the constraints.

advertisement

6. Which is a bottom-up approach to database design that design by examining the relationship between attributes:

- a) Functional dependency
- b) Database modeling
- c) Normalization
- d) Decomposition

[View Answer](#)

Answer: c

Explanation: Normalisation is the process of removing redundancy and unwanted data.



7. Which forms simplifies and ensures that there are minimal data aggregates and repetitive groups:

- a) 1NF
- b) 2NF
- c) 3NF
- d) All of the mentioned

[View Answer](#)

Answer: c

Explanation: The first normal form is used to eliminate the duplicate information.

8. Which forms has a relation that possesses data about an individual entity:

- a) 2NF
- b) 3NF
- c) 4NF
- d) 5NF

[View Answer](#)

Answer: c

Explanation: A Table is in 4NF if and only if, for every one of its non-trivial multivalued dependencies  $X \twoheadrightarrow Y$ ,  $X$  is a superkey—that is,  $X$  is either a candidate key or a superset thereof.

9. Which forms are based on the concept of functional dependency:

- a) 1NF
- b) 2NF
- c) 3NF
- d) 4NF

[View Answer](#)

Answer: c

Explanation: The table is in 3NF if every non-prime attribute of  $R$  is non-transitively dependent (i.e. directly dependent) on every superkey of  $R$ .

advertisement



10.

Empdt1(empcode, name, street, city, state, pincode).

For any pincode, there is only one city and state. Also, for given street, city and state, there is just one pincode. In normalization terms, empdt1 is a relation in

- a) 1 NF only
- b) 2 NF and hence also in 1 NF
- c) 3NF and hence also in 2NF and 1NF
- d) BCNF and hence also in 3NF, 2NF and 1NF

View Answer

Answer: b

Explanation: The relation in second normal form is also in first normal form and no partial dependencies on any column in primary key.

### Sanfoundry Global Education & Learning Series – Database Management System.

To practice all areas of Database Management System, [here is complete set on 1000+ Multiple Choice Questions and Answers on Database Management System](#).

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our social networks below and stay updated with latest contests, videos, internships and jobs!

[Telegram](#) | [Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

« [Prev - Database Questions and Answers – Atomic Domains](#)

» [Next - Database Questions and Answers – Functional-Dependency Theory](#)

advertisement



# Database Questions and Answers – Functional-Dependency Theory

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Functional-Dependency Theory”.

1. We can use the following three rules to find logically implied functional dependencies. This collection of rules is called
- a) Axioms
  - b) Armstrong's axioms
  - c) Armstrong
  - d) Closure

[View Answer](#)

Answer: b

Explanation: By applying these rules repeatedly, we can find all of F+, given F.

advertisement



# Database Questions and Answers – Algorithms for Decomposition

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Algorithms for Decomposition”.

1. A relation is in \_\_\_\_\_ if an attribute of a composite key is dependent on an attribute of other composite key.
- a) 2NF
  - b) 3NF
  - c) BCNF
  - d) 1NF

[View Answer](#)

Answer: b

Explanation: A relation is in 3 NF if an attribute of a composite key is dependent on an attribute of other composite key. (If an attribute of a composite key is dependent on an attribute of other composite key then the relation is not in BCNF, hence it has to be decomposed.).

2. What are the desirable properties of a decomposition

- a) Partition constraint
- b) Dependency preservation
- c) Redundancy
- d) Security

View Answer

Answer: b

Explanation: Lossless join and dependency preserving are the two goals of the decomposition.

3. R (A,B,C,D) is a relation. Which of the following does not have a lossless join dependency preserving BCNF decomposition?

- a)  $A \rightarrow B$ ,  $B \rightarrow CD$
- b)  $A \rightarrow B$ ,  $B \rightarrow C$ ,  $C \rightarrow D$
- c)  $AB \rightarrow C$ ,  $C \rightarrow AD$
- d)  $A \rightarrow BCD$

View Answer

Answer: d

Explanation: This relation gives a relation without any loss in the values.

4.

Class (course id, title, dept name, credits, sec id, semester, **YEAR**, building, room **NUMBER**, capacity, **TI**  
The **SET OF** functional dependencies that we require **TO** hold **ON** class are:

course id->title, dept name, credits  
building, room number->capacity  
course id, sec id, semester, year->building, room **NUMBER**, **TIME** slot id  
A candidate **KEY FOR** this schema **IS** {course id, sec id, semester, **YEAR**}

Consider the above conditions. Which of the following relation holds?

- a) Course id-> title, dept name, credits
- b) Title-> dept name, credits
- c) Dept name-> credits
- d) Cannot be determined

[View Answer](#)

Answer: a

Explanation: Here course id is not a superkey. Thus, class is not in BCNF.

advertisement

5. The algorithm that takes a set of dependencies and adds one schema at a time, instead of decomposing the initial schema repeatedly is

- a) BCNF algorithm
- b) 2NF algorithm
- c) 3NF synthesis algorithm
- d) 1NF algorithm

[View Answer](#)

Answer: c

Explanation: The result is not uniquely defined, since a set of functional dependencies can have more than one canonical cover, and, further, in some cases, the result of the algorithm depends on the order in which it considers the dependencies in Fc. ^

6. The functional dependency can be tested easily on the materialized view, using the constraints

- \_\_\_\_\_.
- a) Primary key
  - b) Null
  - c) Unique
  - d) Both Null and Unique

[View Answer](#)

Answer: d

Explanation: Primary key contains both unique and not null constraints.

7. Which normal form is considered adequate for normal relational database design?

- a) 2NF
- b) 5NF
- c) 4NF
- d) 3NF

[View Answer](#)

Answer: d

Explanation: A relational database table is often described as “normalized” if it is in the Third Normal Form because most of the 3NF tables are free of insertion, update, and deletion anomalies.

advertisement

^

8. Relation R with an associated set of functional dependencies, F, is decomposed into BCNF. The redundancy (arising out of functional dependencies) in the resulting set of relations is

- a) Zero
- b) More than zero but less than that of an equivalent 3NF decomposition
- c) Proportional to the size of  $F^+$
- d) Indeterminate

View Answer

Answer: b

Explanation: Redundancy in BCNF is low when compared to 3NF. For more details on BCNF.

9. A table has fields F1, F2, F3, F4, and F5, with the following functional dependencies:

$F1 \rightarrow F3$

$F2 \rightarrow F4$

$(F1, F2) \rightarrow F5$

in terms of normalization, this table is in

- a) 1NF
- b) 2NF
- c) 3NF
- d) None of the mentioned

View Answer

Answer: a

Explanation: Since the primary key is not given we have to derive the primary key of the table. Using the closure set of attributes we get the primary key as (F1, F2). From functional dependencies, " $F1 \rightarrow F3$ ,  $F2 \rightarrow F4$ ", we can see that there is partial functional dependency therefore it is not in 1NF. Hence the table is in 1NF.

advertisement



10. Let  $R(A,B,C,D,E,P,G)$  be a relational schema in which the following FDs are known to hold:

$AB \rightarrow CD$

$DE \rightarrow P$

$C \rightarrow E$

$P \rightarrow C$

$B \rightarrow G$

The relation schema  $R$  is

- a) in BCNF
- b) in 3NF, but not in BCNF
- c) in 2NF, but not in 3NF
- d) not in 2NF

View Answer

Answer: d

Explanation: From the closure set of attributes we can see that the key for the relation is  $AB$ . The FD  $B \rightarrow G$  is a partial dependency, hence it is not in 2NF.

### Sanfoundry Global Education & Learning Series – Database Management System.

To practice all areas of Database Management System, [here is complete set on 1000+ Multiple Choice Questions and Answers on Database Management System](#).

Participate in the Sanfoundry Certification [contest](#) to get free Certificate of Merit. Join our social networks below and stay updated with latest contests, videos, internships and jobs!

[Telegram](#) | [Youtube](#) | [LinkedIn](#) | [Instagram](#) | [Facebook](#) | [Twitter](#) | [Pinterest](#)

« [Prev - Database Questions and Answers – Functional-Dependency Theory](#)

» [Next - Database Questions and Answers – Multivalued Dependencies](#)

advertisement



## Recommended Posts:

1. [Java Programming Examples on Hard Graph Problems & Algorithms](#)
2. [C++ Programming Examples on Hard Graph Problems & Algorithms](#)
3. [Java Programming Examples on Set & String Problems & Algorithms](#)
4. [MySQL Database Questions and Answers](#)
5. [C Programming Examples on Hard Graph Problems & Algorithms](#)
6. [C Programming Examples on Graph Problems & Algorithms](#)
7. [C++ Programming Examples on Combinatorial Problems & Algorithms](#)
8. [Data Structures & Algorithms II – Questions and Answers](#)
9. [C++ Programming Examples on Set & String Problems & Algorithms](#)
10. [RDBMS Questions and Answers](#)
11. [C Programming Examples on Set & String Problems & Algorithms](#)
12. [C++ Programming Examples on Numerical Problems & Algorithms](#)
13. [C Programming Examples on Numerical Problems & Algorithms](#)
14. [C Programming Examples on Computational Geometry Problems & Algorithms](#)
15. [Java Programming Examples on Numerical Problems & Algorithms](#)
16. [C++ Programming Examples on Computational Geometry Problems & Algorithms](#)
17. [Java Algorithms, Problems & Programming Examples](#)
18. [Java Programming Examples on Computational Geometry Problems & Algorithms](#)
19. [Oracle Database Questions and Answers](#)
20. [Database Management System Questions and Answers](#)

advertisement






[Manish Bhojasia](#), a technology veteran with 20+ years @ Cisco & Wipro, is Founder and CTO at Sanfoundry. He is Linux Kernel Developer & SAN Architect and is passionate about competency developments in these areas. He lives in Bangalore and delivers focused training sessions to IT professionals in Linux Kernel, Linux Debugging, Linux Device Drivers, Linux Networking, Linux Storage, Advanced C Programming, SAN Storage Technologies, SCSI Internals & Storage Protocols such as iSCSI & Fiber Channel. Stay connected with him @ [LinkedIn](#) |

[Youtube](#) | [Instagram](#) | [Facebook](#) | [Twitter](#)

### Subscribe Sanfoundry Newsletter and Posts

Subscribe

[About](#) | [Certifications](#) | [Internships](#) | [Jobs](#) | [Privacy Policy](#) | [Terms](#) | [Copyright](#) | [Contact](#)



© 2011-2021 Sanfoundry. All Rights Reserved.





# Database Questions and Answers – Keys

[« Prev](#)[Next »](#)

This set of Database Multiple Choice Questions & Answers (MCQs) focuses on “Keys”.

1. Which one of the following is a set of one or more attributes taken collectively to uniquely identify a record?

- a) Candidate key
- b) Sub key
- c) Super key
- d) Foreign key

[View Answer](#)

Answer: c

Explanation: Super key is the superset of all the keys in a relation.

advertisement



2. Consider attributes ID, CITY and NAME. Which one of this can be considered as a super key?

- a) NAME
- b) ID
- c) CITY
- d) CITY, ID

[View Answer](#)

Answer: b

Explanation: Here the id is the only attribute which can be taken as a key. Other attributes are not uniquely identified.

3. The subset of a super key is a candidate key under what condition?

- a) No proper subset is a super key
- b) All subsets are super keys
- c) Subset is a super key
- d) Each subset is a super key

[View Answer](#)

Answer: a

Explanation: The subset of a set cannot be the same set. Candidate key is a set from a super key which cannot be the whole of the super set.

4. A \_\_\_\_ is a property of the entire relation, rather than of the individual tuples in which each tuple is unique.

- a) Rows
- b) Key
- c) Attribute
- d) Fields

[View Answer](#)

Answer: b

Explanation: Key is the constraint which specifies uniqueness.

Join Sanfoundry@YouTube

### Advanced C Programming - Introduction (+5 Trick...



5. Which one of the following attribute can be taken as a primary key?

- a) Name
- b) Street
- c) Id
- d) Department

View Answer

Answer: c

Explanation: The attributes name, street and department can repeat for some tuples. But the id attribute has to be unique. So it forms a primary key.

6. Which one of the following cannot be taken as a primary key?

- a) Id
- b) Register number
- c) Dept\_id
- d) Street

View Answer

Answer: d

Explanation: Street is the only attribute which can occur more than once.

7. An attribute in a relation is a foreign key if the \_\_\_\_\_ key from one relation is used as an attribute in that relation.

- a) Candidate
- b) Primary

- c) Super
- d) Sub

View Answer

Answer: b

Explanation: The primary key has to be referred in the other relation to form a foreign key in that relation.

advertisement

8. The relation with the attribute which is the primary key is referenced in another relation. The relation which has the attribute as a primary key is called \_\_\_\_\_
- a) Referential relation
  - b) Referencing relation
  - c) Referenced relation
  - d) Referred relation

View Answer

Answer: c

Explanation: None.

9. The \_\_\_\_\_ is the one in which the primary key of one relation is used as a normal attribute in another relation.
- a) Referential relation
  - b) Referencing relation
  - c) Referenced relation

^

d) Referred relation

View Answer

Answer: c

Explanation: None.

10. A \_\_\_\_\_ integrity constraint requires that the values appearing in specified attributes of any tuple in the referencing relation also appear in specified attributes of at least one tuple in the referenced relation.

- a) Referential
- b) Referencing
- c) Specific
- d) Primary

View Answer

Answer: a

Explanation: A relation, say r1, may include among its attributes the primary key of another relation, say r2. This attribute is called a foreign key from r1, referencing r2. The relation r1 is also called the referencing relation of the foreign key dependency, and r2 is called the referenced relation of the foreign key.

advertisement

**Sanfoundry Global Education & Learning Series – Database Management System.**

To practice all areas of Database Management System, [here is complete set on 1000+ Multiple Choice Questions and Answers on Database Management System.](https://www.sanfoundry.com/database-mcqs-keys/)

# Database Questions and Answers – Multivalued Dependencies

[« Prev](#)[Next »](#)

This set of Database online quiz focuses on “Using Multivalued Dependencies”.

1. The normal form which satisfies multivalued dependencies and which is in BCNF is

- a) 4 NF
- b) 3 NF
- c) 2 NF
- d) All of the mentioned

[View Answer](#)

Answer: a

Explanation: Fourth normal form is more restrictive than BCNF.



advertisement

2. Which of the following is a tuple-generating dependencies?

- a) Functional dependency
- b) Equality-generating dependencies
- c) Multivalued dependencies
- d) Non-functional dependency

[View Answer](#)

Answer: c

Explanation: Multivalued dependencies, do not rule out the existence of certain tuples. Instead, they require that other tuples of a certain form be present in the relation.

3. The main task carried out in the \_\_\_\_\_ is to remove repeating attributes to separate tables.

- a) First Normal Form
- b) Second Normal Form
- c) Third Normal Form
- d) Fourth Normal Form

[View Answer](#)

Answer: a

Explanation: Multivalued dependencies, do not rule out the existence of certain tuples. Instead, they require that other tuples of a certain form be present in the relation.

4. Which of the normal form is based on multivalued dependencies?

- a) First
- b) Second
- c) Third
- d) Fourth

[View Answer](#)

Answer: d

Explanation: Multivalued dependencies, do not rule out the existence of certain tuples. Instead, they require that other tuples of a certain form be present in the relation.

advertisement

5. Which forms has a relation that possesses data about an individual entity?

- a) 2NF
- b) 3NF
- c) 4NF
- d) 5NF

View Answer

Answer: c

Explanation: A Table is in 4NF if and only if, for every one of its non-trivial multivalued dependencies  $X \twoheadrightarrow Y$ , X is a superkey—that is, X is either a candidate key or a superset thereof.

6. If a multivalued dependency holds and is not implied by the corresponding functional dependency, it usually arises from one of the following sources.

- a) A many-to-many relationship set
- b) A multivalued attribute of an entity set
- c) A one-to-many relationship set
- d) Both A many-to-many relationship set and A multivalued attribute of an entity set

View Answer



Answer: d

Explanation: For a many-to-many relationship set each related entity set has its own schema and there is an additional schema for the relationship set. For a multivalued attribute, a separate schema is created consisting of that attribute and the primary key of the entity set.

7. Which of the following has each related entity set has its own schema and there is an additional schema for the relationship set?

- a) A many-to-many relationship set
- b) A multivalued attribute of an entity set
- c) A one-to-many relationship set
- d) None of the mentioned

View Answer

Answer: a

Explanation: If a multivalued dependency holds and is not implied by the corresponding functional dependency, it usually arises from this source.

advertisement

8. In which of the following, a separate schema is created consisting of that attribute and the primary key of the entity set.

- a) A many-to-many relationship set
- b) A multivalued attribute of an entity set
- c) A one-to-many relationship set
- d) None of the mentioned

View Answer

Answer: b

Explanation: If a multivalued dependency holds and is not implied by the corresponding functional dependency, it usually arises from this source.

9. Fifth Normal form is concerned with

- a) Functional dependency
- b) Multivalued dependency
- c) Join dependency
- d) Domain-key

[View Answer](#)

Answer: c

Explanation: If a multivalued dependency holds and is not implied by the corresponding functional dependency, it usually arises from this source.

10. In 2NF

- a) No functional dependencies (FDs) exist
- b) No multivalued dependencies (MVDs) exist
- c) No partial FDs exist
- d) No partial MVDs exist

[View Answer](#)

Answer: c

Explanation: If a multivalued dependency holds and is not implied by the corresponding functional dependency, it usually arises from this source.

advertisement

