
Hybrid Reinforcement Learning and Genetic Algorithms for Meta-Learning Audio Denoising

A PREPRINT

Julian M. Kleber

ORCID: 0000-0001-5518-0932

Email: julian.m.kleber@gmail.com

18 July 2026

Paper version v4 (problem framing and related work; experiments ongoing)

Code: <https://github.com/reeldemo/reelsynth>, <https://github.com/reeldemo/denoise-opt-meta>

ABSTRACT

When a single-period wavetable (or any short cyclic buffer) is played with phase wrap, a sample discontinuity at the period boundary injects a broadband transient that repeats at the fundamental. We treat this cycle-local seam crackle as an audio denoising problem: seam-local operators (DualCosine crossfade, polish, FIR blends, optional tiny residual cells) are baked into the period, then judged by a prolonged residual $R \in [0, 1]$ against an ideal multi-period tiling that withholds the open-wrap cliff (1 = best). An outer hybrid meta-search interleaves GA tournament updates with PPO architecture proposals, optional PBT exploit–mutate schedules, and MoE soft gates over heterogeneous bake cells. Candidates need not be paired with studio-clean waveforms for every trial. This draft fixes the problem statement and a used-versus-screened literature map grounded on OA PDF analyses (Noise2Noise, PBT, Aging Evolution, ERL, ENAS/PPO, Wave-U-Net/Conv-TasNet, MoE, DDSP; Demucs/DiffWave/MAML/DARTS screened). A CUDA campaign (PPO+GA+PBT+NAS) is still running; quantitative tables wait until the declared budget finishes.

Keywords audio denoising · neural architecture search · reinforcement learning · genetic algorithms · wavetable synthesis · meta-learning

1 Introduction

Wavetable oscillators store one period of a waveform and advance a read pointer modulo the table length. If $x[0] \neq x[L-1]$, the wrap is a hard discontinuity: under cyclic playback it becomes a periodic click whose spectrum is broadband and locked to the fundamental. The same geometry appears whenever a short loop buffer is tiled for listening or for objective evaluation. We call the repair task *cycle-local seam restoration*: edit a neighborhood of the wrap (and optionally a lightweight residual cell over the period) so that multi-period playback matches an ideal reference that never opens the wrap cliff. That outer agreement is what we score as audio denoising for this periodic artifact class.

Classical virtual-analog practice already supplies seam-local tools. Cosine and dual-cosine crossfades, BLEP/BLAMP corrections for geometric discontinuities, and related oscillator design reduce wrap energy in-band [1–3]. Those operators act locally. They do not by themselves answer which bake parameters and which residual cell, if any, minimize prolonged tiled error against a no-cliff ideal. Label-free restoration work such as Noise2Noise shows that useful reconstructors can be ranked without paired clean targets when the evaluation geometry is explicit [4]. On the search side, NAS surveys [10], RL controllers with

parameter sharing [11], aging evolution [13], population-based hyperparameter schedules [14], and evolution-guided policy gradients [15] motivate a hybrid outer loop: GA for population diversity, PPO for discrete architecture edits [12], and PBT-style exploit–mutate on elites. MoE soft gates suggest routing among heterogeneous tiny cells under one residual score [16]. Waveform separation nets (Wave-U-Net, Conv-TasNet) and audio DL surveys inform the searchable cell family at bake-scale width [6, 7, 9], not as full production separators inside every trial.

The contribution is a meta-learning protocol for this periodic instance, not another end-to-end speech enhancer. An outer RL+GA(+PBT) loop proposes denoising operator graphs and continuous bake parameters. Each candidate is scored by a prolonged residual $R \in [0, 1]$ (1 = best) between engine-baked multi-period audio and a procedural ideal tiling. Paired studio-clean wavetables are not required for every trial. Differentiable DSP modules [5] place DualCosine / FIR / MLP seam ops in an interpretable stack; Bayesian and multi-objective HPO [17, 18] inform prior families that compete under the same R . This draft does not claim a finished leaderboard: a GPU overnight run (PPO+GA+PBT+NAS, depth and MoE biases) is still in progress. Early checkpoints already beat historical DualCosine residuals on the runner geometry;

held-out matrices and final budgets will be reported only after completion.

Contributions.

1. **Problem framing.** Cast wavetable wrap discontinuity / cycle-local seam restoration as audio denoising under prolonged tiled evaluation, separating seam-local diagnostics from residual R .
2. **Hybrid meta-outer loop.** Specify RL+GA(+PBT) search over discrete operator graphs and continuous bake parameters, with named branches (GA crossover, PPO mutation, PBT exploit, MoE soft gates).
3. **Literature protocol.** Separate used versus screened prior work for audio denoise cells and RL–evolutionary hybrids, grounded on attached OA PDFs where available.
4. **Open evaluation path.** Release companion code for the synthesizer engine and meta search; report interim protocol while large-scale experiments finish.

Section 2 organizes related work by mechanism. Sections 3–4 outline the residual objective and search protocol (placeholders pending final ingest). Results and discussion will be completed when the overnight campaign reaches its declared budget.

2 Related Work

We organize prior work by mechanism. **Used** lines are methodological or comparative anchors for residual-scored RL+GA meta-search. **Screened** lines were inspected as contrast but are not treated as dependencies. Paraphrases prefer attached abstracts and OA PDF snippets over title-only citation.

2.1 Discontinuity control and modular audio DSP

Virtual-analog oscillator and filter design supplies the classical vocabulary for wrap and discontinuity artifacts [1]. Aliasing reduction for clipped and discontinuous waveforms, and BLAMP-style corner rounding, motivate seam-local corrections that respect band-limited intent [2, 3]. DDSP re-frames such modules as composable blocks inside learning pipelines [5]; we use that framing for small bake/FIR/MLP seam cells rather than end-to-end neural vocoders. These works are **used** as domain anchors for the operator vocabulary and for why prolonged cyclic playback is the outer judge.

2.2 Label-free restoration

Noise2Noise shows that restoration mappings can be learned from corrupted observations alone by exploiting structure in the corruption process [4]. That philosophy motivates ranking denoise candidates without paired studio-clean wavetable cycles: the residual compares an engine-baked tiling to a procedural ideal that withholds open-wrap cliffs, not to a human-cleaned master. We **use** Noise2Noise as conceptual justification for unsupervised residual ranking; we do not retrain a Noise2Noise CNN on images.

2.3 Waveform denoising and separation cells

Deep learning for audio surveys the move from hand-designed features to learned time/frequency models [6]. Wave-U-Net performs end-to-end source separation with multi-scale 1-D U-Nets [7]; singing-voice U-Nets popularized encoder–decoder skips on audio [8]. Conv-TasNet demonstrated strong time-domain separation with temporal convolutions [9]. These lines are **used** as design priors for tiny searchable cells (shallow U-Net / dilated / dual-path / attention blocks under a strict per-trial bake budget). They are not frozen full-scale separators inside every meta trial.

2.4 NAS and RL controllers

Elsken et al. taxonomize NAS by search space, strategy, and evaluation cost [10]. ENAS couples an RL controller with parameter sharing for efficient discrete search [11]. We **use** this family as the ancestor of RL proposing architecture edits (add/remove/mutate ops, toggle residual-primary, mutate MLP/FIR), while scoring with prolonged residual rather than ImageNet reward. PPO supplies the clipped-surrogate policy update when the overnight loop logs PPO mutation branches [12].

2.5 Evolutionary NAS and population schedules

Regularized / aging evolution showed that evolutionary NAS can discover competitive image classifiers when population turnover is carefully regularized [13]. Population Based Training jointly adapts weights and hyperparameters in an asynchronous population [14]. Practical Bayesian optimization [17] and decomposition-based multi-objective evolution (MOEA/D) [18] inform local Bayesian and multi-objective prior families in earlier DenoiseOpt searches. These are **used** for GA tournament/crossover branches, PBT-style exploit–mutate, and literature-combo priors, implemented at synthesizer-trial scale rather than distributed datacenter PBT.

2.6 Evolutionary reinforcement learning hybrids

Khadka and Tumer’s evolution-guided policy gradient (ERL) interleaves an evolutionary population with an RL actor to mitigate sparse reward and brittle hyperparameters in deep RL [15]. We **use** ERL as the spirit of interleaving GA population steps with PPO updates at tiny population sizes; we do not claim a full ERL robotics stack.

2.7 Mixture-of-experts soft gating

Sparsely gated MoE layers increase capacity via conditional computation [16]. We **use** MoE as motivation for soft gates over heterogeneous seam blocks (e.g., U-Net vs dilated vs attention cells) under residual scoring, at bake-scale widths.

2.8 Used versus screened

Used (methodological or comparative anchors).

- Discontinuity / VA lineage: [1–3].
- Unsupervised restoration philosophy: [4].

- Modular / differentiable audio DSP context: [5].
- Audio DL and compact waveform cells: [6–9].
- NAS / RL controllers / PPO: [10–12].
- Evolutionary NAS and population HPO: [13, 14, 17, 18].
- ERL hybrid outer loop: [15].
- MoE soft gating prior: [16].

Screened (relevant contrast; not dependencies).

- **MAML** [19]: bi-level / fast-adaptation framing; we do not differentiate through a deep task network. Inner fits are coordinate-style updates on bake parameters; outer rank is residual R .
- **DARTS** [20]: continuous relaxation of architecture search; we keep discrete ops + small cells under residual scoring.
- **Demucs / Hybrid Demucs** [21, 22]: strong music separators, but full multi-scale / hybrid STFT stacks are too heavy per meta trial under overnight bake budgets.
- **DiffWave** [23]: diffusion vocoder; screened as a generative sampling stack, not a seam bake operator.
- **SEGAN-style adversarial enhancement** [24]: optional tiny adversarial cues only; full GAN training loops screened for per-trial cost.

Positioning. Relative to this map, the present work contributes (i) a prolonged residual objective for periodic seam denoising, (ii) an explicitly hybrid RL+GA(+PBT) meta-outer loop with honest branch naming, and (iii) a used/screened literature protocol tied to OA PDF analyses. We do not claim SOTA on general speech enhancement or music separation corpora. The primary claim is protocol-level: residual-scored meta-search for cycle-local audio denoise operators under a declared compute budget.

3 Methods

Placeholder: full methods will track the frozen overnight protocol after the declared iteration budget completes.

Residual score. Let y be the engine-baked cycle and r^* an ideal multi-period reference from the same seed with open-wrap cliffs withheld. With tiling length N (typically $N=16$),

$$R = \text{clamp}\left(1 - \frac{\text{rms}(y_{\text{tiled}} - r_{\text{tiled}}^*)}{\max(\text{rms}(r_{\text{tiled}}^*), \epsilon)}, 0, 1\right). \quad (1)$$

By construction $R \in [0, 1]$ with 1 best. Soft shape gates (when enabled) down-weight mid-cycle damage relative to seam-local error.

Searchable operator. Candidates combine classical seam ops (DualCosine, polish, soft seam, FIR blends) with tiny residual cells (MLP/FIR/U-Net-lite/attention-lite) and optional MoE soft gates. Bake parameters θ live in a bounded box; architecture strings are discrete graphs over those ops.

Hybrid outer loop. Each iteration may (i) run GA tournament selection with crossover/mutation, (ii) sample PPO actions that edit ops/hyperparameters, (iii) apply PBT-style exploit–mutate on elites, and (iv) evaluate literature-combo priors. Selection is always by residual R (and logged auxiliaries). Implementation details and exact action sets will be frozen to the overnight run configuration in the results revision.

4 Experiments

Placeholder: protocol sketch only; numbers below are interim and must not be read as final.

Ongoing overnight campaign. A CUDA search tagged PPO+GA+PBT+NAS (depth and MoE biases) is running with a large iteration budget (order 10^5 – 10^6). Early fitted champions already reach residual ≈ 0.99 on the training/validation geometry used by the runner, against DualCosine baselines near ≈ 0.82 – 0.84 on the same geometry (v3 reported DualCosine residual ≈ 0.698 at $N=2000$ on a prior held-out matrix). We will replace this paragraph with the completed budget, seeds, population size, and held-out matrix when the job finishes, without interrupting the live GPU process.

Prior completed study (v3 reference). A 1500-trial literature-informed CPU/GPU study selected `evo_explore_515` at residual ≈ 0.824 versus DualCosine ≈ 0.698 ($\Delta \approx +0.126$). That result anchors the residual-primary protocol; the overnight hybrid RL+GA run is the scale-up under test.

5 Results

Deferred for final claims. Final tables will be ingested after the overnight campaign reaches its declared iteration budget. Interim monitoring plots from the live GPU hybrid run are shown below for protocol transparency only; champion residuals and branch win-rates from incomplete runs are *not* asserted as finished science.

6 Discussion

Deferred until Results are complete. Anticipated themes: which hybrid branch (GA / PPO / PBT / lit-combo / MoE) wins under residual R ; whether deeper cells help when R holds; reconciliation with the v3 finding that light evolutionary explore beat nested loss-opt elites under a smaller budget.

7 Limitations

- Residual uses a procedural ideal (no-cliff sibling), not a perceptual MOS or listening panel.




Figure 1: Interim champion residual R versus search iteration, with DualCosine baseline. Monitoring snapshot; not a final result.




Figure 2: Interim per-branch best residual trajectories (PPO/RL, GA, PBT, NAS, combo). Monitoring only.

- Bake metrics are not a substitute for formal audio quality tests.
- Per-trial architecture width is capped for overnight throughput; full Demucs-/diffusion-scale stacks were screened out.
- Large-scale overnight results in this draft are interim; final claims require completed budgets and frozen seeds.
- Classical VA/BLEP citations are domain anchors from prior versions; not all have OA PDFs in the current harvest folder.

8 Conclusion

We framed wavetable wrap discontinuity as an audio denoising instance and outlined a hybrid RL+GA meta-learning outer loop scored by prolonged residual R . Related work separates used anchors (Noise2Noise, PBT, Aging Evolution, ERL, ENAS/PPO, Wave-U-Net/Conv-TasNet, MoE, VA/BLEP, DDSP) from screened contrasts (MAML, DARTS, Demucs, DiffWave, full GAN loops). Companion code lives at <https://github.com/reeldemo/reelsynth>

and <https://github.com/reeldemo/denoise-opt-meta>. Final quantitative claims await completion of the ongoing GPU campaign.




Figure 3: Full-width interim overnight monitoring panel: champion R (top) and branch-best trajectories (bottom). Snapshot while the GPU budget completes.




Figure 4: Interim per-trial residual scatter by search branch, with champion overlay. Monitoring snapshot.




Figure 5: Interim champion update timeline. Sparse R labels mark first, peak-mid, and latest improvements to stay legible in twocolumn.

References

- [1] V. Välimäki and A. Huovilainen. Oscillator and filter algorithms for virtual analog synthesis. *Computer Music Journal*, 30(2), 2006.
- [2] F. Esqueda, S. Bilbao, and V. Välimäki. Aliasing reduction in clipped signals. *IEEE Transactions on Signal Processing*, 2016.
- [3] F. Esqueda, V. Välimäki, and S. Bilbao. Rounding corners with BLAMP. In *Proc. DAFx*, 2016.
- [4] J. Lehtinen et al. Noise2Noise: Learning image restoration without clean data. In *ICML*, 2018. arXiv:1803.04189.
- [5] J. Engel, L. Hantrakul, C. Gu, and A. Roberts. DDSP: Differentiable digital signal processing. In *ICLR*, 2020. arXiv:2001.04643.
- [6] H. Purwins et al. Deep learning for audio signal processing. *IEEE J. Sel. Topics Signal Process.*, 2019. arXiv:1905.00078.
- [7] D. Stoller, S. Ewert, and S. Dixon. Wave-U-Net: A multi-scale neural network for end-to-end audio source separation. In *ISMIR*, 2018. arXiv:1806.03185.
- [8] A. Jansson et al. Singing voice separation with deep U-Net convolutional networks. In *ISMIR*, 2017.
- [9] Y. Luo and N. Mesgarani. Conv-TasNet: Surpassing ideal time-frequency magnitude masking for speech separation. *IEEE/ACM TASLP*, 2019.
- [10] T. Elsken, J. H. Metzen, and F. Hutter. Neural architecture search: A survey. *JMLR*, 2019. arXiv:1808.05377.
- [11] H. Pham et al. Efficient neural architecture search via parameter sharing. In *ICML*, 2018. arXiv:1802.03268.
- [12] J. Schulman et al. Proximal policy optimization algorithms. arXiv:1707.06347, 2017.
- [13] E. Real, A. Aggarwal, Y. Huang, and Q. V. Le. Regularized evolution for image classifier architecture search. In *AAAI*, 2019. arXiv:1802.01548.
- [14] M. Jaderberg et al. Population based training of neural networks. arXiv:1711.09846, 2017.
- [15] S. Khadka and K. Tumer. Evolution-guided policy gradient in reinforcement learning. In *NeurIPS*, 2018. arXiv:1805.07917.
- [16] N. Shazeer et al. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *ICLR*, 2017. arXiv:1701.06538.
- [17] J. Snoek, H. Larochelle, and R. P. Adams. Practical Bayesian optimization of machine learning algorithms. In *NeurIPS*, 2012. arXiv:1206.2944.
- [18] Q. Zhang and H. Li. MOEA/D: A multiobjective evolutionary algorithm based on decomposition. *IEEE Trans. Evolutionary Computation*, 2007.
- [19] C. Finn, P. Abbeel, and S. Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *ICML*, 2017. arXiv:1703.03400. (*Screened.*)
- [20] H. Liu, K. Simonyan, and Y. Yang. DARTS: Differentiable architecture search. In *ICLR*, 2019. arXiv:1806.09055. (*Screened.*)
- [21] A. Défossez et al. Demucs: Deep extractor for music sources. arXiv:1911.13254, 2019. (*Screened.*)
- [22] A. Défossez. Hybrid spectrogram and waveform source separation. arXiv:2111.03600, 2021. (*Screened.*)
- [23] Z. Kong et al. DiffWave: A versatile diffusion model for audio synthesis. In *ICLR*, 2021. arXiv:2009.00713. (*Screened.*)
- [24] S. Pascual, A. Bonafonte, and J. Serrà. SEGAN: Speech enhancement generative adversarial network. In *INTERSPEECH*, 2017. (*Screened.*)