```
smacc::ISmaccClient
 # components

    stateMachine

    orthogonal

 + ISmaccClient()
    ~ISmaccClient()
 + initialize()
 + getName()
 + postEvent()
 + postEvent()
 + getComponent()
 + getComponent()
 + getType()
 + getStateMachine()
 + connectSignal()
 + requiresClient()
 + getComponents()
 # onOrthogonalAllocation()
 # createComponent()
 # createNamedComponent()
 # setStateMachine()
 # setOrthogonal()
                        Ų
                     smacc::client_bases
                     ::SmaccSubscriberClient
                          < MessageType >
                     + topicName
                     + queueSize
                     + onFirstMessageReceived_
                     + onMessageReceived_
                     + postMessageEvent
                     + postInitialMessageEvent
# nh_
                     - sub

    firstMessage

                     initialized_
                     + SmaccSubscriberClient()
                     + SmaccSubscriberClient()
                     + ~SmaccSubscriberClient()
                     + onMessageReceived()
                     + onFirstMessageReceived()
                     + onOrthogonalAllocation()
                     + initialize()
                     - messageCallback()
                          < std_msgs::Int32 >
  smacc::client_bases
  ::SmaccSubscriberClient
      < std_msgs::Int32 >
  + topicName
  + queueSize
  + onFirstMessageReceived_
  + onMessageReceived
  + postMessageEvent
  + postInitialMessageEvent
  # nh
  - sub

    firstMessage_

  - initialized_
    SmaccSubscriberClient()
  + SmaccSubscriberClient()
  + ~SmaccSubscriberClient()
  + onMessageReceived()
  + onFirstMessageReceived()
  + onOrthogonalAllocation()
  + initialize()
  messageCallback()
sm_ridgeback_barrel
_search_1::cl_opencv
_perception::ClOpenCVPerception
+ ClOpenCVPerception()
+ ~ClOpenCVPerception()
+ onOrthogonalAllocation()
```