```
# components
- stateMachine_
orthogonal
+ ISmaccClient()
+ ~ISmaccClient()
+ initialize()
+ getName()
+ postEvent()
+ postEvent()
+ getComponent()
+ getComponent()
+ getType()
+ getStateMachine()
+ connectSignal()
+ requiresClient()
+ getComponents()
# onOrthogonalAllocation()
# createComponent()
# createNamedComponent()
# setStateMachine()
# setOrthogonal()
                       A
                    smacc::client bases
                    ::SmaccSubscriberClient
                          < MessageType >
                    + topicName
                    + queueSize
                    + onFirstMessageReceived
                    + onMessageReceived
                    + postMessageEvent
+ postInitialMessageEvent
                    # nh_
                    - sub

    firstMessage_

                    - initialized
                    + SmaccSubscriberClient()
+ SmaccSubscriberClient()
                    + ~SmaccSubscriberClient()
                    + onMessageReceived()
                    + onFirstMessageReceived()
                    + onOrthogonal Allocation()
                    + initialize()
                    messageCallback()
                          < std msgs::Float32 >
smacc::client_bases
::SmaccSubscriberClient
    < std msgs::Float32 >
 + topicName
 + queueSize
 + onFirstMessageReceived_
 + onMessageReceived_
 + postMessageEvent
 + postInitialMessageEvent
# nh
 - sub
- firstMessage_

    initialized_

+ SmaccSubscriberClient()
 + SmaccSubscriberClient()
+ ~SmaccSubscriberClient()
 + onMessageReceived()
 + onFirstMessageReceived()
 + onOrthogonalAllocation()
 + initialize()
 - messageCallback()
```

subscriber

sm_ferrari::cl

+ CISubscriber()

::ClSubscriber

smacc::ISmaccClient