
std::enable_shared _from_this< SmaccStateInfo >
map< const std::type _info *, std::vector < std::shared_ptr< smacc ::introspection::SmaccEventGenerator Info > > >
shared_ptr< smacc:: introspection::SmaccStateMachine Info >
map< const std::type _info *, std::vector < smacc::introspection ::ClientBehaviorInfoEntry > >
vector< smacc::introspection ::SmaccTransitionInfo >
map< const std::type _info *, std::vector < std::shared_ptr< smacc ::introspection::SmaccStateReactor Info > > >
int
vector< std::shared _ptr< smacc::introspection ::SmaccStateInfo > >
string
shared_ptr< smacc:: introspection::SmaccStateInfo >
type_info *
+eventGeneratorsInfo
+stateMachine_
+staticBehaviorInfo
+transitions_
+stateReactorsInfo
+stateIndex_ +depth_
+children_
+fullStateName +demangledStateName
+parentState_
+tid_
smacc::introspection ::SmaccStateInfo
+ SmaccStateInfo()
+ getStateLevel()
+ depth()
+ getAncestors()
+ getFullPath()
+ createChildState()
+ declareTransition()
+ toShortName()
+ getDemangledFullName()
vector< std::shared _ptr< smacc::StateReactor > >
NodeHandle
vector< std::shared _ptr< smacc::SmaccEventGenerator > >
#stateReactors_
#contextNh #nh
#eventGenerators_
#stateInfo_
smacc::ISmaccState
+ getStateMachine()
+ getParentState()
+ getROSNode()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ createEventGenerator()
+ postEvent()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition TypeInfo()
+ getStateReactors()
+ getEventGenerators()
+ getParam()
+ setParam()
+ param()
+ getOrthogonal()
+ getEventGenerator()
+ getStateReactor()
#parentState_
bool
boost::statechart:: simple_state< MostDerived, Context, InnerInitial, historyMode >
InnerInitial
+finishStateThrown
+smacc_inner_type
smacc::SmaccState< MostDerived, Context, InnerInitial, historyMode >
+ SmaccState()
+ SmaccState()
+ ~SmaccState()
+ getStateInfo()
+ getFullName()
+ getShortName()
+ getParentState()
+ exit()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ getGlobalSMData()
+ setGlobalSMData()
+ requiresComponent()
+ getStateMachine()
+ checkWhileLoopConditionAnd ThrowEvent()
+ throwSequenceFinishedEvent()
+ configure_orthogonal _runtime()
+ configure_orthogonal _runtime()
+ configure_orthogonal()
+ static_createStateReactor()
+ static_createEventGenerator()
+ static_createStateReactor_aux()
+ initial_deep_construct()
+ deep_construct()
+ shallow_construct()
- entryStateInternal()
- configure_orthogonal _internal()
boost::statechart:: simple_state< State2, SmUpdateLoop, mpl::list <>, sc::has_deep_history >
+finishStateThrown
list<> *
< State2, SmUpdateLoop >
+smacc_inner_type
smacc::SmaccState< State2, SmUpdateLoop >
+ SmaccState()
+ SmaccState()
+ ~SmaccState()
+ getStateInfo()
+ getFullName()
+ getShortName()
+ getParentState()
+ exit()
+ runtimeConfigure()
+ onEntry()
+ onExit()
+ getGlobalSMData()
+ setGlobalSMData()
+ requiresComponent()
+ getStateMachine()
+ checkWhileLoopConditionAnd ThrowEvent()
+ throwSequenceFinishedEvent()
+ configure_orthogonal _runtime()
+ configure_orthogonal _runtime()
+ configure_orthogonal()
+ static_createStateReactor()
+ static_createEventGenerator()
+ static_createStateReactor_aux()
+ initial_deep_construct()
+ deep_construct()
+ shallow_construct()
- entryStateInternal()
- configure_orthogonal _internal()
ISmaccUpdatable
sm_update_loop::State2
+ runtimeConfigure()
+ update()
+ onEntry()
+ onExit()
+ staticConfigure()