
vector< std::shared_ptr< smacc::StateReactor > >
shared_ptr< smacc::introspection::smacc::introspection::SmaccStateInfo >
NodeHandle
#stateReactors_
#stateInfo_
#nh
smacc::ISmaccState
+ getStateMachine()
+ getParentState()
+ getClassName()
+ configure()
+ requiresComponent()
+ requiresClient()
+ getGlobalSMData()
+ setGlobalSMData()
+ createStateReactor()
+ createStateReactor()
+ postEvent()
+ notifyTransition()
+ notifyTransitionFromTransition$typeinfo()
+ getStateReactors()
+ getParam()
+ setParam()
+ param()
+ getOrthogonal()
+ getROSNode()
#parentState_
boost::signals2::signal< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
Timer
SmaccStatus
recursive_mutex
map< std::string, std::pair< std::function< void:string()>, boost::any > >
list< boost::signals2::connection >
SMRunMode
map< std::string, std::shared_ptr< smacc::smacc::IOrthogonal > >
shared_ptr< smacc::introspection::SmaccStateInfo >
vector< smacc_msgs::SmaccTransitionLogEntry >
ServiceServer
shared_ptr< smacc::introspection::SmaccStateMachineInfo >
#private_nh_
#nh_
unsigned long
Publisher
#currentState_
#timer_
#status_msg_
-m_mutex_
-globalData_
+stateCallbackConnections
-runMode_
#orthogonals_
#currentStateInfo_
-transitionLogHistory_
#transitionHistoryService_
+info_
-stateSeqCounter_
#transitionLogPub
#stateMachineStatusPub
#stateMachinePub_
-nh_
smacc::ISmaccStateMachine
+ ISmaccStateMachine()
+ ~ISmaccStateMachine()
+ Reset()
+ Stop()
+ EStop()
+ getOrthogonal()
+ getOrthogonals()
+ requiresComponent()
+ postEvent()
+ postEvent()
+ getTransitionLogHistory()
+ getGlobalSMData()
+ setGlobalSMData()
+ mapBehavior()
+ updateStatusMessage()
+ getStateMachineName()
+ state_machine_visualization()
+ getCurrentStateInfo()
+ publishTransition()
+ onInitialize()
+ getTransitionLogHistory()
+ createSignalConnection()
+ createSignalConnection()
+ lockStateMachine()
+ unlockStateMachine()
+ notifyOnStateEntryStart()
+ notifyOnStateEntryEnd()
+ notifyOnStateExit()
+ getCurrentStateCounter()
+ getCurrentState()
# onInitializing()
# onInitialized()
# createOrthogonal()
# getParam()
# setParam()
# param()
- propagateEventToStateReactors()
smacc::SmaccSignal< Signature, Combiner, Group, GroupCompare, SlotFunction, ExtendedSlotFunction, Mutex >
boost::signals2::signal< void(), optional_last_value< typename boost::function_traits< void() >::result_type >, int, std::less< int >, function< void () >, typename extended_signature< function_traits< void() >::arity, void() >::function_type, boost::signals2::mutex >
vector< std::shared_ptr< smacc::smacc::SmaccClientBehavior > >
vector< std::shared_ptr< smacc::smacc::ISmaccClient > >
map< const std::type_info *, std::shared_ptr< smacc::smacc::ISmaccComponent > >
-statusPub_
processor_handle
SmaccFifoScheduler *
double
vector< smacc::ISmaccUpdatable * >
thread
atomic< bool >
atomic< unsigned long >
< void()>
#clientBehaviors_
#clients_
#stateMachine_
+currentState
#timer
#stateMachine_
#components_
-smaccStateMachine_
-signalDetector_
-processorHandle_
-scheduler_
-loop_rate_hz
-updatableClientBehaviors
-updatableClients_
-signalDetectorThread_
-end_
-lastState_
smacc::IOrthogonal
+ setStateMachine()
+ addClientBehavior()
+ onEntry()
+ onExit()
+ getName()
+ requiresComponent()
+ requiresClient()
+ getClients()
+ getClientBehaviors()
+ getClientBehavior()
# onInitialize()
smacc::ISmaccClient
+ ISmaccClient()
+ ~ISmaccClient()
+ initialize()
+ setStateMachine()
+ getName()
+ postEvent()
+ postEvent()
+ getComponent()
+ configureEventSourceTypes()
+ getType()
smacc::ISignalDetector
+ SignalDetector()
+ initialize()
+ setProcessorHandle()
+ runThread()
+ join()
+ stop()
+ pollingLoop()
+ pollOnce()
+ postEvent()
- findUpdatableClients()
- findUpdatableBehaviors()
smacc::SmaccSignal< void()>
+stateMachine_
function< void()>
Duration
bool
+currentOrthogonal
#onTimerTick_
#postTimerEvent_
#duration
#oneshot
smacc::SmaccClientBehavior
+ SmaccClientBehavior()
+ ~SmaccClientBehavior()
+ getName()
+ onEntry()
+ onExit()
+ postEvent()
+ postEvent()
+ requiresClient()
+ requiresComponent()
- configureEventSourceTypes()
ros_timer_client::CRosTimer
+ onTimerTick()
+ onTimerTick()
+ CRosTimer()
+ ~CRosTimer()
+ initialize()
+ configureEventSourceTypes()
# timerCallback()
scoped_connection
-postTimerEvent_
-timerClient_
<_
ros_timer_client::CbTimer
+ onEntry()
+ onExit()
+ configureEventSourceTypes()