```
smacc::ISmaccClient
   # components

    stateMachine

   + ISmaccClient()
   + ~ISmaccClient()
   + initialize()
   + setStateMachine()
   + getName()
   + postEvent()
   + postEvent()
   + getComponent()
   + configureEventSourceTypes()
   + getType()
   + getStateMachine()
   # createComponent()
                   smacc::client bases
                   ::SmaccSubscriberClient
                         < MessageType >
                   + topicName
                   + queueSize
                   + onFirstMessageReceived_
                   + onMessageReceived_
                   + postMessageEvent
                   + postInitialMessageEvent
                   # nh
                   - sub

    firstMessage_

                   - initialized
                   + SmaccSubscriberClient()
                   + SmaccSubscriberClient()
                   + ~SmaccSubscriberClient()
                   + onMessageReceived()
                   + onFirstMessageReceived()
                   + configureEventSourceTypes()
                   + initialize()
                   messageCallback()
                         < std msgs::UInt16 >
smacc::client_bases
::SmaccSubscriberClient
    < std msgs::UInt16 >
+ topicName
+ queueSize
+ onFirstMessageReceived_
+ onMessageReceived_
+ postMessageEvent
+ postInitialMessageEvent
# nh
- sub
- firstMessage_
- initialized
+ SmaccSubscriberClient()
+ SmaccSubscriberClient()
+ ~SmaccSubscriberClient()
+ onMessageReceived()
```

sm\_packML::cl\_subscriber ::ClSubscriber

Δ

+ onFirstMessageReceived() + configureEventSourceTypes()

+ initialize()

messageCallback()