

Table of Contents

Create a local repository	1
---------------------------------	---

Create a local repository

When working with Git, people often mention Git repository, short form as repo. Earlier we installed Git, that doesn't mean we can use it. We need to manually tell machine when to use Git and in which directory. We need to create a Git repository in the directory where we need to use Git. So, Git starts saving history in the directory after Git repo is setup.

Follow the table for all git commands. Note Git commands to be executed in **Git bash terminal**.

<u>Command description</u>	<u>Commands</u>
Navigate to the directory where you want to use Git	\$ mkdir test , \$cd test
git status gives information on the current status of a git repository and its contents It's very useful, but at the moment we don't actually have any repos to check the status of!	\$ git status Output: fatal: not a git repository (or any of the parent directories)
Use git init to create a new git repository. Before we can do anything git-related, we must initialize a repo first!. This is something you do once per project. Initialize the repo in the top-level folder containing your project. Git tracks the directory and <u>all nested directories</u> .	\$ git init
More information on Git init command can be found at www.git-scm.com/docs/git-init . As the documentation says “.git” folder is created when repo is initialized. Use \$ls -al command inside the initialized folder to see “.git” hidden file. Do not modify the content inside the folder. This folder saves the history. If this folder is deleted, entry history of the project will also be deleted.	
<u>Warning: DO NOT INIT A REPO INSIDE OF A REPO!. Before running git init, use git status to verify that you are not currently inside of a repo.</u> If you do end up making a repo inside of a repo, you can delete it and try again! To delete a repo, locate the associated “.git” (dot is used to tell its hidden folder) directory and delete it.	
Git is Watching Us after init command. Try making a new file in your repo, and then run git status again. You'll see that git noticed the file, but it is "untracked". To check this Go to the folder where "test" is created and create a text document named "demo." Open "demo" and put any content, like "Hello Simplilearn." Save and close the file. Check the status	
www.git-scm.com/docs/git-status	\$ git status