LAB EXPERIMENTS

SELECT with various clauses – BETWEEN, IN, Aggregate Function

```
mysql>
mysql> -- Using BETWEEN
mysql> SELECT * FROM Students
    -> WHERE Marks BETWEEN 70 AND 90;
+-----------+-------+------------+------+-------+---------+
| StudentID | Name  | Department | Age  | Marks | City    |
+-----------+-------+------------+------+-------+---------+
|         1 | Arun  | CSE        |   20 |    85 | Chennai |
|         4 | Divya | ECE        |   20 |    78 | Madurai |
+-----------+-------+------------+------+-------+---------+
2 rows in set (0.01 sec)

mysql>
mysql> -- Using IN
mysql> SELECT * FROM Students
    -> WHERE Department IN ('CSE', 'IT');
+-----------+-------+------------+------+-------+------------+
| StudentID | Name  | Department | Age  | Marks | City       |
+-----------+-------+------------+------+-------+------------+
|         1 | Arun  | CSE        |   20 |    85 | Chennai    |
|         2 | Priya | IT         |   19 |    92 | Coimbatore |
|         3 | Kumar | CSE        |   21 |    68 | Chennai    |
|         5 | Rahul | IT         |   22 |    55 | Salem      |
|         6 | Meena | CSE        |   19 |    95 | Coimbatore |
+-----------+-------+------------+------+-------+------------+
5 rows in set (0.00 sec)

mysql>
mysql> -- Aggregate functions
mysql> SELECT
    ->     COUNT(*) AS TotalStudents,
    ->     MAX(Marks) AS HighestMarks,
    ->     MIN(Marks) AS LowestMarks,
    ->     AVG(Marks) AS AverageMarks,
    ->     SUM(Marks) AS TotalMarks
    -> FROM Students;
+---------------+--------------+-------------+--------------+------------+
| TotalStudents | HighestMarks | LowestMarks | AverageMarks | TotalMarks |
+---------------+--------------+-------------+--------------+------------+
|             6 |           95 |          55 |      78.8333 |        473 |
+---------------+--------------+-------------+--------------+------------+
1 row in set (0.01 sec)

mysql>
```