4 . DML Commands using UPDATE, DELETE

```
mysql> update learners set l_name = "meenakshi" where l_id = 2 ;
Query OK, 1 row affected (0.47 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql> update learners set l_age = l_age + 1 where dept_id = 202 ;
Query OK, 2 rows affected (0.38 sec)
Rows matched: 2  Changed: 2  Warnings: 0

mysql> select * from learners ;
+------+-----------+-------+------------+------------------+---------+
| l_id | l_name    | l_age | l_city     | email            | dept_id |
+------+-----------+-------+------------+------------------+---------+
|    1 | arun      |    19 | chennai    | arun07@gmail.com |     201 |
|    2 | meenakshi |    21 | chennai    | meena@gmail.com  |     202 |
|    3 | dinesh    |    22 | madurai    | dinesh@gmail.com |     203 |
|    4 | swathi    |    19 | coimbatore | swathi@gmail.com |     202 |
|    5 | harish    |    21 | salem      | harish@gmail.com |     201 |
+------+-----------+-------+------------+------------------+---------+
5 rows in set (0.00 sec)

mysql> delete l_city from learners ;
ERROR 1109 (42S02): Unknown table 'l_city' in MULTI DELETE
mysql> delete from learners where l_id = 5 ;
Query OK, 1 row affected (1.62 sec)
```

```
mysql> delete l_city from learners ;
ERROR 1109 (42S02): Unknown table 'l_city' in MULTI DELETE
mysql> delete from learners where l_id = 5 ;
Query OK, 1 row affected (1.62 sec)

mysql> delete from learners where l_age < 20 ;
Query OK, 2 rows affected (0.52 sec)

mysql> select * from learners ;
+------+-----------+-------+---------+------------------+---------+
| l_id | l_name    | l_age | l_city  | email            | dept_id |
+------+-----------+-------+---------+------------------+---------+
|    2 | meenakshi |    21 | chennai | meena@gmail.com  |     202 |
|    3 | dinesh    |    22 | madurai | dinesh@gmail.com |     203 |
+------+-----------+-------+---------+------------------+---------+
2 rows in set (0.00 sec)
```