#### Electrostatics Basics

Line Charge:	₽(¬) _	1	1	$\frac{\lambda(\vec{r'})}{  \vec{r_{\rm sep}}  ^2} \hat{r}_{\rm sep}  dl'$
Line Charge.	E(T) =	$4\pi\epsilon_0$ .	J	$\frac{1}{  r_{\text{sep}}  ^2} r_{\text{sep}} u t$

Surface Charge: 
$$\vec{E}(\vec{r}) = \frac{1}{4\pi\epsilon_0} \int \frac{|r_{\text{sep}}||^2}{|r_{\text{sep}}||^2} \hat{r}_{\text{sep}} da'$$

Volume Charge: 
$$\vec{E}(\vec{r}) = \frac{1}{4\pi\epsilon_0} \int \frac{\rho(r')}{||r_{\text{sep}}^{\prime}||^2} \hat{r}_{\text{sep}} d\tau'$$

Potential Difference: 
$$V(\vec{b}) - V(\vec{a}) = -\int_{\vec{a}}^{\vec{b}} \vec{E} \cdot d\vec{l}$$

Potential of a Volume 
$$V(\vec{r}) = \frac{1}{4\pi\epsilon_0} \int \frac{\rho(\vec{r'})}{||r_{\vec{sep}}||} d\tau'$$

Charge: 
$$V(\vec{r}) = \frac{1}{4\pi\epsilon_0} \int ||\vec{r}_{\text{sep}}||^4 V(\vec{r}) d\vec{r}$$
Potential of a Collection of Point Charges:  $V(\vec{r}) = \frac{1}{4\pi\epsilon_0} \sum_{i=0}^{n} \frac{q_i}{||\vec{r}_{\text{sep}}||^4}$ 

Point Charges: 
$$v(\vec{r}) = \frac{1}{4\pi\epsilon_0} \sum_{i=0}^{2} \frac{1}{||\vec{r_{\rm sep}}||}$$
 Work to Move a Charge: 
$$W = \int_{a}^{b} \vec{F} \cdot d\vec{l} = -Q \int_{a}^{b} \vec{E} \cdot d\vec{l}$$

Work to Move a Charge (Potential): 
$$W = Q[V(\vec{b}) - V(\vec{a})]$$

Energy of a Collection of Point Charges: 
$$W = \frac{1}{2} \sum_{i=1}^{n} q_i V(\vec{r_i})$$

Energy of a Continuous Charge Distribution: 
$$W=\frac{\epsilon_0}{2}~\int_{\cdot}~E^2d\tau=\frac{1}{2}~\iiint \rho V d\tau$$

Field at a Charged 
$$\vec{E}_{\rm surf} = \frac{1}{2} \left( \vec{E}_{\rm above} + \vec{E}_{\rm below} \right)$$
 Surface:

Parallel Plate Voltage: 
$$V = \frac{Q}{Ac}d$$

Parallel Plate Voltage: 
$$V = \frac{\sqrt{\epsilon_0}}{A\epsilon_0} d$$
  
Capacitance:  $C \equiv \frac{Q}{\epsilon_0}$ 

Energy of a Capacitor: 
$$W = \int_0^Q \left(\frac{q}{C}\right) dq = \frac{1}{2} \frac{Q^2}{C} = \frac{1}{2} C V^2$$

# Electrostatic Multipoles

Generalized Multipole 
$$V(r) = \frac{1}{4\pi\epsilon_0} \sum_{n=0}^{\infty} \frac{1}{r^{n+1}} \int_V ||\vec{r'}||^n P_n(\cos\alpha) \rho(\vec{r'}) d\tau'$$
 Expansion:

Monopole Voltage: 
$$V(r) = \frac{1}{4\pi\epsilon_0} \frac{Q}{r}$$
 Dipole Voltage: 
$$V(r) = \frac{1}{r} \frac{Q}{r}$$

$$\begin{split} \text{Monopole Voltage:} & V(r) = \frac{1}{4\pi\epsilon_0} \frac{Q}{r} \\ \text{Dipole Voltage:} & V(r) = \frac{1}{4\pi\epsilon_0} \frac{p}{r^2} \cdot \hat{r} \\ \text{Dipole Moment (Continuous):} & \vec{p} \equiv \int_V \vec{r'} \rho(\vec{r'}) d\tau' \end{split}$$

Dipole Moment (Discrete): 
$$\vec{p} = \sum_{i=1}^{n} q_i \vec{r'}_i$$

Dipole Moment (Change of Origin): 
$$\vec{p'} = \vec{p} - Q\vec{a}$$

Origin): 
$$\vec{N} = \vec{p} \times \vec{E}$$

Torque of a Dipole:  $\vec{N} = \vec{p} \times \vec{E}$ 

Energy of a Dipole:  $\vec{U} = -\vec{\pi} \cdot \vec{E}$ 

Energy of a Dipole: 
$$U = -\vec{p} \cdot \vec{E}$$
 Force on a Dipole: 
$$\vec{F} = (\vec{p} \cdot \nabla) \vec{B}$$

Force on a Dipole: 
$$F = (\vec{p} \cdot \nabla)E$$
  
Field of a Dipole:  $\vec{E} = \frac{1}{\vec{p}} \left(2\cos\theta\hat{r} + \frac{1}{\vec{p}}\right)$ 

# $\vec{F} = (\vec{p} \cdot \nabla) \vec{E}$ $\vec{E} = \frac{1}{4\pi\epsilon_0} \frac{p}{r^2} \left( 2\cos\theta \hat{r} + \sin\theta \hat{\theta} \right)$ Field of a Dipole:

# Electrostatics in Matter

Electric Displacement: 
$$\vec{D} \equiv \epsilon_0 \vec{E} + \vec{P}$$

Bound Surface Charge: 
$$\sigma_{\rm bound} = \vec{P} \cdot \hat{n}$$

Bound Volume Charge: 
$$\rho_{\text{bound}} \equiv -\nabla \cdot \vec{P}$$

Linear Dielectrics – Polarization: 
$$\vec{P} = \epsilon_0 \chi_e \vec{E}$$

Linear Dielectrics – 
$$\vec{D} = \epsilon \vec{E}$$

Electric Permittivity: 
$$\epsilon = \epsilon_0 (1 + \chi_e) = \epsilon_0 \epsilon_r$$

Gauss's Law for 
$$\vec{D}$$
  $\nabla \cdot \vec{D} = \rho_f$ 

(Derivative): 
$$\nabla \cdot D = \rho$$

Gauss's Law for 
$$\vec{D}$$
 
$$\oint \vec{D} \cdot d\vec{A} = Q_{f_{\text{encl}}}$$

Force on a Dielectric: 
$$F = -\nabla U$$

#### $W = \frac{1}{2} \int \vec{D} \cdot \vec{E} d\tau$ Energy of a Dielectric:

#### Names of Stuff

- $\epsilon_0$ : Permittivity of Free Space
- $\epsilon_r$ : Dielectric Constant or Relative Permittivity
- $\epsilon$ : Permittivity of a Material

PHYS 301 Formula Sheet. Critchlow/Wilson/Predinchuk 2022.

## Techniques for Solving Problems

Cylindrical Laplacian Solution:

$$V(s,\phi) = A \ln s + B + \sum_{n=1}^{\infty} \left( A_n s^n + \frac{B_n}{s^n} \right) \left( C_n \cos(\phi n) + D_n \sin(\phi n) \right)$$

Solution for Spherical 
$$V(r,\theta) = \sum_{l=0}^{\infty} \left( A_l r^l + \frac{B_l}{r^{l+1}} \right) P_l(\cos \theta)$$
 Laplacians:

Method of Images General 
$$\sum \frac{q_i}{||\vec{r_{sep,i}}||} = 0$$
 Principle:

Method of Images for Two Points: 
$$-\frac{q_1}{q_2} = \frac{||\vec{r_{\rm sep_1}}||}{||\vec{r_{\rm sep_2}}||}$$

Image Charge Surface 
$$\sigma = -\epsilon_0 \frac{\partial V}{\partial n}$$
 Charge:

Taylor Expansion: 
$$f(x) \approx \sum_{n=0}^{\infty} \frac{f^{(n)}(0)}{n!}$$

Because I can't remember: 
$$f(x) \approx f(0) + f'(0) \cdot x + f''(0) \cdot \frac{x^2}{2} + \cdots$$

Legendre Polynomials: 
$$P_0(\cos\theta) = 1$$

$$P_1(\cos\theta) = \cos\theta$$

$$P_2(\cos\theta) = \frac{3}{2}\cos^2\theta - \frac{1}{2}$$

$$P_3(\cos\theta) = \frac{5}{2}\cos^3\theta - \frac{3}{2}\cos\theta$$

### Magnetostatics

Lorentz Force Law: 
$$\vec{F}_{\text{mag}} = Q(\vec{v} \times \vec{B})$$

Surface Current Density: 
$$\vec{K} \equiv \frac{d\vec{I}}{dl_\perp}$$
 
$$\vec{K} = \sigma \vec{v}_\perp$$

Volume Current Density: 
$$J \equiv \frac{dI}{da_{\perp}}$$
 
$$\vec{J} = \rho \vec{v}$$

Magnetic Force (General): 
$$\vec{F}_{\rm mag} = \int I(d\vec{l}\times\vec{B}) = I\int (d\vec{l}\times\vec{B})$$

Magnetic Force (Surface): 
$$\vec{F}_{\text{mag}} = \int (\vec{K} \times \vec{B}) da$$

Magnetic Force (Volume): 
$$\vec{F}_{\text{mag}} = \int (\vec{J} \times \vec{B}) d\tau$$

Biot-Savart Law: 
$$\vec{B}(\vec{r}) = \frac{\mu_0}{4\pi} \int \frac{I \times r_{\rm sep}}{||r_{\rm sep}||^2} dl'$$

Biot-Savart Law: 
$$\vec{B}(\vec{r}) = \frac{\mu_0}{4\pi} \int \frac{\vec{I} \times \hat{r}_{\text{sep}}}{||r_{\vec{\text{sep}}}||^2} dl'$$

$$\vec{B}(\vec{r}) = \frac{\mu_0}{4\pi} I \int \frac{d\vec{l}' \times \hat{r}_{\text{sep}}}{||r_{\vec{\text{sep}}}||^2} dl'$$
Biot-Savart – Surface: 
$$\vec{B}(\vec{r}) = \frac{\mu_0}{4\pi} \int \frac{\vec{K}(\vec{r}') \times \hat{r}_{\text{sep}}}{||r_{\vec{\text{sep}}}||^2} da'$$
Biot-Savart – Volume: 
$$\vec{B}(\vec{r}) = \frac{\mu_0}{4\pi} \int \frac{\vec{J}(\vec{r}') \times \hat{r}_{\text{sep}}}{||r_{\vec{\text{sep}}}||^2} d\tau'$$

Biot-Savart – Volume: 
$$\vec{B}(\vec{r}) = \frac{\mu_0}{r} \int \frac{\vec{J}(\vec{r}') \times \hat{r}_{\text{sep}}}{\vec{J}(\vec{r}') \times \hat{r}_{\text{sep}}} d\tau'$$

Ampere's Law: 
$$\vec{\nabla} \times \vec{B} = \mu_0 \vec{J}$$
 
$$\oint \vec{B} \cdot d\vec{l} = \mu_0 I_{\rm encl}$$

Magnetic Vector Potential: 
$$\vec{B} = \vec{\nabla} \times \vec{A}$$
  
 $\vec{\nabla} \cdot \vec{A} = 0$ 

$$\nabla^2 \vec{A} = 0$$

$$\nabla^2 \vec{A} = -\mu_0 \vec{J}$$

Magnetic Vector Potential: 
$$\vec{B} = \vec{\nabla} \times \vec{A}$$
 
$$\vec{\nabla} \cdot \vec{A} = 0$$
 
$$\nabla^2 \vec{A} = -\mu_0 \vec{J}$$
 Vector Potential – Line: 
$$\vec{A} = \frac{\mu_0}{4\pi} \int \frac{\vec{I}}{||\vec{r_{\rm sep}}||} dl' = \frac{\mu_0 I}{4\pi} \int \frac{1}{||\vec{r_{\rm sep}}||} d\vec{l'}$$
 Vector Potential – Surface: 
$$\vec{A} = \frac{\mu_0}{4\pi} \int \frac{\vec{K}}{||\vec{r_{\rm sep}}||} d\vec{l'}$$

Vector Potential – Surface: 
$$\vec{A} = \frac{\mu_0}{4\pi} \int \frac{\vec{K}}{||\vec{r}_{\text{sep}}||} da'$$
 Vector Potential – Volume: 
$$\vec{A} = \frac{\mu_0}{4\pi} \int \frac{\vec{J}(\vec{r}')}{||\vec{r}_{\text{sep}}||} d\tau'$$

Vector Potential – Volume: 
$$\vec{A} = \frac{\mu_0}{4\pi} \int \frac{\vec{J}(\vec{r'})}{||\vec{r'}||} d\tau'$$

Magnetic Dipole Moment: 
$$\vec{m} \equiv I \int d\vec{a} = I \vec{a}$$

Magnetic Dipole Potential 
$$\vec{A}_{\rm dip}(\vec{r}) = \frac{\mu_0}{4\pi} \frac{\vec{m} \times \hat{r}}{r^2}$$
  
Expansion:

Magnetic Torque: 
$$\vec{N} = \vec{m} \times \vec{B}$$

Energy of a Dipole: 
$$U = -\vec{m} \cdot \vec{B}$$

Energy of a Dipole: 
$$U = -\vec{m} \cdot \vec{B}$$

Force on a Magnetic Dipole: 
$$\vec{F} = \nabla(\vec{m} \cdot \vec{B})$$

Force Between Two Current-Carrying Wires: 
$$\frac{F}{l} = \frac{\mu_0 I_1 I_2}{2\pi r}$$

Linear Current: 
$$\vec{I} = \int \vec{K} \cdot d\vec{l} = \iint \vec{J} \cdot d\vec{a}$$

Gauss's Law:	$ec{ abla} \cdot ec{E} = rac{1}{\epsilon_0}  ho$	$\oint \vec{E} \cdot d\vec{a} = rac{Q_{ene}}{\epsilon_0}$
No monopoles:	$\vec{\nabla} \cdot \vec{B} = 0$	$ \oint \vec{B} \cdot d\vec{a} = 0 $
Faraday's Law:	$\vec{\nabla} \times \vec{E} = -\frac{\partial \vec{B}}{\partial \vec{a}}$	$\oint \vec{E} \cdot \vec{dl} = \frac{-\partial \Phi_B}{\partial t}$

Ampere's Law  $\vec{\nabla} \times \vec{B} = \mu_0 \vec{J} + \mu_0 \epsilon_0 \frac{\partial \vec{E}}{\partial t} \qquad \oint \vec{B} \cdot d\vec{l} = \mu_0 I_{enc} + \mu_0 \epsilon_0 \frac{\partial \Phi_E}{\partial t}$ with Maxwell's Correction:

#### Magnetostatics in Matter

Paramagnets: magnetization is parallel to  $\vec{B}$ magnetization is **opposite** to  $\vec{B}$ Diamagnets:

magnetization holds outside the presence of Ferromagnets:

an external magnetic field.

 $\vec{M} \equiv$  magnetic dipole per unit volume Magnetization:

 $\vec{J}_{\text{bound}} = \vec{\nabla} \times \vec{M}$ Bound Volume Current:  $\vec{K}_{\text{bound}} = \vec{M} \times \hat{n}$ Bound Surface Current:  $\vec{J} = \vec{J}_b + \vec{J}_f$ Free Current:  $\vec{H} \equiv \frac{1}{\mu_0} \vec{B} - \vec{M}$ Auxillary Field:

Ampere's Law for  $\vec{\nabla} \times \vec{H} = \vec{J}_f$ Auxillary Fields:  $\oint \vec{H} \cdot d\vec{l} = I_{fencl}$ 

 $\vec{M} = \chi_m \vec{H}$ Linear Magnetics:

Permeability:  $\mu \equiv \mu_0 (1 + \chi_m)$ Relative Permeability:  $\mu_r = 1 + \chi_m$ 

Linear Magnetics with E  $\vec{B} = \mu \vec{H}$ . and H Fields:

 $\vec{B} = \frac{\mu_0 m}{4\pi r^3} (2\cos(\theta)\hat{r} + \sin(\theta)\hat{\theta}), \text{ for } \vec{m} = m\hat{z}$ Dipole Field:

Field Inside a Uniformly  $\vec{B} = \frac{2}{3}\mu_0\vec{M}$ Magnetized Sphere: Really?:  $\vec{J}_b = \chi_m \vec{J}_f$ 

 $\vec{F} = \nabla(\vec{m} \cdot \vec{B})$ Force on a dipole moment:

### Electrodynamics

Ohm's Law:

Power in a Circuit:

$$\begin{split} P &= VI = I^2 R = \frac{V^2}{R} \\ \mathcal{E} &= \frac{F_{\text{mag, tot}}}{Q} = \int (\vec{v} \times \vec{B}) \cdot d\vec{l} \end{split}$$
Electromotive Force:

 $\mathcal{E} = \oint \vec{f} \cdot d\vec{I}$ 

 $\vec{\nabla} \times \vec{E} = -$ Faraday's Law:

Inductance:

Work of a Magnetic Field:

 $W = \frac{1}{2\mu_0} \int_{\text{all space}} B^2 d\tau$ 

 $\vec{J}_d \equiv \epsilon_0 \frac{\partial \vec{E}}{\partial t}$ Displacement Current:

 $\oint \vec{E} \cdot d\vec{l} = -\frac{d\Phi}{dt}$ Faraday's Law in Integral


# Maxwell's Equations in Matter

 $\vec{\nabla} \cdot \vec{D} = \rho_f$ Gauss's Law:

(unnamed)

 $\vec{\nabla} \times \vec{E} = -\frac{\partial \vec{B}}{\partial t}$ Faraday's Law:

 $\vec{\nabla} \times \vec{H} = \vec{J}_f + \frac{\partial \vec{D}}{\partial t}$ Ampere's Law with Maxwell's Correction:



### Boundary Conditions in Electrostatics

$$\begin{split} \vec{D}_{\text{above}}^{\perp} - \vec{D}_{\text{below}}^{\perp} &= \sigma_f & V_{\text{above}} = V_{\text{below}} \\ \vec{E}_{\text{above}}^{\perp} - \vec{E}_{\text{below}}^{\perp} &= \sigma_{\text{tot}}/\epsilon_0 & \vec{E}_{\text{above}}^{\parallel} - \vec{E}_{\text{below}}^{\parallel} &= \vec{0} \\ \vec{D}_{\text{above}}^{\parallel} - \vec{D}_{\text{below}}^{\parallel} &= \vec{P}_{\text{above}}^{\parallel} - \vec{P}_{\text{below}}^{\parallel} & \epsilon_{\text{above}} \vec{E}_{\text{above}}^{\perp} - \epsilon_{\text{below}} \vec{E}_{\text{below}}^{\perp} &= \sigma_f \\ \epsilon_{\text{above}} &\frac{\partial V_{\text{above}}}{\partial n} - \epsilon_{\text{below}} \frac{\partial V_{\text{below}}}{\partial n} &= -\sigma_f \end{split}$$

### Boundary Conditions in Magnetostatics

$$\begin{split} \vec{B}_{\mathrm{above}}^{\parallel} - \vec{B}_{\mathrm{below}}^{\parallel} &= \mu_0 \vec{K} \\ \vec{A}_{\mathrm{above}} - \vec{B}_{\mathrm{below}}^{\parallel} &= \mu_0 (\vec{K} \times \hat{\mathbf{n}}) \\ \vec{A}_{\mathrm{above}} &= \vec{A}_{\mathrm{below}} \\ \vec{H}_{\mathrm{above}}^{\perp} - \vec{H}_{\mathrm{below}}^{\perp} &= -(\vec{M}_{\mathrm{above}}^{\perp} - \vec{M}_{\mathrm{below}}^{\perp}) \\ \vec{H}_{\mathrm{above}}^{\perp} - \vec{H}_{\mathrm{below}}^{\parallel} &= \vec{K}_f \times \hat{\mathbf{n}} \end{split}$$

#### More Boundary Conditions

Equations 7.60-63 are the general boundary conditions for electrodynamics. In the case of *linear* media, they can be expressed in terms of E and B alone:

$$\begin{array}{ll} \text{(i)} \ \ \epsilon_1 E_1^\perp - \epsilon_2 E_2^\perp = \sigma_f, & \text{(iii)} \ \ \mathbf{E}_1^\parallel - \mathbf{E}_2^\parallel = \mathbf{0}, \\ \\ \text{(ii)} \ \ B_1^\perp - B_2^\perp = 0, & \text{(iv)} \ \ \frac{1}{\mu_1} \mathbf{B}_1^\parallel - \frac{1}{\mu_2} \mathbf{B}_2^\parallel = \mathbf{K}_f \times \hat{\mathbf{n}}. \end{array} \right\}$$

In particular, if there is no free charge or free current at the interface, then

(i) 
$$\epsilon_1 E_1^{\perp} - \epsilon_2 E_2^{\perp} = 0$$
, (ii)  $\mathbf{E}_1^{\parallel} - \mathbf{E}_2^{\parallel} = \mathbf{0}$ ,  
(ii)  $B_1^{\perp} - B_2^{\perp} = 0$ , (iv)  $\frac{1}{\mu_1} \mathbf{B}_1^{\parallel} - \frac{1}{\mu_2} \mathbf{B}_2^{\parallel} = \mathbf{0}$ . (7.65)

As we shall see in Chapter 9, these equations are the basis for the theory of reflection and refraction.

# Common Fields

Magnetic Sheet:

E and V for inf line: 
$$E(s) = \frac{\lambda}{2\pi\epsilon_0 s}, V(s) = \frac{\lambda}{2\pi\epsilon_0} \ln |\frac{s_0}{s}|$$

E and V for inf plane: 
$$E = \frac{|\sigma|}{2\epsilon_0}, V = \mp \frac{\sigma z}{2\epsilon_0}$$

E and V at 
$$(0,0,z)$$
 of 
$$E(z) = \frac{\lambda zR}{2\epsilon_0(R^2+z^2)^{\frac{3}{2}}}, V(z) = \frac{\lambda \cdot R}{2\epsilon_0\sqrt{R^2+z^2}}$$

E and V at 
$$(0,0,z)$$
 of disk: 
$$E(z) = \frac{\sigma}{2\epsilon_0} [1 - \frac{z}{\sqrt{z^2 + R^2}}]$$
 
$$V(z) = \frac{\sigma}{2\epsilon_0} [\sqrt{R^2 + z^2} - |z|]$$

E and V for uniform 
$$E(r) = \frac{\sigma R^2}{\epsilon_0 r^2} u(r-R)$$
 hollow sphere: 
$$V(r) = \frac{\sigma R}{\epsilon_0 r^2} u(R-r) + \frac{\sigma R^2}{\epsilon_0 r^2} u(r-R)$$

$$V(r) = \frac{\sigma R}{\epsilon_0} u(R - r) + \frac{\sigma R^2}{\epsilon_0 r} u(r - R)$$

Magnetic Wire: 
$$\frac{\mu_0}{4\pi} \frac{I}{r} (\sin(\theta_1) - \sin(\theta_2))$$

Magnetic Field of an Arc 
$$\mu_0 I R^2 \theta$$

Along z: 
$$\frac{\mu_0 T R \ v}{4\pi (z^2 + R^2)^{3/2}}$$

Magnetic Field of a Solenoid: 
$$\mu_0 nI$$

B-field in thin magnetized cylinder: 
$$B = \mu_0 M$$

B-field in magnetized 
$$B=\tfrac{2}{3}\mu_0 M=\tfrac{2}{3}\mu_0\sigma R\omega \text{ for spinning sphere sphere:}$$