CSCI 466: Networks

Operational Security (Firewalls, Protocols, Etc)

Reese Pearsall Fall 2024

*All images are stolen from the internet

Announcements


PA3 due **Sunday November 3rd**

Quiz on Friday (no class)



Spoofing MAC Addresses


We used scapy to spoof network layer and transport layer information, but we can also use it to spoof MAC addresses or things like ARP packets




There is a variety of tools out there that allow you to override the MAC addresses of your NIC

Technitium is one program that overrides Windows settings to spoof MAC addresses

Review



- Same key used for encrypting and decrypting
- Using block ciphers (AES), we can encrypt an arbitrary size of data
- Issue: How to securely share secret keys with each other?




- Two keys: Public Key (a lock), and a price key (the key)
- Public key is used to encrypt. Private key used to decrypt message
- Using math, we can securely send messages over an unsecure channel without sharing any sensitive information
- Issue: We can not encrypt stuff bigger than our key (2048 bits)
- Symmetric and asymmetric cryptography are used together

(use RSA to send the key for symmetric crypto!)

Review

Symmetric Crypto Asymmetric Crypto and Hashing all work together to send secure, authentic messages



- Transport Layer Security (TLS) is a protocol used to provide communication security over a TCP connection
- This exists somewhere between the application layer and transport layer


Application
TLS socket
TCP socket
TCP
IP
TCP API
TCP enhanced with TLS


TLS will always be running if you are doing web communication with https

https = Hypertext Transfer Protocol **Secure**




HTTPS/TLS will handle all the encryption, key generation, certificate checking, authentication for you!





UDP does not use TLS



TLS/SSL does not mandate that two users use a specific symmetric key algorithm

Server will select encryption and hashing algorithm to use

TLS connection can be closed using a TCP FIN

- 1. The client sends a list of cryptographic algorithms it supports, along with a client nonce.
- 2. From the list, the server chooses a symmetric algorithm (for example, AES) and a public key algorithm (for example, RSA with a specific key length), and HMAC algorithm (MD5 or SHA-1) along with the HMAC keys. It sends back to the client its choices, as well as a certificate and a server nonce.

- 1. The client sends a list of cryptographic algorithms it supports, along with a client nonce.
- 2. From the list, the server chooses a symmetric algorithm (for example, AES) and a public key algorithm (for example, RSA with a specific key length), and HMAC algorithm (MD5 or SHA-1) along with the HMAC keys. It sends back to the client its choices, as well as a certificate and a server nonce.
- 3. The client verifies the certificate, extracts the server's public key, generates a Pre-Master Secret (PMS), encrypts the PMS with the server's public key, and sends the encrypted PMS to the server.


- 1. The client sends a list of cryptographic algorithms it supports, along with a client nonce.
- 2. From the list, the server chooses a symmetric algorithm (for example, AES) and a public key algorithm (for example, RSA with a specific key length), and HMAC algorithm (MD5 or SHA-1) along with the HMAC keys. It sends back to the client its choices, as well as a certificate and a server nonce.
- 3. The client verifies the certificate, extracts the server's public key, generates a Pre-Master Secret (PMS), encrypts the PMS with the server's public key, and sends the encrypted PMS to the server.
- 4. Using the same key derivation function (as specified by the TLS standard), the client and server independently compute the Master Secret (MS) from the PMS and nonces. The MS is then sliced up to generate the two encryption and two HMAC keys. Furthermore, when the chosen symmetric cipher employs CBC (such as 3DES or AES), then two Initialization Vectors (IVs)—one for each side of the connection—are also obtained from the MS. Henceforth, all messages sent between client and server are encrypted and authenticated (with the HMAC).

- 1. The client sends a list of cryptographic algorithms it supports, along with a client nonce.
- 2. From the list, the server chooses a symmetric algorithm (for example, AES) and a public key algorithm (for example, RSA with a specific key length), and HMAC algorithm (MD5 or SHA-1) along with the HMAC keys. It sends back to the client its choices, as well as a certificate and a server nonce.
- 3. The client verifies the certificate, extracts the server's public key, generates a Pre-Master Secret (PMS), encrypts the PMS with the server's public key, and sends the encrypted PMS to the server.
- 4. Using the same key derivation function (as specified by the TLS standard), the client and server independently compute the Master Secret (MS) from the PMS and nonces. The MS is then sliced up to generate the two encryption and two HMAC keys. Furthermore, when the chosen symmetric cipher employs CBC (such as 3DES or AES), then two Initialization Vectors (IVs)—one for each side of the connection—are also obtained from the MS. Henceforth, all messages sent between client and server are encrypted and authenticated (with the HMAC).
- 5. The client sends the HMAC of all the handshake messages.
- 6. The server sends the HMAC of all the handshake messages.

The TLS Master secret, or "session key" consists of four keys

- ullet $E_B=$ session encryption key for data sent from Bob to Alice
- M_B = session HMAC key for data sent from Bob to Alice, where HMAC [RFC 2104] is a standardized hashed message authentication code (MAC) that we encountered in section 8.3.2
- E_A = session encryption key for data sent from Alice to Bob
- ullet $M_A = session HMAC$ key for data sent from Alice to Bob

Network-Layer Security



This could be a **TCP** segment (unencrypted), **TLS** segment, **UDP** segment, **ICMP** packet etc

We have security at the transport layer, but we might also desire security at a network-layer level

The IP security protocol (IPsec) provides data integrity, origin authentication, attack prevention, and confidentiality at the network-layer

IPsec is most commonly seen when using a Virtual Private Network (VPN)

Public Network- Anyone can access/communicate with the devices on the network

Private Network- Completely isolated from public internet, typically reserved for a particular institution (this can be costly)

VPNs


IPsec is most commonly seen when using a Virtual Private Network (VPN)

Public Network- Anyone can access/communicate with the devices on the network

Private Network- Completely isolated from public internet, typically reserved for a particular institution (this can be costly)

VPNs extend a **private network** over a **public network**

 All messages get encrypted prior to entering any public network (using IPsec), and rerouted through a secure network




Converts vanilla IPv4 datagrams to IPsec datagrams

When a source IPsec entity (host or router) sends secure datagrams to a destination entity, it does so with either the Authentication Header (AH) protocol, or the Encapsulation Security Payload (ESP) protocol

(AH = no confidentiality – not used as much as ESP)


IP Sec

provides datagram-level encryption, authentication, integrity for both user traffic and control traffic (e.g., BGP, DNS messages) two "modes":



transport mode:

 only datagram payload is encrypted, authenticated



tunnel mode:


- entire datagram is encrypted, authenticated
- encrypted datagram encapsulated in new datagram with new IP header, tunneled to destination

Security associations (SAs)

before sending data, security association (SA) established from sending to receiving entity (directional, simplex)

Sending, receiving entitles maintain state information about SA

recall: TCP endpoints also maintain state info IP is connectionless; IPsec is connection-oriented!



- 32-bit identifier: Security Parameter Index (SPI)
- origin SA interface (200.168.1.100)
- destination SA interface (193.68.2.23)
- type of encryption used


- encryption key
- type of integrity check used
- authentication key

VPN Uses

- **Privacy-** makes it harder for websites, ISPs, and advertisers to track your online activities or identify your real location
- Encryption- all network traffic is encrypted (good when using public networks)
- Geo-Restrictions- streaming services have different shows/movies based on country
- Accessing a private network- helpful for remote workers to access their corporate network
- Dealing with bad ISPs ISP may throttle services based on your activities
- Government Censorship

(2024) Around 46% of adults have reported using a VPN

Ipsec Datagram




Endpoint Security

A **firewall** is a combination of hardware and software that isolates an organizations internal network form the internet at large, allowing some packets to pass, and blocking others

Three goals

- All traffic from outside to inside, inside to outside, passes through the firewall
- Only authorized traffic (defined by firewall's policy) will be allowed to pass
- The firewall itself is immune to penetration



Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

Policy	Rules			
No outside web access.				

Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

Policy	Rules			
No outside web access.	Drop all outgoing packets to any IP address, port 80 or 443			

Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

Policy	Rules
No outside web access.	Drop all outgoing packets to any IP address, port 80 or 443
No incoming TCP connections	

Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

Policy	Rules		
No outside web access.	Drop all outgoing packets to any IP address, port 80 or 443		
No incoming TCP connections	Drop all incoming TCP SYN packets		

Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

Example Polices

Policy	Rules			
No outside web access.	Drop all outgoing packets to any IP address, port 80 or 443			
No incoming TCP connections	Drop all incoming TCP SYN packets			

(Would this help with SYN flooding?)

Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

Policy	Rules			
No outside web access.	Drop all outgoing packets to any IP address, port 80 or 443			
No incoming TCP connections	Drop all incoming TCP SYN packets			
Prevent your network from being tracerouted				

Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

Policy	Rules			
No outside web access.	Drop all outgoing packets to any IP address, port 80 or 443			
No incoming TCP connections	Drop all incoming TCP SYN packets			
Prevent your network from being tracerouted	Drop all incoming/outgoing ICMP traffic			

Packet Filter

- → Analyze packet's details, and make decision.
- → Look at IPs, Ports, Protocol, TCP Flags, ICMP Type, and more

action	source address	dest address	protocol	source port	dest port	flag bit
allow	222.22/16	outside of 222.22/16	TCP	> 1023	80	any
allow	outside of 222.22/16	222.22/16	TCP	80	> 1023	ACK
allow	222.22/16	outside of 222.22/16	UDP	> 1023	53	_
allow	outside of 222.22/16	222.22/16	UDP	53	> 1023	_
deny	all	all	all	all	all	all

Access Control List

Allow/Deny Traffic

In Linux world, these tables are set using the iptables program

Stateful Filter

→ Make decisions based on connection information

Firewall may keep an internal table

source address	dest address	source port	dest port	
222.22.1.7	37.96.87.123	12699	80	
222.22.93.2	199.1.205.23	37654	80	
222.22.65.143	203.77.240.43	48712	80	




Access Control List for Stateful Filter

action	source address	dest address	protocol	source port	dest port	flag bit	check conxion
allow	222.22/16	outside of 222.22/16	TCP	> 1023	80	any	
allow	outside of 222.22/16	222.22/16	TCP	80	> 1023	ACK	х
allow	222.22/16	outside of 222.22/16	UDP	> 1023	53	_	
allow	outside of 222.22/16	222.22/16	UDP	53	> 1023	_	х

Example: Random TCP packet with the ACK bit set, even if no TCP connection established

Application gateways

- filter packets on application data as well as on IP/TCP/UDP fields.
- example: allow select internal users to telnet outside



Stateless and Stateful firewalls are examples of Intrusion Prevention Systems (IPS)

There will be times where malicious packets will bypass the firewall, so we need another system within the network to detect potentially malicious traffic

To detect attacks, we need to perform deeper inspection

- → A series of packets
- → The context of a packet
- → Application Data of a Packet

An **instruction detection system (IDS)** inspects packets will generate an alert when potentially malicious traffic is observed

Stateless and Stateful firewalls are examples of Intrusion Prevention Systems (IPS)

There will be times where malicious packets will bypass the firewall, so we need another system within the network to detect potentially malicious traffic

To detect attacks, we need to perform **deeper** inspection

- → A series of packets
- → The context of a packet
- → Application Data of a Packet

An **instruction detection system (IDS)** inspects packets will generate an alert when potentially malicious traffic is observed

What might suspicious traffic look like?

Stateless and Stateful firewalls are examples of Intrusion Prevention Systems (IPS)

There will be times where malicious packets will bypass the firewall, so we need another system within the network to detect potentially malicious traffic

To detect attacks, we need to perform deeper inspection

- → A series of packets
- → The context of a packet
- → Application Data of a Packet

An **instruction detection system (IDS)** inspects packets will generate an alert when potentially malicious traffic is observed

What might suspicious traffic look like?

- → Communication with foreign, unknown IP address
- → Unauthorized web traffic
- → A large spike in traffic

Two types –

1. Signature-Based Detection Systems

Maintain a large database of known "signatures" for malicious packets

-- Malicious IP addresses or URLs

-- Email Addresses

-- Specific String of Bits

-- File/Message Hashes

-- Protocol Specific (nmap)

When would signature-based detection **not work?**

Two types –

1. Signature-Based Detection Systems

Maintain a large database of **known** "signatures" for malicious packets

- -- Malicious IP addresses or URLs -- Email Addresses

-- Specific String of Bits

-- File/Message Hashes

-- Protocol Specific (nmap)

When would signature-based detection **not work?**

Signature-based detection will never work for **new threats**, so we need a way to dynamically analyze threats

2. Anomaly-based Detection System

If you know what "normal" traffic looks like, you can identify unusual, potentially malicious traffic You get a large spike in ICMP packets? Someone might be trying to NMAP you

Nmap

Short for network mapper. It is an open-source Linux command-line tools that is used to scan IP addresses or networks to see which **hosts** are running on their network, discover **open ports** and **services**, and **detect vulnerabilities**

Command issues a bunch of ICMP packets at the target host

Has a lot of great uses to network administrators, and for malicious actors (ie hackers)

```
admin@ip-172-26-0-73:~$ nmap scanme.nmap.org
Starting Nmap 7.40 ( https://nmap.org ) at 2020-07-22 02:48 UTC
Nmap scan report for scanme.nmap.org (45.33.32.156)
Host is up (0.078s latency).
Other addresses for scanme.nmap.org (not scanned): 2600:3c01::f03c:91ff:fe18:bb2f
Not shown: 995 closed ports
PORT
         STATE
                   SERVICE
22/tcp
                   ssh
          open
         filtered smtp
25/tcp
                  http
ao/tcp
          open
9929/tcp open
                  nping-echo
                  Elite
31337/tcp open
Nmap done: 1 IP address (1 host up) scanned in 2.40 seconds
admin@ip-172-26-0-73:~$
```

Can also return things such as OS versions and application versions

Security/Network Engineers will look for **Indicators of Compromise (IOCs)** to determine if a network may have been breached

