CSCI 132: Basic Data Structures and Algorithms

Sorting (Bubble Sort)

Reese Pearsall Spring 2025

Sorting

We will spend the next several lectures discussing how to **sort** a set of values (typically an Array of ints)

Sorting a dataset is a very frequently done task, and working with a sorted dataset is much easier than working with an unsorted dataset

Instead of saying Array. Sort (), we will write four different sorting algorithms

Sorting

We will spend the next several lectures discussing how to **sort** a set of values (typically an Array of ints)

Sorting a dataset is a very frequently done task, and working with a sorted dataset is much easier than working with an unsorted dataset

Instead of saying Array. Sort (), we will write four different sorting algorithms

First, let's write a method that will generate an N-sized array filled with random integers (1-100)


Sorting

```
public int[] getRandomArray(int n) {
   int[] array = new int[n];
   Random rand = new Random();
   for(int i = 0; i < array.length; i++) {
      array[i] = rand.nextInt(101);
   }
   return array;
}</pre>
```


Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted


7 2 5 3 9 1 6


Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





Is 7 greater than 2? → SWAP















Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





At this point, 9 (the biggest number) is at the correct spot in the array.

So, we no longer need to check that index!

Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





At this point, 9 (the biggest number) is at the correct spot in the array.

So, we no longer need to check that index!

Bubble Sort → "The biggest bubbles rise to the top naturally"

Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted






At this point, 9 (the biggest number) is at the correct spot in the array.

So, we no longer need to check that index!

Now, we start over again, but now we check one less spot!





















Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





7 is now in the correct spot of the array

Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted






Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted






Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted



Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted





(fast forwarding....)

Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted



All done!

Iterate through an array and compare **pairs** in the array. When comparing two numbers, if one is bigger than the other, **swap.** Keep iterating until array is sorted



All done!

```
public void bubbleSort(int[] array) {
   int n = array.length;
   for(int i = 0; i < n - 1; i++) {</pre>
      for(int j = 0; j < n - i - 1; j++) {
         if( array[j] > array[j + 1]) {
            //swap
            int temp = array[j];
            array[j] = array[j+1];
            array[j + 1] = temp;
```

```
public void bubbleSort(int[] array) {
   int n = array.length;
   for(int i = 0; i < n - 1; i++) {</pre>
      for(int j = 0; j < n - i - 1; j++) {
         if( array[j] > array[j + 1]) {
            //swap
            int temp = array[j];
            array[j] = array[j+1];
            array[j + 1] = temp;
                    Running time?
```

```
public void bubbleSort(int[] array) {
   int n = array.length;O(1)
   for(int i = 0; i < n - 1; i++) { O(n)
      for(int j = 0; j < n - i - 1; j++) { O(n)
         if( array[j] > array[j + 1]) { O(1)
            //swap
            int temp = array[j]; O(1)
            array[j] = array[j+1]; O(1)
            array[j + 1] = temp; O(1)
                   Running time?
```

```
public void bubbleSort(int[] array) {
   int n = array.length;O(1)
   for(int i = 0; i < n - 1; i++) { O(n)
       for(int j = 0; j < n - i - 1; j++) { O(n)
          if( array[j] > array[j + 1]) { O(1)
              //swap
              int temp = array[j]; O(1)
              array[j] = array[j+1]; O(1)
              array[j + 1] = temp; O(1)
                      Running time?
                                                    For loop in a for loop = \mathbf{n} * \mathbf{n}
                                 n = | array |
```

Bubble Sort Gif

https://upload.wikimedia.org/wikipedia/commons/c/c8/Bubble-sort-example-300px.gif

Bubble Sort (Recursion)

Base Case:

If we have one array element left to sort, return

Recursive case:

Do one loop of bubble sort, call the method again and pass the array except for the last element (last element is already in place!)

Bubble Sort (Recursion)

```
public void bubbleSortRecursion(int[] array, int n) {
       if (n == 1) {
               return;
       for(int i = 0; i < n -1;i++) {</pre>
               if(array[i] > array[i+1]) {
                      int temp = array[i];
                      array[i] = array[i+1];
                      array[i+1] = temp;
       bubbleSortRecursion(array,n-1);
```

n = size of unsorted section of array


Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot






Goal: Find the minimum element

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot

7 2 5 3 9 1 6



start

Goal: Find the minimum element

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot

7 2 5 3 9 1 6

1

start

Goal: Find the minimum element

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot

7 2 5 3 9 1 6
start

Goal: Find the minimum element

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot


7 2 5 3 9 1 6

1

start

Goal: Find the minimum element

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot




Goal: Find the minimum element

minimum so far
$$= 1$$

Now that we've found the minimum value, swap it with the spot that we started at


Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

$$minimum_so_far = 2$$


Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

$$minimum_so_far = 2$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot




start

Goal: Find the minimum element

$$minimum_so_far = 2$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot




start

Goal: Find the minimum element

$$minimum_so_far = 2$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot




start

Goal: Find the minimum element

$$minimum_so_far = 2$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot




start

Goal: Find the minimum element

$$minimum_so_far = 2$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot




start

Goal: Find the minimum element

$$minimum_so_far = 2$$


Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

$$minimum_so_far = 5$$


Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

$$minimum_so_far = 5$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

$$minimum_so_far = 3$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot





start

Goal: Find the minimum element

$$minimum_so_far = 3$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot




1

start

Goal: Find the minimum element

minimum so far
$$= 3$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Goal: Find the minimum element

$$minimum_so_far = 3$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot






Goal: Find the minimum element

minimum so far
$$= 3$$

Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot



Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot





Iterate through the array N times, and during each iteration, **find the minimum element** and place it in the correct spot





Selection Sort Gif

https://upload.wikimedia.org/wikipedia/commons/9/94/Selection-Sort-Animation.gif