

# CSCI 132:

# Basic Data Structures and Algorithms

LinkedLists

Reese Pearsall  
Spring 2023


No class on **MONDAY**

Lab 5 due on Tuesday @ 11:59 PM

- After today, you will be able to do it


Please fill out the early semester survey (can be found on course website)

A **Linked List** is a data structure that consists of a collection of connected nodes



Nodes consists of **data** (String, int, array, etc) and a **pointer to the next node**

A **Linked List** is a data structure that consists of a collection of connected nodes



Nodes consists of **data** (String, int, array, etc) and a **pointer to the next node**


A Linked List also has a pointer to the start of the Linked List (`head`)

A Linked List will hold Node objects

```
public class Node {  
    private int age;  
    private String name;  
    private Node next;  
    public Node(int a, String n) {  
        this.age = a;  
        this.name = n;  
        this.next = null;  
    }  
}
```

} Data

} Pointer to next Node



A Linked List will hold Node objects


```
public void setNext(Node n) {  
    this.next = n;  
}
```

```
System.out.println(reese.getNext().getData())
```

???

```
public Node getNext() {  
    return this.next;  
}
```

```
public String getData() {  
    return this.name + ", Age: " + this.age;  
}
```



A Linked List will hold Node objects


```
public void setNext(Node n) {  
    this.next = n;  
}
```

```
public Node getNext() {  
    return this.next;  
}
```

```
public String getData() {  
    return this.name + ", Age: " + this.age;  
}
```

```
System.out.println(reese.getNext().getData());
```

This would print out the Sarah node's data



A Linked List will hold Node objects



```
public void setNext(Node n) {  
    this.next = n;  
}
```

reese.setNext(susan)

???

```
public Node getNext() {  
    return this.next;  
}
```

```
public String getData() {  
    return this.name + ", Age: " + this.age;  
}
```





A Linked List will hold Node objects


```
public void setNext(Node n) {  
    this.next = n;  
}
```

`reese.setNext(susan)`

Set's the Reese's node `next` value to point to Susan

```
public Node getNext() {  
    return this.next;  
}
```


```
public String getData() {  
    return this.name + ", Age: " + this.age;  
}
```



The Sarah node also got removed from the linked list (!!!)

# Linked List Methods

- `addToFront()` - adds new node to beginning of LL
- `addToBack()` – adds new node to end of LL
- `removeFirst()` – removes first node of LL
- `removeLast()` – removes last node of LL
- `printLinkedList()` – prints nodes and their data



Linked List Methods • `addToFront()` - adds new node to beginning of LL


What if the Linked List is empty?

## Linked List Methods

- `addToFront()` - adds new node to beginning of LL

What if the Linked List is empty?


Set `head` equal to the new node



## Linked List Methods

- `addToFront()` - adds new node to beginning of LL

What if the Linked List is not empty?




## Linked List Methods

- `addToFront()` - adds new node to beginning of LL

What if the Linked List is not empty?


1. Set the new node's `next` value to `head`



## Linked List Methods • addToFront () - adds new node to beginning of LL

What if the Linked List is not empty?

1. Set the new node's `next` value to `head`
2. Update `head` to point to new node





## Linked List Methods • addToFront () - adds new node to beginning of LL

What if the Linked List is not empty?

1. Set the new node's next value to head
2. Update head to point to new node

head



```
public void addToFront(Node newNode) {  
    if(head == null) {  
        head = newNode;  
    }  
    else {  
        newNode.setNext(head);  
        head = newNode;  
    }  
}
```




## Linked List Methods

- `addToBack()` – adds new node to end of LL

We need to find the end of the Linked List, but we don't know how many Nodes there may be...

We need to find the last node!

- But how do we know if a node is the last node ???




## Linked List Methods

- `addToBack()` – adds new node to end of LL

We need to find the end of the Linked List, but we don't know how many Nodes there may be...

We need to find the last node!

- But how do we know if a node is the last node? If a node's `next` value is null



## Linked List Methods


- `addToBack()` – adds new node to end of LL

We need to find the end of the Linked List, but we don't know how many Nodes there may be...

We need to find the last node!

- But how do we know if a node is the last node? If a node's `next` value is null

1. Traverse through the linked list until we find the last node



## Linked List Methods


- `addToBack()` – adds new node to end of LL

We need to find the end of the Linked List, but we don't know how many Nodes there may be...

We need to find the last node!

- But how do we know if a node is the last node? If a node's `next` value is null

1. Traverse through the linked list until we find the last node
2. Set the last node's `next` value equal to the new node




## Linked List Methods

- `addToBack()` – adds new node to end of LL

1. Traverse through the linked list until we find the last node
2. Set the last node's `next` value equal to the new node

```
public void addToBack(Node newNode) {  
  
    Node current = head;  
    while(current.getNext() != null) {  
        current = current.getNext();  
    }  
    current.setNext(newNode);  
}
```



## Linked List Methods

- `printLinkedList()` – prints nodes and their data

Iterate through each Node in the LL, and print the data in that node

- `printLinkedList()` – prints nodes and their data

Iterate through each Node in the LL, and print the data in that node

```
public void printLinkedList() {  
  
    Node current = head;  
    while(current != null) {  
        System.out.println(current.getData());  
        current = current.getNext();  
    }  
  
}
```

## Linked List Methods

- `printLinkedList()` – prints nodes and their data

Iterate through each Node in the LL, and print the data in that node

```
public void printLinkedList() {  
    Node current = head;  
    while(current != null) {  
        System.out.println(current.getData());  
        current = current.getNext();  
    }  
}
```

Always start at the head node


“Keep on looping until we reach the end of the LL”

This line updates the current node we are at  
ie. “move to the next node”



## Linked List Methods


- `removeFirst()` – removes first node of LL



## Linked List Methods

- `removeFirst()` – removes first node of LL


1. Update `head` to be the next node



## Linked List Methods

- `removeFirst()` – removes first node of LL

1. Update `head` to be the next node
2. Update the old `head`'s next value to be `null`




## Linked List Methods

- `removeFirst()` – removes first node of LL

1. Update `head` to be the next node
2. Update the old `head`'s next value to be `null`

```
public void removeFirst() {  
    Node temp = this.head.getNext();  
    head.setNext(null);  
    head = temp;  
}
```

Create a new temporary variable to save 2<sup>nd</sup> node value




## Linked List Methods

- `removeFirst()` – removes first node of LL

1. Update `head` to be the next node
2. Update the old `head`'s next value to be `null`

*There's an easier way to do this*



## Linked List Methods

- `removeFirst()` – removes first node of LL


1. Update `head` to be the next node
2. ~~Update the old `head`'s next value to be `null`~~

*There's an easier way to do this*

We don't need to remove the pointer.

Remember, whenever we iterate or add something to a list, we always start from the `head` node

If a node is not reachable from the `head`, it is essentially removed from the LL !!



# Linked List Methods

- `removeFirst()` – removes first node of LL

1. Update `head` to be the next node
2. ~~Update the old `head`'s next value to be `null`~~

***There's an easier way to do this***


```
public void removeFirst() {  
    if(size != 0) {  
        head = head.getNext();  
    }  
    //Node temp = this.head.getNext();  
    //head.setNext(null);  
    //head = temp;  
}
```

We don't need to remove the pointer.

Remember, whenever we iterate or add something to a list, we always start from the `head` node

If a node is not reachable from the `head`, it is essentially removed from the LL !!


(we need to also check that there is *something* to be removed, otherwise we get an error)



## Linked List Methods

- `removeLast()` – removes last node of LL

???






## Linked List Methods

- `removeLast()` – removes last node of LL

1. Find the second to last node
2. Set that node's `next` value to `null`



## Linked List Methods

- `removeLast()` – removes last node of LL

1. Find the **second to last node**
2. Set that node's next value to null

```
public void removeLast() {  
    Node current = head;  
    while(current.getNext().getNext() != null) {  
        current = current.getNext();  
    }  
    current.setNext(null);  
}
```

