

CSCI 466: Networks

Network Forensics: Tools and example investigation

Reese Pearsall
Fall 2024

Goals of Network Forensics


Answer important questions such as:

- When did the incident happen? What is the timeline?
- What is the root cause of the incident?
- Who attacked us?
- Why did they attack us?
- What is the scope of the damage?





Reflection

- Did staff and organizations perform as expected?
- What will our organization do next time?
- What corrective actions need to happen?



The **Cyber Kill Chain** describes the typical steps a malicious actor carries out to conduct a cyber attack



Malware File Types to Check for

- `.exe` files - Windows executable files
- `.dll` files - Dynamic Linked Libraries
- `.msi` files – Windows installers
- `.bat` files – Windows command line script
- `.vbs` scripts – Visual Basic Scripts
- `.js` scripts – Javascript file
- `.docx` files – Microsoft Word Document (can contain macros)
- `.xlsx` files – Microsoft Excel Spreadsheet (can contain macros)
- `.zip` files – Compressed Archive Files (may have scripts when unzipped)
- `.pdf` files – Can contain suspicious links, or a PDF reader vulnerability

There are many tools we can use for digital forensics, but we are covering some of the more well-known ones

Wireshark

Time	Dst	Dst port	Host	Info
2022-06-27 18:00:01	23.29.125.210	80	23.29.125.210	GET /herALook.dat HTTP/1.1 ← QAKBOT DLL
2022-06-27 18:07:57	45.46.53.140	2222		Client Hello
2022-06-27 18:08:10	45.46.53.140	2222		Client Hello
2022-06-27 18:08:14	45.46.53.140	2222		Client Hello
2022-06-27 18:08:44	45.46.53.140	2222		Client Hello
2022-06-27 18:09:51	45.46.53.140	2222		Client Hello
2022-06-27 18:12:59	45.46.53.140	2222		Client Hello
2022-06-27 18:13:01	45.46.53.140	2222		Client Hello
2022-06-27 18:13:04	179.60.146.16	8888	bande.icu	GET /avoid/jail.json HTTP/1.1
2022-06-27 18:13:05	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:06	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:06	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:07	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:07	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:07	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:08	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:08	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:09	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:09	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:10	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:10	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1
2022-06-27 18:13:11	179.60.146.16	8888	bande.icu	GET /dynamic?emerge=false HTTP/1.1

We can use Wireshark to identify **specific** malicious packets, and find the exact moment where the infection started

C2 server information, Victim information, other relevant evidence

NetworkMiner

NetworkMiner 2.0

File Tools Help

-- Select a network adapter in the list --

Keywords Anomalies

Hosts (129) Files (131) Images (33) Messages Credentials (2) Sessions (113) DNS (271) Parameters (1199)

Filter keyword: ☐ Case sensitive ExactPhrase

D. port	Protocol	Filename	Extension	Size	Details
TCP 53130	TlsCertificate	nr-data.net.cer	cer	1 203 B	TLS Certificate: C
TCP 53130	TlsCertificate	GeoTrust SSL CA - G2.cer	cer	1 117 B	TLS Certificate: C
TCP 53130	TlsCertificate	GeoTrust Global CA.cer	cer	897 B	TLS Certificate: C
TCP 53138	HttpGetNormal	index.html[2].ocsp-response	ocsp-response	1 455 B	gb.symcd.com/
TCP 53139	HttpGetChunked	index.html	html	86 958 B	www.meetup.com
TCP 53142	HttpGetNormal	almond.min.js	javascript	2 758 B	static2.meetupsta
TCP 53140	HttpGetNormal	meetup_query_ui.css	css	6 725 B	static2.meetupsta
TCP 53144	HttpGetNormal	client.min.js	javascript	3 692 B	static2.meetupsta
TCP 53145	HttpGetNormal	infoWidget.min.js	javascript	20 639 B	static2.meetupsta
TCP 53151	HttpGetNormal	groupMetadata.min.js	javascript	2 409 B	static1.meetupsta
TCP 53149	HttpGetNormal	mt-twoButtonCTA-testimonial.css	css	445 B	static1.meetupsta
TCP 53147	HttpGetNormal	print.css	css	2 171 B	static1.meetupsta
TCP 53141	HttpGetNormal	meetup-modern.css	css	223 971 B	static2.meetupsta
TCP 53139	HttpGetNormal	index.html.6D1A30C1.css	css	5 582 B	www.meetup.com
TCP 53146	HttpGetNormal	whitney.css	css	83 455 B	static1.meetupsta
TCP 53150	HttpGetNormal	ghome.min.js	javascript	102 378 B	static1.meetupsta
TCP 53148	HttpGetNormal	chapterbase.css	css	165 101 B	static1.meetupsta
TCP 53143	HttpGetNormal	Meetup.Base.jquery.min.js	javascript	414 355 B	static2.meetupsta
TCP 53152	HttpGetNormal	thumb_156167702.jpeg	jpeg	2 611 B	photos3.meetupst
TCP 53156	HttpGetNormal	thumb_151699612.jpeg.PNG	PNG	2 571 B	photos3.meetupst

Case Panel

Filename MD5

snort.log.... 2f301c2...

Reload Case Files


Live Sniffing Buffer Usage:

NetworkMiner is an automated flow analysis tool that will identify all hosts, downloaded files, emails, logins from a pcap file and attempt to reassemble them for analysis

Very powerful tool that can provide many helpful insights during an investigation



NetworkMiner should always be run in a sandbox environment (VM) that is disconnected from the network



Zui (formerly known as **brim**) is a automated flow analysis tool that will identify any suspicious packets, emails, certificates, files from a pcap file and create a *timeline*

Won't assemble the files, so it will be safer to use

Can help identify potential IOCs


VirusTotal

VirusTotal is a massive database of known malware signatures and malicious fingerprints




We can provide signatures from our investigation to see if they have been flagged as malicious in the past

- File Hashes
- IP Addresses
- Domain Names



The community tab will provide more context around the malicious signatures



Let's do an example investigation with real captured malicious traffic

We will want to keep a notepad to put relevant information as we are analyzing the PCAP file

We will want to be constructing a timeline as we are doing the investigation

babe please stop you
aren't a hard-boiled 1940's
network forensics investigator



beat it toots these streets
ain't what they used to be




Let's do an example investigation with real captured malicious traffic

First, let's try to find the piece of malware that was installed

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help			
http			
Time	Destination	Protocol	Info
12.674904	209.197.3.8	HTTP	GET /filestreamingservice/files/9f86601f-2d70-42ad-
12.729162	10.13.13.99	HTTP	HTTP/1.1 200 OK (application/x-chrome-extension)
39.446064	176.124.198.213	HTTP	GET /Fs8Py/eKTYt3dRbEXw HTTP/1.1
41.067893	10.13.13.99	HTTP	HTTP/1.1 200 OK (image/gif)

This HTTP Get request seems suspicious

- Strange URL in the header




VirusTotal confirms that this IP address is malicious

Investigating DNS


Many of the DNS requests were made to “normal” website. However, this domain seemed a bit strange and this request was made shortly before the malicious HTTP request

Time	Destination	Protocol	Info
0.000000	10.13.13.3	DNS	Standard query 0x222a A alejnr.com
0.000186	10.13.13.3	DNS	Standard query 0x40a4 HTTPS alejnr.com
0.056796	10.13.13.99	DNS	Standard query response 0x40a4 HTTPS alejnr.com SOA pdns1.registrar-servers.com
0.056891	10.13.13.99	DNS	Standard query response 0x222a A alejnr.com A 162.213.255.36

This domain had been flagged as malicious in the past



VirusTotal also provides context as to why it was flagged as malicious



Where did this IP address come from?

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help			
dns.flags.response == 1 && dns.a == 176.124.198.213			
Time	Destination	Protocol	Info

This malicious IP did not come from a DNS response.

This could be an indicator that another piece of malware contacted that IP addressed and issued the HTTP request (malware dropper)

Many of the DNS requests were made to “normal” website. However, this domain seemed a bit strange and this request was made shortly before the malicious HTTP request

dns			
Time	Destination	Protocol	Info
0.000000	10.13.13.3	DNS	Standard query 0x222a A alejnr.com
0.000186	10.13.13.3	DNS	Standard query 0x40a4 HTTPS alejnr.com
0.056796	10.13.13.99	DNS	Standard query response 0x40a4 HTTPS alejnr.com SOA pdns1.registrar-servers.com
0.056891	10.13.13.99	DNS	Standard query response 0x222a A alejnr.com A 162.213.255.36

0.056891	10.13.13.99	DNS	Standard query response 0x222a A alejnr.com A 162.213.255.36	
0.057391	162.213.255.36	TCP	51398 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM	
0.131948	10.13.13.99	TCP	443 → 51398 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1460	
0.132131	162.213.255.36	TCP	51398 → 443 [ACK] Seq=1 Ack=1 Win=64240 Len=0	
0.132458	162.213.255.36	TLSv1.3	Client Hello (SNI=alejnr.com)	
0.132556	10.13.13.99	TCP	443 → 51398 [ACK] Seq=1 Ack=518 Win=64240 Len=0	
0.221301	10.13.13.99	TLSv1.3	Server Hello, Change Cipher Spec, Application Data	
0.221306	10.13.13.99	TCP	443 → 51398 [ACK] Seq=1461 Ack=518 Win=64240 Len=1460 [TCP PDU reassembled in 13]	
0.221307	10.13.13.99	TCP	443 → 51398 [ACK] Seq=2921 Ack=518 Win=64240 Len=1460 [TCP PDU reassembled in 13]	
0.221308	10.13.13.99	TLSv1.3	Application Data, Application Data, Application Data	
0.221578	162.213.255.36	TCP	51398 → 443 [ACK] Seq=518 Ack=5120 Win=64240 Len=0	
0.222840	162.213.255.36	TLSv1.3	Change Cipher Spec, Application Data	
0.222948	10.13.13.99	TCP	443 → 51398 [ACK] Seq=5120 Ack=598 Win=64240 Len=0	
0.223132	162.213.255.36	TLSv1.3	Application Data	
0.223230	10.13.13.99	TCP	443 → 51398 [ACK] Seq=5120 Ack=696 Win=64240 Len=0	
0.223497	162.213.255.36	TLSv1.3	Application Data	
0.223579	10.13.13.99	TCP	443 → 51398 [ACK] Seq=5120 Ack=1172 Win=64240 Len=0	
0.298464	10.13.13.99	TLSv1.3	Application Data, Application Data	

Immediately after we resolve the host name of **alejnr.com**, we start a TCP/TLS connection with that

12.834801 162.213.255.36 TCP 51398 → 443 [FIN, ACK] Seq=1203 Ack=120492 Win=64240 Len=0

39.446064 176.124.198.213 HTTP GET /Fs8Py/eKTYt3dRbEXw HTTP/1.1

We stop talking to that malicious domain, and then shortly after the malicious HTTP GET request is done

Theory:

We reached out to this malicious domain [alejnr.com](#) and downloaded a malicious file which issued this HTTP request

What is in this malicious HTTP request?

39.446064	176.124.198.213	HTTP	GET /Fs8Py/eKTYt3dRbEXw HTTP/1.1	Request
41.067893	10.13.13.99	HTTP	HTTP/1.1 200 OK (image/gif)	Response

41.067893 10.13.13.99 HTTP HTTP/1.1 200 OK (image/gif)


> Transmission Control Protocol, Src Port: 80, Dst Port: 51399, Seq: 542069, Ack: 178, Len: 1195
> [415 Reassembled TCP Segments (543263 bytes): #260(1288), #261(1460), #262(1460), #263(1460), #264(1460)]
v Hypertext Transfer Protocol

> HTTP/1.1 200 OK\r\n
Date: Mon, 22 May 2023 17:01:04 GMT\r\n
Server: Apache/2.4.41 (Ubuntu)\r\n
Accept-Ranges: bytes\r\n
> Content-Length: 543048\r\n
Keep-Alive: timeout=5, max=100\r\n
Connection: Keep-Alive\r\n
Content-Type: image/gif\r\n
\r\n

Wireshark thinks this file is GIF

Wireshark notices that there is something weird going on...

> [Expert Info (Note/Malformed): HTTP body subdissector failed, trying heuristic subdissector]

 MONTANA
STATE UNIVERSITY

18

What is in this malicious HTTP request?

41.067893 10.13.13.99 HTTP HTTP/1.1 200 OK (image/gif)

Right click → Follow TCP Stream

GET /Fs8Py/eKTYt3dRbEXw HTTP/1.1
User-Agent: Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.22621.963
Host: 176.124.198.213
Connection: Keep-Alive

This is the “raw” contents of the GIF file
There is something very wrong here...

HTTP/1.1 200 OK
Date: Mon, 22 May 2023 17:01:04 GMT
Server: Apache/2.4.41 (Ubuntu)
Accept-Ranges: bytes
Content-Length: 543048
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: image/gif

MZ.....@..... .!..L.!This program cannot be run in DOS mode.
\$......u.S.....]U.....]a.....]`.....X.....]W.....]d.....]P.....]Q.....]V.....Rich.....PE..L.....P.....!..
.....k.....W.....@.....K.....\C.....f.....f.@).....
..@.....x.....text.....`rdata.....@..@.data..p.C..P.....B.....@.....rsrc..
D...f..P..N.....@..@.reloc..V...`k.....@..B.....
.....\...%8.....U..V...\.8...E..t
V.....^].....h...%8.....A.....U..V...h...8...E..t
V.....^].....U..VW..}.W...h...G..F.._..^].....t.P...f.Y...|...H... 3..H.;t..A..H..P...H..A..t...P..P.....U...3.....
..w8r...w13... ..w&r...w.P..h.f.....u..
W..M..u.....]...\$.4..h./...D\$.P.D\$.h...D\$.....{.....U.....f...W.N...t...\f..D...u
h.....U..P...f.....F.....t
P...f...W...~...f.....F..F Pj.S.U.....N.._].....U..j.h(...d....PQV..P..3.P.E.d.....u..E.....F...t
P...f.....M..F...|.....t..V..P..F..V...t..P...F...F..H..E..t
V..p.f.....M.d.
...Y^..].....U..j.h...d....P...SV..P..3.P.E.d.....t
.\f..D...u
h.....T...1..t.....9F.tC.V...u..A.Q.....U.W.E...f....t/..~..t).F..M.d.
...Y^[...].F..
..f..j..t.W.5....3..M.d.
...Y^[...].t...i...U..O...f.V.095|f.t.h..f..Rr.....u...f...5|f..M.i 0...f.....t.P..R...E....tC...f..295p.f.t.h..f..B`.....u...f...5p.f...P...f..

What is in this malicious HTTP request?

41.067893 10.13.13.99 HTTP HTTP/1.1 200 OK (image/gif)

Right click → Follow TCP Stream

```
GET /Fs8Py/eKTYt3dRbEXw HTTP/1.1
User-Agent: Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.22621.963
Host: 176.124.198.213
Connection: Keep-Alive

HTTP/1.1 200 OK
Date: Mon, 22 May 2023 17:01:04 GMT
Server: Apache/2.4.41 (Ubuntu)
Accept-Ranges: bytes
Content-Length: 543048
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: image/gif

MZ.....@.....
$.....u.S.....]U.....]a.....]`.....X.....]W.....]d.....]P.....]Q.....]V.....Rich.....PE..L.....P.....!..
.....k.....W.....@.....K.....\C.....f.....f.@).....
..@.....x.....text.....`..rdata.....@..@.data...p.C.P.....B.....@...rsrc...
D...f..P..N.....@..@.reloc..V...`k.....@..B.....
.....
.....\...%8.....U..V...\.8...E..t
V.....^].....h...%8.....A.....U..V...h...8...E..t
V.....^].....U..VW..}.W...h...G..F.._..^].....t.P...f.Y...|...H... 3..H.;t..A..H..P...H..A..t...P..P.....U...3.....
.w8r...w13... ..w&r...w.P..h.f.....u..
W..M..u...].$.4..h./...D$.P.D$.h...D$.....{.....U.....f...W.N...t...\f..D...u
h.....U..P...f...F.....t
P...f...W...~...f...F..F Pj.S.U.....N.._].....U..j.h(...d....PQV..P..3.P.E.d.....u..E.....F...t
P...f.....M..F...|.....t..V..P..F..V...t..P...F...F..H..E..t
V..p.f.....M.d.
...Y^..].U..j.h...d....P...SV..P..3.P.E.d.....t
.\f..D...u
h....T...1..t....9F.tC.V...u..A.Q.....U.W.E...f....t/..~..t).F..M.d.
...Y^[...].F..
..f..j..t.W.5....3..M.d.
...Y^[...].t...i...U..O...f.V.095|f.t.h..f..Rr.....u...f...5|f..M.i 0...f.....t.P..R...E....tC...f..295p.f.t.h..f..B`.....u...f...5p.f..P...f..
```

“This program cannot be run in DOS mode” is a very special string that appears in almost every Windows executable (.exe) or DLL file

It doesn’t make sense that this is part of a GIF file

What is in this malicious HTTP request?

41.067893 10.13.13.99 HTTP HTTP/1.1 200 OK (image/gif)

Right click → Follow TCP Stream

```
GET /Fs8Py/eKTYt3dRbEXw HTTP/1.1
User-Agent: Mozilla/5.0 (Windows NT; Windows NT 10.0; en-US) WindowsPowerShell/5.1.22621.963
Host: 176.124.198.213
Connection: Keep-Alive
```

Answer: this is actually a DLL
file pretending to be a GIF file

```
HTTP/1.1 200 OK
Date: Mon, 22 May 2023 17:01:04 GMT
Server: Apache/2.4.41 (Ubuntu)
Accept-Ranges: bytes
Content-Length: 543048
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: image/gif
```

```
MZ.....@.....
.....!..L.!This program cannot be run in DOS mode.
$......u.S.....]U.....]a.....]`.....X.....]W.....]d.....]P.....]Q.....]V.....Rich.....PE..L.....P.....!..
.....k.....W.....@.....K.....\C.....f.....f.@).....
..@.....x.....text.....`rdata.....@..@.data..p.C.P.....B.....@.....rsrc.....
D...f..P..N.....@..@.reloc..V...`k.....@..B.....
.....\...%8.....U..V...\.8...E..t
V.....^].....h...%8.....A.....U..V...h...8...E..t
V.....^].....U..VW..}.W...h...G..F.._..^].....t.P...f.Y...|...H... 3..H.;.t..A..H..P...H..A..t...P..P.....U...3.....
.w8r...w13... ..w&r...w.P..h.f.....u..
W..M..u.....]...$.4..h./...D$.P.D$.h...D$.....{.....U.....f...W.N...t...\f..D...u
h.....U..P...f...F.....t
P...f...W...~...f...F..F.Pj.S.U.....N.._].....U..j.h(...d....PQV..P..3.P.E.d.....u..E.....F...t
P...f.....M..F...|.....t..V..P..F..V...t..P...F...F..H..E..t
V..p.f.....M.d.
...Y^..].....U..j.h...d....P...SV..P..3.P.E.d.....t
.\f..D...u
h....T...1..t....9F.tC.V...u..A.Q.....u.W.E...f....t/..~..t).F..M.d.
...Y^[...].F..
..f..j..t.W.5....3..M.d.
...Y^[...].t...i...U..O...f.V.095|f.t.h..f..Rr.....u...f...5|f..M.i 0...f.....t.P..R...E....tC...f..295p.f.t.h..f..B`.....u...f...5p.f..P...f..
```

What is this malicious DLL file?

← → Untitled

from evidence.pcap

1 176.124.198.213

We can plug our malicious IP from the GET request into ZUI



06 PM

09 PM

Tue 23

6 Shapes — Filter or [fuse](#) to view results as one shape.

- > {event_type: alert (1), ts: 2023-05-22T17:01:05.168365Z, src_ip: 176.124.198.213, src_port: 80 (port=(uint16)), dest_ip: 10.13.13.99, dest_port: 51399 (port=(uint16))}
- > {event_type: alert (2), ts: 2023-05-22T17:01:05.168365Z, src_ip: 176.124.198.213, src_port: 80 (port=(uint16)), dest_ip: 10.13.13.99, dest_port: 51399 (port=(uint16))}
- > {event_type: alert (1), ts: 2023-05-22T17:01:04.833192Z, src_ip: 10.13.13.99, src_port: 51399 (port=(uint16)), dest_ip: 176.124.198.213, dest_port: 80 (port=(uint16))}
- > {event_type: alert (3), ts: 2023-05-22T17:01:04.833192Z, src_ip: 10.13.13.99, src_port: 51399 (port=(uint16)), dest_ip: 176.124.198.213, dest_port: 80 (port=(uint16))}
- > {_path: files, ts: 2023-05-22T17:01:04.831964Z, fuid: "FbJKHe3GIwuHlR1Ca", uid: "CpsUUb4BkfAPLSPCqj", id: {orig_h: 10.13.13.99, orig_p: 51399 (port=(uint16)) ...+2 }, s
- > {_path: http, ts: 2023-05-22T17:01:04.34159Z, uid: "CpsUUb4BkfAPLSPCqj", id: {orig_h: 10.13.13.99, orig_p: 51399 (port=(uint16)) ...+2 }, trans_depth: 1 (uint64), method
- > {_path: conn, ts: 2023-05-22T17:01:04.165966Z, uid: "CpsUUb4BkfAPLSPCqj", id: {orig_h: 10.13.13.99, orig_p: 51399 (port=(uint16)) ...+2 }, proto: "tcp" (zenum), service:

```
{
  event_type: alert (1),
  ts: 2023-05-22T17:01:05.168365Z,
  src_ip: 176.124.198.213,
  src_port: 80 (port=(uint16)),
  dest_ip: 10.13.13.99,
  dest_port: 51399 (port=(uint16)),
  vlan: null ([uint16]),
  proto: "TCP",
  app_proto: "http",
  alert: > {severity: 1 (uint16), signature: "ET POLICY PE EXE or DLL Windows file download HTTP", category: "Poten",
  flow_id: 1044800720635982 (uint64),
  pcap_cnt: 306 (uint64),
  tx_id: 0 (uint64),
  icmp_code: null,
  icmp_type: null,
  tunnel: null ({src_ip:ip,src_port:port=(uint16),dest_ip:ip,dest_port:port=(uint16),proto:string,depth:uint64}),
  community_id: "1:Y7hUFSibc6FFYTgqW3tuVPi5vpY="
}
```

ZUI actually determined something malicious was possibly going on from our PCAP file

We can expand the “files” info to see information about this file that was downloaded

What is this malicious DLL file?

```
_path: files,
ts: 2023-05-22T17:01:04.831964Z,
fuid: "FbJKHe3GIwuHlR1Ca",
uid: "CpsUUb4BkfAPLSPCqj",
id: > {orig_h: 10.13.13.99, orig_p: 51399 (port=(uint16)), resp_h: 176.124.198.213, resp_p: 80 (port=(uint16))},
source: "HTTP",
depth: 0 (uint64),
analyzers: > |["PE", "MD5", "SHA1"]|,
mime_type: "application/x-dosexec",
filename: null,
duration: 1.131455s,
local_orig: false,
is_orig: false,
seen_bytes: 543048 (uint64),
total_bytes: 543048 (uint64),
missing_bytes: 0 (uint64),
overflow_bytes: 0 (uint64),
timeout: false,
parent_fuid: null,
md5: "684f5e808312f7d7bcc7f4405ea706ad",
sha1: "6f2401d618fd2463461c5346ff64216c334842f8",
sha256: null,
extracted: null,
```

ZUI will compute the file hash for us !

By plugging it into VirusTotal, we can see that this DLL file-pretending-to-be-a-gif is a known malicious file!

56 / 73
Community Score

56/73 security vendors flagged this file as malicious

ff99eaa3851bee30db140846f083a5f8064eaad2707ab5a6d8a0b6d4dd9b8c61
A3DUtils.dll
Size: 530.32 KB | Last Analysis Date: 1 month ago

pedll overlay

DETECTION DETAILS RELATIONS BEHAVIOR COMMUNITY 3

Join our Community and enjoy additional community insights and crowdsourced detections, plus an API key to automate checks.


Popular threat label: trojan.pikabot/lazy | Threat categories: trojan, banker | Family labels: pikabot, lazy, qakbot

The name of this malware is "PIKABOT"


VT seemed to redirect to the SHA256 hash value

What is this malicious DLL file?

This domain had been flagged as malicious in the past




VirusTotal also provides context as to why it was flagged as malicious



We saw “PIKABOT” earlier when we were investigating **alejnr.com**

The name of this malware is “PIKABOT”



VT seemed to redirect to the SHA256 hash value

What happens after the malware was downloaded?


Let's see if we can find evidence of **command and control** from this cyber attack

We can start plugging in IP addresses into VirusTotal to see if we get a hit

No.	Time	Destination	Protocol	Info
1645	401.318608	129.213.54.49	TCP	51422 → 2078 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
1646	401.388236	10.13.13.99	TCP	2078 → 51422 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1460
1647	401.388558	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=1 Ack=1 Win=65535 Len=0
1648	401.389095	129.213.54.49	TLSv1.2	Client Hello
1649	401.389336	10.13.13.99	TCP	2078 → 51422 [ACK] Seq=1 Ack=148 Win=64240 Len=0
1650	401.588331	10.13.13.99	TLSv1.2	Server Hello
1651	401.588472	10.13.13.99	TLSv1.2	Certificate, Server Key Exchange, Server Hello Done
1652	401.588675	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=148 Ack=1377 Win=65535 Len=0
1653	401.588774	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=148 Ack=2170 Win=65535 Len=0
1654	401.596481	129.213.54.49	TLSv1.2	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message

What happens after the malware was downloaded?

Let's see if we can find evidence of **command and control** from this cyber attack



We discover that 129.213.54.49 is the IP address for the PIKABOT C2 server

What happens after the malware was downloaded?

Let's see if we can find evidence of **command and control** from this cyber attack

```
✓ {  
  _path: notice,  
  ts: 2023-05-22T23:47:01.833695Z,  
  uid: "Cb45fX1d1qHMAfZA58",  
  id: > {orig_h: 10.13.13.99, orig_p: 51976 (port=(uint16)), resp_h: 129.213.54.49, resp_p: 2078 (port=(uint16))},  
  fuid: "FuX96l2lqECdlDLRZi",  
  file_mime_type: null,  
  file_desc: null,  
  proto: "tcp" (zenum),  
  note: "SSL::Invalid_Server_Cert" (zenum),  
  msg: "SSL certificate validation failed with (self signed certificate)",  
  sub: "CN=nonveracitygalvanometry.band,L=Wrinkles Fireless,OU=Prediet,O=Awarrant,ST=EN,C=MX",  
  src: 10.13.13.99,  
  dst: 129.213.54.49,  
  p: 2078 (port=(uint16)),  
  n: null,  
  peer_descr: null,  
  actions: > [{"Notice::ACTION_LOG" (zenum), "Notice::ACTION_ADD_GEODATA" (zenum)}],  
  email_dest: > []
```

ZUI also generated a notice that this could possibly be a C2 server

What damage was done?


A good amount of Data was exchanged with the C2 server

ip.dst == 129.213.54.49				
No.	Time	Destination	Protocol	Info
1645	401.318608	129.213.54.49	TCP	51422 → 2078 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
1647	401.388558	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=1 Ack=1 Win=65535 Len=0
1648	401.389095	129.213.54.49	TLSv1.2	Client Hello
1652	401.588675	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=148 Ack=1377 Win=65535 Len=0
1653	401.588774	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=148 Ack=2170 Win=65535 Len=0
1654	401.596481	129.213.54.49	TLSv1.2	Client Key Exchange, Change Cipher Spec, Encrypted Handshake Message
1657	401.670964	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=241 Ack=2412 Win=65535 Len=0
1658	401.671833	129.213.54.49	TLSv1.2	Application Data
1664	402.332268	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=923 Ack=7376 Win=65535 Len=0
1699	477.289340	129.213.54.49	TCP	51422 → 2078 [ACK] Seq=923 Ack=7408 Win=65535 Len=0
1931	509.527676	129.213.54.49	TCP	51422 → 2078 [FIN, ACK] Seq=923 Ack=7408 Win=65535 Len=0
1932	509.527858	129.213.54.49	TCP	51422 → 2078 [RST, ACK] Seq=924 Ack=7408 Win=0 Len=0
1934	509.528071	129.213.54.49	TCP	51422 → 2078 [RST] Seq=924 Win=0 Len=0
1945	581.408795	129.213.54.49	TCP	51426 → 2078 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
1947	581.480214	129.213.54.49	TCP	51426 → 2078 [ACK] Seq=1 Ack=1 Win=65535 Len=0
1948	581.480704	129.213.54.49	TLSv1.2	Client Hello
1951	581.545081	129.213.54.49	TCP	51426 → 2078 [ACK] Seq=324 Ack=110 Win=65535 Len=0
1952	581.545773	129.213.54.49	TLSv1.2	Change Cipher Spec, Encrypted Handshake Message
1954	581.548096	129.213.54.49	TLSv1.2	Application Data


Since this all HTTPS encrypted traffic, we cannot see the content of these messages

However, this is evidence that it is possible that data may have been exfiltrated

Timeline



Timeline



How did this attack begin?


Finding Root cause

PIKABOT is a well-documented malware. We can do a little bit of investigation ourselves to figure out what happened

Distribution Methods

PikaBot, along with various other malicious loaders like QBot and DarkGate, heavily depends on email spam campaigns for distribution. Its initial access strategies are intricately crafted, utilizing geographically targeted spam emails tailored for specific countries. These emails frequently include links to external **Server Message Block (SMB)** shares hosting malicious zip files.

SMB shares refer to resources or folders on a server or computer accessible to other devices or users on a network using the SMB protocol. The threat actors frequently exploit such shares for malware distribution. In this instance, the act of downloading and opening the provided zip file leads to PikaBot infection.



How does Pikabot malware work?

Many Pikabot infections start with a malicious email, particularly using email thread hijacking; however, other cases have been distributed via malspam and malvertising [5]. Once downloaded, Pikabot runs anti-analysis techniques and checks the system's language, self-terminating if the language matches that of a Commonwealth of Independent States (CIS) country, such as Russian or Ukrainian. It will then gather key information to send to a command-and-control (C2) server, at which point additional payload downloads may be observed [2]. Early response to a Pikabot infection is important for organizations to prevent escalation to a significant compromise such as ransomware.

Full IOC: <https://github.com/pan-unit42/tweets/blob/master/2023-05-22-IOCs-for-Pikabot-infection-with-Cobalt-Strike.txt>

Timeline

