

THIS REPRESENTS THE PRODUCT ASSY FOR THE 1450XLD

ENGINEERING RELEASED

PART NO.

CA061812-001 DOMESTIC 1450XLD DESC

	1450XLD	DRAWN BY	DATE				E. Plur		Drive		
NEXT ASSY USED ON		CHECKED		A	ATARI*		San Jose, CA 95134 WA Warner Communications Company				
CONFIDENTIAL: Reproductive written permission of Atari is drawing is only conditionally possession thereof confers or tues, the subject matter of the discounties.	RECEIVING THIS DRAWING on Forbidden without the specific nc., Sunnyvale, California. This issued, and neither receipt not ransfers any right in, or license to trawing or any design or technical	ENGINEER APPROVED		TITLE	(PRODUC		-	50XL	D))	
drawing or any part thereof, e for Atari Incorporated and for tion's written license, no righ	nor any right to reproduce this scept for manufacture by vendors manufacture under the corpora- it to reproduce this drawing is	APPROVED	- "	SIZE	DRAWING N	NO. 812-XX	Х			REV 3	
granted or the subject matter ment with or written permissi	thereof unless by written agree- on from the corporation.			SCALE	:		SHEET	1	OF	8	

PAGE 2

1450 PRODUCT

Rev. 3

	 	1	1	'		ST	atus	
į		i	i		RELEASE			LEASED
		i	REFERENCE				EXP. RELE.	
ITEM	PART NO.	DESCRIPTION	DESIGNATION	QTY I	. DATE	REV #	-	<u> RESPONSTBLE</u>
	1 00/2/25	I A CHANG DECETATION AND A SEA	1 000					1
_	1 0060629	OPPS RESISTOR AXIAL LEAD	R22					1
I	•		R264,265	121			l	1
	14-51R0		R241,249	2	1		l I	l i
	14-5100		1 R92		į		 -	i .
	14-5270	•	R24	1 4 1			l	1
	14-5330			10			!	1
X	! 14-5560		•	2 3	1	! !)]	1
	14-5750	•	R133,134,137		1	 		1
	14-5101	•		18		 	i ·	1
!	1	I TAN CHEM MEDIDION IN ON	266-278,223,		i	· •		1
•	; [ŀ	227	1		,		ì
,	1 4- 5151	150 OHMS RESISTOR 1/4N 5%	R214,218,222	i 4 i			ļ	i
	1		229					i
I		150 OHMS RESISTOR 2N 5%	R180	1 1				
	14-5181	1 180 OHMS RESISTOR 1/4N 5%	R145,208	2			1	1
	14-5201	200 OHMS RESISTOR 1/4N 5%	R111	1 1	1	,	l	I
	14-5221	1 220 OHMS RESISTOR 1/4W 5%	R28,211	2	i		}	1
X		237 OHMS RESISTOR 1/4H 5%	R259,261	2	!		1	l
	14-5241	240 OHMS RESISTOR 1/4N 5%	R142	1	ļ		1	1
	1 4- 5271	278 OHMS RESISTOR 1/4W 5%	R178	1 1	ļ		}	1
X	1	270 OHMS RESISTOR 1/2H 5%	R207	1	1			1
	14-5361	•	R191,242,249	3	!			1
	14-5391	•	R132,175	2	!	i		I
×		•	R238,252	2				1
	1 4 –5 4 31	=	•				l	1
	1 4-54 71	· ·	R46,60,61,115					1
	ļ	!	157,158,237,			· ·	l	1
	!		239,247,253					1
I	•	1 600 OHMS RESISTOR 1/4W 5%	R86	1			İ	1
X	•	1 715 OHMS RESISTOR 1/8N 5%	R260					l .
	i 1 1 -5751		R128,205,129,	7 1	Ī		i	1
•	ł ,	•	206 R184		i			1
X	! ! 1 1- 5102	•	R77,78,110,		ì			l l
	1 17-3102 1	•	114,118,120-	•	1	, I		l
	! 	· ·	123,139,146,					ì
			147,153,156,		·			Ì
1	, 1	·	164,165		Ì	ļ		i
	ENCIN	·	R167-170,172-	i	Í			Ì
	FIACHIA	ENING RELEAGED	174,177,181			ĺ		İ
	I	•	190,192,195,		1	1		l
Ų	<u> </u>	· ·	196,199,202,		ĺ	1		1
	i	i	209,212,231		1	1		1
ĺ	Ì	1	R240,251,263	1	l		l	I
X.		1 1.5K OHHS RESISTOR 1/4W 5%	R26,201	2	į			1
	14-5162	•	•	1 1	i			1
ļ	14-5182	•	• • •	6	į			I
	1	•	171		İ			
ĺ	1 4- 5202	•	•	2	ļ	:		1
I	•	•	•	1				1
1	14-5222		R6,100,148,	8		1		1
1	1	1	154,185,186		1	1		I

!	1		1	1			atus	
	1	1	1	1	RELEA	SED		RELEASED
	1	1	REFERENCE	1 1		1	EXP. RELE	E•
ITEM_	PART NO.	<u> </u>	<u> DESIGNATION</u>	laty 1	DATE	REV #	<u> </u> DATE	<u> RESPONSTBLE</u>
			1]	!	!
	14-5272	1 2.7K OHMS RESISTOR 1/4W 5%	R47,95	121		1	!	ļ
	14-5302	J 3K OHMS RESISTOR 1/4H 5%	R7-9,18-21,30			ļ	!	1
	1	!	1 -31,41-45,67,			1	ļ	1
	1	1	1 79-82,84,87,				<u> </u>	ļ.
	ĺ	1	1 112,113,119			1	 	1
			1 136,138	1		1	!	i .
			1 R159,224,226,			1	!	i
			1 279			I	[İ
	14-5332	1 3.3K OHMS RESISTOR 1/4W 5%		13		!	! ·	
	14-5392	3.9K OHMS RESISTOR 1/4W 5%		13		1	<u> </u>	1
	1 1-51 72	1 4.7K OHMS RESISTOR 1/4N 5%	1 R4,32,33,35-			ļ		1
	!	!	1 40,49,50,56-			!		İ
į		!	59,62,128,141			!	}	ļ
		!	1 163,179,189	1 1			l	l l
	l	!	1 193,196	1 1	***	!]	
		!	R198,216,217				!	1
			220,221,243					į
_!			R244,250,258				<u> </u> -	į
X	•	4.75KOHMS RESISTOR 1/8H 1%	R280,281	12			!	į.
	14-5562	5.6K OHMS RESISTOR 1/4W 5%	R85	11 1		1	1	1
	14-5622	1 6.2K OHMS RESISTOR 1/4W 5%	R104,149	12		,] 	1
	14-5682	6.8K OHMS RESISTOR 1/4H 5%		12		1	1	ł
X.		8.25KOHHS RESISTOR 1/8H 1%	R194,197,200,	19 1		1	 	1
	44 5040	1 O ALL OUNCE DECENTATION A JAM EST	203,282	1 1		1	} !	1
	14-5912	1 9.1K OHMS RESISTOR 1/4N 5%	R127	1 1		1	<u> </u>	l I
	14-5103	1 10K OHMS RESISTOR 1/4N 5%	R2,18-17,34,			1	 	1
1			65,80,93,117,			1	l !	1
		1	1 140,161,176,	1 1		1	l 1	1
_		1 40 0V0WC DECTETOD 4 /01 EV	1 192,228,234	1 1		1 1	i	1
X	•	1 13.3KOHHS RESISTOR 1/8H 5%	R232	1 2		1 1	! 1	1
	14-5153	1 15.0KOHMS RESISTOR 1/8W 5%	R116,283			1 1	i I	i I
-	14-5183	1 18K OHMS RESISTOR 1/4H 5%	•	11		1 1	! !	l I
1	14-5203	20K OHMS RESISTOR 1/4N 5%	R108,210,215,			1 1	[1
	14 5222	1 22V DUNC OCCUCTOD 4 /AU EV	1 219,235,255			1 1	l I	1
	14-5223	22K OHMS RESISTOR 1/4W 5%	[R183,188,213	: - :		1 1	} 1	1
	14-5273	27K OHMS RESISTOR 1/4W 5%	R151,152	121		1]	1
X	•	28.7KOHMS RESISTOR 1/8H 1%	R233	1 1 1		1 1	l I	1
	14-5333	33K OHMS RESISTOR 1/4N 5%	R99	1 4 1		1 1	l 1	1
	14-5363	36K OHMS RESISTOR 1/4N 5% 39K OHMS RESISTOR 1/4N 5%	R123 R94	1 4 1		1	! !	1
-	14-5393	47K OHMS RESISTOR 1/4H 5%	K77 R187	; 4 1 ; 4 1		1 1	I I	1
	14-5473	-	•	111		1 1		1
	14-5563	56K OHMS RESISTOR 1/4N 5%	R1,3,48,64,96 101,102,160,			: :	! 	i i
i	1	1	161,102,100, 162	1 1		1 1	: 1	1
 	1 4- 5753	75K OHMS RESISTOR 1/4H 5%	1 R124	1 1		1 1 1		i
-	14-5124	1 120K OHHS RESISTOR 1/4H 5%	R183	. • 1 [1 1		i		i
X X		1 150K OHHS RESISTOR 1/4W 5%	R246,256	121		1 1	, 	i
X X		1 160K OHMS RESISTOR 1/4W 5%	R105,106	121		1		i
	14-5224	220K OHMS RESISTOR 1/4H 5%	R23	1		1		i
X X		250K OHMS RESISTOR 1/4H 5%	R284	1 1		, ,	•	i
l	1 4- 51 05	1 IN OHNS RESISTOR 1/4H 5Z	R236,245,254,	 4				i
1	 11-91 09	I III OLEM INTOTATION TO ME OF	257	1 1			1	i
l l	!		23/ R91				1	I .

		1	<u> </u>	1 1		STA	ATUS	
1		l	ĺ	ĺ	RELEAS	E D	NOT R	ELEASED
			REFERENCE	1 1		•	EXP. RELE.	•
ITEM	PART NO.	<u>DESCRIPTION</u>	DESIGNATION	<u>loty</u>	DATE	REV #	DATE	RESPONSIBLE
X		I CAP 12-70PF VARIABLE	 C135	1 11				i i
	C014179-01		C109,131	121		! ! 		1
	CO14179-02			1 2 1	· -			i
		•	C144	1 1				İ
ا ک		•	C177,190	2		İ		1
0 1	C014179-19	CAP 150 PF 20%	C116,123,125	3		l l		1
			C118	1	,			1
81+10			C19,102	2	!			1
*/			C156	1				
0 x			C148	1				!
J 1				2				1
X	C014180-17			11		i i		1
	CU17101-1/	•	C9,10,12,22-		ı			1
	!		42,44-60,122,					1
i	· :		215	I I		!		i
x,				2		İ		i
x			C94	1 1		i		İ
X į	!	CAP .0033UF	C101	1 1	!			İ
?	CO14181-02	CAP .01 UF DECOUPLING	C26,34,43,121	24	1			1
l			128,130,137			l		l
			141,146,149,			1		1
			152-154, <u>158-</u>					i
] 1			<u>165</u> ,168,171 172	[1	. [1
ı Xi			C93	1 1		1		1
-,		•		2	1	1		i
i			C179,183,194,		İ	i		İ
ĺ			198			1		1
1	CO17803-01	CAP +022 UF		1	!	l		i
ŀ				2				1
x l				2		ł		1
ŀ	CO14180-09			4	ļ	1		1
i	CO14181-03	·	C2-8,11,13-18 20,21,25,28,		į	! !		1
 			31,32,62-92,		ì	1 		1
l Į	; •		98,99,111-115		1	, , 		·
i			117,119,126,		1	i		İ
i	Ī		127,132,134,		1	ı		
1	1	 	138,139,174,					l
1	{	•	187,201,201,		!	1		1
ļ	!		205,208,209,					1
1			211,212,216,					1
1	C01700E	•	217		1	. !		1
1			C169,170 C181,185,192,	2		 i		1
1	OT 1100, 10	·	196	, , , , ,		1 [i
,	CO14181-05	· · · · · · · · · · · · · · · · · · ·		2		, , , , , , , , , , , , , , , , , , ,		i
i			C96,97,105,		•	i		İ
i	i	·	145,147,150,		!	1		I
ŀ	!	•	151		l	1		I
X l				1		ļ		Į.
X	-	CAP -82 UF	C187	1 1		•		!

PROJECT: 1251 DATE : 4-26-83

		1	1	\perp		ST	ATUS		
1		ĺ	ł	\mathbf{i}	RELEA	SED	NOT	RELEASED	
	l	1	REFERENCE	1 1		1	EXP. RELE	E.	
ITEN	PART NO.	1 DESCRIPTION	DESIGNATION	IQTY I	DATE	REV #		RESPONSIBL	
ا		1		1 1	<u>-</u> .	1		ı	
	C016569	CAP 1 UF 20%	C178,193	12		1	1	1	
I		CAP 2.2 UF 20%	C184,191	121		1	1	1	
I		1 CAP 3.9 UF	1 C124	111		1		ŀ	
X		CAP 4.7 UF NON POLARIZED	C103,104,106	13		1		i	
X		CAP 4.7 UF 20%	C173,186	12 1		1		1	
? x		CAP 4.7 UF 20% 16V	1 C218	11		1		1	
-	C014371	CAP 10 UF 10V	C29,120,133,	15 1		1		1	
A		1	199,214	1 1		1		1	
	C014393	CAP 22 UF	C61	1				I	
	CO15505	CAP 47 UF 20% 16V	C1,175,176,			1		I	
Į		1	1 188,189,200,	1 1		1		1	
1		1	213	1 1		1		- 1	
1	CO14378	CAP 470 UF	C206	11	~	1		1	
X		CAP 6800 UF 20% 35V	C203,204,210	13 1		1	Ì	1	
Į	CO61848	CRYSTAL 1.8432 NHZ	1 Y2	1		1		ļ	
1	CO16090	I CRYSTAL 3.58 NHZ	Y1	1		1		1	
	CO17536	CRYSTAL 4.433618 NHZ	Y3	11		1		ł	
X		I CRYSTAL 8 MHZ	Y4	111				1	
X.) DIODE 1N4446	CR1,6,7,8,10	- 33		1		1	
j		1	32,35,36,38-			1		1	
į		İ	1 41	1 1		İ		ĺ	
i	31-1 N4 001	DIODE 1N4001	CR4,5,9,48-5	2181		i		ĺ	
x	CO61845	DIODE 1N4733A	CR2,3	121		i		i	
x		DIODE ZENER 3.3 5% 1N5226B	CR33	111		İ		i	
×		DIODE ZENER 4.7 5% 1N5230B	CR34	iii		i i		į	
×		DIODE ZENER 6.2 5% 1N5234B	CR37	11 1		i		İ	
X		I DIODE HR750 (HOTOROLA)	CR42-45	141		i		1	
i	C014398	I DIODE NR501 (NOTOROLA)	CR46,47	12 1				1	
i	33-2N3906	TRANSISTOR 2N3906	01,2	i 2 i		i i		i	
i	CO14809	TRANSISTOR NPSA55	03	i 1 i		i		İ	
X	C016000	TRANSISTOR MPSA13	Q4	i 1 i		i		i	
i	34-2N3904	TRANSISTOR 2N3904	Q5-9	15 i		i		1	
X		TRANSISTOR 2N4124	Q10,18,19,21			i i		i	
i		1	1 23	i i		i		i ·	
X		TRANSISTOR 2N4403	Q11	11 i		i		1	
×		TRANSISTOR 2N2907A	į Q13	111		i i		i	
X,		TRANSISTOR TIP 111	020,22	121		1		1	
	C061847	OPTO ISOLATOR 4N25		? i 1		i i		1	
	19 -1 11504	POT 500K	į VR1	i 1 i		i		i	
X.		POT 25K	VR2,3	12 1		i		i	
X		I POT 2K	VR4,5	12 1		i		i	
X.		I TEST PTS	TP1-18	18		i		i	
	C014384	FERRITE BEADS	L1-4,6-8	7		j i		i	
-	C011301	INDUCTOR 1.5 UH	L5	11 1		1		i	
	00127 17	INDUCTOR 3.3 UH	L14,15	12 1		1	ı. 	i	
X		INDUCTOR 109 UH 10%	L9,10	12 1		1		i	
X [I INDUCTOR 270 UH	L13					i	
~ [I INDUCTOR 390 UH	L11,12	12 1		. !			

4

-		1		1.	1 1	<u>STATUS</u>				
		1		1	1	RELEASED		I NOT RELEASED		
		1		REFERENCE	1		1	EXP. RELE.	•	
ITEM J	PART NO.	<u> </u>	DESCRIPTION	DESIGNATION	TOTY !	DATE	REV #	DATE	<u> RESPONSTBLE</u>	
	004.8007	TO (EASY	7501	1			[1	
İ	C014806	IC 6502H	CPU	ļ	11]	1	i	
	C012296	IC	ANTIC	1	1 1		1		!	
	C014805	IIC	CTIA	!	111			l	1	
	C012294	I IC	POKEY		111		!	l	1	
-	C014795	I IC	PIA		11 1		l		!	
	CO61720	I IC SCO1	VOTRAX (SPEECH PROCESSOR)	I U4	11 1				1	
	CO61687	IC 74LS273		i	121		1	l	1	
X	<u>C061923</u>		F/F	1	11			i	1	
ļ	C014313	-	BUFFER TRISTATE		13 1		1	ł	1	
	C014345	IC 74LS158	MUX		12		1	1	1	
	C060612	IC 4164	RAM	1	181			1	l	
T T	C060615	IC 2764	EPROH (16K×8)	1	121			l		
X	C061924	IC 27128	EPROM (16K × 8)	1	11		i 1		1	
?x	C060609	IC	PAL	1	111				1	
Į	C014344	IC 74LS138	MUX		13 1		1		1	
	C060613	IC 74LS375		1	11		1	ł	1	
1	CO60472	I IC DOL	DIGITAL DELAY LINE	1	111		1	Į	ì	
	CO60474	I IC 74LS51	AND OR INVT	İ	11 1		1		1	
X	CD61698	IC 6551	SERIAL COMM ASUNC	i	iı i		1	1	i	
-	C061692	IC 74HC492		I U34	11 1		i i		1	
	CD61691	•	MULTIPLEXER	i	11 1		İ	1	Ì	
	C061925	-	F/F	i	1 1		i	}	İ	
	C061481	-	NAND 8IN	i	i i i		i i		i	
	CO61689	IC 74LS245		1	12 1		[i	
	CO61926	IC 74LS133		1	11 1		1		i	
<u>-</u> 1	CO19816	•	BUFFER	1	11 1			1	1	
X		IC LH555	TIMER	1	11.1		1 1	,	i	
-	CD17099	•	COUNTER SYNC	i I	111		; 1 :	ļ	1	
	C01/077	IC 74LS74		1	12 1		! !	ļ	1	
		•	MIROPROCESSOR (INTEL)	1	1 3 1		1 1 1 1		1	
	C061928	I IC 8050H		1			l ;	<u> </u>	1	
	C061921		DISK CONTROLLER	i	11		} . 1	<u> </u>	i .	
	C061929	I IC 74LS374		1	12 1		!		1	
	CD61930	I IC 74LS221			1 1		! !		1	
	CD10174	•	TRNSSISTOR ARRAY	1	111		! !		1	
I		•	TRANSISTOR ARRAY	1	11 1				1	
-	CO17951	•	OP AMP	1	111		. !	·	!	
X.		-	OP AMP	ļ					!	
	CO14332	-	VOLTAGE REGULATOR	1	111		!		!	
	<u>CD61931</u>	IC 75478		?	14		!		<u>!</u>	
	C061932	IC 74LS123		1	2				1	
	C017244	IC 74LS157		1	1				1	
١	C017101	•	FREQ/VOLTAGE CONV	İ	121				Į.	
X			VOLTAGE REG	1	13		1		1	
X		IC LM320-5	VOLTAGE REG	1	1		!		1	
1	CD15950	IC LX339	COMPARATOR	I	1			!	ł	
1	C017 097	-	AND 2IN QUAD	1	2				1	
X	CD61933	IC 74LS11	AND 3IN	i	111			ļ	1	
į	CO17096	IC 74LS04	HEX INV	1	4				1	
i	C016540	•	NAND ZIN QUAD	I	1 . [l Ì		I	
	0061719	-	DUAL PERIPHERAL DRIVER	1	111		1 1		1	
i	CD61934	•	OR 210 QUAD	İ	i 1 i		İ		ŀ	
i	C014362	IC 74LS32		İ	i 1 i				ı	
				•					-	

		1	1			ST	ATUS	
ĺ	1	1	j	i î	RELEASE			LEASED
1]	1	REFERENCE	i ī			EXP, RELE,	
ITEM	PART NO.	DESCRIPTION	DESIGNATION	IQTY	DATE	REV #	DATE	<u> IRESPONSTBLE</u>
1		1		1				1
ĺ	CO14320	I IC LM324 OP AMP QUAD	1	11	1	!		1
X.	C061935	I IC 7486 HEX INVRT BUFFER	1	121	l	1	}	1
1	C014341	IC 74LS80 NAND 2IN	i	12	1	-		I
- 1		I IC 74LS86 EX OR QUAD	İ	11	1			
X)		I IC 74LS38 NAND 2IN BUFFER	l	11	ļ			1
1	C014340	IC 74LS02 NOR 2IN	1	11	1	-		l
		UDN5713H	1	1	I			1
X		I UH1651 RF HODULATOR	1	11	1			ł
X	C061844	TRANSFORMER AUDIO	i	11	1	1		1
T		I RELAY PC HOUNT DIP	1	11	I	!		1
		KEYBOARD	1	11	1	i		1
	C014715	POHER JACK	J12	11	1			1
-	C014386-09	SOCKET 41 PIN	1	17	1			1
		SOCKET 28 PIN	1	14 1	l	(•
1		SOCKET 22 PION	i	1	~	ļ		1
ı	CO14386-03	SOCKET 16 PIN	1	18 1	I			1
X į		HEADER 17 PIN	1	1	l			1
X.		HEADER 10 PIN	J13,14	1. 1	1	İ		1
X		HEADER 6 PION	J18,24	1 1	ļ	ĺ		1
X		I HEADER 4 PIN	J15-17,19,21-	1	ļ	ļ		i.
ł			1 23,25,28,29	1 1	1			ļ
X		HEADER 2 PIN	J20,26,27	1 1	ļ			1
ļ	C060410	CARTRIDGE RT. CONN.	1	1 1	ļ			
I	C019448	PADDLE CONN.	1 5,6	12	į			1
Į.	C014725	SIO CONN.	J1	111	1			1
	C014388	MONITOR CONN.	1 J2					1
l		KEYBOARD CONN.) J8	11	1			1
ļ	C012241	Sattch Channel	SMZ	111	!	ļ		1
1	CO61022	I SHITCH POHER	i shi	11	l.			1
XX		I PCB MODEL 1250	į.	1 1	1	ļ		1
XX		HEAT SONK	1	13 1	1			1
XX		SHIELD FCC UPPER	Į.	1	!			1
XX		SHIELD FCC LOWER	1	111	1			1
XX		POMER ADAPTER	!		ļ			l
XX		DOS DISKETTE	i	1 1	l			t .
XX		ENVELOPE DISKETTE	1	111	Į.			1
XX		LED	1	13 1	l l	ļ		1
XX		TH50-2	1		1	1		1
XX		CABLE KEYBOARD	l I	1 4 1	1			1 1
IX		FAN DC BRUSHLESS	1	1 4 1	1	ļ		1
XX)		SHEET METAL DRIVE MOUNTING	1	1 4 1	!	1		I 1
IX		BEZEL FRONT	1	1 4 1	ŧ	i 1		; 1
XX		BEZEL KEY BOARD	1	11 1	1	1		1 1
XX		HARDHARE	I	1 4 1	1	•		I
XX)		INDICATOR STRIP	1	11 1	ı			ŧ
XX		MASHER, INSULATOR	1	2	, 1	,		[
XX		DUAL SHIPPER	i		i	i		
-~!		x NEW XX TAND	I MAIDADT	1	•			•

PAGE

8

			1.	1 1	STATUS				
1		1	1	\mathbf{I}	RELEA	ASED .	NOT RE	1 FASED	
1		1	REFERENCE	$\mathbf{I} = \overline{\mathbf{I}}$			EXP. RELE.	1	
ITEM	PART NO.	<u> </u> DESCRIPTION	1 DESIGNATION	IQTY	DATE	REV #	DATE	RESPONSIBLE	
ı		t	1	1 1		1	1	1	
XX		Logo-Name Plate	1	11		1	1	1	
XX		GRAPHIC BOX	1	111		1	1	1	
XX]		Operators Hanual	1	11		l	ì	1	
II		I HARRANTY CARD	1	111		l	l	1	
XX.		DOS MANUAL		11		l	1	1	
XX		LABEL SERIAL FCC	İ	111		1	1	1	
XX		STYROFOAM UPPER		111		1	ł	1	
XX		I STYROFOAM LOHER	İ	11		1	1	1	
XX;		I POLY BAG	Ì	111		ĺ	1	l	
XX		COVER TOP PLASTIC		11 i		Ì	1	1	
XXI		COVER BOTTOM PLASTIC	I	11 1		i	i	i	
XX		I PCB ASSY	i	iii		i	ì	i	

** TANDON PART