

SabbPe

Payment Gateway

Merchant Integration Guide

Prepared for Indumentis Trading OPC Pvt. Ltd.

Prepared for

Indumentis Trading OPC Pvt. Ltd.

<https://www.indumentis.co.in>

Issued by

One78 SabbPe Technology Solutions

<https://www.sabbpe.com>

Overview

This document provides everything Indumentis needs to integrate SabbPe Payment Gateway into their platform. The integration involves two API calls — a token generation step followed by payment initiation.

Production Base URL

```
https://pymnts.sabbpe.com
```

How It Works

1. Your backend calls `/sabbpe/v1/token` with your credentials → receives a `sabbpe_token`
2. Your backend calls `/sabbpe/v1/initiate` with the token + order details → receives a `payment_url`
3. Your frontend redirects the customer to the `payment_url` — they complete payment on the hosted checkout page
4. After payment, the customer is redirected back to your website with a status parameter

Your Credentials

Use the following credentials in your API calls. Keep these server-side only — never expose them in frontend code or browser network requests.

Step 1 — Token Generation Credentials	
sabbpe_userid	665890
sabbpe_merchantid	998779
sabbpe_password	Test@123456
Step 2 — Payment Initiation	
frontend_url	https://www.indumentti.co.in
customer.email	rakesh@gmail.com
customer.phone	9958750014
Callback Configuration	
callback_url	https://www.indumentti.co.in/api/payment/sabbpe/callback

 **Note:** sabbpe_password and all credentials above must only be used in server-side code. Never include them in JavaScript running in the browser.

API 1 — Generate Token

POST /sabbpe/v1/token

Generate a one-time authentication token before initiating a payment. Valid for 10 minutes, single-use.

Request Fields

Field	Type	Required	Description
sabbpe_userid	String	Required	Your merchant user ID — use "665890"

<code>sabbpe_merchantid</code>	String	Required	Your merchant ID — use "998779"
<code>sabbpe_password</code>	String	Required	Your merchant password — use "Test@123456"
<code>timestamp</code>	String	Required	Current server time in format: yyyy-MM-dd HH:mm:ss. Must be within ± 5 minutes of SabbPe server time. Always generate server-side.
<code>merchant_order_ref</code>	String	Required	Your unique order ID for this transaction. Max 128 characters. Must be unique per order — never reuse.

Sample Request

```
curl -X POST https://pymnts.sabbpe.com/sabbpe/v1/token \ -H "Content-Type: application/json" \ -d "{ \"sabbpe_userid\": \"665890\", \"sabbpe_password\": \"Test@123456\", \"sabbpe_merchantid\": \"998779\", \"timestamp\": \"$(date '+%Y-%m-%d %H:%M:%S')\", \"merchant_order_ref\": \"INDUMENTI-ORD-001\" }"
```

Success Response

```
{
  "status": true,
  "transaction_id": "ded86c0b-b617-400f-a686-5cb77494950e",
  "sabbpe_token": "AbCdEfGh...base64encodedtoken...==",
  "token_expiry_minutes": 10,
  "merchant_order_ref": "INDUMENTI-ORD-001",
  "message": "Token generated successfully"
}
```

What to use from this response

Field	How to use
<code>sabbpe_token</code>	Pass this as sabbpe_token in the /sabbpe/v1/initiate request body
<code>transaction_id</code>	Store in your DB against the order for future reference

Error Scenarios

Scenario	message in response
Wrong password	Invalid merchant credentials
Timestamp too old/ahead	Invalid timestamp. Only +/- 5 minutes from server time is allowed

Wrong timestamp format	Invalid timestamp format. Expected: yyyy-MM-dd HH:mm:ss
Duplicate order ref	merchant_order_ref already exists. Please use a new order reference

API 2 — Initiate Payment

POST /sabbpe/v1/initiate

Initiate a payment session using the token from API 1. Returns a `payment_url` — redirect your customer to this URL to complete payment.

Request Fields

Field	Type	Required	Description
<code>sabbpe_token</code>	String	Required	Token received from /sabbpe/v1/token. Single-use, expires in 10 minutes
<code>amount</code>	Double	Required	Payment amount in INR. E.g. 10.00, 499.99, 1299.00
<code>productinfo</code>	String	Required	Short product description shown on checkout. Max 45 characters. E.g. "Casual Polo T-Shirt"
<code>frontend_url</code>	String	Required	Your website base URL. Use "https://www.indumentti.co.in". Customer is redirected here after payment.
<code>customer.firstname</code>	String	Required	Customer's first name
<code>customer.email</code>	String	Required	Customer's registered email address from your database
<code>customer.phone</code>	String	Required	Customer's 10-digit mobile number from your database

Sample Request

```
curl -X POST https://pymnts.sabbpe.com/sabbpe/v1/initiate \
-H "Content-Type: application/json" \
-d '{
  "sabbpe_token": "AbCdEfGh...base64encodedtoken...==",
  "amount": 10.00,
  "productinfo": "Casual Polo T-Shirt",
  "frontend_url": "https://www.indumentti.co.in",
  "customer": {
    "firstname": "Rakesh",
```

```
"email": "rakesh@gmail.com",  
"phone": "9958750014"  
}  
'
```

Success Response

```
{  
  "status": true,  
  "transaction_id": "ded86c0b-b617-400f-a686-5cb77494950e",  
  "merchant_order_ref": "INDUMENTI-ORD-001",  
  "payment_url": "Live url",  
  "gateway": "Chosen By Sabbpe",  
  "txnid": "SBEBZ618B7D2DC17A4F7B922F",  
  "initiation_status": "INITIATED",  
  "message": "Payment initiated successfully"  
}
```

What to do with this response

Field	What to do
<code>payment_url</code>	Redirect customer to this URL immediately. This is the hosted payment page.
<code>txnid</code>	Store in your DB — this is the SabbPe gateway transaction ID

Error Scenarios

Scenario	message in response
Token already used	Token already used or invalid status: INITIATED
Token expired	SabbPe token expired
Missing frontend_url	Missing frontend_url in initiate payload
Customer not found	Payment initiation failed: Customer not found: email@example.com

After Payment

Customer Redirectrakesh@gmail.com

After the customer completes or cancels payment, they are redirected back to your `frontend_url` with these query parameters:

```
https://www.indumentti.co.in?status=SUCCESS&txnid=INDUMENTI-ORD-001&easepayid=XXXXXX
```

Parameter	Values	Action
status	SUCCESS	Show success page. Confirm order on your backend.
status	FAILURE	Show failure page. Do not fulfil the order.
txnid	Order ref	Your merchant_order_ref passed during token generation

Backend Callback

SabbPe also sends a server-to-server POST to your registered callback URL after payment. Your backend must:

5. Respond with HTTP 200
6. Read the status and txnid from the POST body
7. Update your order status accordingly

Your registered callback URL:

```
https://www.indumentti.co.in/api/payment/sabbpe/callback
```

 **Note:** Always confirm payment on your backend via the callback before marking an order as paid. Never rely only on the frontend redirect.

Integration Checklist

- Generate a unique merchant_order_ref for every new transaction
- Always generate timestamp server-side — never from the browser
- Call /token and /initiate from your backend, not the browser
- Redirect customer to payment_url within 10 minutes of token generation
- Never reuse a sabbpe_token — generate a new token per order
- Implement your callback endpoint to receive payment confirmation
- Keep sabbpe_password and all credentials server-side only

Support

Technical Support	support@sabbpe.com
Website	https://www.sabbpe.com
Document Version	1.0 — April 2026