

Transform Decomposition Switching for Efficient Attribute Compression of 3D Point Clouds Using Neural Networks

Reetu Hooda, Dr. W. David Pan and Bernard Benson

Department of Electrical and Computer Engineering
University of Alabama in Huntsville
Huntsville, Alabama USA


15th Dec 2022

Outline


- Introduction
- Problem Statement
- Neural Network Structure
- Simulation Results
- Conclusion

INTRODUCTION

- What is a Point cloud?
 - Geometry -> 3D coordinates
 - Attributes -> color information or normal vectors





- Applications: Cultural heritage, Autonomous driving, Robotics etc.
- Need of Point Cloud Compression.
- MPEG PCC standardization:




OVERVIEW

- Machine learning for media applications.
- Traditional Vs Machine learning based techniques.



TYPES OF DECOMPOSITION




RAHT




Dyadic RAHT

PROBLEM STATEMENT


Edge detection based on the neighborhood




(a) 18 – neighbourhood



(b) Separated Neighbouring blocks



Central
block




Decomposed
blocks


(c) Central block decomposition

- Switching based on characteristics of the neighbors.
- RAHT for flat regions, Dyadic RAHT for discontinuous areas.
- Edge detection using Sobel filters.
- Limitation: threshold dependency.

PROBLEM STATEMENT




3D edge detection scheme



T-SNE visualization for Pleno data


- The scheme can be perceived as Luma values multiplied by constant weights.
- k was chosen by trial and error, hindering generalized applicability.
- Data preprocessing: 18 Luma with targets and T-SNE plot for 15k points.

NEURAL NETWORK ARCHITECTURE




Fully connected neural network (FCNN) architecture

SIMULATION RESULTS



Training Vs validation loss




Training Vs validation accuracy

SIMULATION RESULTS

BD-RATE GAINS FOR PROPOSED SCHEME OVER DYADIC RAHT ON
MICROSOFT VOXELIZED UPPER BODY (MVUB) DATASET.

Test Sequences	No. of Points	BD-rate			Cumulative Gain
		Luma	Cb	Cr	
Andrew	277038	-0.9%	-8.4%	-3.6%	-12.9%
Phil	336323	0.2%	-5.4%	-2.1%	-7.3%
Ricardo	952178	-1.2%	-3.8%	-3.8%	-8.8%
Sarah	304528	-0.9%	-4.9%	-4.4%	-10.2%
David	302584	-2.9%	-3.7%	-2.9%	-9.5%

Confusion matrix



Sensitivity: 95.88%

Specificity: 88.88%

Precision: 89.69%

SIMULATION RESULTS



Pleno dataset

CUMULATIVE BD-RATE GAINS FOR PROPOSED SCHEME OVER DYADIC RAHT ON 10 RANDOM FRAMES ON MVUB DATASET.

Test	Cumulative Gain										Average
Sequences	1	2	3	4	5	6	7	8	9	10	Gain
Andrew	-12.9%	-12.7%	-10.0%	-9.5%	-8.3%	-8.0%	-6.6%	-6.3%	-5.7%	-5.3%	-8.53%
Phil	-7.3%	-5.9%	-5.6%	-3.6%	-3.4%	-3.0%	-2.7%	-2.3%	-2.0%	-1.7%	-3.75%
Ricardo	-8.8%	-8.4%	-6.8%	-5.2%	-4.2%	-4.1%	-3.9%	-3.5%	-3.0%	-2.7%	-5.06%
Sarah	-10.2%	-8.5%	-8.2%	-6.6%	-5.6%	-4.9%	-4.4%	-4.2%	-2.4%	-2.2%	-5.72%
David	-9.5%	-8.2%	-7.6%	-7.3%	-5.7%	-5.4%	-5.2%	-4.6%	-2.7%	-2.5%	-5.87%



SIMULATION RESULTS




8i Voxelized full body dataset

BD-RATE GAINS FOR PROPOSED SCHEME OVER DYADIC RAHT ON 8i VOXELIZED FULL BODIES (8iVFB) DATASET .

Test Sequences	Cumulative Gain				Average Gain
	1	2	3	4	
Soldier	-4.8%	-4.0%	-3.8%	-3.4%	-4.0%
Loot	-8.5%	-6.9%	-5.5%	-3.9%	-6.2%
Long dress	-1.3%	-1.0%	-0.6%	-0.4%	-0.825%
Red and Black	-3.0%	-1.9%	-1.6%	-1.5%	-2.0%

CONCLUSION

- Neural network-based approach for compression of static PC.
- Addressed the threshold dependency problem.
- Main steps: data collection, training SNN, deploying trained network.
- Compared to MPEG-GPCC with only Dyadic.
- Considerable cumulative gain on MVUB and minor gains on 8iVFB datasets.
- Future work: Could use other channels to improve accuracy and performance.



Thank You!

Questions?

