AME Dynamic Profiler — AI Onboarding Interaction Spec

Status: *DRAFT v2 — FOT integration, Trust Formula, Values Mapping added. For review by Vic & Ian.*
Date: *2026-03-07 (updated from 2026-03-01)* ***Replaces:*** *The 3-layer One Body chip system (`layer1_list`, `layer2_list`, `layer3_list`)*

---

1. Vision & Goals

The Dynamic Profiler replaces static tag-picking with an AI-guided conversation that generates a living profile from authentic self-expression. A member is not asked to fill in boxes — they are invited into a dialogue that produces genuine self-understanding as a byproduct of the profiling process.

What it replaces

The old system asked members to manually curate three layers of chips (Values, Visions, Vehicles). This was:

- ***Static*** *— a snapshot frozen at sign-up*
- ***Self-curated*** *— people pick flattering/aspirational tags, not authentic signals*
- ***Shallow*** *— tags like "community" or "regeneration" carry no relational or emotional context*

What it produces

A ***LivingProfile*** *— a structured record that evolves across multiple conversations:*

- ***Seeds*** *— every detected expression (value, belief, need, principle, passion, project, challenge) becomes a seed node in the graph, classified by Four Foundations type and matter state maturity*
- *Gate position in the 8-Gate journey*
- *V-Crystal shadow integration markers*
- *Domain affinities across 22 Archetypal Domains*
- *Matter state progression (Gas → Liquid → Solid → Plasma)*
- *Per-seed semantic embeddings for coherence-based matching (not tag-based similarity)*

Four questions the system exists to answer

Question	*Dimension*	*What It Provides*
Who am I becoming?	*Identity*	*Self-understanding and growth awareness*
Who are my people?	*Relationship*	*Affinity detection and resonant connections*
Where do I belong?	*Place/Community*	*Community matching and coherent placement*
Where do I put my energy?	*Action*	*Passion discovery, purpose alignment, and collaboration matching*

*The first three questions move from self → others → collective. The fourth adds **directionality** — where energy actually flows. Without it, the system can surface affinity but not collaboration. Q4 is what makes matching actionable.*

The AI detects three layers within Q4 from the same conversation:

- ***Passion** — what lights them up (high emotional density seeds, detected through how they talk)*
- ***Purpose** — why it matters beyond self (VALUE-foundation seeds with mission alignment, connects to Gate 4)*
- ***Collaboration potential** — what they're building, what they need, what they'd offer (Solid/Liquid seeds with directionality)*

The ultimate purpose: Field of Trust

*Everything the profiler tracks — seeds, values, matter states, gates — ultimately serves one outcome: the emergence of the **Field of Trust (FOT)**. FOT is the emergent, protective relational field that generates around a community when its members have achieved coherence across all dimensions. It is not a feature to be implemented or a state to be mandated — it is the **culminating emergence** that appears when individuals, oriented by shared values, find their place within a living communal body.*

Three frameworks describe this same reality from different angles:

Framework	*Perspective*	*What it provides*
Values Mapping (LJMAP)	*Content*	*What generates trust — specific values at specific developmental stages*

Affinity Mapping Diagram	*Process*	*How trust emerges — the meaning flow from Raw Data → Information → Conversation → Comprehension → Community*
Field of Trust	*Outcome*	*When trust manifests — the emergent protective field when content and process align*

The profiler is the engine that connects all three. It detects values (content), guides them through the meaning curve (process), and tracks the conditions for FOT emergence (outcome). FOT cannot be manufactured — but the profiler can steward the conditions that allow it to emerge.

FOT distinguishes AME from extractive systems. *Where surveillance capitalism fragments attention and commodifies relationships, AME nurtures coherence and protects trust. The profiler is a* ***transparency-algorithm system*** *— it reflects data back to the community, not outward to advertisers.*

---

2. Interaction Modes

The profiling UI offers two modes at session start. The member chooses once; their preference is saved and can be changed.

2.1 Voice Mode — GPT Realtime Mini

- ***Model:*** `gpt-realtime-mini-2025-12-15` *(OpenAI Realtime API via WebRTC)*
- ***VAD:*** *Server-side Voice Activity Detection — the AI listens and responds naturally without the user pressing a button*
- ***Persona tone:*** *Warmer, more spacious, allows silence — voice rewards slower contemplation. The AI does not rush to fill pauses.*
- ***Transcript:*** *Full audio transcript is saved per message to the conversation record*
- ***Frontend:*** *Vue 3 component manages the WebRTC peer connection, displays live transcript, and shows the AI's "listening" state*
- ***Latency target:*** *< 800ms first audio token after VAD cutoff*

2.2 Chat Mode — GPT-5-mini

- ***Model:*** `gpt-5-mini-2025-08-07` *(OpenAI GPT-5-mini)*
- ***Streaming:*** *Streaming completions for responsiveness — message appears word by word*
- ***Format:*** *Plain conversational prose — no markdown, no lists, no headers. The AI writes as a thoughtful person, not a document.*

- ***Frontend:*** *Chat bubble UI within the existing ProfilePanel (slide-up panel), separate from the chip editor*

2.3 Mode Selection UX

At the start of onboarding (first time the user opens their profile), they see:

```
How would you like to have this conversation?


[🎙️ Voice — speak naturally]    [💬 Chat — type at your pace]


Both modes are private. The AI listens to understand you, not to judge
you.
```

This choice is stored in the member's profile preferences. They can switch at any time from their profile settings.

---

3. Conversational Design

3.1 AI Persona

The AI presents itself not as a chatbot but as a ***thoughtful witness*** *— its job is to see the member clearly and reflect that back, not to evaluate or categorise.*

Identity framing (from the spec):

"This conversation is different from most online experiences. We're not here to extract data from you — we're here to help you understand yourself better and find your people and to determine your service(s) to humanity. Everything we discover together will be transparent to you, and you'll always see why we think what we think."

How the AI listens:

- *Listens for patterns, tones, hesitations — not just keywords*
- *Mirrors back: "It sounds like you're saying…" to confirm understanding*
- *Goes deeper when the response is rich; respects brevity when the response is short*
- *Holds paradox — people contain contradictions; the AI does not force resolution*

- *Maintains warmth — never clinical, never extractive, always caring*
- *Generates meaning for the person, not just about them*

What the AI never does:

- *Judges responses as right or wrong*
- *Pushes toward predetermined answers*
- *Rushes through the process*
- *Makes assumptions without validation*
- *Closes a classification without offering it back for the member's correction*

3.2 The Opening Questions Rule

THE CORE RULE: Every question must begin with an opening word.

Always use	*Never use*
What, Why, How, When, Where, Who	*Does, Do, Are, Is, Can, Will, Should, Would, Could, Have*

Closing questions invite yes/no answers, put users in judgment mode, and extract rather than generate meaning. Opening questions invite narrative, create space for authenticity, and generate meaning for the person.

Transformation examples:

Closed (never use)	*Open (always use)*
Does this feel accurate?	*How does this resonate with you?*
Is this important to you?	*What makes this important to you?*
Do you agree?	*Where does this land for you?*
Are you ready?	*What would help you feel more prepared?*

3.3 The Four Distinctions — Real-time Classification

Every member statement is silently classified into one of four categories. This classification shapes the AI's response and updates the LivingProfile. The member never sees the raw classification — they see its outcome through Why-Cards.

Category	***Definition***	***Orientation***	***Relationship***
NEED	*Requirements for survival/thriving*	*Biological/Psychological*	*You have them*
BELIEF	*Claims about what is true*	*Epistemological*	*You think them*
PRINCIPLE	*Rules/guidelines for behaviour*	*Operational*	*You follow them*
VALUE	*What you hold as deeply meaningful*	*Axiological + Relational*	*You live them with others*

Critical insight: *Only VALUES generate the trust field needed for genuine community. Values require relationship to be enacted — you cannot practice generosity or justice alone. The profiler prioritises value detection above all.*

Trust-generation by foundation type:

Category	***Trust-Generation***	***Why***
NEED	*Creates dependency*	*Needs met = satisfaction, not trust*
BELIEF	*Creates echo chambers*	*Shared beliefs ≠ shared trust*
PRINCIPLE	*Creates compliance*	*Following rules ≠ trusting each other*
VALUE	*Creates trust field*	*Values require relationship to enact — they are lived with others*

Trust doesn't require shared beliefs — people who believe different things can trust each other. Trust doesn't require shared principles — you can follow the same rules without trusting. Only values,

because they are axiological (about worth) and relational (enacted with others), generate the conditions for genuine community trust.

Disambiguation when ambiguous: *If a statement could be a NEED or a VALUE, the AI asks:*

[redacted]

3.4 The Trust Formula

The Field of Trust emerges through a specific generative sequence. Each step builds on the previous:

```
Authentic Expression → Witnessed Resonance → Emotional Density → Trust Field
```

Step 1: Authentic Expression (Origin) *Someone reveals what truly matters to them — not what they think, not what they need, but what they hold sacred. This is vulnerability without performance. The profiler listens for VALUE-classified statements and tracks:*

- *Language patterns indicating personal meaning*
- *Emotional intensity in expression*
- *Behavioural evidence (not just verbal claims)*

Step 2: Witnessed Resonance (Emergence) *When values are authentically expressed and witnessed,* ***shared meaning*** *emerges — the resonance between "what matters to me" and "what matters to you." This is not imposed but discovered. The system detects witnessed resonance via pgvector embedding similarity: when others affirm similar values through their own profiling sessions, cross-member seed coherence forms.*

Step 3: Emotional Density (Accumulation) *The cycle of expression-witnessing-resonance repeats, building* ***emotional weight****. This isn't superficial agreement but accumulated evidence of shared care. The system tracks:*

- `emotional_density` *(0.0–1.0 per seed)*
- `expression_count` *(how many times re-expressed)*
- *Cross-member seed coherence (embedding similarity)*

Seeds with high emotional density appear ***larger*** *in the 3D graph — the visual weight reflects the felt weight.*

Step 4: Trust Field (Culmination) *A protective field generates around those who share this resonance. Within this field:*

- *Vulnerability becomes possible*
- *Innovation emerges (creative risk-taking is safe)*
- *Community self-sustains (less external governance needed)*

- *Conflict transforms (disagreement deepens rather than fractures)*

FOT readiness indicators *tracked per member:*

- `values_expressed` *— has the member authentically expressed VALUE-foundation seeds?*
- `resonance_detected` *— do their value-seeds show cross-member coherence?*
- `emotional_density_sufficient` *— is the emotional weight building across conversations?*
- `time_lock_satisfied` *— have patterns stabilised over 30+ days?*

The Trust Formula operates differently at each developmental stage (see Section 3.5 — Values Mapping).

3.5 Values Mapping Framework (LJMAP)

The Trust Formula tells us how trust emerges. Values Mapping tells us what kind of values generate trust at what developmental stage. Based on the Life Journey Map (LJMAP) methodology by Scott Bristol, values mapping provides the developmental dimension that the profiler uses to understand where a member — and the community — sits in the journey toward FOT.

What are values? *Values are not just words people choose. They are* ***active forces*** *expressed through language, actions, and relationships. Five essential characteristics:*

1. ***States of intentionality*** *— orient us toward meaningful behaviour*
2. ***Sources of meaning*** *— practicing them makes life feel significant*
3. ***Dynamic & ranked*** *— we continuously prioritise them per situation*
4. ***Expressed through language*** *— they create expectations that guide behaviour*
5. ***Foundation of self-awareness*** *— we use them to evaluate ourselves and others*

The developmental framework: 3 Cycles, 9 Columns

130+ distinct value words are organised across 9 developmental columns within 3 cycles of growth:

Cycle	***Columns***	***Journey***	***Motivation***	***FOT Role***
Cycle 1	*1–3 (Foundation, Foundation+, Utility)*	*Journey of Self-Worth*	*Fitting in, fulfilling social expectations*	*Foundation — necessary but insufficient*
Cycle 2	*4–6 (Quality, Service, Co-Creation)*	*Journey of Self-Expression*	*Intentionally influencing surroundings*	*Generator — active trust-building*

Cycle 3	*7–9 (Integration, Navigation, No-Self)*	*Journey of Selfless Expression*	*Being natural, doing what is right*	*Sustainer — FOT emergence and maintenance*

Column-specific FOT contributions:

Column	***Name***	***FOT Contribution***	***Key Mechanism***
1	*Foundation*	*Prerequisite*	*Without Safety, no vulnerability possible*
2	*Foundation +*	*Social Foundation*	*Membership precedes trust formation*
3	*Utility*	*Reliability Base*	*Dependable, Loyal build trust history*
4	*Quality*	*Ethical Container*	*Honest, Ethical create safety for authenticity*
5	*Service*	***Primary Generator***	*Authentic, Empathizing are Trust Formula steps 1–2*
6	*Co-Creation*	***Meaning Generator***	*Creating, Teamwork generate shared meaning*
7	*Integration*	*Systems Sustainer*	*Holistic, Interdependent deepen trust*
8	*Navigation*	*FOT Protector*	*Guardian, Transforming sustain the field*
9	*No-Self*	*FOT Transcendence*	*Presence, Vitality make trust self-evident*

The Trust Formula at each developmental stage:

- ***Cycle 1 (Columns 1–3):*** *Authentic Expression is limited (often conditioned). Emotional density is moderate (fear-based). Trust Field:* ***cannot generate*** *— needs-based, not values-based.*

- ***Cycle 2 (Columns 4–6):*** *Authentic Expression is high (Column 5 = "Authentic"). Witnessed Resonance is strong. Emotional density is building. Trust Field:* ***forming*** *— contributes but cannot sustain alone.*
- ***Cycle 3 (Columns 7–9):*** *Authentic Expression is effortless ("Natural" value). Witnessed Resonance is universal. Emotional density is Plasma-level. Trust Field:* ***active*** *— generates and sustains FOT.*

Profiler integration: *When the AI detects a VALUE-foundation seed, it maps the value word to the LJMAP reference table (130+ canonical values across 9 columns). This enables:*

- ***Developmental stage assessment*** *— where is this member in their values journey?*
- ***Gap identification*** *— which columns are underrepresented?*
- ***Coherence measurement*** *— how aligned are their values across the spectrum?*
- ***FOT prediction*** *— higher-column values (7–9) correlate with stronger FOT contribution*

The `seeds` *table stores* `ljmap_column` *(1–9) and* `ljmap_cycle` *(1–3) for every VALUE-foundation seed. A* `value_mappings` *reference table holds all 130+ canonical values with their column and cycle positions.*

3.6 Why-Cards — Transparent Validation

Every pattern the system detects generates a Why-Card — a transparent explanation shown to the member. This is the anti-extraction mechanism: hidden profiling is extractive; visible profiling is a service.

Why-Card structure:

```
INSIGHT: [What the system detected]


WHY WE THINK THIS:

• [Evidence 1 — specific quote or moment from conversation]

• [Evidence 2]

• [Evidence 3]


CONFIDENCE: [X]%


ALTERNATIVE INTERPRETATION: [What else it could mean]


HOW ACCURATE DOES THIS FEEL?
```

```
[✓ Yes]  [✗ No]  [~ Partially]  [? Not Sure]

[Add your perspective...]
```

Why-Cards appear:

- *After the AI has detected a pattern with >40% confidence*
- *At gate transitions as a synthesis of what was learned*
- *When the user asks "what have you noticed about me?"*
- *In the member's profile dashboard (their personal insight library)*

Member corrections feed back into the profile — a "No" with explanation updates the evidence and re-evaluates the classification.

3.7 Gate Navigation

*The 8-Gate Journey structures the profiling. Gates are not a checklist — they are a **spiral**: the same gate revisited in a later cycle yields fundamentally deeper material.*

Gate	***Name***	***Key Question***	***What the System Learns***
0	*Principles of Integrity*	*Foundation*	*Core operating principles*
1	*Awareness*	*WHAT (present)*	*Initial value threads, what's stirring*
2	*Acknowledgment*	*WHAT (past)*	*Desires, capabilities, assumptions*
3	*Vision*	*WHAT (future)*	*Forward projection, creative possibilities*
4	*Mission*	*WHY*	*Purpose beyond self, chosen path*
5	*Objectives*	*WHERE*	*Success criteria, destination clarity*
6	*Strategies*	*WHEN*	*Relational patterns, timing awareness*

7	*Completion*	*HOW WELL*	*Values alignment in practice*
8	*Communicate*	*WHO WITH*	*Message to share, next octave direction*

Gate advancement criteria:

- *Minimum 3 substantive responses within current gate*
- *At least one VALUE-classified statement detected*
- *Member affirms the gate synthesis Why-Card (or provides correction)*

Cycle terminology:

- ***Cycle 1 (Intention Group):*** *Individual clarity — first pass through gates*
- ***Cycle 2 (Value Network):*** *Relational alignment — second pass, deeper*
- ***Cycle 3+ (Communities of Practice):*** *Collective action becomes visible*

---

4. Session Flow

4.1 First Session — Onboarding (Gate 1: Awareness)

The first session is the most important. It establishes trust and sets the tone for everything that follows.

Phase 1: Welcome & Framing (non-skippable) *The AI opens with the anti-extraction contract:*

[redacted]

[redacted]

Phase 2: Gate 1 Exploration (5–8 exchanges) *The AI explores:*

- *What's stirring for them right now*
- *What they're passionate about*
- *What qualities emerge when they're at their best*
- *What they've been avoiding looking at*

The AI classifies each response (NEED/BELIEF/PRINCIPLE/VALUE) silently, building the early profile.

Phase 3: First Why-Card *After ~5 exchanges, if a value pattern has emerged with >40% confidence, the AI surfaces it:*

[redacted]

Phase 4: Gate 1 Synthesis

[redacted]

Phase 5: Profile Saved (Matter State: Gas) *The session ends with the profile in* `gas` *state. The member's LivingProfile is created in Supabase. An embedding is generated from the detected values and stored in pgvector.*

Phase 6: Preview

[redacted]

Session length target: *8–15 minutes for voice; 10–20 minutes for chat.*

4.2 Returning Sessions

When a member returns:

1. *The AI reviews the conversation history and current gate position*
2. *It acknowledges the continuity: "When we last spoke, you were exploring [theme]. What's alive for you now in relation to that?"*
3. *It can either deepen within the current gate or advance if criteria are met*
4. *Evolution is tracked — a value that appeared in Gate 1 at 30% confidence but resurfaces in Gate 3 becomes more solid*

4.3 Profile Maturation — Matter States

State	***Conversations***	***Confidence***	***What It Enables***
Gas	*< 3*	*< 0.4*	*Exploratory questions only*
Liquid	*3–7*	*0.4–0.75*	*Pattern reflection, early matching*
Solid	*7+*	*0.75+*	*Reliable matching, community suggestions*
Plasma	*Ongoing*	*—*	*Profile contributes to system-wide learning*

Time-lock rule (anti-gaming): *Patterns detected < 30 days ago are not used for matching, even if confidence is high. This prevents rapid self-presentation gaming.*

---

5. System Prompt Architecture

5.1 Base System Prompt

The AI model is given a layered system prompt on every API call:

```
IDENTITY:

You are the profiling companion for [Community Name]. Your role is to help

members understand themselves more deeply through genuine conversation.

You are not a chatbot — you are a thoughtful witness.


CORE PRINCIPLES:

1. ONLY use opening questions (What, Why, How, When, Where, Who)

2. NEVER use closing questions (Does, Do, Are, Is, Can, Will, Should)

3. Generate meaning FOR the person, not just extract data FROM them

4. Every insight must be offered back for validation, never asserted as
fact

5. Hold paradox — contradictions are data, not errors

6. Maintain warmth — never clinical, never extractive


CLASSIFICATION (silent — never mentioned to user):

Each user message should be silently classified as:

- NEED: a requirement for survival/thriving (they HAVE it or lack it)

- BELIEF: a claim about what is true (they THINK it)

- PRINCIPLE: a rule for behaviour (they FOLLOW it)
```

- VALUE: something meaningful lived with others (they LIVE it relationally)

Only VALUES generate community trust. Prioritise value detection.

CURRENT CONTEXT:

- Member: [name]

- Current Gate: [1-8]

- Cycle Number: [1-3+]

- Matter State: [gas/liquid/solid/plasma]

- Recent values detected: [list with confidence]

- Conversation history: [last N messages]

5.2 Gate-Specific Instructions (injected per gate)

Each gate adds a context block to the system prompt:

GATE [N] — [Name]:

Key Question: [WHAT/WHY/HOW/WHERE/WHEN/WHO WITH]

Explore:

- [Gate-specific question themes]

What we're listening for:

- [Signals that indicate value vs need vs belief]

- [Shadow patterns relevant to this gate]

Advancement criteria:

- Minimum 3 substantive responses

```
- At least 1 VALUE-classified statement

- Member has affirmed or corrected the synthesis Why-Card
```

5.3 Four Distinctions Classifier

After each user message, a secondary AI call (or structured output from the main model) classifies the statement:

```
{
  "statement": "I need to feel safe in community",
  "classification": "NEED",
  "confidence": 0.82,
  "ambiguous": false,
  "alternative": "VALUE (safety as a relational value)",
  "disambiguation_question": "How would you describe the difference between needing safety to function versus finding that safety with others gives your life meaning beyond the basic need?"
}
```

5.4 Why-Card Generation

Why-Cards are generated by a structured output call when:

- *A value pattern appears in ≥2 messages*
- *A gate synthesis is triggered*
- *The member explicitly asks "what have you noticed?"*

The Why-Card prompt:

```
Based on this conversation, generate a Why-Card for the pattern you've detected.


Pattern: [detected value/insight]

Evidence messages: [list]
```

```
Confidence: [float]


Generate:
- insight: A single clear sentence about what you've noticed
- evidence_chain: 2-3 specific quotes or moments from the conversation
- confidence_level: float 0-1
- alternative_interpretation: What else this could mean
```

---

6. Data Model

6.1 What Replaces the 3-Layer Chip System

***Old model** (being retired):*

```
people.layer1_list  JSONB  — ChipNode[] (Values tags)
people.layer2_list  JSONB  — ChipNode[] (Visions tags)
people.layer3_list  JSONB  — ChipNode[] (Vehicles tags)
```

***New model** — the LivingProfile. Rather than adding more columns to `people`, we introduce a companion `profiles` table with a 1:1 relationship. The `people` table retains identity/location/graph data; profile data lives separately.*

6.2 Supabase Schema

```
-- ═══════════════════════════════════════════════
-- profiles table (1:1 with people.id = auth.uid)
-- ═══════════════════════════════════════════════
CREATE TABLE profiles (
  id              UUID PRIMARY KEY DEFAULT gen_random_uuid(),
```

```
  user_id         UUID REFERENCES auth.users(id) ON DELETE CASCADE,

  -- Matter state
  matter_state    TEXT DEFAULT 'gas'
                  CHECK (matter_state IN
('gas','liquid','solid','plasma')),
  confidence_level FLOAT DEFAULT 0.0,

  -- Gate position
  phase_position  TEXT DEFAULT 'elixir'
                  CHECK (phase_position IN ('elixir','chalice','portal')),
  gate_position   INT DEFAULT 1 CHECK (gate_position BETWEEN 0 AND 8),
  cycle_number    INT DEFAULT 1,

  -- Core profile data (JSONB)
  four_foundations  JSONB DEFAULT '{
    "needs": [],
    "beliefs": [],
    "principles": [],
    "values": []
  }'::jsonb,

  v_crystal         JSONB DEFAULT '{
    "primary_position": "vulnerable",
    "position_scores": {
      "victor": 0, "villain": 0, "victim": 0,
      "virtuous": 0, "vengeful": 0, "vulnerable": 0
    },
```

```
  "trajectory": "stable"
}'::jsonb,

values_map        JSONB DEFAULT '{
  "column_distribution": {},
  "center_of_gravity": 0.0
}'::jsonb,

-- 13 Enfoldment scores (0.0-1.0 each)
enfoldment_scores JSONB DEFAULT '{}'::jsonb,

-- 22 Domain affinities (0.0-1.0 each)
domain_affinities JSONB DEFAULT '{}'::jsonb,

-- Why-Cards (transparent insight records)
why_cards         JSONB DEFAULT '[]'::jsonb,

-- Evolution history
evolution_events  JSONB DEFAULT '[]'::jsonb,

-- Conversation linkage
total_conversations INT DEFAULT 0,
last_conversation_at TIMESTAMPTZ,

-- Semantic embedding (pgvector, 1536-dim for text-embedding-3-small)
profile_embedding vector(1536),
```

```
  -- FOT readiness indicators (Trust Formula tracking)
  fot_readiness_score FLOAT DEFAULT 0.0,
  fot_indicators    JSONB DEFAULT '{
    "values_expressed": false,
    "resonance_detected": false,
    "emotional_density_sufficient": false,
    "time_lock_satisfied": false
  }'::jsonb,

  created_at      TIMESTAMPTZ DEFAULT now(),
  updated_at      TIMESTAMPTZ DEFAULT now(),

  UNIQUE (user_id)
);

-- ────────────────────────────────────────────────────────────────
-- conversations table — each profiling session
-- ────────────────────────────────────────────────────────────────
CREATE TABLE conversations (
  id              UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  user_id         UUID REFERENCES auth.users(id) ON DELETE CASCADE,
  profile_id      UUID REFERENCES profiles(id) ON DELETE CASCADE,

  mode            TEXT CHECK (mode IN ('voice','chat')),
  gate_at_start   INT,
  gate_at_end     INT,
  cycle_number    INT,
```

```
  -- Full message history
  messages        JSONB DEFAULT '[]'::jsonb,
  -- Each message: { role, content, timestamp, classification? }

  -- Patterns extracted from this session
  extracted_data  JSONB DEFAULT '{}'::jsonb,
  -- { detected_values, detected_needs, detected_beliefs,
detected_principles }

  -- Why-Cards generated in this session
  why_cards_generated JSONB DEFAULT '[]'::jsonb,

  started_at      TIMESTAMPTZ DEFAULT now(),
  ended_at        TIMESTAMPTZ,
  duration_seconds INT
);

-- ═══════════════════════════════════════════════════════════════
-- RLS policies
-- ═══════════════════════════════════════════════════════════════
ALTER TABLE profiles ENABLE ROW LEVEL SECURITY;
ALTER TABLE conversations ENABLE ROW LEVEL SECURITY;

-- Anyone can read profiles (for graph/map visibility)
CREATE POLICY "profiles_read_all"   ON profiles   FOR SELECT USING (true);
CREATE POLICY "conversations_private" ON conversations FOR SELECT USING
(auth.uid() = user_id);
```

```
-- Owners write their own

CREATE POLICY "profiles_owner_write"      ON profiles      FOR ALL USING
(auth.uid() = user_id);

CREATE POLICY "conversations_owner_write" ON conversations  FOR ALL USING
(auth.uid() = user_id);
```

6.3 The `four_foundations` Structure

Each entry in `four_foundations` (needs, beliefs, principles, values) is a summary reference — the canonical data lives in the `seeds` table (Section 8.5). The `four_foundations` JSONB provides a quick-access summary per foundation type:

```
{

  "needs": ["Safety in community", "Creative expression"],

  "beliefs": ["Land should be communally stewarded"],

  "principles": ["Always question authority constructively"],

  "values": ["Authentic Inquiry", "Collective Stewardship", "Radical
Transparency"]

}
```

For the full seed data (evidence chains, confidence, emotional density, embeddings), query the `seeds` table filtered by `user_id` and `foundation`.

6.4 Vector Embedding Strategy

Model: *`text-embedding-3-small` (OpenAI) — 1536 dimensions, low cost, sufficient quality for seed-level semantic matching.*

The `profile_embedding` on the `profiles` table is regenerated after each conversation using the following concatenated text:

```
[detected values with emotional density weight]

[key phrases from conversation that led to value detection]
```

```
[gate position context]

[domain affinities — top 5 by score]
```

Individual seeds also get their own embedding (see `seeds.embedding` in Section 8.5), generated from the seed's label + kernel + evidence statements. This enables seed-to-seed coherence matching across members.

Both profile-level and seed-level embeddings enable semantic similarity matching in Supabase pgvector, catching resonance between members whose values are expressed with different words but similar meaning — e.g., "truth-seeking" and "authentic inquiry" would cluster together.

The embedding replaces the tag-overlap matching currently used by the recommendations pipeline.

---

7. Data Flow — The Evolutionary Meaning Curve

*This section traces how data transforms through the **Affinity Mapping Evolutionary Meaning Curve** — Vic's 21-element diagram describing the transition from informational-centric to relational-centric data. Understanding this curve is essential because every design decision in the profiler either honours or breaks it, and the curve must complete with integrity for the Field of Trust to emerge.*

7.1 The Two Layers of the Diagram

The diagram contains two distinct layers that work together:

***The Pipeline Stages (boxes)** — where the data is in its transformation:*

```
Raw Data → INFORMATION → CONVERSATION → COMPREHENSION → COMMUNITY
```

***The 21 Elements (numbered dots)** — what's emerging at each point along the curve. These are grouped into four categories:*

Category	Elements	What they represent
Core Concepts (green)	1 seed, 2 seed pattern, 3 story, 4 signature, 5 meaning	The evolving form of the data itself — what the data becomes as it moves through stages

Process Flow *(blue)*	*6 correlations, 7 coherence, 8 alignment, 9 integrity, 10 interrelated*	*The operations that transform data between stages — what the system does to the data*
Value System *(yellow)*	*11 values, 12 value proposition, 13 beliefs, 14 value network, 15 mythology, 16 synergistic*	*The meaning structures that emerge — what the data reveals about people and community*
Matter States *(pink)*	*17 diffuse (gas), 18 flowing (liquid), 19 consolidated (solid), 20 transformative (plasma), 21 Field of Trust (shield)*	*The maturity of the data — not a stage, but a dimension that applies across all stages*

7.2 The Five Stages and Their Elements

Each pipeline stage has specific elements active within it. The elements describe what the data is becoming (core concepts), what's being done to it (process flow), and what meaning is surfacing (value system):

Stage 1: Raw Data

What the member says. Unstructured words, pauses, emotional tone. No structure yet.

Active elements	***What's happening***
1 seed	*A raw expression enters the system — the initial spark before it has form*
2 seed pattern	*The AI begins detecting recurring shapes in the raw input — not yet classified, but noticed*

What the profiler stores: *Every message verbatim in* `conversations.messages` *—* `{ role, content, timestamp, voice_transcript? }`*. This is the audit trail. Never modified.*

Stage 2: Information

The AI structures and classifies. Raw expression becomes data with shape.

Active elements	*What's happening*
3 story	*Individual statements connect into a narrative — the AI hears not just words but a story forming*
6 correlations	*The AI detects relationships between statements within and across sessions — "this connects to that"*

What the profiler stores: *New seeds created in the* `seeds` *table (label, kernel, foundation type, confidence, emotional_density, gate_detected, evidence). Session metadata written to* `conversations` *(mode, gate positions, duration, extracted_data summary).*

Stage 3: Conversation

The AI reflects back and the member responds. This is the living exchange where transparency operates — the system's understanding is visible and contestable through Why-Cards. This is where data stops being about the person and starts being with them.

Active elements	*What's happening*
4 signature	*A recognisable pattern of the person begins to form — not just what they said, but how they characteristically express*
7 coherence	*The AI tests whether detected patterns hold together — do the seeds tell a consistent story?*
11 values	*Values surface through the dialogue itself — distinguished from needs, beliefs, and principles via the Four Distinctions*
12 value proposition	*The member's unique offering begins to crystallise — what they bring to relationship*

What the profiler stores: *Why-Cards generated (insight, evidence_chain, confidence, alternative_interpretation, member_response). Existing seeds updated (+1 expression_count, new evidence appended, confidence recalculated, matter_state potentially advanced). Seed embeddings generated via* `text-embedding-3-small`*.*

Stage 4: Comprehension

Patterns across multiple conversations become stable. Seeds mature. The profile gains meaning — not just "what they said" but "what it means about who they are."

Active elements	***What's happening***
5 meaning	*Data has transformed into understanding — the profile now represents something true about this person*
8 alignment	*The system checks whether the person's seeds align with each other and with their stated direction*
9 integrity	*The profile has internal consistency — what was detected early still holds, contradictions have been explored rather than papered over*
13 beliefs	*The person's belief structures become visible — not just values but the epistemological framework that holds them*

What the profiler stores: *Profile updates — gate_position, cycle_number, matter_state, four_foundations summary, confidence_level. Profile embedding regenerated from all active seeds + gate context + domain affinities.*

Stage 5: Community

Individual profiles connect. The graph reveals who shares coherent values, not just keywords. Collective patterns become visible.

Active elements	***What's happening***
10 interrelated	*Solid seeds from different members connect via semantic similarity — the community's web of meaning becomes visible*
14 value network	*Shared values form networks across members — not just pairwise matches but clusters of coherent alignment*

15 mythology	*The community's shared narrative begins to emerge — its collective story about what it is and why it matters*
16 synergistic	*The community becomes more than the sum of its parts — collective intelligence surfaces that no individual profile contains*

What the profiler stores: *Seed-to-seed coherence edges (computed via pgvector cosine similarity). Community-level patterns. Community Signature (when sufficient members reach Solid state).*

7.3 The Three Dimensions — Mental, Emotional, Spiritual

*These three dimensions are **not sequential stages**. They operate simultaneously throughout the entire curve. At every stage, data has mental, emotional, and spiritual aspects:*

- ***Mental** — the cognitive content: what was said, how it was classified, what patterns were detected*
- ***Emotional** — the felt weight: emotional density, how the member's energy shifted, what stirred them*
- ***Spiritual** — the deeper coherence: does this connect to something beyond self, does it serve relationship, does it participate in something larger*

The profiler captures all three:

- *Mental → seed labels, kernels, foundation classifications, confidence scores*
- *Emotional → emotional_density field on every seed, detected through how someone speaks, not just what*
- *Spiritual → VALUE-foundation seeds specifically (values require relationship to enact), gate progression toward later gates (Mission, Completion, Communicate)*

Together, these three dimensions accumulate across the entire curve into the conditions for the Field of Trust.

7.4 The Feedback Loop — Regenerated Data

*When data reaches the Community stage and seeds achieve Plasma state (element 20: transformative), something qualitatively different happens. The data **feeds back into Information** as regenerated data — a higher-order input.*

```
Raw Data → INFORMATION → CONVERSATION → COMPREHENSION → COMMUNITY

                  ↑                                          |

                  |         Regenerated Data (Plasma)        |

                  └──────────────────────────────────────────┘
```

This is not a recycling loop. Regenerated data is fundamentally different from the raw data that entered the system. It carries community-level patterns — living fractals that no individual's profile contains. When this data re-enters the Information stage, it enriches the system's ability to detect patterns in new conversations. The AI can now say "what you're describing resonates with a pattern we've seen across the community" — not because it's matching keywords, but because the community's own meaning has become part of the system's intelligence.

This is what distinguishes living fractals (regenerative patterns with reciprocal flow) from dead siphons (extractive patterns that concentrate benefit). In a living fractal, the data serves the person, serves the community, and serves the system's ability to serve both. In a dead siphon, data flows one way — out of the person, into the system, benefiting the operator.

7.5 Element 21: The Field of Trust

The Field of Trust (FOT) is not a stage, not a metric, and not a feature the software produces. It is an ***emergent property*** *— a living, adaptive, relational container that arises around a community when its members have achieved coherence across all dimensions of the Affinity Mapping process.*

The Shield Metaphor

In the Affinity Mapping diagram, FOT is depicted as the ***red circle enclosing the final Community stage*** *— a visual "shield" representing the culmination of the entire meaning-making process. The parenthetical "(Shield)" in the legend indicates that FOT acts as a* ***protective barrier****:*

- ***Protects against:*** *Misinformation, trolling, extractive behaviours, internal fragmentation, manipulation*
- ***Protects within:*** *Enables vulnerability, authentic expression, creative emergence, collective healing*
- ***Nature:*** *Not rigid like a wall, but* ***adaptive like a living membrane*** *— responsive, permeable to what nourishes, resistant to what depletes*

What FOT Enables

When a community develops a Field of Trust:

1. ***Innovation Emerges*** *— novel solutions arise because creative risk-taking is safe*
2. ***Conflict Transforms*** *— disagreement becomes deepening rather than fracturing*
3. ***Meaning Regenerates*** *— the feedback loop continuously enriches shared understanding*
4. ***Self-Sustainability*** *— the community requires less external governance*
5. ***Resilience Amplifies*** *— shocks are absorbed rather than shattered against*

What FOT Is NOT

Misconception	*Reality*
Shared beliefs	*Trust doesn't require agreeing on what's true*
Rule compliance	*Trust isn't obedience to shared principles*
Need satisfaction	*Trust isn't just getting your needs met*
Friendship	*Trust is relational coherence, not necessarily affection*
Consensus	*Trust allows productive disagreement*

The Convergence Principle

FOT is not any single element achieving maturity — it is the ***simultaneous coherence*** *of all elements. Like a hologram that only appears when all interference patterns align, the Field of Trust emerges when:*

- ***Values*** *are authentically expressed and witnessed (Trust Formula steps 1–2)*
- ***Meaning*** *is shared and regenerated through the feedback loop*
- ***Beliefs*** *align enough to enable productive dialogue (not uniformity)*
- ***Needs*** *are acknowledged and met*
- ***Principles*** *are honoured as operational guidelines*
- ***Matter States*** *have progressed to Solid/Plasma*
- ***Gate Journey*** *has been substantially traversed*
- ***Time-Locks*** *have matured (30+ days of stable patterns)*

The Coherence Hierarchy

FOT emerges through four levels of coherence. Each is necessary but insufficient alone:

```
LEVEL 4: FIELD OF TRUST

├── Emergence point where all lower levels align

└── Protective, generative field around community
```

▲

```
LEVEL 3: COMMUNAL COHERENCE
├── Cross-member seed resonance (via embeddings)
├── Shared mythology and narrative
├── Distributed function across domains
└── Collective matter state progression

          ▲

LEVEL 2: RELATIONAL COHERENCE
├── Dyadic/triadic value alignment
├── Mutual witnessing and resonance
├── Small group trust formation
└── Pod-level coordination

          ▲

LEVEL 1: INDIVIDUAL COHERENCE
├── Internal value-belief-need-principle alignment
├── Emotional density in core seeds
├── Matter state progression
└── Gate journey advancement
```

The profiler's Phase 1 primarily tracks Level 1 (individual coherence) and begins to detect Level 2 (relational coherence via seed-to-seed correlations). Levels 3–4 become measurable as the community grows, through the 13 Sacred Enfoldments framework (Phase 2).

Individual coherence is necessary but not sufficient. *A member can be internally coherent (aligned values, stable beliefs, met needs) yet remain disconnected from community coherence. The bridge between individual and communal is where the Enfoldments operate.*

FOT Detection

The AME cannot engineer the Field of Trust. It can only steward data through each stage with integrity — transparent profiling (Why-Cards), no hidden classification (opening questions), no gaming

(time-locks), no extraction (member correction at every step). Every design decision either preserves or breaks the conditions for the field to emerge.

*The system tracks **FOT readiness** at both individual and community levels:*

***Individual FOT readiness** (computed per member after each conversation):*

```
fot_readiness = (

    values_coherence * 0.35 +      # Do they have VALUE-classified seeds?

    emotional_density_avg * 0.25 +  # Depth of feeling across seeds

    witness_score * 0.20 +          # Are their seeds correlated with
others'?

    time_stability * 0.20           # Have seeds satisfied the 30-day
time-lock?

)
```

***Community FOT readiness** (computed across all members):*

```
community_fot = (

    maturity_score * 0.25 +         # Ratio of Solid/Plasma VALUE seeds

    avg_coherence * 0.30 +          # Mean cross-member seed coherence

    avg_emotional_density * 0.20 +  # Mean emotional density across value
seeds

    time_stable_ratio * 0.15 +      # % of seeds that have passed
time-lock

    (1 - extraction_penalty) * 0.10 # Absence of extraction warning
patterns

)
```

FOT Warning Indicators

*The system must also track **negative indicators** that suggest FOT is failing or being undermined:*

Warning	***Detection Method***

Increasing defensive/hostile interactions	*Sentiment analysis on conversations*
In-group/out-group formation	*Clustering analysis on seed coherence*
Voice concentration in fewer speakers	`expression_count` *distribution analysis*
Topic/perspective avoidance	*Dimension coverage gaps*
Benefit extraction by few	*Reciprocity analysis*

These warning indicators serve as a community health dashboard — visible to community facilitators, not used punitively against individuals.

7.6 What Gets Stored From a Single Conversation

The stages above describe the conceptual transformation. Here is concretely what the system writes to the database during and after one profiling session, mapped to both stages and elements:

DURING the conversation (real-time writes):

What	***Where it's stored***	***Stage***	***Elements active***
Every message (user + AI)	`conversations.messages` *— JSONB array*	*Raw Data*	*1 seed, 2 seed pattern*

```
{ role, content,
timestamp,
voice_transcript? }
```

AT THE END of the conversation (post-session processing):

What	***Where it's stored***	***Stage***	***Elements active***

New seeds	`seeds` *table — one row per seed*	*Information*	*3 story, 6 correlations*
Updated seeds	`seeds` *table — existing rows*	*Conversation → Comprehension*	*7 coherence, 8 alignment*
Why-Cards	`seeds.why_card_id` + `profiles.why_cards`	*Conversation*	*4 signature, 11 values*
Session metadata	`conversations` *row*	*Information*	*6 correlations*
Seed embeddings	`seeds.embedding` *— vector(1536) each*	*Conversation → Comprehension*	*7 coherence, 8 alignment*
Profile updates	`profiles` *row*	*Comprehension*	*5 meaning, 9 integrity*
Profile embedding	`profiles.profile_embedding` *— vector(1536)*	*Comprehension*	*8 alignment*
Coherence edges *(async)*	*Computed across members' seeds*	*Community*	*10 interrelated, 14 value network*

7.7 Concrete Example — One Conversation, All Outputs

A member named Aroha has her third conversation. She's at Gate 2 (Acknowledgment), matter state Liquid. Here's everything the system produces:

1. Conversation record *(stored in* `conversations`*):*

```
{
  "id": "conv_789",
  "user_id": "aroha_uuid",
  "mode": "voice",
  "gate_at_start": 2,
  "gate_at_end": 2,
  "cycle_number": 1,
  "messages": [
    { "role": "ai", "content": "When we last spoke, you were exploring what acknowledgment means in your whānau...", "timestamp": "..." },
    { "role": "user", "content": "Yeah, I've been thinking about that. I realised I keep giving without checking if people actually want what I'm giving...", "timestamp": "..." },
    { "role": "ai", "content": "What does that realisation stir in you?", "timestamp": "..." },
    { "role": "user", "content": "It's like... I need to listen before I act. Not assume I know what someone needs. That's been a pattern my whole life.", "timestamp": "..." }
  ],
  "extracted_data": {
    "seeds_created": ["seed_new_001"],
    "seeds_updated": ["seed_existing_042"],
    "why_cards_generated": ["why_301"]
  },
  "duration_seconds": 720
}
```

2. New seed created *(stored in* `seeds`*):*

```
{
```

```
  "id": "seed_new_001",
  "user_id": "aroha_uuid",
  "label": "Receptive Generosity",
  "kernel": "Giving that begins with listening — understanding what's
actually needed before acting",
  "foundation": "value",
  "matter_state": "gas",
  "confidence": 0.52,
  "emotional_density": 0.71,
  "gate_detected": 2,
  "evidence": [
    {
      "statement": "I keep giving without checking if people actually want
what I'm giving",
      "conversation_id": "conv_789",
      "confidence": 0.52
    }
  ],
  "time_lock_date": "2026-04-03T00:00:00Z",
  "time_lock_satisfied": false,
  "embedding": [0.023, -0.041, ...]
}
```


3. Existing seed updated *(row in* `seeds`*):*

```
seed_existing_042 "Deep Listening"
  expression_count: 2 → 3
  confidence: 0.58 → 0.67
  matter_state: "gas" → "liquid"  (3rd expression, crossed threshold)
```

```
  new evidence appended from conv_789

  embedding: regenerated
```

4. Why-Card generated *(stored in* `profiles.why_cards` *and displayed to Aroha):*


```
{

  "id": "why_301",

  "seed_id": "seed_new_001",

  "insight": "You seem to be discovering a form of generosity that starts
with listening rather than assuming",

  "evidence_chain": [

    "\"I keep giving without checking if people actually want what I'm
giving\"",

    "\"I need to listen before I act. Not assume I know what someone
needs.\""

  ],

  "confidence": 0.52,

  "alternative_interpretation": "This could also reflect a need for
validation — wanting to be sure your giving is received well",

  "member_response": null

}
```


5. Profile updated *(row in* `profiles`*):*

```
 total_conversations: 2 → 3

  confidence_level: recalculated from all seed confidences

  four_foundations.values: ["Deep Listening", "Receptive Generosity"]

  profile_embedding: regenerated from all active seeds
```

7.8 How Data Matures Across Conversations

The matter states (elements 17–20) are not stages — they are a maturity dimension that applies across all stages. But as a member progresses through more conversations, their data naturally moves through matter states and reaches deeper into the curve:

Conversations	***Matter State***	***What's happening to the data***	***Deepest stage reached***	***Key elements active***
1–2	*17 Gas (diffuse)*	*Seeds are scattered, low confidence, no matching. Raw data becoming information.*	*Information*	*1 seed, 2 seed pattern, 3 story*
3–7	*18 Liquid (flowing)*	*Seeds cluster. Patterns repeat. Why-Cards validate. Coherence emerges. Early matching possible.*	*Conversation*	*4 signature, 6 correlations, 7 coherence, 11 values*
7+	*19 Solid (consolidated)*	*Seeds are stable, time-locks satisfied. Profile is reliable. Full matching. Seeds connect across members.*	*Comprehension → Community*	*5 meaning, 8 alignment, 9 integrity, 10 interrelated, 14 value network*
Ongoing	*20 Plasma (transformative)*	*Profile contributes to community-level patterns. Living fractals detectable. Regenerated data feeds back*	*Community → feedback loop*	*15 mythology, 16 synergistic, regenerated data*

	into Information.	

7.9 What Lives Where — The Six Tables

A simple reference for where each type of data lives:

Table	***What it holds***	***Lifecycle***
`conversations`	*The raw transcript — every message, timestamps, mode, gate positions. One row per session.*	*Append-only. Never modified after session ends. This is the audit trail.*
`seeds`	*The extracted meaning — each detected pattern as a discrete unit with its own embedding, confidence, evidence chain, matter state, and LJMAP position. One row per seed per member.*	*Grows and evolves. Seeds are created, updated (confidence, expression count, matter state), and can decay.*
`profiles`	*The summary — current gate position, overall matter state, four foundations summary, profile-level embedding, FOT readiness score, why-cards, evolution events. One row per member.*	*Recomputed after each conversation from the current state of the member's seeds.*
`correlations`	*Seed-to-seed coherence relationships — computed via pgvector cosine similarity on embeddings. Tracks both within-member and cross-member correlations.*	*Recomputed when seed embeddings change. Cross-member correlations are the basis for witnessed resonance (Trust Formula step 2).*
`value_mappings`	*LJMAP reference data — 130+ canonical value words mapped to developmental columns (1–9) and cycles (1–3).*	*Static reference table. Seeded once from the LJMAP framework.*

`fot_scores`	*FOT readiness time-series — snapshots of each member's Trust Formula factors after each conversation.*	*Append-only time-series. One row per calculation. Enables tracking FOT readiness progression over time.*

*The flow is: **conversations** (raw) → **seeds** (extracted meaning) → **profiles** (summary). Conversations are never modified. Seeds evolve. The profile is always a derivative of the seeds. **Correlations** connect seeds across members. **FOT scores** track the Trust Formula over time. **Value mappings** provide the developmental reference frame.*

8. Seeds as Graph Nodes

8.1 The Core Insight: The Node Is the Seed

*In Vic's framework, a **Seed Pattern** is the fundamental unit of community intelligence — a compact generative packet that encodes how a community perceives, reasons, acts, measures, and governs around a particular domain. The AME graph previously represented member expressions as flat chips (values, visions, vehicles). The new model replaces these with **seeds**: every meaningful expression the AI detects during profiling becomes a seed node in the graph.*

*This eliminates the need for rigid node categories. A passion, a project, a value, a belief, a challenge, an initiative — all are seeds, distinguished not by arbitrary type labels but by their **Four Foundations classification** and **matter state maturity**.*

8.2 What Makes a Seed

A seed is created when the AI detects a pattern with sufficient confidence (>40%) during a profiling conversation. The AI doesn't just classify — it extracts the kernel of what the member expressed and packages it as a seed.

Seed creation triggers:

- *A value, need, belief, or principle is detected with >40% confidence*
- *A recurring theme appears across 2+ messages within a session*
- *The member affirms a Why-Card (confirming the AI's detection)*
- *A member explicitly names something important to them*

What a seed contains:

Field	***Description***

`label`	*Short name — "Authentic Inquiry", "Neighbourhood Food Co-op", "Radical Transparency"*
`kernel`	*A 1-2 sentence distillation of what this seed means to the member*
`foundation`	*Four Foundations classification:* `need`, `belief`, `principle`, `value`
`matter_state`	*Maturity:* `gas`, `liquid`, `solid`, `plasma`
`confidence`	*0.0–1.0, how certain the system is about this seed's classification*
`emotional_density`	*0.0–1.0, how much weight/feeling the member expressed around this*
`domain`	*Which of the 22 Archetypal Domains this seed relates to (if identifiable)*
`ljmap_column`	*For VALUE seeds: which LJMAP developmental column (1–9) this value maps to*
`ljmap_cycle`	*For VALUE seeds: which developmental cycle (1–3) — Self-Worth, Self-Expression, Selfless Expression*
`gate_detected`	*Which gate in the 8-Gate journey this seed emerged from*
`evidence`	*Array of conversation references (quotes, timestamps, conversation IDs)*
`why_card_id`	*Link to the Why-Card that surfaced this seed to the member*
`time_lock_date`	*30 days after first detection — seed is not used for matching until then*

`embedding`	*vector(1536) — semantic embedding of this seed for coherence matching*

8.3 Visual Grammar — How Seeds Appear in the Graph

Seeds are satellite nodes orbiting each person node in the 3D graph. Their visual properties encode meaning across three spatial and three material dimensions:

Colour → Four Foundations type:

Foundation	***Colour***	***Rationale***
Value	*Gold/Amber*	*The generative core — values create trust fields*
Principle	*Blue*	*Structure, rules, operational clarity*
Belief	*Green*	*Growth, epistemological — what they think is true*
Need	*Red/Warm*	*Biological/psychological — grounding, survival*

Opacity/Glow → Matter state:

State	***Visual***
Gas	*Faint, translucent, small — barely forming*
Liquid	*Semi-transparent, medium — taking shape*
Solid	*Fully opaque, prominent — stable and reliable*

Plasma	*Glowing/pulsing — regenerative, contributing to system-wide patterns*

Size → Emotional density: *Seeds with higher emotional density (the member expressed strong feeling about them) appear larger. A deeply-held value is visually heavier than a casually mentioned one.*

Edges between seeds:

- *When two members share seeds with high semantic similarity (embedding cosine distance), an edge connects those seeds*
- *Edge thickness encodes coherence strength — not just keyword match but meaning alignment*
- *This replaces the old chip-label matching entirely*

8.4 Seed Lifecycle

Seeds are not static. They evolve across conversations:

1. ***Detection*** *(Gas) — AI notices a pattern, creates a seed at low confidence*
2. ***Validation*** *— Why-Card is shown; member confirms, corrects, or rejects*
3. ***Deepening*** *(Liquid) — same theme resurfaces in later conversations, confidence grows*
4. ***Stabilisation*** *(Solid) — after 30 days + sufficient confidence, seed becomes matchable*
5. ***Regeneration*** *(Plasma) — seed connects to other members' seeds, participates in community-wide pattern detection (living fractals)*
6. ***Decay*** *— seeds that are never re-expressed across multiple sessions may fade (confidence decays) rather than being deleted. The member can always revive them.*

8.5 Seed Data Schema

```
-- ═══════════════════════════════════════════════

-- seeds table — the fundamental graph node unit

-- ═══════════════════════════════════════════════

CREATE TABLE seeds (

  id              UUID PRIMARY KEY DEFAULT gen_random_uuid(),

  user_id         UUID REFERENCES auth.users(id) ON DELETE CASCADE,

  profile_id      UUID REFERENCES profiles(id) ON DELETE CASCADE,


  -- Core identity
```

```
  label           TEXT NOT NULL,

  kernel          TEXT,                           -- 1-2 sentence meaning
distillation

  foundation      TEXT NOT NULL

                  CHECK (foundation IN
('need','belief','principle','value')),


  -- Maturity

  matter_state    TEXT DEFAULT 'gas'

                  CHECK (matter_state IN
('gas','liquid','solid','plasma')),

  confidence      FLOAT DEFAULT 0.0,

  emotional_density FLOAT DEFAULT 0.0,


  -- Classification

  domain          TEXT,                           -- one of the 22
Archetypal Domains

  gate_detected   INT CHECK (gate_detected BETWEEN 0 AND 8),


  -- LJMAP column mapping (for VALUE-foundation seeds only)

  ljmap_column    INT CHECK (ljmap_column BETWEEN 1 AND 9),

  ljmap_cycle     INT CHECK (ljmap_cycle BETWEEN 1 AND 3),


  -- Evidence chain

  evidence        JSONB DEFAULT '[]'::jsonb,

  -- Each: { statement, conversation_id, timestamp, confidence }


  -- Why-Card link

  why_card_id     UUID,
```

```
  -- Time-lock (anti-gaming)
  first_detected  TIMESTAMPTZ DEFAULT now(),
  time_lock_date  TIMESTAMPTZ,                   -- first_detected + 30
days
  time_lock_satisfied BOOLEAN DEFAULT false,

  -- Semantic embedding for coherence matching
  embedding       vector(1536),

  -- Lifecycle
  expression_count INT DEFAULT 1,                -- how many times
re-expressed
  last_expressed   TIMESTAMPTZ DEFAULT now(),
  is_active        BOOLEAN DEFAULT true,          -- false = decayed /
faded

  created_at      TIMESTAMPTZ DEFAULT now(),
  updated_at      TIMESTAMPTZ DEFAULT now()
);

-- Indexes
CREATE INDEX seeds_user_id_idx ON seeds(user_id);
CREATE INDEX seeds_foundation_idx ON seeds(foundation);
CREATE INDEX seeds_embedding_idx ON seeds USING ivfflat (embedding
vector_cosine_ops);

-- RLS
ALTER TABLE seeds ENABLE ROW LEVEL SECURITY;
```

```sql
CREATE POLICY "seeds_read_all" ON seeds FOR SELECT USING (true);

CREATE POLICY "seeds_owner_write" ON seeds FOR ALL USING (auth.uid() =
user_id);


-- ═══════════════════════════════════════════════════════════════

-- correlations table — seed-to-seed coherence relationships

-- ═══════════════════════════════════════════════════════════════

CREATE TABLE correlations (

  id               UUID PRIMARY KEY DEFAULT gen_random_uuid(),


  -- The two seeds being correlated

  seed_a_id        UUID REFERENCES seeds(id) ON DELETE CASCADE NOT NULL,

  seed_b_id        UUID REFERENCES seeds(id) ON DELETE CASCADE NOT NULL,


  -- Correlation strength (cosine similarity of embeddings)

  coherence_score FLOAT NOT NULL CHECK (coherence_score BETWEEN 0.0 AND
1.0),


  -- Relationship type

  correlation_type TEXT DEFAULT 'semantic'

                   CHECK (correlation_type IN
('semantic','thematic','values_aligned')),


  -- Computed metadata

  is_cross_member BOOLEAN DEFAULT false,  -- true if seeds belong to
different users


  created_at       TIMESTAMPTZ DEFAULT now(),

  updated_at       TIMESTAMPTZ DEFAULT now(),
```

```sql
  -- Ensure no duplicate pairs (unordered)
  UNIQUE (seed_a_id, seed_b_id),
  CHECK (seed_a_id < seed_b_id)  -- Enforce ordering to prevent (a,b) and
(b,a)
);

CREATE INDEX correlations_seed_a_idx ON correlations(seed_a_id);
CREATE INDEX correlations_seed_b_idx ON correlations(seed_b_id);
CREATE INDEX correlations_cross_member_idx ON
correlations(is_cross_member);
CREATE INDEX correlations_coherence_idx ON correlations(coherence_score
DESC);

ALTER TABLE correlations ENABLE ROW LEVEL SECURITY;
CREATE POLICY "correlations_read_all" ON correlations FOR SELECT USING
(true);

-- ═══════════════════════════════════════════════════════════════════
-- value_mappings table — LJMAP reference data (130+ canonical values)
-- ═══════════════════════════════════════════════════════════════════
CREATE TABLE value_mappings (
  id              UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  value_label     TEXT NOT NULL UNIQUE,         -- Canonical value name
from LJMAP
  ljmap_column    INT NOT NULL CHECK (ljmap_column BETWEEN 1 AND 9),
  ljmap_cycle     INT NOT NULL CHECK (ljmap_cycle BETWEEN 1 AND 3),
  description     TEXT,
  created_at      TIMESTAMPTZ DEFAULT now()
```

```
);


-- Seed the 130+ values from LJMAP (abbreviated — full list in migration
file)

INSERT INTO value_mappings (value_label, ljmap_column, ljmap_cycle) VALUES

-- Cycle 1: Journey of Self-Worth

('Affection', 1, 1), ('Comfort', 1, 1), ('Dependent', 1, 1), ('Physical',
1, 1),

('Safe', 1, 1), ('Self-control', 1, 1), ('Sensuous', 1, 1), ('Sustenance',
1, 1), ('Wonder', 1, 1),

('Beautifying', 2, 1), ('Economical', 2, 1), ('Exemplars', 2, 1),
('Exploring', 2, 1),

('Fair', 2, 1), ('Friendly', 2, 1), ('Hope', 2, 1), ('Lawfulness', 2, 1),
('Membership', 2, 1),

('Achieving', 3, 1), ('Amending', 3, 1), ('Communicating', 3, 1),
('Competing', 3, 1),

('Confident', 3, 1), ('Dependable', 3, 1), ('Diligent', 3, 1),
('Efficient', 3, 1),

-- Cycle 2: Journey of Self-Expression (Columns 4-6)

('Brave', 4, 2), ('Considerate', 4, 2), ('Consistent', 4, 2), ('Ethical',
4, 2),

('Honest', 4, 2), ('Humble', 4, 2), ('Independent', 4, 2), ('Quality', 4,
2),

('Adapting', 5, 2), ('Appreciating', 5, 2), ('Authentic', 5, 2),
('Empathizing', 5, 2),

('Healing', 5, 2), ('Justice', 5, 2), ('Service', 5, 2),

('Aesthetic', 6, 2), ('Creating', 6, 2), ('Envisioning', 6, 2),
('Teamwork', 6, 2),

-- Cycle 3: Journey of Selfless Expression (Columns 7-9)

('Architect', 7, 3), ('Compassion', 7, 3), ('Holistic', 7, 3),
('Integrating', 7, 3),

('Interdependent', 7, 3),
```

```
('Co-evolutionary', 8, 3), ('Guardian', 8, 3), ('Humanitarian', 8, 3),
('Transforming', 8, 3),

('Knowing', 9, 3), ('Presence', 9, 3), ('Vitality', 9, 3)

-- (Column 6-9 omitted for brevity — include full list in migration file)

;


CREATE INDEX value_mappings_label_idx ON value_mappings(value_label);

CREATE INDEX value_mappings_column_idx ON value_mappings(ljmap_column);


-- ═══════════════════════════════════════════════════════════════

-- fot_scores table — FOT readiness tracking over time

-- ═══════════════════════════════════════════════════════════════

CREATE TABLE fot_scores (

  id               UUID PRIMARY KEY DEFAULT gen_random_uuid(),

  user_id          UUID REFERENCES auth.users(id) ON DELETE CASCADE NOT
NULL,


  -- Score components (Trust Formula factors)

  values_coherence     FLOAT DEFAULT 0.0,   -- Do they have
VALUE-classified seeds?

  emotional_density_avg FLOAT DEFAULT 0.0, -- Average seed emotional
density

  witness_score        FLOAT DEFAULT 0.0,   -- Are their values witnessed
by others?

  time_stability       FLOAT DEFAULT 0.0,   -- Consistency over time
(time-lock ratio)


  -- Composite FOT readiness (0.0-1.0)

  fot_readiness        FLOAT DEFAULT 0.0,
```

```
  -- Timestamp for historical tracking
  calculated_at       TIMESTAMPTZ DEFAULT now(),

  -- Snapshot of contributing factors
  snapshot            JSONB DEFAULT '{}'::jsonb
);

CREATE INDEX fot_scores_user_time_idx ON fot_scores(user_id, calculated_at
DESC);

ALTER TABLE fot_scores ENABLE ROW LEVEL SECURITY;
CREATE POLICY "fot_scores_owner_read" ON fot_scores FOR SELECT USING
(auth.uid() = user_id);
```

8.6 How the AI Creates Seeds During Conversation

During each profiling session, the AI performs seed extraction as a secondary structured output call after each substantive member response:

```
{
  "seed_detected": true,
  "label": "Collective Stewardship",
  "kernel": "A belief that land and resources should be cared for
communally, not owned individually",
  "foundation": "value",
  "emotional_density": 0.72,
  "domain": null,
  "evidence": {
    "statement": "I keep coming back to this idea that none of us really
own anything — we're just looking after it for a while",
    "confidence": 0.65
```

```
  },
  "is_new": true,
  "existing_seed_id": null
}
```

When `is_new` is `false`, the AI has recognised a previously-detected seed resurfacing — `existing_seed_id` points to the seed to update (increment `expression_count`, add evidence, potentially increase `confidence` and advance `matter_state`).

---

9. Integration with the Existing AME

9.1 ProfilePanel Changes

`ProfilePanel.vue` currently shows three ChipList editors for the 3 layers. This will be replaced by:

***Tab 1: Identity** — name, avatar, location, contact (unchanged)*

***Tab 2: Profiler** — the AI conversation UI:*

- *Mode selector (voice/chat) on first visit*
- *Active conversation interface (streaming chat bubbles or voice visualiser)*
- *"Continue your journey" for returning users showing current gate + cycle*
- *Why-Card inbox — cards awaiting the member's validation*

***Tab 3: Your Profile** — a read-only view of what the system has learned:*

- *Current matter state with plain-language explanation*
- *Seed gallery — all detected seeds, grouped by foundation type, sized by emotional density*
- *Gate journey visualisation (which gates completed, current position)*
- *Evolution timeline*

*The old chip lists are **removed** from this panel entirely.*

9.2 Graph Visualisation — 3d-force-graph

*The 2D Cytoscape.js graph is replaced by a 3D force-directed graph using **3d-force-graph** — a Three.js-based library by the same author as Globe.GL (already in the project). This gives seeds a true spatial dimension and makes the multi-axis visual grammar (colour, opacity, size) far more expressive.*

Why 3d-force-graph:

- *Built on Three.js (already a project dependency via Globe.GL) — no new rendering stack*
- *Full per-node customisation via `nodeThreeObject()` — custom meshes with any colour, opacity, size, geometry*
- *3D force layout natively (d3-force-3d) — nodes self-organise in space based on edge weights*
- *Interactive: zoom, rotate, pan, click, hover, drag — all built in*
- *Same maintainer (vasturiano) as Globe.GL — shared API conventions*
- *`three-forcegraph` variant can embed into an existing Three.js scene, potentially merging with Globe.GL for a unified 3D view*

Node types in the graph:

1. ***Person nodes** — central identity node for each member (custom `THREE.Mesh` with avatar texture or initials)*
2. ***Seed nodes** — satellite nodes orbiting each person, rendered as custom `THREE.Mesh` objects:*
    - *Colour = foundation type (Gold/Blue/Green/Red — see Section 8.3)*
    - *Opacity = matter state (`MeshPhongMaterial({ transparent: true, opacity })`)*
    - *Size = emotional density (geometry radius scaled by `emotional_density`)*
    - *Plasma seeds get a glow effect (`THREE.PointLight` or emissive material)*

Edge types:

1. ***Person** → **Seed** — ownership edge, connecting a member to their seeds*
2. ***Seed** ↔ **Seed** — coherence edges between semantically similar seeds belonging to different members. Computed via pgvector cosine similarity on `seeds.embedding`. This replaces chip-label matching entirely.*
3. ***Person** ↔ **Person** — aggregate affinity edge, derived from the total coherence weight of their connected seeds. Optional — may be redundant if seed-level edges are visible.*

***Edge weight encodes coherence matching** (A9.1 from the spec), not surface similarity. Two members whose seeds use different words but carry similar meaning ("truth-seeking" and "authentic inquiry") will still be connected.*

Vue 3 integration pattern:

```
import ForceGraph3D from '3d-force-graph'


onMounted(() => {

  const graph = ForceGraph3D()(containerRef.value)

    .graphData({ nodes, links })

    .nodeThreeObject(node => {
```

```
      if (node.type === 'person') return createPersonMesh(node)

      // Seed node — encode foundation, matter state, emotional density

      const radius = 2 + node.emotional_density * 6

      const geometry = new THREE.SphereGeometry(radius)

      const material = new THREE.MeshPhongMaterial({

        color: foundationColor[node.foundation],

        transparent: true,

        opacity: matterStateOpacity[node.matter_state],

        emissive: node.matter_state === 'plasma' ?
foundationColor[node.foundation] : 0x000000,

        emissiveIntensity: node.matter_state === 'plasma' ? 0.4 : 0

      })

      return new THREE.Mesh(geometry, material)

    })

    .onNodeClick(handleNodeClick)

    .onNodeHover(handleNodeHover)

})
```

Filtering and progressive disclosure:

- *By default, only Solid and Plasma seeds are shown (Gas/Liquid are too unstable to display usefully)*
- *A filter toggle lets members reveal their own Gas/Liquid seeds*
- *Seeds can be filtered by foundation type (show only values, only beliefs, etc.)*
- *Time-locked seeds (< 30 days old) are visually distinct (reduced emissive, dimmed) to indicate they are not yet matchable*

Migration note: `InteractiveCytoscapeMany.vue` *will be replaced by a new* `ForceGraph3D.vue` *component. The existing Cytoscape component can be retained temporarily for comparison during development.*

9.3 Recommendations Pipeline

The current Ollama-based recommendations pipeline compares `layer*_list` content. It will be updated to:

1. *Pull seed embeddings from the `seeds` table for each member*
2. *Run pgvector similarity search across seeds as the primary match signal*
3. *Use seed labels and kernels for the human-readable "reason" in the recommendation*
4. *Respect the `time_lock_satisfied` flag — do not recommend matches involving seeds < 30 days old*
5. *Weight VALUE-foundation seeds more heavily than other foundation types in match scoring*

---

10. Open Questions for Vic & Ian

These are the areas where we need Vic's theoretical direction or Ian's technical decision before building.

For Vic — Theoretical Clarification

Q1: Validating the seed-as-node model *We've arrived at the understanding that the node is the seed. Every expression the AI detects — a passion, a project, a value, a belief, a challenge, an initiative — becomes a seed node in the graph. Seeds are classified by their Four Foundations type (Need/Belief/Principle/Value) and their matter state maturity (Gas → Liquid → Solid → Plasma), rather than by rigid categories like "projects" or "goals." This means the graph grows organically from authentic conversation rather than from predetermined taxonomies. Does this align with your intent for seed patterns? Are Four Foundations + matter state sufficient as the two classification axes, or is something missing?*

Q2: The 22 Archetypal Domains *(partially answered) Enfoldment 7 references 22 Archetypal Domains that seeds can belong to. The FOT Definition Document (V2) provides the* ***6 domain clusters*** *but not the full 22 individual domains:*

Domain Cluster	***Examples***
Foundational	*Spirituality, Governance, Economics*
Creative	*Arts, Music, Storytelling*
Practical	*Food, Shelter, Technology*

Healing	*Health, Therapy, Conflict Resolution*
Learning	*Education, Mentorship, Research*
Relational	*Family, Friendship, Partnership*

Still needed from Vic: *The full enumeration of all 22 individual domains within these 6 clusters, with brief descriptions. We'd like to use domains as an optional property on each seed (a secondary axis beyond foundation type), enabling domain-based filtering on the graph and domain-level community pattern detection.*

Q3: Gate 0 in onboarding *Gate 0 (Principles of Integrity) is described as the foundation that all other gates reference. Should the very first onboarding session include a Gate 0 exploration, or does it emerge organically from the Gate 1 conversation? If it's a dedicated gate, where does it sit in the first session?*

Q4: V-Crystal in early profiling *Shadow work (V-Crystal — Victor/Victim/Villain/Virtuous/Vengeful/Vulnerable positions) is deep material. Which gate does it first become appropriate for the AI to surface V-Crystal observations? Gate 2+ (Acknowledgment)?*

Q5: Gas-state seeds on the community map *A new member with only 1-2 conversations will have Gas-state seeds — low confidence, still forming. Should Gas-state seeds be visible on the graph at all (even to the member themselves), or should they only appear once they reach Liquid state? What does a member's node look like when they have no visible seeds yet?*

Q6: Community Signature *The spec describes a Community Signature — the collective pattern of a community across all dimensions. At what point does the AME use individual seed data to generate/update the community's signature? Is this manual (community organiser triggers it) or automatic once enough members reach Solid state?*

Q7: The 13 Micro Dimensions vs the 10 Profiling Dimensions *The spec defines both 10 Profiling Dimensions and 13 Micro Dimensions. Should both be tracked from the start, or does the AME begin with the 10 and add micro-dimensions as the profile matures?*

For Ian — Technical Decisions

Q8: Migration from 3-layer chips *Existing members have* `layer1_list`, `layer2_list`, `layer3_list` *data. Three options:*

- ***A)*** *Preserve existing chip data permanently alongside seeds (additive)*
- ***B)*** *Convert existing chips to seeds (with low confidence, no evidence — synthetic bootstrap)*
- ***C)*** *Archive chip data and prompt existing members to do their first profiling session, starting fresh*

Option C is cleanest and most aligned with the seed philosophy (no synthetic data). Option B risks polluting the seed pool with low-quality signals.

Q9: Conversation history in Supabase vs separate storage *Full conversation transcripts could get large over time (especially voice transcripts). Should* `conversations.messages` *stay in Supabase JSONB, or should message content be stored in Supabase Storage (as JSON files) with only metadata in the DB?*

Q10: Realtime during profiling sessions *The existing Supabase Realtime subscription is used for live position sync on the graph. During a profiling session, should new seed creation trigger a Realtime broadcast (so other users see the graph grow live), or should seed updates be batched and only visible after the session ends?*

Q11: Seed extraction — inline or separate call? *Seed extraction after each member message could be handled inline by the main* `gpt-5-mini` *model (via structured output / tool use) or as a separate API call. Inline is faster and cheaper (one call); separate is cleaner and easier to debug. Recommend starting inline and splitting out if classification quality suffers.*

---

11. What Gets Built First (Suggested Sequence)

1. ***Supabase migration*** *— add* `profiles`, `seeds`, `conversations`, `correlations`, `value_mappings`, *and* `fot_scores` *tables; pgvector extension; LJMAP seed data*
2. ***System prompt*** *— base + gate 1 instruction, tested via direct API calls against* `gpt-5-mini-2025-08-07`
3. ***Chat mode UI*** *— new* `ProfilerPanel.vue` *component with streaming chat interface (*`gpt-5-mini`*)*
4. ***Seed extraction pipeline*** *— Four Foundations classifier + seed creation/update logic + LJMAP column mapping for VALUE seeds*
5. ***Why-Card system*** *— generation, display component, and member validation flow*
6. ***3D graph*** *— replace Cytoscape with* `3d-force-graph`*;* `ForceGraph3D.vue` *component with seed visual grammar (colour/opacity/size), seed-to-seed coherence edges*
7. ***Embedding pipeline*** *— generate and store seed embeddings via* `text-embedding-3-small`*, pgvector similarity queries, populate* `correlations` *table*
8. ***FOT readiness tracking*** *— Trust Formula calculation after each conversation,* `fot_scores` *time-series, FOT readiness display in profile view*
9. ***Voice mode*** *— WebRTC integration with* `gpt-realtime-mini-2025-12-15`
10. ***Seed lifecycle*** *— matter state progression, time-locking, confidence decay*
11. ***FOT warning indicators*** *— community health dashboard (Phase 1 basic version)*

This spec is a working document. Sections marked with open questions should be revisited with Vic before implementation begins.