Lab Number : 33 Date:2026/03/19

Title: Configuring SSH server to allow/deny login for selected hosts only.

1.Open SSH configuration file

Command:

```
root@localhost:/# sudo vi /etc/ssh/sshd_config
```

2. Allow login only from a specific IP or name

Command:

```
# override default of no subsystems
Subsystem       sftp    /usr/libexec/openssh/sftp-server

# Example of overriding settings on a per-user basis
#Match User anoncvs
#       X11Forwarding no
#       AllowTcpForwarding no
#       PermitTTY no
#       ForceCommand cvs serve
AllowUsers student
AllowUsers student@192.168.0.1*
```

3. Deny login from specific hosts/users.

Command:

```
# override default of no subsystems
Subsystem       sftp    /usr/libexec/openssh/sftp-server

# Example of overriding settings on a per-user basis
#Match User anoncvs
#       X11Forwarding no
#       AllowTcpForwarding no
#       PermitTTY no
#       ForceCommand cvs serve
DenyUsers production
-- INSERT --                                                    133,21
```

4. Restart SSH service

```
root@localhost:/# sudo systemctl restart sshd
```

Status:

```
root@localhost:/# sudo systemctl status sshd
● sshd.service - OpenSSH server daemon
     Loaded: loaded (/usr/lib/systemd/system/sshd.service; enabled; preset: ena>
     Active: active (running) since Thu 2026-03-19 07:37:36 +0545; 11s ago
 Invocation: 2fc250ac232f4ecea0432f013f216b79
       Docs: man:sshd(8)
             man:sshd_config(5)
   Main PID: 8122 (sshd)
      Tasks: 1 (limit: 20120)
     Memory: 1.2M (peak: 1.5M)
        CPU: 20ms
     CGroup: /system.slice/sshd.service
             └─8122 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Mar 19 07:37:36 localhost.localdomain systemd[1]: Starting sshd.service - OpenS>
Mar 19 07:37:36 localhost.localdomain sshd[8122]: Server listening on 0.0.0.0 p>
Mar 19 07:37:36 localhost.localdomain sshd[8122]: Server listening on :: port 2>
Mar 19 07:37:36 localhost.localdomain systemd[1]: Started sshd.service - OpenSS>
lines 1-17/17 (END)
```