

```
Poojashree@localhost:~  
[Poojashree@localhost ~]$ vi sender.c  
[Poojashree@localhost ~]$ gcc sender.c -o sender  
[Poojashree@localhost ~]$ ./sender  
[Poojashree@localhost ~]$
```

```
Poojashree@localhost:~  
[Poojashree@localhost ~]$ vi receiver.c  
[Poojashree@localhost ~]$ gcc receiver.c -o receiver  
[Poojashree@localhost ~]$ ./receiver  
Message Received: Welcome to Shared Memory  
[Poojashree@localhost ~]$
```

Poojashree@localhost:~ — vi sender.c

Poojashree@localhost:~ — vi sender.c

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
#define SharedMemSize 50
void main(){
char c;
int shmid;
key_t key;
char *shared_memory;
key = 5677;
if ((shmid = shmget(key, SharedMemSize, IPC_CREAT | 0666)) < 0){
perror("shmget");
exit(1);
}
if((shared_memory= shmat(shmid, NULL, 0)) == (char *) -1) {
perror("shmat");
exit(1);
}
sprintf(shared_memory," Welcome to Shared Memory");
sleep(2);
exit(0);
}
```

Poojashree@localhost:~ — vi receiver.c

Poojashree@localhost:~ — vi sender.c

Poojashree@localhost:~ — vi receiver.c

```
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#include <stdlib.h>
#define SharedMemSize 50
void main(){
int shmid;
key_t key;
char *shared_memory;
key = 5677;
if ((shmid = shmget(key, SharedMemSize, 0666)) < 0) {
perror("shmget");
exit(1);
}
if((shared_memory = shmat(shmid, NULL, 0))== (char *) -1) {
perror("shmat");
exit(1);
}
printf("Message Received: %s \n",shared_memory);
exit(0);
-- INSERT --
```