

```
poojashree241801201@localhost:~  
[poojashree241801201@localhost ~]$ touch fork_program.c  
[poojashree241801201@localhost ~]$ ls  
chennai  Documents      marks.awk  _program.c  sample  Templates  
cpu      Downloads     marks.dat  psg         sample.txt test  
delhi    fork          Music      Public      shell_lab Videos  
Desktop  fork_program.c Pictures    salary.awk  tamilnadu  
[poojashree241801201@localhost ~]$ vi fork_program.c  
[poojashree241801201@localhost ~]$
```


poojashree241801201@localhost:~ — /usr/bin/vim fork_progra...

```
if(pid == -1)
{
    printf("CHILD PROCESS NOT CREATED\n");
    exit(0);
}
if(pid == 0)
{
    printf("\n--- CHILD PROCESS ---\n");
    printf("Child process ID: %d\n", getpid());
    printf("Parent Process ID: %d\n", getppid());
}
else
{
    printf("\n--- PARENT PROCESS ---\n");
    printf("Parent Process ID: %d\n", getpid());
    printf("Parent's Parent Process ID: %d\n", getppid());
}
printf("IT CAN BE EXECUTED TWICE\n");
return 0;
}
```

25,1-8

Bot

Mar 16 13:03

poojashree241801201@localhost:~ — /usr/bin/vim fork_progra...

```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
int main()
{
    int pid;
    pid=fork();
    printf("THIS LINE EXECUTED TWICE\n");
    if(pid == -1)
    {
        printf("CHILD PROCESS NOT CREATED\n");
        exit(0);
    }
    if(pid == 0)
    {
        printf("\n--- CHILD PROCESS ---\n");
        printf("Child process ID: %d\n", getpid());
        printf("Parent Process ID: %d\n", getppid());
    }
    else
    {
        printf("\n--- PARENT PROCESS ---\n");
        printf("Parent Process ID: %d\n", getpid());
        printf("Parent's Parent Process ID: %d\n", getppid());
    }
}
```

1,8

Top