TheTestingAcademy

QUALITY ASSURANCE | TEST PLAN | DRAFT

VWO login page | Jira AW-2

Document overview

Ticket summary	[VWO] Add Passkey and SSO Login Options to VWO Login Page
Test basis	AW-2 description and acceptance criteria retrieved from Jira. No linked issues, components, labels, attachments, fix version, or sprint were returned.
Company profile	Company details supplied with the skill: VWO is described as a Bingify product, focused on A/B testing, with 5,000 employees. This profile was not independently verified.
Purpose	Assess the two new login methods while preserving a clear view of missing requirements. This plan is not approved or final.

> **Approval note:** Multiple release-relevant details remain undefined. Resolve the questions in section 3 and obtain QA/product approval before treating this plan as a sign-off basis.

1. Scope and objectives

Objective: Verify that the VWO login page presents the SSO and Passkey options in the specified order; successful authentication reaches the dashboard; failures and unsupported environments give appropriate guidance; and authentication uses secure protocols without exposing sensitive data in the UI or network logs.

In scope

- Visibility and placement of "Sign in using SSO" and "Sign in with Passkey" below "Sign in with Google".
- Successful and failed SSO authentication, including each configured identity provider.
- Successful Passkey authentication when a registered passkey is available and verified.
- Passkey-unavailable, authentication-failure, and unsupported-browser/device feedback.
- Compatibility across the product-approved browser/device support matrix.
- Use of the applicable OAuth, SAML, or WebAuthn protocol and checks for sensitive-data exposure in UI and network logs.
- Focused regression checks for existing login options, based on the ticket's "alongside existing authentication methods" statement.

Out of scope until clarified

- Identity-provider configuration or behavior outside the VWO integration boundary.
- Passkey enrollment, account recovery, account linking, or changes to existing authentication policy; AW-2 does not define these flows.
- Performance, accessibility, localization, and security certification targets not specified in AW-2.

2. Acceptance criteria and traceability

ID	Acceptance criterion from AW-2	Planned coverage
AC-1	Both new buttons appear on the login page, below "Sign in with Google".	TS-01
AC-2	Valid SSO credentials authenticate the user and redirect to the dashboard; invalid credentials show an appropriate error.	TS-02, TS-03
AC-3	A registered, verified passkey authenticates the user and redirects to the dashboard; no available passkey produces fallback or guidance.	TS-04, TS-05
AC-4	Appropriate errors appear for failed SSO authentication, failed Passkey authentication, and unsupported browser/device.	TS-03, TS-06, TS-07
AC-5	Passkey works on supported browsers/devices; SSO works with all configured identity providers.	TS-02, TS-08
AC-6	Authentication follows secure OAuth/SAML/WebAuthn protocols; sensitive data is not exposed in the UI or network logs.	TS-09

AC identifiers are assigned here for traceability; they do not add requirements beyond the ticket description.

3. Gaps and questions for the author

#	Area	Finding	Question to author
1	SSO configuration	Configured identity providers are not named.	Which providers, environments, and configurations must pass before release?
2	SSO outcomes	Redirect destination details and expected behavior for provider outage, cancellation, timeout, or malformed response are not defined.	What destination and user-facing behavior are expected for each outcome?
3	Passkeys	Supported browsers/devices, platform authenticator requirements, and enrolled-account setup are not listed.	What exact browser/device matrix and test-account setup should QA use?
4	Passkey fallback	"Fallback or guidance message" does not define text, action, or fallback authentication path.	What should users see and be able to do when no passkey is available?
5	Error handling	Error content, localization, retry behavior, lockout/rate-limit behavior, and recovery from failed authentication are unspecified.	What messages and retry/security policies are approved for each failure state?
6	Security	Protocols are named, but the flow-to-protocol mapping and required security checks are not defined.	Which protocol applies to each provider and what security validation is release-gating?
7	Privacy/logging	"Network logs" and sensitive data are not scoped; observability and retention requirements are absent.	Which logs, fields, and capture points must be inspected, and what data must never appear?
8	Authorization / account state	Roles, eligible account types, disabled/unverified accounts, and expected access restrictions are not described.	Which account states and roles must be tested for each login method?
9	Regression	New buttons are to appear alongside existing methods, but the regression scope is not stated.	Which existing login flows and dashboard routes are release-critical regression checks?
10	Accessibility / responsive	No keyboard, screen-reader, focus, contrast, layout, or touch requirements are specified.	Which accessibility standard and responsive breakpoints are required?
11	Quality targets	No performance, availability, audit, or monitoring target is provided.	Are measurable non-functional targets required for this change?
12	Delivery context	Test environment, flags, test data, owner, sprint, and fix version are not available in the ticket response.	What environment, test accounts, feature flags, owner, and planned release window should QA use?

#	Area	Finding	Question to author
13	Design and dependencies	No attachment, mockup, linked issue, or component was returned.	Is there an approved design or dependency not linked to AW-2?

4. Requirement checklist

Status key: Present = explicitly stated; Ambiguous = partly stated or insufficient to test precisely; Missing = not stated in AW-2.

Checklist item	Status	Evidence / note
Clear user story / goal	**Present**	Story states the user goal and benefit.
Acceptance criteria are testable	**Ambiguous**	Core outcomes exist; "appropriate", "supported", and "secure" need measurable definitions.
Happy path fully described	**Ambiguous**	SSO and Passkey success are stated; provider setup, session, and exact dashboard destination are not.
Negative / error paths described	**Ambiguous**	Credential/authentication failure and unsupported Passkey environment are named; expected behavior is incomplete.
Boundary and empty states	**Missing**	No limits, empty states, or state boundaries are defined.
State transitions / workflow steps	**Ambiguous**	Login-to-dashboard transitions exist; cancellation, timeout, retry, and recovery are absent.
Required test data	**Missing**	No test accounts, provider accounts, or registered-passkey setup is specified.
Environment / config / feature flags	**Ambiguous**	Supported environments and configured providers are referenced, not enumerated.
External dependencies / integrations	**Ambiguous**	Identity providers are implied, but providers and dependencies are unnamed.
Preconditions / setup	**Missing**	No setup instructions or account preconditions are given.
Performance / load expectations	**Missing**	No performance target is specified.
Security / authorization	**Ambiguous**	Secure protocols and data non-exposure are stated; authorization rules and validation details are absent.
Accessibility expectations	**Missing**	No accessibility requirements are stated.
Internationalization / localization	**Missing**	No language or locale behavior is stated.
Audit / logging / observability	**Ambiguous**	Network logs must not expose sensitive data; audit and observability needs are not specified.
Impact on existing features	**Ambiguous**	New methods are alongside existing methods; regression expectations are not specified.
Backward compatibility / migration	**Missing**	No compatibility or migration requirements are stated.

Checklist item	Status	Evidence / note
Mobile / responsive / browser matrix	**Ambiguous**	Passkey support varies by browser/device; exact matrix and responsive behavior are absent.
Rollback / feature-flag behavior	**Missing**	No rollback or feature-flag behavior is stated.
Unambiguous wording	**Ambiguous**	"Smooth", "appropriate", "supported", and "secure protocols" need clarification.
Terms defined consistently	**Ambiguous**	SSO, configured provider, registered passkey, and supported environment are not defined.
Mockups / designs linked and aligned	**Missing**	No attachment or design link was returned.

5. Test scenarios

Priority guide: **P0** authentication/security release blocker; **P1** core login behavior; **P2** compatibility or conditional coverage. Exact messages, provider-specific behavior, and support boundaries require approved product specifications.

ID	Priority	Type	Scenario and expected result	Maps to
TS-01	**P1**	Positive / UI	Open the login page. Confirm both named options are visible below "Sign in with Google".	AC-1
TS-02	**P0**	Positive / SSO	For each configured identity provider, authenticate with a valid test account. Confirm successful login and the approved dashboard destination.	AC-2, AC-5; G-1, G-2
TS-03	**P0**	Negative / SSO	Attempt SSO with invalid test credentials. Confirm access is denied and an approved error is displayed without exposing sensitive data.	AC-2, AC-4; G-5
TS-04	**P0**	Positive / Passkey	Use an account with a registered passkey in a supported environment and complete verification. Confirm login and the approved dashboard destination.	AC-3, AC-5; G-3
TS-05	**P1**	Negative / Passkey	Use an account with no available registered passkey. Confirm the approved fallback or guidance message and action.	AC-3; G-4

ID	Priority	Type	Scenario and expected result	Maps to
TS-06	**P0**	Negative / Passkey	Cause Passkey verification to fail with a controlled test condition. Confirm authentication is denied and the approved error is shown.	AC-4; G-5
TS-07	**P1**	Boundary / compatibility	Attempt Passkey login in a browser/device confirmed as unsupported. Confirm the approved unsupported-environment guidance and no successful authentication.	AC-4, AC-5; G-3
TS-08	**P1**	Compatibility	Run Passkey login across each product-approved supported browser/device combination. Confirm successful flow where the platform supports the configured passkey.	AC-5; G-3
TS-09	**P0**	Security	Inspect applicable authentication exchanges and UI/network logs. Confirm the configured OAuth, SAML, or WebAuthn flow is used and sensitive data is not exposed.	AC-6; G-6, G-7
TS-10	**P1**	Regression	Verify existing login options remain present and usable after adding SSO and Passkey options. Confirm only approved access reaches the dashboard.	AC-1; G-9
TS-11	**P2**	Negative / SSO	Exercise agreed provider failure conditions such as cancellation, timeout, or unavailable provider. Record results against product-approved expected behavior.	Gap-driven; G-2, G-5
TS-12	**P2**	Accessibility / responsive	After requirements are approved, check keyboard access, focus order, assistive-technology labels, and responsive layout for both new options.	Gap-driven; G-10

ID	Priority	Type	Scenario and expected result	Maps to
TS-13	P1	Authorization / account state	After account eligibility rules are approved, test allowed and restricted accounts with both methods. Confirm authentication and dashboard access follow the approved policy.	Gap-driven; G-8

G-n references the numbered questions in section 3. TS-11 through TS-13 are conditional until expected behavior, policy, and release priority are approved.

6. Test data and environment

- **Data:** Request valid and invalid SSO test accounts for every configured provider; an account with a registered passkey; an account with no available passkey; and a controlled failed-verification case. The ticket does not supply these accounts or setup steps.
- **Environment / flags:** Use a product-approved QA environment with SSO providers and Passkey support configured. Environment URL, flags, provider configuration, and browser/device matrix are pending.
- **Roles / permissions:** Role and account eligibility rules are unspecified. Use only product-approved test identities; confirm required roles/account states with the author.
- **Evidence:** Capture outcomes and sanitized logs only. Do not store credentials, passkey secrets, tokens, or other sensitive values in test evidence.

7. Risks and assumptions

- **Assumptions:** "Dashboard" means the product-approved post-login destination. This plan does not assume a particular URL or redirect policy.
- **Assumptions:** The configured identity providers and supported browser/device list will be supplied by the product team before execution.
- **Risk:** Missing provider, test-account, and support-matrix details can leave authentication paths untested or produce inconsistent results.
- **Risk:** Vague security and error requirements can prevent objective release sign-off.
- **Risk:** Test logs or evidence could expose sensitive values if approved capture and redaction rules are not defined.

8. Entry and exit criteria

Entry

- QA build and environment are available; the feature is enabled as intended for that environment.
- Product confirms configured identity providers, supported browser/device matrix, test accounts, expected errors, and dashboard destination.
- Security and privacy owners define protocol mapping and safe log/evidence inspection guidance.

Exit

- All approved P0 and P1 scenarios pass; failures are documented and triaged by the QA/product owner.
- Every configured provider and approved supported Passkey environment has recorded results.
- No unresolved critical authentication or sensitive-data exposure defect remains. The responsible QA owner approves any accepted residual risk.
- Human review resolves or explicitly accepts the open questions before the plan is used for release sign-off.

9. Resource allocation

QA owner, product contact, identity-provider administrator, and security reviewer are not identified in AW-2. Assign owners before execution. Provider and browser/device coverage depend on access to configured test environments and accounts.

10. Timeline and sprint details

No sprint, fix version, release date, or estimate was returned for AW-2. Schedule test execution after entry criteria are met; the QA lead and product owner must provide dates and sign-off expectations.

Human review gate

> **Assumed:** The goal is to test the login-page options and authentication outcomes stated in AW-2, not to define new product behavior.
>
> **Could not confirm:** Provider list, environment, support matrix, test data, exact errors/fallbacks, security checks, role/account rules, regression boundary, owners, sprint, and release timing.
>
> **Open questions blocking sign-off:** Sections 3 and 4 identify missing or ambiguous requirements. Resolve them or document explicit owner-approved exceptions.
>
> **Approval request:** QA and product owners must review and approve or edit this draft before it is treated as approved. Do not begin test-case or automation authoring from this draft until a human approves it.