

Code

The `<Code>` component renders syntax highlighted code. It is useful when using a [Markdown code block](#) is not possible, for example, to render data coming from external sources like files, databases, or APIs.

Preview

example.md

```
## Welcome
```

```
+Hello from **space**!
```

Import

```
import { Code } from '@astrojs/starlight/components';
```

Usage

Use the `<Code>` component to render syntax highlighted code, for example when displaying code fetched from external sources.

See the [Expressive Code “Code Component” docs](#) for full details on how to use the `<Code>` component and the list of available props.

```
import { Code } from '@astrojs/starlight/components';

export const exampleCode = `console.log('This could come from a file or
CMS!');`;

export const fileName = 'example.js';
export const highlights = ['file', 'CMS'];

<Code code={exampleCode} lang="js" title={fileName} mark={highlights} />
```

Preview

example.js

```
console.log('This could come from a file or CMS!');
```

Display imported code

In MDX files and Astro components, use [Vite's ?raw import suffix](#) to import any code file as a string. You can then pass this imported string to the `<Code>` component to include it on your page.

src/content/docs/example.mdx

```
import { Code } from '@astrojs/starlight/components';
import importedCode from '/tsconfig.json?raw';

<Code code={importedCode} lang="json" title="tsconfig.json" />
```

Preview

tsconfig.json

```
{
  "extends": "astro/tsconfigs/strict",
  "include": [".astro/types.d.ts", "**/*"],
  "exclude": ["dist"]
}
```

<Code> Props

Implementation: [Code.astro](#)

The <Code> component accepts all the props documented in the [Expressive Code “Code Component” docs](#).