


To CompositorFrameSink And Beyond

danakj@chromium.org


Types of compositors through time

- Round 1: Prehistoric
 - Compositor (renderer and browser process)
- Round 2: Ubercompositor
 - Delegating Compositor (renderer process)
 - Direct Compositor (browser process)
- Round 3: Surfaces
 - Layer Compositor (LayerTreeHost + LayerTreeHostImpl)
 - Display Compositor (Display)


1. Prehistoric Compositor




2. Ubercompositor (Direct vs Delegated rendering)




2. Ubercompositor




3. Surfaces



3. Surfaces



3. Surfaces



OutputSurface API

Managing the backbuffer, swapping it, and using overlays.

```
class OutputSurface {  
    virtual void EnsureBackbuffer() = 0;  
    virtual void DiscardBackbuffer() = 0;  
  
    virtual bool IsDisplayedAsOverlayPlane() const = 0;  
  
    virtual void Reshape(const gfx::Size& size,  
                        float device_scale_factor,  
                        const gfx::ColorSpace& color_space,  
                        bool has_alpha) = 0;  
  
    virtual void SwapBuffers(OutputSurfaceFrame frame) = 0;  
};
```

```
class OutputSurfaceClient {  
    virtual void DidReceiveSwapBuffersAck() = 0;  
    virtual void DidLoseOutputSurface() = 0;  
};
```


CompositorFrameSink API

Managing the backbuffer, swapping it,
and using overlays.


```
class CompositorFrameSink {  
    virtual void SubmitCompositorFrame(  
        CompositorFrame frame) = 0;  
};
```

```
class CompositorFrameSinkClient {  
    virtual void DidReceiveCompositorFrameAck() = 0;  
    virtual void DidLoseCompositorFrameAck() = 0;  
  
    // Layer compositor-specific stuff.  
    virtual void SetTreeActivationCallback(  
        const base::Closure& callback) = 0;  
};
```


4. Surfaces++11




4. Surfaces++11



4. Surfaces++11



4. Surfaces++11




Why Display compositor in the Gpu process?

- Vulkan API is very low level, more tightly couples the Vulkan client code to the driver.
- Requires in-process GPU access which is scary for security, want to do it from the sandboxed GPU process.
- Remove the command buffer from the Display compositor's GL contexts (strictly overhead).
- Better scheduling possibilities with frames that take a long time to draw when we can see the actual draw time, not the command buffer time.


Gpu Compositing vs Software Compositing

- What changes in the compositing stack between Gpu vs Software?
1. `cc::CompositorFrameSink` and `cc::OutputSurface` don't come with a GL context (ie null `ContextProvider`)
 2. Results in rastering display lists into bitmaps instead of textures.
 3. `CompositorFrame`'s `DrawQuads` point to shared memory bitmaps instead of textures.
 4. Display compositor uses `cc::SoftwareRenderer` instead of `cc::GLRenderer` to compose all of the `DrawQuads`.

Gpu Compositing



SW Compositing



The End

I hope this was eye opening.

Here's a beautiful cat.

Questions?

