SHIP DESIGN PLANNING NOTES - DECK 3

Cabin 3046 entrance door: the door gives a clear opening of 843 mm.

Crew corridor 3-38
Clear width: 812 mm

Accessible toilet 3-22
Turning space diameter: 1381 mm
Final figures to be confirmed by the yard after detail design.

Superstructure end bulkhead door, frame 32
Door sill height 276 mm above deck

Balcony door 3052 threshold: the threshold is 24 mm high.

Bar counter 19: the table top is at 690 mm.

Fresh water tank capacity 110 m3

SHIP DESIGN PLANNING NOTES - DECK 2

Project RV-0042, page 2

Passenger corridor 2-03
Clear width: 1060 mm

Accessible toilet 2-56
Toilet seat height 400 mm
Final figures to be confirmed by the yard after detail design.

Sun deck railing, deck 2: the guard rail is 933 mm high from the deck.
Arrangement follows the outline specification, revision C.

Cabin 2035 light switch
Mounting height: 1311 mm
All doors on accessible routes are side-hinged.

Accessible cabin 2045 door
Clear opening: 769 mm

Ballast water exchange system
Exchange efficiency 88 %

Hull bottom plate thickness: 302 mm

SHIP DESIGN PLANNING NOTES - DECK 6

Ramp to the pool deck
Ramp running slope 1:13

Gangway ramp, deck 6: the ramp rises with a running slope of 1:15.

Stair to deck 6, handrail
Height above stair nosings: 892 mm

Hull bottom plate thickness: 333 mm