MV NORDIC AURORA - DESIGN SPECIFICATION

Document NA-2026-DS-06, revision B. Basic design, deck 6 and open decks.
Prepared by the outfitting design team for regulatory review.

1. GENERAL

The vessel is a day passenger ship for coastal routes with 400 passengers.
Main particulars are given for reference only and are not part of this review.
Length overall: 92.4 m
Fresh water tank capacity: 45 m3
Main engines: 2 x 3200 kW

2. ACCESSIBLE ROUTES AND CORRIDORS

All public corridors on deck 6 form part of the accessible route.
Corridor 6-01, main passenger corridor: clear width 1100 mm.
Corridor 6-02, passenger corridor to the aft lounge: clear width 850 mm.
Accessible route to cabin 6112: clear width 950 mm.

3. DOORS

Doors on accessible routes are side-hinged and open with one hand.
Cabin 6112 entrance door: clear opening 860 mm.
Public toilet 6-03 door: clear opening 780 mm.
Cabin 6112 door threshold height: 10 mm.
Balcony door 6120 threshold height: 22 mm.

4. RAMPS AND STAIRS

Ramp from the lobby to the pool deck: running slope 1:14.
Aft lobby ramp: running slope 1:10.
Main stair to deck 7: handrail height 900 mm above the stair nosings.
Crew stair aft: handrail height 1010 mm above the stair nosings.

5. ACCESSIBLE CABIN 6112 AND PUBLIC SPACES
Cabin 6112 is the accessible cabin on deck 6, next to the main lift.
Cabin 6112 wheelchair turning space: diameter 1600 mm.
Cabin 6112 bathroom: toilet seat height 450 mm.
Cabin 6112 light switch: mounting height 1300 mm.
Public toilet 6-03: toilet seat height 400 mm.
Reception counter, deck 6: counter top height 800 mm.
Aft lounge bar counter: counter top height 960 mm.

6. OPEN DECKS AND WEATHERTIGHT DOORS
Superstructure end bulkhead door, frame 52: sill height 460 mm above deck.
Forward superstructure end door, frame 118: sill height 300 mm above deck.
Sun deck guard rail: height 1050 mm above the deck.
Mooring deck guard rail: height 940 mm above the deck.

7. BALLAST WATER
Ballast water exchange system: volumetric exchange efficiency 96 %.

8. STRUCTURE (FOR INFORMATION)
Hull bottom plating thickness: 12 mm.

9. NOTES
Final dimensions are confirmed after detail design and yard measurements.
Deviations from this specification require approval by the design manager.