

Literate programming with Python, R, Julia and Stata**

Miguel Portela

Universidade do Minho

1 julho, 2021

Abstract

In this presentation I will discuss how we can enhance the workflow by using literate programming to combine key features of different statistical packages, namely Stata, R, Julia and Python, on the one hand, and Latex as the typesetting system on the other. The goal is to demonstrate and share a template aiming at producing a highly automated report, or research paper, within the same framework. The tasks will run from exploratory data analysis to regression analysis, where the output, from summary to regression tables and figures, is seamlessly included in the final document. Furthermore, important elements of Latex editing, such as automatic referencing, will be highlighted. We aim at freeing the researcher from repetitive tasks to focus on critical and creative writing. Efficiency and replicability will be at the core of the discussion. RStudio will be used to edit and compile R Markdown. The focus will be on producing PDF outputs. In the presentation I will make use of packages such as bookdown, knitr, stargazer, dlookr, ggplot2, plotly, Statamarkdown, reticulate, JuliaCall, pandas, numpy, matplotlib or FixedEffectModels.

**Corresponding address: miguel.portela@eeg.uminho.pt. The current template adapts part of the Rmd code by Paul C. Bauer, Mannheim Centre for European Social Research.

1 Exploratory data analysis

I start by exploring the data **NLSWORK** (National Longitudinal Survey. Young Women 14-26 years of age in 1968).

2 A tibble: 6 x 21


```
idcode year birth_yr age race msp nev_mar grade collgrad not_smsa <dbl> 1 1 70 51 18 2
[black] 0 1 12 0 0 2 1 71 51 19 2 [black] 1 0 12 0 0 3 1 72 51 20 2 [black] 1 0 12 0 0 4 1 73 51 21 2
[black] 1 0 12 0 0 5 1 75 51 23 2 [black] 1 0 12 0 0 6 1 77 51 25 2 [black] 0 0 12 0 0 # ... with 11
more variables: c_city , south , ind_code , # occ_code , union , wks_ue , ttl_exp , tenure , # hours ,
wks_work , ln_wage
```


Table 1: Summary statistics


Statistic	N	Mean	St. Dev.	Min	Pctl(25)	Pctl(75)	Max
idcode	28,534	2,601.284	1,487.359	1	1,327	3,881	5,159
year	28,534	77.959	6.384	68	72	83	88
birth_yr	28,534	48.085	3.013	41	46	51	54
age	28,510	29.045	6.701	14.000	23.000	34.000	46.000
race	28,534	1.303	0.482	1	1	2	3
msp	28,518	0.603	0.489	0.000	0.000	1.000	1.000
nev_mar	28,518	0.230	0.421	0.000	0.000	0.000	1.000
grade	28,532	12.533	2.324	0.000	12.000	14.000	18.000
collgrad	28,534	0.168	0.374	0	0	0	1
not_smsa	28,526	0.282	0.450	0.000	0.000	1.000	1.000
c_city	28,526	0.357	0.479	0.000	0.000	1.000	1.000
south	28,526	0.410	0.492	0.000	0.000	1.000	1.000
ind_code	28,193	7.693	2.994	1.000	5.000	11.000	12.000
occ_code	28,413	4.778	3.065	1.000	3.000	6.000	13.000
union	19,238	0.234	0.424	0.000	0.000	0.000	1.000
wks_ue	22,830	2.548	7.294	0.000	0.000	0.000	76.000
ttl_exp	28,534	6.215	4.652	0.000	2.462	9.128	28.885
tenure	28,101	3.124	3.751	0.000	0.500	4.167	25.917
hours	28,467	36.560	9.870	1.000	35.000	40.000	168.000
wks_work	27,831	53.989	29.032	0.000	36.000	72.000	104.000
ln_wage	28,534	1.675	0.478	0.000	1.361	1.964	5.264

```
[1] "idcode" "year" "birth_yr" "age" "race" "msp"
[7] "nev_mar" "grade" "collgrad" "not_smsa" "c_city" "south"
```

```
[13] "ind_code" "occ_code" "union"      "wks_ue"    "ttl_exp"   "tenure"
[19] "hours"    "wks_work" "ln_wage"
```








```


num [1:28534] 1.45 1.03 1.59 1.78 1.78 ...
- attr(*, "label")= chr "ln(wage/GNP deflator)"
- attr(*, "format.stata")= chr "%9.0g"


```


density.default(x = ln_wage)



N = 28534 Bandwidth = 0.05201







The average age in our data is 29.

3 Tables

R Markdown PDF is now able to produce good tables with our output. For `stargazer` the label is contained in the function, while for `kable` it's contained in the chunk name.

3.1 `stargazer()`: Summary and regression tables

Table 1 shows data's summary statistics.¹ `stargazer()` is an excellent solution to export outputs.

```
library(stargazer)
stargazer(cars,
  title = "Summary table with stargazer",
  label="tab1cars",
  table.placement = "H",
  header=FALSE)
```

¹You can reference the table as 2.

Table 2: Summary table with stargazer

Statistic	N	Mean	St. Dev.	Min	Pctl(25)	Pctl(75)	Max
speed	50	15.400	5.288	4	12	19	25
dist	50	42.980	25.769	2	26	56	120

Table 3 reports regression outputs. Name the models as you can refer to their names in the text (M1, M2, M3).

```
library(stargazer)
model1 <- lm(speed ~ dist, data = cars)
model2 <- lm(speed ~ dist, data = cars)
model3 <- lm(dist ~ speed, data = cars)
stargazer(model1, model2, model3,
  title = "Regression table with stargazer",
  label="tab2",
  table.placement = "H",
  column.labels = c("M1", "M2", "M3"),
  model.numbers = FALSE,
  header=FALSE)
```

Table 3: Regression table with stargazer

	<i>Dependent variable:</i>		
	speed	dist	
	M1	M2	M3
dist	0.166*** (0.017)	0.166*** (0.017)	
speed			3.932*** (0.416)
Constant	8.284*** (0.874)	8.284*** (0.874)	−17.579** (6.758)
Observations	50	50	50
R ²	0.651	0.651	0.651
Adjusted R ²	0.644	0.644	0.644
Residual Std. Error (df = 48)	3.156	3.156	15.380
F Statistic (df = 1; 48)	89.567***	89.567***	89.567***

Note:

*p<0.1; **p<0.05; ***p<0.01

4 Figures

4.1 Graphs with R

You can insert figures like this. One would like to produce and insert them on the fly in the .rmd file. Figure ?? is such an example.

```
plot(cars$speed, cars$dist)
```




Figure 1: Scatterplot of Speed and Distance

(#fig:Figures 1, fig-1)

However, in some cases it does not work.

4.2 Example: ggplot2 graphs

See the ggplot2 output reported in Figure ??.

```
mtcars$cyl <- as.factor(mtcars$cyl) # Convert cyl to factor
library(ggplot2)
ggplot(mtcars, aes(x=wt, y=mpg, shape=cyl)) + geom_point() +
  labs(x="Weight (lb/1000)", y = "Miles/(US) gallon",
       shape="Number of \n Cylinders") + theme_classic()
```




Figure 2: Miles per gallon according to the weight

4.3 Another example using Plotly

With Plotly we can produce interactive graphs which play well, for example, once can embed in html webpages (drop by [here](#) for an example). One can insert this type of graphs in R Markdown PDF using Orca (it generates static images from Plotly graphs). Go [here](#) to check how to install it. See Figure 3 for an example.

```
library(plotly)
p <- plot_ly(cars, type = "scatter", mode="markers",
             x=~speed,
             y=~dist)
#Sys.setenv('MAPBOX_TOKEN' = '12423423') # set arbitrary token
#orca(p, "logs/plotly-plot.pdf")
```


5 Python

5.1 API data download using Python

```
import sys
print(sys.version)
```

3.9.4 (tags/v3.9.4:1f2e308, Apr 6 2021, 13:40:21) [MSC v.1928 64 bit (AMD64)]

Figure 3: Example: export a Plotly figure using ‘orca’



```
import json
##from json.decoder import JSONDecodeError
import requests
import numpy as np
import pandas as pd

## INE: https://www.ine.pt/ine/json_indicador/pindica.jsp?
## op=2&varcd=0008074&Dim1=S7A2015&Dim2=200&Dim3=3&lang=PT

# api-endpoint

URL = "https://www.ine.pt/ine/json_indicador/pindica.jsp"

# define parameters

OP="2"
```

```

VARCD="0008074"
DIM1="S7A2015"
DIM2="200"
DIM3="3"
LANG="PT"

# defining a params dict for the parameters to be sent to the API
PARAMS = {'op':OP,'varcd':VARCD,'Dim1':DIM1,'Dim2':DIM2,'Dim3':DIM3,'lang':LANG}

# sending get request and saving the response as response object
r = requests.get(url = URL,params=PARAMS)

# extracting data in json format
data = r.json()

valor = data[0]['Dados']['2015'][0]['valor']

valor

```

'1.8'

The criminal rate is 1.8%o.

5.2 Import data from PDF files

```

cd C:/Users/mangelo.EEG/Documents/GitHub/prjs/pdfs
find . -name '*.pdf' -print0 | xargs -0 -n1 pdfsandwich -gray
find . -name '*ocr.pdf' -print0 | xargs -0 -n1 pdftotext

```

['ORNALOFICIAL', 'Tercba-feira, 2 de julho de 2019', '', 'IDY', 'Série', 'Numero 30', ''

FILE: s/IVSerie-030-2019-07-02_ocr

Empty DataFrame

Columns: [linha, output, outra, source]

Index: []

And now we use Stata to explore the data.

```
quiet cd "C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs"
quiet import delimited "C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/PE.csv", encoding
tab source
```

no observations

5.3 Run a Python script to read a PDF using the shell to run the commands wget, pdfsandwich and pdftotext

```
python3 "C:/Users/mangelo.EEG/Documents/GitHub/prjs/chunks/python_chunk.py"
```

python3: can't open file 'C:/Users/mangelo.EEG/Documents/GitHub/prjs/chunks/python_chunk

5.4 Use Stata to list the fiscal numbers (read the data produced with Python)

```
quietly{
cd C:/Users/mangelo.EEG/Documents/GitHub/prjs/chunks

use C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/nipcs, clear
compress
contract nipc
drop _freq
drop if nipc == .
format %12.0f nipc
}

//codebook nipc

tab nipc
```

nipc	Freq.	Percent	Cum.
510649068	1	4.35	4.35

510779174		1	4.35	8.70
511056737		1	4.35	13.04
511117060		1	4.35	17.39
511124899		1	4.35	21.74
511240619		1	4.35	26.09
511247478		1	4.35	30.43
513208348		1	4.35	34.78
513587128		1	4.35	39.13
514118890		1	4.35	43.48
514525657		1	4.35	47.83
514532718		1	4.35	52.17
514591889		1	4.35	56.52
515002666		1	4.35	60.87
515080985		1	4.35	65.22
515092550		1	4.35	69.57
515092649		1	4.35	73.91
515464236		1	4.35	78.26
515478377		1	4.35	82.61
515484920		1	4.35	86.96
515517135		1	4.35	91.30
515518565		1	4.35	95.65
515522988		1	4.35	100.00
-----+-----				
Total		23	100.00	

6 Julia experiments

6.1 Computations

v"1.6.1"

6.2 Grab results in R

Julia Object of type FixedEffectModel.

Fixed Effect Model

```
=====
Number of obs:          147715  Degrees of freedom:          67180
R2:                     0.978   R2 Adjusted:              0.960
F-Stat:                 23.3618  p-value:                0.000
```

```

R2 within:                0.001    Iterations:                250
=====
lnrealwage |      Estimate   Std.Error t value Pr(>|t|)   Lower 95%   Upper 95%
-----
education  |  0.00155636  0.000597587  2.60441    0.009  0.000385093  0.00272763
lnsales    |  0.00622982  0.000987569  6.30824    0.000  0.00429419  0.00816545
=====

```

6.3 Insert Julia's results

The estimated return to education is 0.2%. The model has an R^2 of 0.9782.

6.4 Computation time: run the HDFE with Stata and R and compare to Julia

```

use C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/data_short, clear

timer on 1

    reghdfe lnrealwage education lnsales,absorb(workerid firmid year)

timer off 1
timer list 1
timer clear 1

```

(MWFE estimator converged in 236 iterations)

HDFE Linear regression	Number of obs	=	147,715
Absorbing 3 HD FE groups	F(2, 99667)	=	28.91
	Prob > F	=	0.0000
	R-squared	=	0.9782
	Adj R-squared	=	0.9677
	Within R-sq.	=	0.0006
	Root MSE	=	0.0943

```

-----
lnrealwage |      Coef.   Std. Err.      t    P>|t|     [95% Conf. Interval]
-----

```

education		.0015563	.0005372	2.90	0.004	.0005034	.0026092
lnsales		.0062299	.0008877	7.02	0.000	.0044899	.0079698
_cons		1.577908	.0148587	106.19	0.000	1.548785	1.60703

Absorbed degrees of freedom:

Absorbed FE		Categories	- Redundant	= Num. Coefs	
workerid		44047	0	44047	
firmid		23127	19131	3996	
year		4	1	3	?

? = number of redundant parameters may be higher

1: 20.90 / 1 = 20.9040

```
library(lfe)
data_short <- read_dta("C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/data_short.dta")

system.time(est_hdfe <- felm(data_short$lnrealwage ~ data_short$education + data_short$lnsales, data_short, as.factor(workerid), as.factor(firmid), as.factor(year)))

summary(est_hdfe)
```

6.5 Output Julia's table for HDFE

7 Miguel's tests

7.1 R

Table 5 ... See Section 7.2

Example of an equation

$$\int_0^{2\pi} \sin x \, dx$$

Example of a matrix

	lnrealwage	
	(1)	(2)
education	0.006*** (0.000)	0.002** (0.001)
lnsales	0.013*** (0.001)	0.006*** (0.001)
workerid	Yes	Yes
year	Yes	Yes
firmed		Yes
Estimator	OLS	OLS
N	147,715	147,715
R^2	0.970	0.978

$$\mathbf{X} = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

or

$$f\left(k\right)=\binom{n}{k}p^k\left(1-p\right)^{n-k}\tag{1}$$

See Equation (1).

$$y_{ijt} = \beta x_{ijt} + \eta_i + \gamma_j + \lambda_t + \varepsilon_{ijt} \tag{2}$$

Table 4: Summary table

Statistic	N	Pctl(75)	St. Dev.
idcode	28,534	3,881	1,487.359
year	28,534	83	6.384
birth_yr	28,534	51	3.013
age	28,510	34.000	6.701
race	28,534	2	0.482
msp	28,518	1.000	0.489
nev_mar	28,518	0.000	0.421
grade	28,532	14.000	2.324
collgrad	28,534	0	0.374
not_smsa	28,526	1.000	0.450
c_city	28,526	1.000	0.479
south	28,526	1.000	0.492
ind_code	28,193	11.000	2.994
occ_code	28,413	6.000	3.065
union	19,238	0.000	0.424
wks_ue	22,830	0.000	7.294
ttl_exp	28,534	9.128	4.652
tenure	28,101	4.167	3.751
hours	28,467	40.000	9.870
wks_work	27,831	72.000	29.032
ln_wage	28,534	1.964	0.478




Table 5: Regression table with stargazer

	<i>Dependent variable:</i>		
	M1	price M2	M3
mpg	−49.512 (86.156)	−52.217 (83.740)	−63.210 (84.218)
weight	1.747*** (0.641)	2.111*** (0.619)	2.442*** (0.688)
rep78			
Observations	74	69	69
R ²	0.293	0.365	0.376
Adjusted R ²	0.273	0.335	0.337
Residual Std. Error	2,514.029 (df = 71)	2,374.370 (df = 65)	2,370.832 (df = 64)
F Statistic	14.740*** (df = 2; 71)	12.437*** (df = 3; 65)	9.654*** (df = 4; 64)

Note:

*p<0.1; **p<0.05; ***p<0.01

```
library(stargazer)
stargazer(cars,
  title = "Summary 24",
  label="tab24",
  table.placement = "ht",
  header=FALSE)
```

Table 6: Summary 24

Statistic	N	Mean	St. Dev.	Min	Pctl(25)	Pctl(75)	Max
speed	50	15.400	5.288	4	12	19	25
dist	50	42.980	25.769	2	26	56	120

7.2 Stata

This a Stata example, [Arellano \(2003\)](#). See also [Arellano and Bond \(1991\)](#) and [Blundell and Bond \(1998\)](#). While ... (check [Arellano and Bover 1995](#)).

Variable	Obs	Mean	Std. Dev.	Min	Max
price	74	6165.257	2949.496	3291	15906
Repair					
Record 1978	Freq.	Percent	Cum.		
1	2	2.90	2.90		
2	8	11.59	14.49		
3	30	43.48	57.97		
4	18	26.09	84.06		
5	11	15.94	100.00		
Total	69	100.00			

(file C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs/density.pdf written in PD
> F format)

Source	SS	df	MS	Number of obs	=	234
				F(7, 226)	=	46.99
Model	145.879747	7	20.8399639	Prob > F	=	0.0000
Residual	100.230749	226	.443498888	R-squared	=	0.5927
				Adj R-squared	=	0.5801
Total	246.110496	233	1.05626822	Root MSE	=	.66596

ln gdp	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
education	.2136664	.0193553	11.04	0.000	.1755265	.2518063
lnk	.1978085	.0308039	6.42	0.000	.1371089	.2585082
openk	.0062439	.0011852	5.27	0.000	.0039085	.0085794
year						
1975	-.0694608	.1387178	-0.50	0.617	-.3428064	.2038849
1980	-.177992	.1401702	-1.27	0.205	-.4541996	.0982156
1985	-.2226975	.1400607	-1.59	0.113	-.4986894	.0532943
1990	-.34965	.1425169	-2.45	0.015	-.6304819	-.0688182

_cons		3.38917	.7508785	4.51	0.000	1.909552	4.868789
<hr/>							
Variable		Obs	Mean	Std. Dev.	Min	Max	
<hr/>							
ln_gdp		857	9.302996	1.200567	5.983335	12.51058	

7.3 Grab Stata's output

```
use C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/data_full, clear
quiet generate ln_gdp = ln(rgdwpok)
summarize ln_gdp
```

Variable		Obs	Mean	Std. Dev.	Min	Max
<hr/>						
ln_gdp		857	9.302996	1.200567	5.983335	12.51058

The mean ln GDP is 9.3.

See <https://www.ssc.wisc.edu/~hemken/Stataworkshops/stata.html#stata-and-r-markdown-the-statamarkdown-package>




Figure 4: Wage density

Table 7: Regression analysis

	Simple model	Include capital	Full model
Education	0.3169*** (0.0093)	0.212*** (0.020)	0.2*** (0.0)
Capital		0.125*** (0.029)	0.2*** (0.0)
Openness degree			0.0*** (0.0)
R^2	0.58	0.54	0.59
RMSE	0.78	0.70	0.67
N	857	234	234

* $p < 0.1$; ** $p < 0.05$; *** $p < 0.01$

7.4 Use Stata to export statistics to Excel

We now export a set of statistics to an Excel file.

version 16.1

c:\ado\plus/x/xtabond2.ado

Checksum for c:/ado/plus/x/xtabond2.ado = 3720163387, size = 40472

C:\Users\mangelo.EEG\Documents\GitHub\prjs\logs

Variable	Obs	Unique	Mean	Min	Max	Label
country	839	106	.	.	.	Country name
year	839	9	1980.906	1960	2000	Year of observation
education	839	574	4.794076	.04	12.25	Education
lngdp	839	838	9.308131	5.983335	12.51058	Log Real GDP per Worker
open	839	2	.4982122	0	1	1 = high degree of open...
gdp	839	838	20100.66	396.7612	271192.2	GDP level

Note: file will be replaced when the first putexcel command is issued

```
`"a"' `"b"' `"c"' `"d"' `"e"' `"f"' `"g"' `"h"' `"i"' `"j"' `"k"' `"l"' `"m"' `
> `"n"' `"p"' `"r"' `"s"' `"t"' `"u"' `"v"' `"z"'

8.                                quietly {
9.                                collapse (mean) lngdp education,by(country
> )
10.                                putexcel set descriptives.xlsx, sh
> eet("FIRST LETTER `vv'") modify
11.
19.                                putexcel D3 = matrix(t),nf
> ormat("0.00")
20.                                }
21.                                }
22.
```

Country's first letter: a

Number of countries: .

Country's first letter: b

Number of countries: .

Country's first letter: c

Number of countries: .

Country's first letter: d

Number of countries: .

Country's first letter: e

Number of countries: .

Country's first letter: f

Number of countries: .

Country's first letter: g

Number of countries: .

Country's first letter: h

Number of countries: .

Country's first letter: i

Number of countries: .

Country's first letter: j

Number of countries: .

Country's first letter: k

Number of countries: .

Country's first letter: l

Number of countries: .

Country's first letter: m

Number of countries: .

Country's first letter: n

Number of countries: .

Country's first letter: p

Number of countries: .

Country's first letter: r

Number of countries: .

Country's first letter: s

Number of countries: .

Country's first letter: t

Number of countries: .

Country's first letter: u

Number of countries: .

Country's first letter: v

Number of countries: .

insufficient observations
r(2001);

end of do-file
r(2001);

See Figure 5.




Figure 5: Scatterplot test MP

8 Final remarks

Check the replication package for Bonhomme, Lamadon and Manresa (2019): <https://github.com/tlamadon/blm-replicate>

References

- Arellano, Manuel. 2003. *Panel Data Econometrics*. Oxford University Press.
- Arellano, Manuel and Stephen Bond. 1991. “Some Tests of Specification for Panel Data: Monte Carlo Evidence and an Application to Employment Equations.” *The Review of Economic Studies* 58(2):277–97.
- Arellano, Manuel and Olympia Bover. 1995. “Another Look at the Instrumental Variable Estimation of Error-Components Models.” *Journal of Econometrics* 68(1):29–51.
- Blundell, Richard and Stephen Bond. 1998. “Initial Conditions and Moment Restrictions in Dynamic Panel Data Models.” *Journal of Econometrics* 87(1):115–43.

Appendix: Chunk options

8.1 Software versioning

8.1.1 R

```
cat(paste("#", capture.output(sessionInfo()), "\n", collapse = ""))

# R version 4.1.0 (2021-05-18)
# Platform: x86_64-w64-mingw32/x64 (64-bit)
# Running under: Windows 10 x64 (build 18363)
#
# Matrix products: default
#
# locale:
# [1] LC_COLLATE=Portuguese_Portugal.1252 LC_CTYPE=C
# [3] LC_MONETARY=Portuguese_Portugal.1252 LC_NUMERIC=C
# [5] LC_TIME=Portuguese_Portugal.1252
#
# attached base packages:
# [1] stats      graphics  grDevices  utils      datasets  methods   base
#
# other attached packages:
# [1] plotly_4.9.4.1      naniar_0.6.1      visdat_0.5.3
# [4] dlookr_0.4.5        dplyr_1.0.6       ggplot2_3.3.3
# [7] haven_2.4.1         ExPanDaR_0.5.3    JuliaCall_0.17.4
# [10] Statamarkdown_0.6.1 stargazer_5.2.2    reticulate_1.20
```

```

#
# loaded via a namespace (and not attached):
#   [1] colorspace_2.0-1      ellipsis_0.3.2        class_7.3-19
#   [4] rio_0.5.26            htmlTable_2.2.1       base64enc_0.1-3
#   [7] rstudioapi_0.13       proxy_0.4-25          farver_2.1.0
#  [10] DT_0.18               mvtnorm_1.1-1         fansi_0.4.2
#  [13] xml2_1.3.2            splines_4.1.0         extrafont_0.17
#  [16] libcoin_1.0-8         knitr_1.33            Formula_1.2-4
#  [19] jsonlite_1.7.2        Rttf2pt1_1.3.8        cluster_2.1.2
#  [22] png_0.1-7             shiny_1.6.0           readr_1.4.0
#  [25] compiler_4.1.0        httr_1.4.2            tictoc_1.0.1
#  [28] backports_1.2.1       lazyeval_0.2.2        assertthat_0.2.1
#  [31] Matrix_1.3-3          fastmap_1.1.0         cli_2.5.0
#  [34] later_1.2.0           hrbrthemes_0.8.0      htmltools_0.5.1.1
#  [37] tools_4.1.0           partykit_1.2-13       gtable_0.3.0
#  [40] glue_1.4.2            Rcpp_1.0.6            carData_3.0-4
#  [43] cellranger_1.1.0      vctrs_0.3.8           svglite_2.0.0
#  [46] extrafontdb_1.0       crosstalk_1.1.1       inum_1.0-4
#  [49] xfun_0.23             stringr_1.4.0         openxlsx_4.2.3
#  [52] rvest_1.0.0           mime_0.11             lifecycle_1.0.0
#  [55] shinycssloaders_1.0.0 RcmdrMisc_2.7-1       MASS_7.3-54
#  [58] zoo_1.8-9             scales_1.1.1          hms_1.1.0
#  [61] promises_1.2.0.1      sandwich_3.0-1        RColorBrewer_1.1-2
#  [64] yaml_2.2.1            curl_4.3.1            gridExtra_2.3
#  [67] UpSetR_1.4.0          gdtools_0.2.3         rpart_4.1-15
#  [70] latticeExtra_0.6-29   stringi_1.6.2         highr_0.9
#  [73] corrplot_0.88         nortest_1.0-4         e1071_1.7-7
#  [76] checkmate_2.0.0       zip_2.1.1             rlang_0.4.11
#  [79] pkgconfig_2.0.3       systemfonts_1.0.2     evaluate_0.14
#  [82] lattice_0.20-44       purrr_0.3.4           labeling_0.4.2
#  [85] htmlwidgets_1.5.3     tidysselect_1.1.1     plyr_1.8.6
#  [88] magrittr_2.0.1        bookdown_0.22         R6_2.5.0
#  [91] generics_0.1.0        Hmisc_4.5-0           DBI_1.1.1
#  [94] pillar_1.6.1          foreign_0.8-81        withr_2.4.2
#  [97] prettydoc_0.4.1       survival_3.2-11       abind_1.4-5
# [100] nnet_7.3-16           tibble_3.1.2          crayon_1.4.1
# [103] car_3.0-10            utf8_1.2.1            rmarkdown_2.8
# [106] jpeg_0.1-8.1          grid_4.1.0            readxl_1.3.1
# [109] data.table_1.14.0     forcats_0.5.1         webshot_0.5.2
# [112] digest_0.6.27         xtable_1.8-4          tidyr_1.1.3
# [115] httpuv_1.6.1          openssl_1.4.4         munsell_0.5.0

```



```
# [118] viridisLite_0.4.0      kableExtra_1.3.4      askpass_1.1
```

```
# or use message() instead of cat()
```

8.1.2 Python

```
import sys
print(sys.version)
```

```
3.9.4 (tags/v3.9.4:1f2e308, Apr  6 2021, 13:40:21) [MSC v.1928 64 bit (AMD64)]
```

8.1.3 Julia

```
v"1.6.1"
```

8.1.4 Stata

```
version 16.1
```

```
c:\ado\plus/x/xtabond2.ado
```

```
Checksum for c:/ado/plus/x/xtabond2.ado = 3720163387, size = 40472
```

8.2 All the code in the paper

To simply attach all the code you used in the PDF file in the appendix see the R chunk in the underlying .rmd file:

```
knitr::opts_chunk$set(cache = FALSE)
# Use chache = TRUE if you want to speed up compilation

# A function to allow for showing some of the inline code
rinline <- function(code){
  html <- '<code class="r">` `` `r CODE` ``</code>'
  sub("CODE", code, html)

  ##https://opensource.com/article/19/5/python-3-default-mac
```

```

Sys.setenv(RETICULATE_PYTHON = "C:/Users/mangelo.EEG/AppData/Local/Microsoft/WindowsAp

##install.packages("reticulate")
library(reticulate)
##use_python("/Library/Frameworks/Python.framework/Versions/3.8/bin/python3")

use_virtualenv("C:/Users/mangelo.EEG/Documents/python")

##knitr::opts_chunk$set(pyhton.reticulate=FALSE)

# library(devtools) # before this you may need to install devtools
# install_github("hemken/Statamarkdown")

library(JuliaCall)

library(Statamarkdown)
stataexe <- "C:/Program Files/Stata16/StataMP-64.exe"
knitr::opts_chunk$set(engine.path=list(stata=stataexe))

}
Sys.setenv(RETICULATE_PYTHON = "C:/Program Files/Python39/python.exe")
library(reticulate)
use_virtualenv("C:/Users/mangelo.EEG/Documents/python")
library(stargazer)
library(Statamarkdown)
stataexe <- "C:/Program Files/Stata16/StataMP-64.exe"
#stataexe <- "/Applications/Stata15/StataMP.app/Contents/MacOS//stata-mp"
knitr::opts_chunk$set(engine.path=list(stata=stataexe))
library(JuliaCall)
options(JULIA_HOME = "C:/Users/mangelo.EEG/AppData/Local/Programs/Julia-1.6.1/bin")
julia_setup()

## ExPanDaR: Explore Panel Data Interactively

library(ExPanDaR)

## type ExPanD() in the Console

setwd("C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs")

```

```

library(haven)
library(ggplot2)

nlswork <- read_dta("C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/nlswork.dta")

nls<-data.frame(nlswork)

attach(nlswork)

head(nlswork)

library(stargazer)
stargazer(nls,
          title = "Summary statistics",
          label="tab1",
          table.placement = "ht",
          header=FALSE)

library(dplyr)
library(dlookr)
library(ggplot2)

##eda_report(nlswork,output_dir = "C:/Users/mangelo.EEG/Documents/GitHub/prjs/reports/

## The data

names(nlswork)
##summary(nlswork)

## Missing values

library("visdat")

vis_dat(nlswork)

## https://cran.r-project.org/web/packages/naniar/vignettes/naniar-visualisation.html

library(naniar)

vis_miss(nlswork)

```

```

gg_miss_upset(nlswork)

## GRAPHS
dplyr::glimpse(nlswork$ln_wage)
d <- density(ln_wage)
plot(d)

plot(nls$ln_wage, nls$ttl_exp)

ggplot(nlswork,
       aes(x = hours,
           y = year)) +
geom_miss_point()

ggplot(nlswork,
       aes(x = hours,
           y = year)) +
geom_miss_point() +
facet_wrap(race)

stats <- summary(nlswork$age)

library(stargazer)
stargazer(cars,
          title = "Summary table with stargazer",
          label="tab1cars",
          table.placement = "H",
          header=FALSE)

library(stargazer)
model1 <- lm(speed ~ dist, data = cars)
model2 <- lm(speed ~ dist, data = cars)
model3 <- lm(dist ~ speed, data = cars)
stargazer(model1, model2, model3,
          title = "Regression table with stargazer",
          label="tab2",
          table.placement = "H",
          column.labels = c("M1", "M2", "M3"),
          model.numbers = FALSE,
          header=FALSE)
plot(cars$speed, cars$dist)

```

```

mtcars$cyl <- as.factor(mtcars$cyl) # Convert cyl to factor
library(ggplot2)
ggplot(mtcars, aes(x=wt, y=mpg, shape=cyl)) + geom_point() +
  labs(x="Weight (lb/1000)", y = "Miles/(US) gallon",
       shape="Number of \n Cylinders") + theme_classic()
library(plotly)
p <- plot_ly(cars, type = "scatter", mode="markers",
             x=~speed,
             y=~dist)
#Sys.setenv('MAPBOX_TOKEN' = '12423423') # set arbitrary token
#orca(p, "logs/plotly-plot.pdf")
import sys
print(sys.version)

import json
##from json.decoder import JSONDecodeError
import requests
import numpy as np
import pandas as pd

## INE: https://www.ine.pt/ine/json_indicador/pindica.jsp?
## op=2&varcd=0008074&Dim1=S7A2015&Dim2=200&Dim3=3&lang=PT

# api-endpoint

URL = "https://www.ine.pt/ine/json_indicador/pindica.jsp"

# define parameters

OP="2"
VARCD="0008074"
DIM1="S7A2015"
DIM2="200"
DIM3="3"
LANG="PT"

# defining a params dict for the parameters to be sent to the API
PARAMS = {'op':OP, 'varcd':VARCD, 'Dim1':DIM1, 'Dim2':DIM2, 'Dim3':DIM3, 'lang':LANG}

```

```

# sending get request and saving the response as response object
r = requests.get(url = URL,params=PARAMS)

# extracting data in json format
data = r.json()

valor = data[0]['Dados']['2015'][0]['valor']

valor

cd C:/Users/mangelo.EEG/Documents/GitHub/prjs/pdfs
find . -name '*.pdf' -print0 | xargs -0 -n1 pdfsandwich -gray
find . -name '*ocr.pdf' -print0 | xargs -0 -n1 pdftotext
import os
import numpy as np
import pandas as pd
import re

## CHECK PyPDF2

## wget -A pdf -m -p -E -k -K -np https://joram.madeira.gov.pt/joram/4serie/
## find . -name '*.pdf' -print0 | xargs -0 -n1 pdfsandwich -gray
## find . -name '*ocr.pdf' -print0 | xargs -0 -n1 pdftotext

# Create list with .txt files for the specified folder
files_list = list()
for (dirpath, dirnames, filenames) in os.walk('C:/Users/mangelo.EEG/Documents/GitHub/prj
    files_list += [os.path.join(dirpath, file)
        for file in filenames if file.endswith('.txt')]

##print("START:FILES -- list")

##print(files_list)

##print("END:FILES -- list")

p1 = r'PORTARIA'
p2 = r'EXTENSAO'
p3 = r'Materiais'

```

```

p5 = r'PE das'

linha = []
output = []
other = []
palavra = []
source = []

for file in files_list:

    f = open(file, "r", encoding='latin8')
    data = f.read()
    f.close()

    line = []
    nh = 0

    tmp1 = str(data)
    #print(tmp1)
    tmp2 = tmp1.splitlines()
    #print(tmp2)
    for n,tmp3 in enumerate(tmp2):
        #print(tmp3)
        if (tmp3.find("PE das") == 0):
            tmp4 = tmp3 + tmp2[2]
            line.append(tmp4)
            #print(n)
            nh = 1
        elif (nh == 1):
            nh = 0
            continue
        elif (nh == 0):
            line.append(tmp3)

    print(line)

    print(" ")

    print("FILE: ", file[46:-4])

```

```

for num, word in enumerate(line):
    if num == 0:
        continue
    else:
        match1 = re.search(p1, word)
        match2 = re.search(p2, word)
        match3 = re.search(p3, word)
        match4 = re.search(r'\d{9}', word)
        match5 = re.search(p5, word)
        ##print(" ")
        ##print("START: ", num)

        if match1:
            ##print(" ")
            print("match 1")
            if match4:
                ##print(" ")
                print("match 4")
                linha.append(num)
                output.append(re.search(r'\d{9}', word).group())
                other.append("vazio")
                palavra.append(p1)
                source.append(file[46:-4])
            elif match2:
                ##print(" ")
                print("match 2")
                linha.append(num)
                output.append(re.search(r'\d{9}', word).group())
                other.append("vazio")
                palavra.append(p2)
                source.append(file[46:-4])
            elif match3:
                ##print(" ")
                print("match 3")
                linha.append(num)
                output.append(re.search(r'\d{9}', word).group())
                other.append("vazio")
                palavra.append(p3)
                source.append(file[46:-4])
            elif match5:

```



```

        ##print(" ")
        print("-> match 5")
        ##word.sub(" e o ", " e a ",1)
        print(word)
        linha.append(num)

    if (word.find(" e o ") > 0):
        print("11111")
        output.append((word.split("re a", 1)[1]).split(" e o ", 1))
        other.append((word.split("re a", 1)[1]).split(" e o ", 1))
    elif (word.find(" e a ") > 0):
        print("99999")
        output.append((word.split("re a", 1)[1]).split(" e a ", 1))
        other.append((word.split("re a", 1)[1]).split(" e a ", 1))

    palavra.append(p5)
    source.append(file[46:-4])

## o paragrafo tem de estar na mesma linha e temos de ter 'e a' em vez de 'e o'
df = pd.DataFrame({'linha': linha, 'output': output,
                   'outra': other, 'source': source})

print(df)

df.to_csv('data/PE.csv', index=False)
df.to_stata('data/PE.dta', write_index = False)

quiet cd "C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs"
quiet import delimited "C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/PE.csv", encoding="utf-8"
tab source

python3 "C:/Users/mangelo.EEG/Documents/GitHub/prjs/chunks/python_chunk.py"

quietly{
cd C:/Users/mangelo.EEG/Documents/GitHub/prjs/chunks

use C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/nipcs, clear
compress
contract nipc
drop _freq
drop if nipc == .

```

```

format %12.0f nipc
}

//codebook nipc

tab nipc
## This is a julia language chunk.
## In julia, the command without ending semicolon will trigger the display
## so is JuliaCall package.
## The julia display will follow immediately after the corresponding command
## just as the R code in R Markdown.

using ReadStat
using StatFiles
using StatsBase
using DataFrames
using FixedEffectModels

@time results_hdfe1 = reg(DataFrame(load("C:/Users/mangelo.EEG/Documents/GitHub/prjs/dat

@time results_hdfe2 = reg(DataFrame(load("C:/Users/mangelo.EEG/Documents/GitHub/prjs/dat

using RegressionTables
regtable(results_hdfe1,results_hdfe2; renderSettings = latexOutput("logs/hdfe_output.tex

VERSION
library(JuliaCall)

    julia_eval("results_hdfe2")

betas <- julia_eval("coef(results_hdfe2)")
r2 <- julia_eval("r2(results_hdfe2)")

use C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/data_short, clear

timer on 1

    reghdfe lnrealwage education lnsales,absorb(workerid firmid year)

timer off 1

```

```

timer list 1
timer clear 1
library(lfe)
data_short <- read_dta("C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/data_short.dta")

system.time(est_hdfe <- felm(data_short$lnrealwage ~ data_short$education + data_short$1

summary(est_hdfe)
library(stargazer)
library(Statamarkdown)
stataexe <- "C:/Program Files/Stata16/StataMP-64.exe"
knitr::opts_chunk$set(engine.path=list(stata=stataexe))

setwd("C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs")
rm(list = ls())
library(haven)
nlswork <- read_dta("../data/nlswork.dta")

auto <- read_dta("../data/auto.dta")

attach(nlswork)

regs1 <- lm(auto$price ~ auto$mpg + auto$weight)
regs2 <- lm(auto$price ~ auto$mpg + auto$weight + auto$rep78)
regs3 <- lm(auto$price ~ auto$mpg + auto$weight + auto$rep78 + auto$trunk)

regs4 <- lm(ln_wage ~ union)
regs5 <- lm(ln_wage ~ union + collgrad)
regs6 <- lm(ln_wage ~ union + collgrad + age)

##summary(auto)
##summary(regs1)

## https://www.jakeruss.com/cheatsheets/stargazer/

nls<-data.frame(nlswork)

stargazer(nls, summary.stat = c("n", "p75", "sd"), summary.logical = FALSE,
          title = "Summary table",
          label="tab23",

```

```

        table.placement = "ht",
        header=FALSE)

stargazer(regs1, regs2, regs3,
          title = "Regression table with stargazer",
          label="tab3",
          table.placement = "ht",
          column.labels = c("M1", "M2", "M3"),
          model.numbers = FALSE,
          header=FALSE,keep=c(0,1,2,3))

attach(auto)

library(naniar)
vis_miss(nlswork)

# plot(y=price,x=mpg)

library(stargazer)
stargazer(cars,
          title = "Summary 24",
          label="tab24",
          table.placement = "ht",
          header=FALSE)

quiet sysuse auto
sum price

tab rep78

quiet cd "C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs"

quiet use ../data/nlswork, clear

twoway (kdensity ln_wage if collgrad == 0) || (kdensity ln_wage if collgrad == 1), schem

graph export "C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs/density.pdf", replace

use ../data/data_full, clear

```

```

quiet generate lngdp = ln(rgdpwok)
quiet ge lnk = ln(capital)

label var rgdpwok "Real GDP per worker"
label var education "Education (in years)"
label var capital "Capital"
label var open "Degree of openness"

// # regression analysis

quiet reg lngdp education
estimates store r1

quiet reg lngdp education lnk
est store r2

reg lngdp education lnk openk i.year
est store r3

outreg, clear
quiet estimates restore r1
outreg using growth_analysis_frag, tex fragment replace rtitles("Education" \ "
/* drop(_cons) /*
/* ctitle("", "Simple model") /*
/* nodisplay varlabels bdec(4) se starlevels(10 5 1) starloc(1) summstat

quiet estimates restore r2
outreg using growth_analysis_frag, tex fragment merge rtitles("Education" \ "" \
/* drop(_cons) /*
/* ctitle("", "Include capital") /*
/* nodisplay varlabels bdec(3) se starlevels(10 5 1) starloc(1) summstat

quiet estimates restore r3
outreg using growth_analysis_frag, tex fragment merge rtitles("Education" \ "" \
/* drop(_cons 1975.year 1980.year 1985.year 1990.year) /*
/* ctitle("", "Full model") /*
/* nodisplay varlabels bdec(1) se starlevels(10 5 1) starloc(1) summstat

sum lngdp
use C:/Users/mangelo.EEG/Documents/GitHub/prjs/data/data_full, clear

```

```

        quiet generate lngdp = ln(rgdpwok)
        summarize lngdp
file open myfile using example.txt, write replace
file write myfile "`r(mean)'"
file close myfile
unlink("example.txt")
version
//ado describe

findfile xtabond2.ado
checksum "c:/ado/plus/x/xtabond2.ado"

// PUTEXCEL

cd "C:/Users/mangelo.EEG/Documents/GitHub/prjs/logs"

quiet use ../data/graph_data, clear
        codebook, compact

        putexcel clear
        putexcel set descriptives.xlsx, sheet("Avg. Educ. & desc.") replace

gen first = substr(country,1,1)

        levelsof first,local(ff)

        foreach vv of local ff {

                di _new(3) "Country's first letter: `vv'"

        preserve
        quiet keep if first == "`vv'"

        quiet unique country

                if r(unique) > 5 {
                di _new(2) "        Number of countries:      " r(unique) _new(1)
                quietly {
                        collapse (mean) lngdp education,by(country)

```

```

        putexcel set descriptives.xlsx, sheet("FIRST LETTER `vv'") modify

        regress lngdp education

        matrix list r(table)

        matrix results = r(table)
        mat l results

        mat b = results[1,1...] '
        mat t = results[3,1...] '

        putexcel C2="Coef." F2="t"
        putexcel B3 = matrix(b), rownames nformat(number_d2) right
        putexcel D3 = matrix(t),nformat("0.00")
    }
}

if r(unique) <= 5 {
    // di _new(2) " Insufficient number of countries; n countries = " r(unique)
}

restore

}

// tabulate, summarize() -- EXAMPLE

tabulate first year, summarize(education) nost nof noob

collapse (mean) education,by(first year)

reshape wide education,i(first) j(year)
mkmat education*,matrix(mean_educ) rownames(first)

putexcel set descriptives.xlsx, sheet("Mean Education") modify

        putexcel C2="1960" D2="1965" E2="1970" F2="1975" G2="1980" H2="1985" I2="1990" J2="1995"
        putexcel B3 = matrix(mean_educ), rownames nformat(number_d2) right
plot(x = mpg, y = price,
     pch = 16, frame = FALSE,

```

```
    xlab = "wt", ylab = "mpg", col = "#2E9FDF")
cat(paste("#", capture.output(sessionInfo()), "\n", collapse = ""))
# or use message() instead of cat()
import sys
print(sys.version)
VERSION
version
//ado describe

findfile xtabond2.ado
checksum "c:/ado/plus/x/xtabond2.ado"
```