# P-Channel Enhancement-Mode Vertical DMOS FET

## Features

► Free from secondary breakdown
► Low power drive requirement
► Ease of paralleling
► Low $C_{ISS}$ and fast switching speeds
► High input impedance and high gain
► Excellent thermal stability
► Integral source-to-drain diode

## Applications

► Motor controls
► Converters, amplifiers, and switches
► Power supply circuits
► Drivers (relays, hammers, solenoids, lamps, memories, displays, bipolar transistors, etc.)

## General Description

The Supertex VP2206 is an enhancement-mode (normally-off) transistor that utilizes a vertical DMOS structure and Supertex's well-proven silicon-gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors, and the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

## Ordering Information

| Part Number | Package Option | Packing |
|---|---|---|
| VP2206N2-G | TO-39 | 500/Bag |
| VP2206N3-G | TO-92 | 1000/Bag |
| VP2206N3-G P002 | | |
| VP2206N3-G P003 | | |
| VP2206N3-G P005 | TO-92 | 2000/Reel |
| VP2206N3-G P013 | | |
| VP2206N3-G P014 | | |

*-G denotes a lead (Pb)-free / RoHS compliant package.*
*Contact factory for Wafer / Die availablity.*
*Devices in Wafer / Die form are lead (Pb)-free / RoHS compliant.*

## Product Summary

| $BV_{DSS}/BV_{DGS}$ | $R_{DS(ON)}$ (max) | $I_{D(ON)}$ (min) |
|---|---|---|
| -60V | 0.9Ω | -4.0A |

## Pin Configuration



**TO-39**

**TO-92**

## Absolute Maximum Ratings

| Parameter | Value |
|---|---|
| Drain-to-source voltage | $BV_{DSS}$ |
| Drain-to-gate voltage | $BV_{DGS}$ |
| Gate-to-source voltage | ±20V |
| Operating and storage temperature | -55°C to +150°C |

*Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.*

## Typical Thermal Resistance

| Package | $\theta_{ja}$ |
|---|---|
| TO-39 | N/A |
| TO-92 | 132°C/W |

## Product Marking



VP 2206N2 YYWW — YY = Year Sealed / WW = Week Sealed

*Package may or may not include the following marks: Si or* 

**TO-39**

SiVP 2206 YYWW — YY = Year Sealed / WW = Week Sealed / ___ = "Green" Packaging

*Package may or may not include the following marks: Si or* 

**TO-92**

## Thermal Characteristics

| Package | $I_D$ (continuous)† | $I_D$ (pulsed) | Power Dissipation @$T_c$ = 25°C | $I_{DR}$† | $I_{DRM}$ |
|---|---|---|---|---|---|
| TO-39 | -750mA | -8.0A | 0.36W | -750mA | -8.0A |
| TO-92 | -640mA | -4.0 | 0.74W | -640mA | -4.0 |

*Notes:*

†  $I_D$ (continuous) is limited by max rated $T_j$ .

## Electrical Characteristics *($T_A$ = 25°C unless otherwise specified)*

| Sym | Parameter | Min | Typ | Max | Units | Conditions |
|---|---|---|---|---|---|---|
| $BV_{DSS}$ | Drain-to-source breakdown voltage | -60 | - | - | V | $V_{GS}$ = 0V, $I_D$ = -10mA |
| $V_{GS(th)}$ | Gate threshold voltage | -1.0 | - | -3.5 | V | $V_{GS}$ = $V_{DS}$, $I_D$= -10mA |
| $\Delta V_{GS(th)}$ | Change in $V_{GS(th)}$ with temperature | - | -4.3 | -5.5 | mV/°C | $V_{GS}$ = $V_{DS}$, $I_D$ = -10mA |
| $I_{GSS}$ | Gate body leakage | - | -1.0 | -100 | nA | $V_{GS}$ = ± 20V, $V_{DS}$ = 0V |
| $I_{DSS}$ | Zero gate voltage drain current | - | - | -50 | μA | $V_{GS}$ = 0V, $V_{DS}$ = Max Rating |
| | | - | - | -10 | mA | $V_{DS}$ = 0.8 Max Rating, $V_{GS}$ = 0V, $T_A$ = 125°C |
| $I_{D(ON)}$ | On-state drain current | -0.85 | -2.0 | - | | $V_{GS}$ = -5.0V, $V_{DS}$ = -25V |
| | | -4.0 | -9.0 | - | A | $V_{GS}$ = -10V, $V_{DS}$ = -25V |
| $R_{DS(ON)}$ | Static drain-to-source on-state resistance | - | 1.3 | 1.5 | Ω | $V_{GS}$ = -5.0V, $I_D$ = -1.0A |
| | | - | 0.75 | 0.9 | | $V_{GS}$ = -10V, $I_D$ = -3.5A |
| $\Delta R_{DS(ON)}$ | Change in $R_{DS(ON)}$ with temperature | - | 0.85 | 1.2 | %/°C | $V_{GS}$ = -10V, $I_D$ = -3.5A |
| $G_{FS}$ | Forward transductance | 800 | 1400 | - | mmho | $V_{DS}$ = -25V, $I_D$ = -2.0A |
| $C_{ISS}$ | Input capacitance | - | 325 | 450 | pF | $V_{GS}$ = 0V, $V_{DS}$ = -25V, f = 1.0MHz |
| $C_{OSS}$ | Common source output capacitance | - | 125 | 180 | | |
| $C_{RSS}$ | Reverse transfer capacitance | - | 30 | 40 | | |
| $t_{d(ON)}$ | Turn-on delay time | - | 4.0 | 15 | ns | $V_{DD}$ = -25V, $I_D$ = -4.0A, $R_{GEN}$ = 10Ω |
| $t_r$ | Rise time | - | 16 | 25 | | |
| $t_{d(OFF)}$ | Turn-off delay time | - | 16 | 50 | | |
| $t_f$ | Fall time | - | 22 | 50 | | |
| $V_{SD}$ | Diode forward voltage drop | - | -1.1 | -1.6 | V | $V_{GS}$ = 0V, $I_{SD}$ = -3.5A |
| $t_{rr}$ | Reverse recovery time | - | 500 | - | ns | $V_{GS}$ = 0V, $I_{SD}$ = -1.0A |

*Notes:*

1. All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300μs pulse, 2% duty cycle.)
2. All A.C. parameters sample tested.

## Switching Waveforms and Test Circuit

# Typical Performance Curves

### BV$_{DSS}$ Variation with Temperature



### On-Resistance vs. Drain Current



### Transfer Characteristics



### V$_{(th)}$ and R$_{DS}$ Variation with Temperature



### Capacitance vs. Drain-to-Source Voltage



### Gate Drive Dynamic Characteristics

## Typical Performance Curves *(cont.)*

### Output Characteristics



### Saturation Characteristics



### Transconductance vs. Drain Current



### Power Dissipation vs. Case Temperature



### Maximum Rated Safe Operating Area



### Thermal Response Characteristics

# 3-Lead TO-39 Package Outline (N2)



**Bottom View**



**Side View**

| Symbol | | α | β | A | Φa | Φb | ΦD | ΦD1 | h | j | k | L |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Dimension (inches)** | MIN | 45° NOM | 90° NOM | .240 | .190 | .016 | .350 | .315 | .009 | .028 | .029 | .500 |
| | NOM | | | - | - | - | - | - | - | - | - | - |
| | MAX | | | .260 | .210 | .021 | .370 | .335 | .125 | .034 | .040 | .560* |

*JEDEC Registration TO-39.*
*\* This dimension is not specified in the JEDEC drawing.*
***Drawings not to scale.***
***Supertex Doc. #:*** *DSPD-3TO39N2, Version B052009.*

# 3-Lead TO-92 Package Outline (N3)

**Front View**

**Side View**

**Bottom View**

| Symbol | | A | b | c | D | E | E1 | e | e1 | L |
|---|---|---|---|---|---|---|---|---|---|---|
| Dimensions (inches) | MIN | .170 | .014† | .014† | .175 | .125 | .080 | .095 | .045 | .500 |
| | NOM | - | - | - | - | - | - | - | - | - |
| | MAX | .210 | .022† | .022† | .205 | .165 | .105 | .105 | .055 | .610* |

*JEDEC Registration TO-92.*
*\* This dimension is not specified in the JEDEC drawing.*
*† This dimension differs from the JEDEC drawing.*
***Drawings not to scale.***
***Supertex Doc.#:*** *DSPD-3TO92N3, Version E041009.*

*(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to http://www.supertex.com/packaging.html.)*

**Supertex inc.**

1235 Bordeaux Drive, Sunnyvale, CA 94089
Tel: 408-222-8888
*www.supertex.com*