EasyDriver v4.5

www.schmalzhaus.com/EasyDriver

An easy to use bipolar stepper motor driver
Use 4 wire, 6 wire or 8 wire steper motors
From about 150mA/phase to about 750mA/phase
Defaults to 5V for Vcc (logic supply), settable to 3.3V
Supply 8V to 30V DC power input on JP1
Do not connect or disconnect motor
whlie EasyDriver is powered

DEFAULT OPTIONS
Short JP5, JP6, JP7 pins
to GND or Vcc to override

SLEEP = Vcc (awake)
MS1 = Vcc (1/8 microstep)
MS2 = Vcc (1/8 microstep)
ENABLE = GND (enabled)
RESET = Vcc (not reset)
PFD = Vcc (slow decay mode)

JP5 JP6 JP7

DIR is level sensitive
A rising edge on STEP
causes a step
Both take 0V to Vcc

JP2 JP3

Coil 1 of motor across
OUT1B and OUT1A
Coil 2 of motor across
OUT2B and OUT2A

TP1 = Vref input to driver
Monitor this test point with meter
as you adjust current adj pot
Valid range 1.0V to Vcc
At Vref of 5V max current will be 833mA
At Vref of 2V max current will be 333mA
At Vref of 1V max current will be 166mA
Minimum current gives smoothest microsteps
Maximum current gives highest torque
Max Coil Current(in Amps) = Vref(in Volts)/6
Set R16 to 2.0V at factory = 333mA/phase

PFD intermediate voltage
Set for 'mixed-decay' mode.





Change List:
v4.3 12/09/09 BPS Added mounting holes
v4.4 10/24/28 BPS
Fixed MIN/MAX silkscreen
All vias now .02"
v4.4 1/3/12 BPS : C3 now 47uF
v4.5 2/25/14 BPS
Added series resistors and pull douns on STEP/DIR
Updated pot foopprint
Made bottom layer GND rather than VCC
Updated to latest SparkFun footprints
Suithed from CC BY 3.0 to CC BY-SA 3.0 license
Fixed pot silkscreen direction
R5 now 2.5K Ohms to get down to 1V on Vref
R17 now 6.8K to set PDF to 'mixed-decay' mode

open hardware

TITLE: EasyDriver_v45	SFE
Design by: Brian Schmalz Produced by Spark Fun Electronics	REV: 4.5
Date: 8/18/2015 10:28:17 PM	Sheet: 1/1