

Core Banking Solution

Scripting Events

10.2.25

Contents

Scripting Events

Repositories and Classes

Events

Account Related Events

Display Effective Available Amount and
Available Amount

Restricting Number of Joint Holders of
Account

Sum Up Customer Account Balances

Special Savings Account Special Debit
Transaction

Special Savings Account Transfer In
Transaction

Check Linkage of FFD A/c to Package ID

Check Linkage of Package A/c ID Closure

Process Third Party Details

Validate Delink Account from Package
Account ID

Validate Link Account to Package Account
ID

Fetch Manual Pool Account Details

Script Hook for Restricted Accounts Access Inquiry

Generating IBAN Number for MCY Accounts

Generating IBAN Number for Operative Accounts

Get Account Balance in HCULI

MIS Codes updation for SOL Transfer

MIS Codes updation for Scheme Transfer

SOL Transfer Validation

Queue ID for the Account under Excess Management

Automatic Decisions for an account

Check Digit for Random Account Generation

Transfer of Accounts Across Scheme Codes

Script to check Pre-notification Advice

Script to derive Inactivity Period Start date

Script to derive Escheatment Period Start Date

Script to Modify the Product Overdraft

Limit Start Date and End Date

Script for Check Book Reorder Processing

Script for Customized Closure of Account

Script to Modify OD Product Dates

Script to Modify

Script to Validate Access Check for
Account ID

ACH Events

Creation of ACH Return Processing
Transaction

Define ACH Offus Processing

Define ACH Onus Processing

Define ACH Inward Debit Transaction

Parse ACH Details

Parse ACH Header Details

Bill Payment Interface Access for Customer
Processing

Generate an Outward File Name as per
Implementation

File Duplicate Check in HACHUPL Menu
Option

Initializing ACH Dependent Values

Multirepay Demand Satisfaction Processing

Populate Reason Code For ACH

Preprocessing Records for Accessing

Transcription Script for Return Processing

Transcription Script for Settlement
Processing

Transcription Script for Suspense
Processing

Update Entry Status For ACH

XML to DB Mapping

XML to DB Mapping for Header Record

ACH Check Authorization Required For CP

ACHUPL Get File Type

ACH Holiday Check For BACS

ACH Use HCRT Services For reversal

Get Rectification Accounts

Get File rectification Accounts

ACH-get Business Days

To skip the ACH records from GEMQ

To identify whether the ACH instruction in
upload flat file is unpaid claim generation or
not

To generate the unpaid claim ACH instruction

ACH – is MRI table Operation required

Generate SQL Query for Batch Programs in ACH

Update AED Records

Creation of ACH Outward Return Processing Transaction

Consolidated Settlement Transaction Creation Script

Consolidated Customer Transaction Creation Script

MANTM Process for Non Fin Message

Script to Populate Transaction Code from Loans Module

Script to create mandate for First Collection Transaction Code

Script to Identify Payments within a Specific Period

Script to Validate Authorization Details

Script to Update Status of the ACH instruction After Suspense Processing

Script to Cancel Mandate

Script to Cancel Mandate after Receiving Final Payment

Script to Create Inward Mandate

Script to Amend Inward Mandate

Script to Cancel Inward Mandate

Script to Reinstate Inward Mandate

Script to Check if Mandate Exists for First Collection Transaction Code

Script to Populate Transaction Code from Loans Module

Script to Create Mandate for First Collection Transaction Code

Script to Identify Payments within a Specific Period

Script to Validate Authorization Details

Asset Classification Events

Calculating the DPD counter for a Given Asset

Classify an Asset

Provision for an Asset

ATM and Anywhere Events

ATM Structure Formatting Hook

Transaction Authorization Hook

Transaction Particulars Hook

Batch Job Related Events

Allocating Machine ID for a Job

Ignore BJMS Framework for Routing Jobs

Job Collector Details

Calculations

Calculation of Withholding Tax

Calculate Rectified Amount of DDIC

Calculate EGCG Premium Amount

Provide Customization Place

Amount Calculation Script

Card Management System

Customized Card Details Uploads

Card Account Linkage Script

Card Uploads, Download and Reports

Custom Card Details Upload

Custom Card Account Linkage

Centralized Events

Verify Branch EOD and BOD Process
Completion

Verify Account Modification from Another SOL

Verify Target SOL ID and Database Status Code

Channel Information Events

Channel Discount Charge Setup

Reversal of Charges

Overriding Channel Information Fields

Script to Decide Whether Treasury Liability to be Set or Not

Charge Related Events

Calculation of Account Closure Charges

Assess Commitment Fee

Calculation of Bank Guarantee Charges

Calculation of No Bill Utilization of DC Charges

Calculation of Charges for Demand Drafts

MTT Script for DD Charge Calculation from CDCI

Calculation of Issue Advise of DC Charges

Calculation of Amendment of DC Charges

Calculation of Issue of DC Charges

Calculation of Closure of DC Charges

Calculation of Reinstatement of DC Charges

Calculation of Transfer of DC Charges

Check for CLCM Discount

Calculation of General Charges

Get Part Transaction Business Type List

Calculation of HO Charges

HPTTM Script for Intra Limit Regularization Event

Calculation of Inward Clearing Charges

Calculate Plan Change Fee

Calculation of Outward Clearing Charges

Calculation of Outward Clearing Rejection Charges

HPTTM Script for Pass Book Issue Event

Pass Book Issue Charge Event

HPTTM Script for Pass Book Printing Event

Pass Book Printing Charge

Define DC or BG Charge Collection Transaction

Calculation of Stop Payment Charges
External Charge Calculation Script
Customize CXL Transaction Remarks
Calculate Package Maintenance Charges
LMS Fee Maintenance Charges
OD Protection Fee Calculation
Charges in Syndication Loan
OD Protection Charge Collection Script
Excess Management Waive Charges
Charge entry insertion in CXL table
Drawer – Drawee Charges
Script to get Base Date for Charge
Prenotification
Script to check Pre-notification Advice
Script to Calculate Notice Penalty For Loss
Of Interest
Clearing Events
ECS Events
Get ECS Mandate Serial Number
Define Bulk Transaction in ECS
Upload ECS Bulk

Populate ECS Error COde and Error Message

Define ECS Inward Bulk Transaction

Read Upload File of ECS Inward Bulk

Read the Upload File by Position

Define Inward Bulk Transaction

Check Release to Shadow Balance in Outward Clearing

Check for OCI fields Mandatory

Define Outward Clearing Instrument Credit Value Date

Upload and Verify Outward Clearing Transaction

Check OCP Fields Mandatory

Parse the Record from outward Return Processing

Massage Inward Clearing Media Record

Scheme Types to Find Accounts to which Instrument Belongs

The Original Outward Instrument Details for the Unpaid Claim Request Received

Script to get Inward Reject Reason Code

Script to Set an Instrument to Force
Suspense

Connect24 Events

Connect24 Pre-processing Script

Connect24 Post-processing Script

Uniserver Fee Information Script Event

Script to Create Transactions for CDCI
Transaction

Pre-processing Script for Stand-in Server
Request

Post-processing Script for Stand-in Server
Request

CIF Related Events

Find Customer Category

Display High Value Transactions and
Account Type

Date and Calendar Related Events

Check ECP for Future Mapping

Custom Pre or Post Calendar Changes
Operations

Get Next Working Date With Holiday
Check

Check if the Date Passed is Falling on a
Currency Holiday

Currency Next Calendar Validations for
Commercial Loans Module

Currency Previous Calendar Validations for
Commercial Loans Module

Get Next Business Working Date

Check for Holiday on the Renewal Date

Get Next Working Date With Holiday
Check

Get Number of Days in a Year

Script to Modify The Interest Part
Transaction Value Date

Modify SI Part Transaction Value Date

Modify Renewal Part Transaction Value
Date

Modify Closure Part Transaction Value
Date

Demand Draft Events

DD Payment Upload

Calculate Charges for DD Transactions

Validate DD Record to be Uploaded

Populate Issue Bank or Branch in HICTM
Menu Option

Populate Payee Name in Additional Details
Screen

Populate Issue Bank or Branch while
Paying a Bankers Cheque

Populate Issue Bank or Branch in HDDMP
Menu Option

DD Status Upload

Calculate Charges for DD Transactions

Memo Pad Upload

Stop Payment Upload

TDS Upload

Transfer Transaction Upload

ICV, IVS and TVS Upload

DSA Related Events

Populate DSAM Upload Fields

Get the Data for DSA to Upload

Events for Default Population

Populate CSFL Fields with Default Values

Populate CTCM fields with Default Values

Populate CULAC Details with Default

Values

Populate Dr or Cr Indicator for CULAC

Populate Job Group of DCLOB

Populate DCOD fields with Default Values

Populate DCOLD menu fields

Populate sol ID and Tenor fields for DDIC menu

Populate DDBP fields

Default Population for DEFLAB Fields

Post Query of HINQDIV

Populate Message Field for DSFTT

Populate Bank Code of DSPLIC

Post Process for DTCS

Populate HDTMR Fields by Default

Populate DC Close Date By Default

Post Query for DTSL.icfg

Default Population of Message for ECHDNLD

Populate Default Values for Interest Accrual or Booking or Payment or collection

Populate Rates of INTADV Menu Option

Populate Details of CLBOOK and

CLACCR

Populate Values of IDCM

Populate LADML details

SDDR Output

SREAP Output

Default Populate One Part Transaction

Default Populate VHP Repayment Schedule

Events for Structured Products

Enhanced/Guaranteed Interest/No. of Shares
based on Strike Price Precision

Upfront Shares in MSPO menu considering
the Strike Price Precision

Ref Amount for Fee calculation based on
Strike Price Precision

Premium Amount for ELC Products based
on Fixing Price Precision

Calculate the Balance Amount and
Accumulated Share Value

Populate Transaction Reference Number
and Particulars

EOT Events

Get Holiday Status for EOT Event

To Populate Transaction Codes for EOT Event

Validation to Exempt Transaction for EOT Event

FAB Events

Customize Selection of Print Voucher Template

Get TC, Currency Sale and Purchase Charge Details in FAB

Facilitating Automated Tasks

Automatic Verification of HACM Menu Option

Finacle Treasury Events

Finacle Treasury Cash Flows

Upload Finacle Treasury Transactions

Create Finacle Treasury

IBR Events

Customize Names of IBR files

Populate Default Values in HCFLSIBR Menu Option

Interest Related Events

Interpolation Script – Script for Arriving

Rate of Interest Application

Commission Charge Back Process

Commission Booking Process

Commission Reconciliation Process

Script for RSI Recognize Suspended
Interest Menu Option

Interest Calculation

For OD Debit and Credit Interest

Scripts to do call to External System

Liquidity Management Related Events

Get individual interest amount for all
participating accounts (Notional Pooling
case only)

Script Hook for Dumping Account, Data
centre and Bank level information

Script Hook for Dumping Transaction
Details

Miscellaneous Events

Account Details Display in HTM

Dual Language Support

Get Advance Number

Break FFD in FIFO Method

Define Field Based on Customer List
Operation

Get Interest Rate for Foreign Bill Interest
Calculation

Sum up Customer Account Balances

Restrict Number of Joint Holders

Utilization of Limits

Multilingual Number to Words Conversion

Calculate Number of Withdrawals

Reversal Transaction Script

Test User Hooks

Validate Transactions Prior to Deletion

Illegal Character Check for Pin Code Field
Entered

Multilingual Based Events

Multilingual Number to Words Conversion

Mutual Funds Events

Calculate Commission

Calculate Base Price Out

Calculate Commission Based on
Transaction Type

Create Mutual Fund Settlement Transaction

Define Mutual Funds Financial Transaction Other Events

General Scripts IB Slips

Change Record Format

Create Balancing Transaction during
Download

Decrypt a File

Direct Debit Mandate

Encryption of File

CIF Core Interface Update Scripts

Product Selector Script

Bank Level Parameter Maintenance Using
HSCFM Menu

Get Descriptions for CVD Codes

Get Descriptions for CVDINQ codes

Post Query of DTCS

ETD To HTD Error Failure Capture

EXEMOP for 24x7 Menu Access

Get Lien Requester Details

Get Participant Distribution Amount

Get Maximum Number of Lines Required

in the Passbook

Copy the Values from Master to Placement Level

Change Record Format

Control Access to Menu Options

Move Record to AED History

HMRDSP – Multirepay Demand Satisfaction Process

Return PDC Zone

Truncate RTL Table

Revolving OD Bill Generation

Script Hook for Batch Freezing of Account

Amount Calculation Script

Transaction Rate for Forward Contract Number and SOL ID

To Override/Consider Exceptions During Transaction Processing

Decrypt a File

Direct Debit Mandate

Raise Exception while Modifying Account / Limit Node Attached to Expired Insurance Security

User Hook for Connect24
(GetContraAccountBal)

Amount Used for Calculating the Fee
Charges for Different Events

Script Hook for Inactive Dormant Batch
program

Memo Pad Upload

Parsing Logic Script

Script for Finding Stronger or Weaker
Currency

UIC Prepayment Loan Transaction

Calculate the account pref interest rate

Fetch Amortization Amount

XML Upload of AED

Criteria Checking for incoming messages to
be STP

Validations related to STP(State through
Processing)

Fetching the Value of Amount Field

Populating 'Replacing String', From
position' and 'To position

Dumping the Login SOL and Entity (bill)
SOL

Script to Calculate Bucket Based on Rule Action

Script to Calculate Schedule Based on Rule Action System

Script to Calculate Schedule Based on Rule Action External

Script to Change Status of Individual Saving Accounts to Skip Freeze

Script to Raise Custom Exception for Total Contribution Cap Exceeded

Script to Raise Custom Exception for Contribution Cap Exceeded

Script to raise Custom Exception for Current Year Contribution Restriction

Script to Get Value of Reasonable Excuse Marker and Free Text Field

Script for Offshore Hierarchy Logic

Script for Onshore Hierarchy Logic

Script to Open Zone for Autorepresentation

Script to lodge Instrument

Script to Segregate Header Details

Script to Create FPID for FPS

Script to Fetch Original PO for Recovery

Script for Outward Transaction Recovery

Script for Transaction Creation

Script for Matching PO for Recovery
Response

Script for Creating FEE Transactions

Script for Creating Remittance Transaction

Script for EM Queue Transfer

Script to Validate SFMS Message

Script for Event Mapping for SFMS
Message

Script for Creating Customer Processing
Transaction

Script to Decide Charge Collection

Requirement for Inward Auto Returns

Script for Freezing ISA Accounts for
Address Change

Script for Validating PO CutOff Time.

Script for Validating PO CutOff Time.

Script for Bank Validation and Decision

Script for Access Check Validation

Script to Send Notification

Script to Insert Notification Details

Script to Check Additional Criterion for Pool Selection

Script for Handling Other Account Level Tolerances During Pool Reassessment

Script to Insert Notification Details

Script to Insert Notification Details

Script to Fetch PO of Original Message

PO Black List Scan Script

Script to Handle all the ISCD Validations

Script to Map Input Mandate Fields to Advice Message

Script to Transfer Details in Queue

Script for Discretionary Limit Check

RULE_CustomAllocRules Script

RULE_CustomDecisionRules Script

RE_ ExeAddnlExtraCnd Script

Script to Modify COTODParameters

notifyCustomerForBCEM.sscr

Script to Calculate APY

Script for Issue Paying in Book

Script to Build Code for Marking Instruments as Forced Suspence

Script to Build Custom Logic

Script to Calculate Bucket Based on Rule Action

Script to Calculate Schedule Based on Rule Action System

Script to Calculate Schedule Based on Rule Action External

Script to do Release to Shadow Balance Operation on an Instrument

To Override/Consider Exceptions During Transaction Processing

Scripts for MBCD

Script to Validate the Details in MBCD Menu

Script to Process the Details in MBCD Menu

Scripts for MCTRD

Script to Default Populate Details for MCTRD Menu

Script to Fetch Data for Modify and Inquire Modes in MCTRD Menu

Script to Populate the Details for ADD Mode in MCTRD Menu

Script to Validate the Details for
Add/Modify mode in MCTRD Menu

Script to Add the Details in MCTRD
Menu

Script to Modify the Details MCTRD
Menu

Scripts for GRCE

Script to Invoke Batch Job GRCE

Script to Set Register Information for
Batch Job GRCE

Script to Get the List of Customers for
the Batch GRCE

Script to Process Details of Each
Customer for the Batch GRCE

Script to Generate Report for the Batch
GRCE

Overdraft Events

URODF – Upload Revolving Overdraft Fee

MAN Tod Grant

PROO/HODBLCOL - Pay Revolving
Overdraft Online / Bill Collection of
Revolving Overdraft

HCOTA – Charge Off Transaction Account

Grant for Informal TOD for Transaction
from uniser

Modify Product overdraft limits dates

Grant for Informal TOD for Transaction for
Debit Transaction after Checking the
Informal Balance

Parse Events

Parse the input to populate InPARMA Class

Parsing Logic for Funds Verify Details

Other Scripts

Parsing Logic for TTUM 711 record

Passbook Related Events

Passbook Printing

Past Due Details Maintenance

Maintain Additional Details and Validate
Option Code

Past Due Details Inquiry and Report
Generation

Payment System Events

Define Outward Swift Payment Process

Derive Sol ID for the Message Based on
Paysys ID

Format Finacle Amount to Paysys Amount
Format

Format Finacle Date to Paysys Date Format

Format Finacle Time to Paysys Time
Format

Format Swift Message for PORD Display

Get Plugged Parties for Routing

Get Plug Parties for Routing

Get Reroute Paysys ID

Get Routing Details from Outward Mapping
Equation

Get RTGS Inward Suspense Message
Details

Get RTGS UTR Number

Get Swift Parameters Information

Check Homogeneity of Message

Map POrd for Rerouting

Parse Swift Message

Parsing Logic for PaySys Message

Format SMH Message

Convert Swift Format to SMH Format

Rerouting Logic

Format Paysys Amount to Finacle Format

Plug In Parties for Routing

Calculate Payment Dates

Define PORD Customer Payment
Transaction

Validate Payment Dates

Validate PORD Message Details

Define Insurance Transaction

RTGS Creation

Reroute PORD Entry For SWIFT

Reroute RTGS Payment

Reroute SWIFT Payment

Format Inward RTGS Message

Format Out Messages for RTGS

Scan For RTGS Blacklist Customers

Validate RTGS details

Payment Order Charge Calculation

PO Script for Data Population for NEFT &
RTGS

Select Parsing Script Based on the Paysys
ID

Upload a File for the Paysys ID NEFT

Upload a File for the Paysys ID RTGS

Getting Additional Details from the Incoming RTGS Message

Upload a File for the Paysys ID SFMS

Parse the Input Message Header and Footer Details

Parse the Input Message Header and Footer Details in Finacle Internal Format

Validates the Criteria of the HGUPSM

Get the Name of the Script for Grouping and Ungrouping Payment Messages in HGUPSM

Ungrouping the N02 NEFT Messages

Transmit a File for the Paysys ID NEFT through HTRSWIFT

Transmit a File for the Paysys ID RTGS

Transmit a File for the Paysys ID SFMS

To Parse the Input Message Details and Outputs the Formatted SFMS Message

Deriving the Bank Code and Branch Code

Deriving the Bank Details and Branch Details

Derivation of Details for POIE
Derivation of Paysys ID for IE
Derivation of SolID for IE
Getting Charge Event Id for IE
Inward Credits for Message for IE
Message Rerouting Logic of PAYSYS for IE
Rerouting of Payment for IE
Validate the Extra Inter Entity
Link Network Directory
BACS AED XML Upload Script
BACS ahbx0005 Update Status Fields
BACS Check Authorization Required For CP
BACS Get Processing Date Script
BACS Get Settlement Account For Contra Handling
BACS Multi File Type Upload Script
BACS Check ACH Holiday For TD-SI Script
Update AED Custom fields for PO Creation during Interest Calculation

BACS GenMultiOutFile Script

Map Mandate Data To PORDM

BACS Check Ach Holiday For PO

SEPA-form Query For HGARFG/HGARFR

SEPA-Generate Multi Out File For
HGARFG

SEPA-Update Status Fields for
HGARFG/HGARFR

SEPA-Settlement Date and Effective date
validation for SEPA Credit and Direct
Debits

Fetch DepartmentNumber Field for PO
Creation

Bank Validation and Decision

Event Mapping scripts for SFMS Message

Format scripts for SFMS Message

Mapping of Message Id from SWIFT to
Other Payment System

Mapping of Message ID from Other
Payment System Message ID to SWIFT

Mapping for n series Messages to a Single
Message

Risk Limit Status Update Script

Batch Limit Status Update Script

Service Preference Serial Number Update

AUTOREPRESENTMENT script

Check for Autorepresentation

Open Zone for Cheque Mode of
Autorepresentation

Script to Lodge Instruments

Instrument Message Id

Script to Validate Blacklisted Payments

Auto Set Release For OCTM

Profile Charge Transaction Creation Script

Outward Clearing Data Upload

Script to Generate Non Renewal
Nidification

Script to Generate Rescission Notification

Script to Validate Other Bank Account

Script to do Modules Check for BACS

Script to Get Payment System ID

PDC Scripts

Create Contingent Transaction

Fetch Zone Details for PDC

Referral Related Events

Adding Custom Events in HREATM and HREALM

Modifying Default Approval Process in Referral

Referral Exceptions – Sending Exceptions for Custom Referral

Get List of Exceptions to be Ignored

Sending Exceptions for Custom Referral

Securitization Events

Buyback Authorization Pool Transaction Script

Buyback Authorization Transaction Script

Credit Collection to Escrow Transaction Script

Credit Collection to SPV Transaction Script

Loans Waiver of Fee and Interest Transaction Script

Pool Authorization Transaction Script

Pool Selection Additional Criteria Script

Buyback Additional Selection Script

Credit Collection to SPV Amortization

Transaction Script

SI Related Scripts

Fetch Template

SI Amount Derivation

SI Execution

Distinguish Between Carry Forward SI and Regular SI

Pre Process Script for SI Execution

Post Process Script for SI Execution

Scripts to do call to External System

Swift Message Events

Script for MT110 Swift Message

Script for MT111 Swift Message

Script for MT192 Swift Message

Generate Swift Message MT102

Generate MT103 Swift Message

Format MT110 Swift Message

Generate MT110 Ungrouped Swift Message

Generate Swift Message MT202

Generate MT203 Swift Message

Format MT100 Message

Format MT102 Message

Populate Swift Message MT102

Form the MT103 Swift Message

Format MT103 Message

Form Date to Paysys Date Format

Form MT110 Swift Message

Format Swift Message MT110

Form MT111 Swift Message

Format MT111 Swift Message

Format MT191 Message

Form MT202 Swift Message

Format MT202 Message

Form MT400 Message

Format MT400 Swift Message

Form MT410 Swift Message

Format MT410 Swift Message

Form MT412 Message

Format MT412 Swift Message

Forma MT416 Swift Message

Format MT416 Swift Message for the
Given tags

Form MT420 Message

Format MT420 Swift Message

Form MT422 Message

Format MT422 Message

Form MT430 Message

Format MT430 Message

Form MT495 Message

Format MT495 Message

Form MT496 Message

MT643EventMapping

MT644EventMapping

MT645EventMapping

MT646EventMapping

Form MT700 Message

Format MT700 Swift Message

Format MT701 Message

Format MT705 Swift Message

Form MT707 Message

Form MT707 Swift Message

Format MT707 Swift Message for the
Given Tags

Form MT710 Swift Message

Format MT710 Message

Format MT711 Message

Form MT720 Message

Format MT720 Message

Format MT721 Message

Form MT730 Message

Format MT730 Message

Form Swift Message MT732

Format the MT732 Swift Message

Form MT734 Swift Message

Format MT734 Swift Message

Form MT740 Swift Message

Format Swift Message MT740

Form MT742 Swift Message

Format MT742 Swift Message

Form MT747 Swift Message

Format MT747 Swift Message

Form MT750 Message

Format MT750 Message

Form MT752 Swift Message

Format MT752 Swift Message

Form MT754 Swift Message

Format MT754 Swift Message

Form MT756 Swift Message

Format MT756 Swift Message

Generate MT760 Message

Form MT760 Message

Form MT767 Swift Message

Format MT767 Message

Form MT768 Message

Form MT769 Message

Form MT900 Message

Form MT910 Message

Format MT940 Swift Message

Format MT942 Swift Message

Format MT950 Swift Message

Form MT999 Message

Swift Message Events To Generate Non
Renewal Notification via MT799 Swift
Message

To Generate Non Renewal Notification via

MT799 Swift Message

TDS Related Scripts

Get TDS Amount Deducted for the Account

TDS Shortfall Error or Warning

TDS Recovery Script

TDS Upload Related Scripts

Term Loan Events

Amortize Loan Account Charges

Auto Reschedule Loan Accounts

Discounted Loan - Upfront Interest

Calculation Interest Adjustment

Collect Fee for Recovery after Charge Off
Transaction

Create Transaction for Problem Loan
Account Debt Consolidation

Create Transaction for Commercial Loan
Account Deferred Interest Waiver

Draw Down Transaction Creation

Loans Rescheduling and Fee Assessment

Create Transaction for Loan Fee
Assessment and Collection

Create Transaction for Loan Account Fee

Consolidation

Create Transactions for Interest Waiver

Loan Account Late Fee Assessment

Recovery After Charge Off Transactions -
Liability Collection

Recovery After Charge Off Transactions -
Liability Reversal

Loan Account Charge Off

Create Transactions for Loan Account
Payoff

Sample Script to Compute Notice Fees for
Loan Account Prepayment

Loan Charge Transaction

Loan Demand Satisfaction

Create Transactions for Loan
Disbursements

Create Loan Fee Refund Transaction

Create Loan Payment Transaction

Loans Rescheduling Transaction

Create Transaction to Mark Account as Past
Due

Calculate Loan Account Pre-payment Fee

Collect Reversal Fee for Recovery after Charge Off Transaction

Discounted Loan - Upfront Interest Calculation Rescheduling and Rephasement

Reverse Loan Account Charge Off Transaction

Past Due Transaction Reversal

Loan Payoff Transaction Script

Permitted Prepayment Amount for the Account

Calculation of Settlement Amount according to CCA(Customer Credit Act) Formula

Trade Finance Events

Determine Contingent Accounts in DCS and BGS

Define IRM Inward Processing

Validate ACH History Details

Populate FBM details with Swift Message

Get the Currency Position

Populate IRM details From Swift Message

Populate the Values for IRM Service

Populate Default Values for 202 Message

Create Contingent Transactions

Create Transaction for HECGCRPC
Calculation

Euro Message Details

Validating Commodity for Disbursements

GMM Shipping Guarantee Details

Script for User Action (User Additional
Details)

Check Customer Eligibility to Open RPC
Account

Combined TC and Currency Processing in
ORM

Transaction Events

Financial Transaction Creation Events

BCCALC Related Scripts

Creation of Inland Bills Related
Transactions

Script for Creating Margin Transactions

Import Bill Acceptance Event

FX Bill Lodge Event

Past Due Transaction

Transaction for Interest Reversal

Creation of Foreign Bills Related Transactions

Schedule Payment for Loans

Contingent Accounting for Limit Nodes

Creation of contingent revaluation transaction

Loan Demand Satisfaction Transaction

Creating Transaction When HMRDSP Batch Job is Run

Define Revolving OD Bill Collection Transaction

Define Revolving OD Late Fee Transaction

Reverse Charge off Transaction

Show Error or Not When TOD Penalty Date is Less than Expiry Date

MTT Events

Define Transaction

Demonstration Script for Listing and Signature Display

Display Effective Available Amount and Available Amount

Automatic Verification of HIMC Menu Option

Reversal of Insurance Transaction

Automatic Verification of HINTTM Menu Option

Create Rebate Payment Transaction

Execute HDTE and HPPT Menu Options in Sequence

MTT Script for Payment Distribution Batch Transactions

Commission Confirmation Transaction Creation

Foreign Bill Transactions

MTT Script for PD Batch Transactions

UCT– Create Upload Charge Transaction

Create Acct closure transaction while tran type is C or T

Create Acct closure transaction while tran type is B

Create transaction for transferring the fee and interest outstanding amounts to target scheme from source scheme

Create transaction for transferring the fee and interest outstanding amounts to target SOL from source SOL

Account Lien Maintenance

Check and Display Account Balance

Check Part Transaction

Define Reversal Transaction

Define Transaction for Scheme Code Transfer

Define Transaction for SOL Transfer

Create Transaction for Suspense Account

Mask GL Subhead Transaction

Create Debit Authorisation Charge Transaction

Display Vostro Transfer Transaction

Fee Amortization

Clearing Transactions

Validate FTI Criteria

Get CYC Rate Codes from Scripts

Get GCT Home Currency Code and Rate Codes from Scripts

Instruments Regularization when Shadow

Balance is Y

Script to Create Transactions for Advance
Interest Type of Loan Accounts

Create Contingent Transaction for PDCs

Other Financial Transactions

Part Transaction Request Post

Define Insurance Financial Transaction

RPCTM Transaction Creation

DDSL - Draw Down Syndicated Loan

Transactions Through HTM

User Additional Detail Display

Utilization of Limits

Interest Reversal

Revocation

Script to Customize DTD Transaction
Remarks

Notice Saver Debit Transaction

Foreign Bills Event Transactions Script

Creating a Transaction in Transaction
Details Tab During Account Opening for
TD Type of Accounts

Script for handling Customer Provisioning

Transactions

Post Query for DTDI

Populate Transaction Source and Lien
Resource Code

Transfer Transaction

Create Balancing Transaction during
Download

Script Hook for Foreign Cheques Collection
Transaction Creation

Customize DTD Transaction Remarks

Check HCRT PTran Reversal required

Check Charge PartTran For File Reversal

Statement Generation of those accounts
which had no transactions in a set period

String Field Population before posting of
transaction in DTD table

Upload Events

Loan Upload

Fee and Amortization Details Upload

Delinquency Details Upload

Document Details Upload

Loans Account Master Upload

Loans Additional Details Upload
Loans Transaction Upload
Principal Demand and Late Fee Upload
Schedule Balance Upload
Salary Upload Events
 Bill Recovery during Salary Upload
 Customize Input Values for Salary Upload
 Salary Upload for Lien Processing
Upload Beneficiary Account Details
Populate DDSTU upload fields
Populate DSPR Upload Output Fields
ICV, IVS, TVS and LAVS Upload
Miscellaneous Details Upload
Account Turnover Upload
Fee and Amortization Details Upload
Customer Instructions Upload
Delinquency Details Upload
Document Details Upload
Drawing Power Upload
EOD Account Balance Upload

General Upload Related Scripts

GL Subhead Transaction Upload

Lien Upload

Principal Demand and Late Fee Upload

Sanction Limit Upload

Schedule Balance Upload

Security Register Upload

Standing Instructions Upload

Stop Payment Upload

TDS Upload

Temporary Overdraft Upload

Transfer Transaction Upload

ICV, IVS and TVS Upload

Uploading External Source Securities into
Finacle

BIC, HOL and CTV Upload Related Scripts

Finacle ePlatform Upload

Validations for Uploading Debit Balance
Limit

Upload Originator Details

UploadOriginatorDetailsForVOCA

UploadOriginatorDetailsXMLFormatForVO

Outward Clearing Data Upload Duplicate
Check

Validation Events

Customization of Validations

Validate Customer Listing Criteria1

Validate Customer Listing Criteria2

Validate Beneficiary Account Details

Validate BIC payment

Check Whether the account is Finacle or
Non-Finacle

Check whether the DA account is Finacle or
Non-Finacle

Validation of Limit Node Details

Validate LSD Criteria

Check for Menu Validity

Validate Account Fields

Validate NUM details

Check Black List Status

Check Cutoff Time status

Check for Mandatory of PTV fields

Validate RRCDM Criteria

Validate the Number of Days for Months in
General Calendar Mapping Maintenance

Validate DD Payment Record to be
Uploaded

Validating HLNREV Menu Option Fields
Amount Calculation Script

Validating HPULN Menu Option Fields

Validating HPULNTH Menu Option Fields

Validating HRLH Menu Option Fields

Validation for Batch Deferment

ISCD Modulus Check For
ACHODCL/ACHODRL

ISCD validation script for
HACHODCL/HACHODRL

ValidateMT202CV.scr

ISCD validation script for HACHORP

BACS Validate ISCD MC For TD

BACS Validate ISCD for TD

BACS-Validate ISCD/MC for CMCMTM

BACS-Validate ISCD/MC for CMMTRR

BACS-Validate ISCD/MC for

HGARFG/HGARFR

BACS-validate ISCD for CMCMTM menu

BACS-validate ISCD for CMMTRR menu

BACS-validate ISCD for
HGARFG/HGARFR menus

NDT Sort Code Validation

Commission ID Confirmation

Validate SFMS Message

RE_ValAddnlExtraCnd.scr

Validate PINCODE

Appendix

Addendum

Addendum for 10.2.15

autoReimburseClaim.scr

checkPaySysIdForBPARC.scr

chkIfChnlEnbForInqAudit.scr

ContRevalTran.scr

getStmntNextPrintDate.scr

getWTaxIslamic.scr

getWTaxParametersIslamic.scr

IN_almHistDtls.scr

IN_almListDtls.scr
IN_chkIfWeighted.scr
IN_DecreedReport_custval.scr
IN_DecreedReport_defaultpop.scr
IN_DecreedReport.scr
IN_FetchASBADDataForHALMValidation.sc
IN_FetchHALMForASBA.scr
IN_FetchLocaleDataForBills.scr
IN_FetchLocaleDataForFactoring.scr
IN_FetchLocaleDataForTfin.scr
IN_FetchPandLRecoveryPHForGSPM.scr
IN_FetchPandLRecoveryPHForGSPM.scr
IN_fetchRDSI.scr
IN_FetchTranAcctSchmParamsForDelete_p
IN_GetWeightedAvgAmt.scr
IN_GovtSchmeReport.scr
IN_GovtSchmeReport_custval.scr
IN_GovtSchmeReport_defaultpop.scr
IN_GWK_VERIFY_post_process_data.scr
IN_isKccAccntPastDue.scr
IN_KCC_Report_custval.scr

IN_KCC_Report_defaultpop.scr
IN_KCC_Report.scr
IN_KitBatchCall.scr
IN_KitCustomerCoreLink.scr
IN_KitProcTbl.scr
IN_KitReportGen.scr
IN_liftLienWithTransaction.scr
IN_Loan_Disbursement.scr
IN_Loan_Disbursement_Report
_custval.scr
IN_Loan_Disbursement_Report_defaultpop.
IN_Minority_Report_Dist.scr
IN_Minority_Report_State.scr
IN_Minority_Report_State _custval.scr
IN_Minority_Report_Dist_defaultpop.scr
IN_Minority_Report_State_defaultpop.scr
IN_Minority_Report_Dist _custval.scr
IN_MTDSEdet_fetch.scr (15AA - MTDSE
Menu)
IN_MTDSEdet_fetch_Inq.scr (15AA -
MTDSE Menu)

IN_MTDSEgetData.scr (15AA - MTDSE Menu)

IN_MTDSEsubmitData.scr (15AA - MTDSE Menu)

IN_MTDSEsubmitForAddMode.scr (15AA - MTDSE Menu)

IN_MTDSEsubmitForCncl.scr (15AA - MTDSE Menu)

IN_MTDSEsubmitForMod.scr (15AA - MTDSE Menu)

IN_MTDSEsubmitForVerfy.scr (15AA - MTDSE Menu)

IN_MTDSEvalidate_Data.scr (15AA - MTDSE Menu)

IN_MTDSEvalidateSubmit_Data.scr (15AA - MTDSE Menu)

IN_OpenKitAccounts.scr

IN_ProcessRDAcct.scr

IN_processRDSI.scr

IN_procTblIN_DSL.scr

IN_San_Acct_Derive.scr

IN_SRV_AddFactParameter_validate_locale

IN_SRV_AddFactParameter_process_locale

IN_SRV_AddFxBillParameter_process_locale

IN_SRV_AddFxBillParameter_validate_locale

IN_SRV_AddLienOnAcct_process_locale_c

IN_SRV_AddLienOnAcctAndVerify_proces

IN_SRV_AddLoan and CLAcct Validate
Scripts

IN_SRV_Add LoanAcctSchmParams and
CLAcctSchmParams Scripts

IN_SRV_AddTranAcctSchmParams_validate

IN_SRV and GSPM Scripts

IN_SRV_AddTranAcctSchmParams_process

IN_SRV_CancelFxBillParameter_process_lo

IN_SRV_CancelLienOnAcct_process_locale

IN_SRV_CancelTDAcct_process_locale_da

IN_SRV_CancelTranAcctSchmParams_proc

IN_SRV_CancelFactParameter_process_loc

IN_SRV_DeleteFxBillParameter_process_lo

IN_SRV_DeleteFactParameter_process_loc

IN_SRV_DeleteTranAcctSchmParams_proc

IN_SRV_FetchFactParmForCancel_process_

IN_SRV_FetchFactParmForCopy_process_l

IN_SRV_FetchFactParmForDelete_process_
IN_SRV_FetchFactParmForInquire_process_
IN_SRV_FetchFactParmForModify_process_
IN_SRV_FetchFactParmForVerify_process_
IN_SRV_FetchFxBillParamForCancel_proce
IN_SRV_FetchFxBillParamForModify_proce
IN_SRV_FetchFxBillParamForCopy_proces
IN_SRV_FetchFxBillParamForDelete_proce
IN_SRV_FetchFxBillParamForUndelete_pro
IN_SRV_FetchLienDtlsForCncl_process_loc
IN_SRV_FetchLienDtlsForVfy_process_loc
IN_SRV_FetchLienDtlsOnAcForMod_proce
IN_SRV_FetchTDAcctOpenDtlForModify_
IN_SRV_FetchTDAcctOpenDtlForVerify_p
IN_SRV_
FetchTranAcctSchmParamsForModify_proce
IN_SRV_FetchTranAcctSchmParamsForCan
IN_SRV_FetchTranAcctSchmParamsForVe
IN_SRV_FetchTranAcctSchmParamsForUn
IN_SRV_FetchTranAcctSchmParamsForCo
IN_SRV_Fetch and Inquire Scripts

IN_SRV_FetchFactParmForUndelete_process
IN_SRV_FetchFxBillParamForVerify_process
IN_SRV_FetchLienHistoryRecDtls_process
IN_SRV_FetchLienListRecDtls_process_locale_data
IN_SRV_FetchTDAcctOpenDtlForCancel_process
IN_SRV_InquireFxBillParameter_process_locale_data
IN_SRV_InquireLienDtls_process_locale_data
IN_SRV_InquireTranAcctSchmParams_process_locale_data
IN_SRV_ModifyFactParameter_validate_locale_data
IN_SRV_ModifyFxBillParameter_process_locale_data
IN_SRV_ModifyFxBillParameter_validate_locale_data
IN_SRV_ModifyLienOnAcct_process_locale_data
IN_SRV_ModifyLienOnAcctAndVerify_process_locale_data
IN_SRV_Modify LoanAcctSchmParams
and CLAcctSchmParams Scripts
IN_SRV_Modify LoanAcct and CLAcct
Validate Scripts
IN_SRV_ModifyTDAcct_process_locale_data
IN_SRV_ModifyTDAcct_validate_locale_data
IN_SRV_ModifyTranAcctSchmParams_process_locale_data
IN_SRV_ModifyTranAcctSchmParams_validate_locale_data

IN_SRV_OpenTDAcct_process_locale_data
IN_SRV_OpenTDAcct_validate_locale_data
IN_SRV_UndeleteFactParameter_process_lo
IN_SRV_UndeleteFxBillParameter_process_
IN_SRV_UndeleteTranAcctSchmParams_pr
IN_SRV_Verify Undelete Cancel Delete
LoanAcct and CLAcct.scr
IN_SRV_VerifyFactParameter_process_loca
IN_SRV_VerifyFxBillParameter_process_lo
IN_SRV_VerifyLienOnAcct_process_locale
IN_SRV_VerifyTDAcct_process_locale_dat
IN_SRV_VerifyTDAcct_validate_locale_da
IN_SRV_VerifyTranAcctSchmParams_proc
IN_SubmitHALMForASBA.scr
IN_SubmitLocaleDataForBills.scr
IN_SubmitLocaleDataForFactoring.scr
IN_SubmitLocaleDataForTfin.scr
IN_SubmitPandLRecoveryPHForGSPM.scr
IN_SubmitPandLRecoveryPHForGSPM.scr
IN_Suit_Report.scr
IN_Suit_Report_custval.scr

IN_Suit_Report_defaultpop.scr

IN_TDSInsert.scr (15AA)

IN_updateAcctOpnDateForWKIT.scr

IN_uploadDistSolDetails.scr

IN_ValidateHALMForASBA.scr

IN_ValidateINDSI.scr

IN_ValidateKitRequest.scr

IN_ValidateLocaleDataForTfin.scr

IN_ValidatePandLRecoveryPHForGSPM.sc

IN_ValidatePandLRecoveryPHForGSPM.sc

IN_WeightedCalculationInsert.scr (15AA)

IN_welcomeKitAcctCustDtl.scr

IN_welcomeKitInsertAcctDtl.scr

IN_welcomeKitInsertCustDtl.scr

IN_WKITAccountActivation.scr

modChrgAmt.scr

MT700EventMapping.scr

PurchaseAcptAdvice.scr

Scripts added for PPF Accounts and Special
RD Enhancements

SQL Scripts

SRV_VerifyCAAcct_post_process_data.scr

SRV_VerifySBAcct_post_process_data.scr

SRV-IN-KCC scripts

XXX.scr

Addendum for 10.2.16

DCNonRenewalNotification.scr

DCRescissionNotification.scr

getTransactionCodeDtls.scr

NG_AcotliqBatchInit.scr

NG_AcotliqModifyLienAmt.scr

NG_AcotliqSubmit.scr

NG_AddIntProcessData.scr

NG_AddIntRateforPdts.scr

NG_BA_AcctActivate.scr

NG_BUCTRCDInsertCOTDtl.scr

NG_BUCTRCDUpld.scr

NG_bulkAcctCall.scr

NG_bulkAcctCustCoreLink.scr

NG_bulkAcctOpen.scr

NG_bulkAcctProcBCA.scr

NG_bulkAcctProcess.scr

NG_bulkAcctReportGen.scr
NG_CCOTHTblopr.scr
NG_CCOTMVerifyTblopr.scr
NG_CCOTRTblopr.scr
NG_CHDTgetData.scr
NG_CHDTsubmitData.scr
NG_CheckDigit.scr
NG_CotAccrualRecalcBatch.scr
NG_cotAcctSolXfer.scr
NG_cotAcctXfr.scr
NG_CotDailyAccOnConcessnRate.scr
NG_CotDailyAccrual.scr
NG_CotDailyAccrualRecordFetch.scr
NG_CotLiqDailyAccrualRecFetch.scr
NG_CotMonthlyCollectnBatch.scr
NG_CotRebuildCorrectn.scr
NG_CotRebuildForAcct.scr
NG_CotRebuildForSet.scr
NG_CotRebuildForSol.scr
NG_CotRebuildInit.scr
NG_CotRebuildNoLien.scr

NG_CotRebuildSubmit.scr
NG_CotRebuildValidate.scr
NG_cotSchmXfr.scr
NG_CotTableUpdates.scr
NG_DCTSPgetdata.scr
NG_DCTSPsubmitdata.scr
NG_defZeroCot.scr
NG_FetchRevandBnsMLPSdata.scr
NG_GBA_VERIFY_post_process_data.scr
NG_GenerateKYCNum.scr
NG_getCOTForAcctOpen.scr
NG_GL_MovtBatch.scr
NG_GL_procAGL.scr
NG_handleSRVErrors.scr
NG_insertCCOTM.scr
NG_ListBeginSrlNum.scr
NG_MarkLienOnCOTAccruedAmt.scr
NG_MCACTDfetch.scr
NG_MCACTDgetdata.scr
NG_MCACTDsubmitData.scr
NG_MCACTDsubmitForVerify.scr

NG_MCACTDvalidate.scr
NG_MCACTDvalidate_Data.scr
NG_MCHPchrgCalculationFE.scr
NG_MCHPchrgCollection.scr
NG_MCHPgetData.scr
NG_MCHPsubmitData.scr
NG_MCHPvalidate.scr
NG_MCPRchrgCalculationFE.scr
NG_MCPRchrgCollection.scr
NG_MCPRgetData.scr
NG_MCPRgetSumAmount.scr
NG_MCPRsubmitData.scr
NG_MCPRvalidate.scr
NG_msalglsc_Fetch.scr
NG_msalglsc_procSGLM.scr
NG_msalglsc_Submit.scr
NG_NFIUAdditionalDtlsAdd.scr
NG_NFIUAdditionalDtlsFetch.scr
NG_passSheetAdhocCall.scr
NG_passSheetAdhocTran.scr
NG_RevandBnsLocTblInsert.scr

NG_RevIntProcessData.scr

NG_RevIntRateforPdts.scr

NG_SRV_AddAndPostCashTran_process_lo

NG_SRV_AddAndPostCashTran_process_lo

NG_SRV_AddLienOnAcct_validate_locale_

NG_SRV_FetchDfltCAAcctDtls_post_proce

NG_SRV_FetchDfltODAcctDtls_post_proce

NG_SRV_FetchDfltSBAcctDtls_post_proce

NG_SRV_FetchOperAcctDtlForClosure_val

NG_SRV_ModifyAndPostCashTran_proces

NG_SRV_ModifyAndPostCashTran_proces

NG_SRV_ModifyLienOnAcct_validate_loc

NG_SRV_PostTran_process_locale_data.scr

NG_SRV_PostTran_process_locale_data.scr

NG_SRV_VerifyCAAcct_pre_process_data.

NG_SRV_VerifyCAAcct_process_locale_da

NG_SRV_VerifyODAcct_pre_process_data.

NG_SRV_VerifySBAcct_pre_process_data.

NG_UACDInsertAcctDtl.scr

NG_UACDInsertCustDtl.scr

NG_UACDUpld.scr

NG_updateAcctOpnDateForBA.scr

NG_validateAcctDtlForClosure.scr

NG_validateCOTForAcct.scr

NG_validateCOTLien.scr

Sample Scripts Added

Sample Scripts Modified

Scripts for APND menu

Scripts for CTLM menu

Scripts for ILMT menu

Scripts for MPND menu

Scripts for RLPN menu

Scripts for RPN menu

Scripts Hooks Added

Scripts Modified

SPTC_PostQry.scr

STC_PostQry.scr

UPTMAIN_PostQry.scr

UTCMAIN_PostQry.scr

Addendum for 10.2.17

createExtraPartTransactionForAdvEI.scr-
Advance EI

createSchemeTransactionForAccount.scr -
Advance EI

createsolxfrtransaction.scr - Advance EI

EDPRealizOptionalResponse.scr

errorLogIntoDB.scr

ExtraPartTransactionForAdvEI.scr -
Advance EI

GetRefAmtForAdvEI.scr - Advance EI

GetRefAmtForAdvEILoans.scr - Advance
EI

IN_AcctReliefDataUpload.scr - DPD
Freeze

IN_AcctReliefDataValidate.scr - DPD
Freeze

IN_AddMTTLAAddnlDtls.scr - NEFT and
RTGS

IN_addPODetails.scr - UTR and DD No

IN_Advance_EI_Fetch.scr - Advance EI

IN_AdvanceEI_FetchForLNGLI.scr -
Advance EI

IN_advanceEI_validate.scr - Advance EI

IN_advanceEiVal.scr - Advance EI

IN_BGNPAFR_ListGet.scr - NPA Forms report

IN_BGNPAFR_RecordProcess.scr - NPA Forms report

IN_bgnpafr.scr - NPA Forms report

IN_BGNPAFR_SetRegisterInfo.scr - NPA Forms report

IN_bgnpafrReadInput.scr - NPA Forms report

IN_bgnparr.scr - NPA Recovery report

IN_BGNPARR_ListGet.scr - NPA Recovery report

IN_BGNPARR_PostProcessing.scr - NPA Recovery report

IN_BGNPARR_RecordProcess.scr - NPA Recovery report

IN_BGNPARR_SetRegisterInfo.scr - NPA Recovery report

IN_bgnparrReadInput.scr - NPA Recovery report

IN_bgpnpsar.scr - PSL/NON PSL report

IN_BGPNPSAR_ListGet.scr - PSL/NON PSL report

IN_BGNPSAR_PostProcessing.scr -
PSL/NON PSL report

IN_BGNPSAR_RecordProcess.scr -
PSL/NON PSL report

IN_BGNPSAR_SetRegisterInfo.scr -
PSL/NON PSL report

IN_bgpnpsarReadInput.scr - PSL/NON PSL
report

IN_calcNPAREcoveryForLoan.scr - NPA
Recovery report

IN_calcNPAREcoveryForOD.scr - NPA
Recovery report

IN_calculateDPD.scr - DPD Freeze

IN_checkAdvEiTransactionReqdForSCHM.
- Advance EI

IN_checkAdvEiTransactionReqdForSOL.scr
- Advance EI

IN_chkForMatTDAcct.scr - Part closure
after maturity - HCAACTD menu

IN_dtlsCapForNC.scr - NonCust - HTM
menu

IN_fetchAdvanceEiForPopup.scr - Advance
EI

IN_fetchNonCustDetails.scr - NonCust -
HTM menu

IN_fetchNonCustDtlsForCopy.scr -
NonCust - HORM

IN_FITL_WCDL_Accts_Fetch.scr -
Linkage of FITL and WCTL accounts to
Loan accounts

IN_FITL_WCDL_Add.scr - Auto Loans-
HLADISB menu

IN_FITL_WCDL_Add.scr - Advance EI

IN_FITL_WCDL_Add.scr - Linkage of
FITL and WCTL accounts to Loan accounts

IN_FITL_WCDL_Fetch.scr - Linkage of
FITL and WCTL accounts to Loan accounts

IN_FITL_WCDL_Fetch.scr - Auto Loans-
HLADISB menu

IN_FITL_WCDL_Fetch.scr - Advance EI

IN_FITL_WCDL_Modify.scr - Linkage of
FITL and WCTL accounts to Loan accounts

IN_FITL_WCDL_Modify.scr - Auto
Loans- HLADISB menu

IN_FITL_WCDL_Modify.scr - Advance EI

IN_FITL_WCDL_VXDUMode.scr -

Linkage of FITL and WCTL accounts to
Loan accounts

IN_getAdvEiDetailsForSolXFER.scr -
Advance EI

IN_getAdvEiDetailsForClosure.scr -
Advance EI

IN_getAdvEiDetailsForSchmXFER.scr -
Advance EI

IN_getAdvEiDetails.scr - Advance EI

IN_getConductorIdForCopy.scr - NonCust -
HTM menu

IN_GetMarginDetails.scr - Auto Loans-
HLADISB menu

IN_getNonCustDtlsForCopy.scr - NonCust
- HORM

IN_getNonCustInd.scr - NonCust

IN_getNonCustIndForORM.scr - NonCust -
HORM menu

IN_GetRefAmtForAutoLoans.scr - Auto
Loans- HLADISB menu

IN_getSchmType.scr - NonCust - HTM
menu

IN_GetSchmType.scr - NEFT and RTGS

IN_GetTransactionDtlsFromIN_LAM.scr -
Auto Loans- HLADISB menu

IN_HTM_AddNonCustData.scr - NonCust -
HTM menu

IN_HTM_fetchNonCustData.scr - NonCust
- HTM menu

IN_HTM_Main_ProcessNonCustData.scr -
NonCust - HTM menu

IN_HTM_ModifyNonCustData.scr -
NonCust - HTM menu

IN_HTM_ValNonCustData.scr - NonCust -
HTM menu

IN_InsertReliefDetailsForCrtstalizedAcct.sc
- DPD Freeze

IN_InsertReliefDetailsForCrtstalizedAcct.sc
- DPD Freeze

IN_isAcctUnderReliefEligibleForPercolation
- DPD Freeze

IN_LAGSPM_Add.scr - Advance EI

IN_LAGSPM_Fetch.scr - Advance EI

IN_LAGSPM_Modify.scr - Advance EI

IN_LAGSPM_VXDUMode.scr - Advance
EI

IN_LAGSPMLLSPFetch.scr - Advance EI

IN_LAGSPMVal.scr - Advance EI

IN_LAGSPMValidate.scr - Auto Loans-
HLADISB menu

IN_LAMFetchMarginDetails.scr - Auto
Loans- HLADISB menu

IN_LAMValidateData.scr - Auto Loans-
HLADISB menu

IN_laupld_add.scr - Auto Loans-
HLADISB menu

IN_laupld_add.scr - Advance EI

IN_laupld_add.scr - Linkage of FITL and
WCTL accounts to Loan accounts

IN_LoanAcctValidate.scr - NEFT and
RTGS

IN_MarginPartTransactionForAutoLoans.scr
- Auto Loans- HLADISB menu

IN_modifyPODetails.scr - UTR and DD No

IN_panprOutstandingAmtForLoanAcct.scr -
PSL/NON PSL report

IN_postXferTransactionForAdvEI.scr -
Advance EI

IN_RELIEFReadInput.scr - DPD Freeze

IN_reposUpdForPost.scr - NonCust - HTM menu

IN_setNonCustInd.scr - NonCust - HTM menu

IN_setNonCustIndForORM.scr - NonCust - HORM menu

IN_SRV_AddLoanAcctSchmParams_post_p - Advance EI

IN_SRV_AddLoanAcctSchmParams_post_p - Auto Loans- HLADISB menu

IN_SRV_AddPymtOrderMaintDtls_process - UTR and DD No

IN_SRV_CancelCLAcct_process_locale_data - HACMCL- Linkage of FITL and WCTL accounts to Loan

IN_SRV_CancelLAAcct_process_locale_data - HACMLA- Linkage of FITL and WCTL accounts to Loan

IN_SRV_DeletePymtOrderMaintDtls_process - UTR and DD No

IN_SRV_DisbLoanAcct_pre_process_data.s - Advance EI

IN_SRV_DisbLoanAcct_pre_process_data.s - Auto Loans- HLADISB menu

IN_SRV_DisburseTransactionFetch_pre_pro
- Auto Loans- HLADISB menu

IN_SRV_DisburseTransactionFetchForRvsl
- Auto Loans- HLADISB menu

IN_SRV_DisburseTransactionFetch_pre_pro
- Advance EI

IN_SRV_DisburseTransactionFetchForRvsl
- Advance EI

IN_SRV_FetchCLAcctDtlForMaintCancel_
- HACMCL- Linkage of FITL and WCTL

IN_SRV_FetchCLAcctDtlForMaintVerify_
- HACMCL- Linkage of FITL and WCTL

IN_SRV_FetchCLAcctDtlForModify_proce
- HACMCL- Linkage of FITL and WCTL
accounts

IN_SRV_FetchLAAcctDtlForMaintCancel_
- HACMLA- Linkage of FITL and WCTL

IN_SRV_FetchLAAcctDtlForMaintVerify_
- HACMLA- Linkage of FITL and WCTL

IN_SRV_FetchLAAcctDtlForModify_proce
- HACMLA- Linkage of FITL and WCTL
accounts

IN_SRV_FetchLADisbData_pre_process_da
- Auto Loans- HLADISB menu

IN_SRV_FetchLADisbDataForRvsl_pre_pro
- Auto Loans- HLADISB menu

IN_SRV_FetchLADisbDataForVfy_pre_pro
- Auto Loans- HLADISB menu

IN_SRV_FetchLADisbDataForXcl_pre_pro
- Auto Loans- HLADISB menu

IN_SRV_FetchLADisbData_pre_process_da
- Advance EI

IN_SRV_FetchLADisbDataForRvsl_pre_pro
- Advance EI

IN_SRV_FetchLADisbDataForVfy_pre_pro
- Advance EI

IN_SRV_FetchLADisbDataForXcl_pre_pro
- Advance EI

IN_SRV_FetchLaGenDetails_process_local
- Advance EI

IN_SRV_FetchPymtOrderMaintDtlsForCop
- UTR and DD No

IN_SRV_FetchPymtOrderMaintDtlsForMod
- UTR and DD No

IN_SRV_FetchPymtOrderMaintDtlsForVeri
- UTR and DD No

IN_SRV_FetchPymtOrderMaintDtlsForDele
- UTR and DD No

IN_SRV_InquirePymtOrderMaintDtls_process
- UTR and DD No

IN_SRV_InquireCLAcct_process_locale_data
- HACMCL- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_InquireLAAcct_process_locale_data
- HACMLA- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_InsertDisbData_pre_process_data.scr
- Advance EI

IN_SRV_InsertDisbData_pre_process_data.scr
- Auto Loans- HLADISB menu

IN_SRV_ModifyCLAcct_process_locale_data
- HACMCL- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_ModifyLAAcct_process_locale_data
- HACMLA- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_ModifyLoanAcctSchmParams_pos
- Auto Loans- HLADISB menu

IN_SRV_ModifyLAAcct_validate_data.scr
- Advance EI

IN_SRV_ModifyLoanAcctSchmParams_pos
- Advance EI

IN_SRV_ModifyPymtOrderMaintDtls_proc
- UTR and DD No

IN_SRV_OpenCLAcct_process_locale_data
- HACMCL- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_OpenLaAcct_process_locale_data.
- HACMLA- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_OpenLaAcct_validate_data.scr -
Advance EI

IN_SRV_VerifyCLAcct_process_locale_dat
- HACMCL- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_VerifyLAAcct_process_locale_dat
- HACMLA- Linkage of FITL and WCTL
accounts to Loan

IN_SRV_VerifyPymtOrderMaintDtls_proce
- UTR and DD No

IN_SRV_XferAcctBtwnSchms_validate_loc
- Advance EI

IN_SRV_XferAcctBtwnSol_validate_locale.
- Advance EI

IN_UploadReliefDetails.scr - DPD Freeze

IN_UploadReliefDtlsjLimo.scr - DPD

Freeze

IN_UploadReliefDtlsLstDmp.scr - DPD
Freeze

IN_UploadReliefDtlsReport.scr - DPD
Freeze

IN_validateAcidType.scr - Linkage of FITL
and WCTL accounts to Loan accounts

IN_validateAutoLoans.scr - Auto Loans-
HLADISB menu

IN_ValidateSchm.scr - NEFT and RTGS

IN_validateTransaction.scr - Auto Loans-
HLADISB menu

IN_validateXFERSchmForAdvEi.scr -
Advance EI

IN_validateXFERSolForAdvEi.scr -
Advance EI

IN_valMarginDetails.scr - Auto Loans-
HLADISB menu

IN_vrfyDelPODetails.scr - UTR and DD
No

LADisbursementMTT.scr - Advance EI

SRV_AddAndPostCashTransaction_post_pr
- NonCust - HTM menu

SRV_ModifyLAAcct_validate_data.scr -
Auto Loans- HLADISB menu

SRV_OpenLaAcct_validate_data.scr - Auto
Loans- HLADISB menu

SRV_PostTransaction_post_process_data.sc
- NonCust - HTM menu

SRV_VerifyTransaction_post_process_data.
- NonCust - HTM menu

Addendum for 10.2.18

Archiving Solutions

getCustomAvgOfMinBal.scr

getCustomBrokenPeriodProfitRate.scr

getMudCustPeriodCalc.scr

GPRPD_output.scr

Scripts Deleted

Scripting Events About the Module

Finacle Core Banking Solution supports a number of deployment topologies from fully distributed to fully centralized and implementation scenarios like single currency, multiple currency, various retail and trade finance banking products, interest methods and so on. To support these features, it is essential that Finacle is open to customization by the bank so that it can implement features that it requires and in the way that it desires. The bank also needs to interface some of their peripheral applications like Treasury, Consumer Finance and soon which are not supported directly by Finacle, with Finacle in various ways. Another area of customizability is in the interface to various special purpose equipment like ATM switches, VRUs, MICR encoders and so on which are supplied by many vendors with some differences in the actual implementation.

Finacle had addressed this issue by defining parameters set up by the bank depending upon its requirements. However, this has the limitation of requiring that the developers of Finacle know all the possible business logic beforehand and then implement them using parameters. However, a far more powerful approach is to allow the bank to take control at certain events, apply their own logic on the data associated with that event and be able to either influence the outcome of that event or communicate the occurrence of the event to other custom applications. The Finacle Script Engine based customization allows the bank to do just this.

The Script Engine Based Customization (SEBC) consists of the specified components:

- The Script Engine

This is an interpretive language processor which allows a wide range of key programming constructs, while allowing the bank to custom develop additional functions that can be called from the scripts.

- The Finacle function

Certain standard functions and certain module specific functions have been developed by Finacle developers which can be called from the scripts.

- Finacle Script Events

Right across Finacle, there are several events that have been opened up by defining script events. What it means is that for a script-enabled event, Finacle checks for the existence of a defined script and if present, transfers control to the script engine to execute that script after populating all the data required by that event in input fields. It is the script's responsibility to apply whatever logic it wants and provide the necessary output fields at the end of the script for Finacle to continue its processing.

Finacle Scripting Events

Scripting events are supported in Finacle for the bank to enable the following kinds of customization:

Manipulate data given as input (event specific ones and not the ones in STDIN class) and

Scripting Events About the Module



Finacle Core Banking Solution supports a number of deployment topologies from fully distributed to fully centralized and implementation scenarios like single currency, multiple currency, various retail and trade finance banking products, interest methods and so on. To support these features, it is essential that Finacle is open to customization by the bank so that it can implement features that it requires and in the way that it desires. The bank also needs to interface some of their peripheral applications like Treasury, Consumer Finance and soon which are not supported directly by Finacle, with Finacle in various ways. Another area of customizability is in the interface to various special purpose equipment like ATM switches, VRUs, MICR encoders and so on which are supplied by many vendors with some differences in the actual implementation.

Finacle had addressed this issue by defining parameters set up by the bank depending upon its requirements. However, this has the limitation of requiring that the developers of Finacle know all the possible business logic beforehand and then implement them using parameters. However, a far more powerful approach is to allow the bank to take control at certain events, apply their own logic on the data associated with that event and be able to either influence the outcome of that event or communicate the occurrence of the event to other custom applications. The Finacle Script Engine based customization allows the bank to do just this.

The Script Engine Based Customization (SEBC) consists of the specified components:

- The Script Engine

This is an interpretive language processor which allows a wide range of key programming constructs, while allowing the bank to custom develop additional functions that can be called from the scripts.

■ The Finacle function

Certain standard functions and certain module specific functions have been developed by Finacle developers which can be called from the scripts.

■ Finacle Script Events

Right across Finacle, there are several events that have been opened up by defining script events. What it means is that for a script-enabled event, Finacle checks for the existence of a defined script and if present, transfers control to the script engine to execute that script after populating all the data required by that event in input fields. It is the script's responsibility to apply whatever logic it wants and provide the necessary output fields at the end of the script for Finacle to continue its processing.

Finacle Scripting Events

Scripting events are supported in Finacle for the bank to enable the following kinds of customization:

manipulate data given as input (event specific ones and not the ones in TFIN class) and provide the output as needed by Finacle to continue processing. Basically, these events occur at the interface between applications or vendor-specific devices. These events provide an easy way to take care of formatting differences between different versions and applications. The account formatting events are an example of this, in which the bank is expected to apply its specific logic to convert an externally known account number to the internally known one and vice versa. Also, events that allow massaging of messages to and from Connect24 fall into this category. Manipulate menu options, screen variables, and key-based screen events to customize the screens and workflow.

Note:

For the full functionality to be available, the bank must install the workflow module of Finacle. The Form Load and Post-Execute events are some examples.

- At various points during different business transactions, transaction creation events or MTT events are generated which allow the bank to customize the transaction that must be posted. These would typically be used for defining charge transactions, CDCI-related transactions, interest provisioning, interest effecting transactions and so on

For Example:

The bank decides the account number format. But this format may contain some format that is common for all the accounts in the Service Outlet and the user wants the same to be appended to the account number entered in some particular format by default. It might be the Bank code, Branch code, Currency code, currency alias, Data center alias etc. which are common to all accounts.

The account number in the database might be 01-02-03-04-0001

Where 01 - corresponds to Bank code, 02 - corresponds to Branch code, 03 - corresponds to the currency alias, 04 - corresponds to the scheme code and 0001- is the actual account number.

The format of the account is such that the user has to enter '-' in between the account number which is very cumbersome. By making use of script, this can be done by default and the user needs to enter only the actual account number '010203040001' and it will be converted to the format by the script written by the user before it is further processed.

For Example:

The branch may be connected to an ATM that supports only 10 character account number and the actual account number size in Finacle may be more. In this case, the Finacle account

number format is to be converted to ATM account number format using some logic. This can be done in scripting. The bank will decide on the logic to derive the unique account number for ATM from Finacle format and will code the same in the Script.

The account number in Finacle may be 01-02-03-04-0001.

Where 01 - corresponds to Bank code 02 - corresponds to Branch code 03 - corresponds to the currency alias 04 - corresponds to the scheme code 0001 is the actual account number.

To convert to 10 character ATM account number format, the bank may decide to leave out the bank code portion as the ATM is attached to the branches of the same Bank and leave out the formatting of account number with '-'.

The ATM account number that is derived can be 0203040001 that should be unique in the data center.

©Copyright Infosys Ltd.

Repositories and Classes



All Finacle script events except for workflow related events and MTT related events, interface with scripts using a standard repository called BANCS. There predefined classes in this repository are:

- STDIN
- INPUT
- OUTPUT

Each of these hold String type of fields.

STDIN class is the set of common fields available in any event.

Using syntax in the scripts, one can accesses the field in the repositories.

For Example:

BANCS.STDIN.dcAlias

The INPUT CLASS contains fields specific to events, which are the data items that are made available to the script defined for that event.

The OUTPUT CLASS contains fields specific to the events, which are the data items that will be accessed by Finacle after the execution of the script to determine its logic of further execution.

Return Status of the Function

One of the standard output fields from the script is successOrFailure. In case a FAILURE is encountered in the script the OUTPUT CLASS variable successOrFailure can be set to FAILURE.

For Example:

BANCS.OUTPUT.successOrFailure = "F"

The valid values are "S" for success and "F" Failure.

The default return status from the script is SUCCESS.

©Copyright Infosys Ltd.

Events

The different scripting events are:

- [Account Related Events](#)
- [ACH Events](#)
- [Asset Classification Events](#)
- [ATM and Anywhere Events](#)
- [Batch Job Related Events](#)
- [Calculations](#)
- [Card Management System](#)
- [Card Uploads, Downloads and Reports](#)
- [Centralized Events](#)
- [Channel Information Events](#)
- [Charge Related Events](#)
- [Clearing Events](#)
- [Connect 24 Events](#)
- [Date and Calendar Related Events](#)
- [Demand Draft Events](#)
- [DSA Related Events](#)
- [Events for Default Population](#)
- [FAB](#)
- [Facilitating Automated Tasks](#)
- [Finacle Treasury](#)

[IBR Events](#)

[Interest Related Events](#)

[Miscellaneous Events](#)

[Multilingual Based Events](#)

[Mutual Funds](#)

[Other Events](#)

[Overdraft Events](#)

[Parse Events](#)

[Passbook Related Events](#)

[Past Due Details Maintenance](#)

[Payment System](#)

[PDC Scripts](#)

[Referral Related Events](#)

[Securatization Events](#)

[SI Related Scripts](#)

[Swift Message Events](#)

[TDS Related Scripts](#)

[Trade Finance Events](#)

[Transaction Events](#)

[Term Loan Events](#)

[Upload Events](#)

[Validation Events](#)

[Workflow Event](#)

©Copyright Infosys Ltd.

Finacle Copyright

Account Related Events



Finacle provides scripts for performing different operations on customer accounts. These scripting events help us in summing up the balances of the accounts of a customer and display balance for an account. There is a script which can be used to restrict the number of joint holders.

The different Account Related events are:

- [Display Effective Available Amount and Available Amount](#)
- [Restricting Number of Joint Holders of Account](#)
- [Sum Up Customer Account Balances](#)
- [Special Savings Account Special Debit Transaction](#)
- [Special Savings Account Transfer In Transaction](#)
- [Check Linkage of FFD A/c to Package ID](#)
- [Check Linkage of Package A/c ID Closure](#)
- [Process Third Party Details](#)
- [Validate Delink Account from Package Account ID](#)
- [Validate Link Account to Package Account ID](#)
- [Fetch Manual Pool Account Details](#)
- [Script Hook for Restricted Accounts Access Inquiry](#)
- [Generating IBAN Number for MCY Accounts](#)

- [Generating IBAN Number for Operative Accounts](#)
- [Get Account Balance in HCULI](#)
- [MIS Codes updation for SOL Transfer](#)
- [MIS Codes updation for Scheme Transfer](#)
- [SOL Transfer Validation](#)
- [Queue ID for the Account under Excess Management](#)
- [Automatic Decisions for an Account](#)
- [Check Digit for Random Account Generation](#)
- [Transfer of Accounts Across Scheme Codes](#)
- [Script to Fetch Entities for Escheatment](#)
- [Script to Derive Inactivity Period Start Date](#)
- [Script to Derive Escheatment Period Start Date](#)
- [Script to Modify the Product Overdraft Limit Start Date and End Date](#)
- [Script for Check Book Reorder Processing](#)
- [Script for Customized Closure of Account](#)
- [Script to Modify OD Product Dates](#)
- [Script to Modify](#)
- [Script to Validate Access Check for Account ID](#)

MIS Codes Updation for SOL Transfer



Rates are adjusted in an SOL to SOL transfer. Any preferential pricing (RV/RR or preferential rate adjustment) is retained after the transfer. No notice to customer is necessary for checking and savings accounts. Time Deposits may require such notifications.

Using a script hook, customization logic is built to retain/Change preferential interest rate after SOL transfer.

This user hook updates the MIS codes at the time of transfer of account across SOLs.

Inputs Available in the Scripts

The Inputs that are dumped into the script will be available in repository BANCS, class INPARAM and with the field names mentioned below. One can access the inputs by referring to the fields in the following manner.

BANCS.INPARAM. <Fieldname>

Script Input	Description
sector_code	Sector of the industry to which the account belongs
sub_sector_code	Sub-sector of the industry to which the account belongs
acct_occp_code	'Occupation code of the customer for whom account is opened
borrower_category_code	Borrower category code of the customer for whom account is opened
purpose_of_advn	Purpose for which the customer has taken the advance
mode_of_advn	Mode of the advance
type_of_advn	Type of the advance
nature_of_advn	Nature of the advance
guar_cover_code	The code for the guarantee coverage provided for the account

industry_type	Type of industry under which the account should be classified
Free_code (1-10)	Used by bank to enter some extra information for MIS
ias_code	It's a field for ias classification code which follows IAS39 standard for greater transparency with regards to financial instruments
hedged_acct_flg	Flag used for classification of account
used_for_net_off_flg	Flag used for classification of account
Free_text(1-15)	Used by bank to enter some extra documentation for MIS

Note:

The Key fields like Account Id, source Sol, target Sol are already getting dumped into the script as part of the existing logic.

Output Expected

The MIS Codes that gets updated into GAM/GAC will be available in the output repository. The defined outputs will be available in repository BANCS, class OUTPARAM and with the field

names mentioned below. One can access the outputs by referring to the fields in the following manner.

BANCS.OUTPARAM. <Fieldname>

Script Input	Description
sector_code	Sector of the industry to which the account belongs
sub_sector_code	Sub-sector of the industry to which the account belongs
acct_occp_code	'Occupation code of the customer for whom account is opened
borrower_category_code	Borrower category code of the customer for whom account is opened
purpose_of_advn	Purpose for which the customer has taken the advance
mode_of_advn	Mode of the advance
type_of_advn	Type of the advance
nature_of_advn	Nature of the advance
guar_cover_code	The code for the guarantee coverage provided for the account

industry_type	Type of industry under which the account should be classified
Free_code (1-10)	Used by bank to enter some extra information for MIS
ias_code	It's a field for ias classification code which follows IAS39 standard for greater transparency with regards to financial instruments
hedged_acct_flg	Flag used for classification of account
used_for_net_off_flg	Flag used for classification of account
Free_text(1-15)	Used by bank to enter some extra documentation for MIS
GACUpdateReqd	Flag used in script to indicate if GAC updation is required or not.

Default logic in case script is not present

Account Transfer will happen without executing the script and any MIS codes updation, as per the existing logic.

Typical usage scenario(s)

It can be used to update MIS Codes of account (s) while transfer between Sols.

Sample Script

Sample script dumpDataForTransferSol.sscr is present in the Sample scripts (\$TBA_SAMPLE/samscripts) directory.

©Copyright Infosys Ltd.

MIS Codes Updation for Scheme Transfer



Rates are adjusted in a Scheme to Scheme transfer. Any preferential pricing (RV/RR or preferential rate adjustment) is retained after the transfer. No notice to customer is necessary for checking and savings accounts. Time Deposits may require such notifications.

Using a script hook, customization logic can be built to retain/Change preferential interest rate after Scheme transfer.

Hence the requirement is to provide a script hook in the product to update the MIS codes at the time of transfer of account across Schemes.

Inputs Available in the Scripts

The Inputs that are dumped into the script will be available in repository BANCS, class INPARAM and with the field names mentioned below. One can access the inputs by referring to the fields in the following manner.

BANCS.INPARAM. <Fieldname>

Script Input	Description
sector_code	Sector of the industry to which the account belongs
sub_sector_code	Sub-sector of the industry to which the account belongs
acct_occp_code	'Occupation code of the customer for whom account is opened
borrower_category_code	Borrower category code of the customer for whom account is opened
purpose_of_advn	Purpose for which the customer has taken the advance
mode_of_advn	Mode of the advance
type_of_advn	Type of the advance
nature_of_advn	Nature of the advance
guar_cover_code	The code for the guarantee coverage provided for the account

industry_type	Type of industry under which the account should be classified
Free_code (1-10)	Used by bank to enter some extra information for MIS
ias_code	It's a field for ias classification code which follows IAS39 standard for greater transparency with regards to financial instruments
hedged_acct_flg	Flag used for classification of account
used_for_net_off_flg	Flag used for classification of account
Free_text(1-15)	Used by bank to enter some extra documentation for MIS

Note:

The Key fields like Account Id, source Sol, target Sol are already getting dumped into the script as part of the existing logic.

Output Expected

The MIS Codes that gets updated into GAC will be available in the output repository. The defined outputs will be available in repository BANCS, class OUTPARAM and with the field

names mentioned below. One can access the outputs by referring to the fields in the following manner.

BANCS.OUTPARAM. <Fieldname>

Script Input	Description
sector_code	Sector of the industry to which the account belongs
sub_sector_code	Sub-sector of the industry to which the account belongs
acct_occp_code	'Occupation code of the customer for whom account is opened
borrower_category_code	Borrower category code of the customer for whom account is opened
purpose_of_advn	Purpose for which the customer has taken the advance
mode_of_advn	Mode of the advance
type_of_advn	Type of the advance
nature_of_advn	Nature of the advance

guar_cover_code	The code for the guarantee coverage provided for the account
industry_type	Type of industry under which the account should be classified
Free_code (1-10)	Used by bank to enter some extra information for MIS
ias_code	It's a field for ias classification code which follows IAS39 standard for greater transparency with regards to financial instruments
hedged_acct_flg	Flag used for classification of account
used_for_net_off_flg	Flag used for classification of account
Free_text(1-15)	Used by bank to enter some extra documentation for MIS
MisCodeUpdateReqd	Flag used in script to indicate if GAC updation is required or not.

Default logic in case script is not present

GacUpdates will happen without executing the script and any dumping / population of the above fields into/from script as per the existing logic.

Typical usage scenario(s)

It can be used to update MIS Codes of account (s) while transfer between Schemes.

Sample Script

Sample script AddnlSchmParamforHACXFRSC.sscr is present in the Sample scripts (\$TBA_SAMPLE/samscripts) directory.

©Copyright Infosys Ltd.

SOL Transfer Validation



This is an existing script hook provided to additional validation during SOL transfer operation. Two additional inputs are dumped now as part of the enhancement.

Inputs Available in the Scripts

The additional Inputs that are dumped into the script will be available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring to the fields in the following manner.

BANCS.INPUT.<Fieldname>

Field Name	Details
AccountId	Foracid of Account Number being Transferred
TargetSolId	Target SOL Id to which transfer is happening

Output Expected

The same output will be available in the output repository. The defined outputs will be available in repository BANCS, class OUTPUT and with the field

names. One can access the outputs by referring to the fields in the following manner.

BANCS.OUTPUT.<Fieldname>

Default logic in case script is not present

Not Applicable

Typical usage scenario(s)

It can be used to implement site specific validation for an account to be transferred between sols.

Sample Script

No Sample script is present in the Sample scripts (\$TBA_SAMPLE/samscripts) directory.

©Copyright Infosys Ltd.

Queue ID for the Account under Excess Management



Script Name:

The script EM_queueGeneration.scr identifies the Queue id for the account under Excess Management. This script must be placed under TBA_SCRIPTS dir.

Input:

The defined inputs are available in repository EXCESS, class GENERAL and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

EXCESS.GENERAL.<fieldName>.

EXCESS.GENERAL.<Field Name>_<Record_number> for item level fields. Please note that the record number starts from 1.

Complete EMHT record is taken as input.

Field Name - Account level	Details
EXCESS.GENERAL.EXCESS_ACID	Customer account which has been taken for Excess Management decisioning.
EXCESS.GENERAL.EXCESS_DATE	Date on which the item entered excess queue.
EXCESS.GENERAL. SOL_ID	Sol Id of the account taken to the excess queue.
EXCESS.GENERAL. ITEM_COUNT	Total number of CHQ or ACH or MANDATE items in EMDT table.
EXCESS.GENERAL.TOT_DEBIT_AMT	Consolidated Amount for all the items under excess queue for the account.
EXCESS.GENERAL.TOT_DEBIT_CRNCY	Currency associated with the total debit amount.
EXCESS.GENERAL. QUEUE_ID	The queue id to which the account belongs.
EXCESS.GENERAL. REF_QUEUE_ID	

	The queue id from which this account was referred to the current queue.
EXCESS.GENERAL. REF_REMARKS	Remarks provided when the account was referred to the current queue.
EXCESS.GENERAL. REF_COUNT	Number of times the account has been referred to a different Queue.
EXCESS.GENERAL. IS_GEN_OR_REGEN	Specifies whether the current run is queue generation or regeneration for the account.

Field Name - Item level	Details
EXCESS_ACCT_ID_<Record_number>	Customer account which has been taken for Excess Management decisioning.
ENTITY_TYPE_<Record_number>	Indicates the Payment mode or CLEARING for the transaction which is under EM.
ENTITY_ID_<Record_number>	The AED or ICI key separated by ~Q or ~R.
EM_DECISION_<Record_number>	Indicates the current decision taken on the Excess item. Valid Values: P-Pay, N-No Pay, D-Defer.
CONFIRM_FLG_<Record_number>	Indicates whether the current decision taken on the Excess item is confirmed. Valid Values: Y-YES or N-NO.
TRAN_ID_<Record_number>	Stores the transaction id for the current transaction.
PREV_DECISION_<Record_number>	Indicates the previously confirmed decision taken on the excess item. Valid Values: NULL, P-Pay, N-No Pay.
PREV_TRAN_ID_<Record_number>	Stores the Transaction Id of the last transaction for the excess item.

PREV_PART_TRAN_ID_<Record_number>	Stores the part transaction Id corresponding to the clearing instrument which has been taken into Excess Management.
DECISION_MODE_<Record_number>	Indicates the mode of the last decision made on the excess item. Valid Values: M-Manual, A-Automatic.
EXCESS_DATE_<Record_number>	Date on which the item entered excess queue.
TRAN_AMT_<Record_number>	Transaction Amount of the item under excess decisioning.
TRAN_CRNCY_<Record_number>	Currency of the transaction Amount of the item under excess decisioning.
WAIVE_CHARGES_<Record_number>	Flag to indicate waiver of charges, if set to Y no charges will levied else charges will be calculated as per the setup. Valid Values: Y or N.
RETURN_REASON_CODE_<Record_number>	Stores the reason code entered by the user when a No Pay decision is taken on the excess item.
ITEM_STATUS_<Record_number>	Open or Closed ~V Denotes whether this item is currently active or closed after closure batch. Valid Values: O-Open or C-Closed.
LAST_DECISION_EFF_AVL_BALANCE_<Record_number>	Effective available balance when the last decision was taken.
LAST_DECISION_ANTICP_CR_<Record_number>	Anticipated Credit when the last decision was taken.
LAST_DECISION_ANTICP_DR_<Record_number>	Anticipated Debit when the last decision was taken.
ACCT_CRNCY_CODE_<Record_number>	Currency associated with the

	anticipated credit or debit amount and the effective available balance.
FREE_CODE_<Record_number>	Free Code for Excess management Record.
SORT_CODE_<Record_number>	Sort Code for Excess management Record.
ORIG_TXN_CONSOLIDATED_FLG_<Record_number>	Flag which denotes whether the transaction which is created in AED or ICI is consolidated or not.

Output:

The output of the script will be available in the specified repository fields:

Field Name - Item level	Details
QUEUE_ID	The queue id to which the account belongs.
successOrFailure	Whether queue id could be assigned successfully or not. 'S' – Success. Failure otherwise.
ERROR_MSG	If successOrFailure is not success, then the corresponding error message.

Default Logic:

This script is not mandatory but the account will not have a queue id.

Typical Usage Scenario:

For all scenarios in Excess, this script should give a queue id for an account under Excess Management.

Example:

NA

©Copyright Infosys Ltd.

Finacle Copyright

Automatic Decisions for an Account



Script Name:

The script EM_GetDecisionForAccount.scr is used to assign decisions for a given criteria whether to pay or no-pay the amount came for excess management. This script must be present in TBA_SCRIPTS dir.

Input:

The defined inputs are available in repository EXCESS, class GENERAL and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

EXCESS. GENERAL.<Fieldname>

Field Name	Details
EXCESS_ACCT_ID_<Record_number>	Customer account which has been taken for Excess Management decisioning.
ENTITY_TYPE_<Record_number>	Indicates the Payment mode or CLEARING for the transaction which is under EM.
ENTITY_ID_<Record_number>	The AED or ICI key separated by ~Q or ~R.
EM_DECISION_<Record_number>	Indicates the current decision taken on the Excess item. Valid Values: P-Pay, N-No Pay, D-Defer.
CONFIRM_FLG_<Record_number>	Indicates whether the current decision taken on the Excess item is confirmed. Valid Values: Y-YES or N-NO.
TRAN_ID_<Record_number>	Stores the transaction id for the current transaction.

PREV_DECISION_<Record_number>	Indicates the previously confirmed decision taken on the excess item. Valid Values: NULL, P-Pay, N-No Pay.
PREV_TRAN_ID_<Record_number>	Stores the Transaction Id of the last transaction for the excess item.
PREV_PART_TRAN_ID_<Record_number>	Stores the part transaction Id corresponding to the clearing instrument which has been taken into Excess Management.
DECISION_MODE_<Record_number>	Indicates the mode of the last decision made on the excess item. Valid Values: M-Manual, A-Automatic.
EXCESS_DATE_<Record_number>	Date on which the item entered excess queue.
TRAN_AMT_<Record_number>	Transaction Amount of the item under excess decisioning.
TRAN_CRNCY_<Record_number>	Currency of the transaction Amount of the item under excess decisioning.
WAIVE_CHARGES_<Record_number>	Flag to indicate waiver of charges, if set to Y no charges will levied, else charges will be calculated as per the setup. Valid Values: Y or N.
RETURN_REASON_CODE_<Record_number>	Stores the reason code entered by the user, when a No Pay decision is taken on the excess item.
ITEM_STATUS_<Record_number>	Open or Closed ~V Denotes whether this item is currently active or closed after closure batch. Valid Values: O-Open or C-Closed.

LAST_DECISION_EFF_AVL_BALANCE_<Record_number>	Effective available balance when the last decision was taken.
LAST_DECISION_ANTICP_CR_<Record_number>	Anticipated Credit when the last decision was taken.
LAST_DECISION_ANTICP_DR_<Record_number>	Anticipated Debit when the last decision was taken.
ACCT_CRNCY_CODE_<Record_number>	Currency associated with the anticipated credit or debit amount and the effective available balance.
FREE_CODE_<Record_number>	Free Code for Excess management Record.
SORT_CODE_<Record_number>	Sort Code for Excess management Record.
ORIG_TXN_CONSOLIDATED_FLG_<Record_number>	Flag which denotes whether the transaction which is created in AED or ICI is consolidated or not.

Output:

The output of the script will be available in the specified repository fields:

EXCESS.GENERAL.<Field_name>

Field Name	Details
DecisionMade_<record_number>	em_decision can be Pay, NoPay or Defer depending on the conditions set in the script.
ConfirmFlag_<record_number>	Confirm flag is set as N or Y, if the decision is confirmed, which will result in immediate transactions.
ChargesWaived_<record_number>	Charges to be waved or not for the transaction. Can be Y or N.
ConsolidatFlg_<record_number>	Can be Y or N.
ReturnReasonCode_<record_number>	Return Code if the decision is No Pay.

Default Logic:

It is mandatory for the script to be present. In its absence a fatal error “Script not found [EM_GetDecisionForAccount.scr]” is displayed, when ADEMR is run.

Typical Usage Scenario:

When automated decisioning needs to be made, ADEMR menu issued. The logic for applying decisions is left to the bank to be customized based on this script.

Example:

NA

©Copyright Infosys Ltd.

Check Digit for Random Account Generation



Script Name:

The script CheckDigit.sscr called only if the Check Digit Flag value is 'S' or 'W'. It calculates the Check Digit by applying Modulus operation. For Random Account Number Generation, this script will return the first number from the sequence of numbers (passed to the script as an input as pipeSepNumbSeq). The first number from the sequence will be returned as next number for account number generation. This next number will be used to form the applyString. Also, it will set the overridePrefixSuffix value, which will override the Prefix and Suffix value, if the Random Account Generation is yes.

This script must be present in TBA_SCRIPTS directory.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
numType	This indicates the type of entity being linked. For example, Accounts, Bills etc. Valid Values are A-Account number, B-Bill number, C-Advice number, D-BAR number, E-TDS certificate number, F-Stock invest number, G-Serial number, I-BG serial number, L-DC reference number,

	R-Forward contract number, U-Customer number, S-DSA Id. For Account Generation, num_type is "A".
applyString	This will have the prefix, next number and suffix value concatenated, if CheckDigit Flag is "W" – FULL WITH SCRIPT, else only the next number. If Random Account Generation is Yes and Random Account Selection Criteria, that is, when isSysGenRanAcct is "N" then this string has nulls value.
nextNum	Next number is sent, in case Random Account Selection Criteria is 'Y'; else next number is generated in the script itself from the sequence.
checkDigitFlag	Indicates what logic should be used for the digit generated. Valid Values are Y, F, S and W. 'F' means system will consider all the prefixes and suffixes (necessarily these should be numeric) also for arriving at the check digit. 'S' means customized logic is used only taking the serial number portion.' W' means totally customized logic as per the user.
prefixString	String to be prefixed.
suffixString	String to be suffixed.
isRanAcctGen	Flag which will hold value Y or N will represent, if Random Account Generation is set. Based on this flag, customization can have a logic to return a random number.
isSysGenRanAcct	Flag that can have Y or N as values. It will represent, if Random Account Number will be system generated or not. In case of No, the customization can Check digit and Modulus logic, only on the input number.
pipeSepNumbSeq	This will hold the pipe separated list of unutilized numbers. Customization can select any number present in the list based on its custom selection logic.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Output parameters from the script are:

nextNum, checkDigit, applyString, successOrFailure, errorString (if

there is any error), overridePrefixSuffix.

Field Name	Details
overridePrefixSuffix	This will be the additional output parameter provided. If its value is defined, then it will override the default prefix and suffix set in the NNTM.
nextNum	The next number to be used for account number generation.
CheckDigit	A digit which need to be appended with the next number formed depending on the CheckDigit Flag value.
applyString	This will have the prefix, next number and suffix value concatenated, if CheckDigit Flag is “W” – FULL WITH SCRIPT, else only the next number.

Default Logic:

Script is mandatory, if Check Digit Flag has a value “S” or “W” and Select Random Account ID is set as “Y”.

Typical Usage Scenario:

This script will be called during account creation (provided selected scheme is set to have A/C generation flag as Y) if the Check Digit Flag value is ‘S’ or ‘W’.

Example:

NA

Transfer of Accounts Across Scheme Codes



The **AddnlSchmParamforHACXFRSC.sscr** is a script called by HACXFRSC and HBTACSC, for the transfer of accounts across scheme codes.

This script must be present in TBA_SCRIPTS directory.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned. You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
Acctid	Account Id
FromschemeCode	From Scheme Code
ToschemeCode	To Scheme Code
schemeType	Scheme Type
custSectorCode	MIS Codes (from GAC table) – Sector Code
custSubSectorCode	MIS Codes (from GAC table) –
acctOccpCode	MIS Codes (from GAC table) –
borrowerCategoryCode	MIS Codes (from GAC table) –
purposeOfAdvn	MIS Codes (from GAC table) –
modeOfAdvn	MIS Codes (from GAC table) –
typeOfAdvn	MIS Codes (from GAC table) –
natureOfAdvn	MIS Codes (from GAC table) –

guarCoverCode	MIS Codes (from GAC table) –
industryType	MIS Codes (from GAC table) –
freeCode1	MIS Codes (from GAC table) –
freeCode2	MIS Codes (from GAC table) –
freeCode3	MIS Codes (from GAC table) –
freeCode4	MIS Codes (from GAC table) –
freeCode5	MIS Codes (from GAC table) –
freeCode6	MIS Codes (from GAC table) –
freeCode7	MIS Codes (from GAC table) –
freeCode8	MIS Codes (from GAC table) –
freeCode9	MIS Codes (from GAC table) –
freeCode10	MIS Codes (from GAC table) –
iasCode	MIS Codes (from GAC table) –
hedgedAcctFlg	MIS Codes (from GAC table) –
usedForNetOffFlg	MIS Codes (from GAC table) –
freeText1	MIS Codes (from GAC table) –
freeText2	MIS Codes (from GAC table) –
freeText3	MIS Codes (from GAC table) –
freeText4	MIS Codes (from GAC table) –
freeText5	MIS Codes (from GAC table) –
freeText6	MIS Codes (from GAC table) –
freeText7	MIS Codes (from GAC table) –
freeText8	MIS Codes (from GAC table) –
freeText9	MIS Codes (from GAC table) –
freeText10	MIS Codes (from GAC table) –

freeText11	MIS Codes (from GAC table) –
freeText12	MIS Codes (from GAC table) –
freeText13	MIS Codes (from GAC table) –
freeText14	MIS Codes (from GAC table) –
freeText15	MIS Codes (from GAC table) –
batchOrOnline	Flag whether calling program is batch or online menu
trfReasonCode	Account Transfer Reason Code
trfReasonCodeDesc	Account Transfer Reason Code Desc
trfRemarks	Account Transfer Reason Remarks

Output:

The output of the script will be available in the specified repository field.

BANCS.OUTPUT.<fieldName>

Output parameters from the script are:

nextNum, checkDigit, applyString, successOrFailure, errorString (if there is any error),overridePrefixSuffix

Field Name	Details
successOrFailure	Success or Failure
acctStmt	Account Statement Code
allowSweeps	Allow Sweeps Flag
sweepMinBal	Sweeps minimum balance
GACUpdateReqd	GAC updated Required Flag
MisCodeUpdateReqd	MIS updated Required Flag
intCompFreqforDr	Daily Compound Interest Flag

applyDiscIntRate	Apply Discount Rate Flag
custSectorCode	MIS Codes (from GAC table) – Sector Code
custSubSectorCode	MIS Codes (from GAC table) –
acctOccpCode	MIS Codes (from GAC table) –
borrowerCategoryCode	MIS Codes (from GAC table) –
purposeOfAdvn	MIS Codes (from GAC table) –
modeOfAdvn	MIS Codes (from GAC table) –
typeOfAdvn	MIS Codes (from GAC table) –
natureOfAdvn	MIS Codes (from GAC table) –
guarCoverCode	MIS Codes (from GAC table) –
industryType	MIS Codes (from GAC table) –
freeCode1	MIS Codes (from GAC table) –
freeCode2	MIS Codes (from GAC table) –
freeCode3	MIS Codes (from GAC table) –
freeCode4	MIS Codes (from GAC table) –
freeCode5	MIS Codes (from GAC table) –
freeCode6	MIS Codes (from GAC table) –
freeCode7	MIS Codes (from GAC table) –
freeCode8	MIS Codes (from GAC table) –
freeCode9	MIS Codes (from GAC table) –
freeCode10	MIS Codes (from GAC table) –
iasCode	MIS Codes (from GAC table) –
hedgedAcctFlg	MIS Codes (from GAC table) –
usedForNetOffFlg	MIS Codes (from GAC table) –
freeText1	MIS Codes (from GAC table) –

freeText2	MIS Codes (from GAC table) –
freeText3	MIS Codes (from GAC table) –
freeText4	MIS Codes (from GAC table) –
freeText5	MIS Codes (from GAC table) –
freeText6	MIS Codes (from GAC table) –
freeText7	MIS Codes (from GAC table) –
freeText8	MIS Codes (from GAC table) –
freeText9	MIS Codes (from GAC table) –
freeText10	MIS Codes (from GAC table) –
freeText11	MIS Codes (from GAC table) –
freeText12	MIS Codes (from GAC table) –
freeText13	MIS Codes (from GAC table) –
freeText14	MIS Codes (from GAC table) –
freeText15	MIS Codes (from GAC table) –
ASTUpdateReqd	AST update Required Flag
stmtFreqType	Statement Frequency Type
freqWeekNum	Statement Frequency
freqStartDate	Statement Frequency
freqHolidayStat	Statement Frequency
freqCalBase	Statement Frequency
updIntTableCode	Flag for whether Account Level Interest Table code should be overridden by target scheme interest table code, or not.
trfReasonCode	Account Transfer Reason Code
trfReasonCodeDesc	Account Transfer Reason Code Desc
trfRemarks	Account Transfer Reason Remarks

Default Logic:

Default logic is none.

Typical Usage Scenario:

This script will be called during Transfer of Accounts across Scheme Codes, through menu HBTACSC, and Verify mode of HACXFRSC.

Example:

NA

©Copyright Infosys Ltd.

Script to Check Pre-notification Advice



For collection of prenotified charges as part of validation, it is checked if prenotification advice has been printed or not. The sample script checkPrenoteAdvice.sscr can be used to bypass advice flag validation and can be used as part of customization, if required.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.accountId	Account Id
BANCS.INPUT.currencyCode	Currency Code
BANCS.INPUT.solId	The sol id
BANCS.INPUT.prenoteDate	The prenotification Date

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Valid Values are "S" or "F." If script is executed successfully then "S" will be returned else "F" will be returned.

©Copyright Infosys Ltd.

Finacle Copyright

ACH Events



ACH is nothing but Automatic Clearing House. Finacle provides scripting events to process or create different types of transactions like

- ONUS Transactions
- OFFUS Transactions
- Inward Debit Transactions
- ACH Return Processing Transactions

Also, there are events which help us in parsing the ACH Details and ACH Header Details.

The different ACH events are:

- [Creation of ACH Return Processing Transaction](#)
- [Define ACH Offus Processing](#)
- [Define ACH Onus Processing](#)
- [Define ACH Inward Debit Transaction](#)
- [Parse ACH Details](#)
- [Parse ACH Header Details](#)
- [Bill Payment Interface Access for Customer Processing](#)
- [Generate an Outward File Name as per Implementation](#)
- [File Duplicate Check in HACHUPL Menu Option](#)
- [Initializing ACH Dependent Values](#)

- [Multirepay Demand Satisfaction Processing](#)
- [Populate Reason Code For ACH](#)
- [Preprocessing Records for Accessing](#)
- [Transcription Script for Return Processing](#)
- [Transcription Script for Settlement Processing](#)
- [Transcription Script for Suspense Processing](#)
- [Update Entry Status For ACH](#)
- [XML to DB Mapping](#)
- [XML to DB Mapping for Header Record](#)
- [A CH Check Authorization Required For CP](#)
- [ACHUPL Get File Type](#)
- [ACH Holiday Check For BACS](#)
- [ACH Use HCRT Services For reversal](#)
- [Get Rectification Accounts](#)
- [Get File Rectification Accounts](#)
- [ACH-get Business Days](#)
- [To Skip the ACH Records from GEMQ](#)
- [To Identify whether the ACH Instruction in Upload Flat File is Unpaid Claim Generation or Not](#)
- [To Generate the Unpaid Claim ACH Instruction](#)

- ACH – is MRI table Operation Required
- Generate SQL Query for Batch Programs in ACH
- Update AED Records
- Creation of ACH Outward Return Processing Transaction
- Consolidated Settlement Transaction Creation Script
- Consolidated Customer Transaction Creation Script
- MANTM Process for Non Fin Message
- Script to Populate Transaction Code from Loans Module
- Script to Create Mandate for First Collection Transaction Code
- Script to Identify Payments within a Specific Period
- Script to Validate Authorization Details
- Script to Update Status of the ACH instruction After Suspense Processing
- Script to Cancel Mandate
- Script to Cancel Mandate after Receiving Final Payment
- Script to Create Inward Mandate
- Script to Amend Inward Mandate
- Script to Cancel Inward Mandate
- Script to Reinstate Inward Mandate
- Script to Check if Mandate Exists for First Collection Transaction

Code

- [Script to Populate Transaction Code from Loans Module](#)
- [Script to Create Mandate for First Collection Transaction Code](#)
- [Script to Identify Payments within a Specific Period](#)
- [Script to Validate Authorization Details](#)

©Copyright Infosys Ltd.

ACH Check Authorization Required For CP



Script Name:

The script `ACH_checkAuthorizationRequiredforCP.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to check Authorization required for CP.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. IsAuthReqdFlg	Authorization Required Flag
BANCS.INPUT. OrigAcct	Originator Account
BANCS.INPUT. RecvAcctDtls	Receiver Account
BANCS.INPUT. SenderBic	Sender Bic
BANCS.INPUT. RecvBic	Receiver Bic

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. IsAuthReqdFlg	Authorization required Flag.

Typical Usage Scenario:

This script is called when Implement Type in PAYSYS Level is “BACS”. This script will be used to check authorization required for Customer Processing.

Example: NA

©Copyright Infosys Ltd.

ACHUPL Get File Type



Script Name:

The script `ACHUPL_getFileType.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to get file Type for Input XML file.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
NA	NA

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
<code>BANCS.OUTPUT.fileType</code>	File Type for Uploading Input XML file.

Typical Usage Scenario:

This script is called when XML Conversion required is "YES" in `paymentsys.dat` and also when XML file is being uploaded.

Example:

NA

©Copyright Infosys Ltd.

Finacle Copyright

ACH Holiday Check For BACS



Script Name:

BACS_checkForAchHoliday.sscr:

The script must be present in TBA_SCRIPTS directory. It is called for checking lead days and ACH holiday and deriving the settlement date.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.SettlementDate	Settlement date dumped from cxx
BANCS.INPUT.PaysysId	Paysys Id

Output:

Field Name	Details
BANCS.OUTPUT.ErrorDesc	Contains Error Message.
BANCS.OUTPUT.successOrFailure	Contains the value "S" for Success/"F" for Failure.
BANCS.OUTPUT. ErrorCode	Contains Error Code for the message
BANCS.OUTPUT. SettlementDate	Contains the derived settlement date based on lead days and ACH Holiday.
BANCS.OUTPUT.EffectiveDate	Contains Effective date

Typical Usage Scenario:

As it is a Sample script, it will be called only if it is present in TBA_SCRIPTS directory.

This script is called from achap015.cxx, when Implement Type in PAYSYS Level is “BACS”. It derives the actual settlement date based upon ACH holiday check and lead days defined at PAYSYS level for the paysys id.

Default logic incase script is not present

If the script is not present, the script related processing doesn't happen and settlement date entered by the user is taken as the final settlement date.

Example:

NA

©Copyright Infosys Ltd.

ACH Use HCRT Services For reversal



Script Name:

The script ACH_useHCRTServicesForReversal.scr must be present in TBA_SCRIPTS directory. This script will be used to decide whether HCRT services are to be used for reversals in Recalls.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. PaysysId	Identifies the paysysId

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. HCRTFlg	Flag to enable or disable HCRT for Recalls.

Typical Usage Scenario:

As it is a Sample script, it will be called only if it is present in TBA_SCRIPTS directory.

This script used to set the value of HCRT flag depending on whether HCRT services are to be used or not.

©Copyright Infosys Ltd.

Get Rectification Accounts



Script Name:

The script `getRectificationAccounts.scr` must be present in `TBA_SCRIPTS` directory. This script is used to derive rectification accounts for HCRT reversals for record recall.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. InwOutwInd	Indicates the inward/outward indicator of the ACH instruction.
BANCS.INPUT. CrDrInd	Indicates the credit/debit indicator of the ACH instruction.
BANCS.INPUT. ReturnStatus	Indicates the return status of the ACH instruction.
BANCS.INPUT. TxnStatus	Indicates the transaction status of the ACH instruction.

Output:

The output of the script will be available in the specified repository fields

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
------------	---------

**BANCS.OUTPUT.
CrRectAcct** Indicates the rectification account to be credited.

**BANCS.OUTPUT.
DrRectAcct** Indicates the rectification account to be debited.

Typical Usage Scenario:

This script used to fetch the rectification accounts for reversal.

©Copyright Infosys Ltd.

Get File rectification Accounts



Script Name:

The script `getFileRectificationAccounts.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to derive rectification accounts for HCRT reversals for file recall.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. CrDrInd	Indicates the credit/debit indicator of the ACH instruction.
BANCS.INPUT. TxnStatus	Indicates the transaction status of the ACH instruction.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT CrRectAcct	Indicates the rectification account to be credited.
BANCS.OUTPUT. DrRectAcct	Indicates the rectification account to be debited.

Typical Usage Scenario:

This script used to fetch the rectification accounts for reversal.

©Copyright Infosys Ltd.

ACH-Get Business Days



Script Name:

The script `ACH_getBusinessDays.scr` will get the Business days.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
<code>BANCS.INPUT.paysysid</code>	Paysys Id

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
<code>BANCS.OUTPUT. ErrorDesc</code>	Error Message.
<code>BANCS.OUTPUT. successOrFailure</code>	Success or Failure Indicator
<code>BANCS.OUTPUT.SettlementDate</code>	The business date

Typical Usage Scenario:

The script `ACH_getBusinessDays.scr` will get the Business days.

Example:

NA

©Copyright Infosys Ltd.

Finacle Copyright

To Skip the ACH Records from GEMQ



Script Name:

The script EM_skipACHRecord.sscr, let the user decide whether to skip an ACH item or not. It must be placed under the dir \$TBA_SCRIPTS.

Input:

The defined inputs are available in repository PAYSYS, class ACH and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

PAYSYS.ACH.<field_name>

Field Name	Details
paysysId	Paysys ID are created using Option PAYSYS with System type- H for use with ACH.
OrigAcct	This field contains the Originator Account ID.
OrigId	A Valid identifier for the originator of transaction. For example, Organisational Code associated with the Account can be used as the orig ID.
OrigInfo1	Additional information about originator.
OrigInfo2	Additional information about originator.
OrigName	Name of the originator.
service_code	Product of the originator or biller.
RecvAcctDtIs	This field stores the receiver account number entered by the user.This will be populated during upload only.
RecvAcct	Receiver Account foracid.
RecvId	Identification of the receiver.
RecvInfo1	Additional information about receiver.

RecvInfo2	receiver_info2.
RecvName	Receiver name.
RecvAcid	Receiver Account acid.
TranAmt	The amount for which the transaction is created.
TranCrncy	Transaction Currency.
CommisionAmt	Commission amount for the transaction.
TotalAmt	Total amount is transaction amount plus commission amount.
OutwardCommision	OutwardCommision.
RejectAmt	RejectAmt.
OtherAmt1	OtherAmt1.
OtherAmt2	OtherAmt2.
SettlementDate	SettlementDate.
DueDate	Due date.
Date1	Additional Date Field. Can be used for customization purposes.
Date2	Additional Date Field. Can be used for customization purposes.
BankCode	Bank Code.
BranchCode	Branch Code.
Solld	Service Outlet Id of the Account.
OrigCode	Originator Code.
RejCode	Rejection Code. Reason Codes are maintained in HPRCM. Mandatory, if transaction is made to rejected status.
RejDesc	Rejection Description -- reason for failure. Populated from ACH_PAYSYS_REASON_CODE_TABLE table for a given rejection code.
EntryStatus	Status of the record. P - Processed, R - Rejected, S - Suspended, U - Under Processing, G - Direct Recall, B - To be recalled, C - Recalled , J - Unmatched Recall.
ReturnStatus	Return Status. Valid values are R - Ready to Send, S - Sent , N - Not to be sent.

FailProcess	Indicates Failure Processing is Automatic or Manual/Suspense Processing. A -Automatic, M -Manual
status2	Additional status field which can be used for customization purposes.
ReturnInd	Values are S -Success,B -Both,F -Failure, N -None
CrDrInd	Credit Debit indicator. Valid values are C - Credit, D - Debit.
InwOutwInd	Valid values are I - Inward, O - Outward.
FreshRetEntry	Entry type. Valid values are 0 - Fresh entry, 1 - return entry, 2 - Reject entry, 3 - Recall entry.
TranCode	Transaction Code. Transaction Codes are defined in HRRCDM in the link tran_code. Mandatory Field
CustTranId	Transaction Id of Customer transaction.
CustTranDate	Transaction date of Customer transaction.
SettTranId	Transaction Id for the settlement transaction.
SettTranDate	Transaction date of Settlement transaction.
TraceNum1	Additional trace number.
TraceNum2	Additional trace number.
TraceNum3	Additional trace number.
ApproverCmnt	Comments by approver.
FreeCode1	Free code. Free Code 1 is maintained in RRCDDM in reference type JB.
FreeCode2	Free code. Free Code 1 is maintained in RRCDDM in reference type JC.
FreeCode3	Free code. Free Code 1 is maintained in RRCDDM in reference type JD.
FreeCode4	Free code. Free Code 1 is maintained in RRCDDM in reference type JE.
FreeCode5	Free code. Free Code 1 is maintained in RRCDDM in reference type JF.
FreeText1	Free text. Additional Information can be entered here.

FreeText2	Free text. Additional Information can be entered here.
FreeText3	Free text. Additional Information can be entered here.
FreeText4	Free text. Additional Information can be entered here.
FreeText5	Free text. Additional Information can be entered here.
IntTranId	Transaction Id when the entry fails and needs suspense processing.
TxnStatus	Indicates the next status that the entry has to perform. C =Float-Customer, F =Customer-Float, O =Settlement-Float, S =Float-Settlement , X =Closed.
SourceId	Source from where transaction is getting uploaded. For example, if it is created from HACHCOD, it is populated as COD.
SingleMultipleDRFlag	Denotes whether single or multiple transactions for a batch. Values are S - Single and M - Multiple.
LienorDebitFlag	Denotes the transaction is direct debit or Lien. Values are D - Debitand L - lien. Default value is D.
SystemId	Denotes the System, if the account is Non Finacle account.
OrigTranAcct	This field is the same as OrigAcct. If OrigAcct is not a finacle account, then it will populated as a internal office a/c, same will happen, in case the entry is lodged from the other module.
LienId	Lien id for the A/c. This Lien placed on account as a result of this transaction. System Generated.
BatchId	Header srl num of the batch record in AHD.
DAReferencenumber	Debit Authorization Reference Number. If the transaction is based on a debit authorization request, then this refers to reference number of the same. Mapped to DBAT.da_ref_no.
OrigSettlementDate	Originator settlement Date.
AutoReturnFlag	Flag to indicate, if auto return is enabled. Values are Y - Yes and N - No.
RefundAcct	Refund account number for refund to other modules.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT. successOrFailure

Default Logic:

All the records will be picked.

Typical Usage Scenario:

Whenever any particular record needs to be dropped from coming into Excess, this will be used. These reasons might vary from bank to bank.

Example:

NA

©Copyright Infosys Ltd.

To Identify whether the ACH Instruction in Infosys® Upload Flat File is Unpaid Claim Generation or Not



Script Name:

The script `BACS_isUnpaidClaimRequest.sscr` is a sample script provided for BACS customization and should be present in `samscripts` directory. This script will be moved to `$TBA_SCRIPTS` folder as `BACS_isUnpaidClaimRequest.scr`.

This script will be used to identify whether the ACH instruction in upload flat file is unpaid claim generation or not.

Input:

The defined inputs are available in repository `BANCS`, class `INPUT` and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

`BANCS.INPUT.<Fieldname>`

Field Name	Details
tranCode	Transaction code of ACH instruction in ACH upload file.
RecvAcctDtls	Receiver account details of ACH instruction in ACH upload file.
IsAcctReq	Flag [Y or N] will be passed, whether unpaid claim suspense account placeholder is required as an output.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`



Field Name	Details
successOrFailure	Return the status, whether the script is success (S) or failure (F).
errorMessage	Appropriate error message.
unpaidClaimSuspAcct	If the IsAcctReq is “Y” , then this will be returned.

Default Logic:

If the script BACS_isUnpaidClaimRequest.scr is not present, then the error “The script BACS_isUnpaidClaimRequest.scr is not available to process” is displayed to the front-end Script.

Typical Usage Scenario:

This script will be called from CXX sources.

Example:

NA

©Copyright Infosys Ltd.

To Generate the Unpaid Claim ACH Instruction



Script Name:

The script `BACS_unPaidClaimACHGeneration.sscr` is a sample script provided for BACS customization and should be present in `samscripts` directory. This script will be moved to `$TBA_SCRIPTS` folder as `BACS_unPaidClaimACHGeneration.scr`

This script will be used to generate the unpaid claim ACH instruction as part of inward cycle.

Input:

The defined inputs are available in repository `BANCS`, class `INPUT` and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

`BANCS.INPUT.<Fieldname>`

Field Name	Details
paysysId	Paysys_id.
Acid	Account.
clmAmt	Claim amount.
presBankCode	Presenting bank code.
presBranchCode	Presenting branch code.
acctSolId	Sol_id of account.
origTranAcct	Original transaction account.
draweeSortCode	Drawee bank identifier.
presSortCode	Presenting bank identifier.
zoneCrncy	CCY of ZONE.

instNum	Instrument number.
instType	Instrument type.
instAlpha	Instrument Alpha.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
unPaidClaimRefNum	Unpaid claim reference number.
unPaidSettmntDate	Unpaid claim settlement date.
errorDesc	Error description.
successOrFailure	Success or failure of the script.

Default Logic:

If the script BACS_unPaidClaimACHGeneration.scr is not present, then the error “BACS_unPaidClaimACHGeneration.scr does not exist” is displayed to the front-end.

Typical Usage Scenario:

This script will be called from CXX sources.

Example:

NA

ACH – is MRI table Operation Required



Script Name:

The script `ACH_isMRITableOperationRequired.scr` checks whether MRI table Operation is required.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
<code>BANCS.INPUT.paysysid</code>	Paysys Id
<code>BANCS.INPUT.BankId</code>	Bank Id
<code>BANCS.INPUT.ImplementType</code>	Implementation Type

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
<code>BANCS.OUTPUT.isMRITableInsertRequired</code>	Flag to indicate whether MRI table insertion is required or not
<code>BANCS.OUTPUT. successOrFailure</code>	Success or Failure Indicator

Typical Usage Scenario:

The script ACH_isMRITableOperationRequired.scr checks whether MRI table Operation is required.

Example:

NA

©Copyright Infosys Ltd.

Generate SQL Query for Batch Programs in ACH



This script has the query for picking up the records that satisfies the criteria given in the batch menu options HACHRP, HACHSP, HACHCP. The **<implementationType>_<exe name>_formQuery.scr** script allows you to generate SQL queries for all batch programs.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
PaysysId	The payment system ID.
Date	The date of payment.
BodDate	The BOD date.
BatchName	The batch identity. Batch name for the menu
InputFileName	Name of the input file.
FlgValue	Indicates if G or R.
HighDate	The maximum date for transaction
FlgValue	Flag value
PaysysId	Paysys Id
InputFileName	Input file name given
Date	Date
FreeText1	Free Text1
SolId	Sol ID

ServiceSolId	Service SOL ID
InwOutwInd	Inward Outward Indicator
FileDestination	File Destination
FinFileFormat	Fin File Format
PymntTypeGroupCode	Payment Type Group Code
DailyConsolFlg	This decides whther to pick records eligible for daily consolidation or not. Y/N
OnusFlg	X – This decides whether to pick onus records
OutwardFlg	O – This decides whether to pick outward records
InwardFlg	I – This decides whether to pick inward records

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.MainQry	The query to the script.

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Update AED Records



The script **<implementation Type>_<exe name>_updateStatusFields.scr** is called while executing all batch programs for updating AED table records.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
BatchName	Batch Name
SelFld3	Field 3 selected from the query
SelFld2	Field 2 selected from the query
SelFld1	Field 1 selected from the query
TranId	Transaction ID
TranDate	Transaction Date
RetOrDishFlg	Return or Dishonor Flag
ReturnFileName	Return File Name
ReturnDate	Return Date
OrigAcct	Originator Account
OrigId	Originator ID
OrigInfo1	Originator Information 1
OrigInfo2	Originator Information 2
OrigName	Originator Name
SrvCode	Service Code

RecvAcct	Receiver Account
RecvAcctDtls	Receiver Account Detaila
RecvId	Receiver ID
RecvInfo1	Receiver Information 1
RecvInfo2	Receiver Information 2
RecvName	Receiver Name
RecvAcid	Receiver Account Acid
TranAmt	Transaction Amount
TranCrncy	Transaction Currency
CommisionAmt	Commission Amount
TotalAmt	Total Amount
OutwardCommision	Outward Commission
RejectAmt	Reject Amount
OtherAmt1	Other Amount1
OtherAmt2	Other Amount2
EffectiveDate	Effective Date
SettlementDate	Settlement Date
OrigSettlementDate	Original Settlement Date
DueDate	Due Date
Date1	Date 1
Date2	Date 2
BankCode	Bank Code
BranchCode	Branch Code
SolId	Sol ID
OrigCode	Originator Code
RejCode	Rejection Code
RejDesc	Rejection Desc
EntryStatus	Entry Status
ReturnStatus	Return Status

FailProcess	Failure Process
status2	Status 2
ReturnInd	Return Indicator
CrDrInd	Credit Debit Indicator
InwOutwInd	Inward Outward Indicator
FreshRetEntry	Fresh Return Entry
TranCode	Transaction Code
CustTranId	Customer Transaction ID
CustTranDate	Customer Transaction Date
SettTranId	Settlement Transaction ID
SettTranDate	Settlement Transaction Date
TraceNum1	Trace Num1
TraceNum2	Trace Num2
TraceNum3	Trace Num3
ApprovedBy	Approved By
ApproverCmnt	Approver Comments
FreeCode1	Free Code1
FreeCode2	Free Code2
FreeCode3	Free Code3
FreeCode4	Free Code4
FreeCode5	Free Code5
FreeText1	Free Text1
FreeText2	Free Text2
FreeText3	Free Text3
FreeText4	Free Text4
FreeText5	Free Text5
TxnStatus	Transaction Status
SourceId	Source ID

SingleMultipleDRFlag	Single Multiple DR flag
LienorDebitFlag	Lien or Debit flag
AutoReturnFlag	Auto Return Flag
CollectChrgFromAmtFlag	Collection charge amount flag.
LienId	Lien ID
BatchHdrSrlNum	Batch Header Serial Number
DAReferencenumber	DA Reference Number
RefundAcct	Refund Account
RateCode	Rate Code
Rate	Rate
ChrgAcct	Charge Account
ChargeAcid	Charge Account Acid
ChrgType	Charge Type
ChrgEventId	Charge Event ID
ChrgRateCode	Charge Rate Code
ChrgRate	Charge Rate
OrigAcctAddress1	Originator Account Address1
OrigAcctAddress2	Originator Account Address2
OrigAcctAddress3	Originator Account Address3
RespAcctAddress1	Responding Account Address1
RespAcctAddress2	Responding Account Address2
RespAcctAddress3	Responding Account Address3
ChargeEventType	Charge Event Type
OneShotFlg	One Shot Flag
UrgentFlg	Urgent Flag
OtherEntityStatus	Other Entity Status
PurposeCode	Purpose Code
OriginationCountry	Origination Country
RespondingCountry	Responding Country

UltimateDebtorName	Ultimate Debtor Name
UltimateDebtorAddress	Ultimate Debtor Address
UltimateDebtorCountry	Ultimate Debtor Country
UltimateDebtorId	Ultimate Debtor ID
UltimateCreditorName	Ultimate Creditor Name
UltimateCreditorAddress	Ultimate Creditor Address
UltimateCreditorCountry	Ultimate Creditor Country
UltimateCreditorId	Ultimate Creditor ID
EndToEndIdentification	End To End Identification
AutoRejectFlag	Auto Reject Flag
AdviceId	Advice ID
RecallDate	Recall Date
RecallInducedBy	Recall Induced By
RecallType	Recall Type
RecallChargeEventId	Recall Charge Event ID
RecallChargeTranId	Recall Charge Tran ID
RecallChargeTranDate	Recall Charge Tran Date
RecallTranId	Recall Tran ID
RecallTranDate	Recall Tran Date
RecvBic	Receiver BIC
SenderBic	Sender BIC
RejectTranId	Reject Transaction ID
RejectTranDate	Reject Transaction Date
CompensationAmt	Compensation Amount
WaiveChargeFlag	Waive Charge Flag
FlgValue	Flag value

Output:

This script returns the updated AED data.

Script Input	Description
BatchName	Batch Name
SelFld3	Field 3 selected from the query
SelFld2	Field 2 selected from the query
SelFld1	Field 1 selected from the query
TranId	Transaction ID
TranDate	Transaction Date
RetOrDishFlg	Return or Dishonor Flag
ReturnFileName	Return File Name
ReturnDate	Return Date
OrigAcct	Originator Account
OrigId	Originator ID
OrigInfo1	Originator Information 1
OrigInfo2	Originator Information 2
OrigName	Originator Name
SrvCode	Service Code
RecvAcct	Receiver Account
RecvAcctDtls	Receiver Account Details
RecvId	Receiver ID
RecvInfo1	Receiver Information 1
RecvInfo2	Receiver Information 2
RecvName	Receiver Name
RecvAcid	Receiver Account Acid
TranAmt	Transaction Amount
TranCrncy	Transaction Currency
CommisionAmt	Commission Amount
TotalAmt	Total Amount

OutwardCommision	Outward Commission
RejectAmt	Reject Amount
OtherAmt1	Other Amount1
OtherAmt2	Other Amount2
EffectiveDate	Effective Date
SettlementDate	Settlement Date
OrigSettlementDate	Original Settlement Date
DueDate	Due Date
Date1	Date 1
Date2	Date 2
BankCode	Bank Code
BranchCode	Branch Code
SolId	Sol ID
OrigCode	Originator Code
RejCode	Rejection Code
RejDesc	Rejection Desc
EntryStatus	Entry Status
ReturnStatus	Return Status
FailProcess	Failure Process
status2	Status 2
ReturnInd	Return Indicator
CrDrInd	Credit Debit Indicator
InwOutwInd	Inward Outward Indicator
FreshRetEntry	Fresh Return Entry
TranCode	Transaction Code
CustTranId	Customer Transaction ID
CustTranDate	Customer Transaction Date
SettTranId	Settlement Transaction ID
SettTranDate	Settlement Transaction Date

TraceNum1	Trace Num1
TraceNum2	Trace Num2
TraceNum3	Trace Num3
ApprovedBy	Approved By
ApproverCmnt	Approver Comments
FreeCode1	Free Code1
FreeCode2	Free Code2
FreeCode3	Free Code3
FreeCode4	Free Code4
FreeCode5	Free Code5
FreeText1	Free Text1
FreeText2	Free Text2
FreeText3	Free Text3
FreeText4	Free Text4
FreeText5	Free Text5
TxnStatus	Transaction Status
SourceId	Source ID
SingleMultipleDRFlag	Single Multiple DR flag
LienorDebitFlag	Lien or Debit flag
AutoReturnFlag	Auto Return Flag
CollectChrgFromAmtFlag	Collection charge amount flag.
LienId	Lien ID
BatchHdrSrlNum	Batch Header Serial Number
DAReferencenumber	DA Reference Number
RefundAcct	Refund Account
RateCode	Rate Code
Rate	Rate
ChrgAcct	Charge Account

ChargeAcid	Charge Account Acid
ChrgType	Charge Type
ChrgEventId	Charge Event ID
ChrgRateCode	Charge Rate Code
ChrgRate	Charge Rate
OrigAcctAddress1	Originator Account Address1
OrigAcctAddress2	Originator Account Address2
OrigAcctAddress3	Originator Account Address3
RespAcctAddress1	Responding Account Address1
RespAcctAddress2	Responding Account Address2
RespAcctAddress3	Responding Account Address3
ChargeEventType	Charge Event Type
OneShotFlg	One Shot Flag
UrgentFlg	Urgent Flag
OtherEntityStatus	Other Entity Status
PurposeCode	Purpose Code
OriginationCountry	Origination Country
RespondingCountry	Responding Country
UltimateDebtorName	Ultimate Debtor Name
UltimateDebtorAddress	Ultimate Debtor Address
UltimateDebtorCountry	Ultimate Debtor Country
UltimateDebtorId	Ultimate Debtor ID
UltimateCreditorName	Ultimate Creditor Name
UltimateCreditorAddress	Ultimate Creditor Address
UltimateCreditorCountry	Ultimate Creditor Country
UltimateCreditorId	Ultimate Creditor ID
EndToEndIdentification	End To End Identification
AutoRejectFlag	Auto Reject Flag
AdviceId	Advice ID

RecallDate	Recall Date
RecallInducedBy	Recall Induced By
RecallType	Recall Type
RecallChargeEventId	Recall Charge Event ID
RecallChargeTranId	Recall Charge Tran ID
RecallChargeTranDate	Recall Charge Tran Date
RecallTranId	Recall Tran ID
RecallTranDate	Recall Tran Date
RecvBic	Receiver BIC
SenderBic	Sender BIC
RejectTranId	Reject Transaction ID
RejectTranDate	Reject Transaction Date
CompensationAmt	Compensation Amount
WaiveChargeFlag	Waive Charge Flag
errormsg	Error Message
SystemId	System Id
successOrFailure	Success Or Failure Result

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Creation of ACH Outward Return Processing Transaction



For HACHORP menu option, the script **createAchorpReturn.scr** handles the transaction part of both original and return records picked by the query. This file handles the transactions of Generating Dishonor, Accepting Dishonor, Generating Contest and Accepting Contest Records.

For Generating Dishonor functionality, the transaction of credit and debit happens between Return Place Holder A/c. and Settlement A/c.

For Accepting Dishonor functionality, the transaction of credit and debit happens between Refund A/c. and Settlement A/c.

For Generating Contest functionality, the transaction of credit and debit happens between Refund A/c.

For Accepting Contest Functionality, the transaction of credit and debit is happening between Settlement A/C and Customer A/C.

Input:

The defined inputs are available in repository, MTT, class like InputDetails and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

MTT.InputDetails.<fieldname>

Script Name	Description
CrDrInd	Credit Debit Indicator
TranAmt	Transaction Amount
EntrySrlNum	Entry Serial Number
contextBankId	Context Bank ID
PaysysId	Paysys ID

EntryStatus	Entry Status
status2	Status 2
ChargeEventId	Charge Event ID
InwOutwInd	Inward Outward Indicator
RouteThroCustAcct	Route Through Customer Account Flag
RefundAcct	Refund Account
OrigTranAcct	Originator Transaction Account
TranCrncy	Transaction Currency
RateCode	Rate Code
Rate	Rate
chargeTranReqd	Charge Transaction Required Flag
ChargeEventType	Charge Event Type
ChrgRateCode	Charge Rate Code
ChrgRate	Charge Rate
ChargeCrAcct	Charge Credit Account
SolId	Sol ID
ChargeForacid	Charge Foracid
SourceId	Source ID
chargeType	Charge Typte
ChrgPartTranBusTypeList	Charge PartTranBus Type List
RefAmount	Reference Amount
FloatAcct	Float Account
OLDTRANSACTIONSTATUS	Old Transaction Status
outDrSettlementAcct	Outward Debit Settlement Account
OLDENTRYSTATUS	Old Entry Status
outCrSettlementAcct	Outward Credit Settlement Account

Output:

Balanced Transaction of both credit and debit on the original and return records.

Field Name	Details
Scripterror	Script Error
successOrFailure	Success Failure Result of the script
Description	Description of Error
TranDate	Transaction Date
TranType	Transaction Type
TranSubType	Transaction Sub Type
Remarks	Remarks
IgnoreExcp	Ignore Exception
Consolidate	Consolidate
PrintAdviceInd	Print Advice Indicator
ChrgPtranBusTypeList	Charge Ptran Bus Type List
CompensationAmt	Compensation Amount
Account	Transaction Account
RefCurrency	Ref Currency
ValueDate	Value Date
ReportCode	Report Code
RefAmount	Ref Amount
RateCode	Rate Code
Rate	Rate
TranIdentifier	Tran Identifier
PTranBusinessType	PTran Business Type
Particulars	Particulars
EventId	Event ID
EventType	Event Type
RateCodeForCollectCrncy	Rate Code for collect currency

RateForCollectCrncy	Rate for collect currency
ReqdCollectCrncyCode	Required Collect Currency Code
ChrgInpCrncy	Charge Input Currency
CompB2kId	CompB2kID
CompB2kIdType	CompB2kID Type
ChrgInpAmount	Charge Input Amount
PartyAccount	Party Account
ChrgAcctSol	Charge Account Sol ID
FetchModifiedCharges	Fetch Modified Charges
ValueDate	Value Date
IsCxlEntryReqd	Is CXL Entry Required
ModuleId	Module ID
ChrgType	Charge Type
ChrgEventType	Charge Event Type
ChrgEventId	Charge Event ID

Default Logic:

The script createAchorpTran.scr must exist in the \$TBA_SCRIPTS directory.

Typical Usage Scenario(s):

The script is available in the \$TBA_SCRIPTS directory. Please refer to createAchorpTran.scr present in scripts directory

©Copyright Infosys Ltd.

Consolidated Settlement Transaction Creation Script



The script **ACHConsolSettlementTran.scr** has the logic for creating consolidate settlement transaction. Used in HACHSP menu option .The above script is present in TBA_SCRIPTS.

Input:

The defined inputs are available in repository, MTT, class InputDetails and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

MTT.InputDetails. <Fieldname>

Field Name	Details
MTT.InputDetails.acctType	Type of Account: Settlement/Float/Excess/Short
MTT.InputDetails.tranAcct	Account for the transaction
MTT.InputDetails.processType	Debit/Credit
MTT.InputDetails.tranAmt	Amount for the transaction
MTT.InputDetails.tranCrncy	Currency for the transaction
MTT.InputDetails.rateCode	Rate Code for the transaction
MTT.InputDetails.paysysId	Paysys Id

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details

BANCS.OUTPUT. scriptError	Error message if any
BANCS.OUTPUT.successFailure	Success or Failure

Typical Usage Scenario(s):

This script is called from HACHSP for creating consolidated transaction.

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Consolidated Customer Transaction Creation Script



The script **ACHConsolCPCustTran.scr** has the logic for creating consolidate customer processing transaction. Used in HACHCP menu option

The above script is present in TBA_SCRIPTS.

Input:

The defined inputs are available in repository, MTT, class InputDetails and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

MTT.InputDetails. <Fieldname>

Field Name	Details
MTT.InputDetails.processType	Debit/Credit
MTT.InputDetails.todFlag	Y/N – This decides whether TOD to be granted or not
MTT.InputDetails.todIntFlag	Y/N – TOD Interest flag
MTT.InputDetails.exchRateCode	Exchange rate code
MTT.InputDetails.totalAmt	Total Amount of all AED records selected for this transaction
MTT.InputDetails.tranAmt	Tran Amount for this transaction
MTT.InputDetails.todAmt	TOD Amount for this transaction
MTT.InputDetails.recallAcct	Recall Account
MTT.InputDetails.tranAcct	Transaction Account
MTT.InputDetails.recallCustAcct	Recall Account
MTT.InputDetails.setType	Type of Set: OUTD/OUTC/INWC/INWD/ON1D/ON2D/ON1C/ON2C

MTT.InputDetails.acctType	Type of Account involved in transaction: Return/Recall/Customer/Suspend
MTT.InputDetails.floatAcct	Float Account
MTT.InputDetails.retAcct	Return Account
MTT.InputDetails.suspAcct	Suspense Account
MTT.InputDetails.tranCrncy	Transaction Currency
MTT.InputDetails.Consolid	FileName/BatchId/DateTime
MTT.InputDetails.todRemarks	TOD Remarks
MTT.InputDetails.PaysysId	Paysys Id

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. scriptError	Error message if any
BANCS.OUTPUT.successFailure	Success or Failure

Typical Usage Scenario(s):

This script is called from HACHCP for creating consolidated transaction. This gets called when consolidate transaction is to be created in Customer Processing

Default logic in case script is not present:

No default logic in the absence of the script.

MANTM Process for Non Fin Message



This new script hook will take AED entry serial number as Input and logic will be customized.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
ENTRYSRLNUM	Aed Entry Srl Num
PAYSYSID	PAYSYSID which is of NACHA type

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Script Input	Description
successOrFailure	Success Or Failure
error	Error

Typical Usage Scenario(s):

Do additional process for processing Refused ACK, ATX and COR SEC codes

Example:

```
<--start
sv_a= BANCS.INPUT.ENTRYSRNUM
sv_b=BANCS.INPUT.PAYSYSID
# Execution logic
BANCS.OUTPUT.successOrFailure = "S"
#BANCS.OUTPUT.error = "ACH NON FIN MSG PROCESSING
FAILED"
end-->
```

Default logic in case script is not present:

By default product will update the necessary tables. If any additional logic or updates are required, same can be done through this script.

©Copyright Infosys Ltd.

Asset Classification Events



The different Asset Classifications events are:

[Calculating the DPD counter for a Given Asset](#)

[Classify an Asset](#)

[Provision for an Asset](#)

©Copyright Infosys Ltd.

ATM and Anywhere Events



The available ATM and Anywhere events are:

■ [ATM Structure Formatting Hook](#)

■ [Transaction Authorization Hook](#)

■ [Transaction Particulars Hook](#)

©Copyright Infosys Ltd.

Batch Job Related Events



The different Batch Job Related events are:

[Allocating Machine ID for a Job](#)

[Ignore BJMS Framework for Routing Jobs](#)

[Job Collector Details](#)

©Copyright Infosys Ltd.

Calculations



The different Calculations related events are:

[Calculation of Withholding Tax](#)

[Calculate Rectified Amount of HHDDIC](#)

[Calculate EGCG Premium Amount](#)

[Provide Customization Place](#)

[Amount Calculation Script](#)

©Copyright Infosys Ltd.

Card Management System



The different events related to Card Management System are:

[Customized Card Details Uploads](#)

[Card Account Linkage Script](#)

©Copyright Infosys Ltd.

Card Uploads, Downloads and Reports

Infosys®



The different events related to Card Uploads, Downloads and Reports are:

[Custom Card Details Upload](#)

[Custom Card Account Linkage](#)

©Copyright Infosys Ltd.

Centralized Events



The different Centralized events are:

- [Verify Accounts Opened from Another SOL](#)
- [Verify Branch EOD and BOD Process Completion](#)
- [Verify Account Modification from Another SOL](#)
- [Verify Target SOL ID and Database Status Code](#)

©Copyright Infosys Ltd.

Channel Information Events



The different events related to Channel Information are:

[Channel Discount Charge Setup](#)

[Reversal of Charges](#)

[Overriding Channel Information Fields](#)

[Script to Decide Whether Treasury Liability to be Set or Not](#)

©Copyright Infosys Ltd.

Charge Related Events

The different Charge Related events are:

- [Calculation of Account Closure Charges](#)
- [Assess Commitment Fee](#)
- [Calculation of Bank Guarantee Charges](#)
- [Calculation of No Bill Utilization of DC Charges](#)
- [Calculation of Charges for Demand Drafts](#)
- [MTT Script for DD Charge Calculation from CDCI](#)
- [Calculation of Issue Advise of DC Charges](#)
- [Calculation of Amendment of DC Charges](#)
- [Calculation of Issue of DC Charges](#)
- [Calculation of Closure of DC Charges](#)
- [Calculation of Reinstatement of DC Charges](#)
- [Calculation of Transfer of DC Charges](#)
- [Check for HHCLCM Discount](#)
- [Calculation of General Charges](#)
- [Get Part Transaction Business Type List](#)
- [Calculation of HO Charges](#)

- [MCS Script for Intra Limit Regularization Event](#)
- [Calculation of Inward Clearing Charges](#)
- [Calculate Plan Change Fee](#)
- [Calculation of Outward Clearing Charges](#)
- [Calculation of Outward Clearing Rejection Charges](#)
- [MCS Script for Pass Book Issue Event](#)
- [Pass Book Issue Charge Event](#)
- [MCS Script for Pass Book Printing Event](#)
- [Pass Book Printing Charge](#)
- [Define DC or BG Charge Collection Transaction](#)
- [Calculation of Stop Payment Charges](#)
- [External Charge Calculation Script](#)
- [Customize CXL Transaction Remarks](#)
- [Calculate Package Maintenance Charges](#)
- [LMS Fee Maintenance Charges](#)
- [OD Protection Fee Calculation](#)
- [Charges in Syndication Loan](#)
- [DSACOMM – Validate event types for discounting](#)
- [OD Protection Charge Collection Script](#)

● [Excess Management Waive Charges](#)

● [Charge Entry Insertion in CXL Table](#)

● [Drawer – Drawee Charges](#)

● [Script to get Base Date for Charge Prenotification](#)

● [Script to check Pre-notification Advice](#)

● [Script to Calculate Notice Penalty For Loss Of Interest](#)

©Copyright Infosys Ltd.

OD Protection Charge Collection Script



Replace the existing content with the following.

For OD Protection charge collection batch, charge event id can be script based. For this script based charges CCOF batch program will dump required fields facilitating calculation of charge amount. The batch program dumps inputs related to CO type of single Tran limit and Running limit relevant to revolving type.

Inputs Available in the Scripts

The Inputs that are dumped into the script will be available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring to the fields in the following manner.

BANCS.INPUT.<Fieldname>

Script Input	Description
noOfRCTODUsed	No of Total Running Clean type TOD utilization
totRCTODAmt	Total Running Clean TOD amount utilized
totRCTODAmtAgainstInt	Total Running Clean TOD amount used against Interest
totRCTODAmtAgainstFee	Total Running Clean TOD amount used against Fee
totNonODProtTODAmtGrant	Total Non-CO type TOD amount granted
noOfNonODProtTODGrant	No of Total Non-CO type TOD granted
totIntTODAmtGrant	Total Interest TOD (IN) amount granted
totAutoBatchTODAmtGrant	Total Auto Batch TOD (BH) amount granted

Output Expected

The output will be available in the output repository as required by charge calculation process. The defined outputs will be available in

repository BANCS, class OUTPUT and with the field

names. One can access the outputs by referring to the fields in the following manner.

BANCS.OUTPUT. <Fieldname>

Default logic in case script is not present

Not Applicable

Typical usage scenario(s)

It can be used for script-based charge collection when CCOF batch is run.

Sample Script

No Sample script is present in the Sample scripts (\$TBA_SAMPLE/samscripts) directory.

©Copyright Infosys Ltd.

Excess Management Waive Charges



Script Name:

The script EMWaiveChrgs.scr is given for customisation at bank level and must be placed in TBA_SCRIPTS directory. This script is to decide on the value for waive charges in Excess Management. If this value is YES, then charges for EM decision will not be collected.

Input:

The defined inputs are available in repository EXCESS, class GENERAL and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

EXCESS.GENERAL.<Field Name>_0

Field Name	Details
EXCESS_ACCT_ID	Customer account which has been taken for Excess Management decisioning.
ENTITY_TYPE	Indicates the Payment mode or CLEARING for the transaction which is under EM.
ENTITY_ID	The AED or ICI key separated by ~Q or ~R.
EM_DECISION	Indicates the current decision taken on the Excess item. Valid Values: P-Pay, N-No Pay, D-Defer.
CONFIRM_FLG	Indicates whether the current decision taken on the Excess item is confirmed. Valid Values: Y-YES or N-NO.
TRAN_ID	Stores the transaction id for the current transaction.
PREV_DECISION	Indicates the previously confirmed decision taken on the excess item. Valid Values: NULL, P-Pay, N-No Pay.
PREV_TRAN_ID	Stores the Transaction Id of the last transaction for the excess item.

PREV_PART_TRAN_ID	Stores the part transaction Id corresponding to the clearing instrument which has been taken into Excess Management.
DECISION_MODE	Indicates the mode of the last decision made on the excess item. Valid Values: M-Manual, A-Automatic.
EXCESS_DATE	Date on which the item entered excess queue.
TRAN_AMT	Transaction Amount of the item under excess decisioning.
TRAN_CRNCY	Currency of the transaction Amount of the item under excess decisioning.
WAIVE_CHARGES	Flag to indicate waiver of charges, if set to Y no charges will levied, else charges will be calculated as per the setup. Valid Values: Y or N.
RETURN_REASON_CODE	Stores the reason code entered by the user, when a No Pay decision is taken on the excess item.
ITEM_STATUS	Open or Closed ~V Denotes whether this item is currently active or closed after closure batch. Valid Values: O-Open or C-Closed.
LAST_DECISION_EFF_AVL_BALANCE	Effective available balance when the last decision was taken.
LAST_DECISION_ANTICP_CR	Anticipated Credit when the last decision was taken.
LAST_DECISION_ANTICP_DR	Anticipated Debit when the last decision was taken.
ACCT_CRNCY_CODE	Currency associated with the anticipated credit or debit amount and the effective available balance.
FREE_CODE	Free Code for Excess management Record.
SORT_CODE	Sort Code for Excess management Record.
ORIG_TXN_CONSOLIDATED_FLG	Flag which denotes whether the transaction which is created in AED or ICI is consolidated or not.

Output:

The output of the script will be available in the specified repository

fields:

EXCESS.GENERAL.<Fieldname>_0

Field Name	Details
WAIVE_CHARGES	Flag to indicate waiver of charges, if set to Y no charges will be levied, else charges will be calculated as per the setup. Valid Values: Y or N

Default Logic:

In case script is not present, then the value of waive_charges field from the table EMDT is assigned and based on this charges will be collected.

Typical Usage Scenario:

Script Hook is provided for overwriting the waive_charges flag value which is coming from the table at bank level.

Example:

NA

©Copyright Infosys Ltd.

Charge Entry Insertion in CXL Table



Script Name:

Charge Routine has a script `prepareCxlGLSegmentString.scr` which must be placed in `TBA_SCRIPTS` directory. CXL script hook is called before inserting any charge entry in CXL table.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Description
<code>BANCS.INPUT.action</code>	This can be INSERT or UPDATE.
<code>BANCS.INPUT.cxlSrNum</code>	Charge serial number.
<code>BANCS.INPUT.compB2kld</code>	This is acid on which charges are implemented.
<code>BANCS.INPUT.compB2kidType</code>	This field will specify the entity type like ACCNT for accounts, FXBILL for bills, IWREJ for inward reject charges, OWREJ for outward reject charges, ECS for ECS charges, DDCHG for DD charges, CACC/CLS/Y for account closure etc.
<code>BANCS.INPUT.srNum</code>	Charge part transaction serial number.
<code>BANCS.INPUT.chrgTranId</code>	Transaction Id of the charge collection. This field is the link between DTD and CXL tables and specifies the charge transaction id.
<code>BANCS.INPUT.chrgPartTranSrNum</code>	Part transaction serial number of the charge part transaction.
<code>BANCS.INPUT.chrgTranDate</code>	Transaction date of the charge part transaction.

BANCS.INPUT.parentTranId	Parent Transaction Id for which the reversal has happened. This is used in case of reversal transactions only.
BANCS.INPUT.parentTranSrInum	Parent Transaction serial number for which the reversal has happened. This is used in case of reversal transactions only.
BANCS.INPUT.parentTranDate	Parent Transaction date for which the reversal has happened. This is used in case of reversal transactions only.
BANCS.INPUT.eventType	Event Type of Charge Collection.
BANCS.INPUT.eventId	Event Id of Charge Collection.
BANCS.INPUT.serviceSolId	Service Branch Sol Id.
BANCS.INPUT.systemCalcAmt	System calculated charge amount.
BANCS.INPUT.actualAmtColl	This field will specify the actual charge collected amount. This field can be different from the system calculated amount.
BANCS.INPUT.collCrncyCode	Collection Currency Code.
BANCS.INPUT.tranParticular	Field provided for entering particulars of transaction.
BANCS.INPUT.tranRmks	Field for entering any remarks that the user wants to put.
BANCS.INPUT.reversalFlg	This determines a reversal transaction.
BANCS.INPUT.startDate	Start date of calculation.
BANCS.INPUT.endDate	End Date of calculation.
BANCS.INPUT.targetAcid	This stores the acid for which the collection has happened.
BANCS.INPUT.custId	Customer Id who is giving the charge.
BANCS.INPUT.chrgBorneByInd	This indicates who is bourns the charge.
BANCS.INPUT.partTranType	Part transaction type. Credit or Debit. Valid values are C and D.
BANCS.INPUT.ptranBusType	ptranBusType.
BANCS.INPUT.chrgAcid	This is the charge account.

BANCS.INPUT.rateCode1	Rate code used for Normal MC scenario.
BANCS.INPUT.rateCode2	Rate code used for MC Scenario 4 where all transactions are converted to Home Crncy.
BANCS.INPUT.rate1	Rate used for conversion between currencies using rate 1.
BANCS.INPUT.consolDebitPtranFlg	Indicates to merge customer part transaction debit or not. This field will specify whether all charges are grouped together and then only one debit happens with the whole amount.
BANCS.INPUT.chrgRptCode	Transaction Report Code.
BANCS.INPUT.amtWithoutDiscount	The output amount with no CLC (customer level discount) or CTG (channel level discount) effect.
BANCS.INPUT.recNotEffective	Indicates if the record is effective or not.
BANCS.INPUT.channelId	Channel Id from where the transaction has happened. This is the HRRCDM code.
BANCS.INPUT.amtAfterFirstLvIDisc	The output amount after CLC or CTG effect based on GCT field channel_pref_bef_cust_pref.
BANCS.INPUT.recordType	Type of Charge or Rebate transaction Record. Valid value : R- Rebate Record , NULL - Charge Record
BANCS.INPUT consolidateTranSrlNum	Serial number of entries in CXL made under a single charge transaction id.
BANCS.INPUT.chrgGIDate	GI date of the charge part transaction.
BANCS.INPUT.parentGIDate	Parent GI date for which the reversal has happened.
BANCS.INPUT.amtBeforeAddtnIDisc	This is the amount left after Channel Level and Customer Level Discounts are applied to the actual Charge-Amount before considering additional discount.
BANCS.INPUT.chrgDebitPartTranSrlNum	This field will store the part Transaction serial number of the charge debit part Transaction.
BANCS.INPUT.defaultChrgCalcFlg	Default charge calculated flag.The valid values are Y or N/A or NULL .
BANCS.INPUT.relPricingRefNum	Relationship pricing reference number.

BANCS.INPUT.chrgReversalReasonCode	Charge Reversal Code.
BANCS.INPUT.rate2	Rate used for conversion between currencies using rate 2.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
GLSegmentSring	The script hook will populate this string.

Default Logic:

If script does not exist normal c functions will be called for calculation.

Typical Usage Scenario:

Script Hook is called before inserting any charge entry in CXL table.

Example:

NA

Drawer – Drawee Charges

Script Name:

The script fxDrDweeCharges.sscr is used for setting up of drawer-drawee charges for script based pttm charges. The script must be present in TBA_SCRIPTS directory as fxDrDweeCharges.scr.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.InwardOrOutward	This field specifies whether the bills is of inward or outward type.
BANCS.INPUT.DrwrDwee	This field specifies whether the party is a drawer or a drawee.
BANCS.INPUT.BillCurrency	This field mentions the currency in which the bill is present.
BANCS.INPUT.businessType	This field contains the reference code of the type 'Part Tran Business Type' which contains the discount details.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.collCrncy	This field contains the currency in which the

	charge is collected.
BANCS.OUTPUT.collAmount	This field contains the charge amount with discount.
BANCS.OUTPUT.AmountWithNoDiscount	This field contains the charge amount without discount.

Default logic:

NA

Typical usage scenario(s) :

NA

Example:

NA

©Copyright Infosys Ltd.

Script to get Base Date for Charge Prenotification



The sample script **getBaseDateForChrgPrenotification.sscr** is used to derive at the base date for charge prenotification. Default logic to derive the base date is based on account opening date. This script is used to derive at the base date using any other logic like logic of fixed quarter.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
baseDate	The base date
Foracid	The account id
Chrg_freq_type	The charge frequency type
Chrg_freq_dd	Charge Frequency Start Date
Cap_freq_type	The cap frequency type
Cap_freq_dd	Cap Frequency Start date
preNotificationFlg	Prenotification flag
capEnableFlag	Cap Enable Flag

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Valid Values are "S" or "F" If script is executed successfully then "S" will be returned else "F" will be returned
baseDate	The base date

Note:

If output base date is null, then input base date will be used.

©Copyright Infosys Ltd.

Clearing Events



Clearing is one of the activities a Bank undertakes as a part of its business. Finacle™ system provides facility for handling clearing activities of a bank. Clearing activities can be divided into inward and outward clearing.

Inward clearing is a process wherein the bank receives various types of negotiable instruments that are drawn on it by its customers and parts the resultant proceeds to the presenter of the instruments.

In case of Outward clearing, the bank gets the proceeds since it acts as a collecting agent on behalf of its customers who have tendered the instruments for credit of their accounts.

There are scripting events available which help us in performing various actions related to clearing from the database.

The different Clearing events are:

- [Check Release to Shadow Balance in Outward Clearing](#)
- [Check for HOCl Fields Mandatory](#)
- [Define Outward Clearing Instrument Credit Value Date](#)
- [Upload and Verify Outward Clearing Transaction](#)
- [Check OCP Fields Mandatory](#)
- [Parse the Record from outward Return Processing](#)
- [Massage Inward Clearing Media Record](#)
- [Scheme Types to Find Accounts to which Instrument Belongs](#)
- [The Original Outward Instrument Details for the Unpaid Claim](#)

Request Received

- [Script to get Inward Reject Reason Code](#)
- [Script to Set an Instrument to Force Suspense](#)

©Copyright Infosys Ltd.

ECS Events

The different ECS related events are:

- [Get ECS Mandate Serial Number](#)
- [Define Bulk Transaction in ECS](#)
- [Upload ECS Bulk](#)
- [Populate ECS Error COde and Error Message](#)
- [Define ECS Inward Bulk Transaction](#)
- [Read Upload File of ECS Inward Bulk](#)
- [Read the Upload File by Position](#)
- [Define Inward Bulk Transaction](#)

©Copyright Infosys Ltd.

The Original Outward Instrument Details for the Unpaid Claim Request Received



Script Name:

The script `BACS_getOriginalInstrumentDtls.sscr` is a sample script provided for BACS customization and should be present in `samscripts` directory. This script will be moved to `$TBA_SCRIPTS` folder as `BACS_getOriginalInstrumentDtls.scr`

This script will be used to identify the original outward instrument details for the unpaid claim request received.

Input:

The defined inputs are available in repository `BANCS`, class `INPUT` and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

`BANCS.INPUT.<Fieldname>`

Field Name	Details
InstrmntNum	Instrument number.
TranAmt	Transaction amount.
BankCode	Bank Code.
BranchCode	Branch Code.
SenderBic	Sender Bank Identifier.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
successOrFailure	This variable will contain whether the script is success or failure.
SolId	SOL_ID of the original outward instrument.
ZoneCode	Zone_code of the original outward instrument.
ZoneDate	Zone_date of the original outward instrument.
SetNum	Setnum of the original outward instrument.
InstSrINum	Instrument serial number of original outward instrument.
errormesg	In case of failure appropriate error message will be returned.

Default Logic:

If the script BACS_getOriginalInstrumentDtls.scr is not present, then the error “Script for getting original instrument details [BACS_getOriginalInstrumentDtls.scr] not available. Instrument Updation Failed” is displayed to the front-end.

Typical Usage Scenario:

This script will be called from CXX sources.

Example:

NA

©Copyright Infosys Ltd.

Connect24 Events



Connect24 is an intermediate component which connects Finacle Core and the Delivery Channels like ATM. Finacle provides events which relate to different functions in Connect24.

The different Connect 24 events are:

[Connect24 Post-processing Script](#)

[Connect24 Pre-processing Script](#)

[Uniserver Fee Information Script Event](#)

[Script to Create Transactions for CDCI Transaction](#)

[Post-processing Script for Stand-in Server Request](#)

[Pre-processing Script for Stand-in Server Request](#)

©Copyright Infosys Ltd.

CIF Related Events



The CIF Related Events are:

[Find Customer Category](#)

[Display High Value Transactions and Account Type](#)

©Copyright Infosys Ltd.

Date and Calendar Related Events



The different Date and Calendar related events are:

[Check ECP for Future Mapping](#)

[Custom Pre or Post Calendar Changes Operations](#)

[Get Next Working Date With Holiday Check](#)

[Check if the Date Passed is Falling on a Currency Holiday](#)

[Currency Next Calendar Validations for Commercial Loans Module](#)

[Currency Previous Calendar Validations for Commercial Loans Module](#)

[Get Next Business Working Date](#)

[Check for Holiday on the Renewal Date](#)

[Get Next Working Date With Holiday Check](#)

[Get Number of Days in a Year](#)

©Copyright Infosys Ltd.

Finacle Copyright

Script to Modify the Interest Part Transaction Value Date

Script Name:

getValueDateForIntCalTran.sscr

Description:

This script is used to do modify the interest part transaction value date based upon custom logic. This script hook is called during interest amount computation and value date of the interest credit or debit can be changed.

Inputs:

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS.INPUT.<Fieldname>

Script Input	Description
acctId	Reference Account number (Account no. of the account for which interest is being run)
partTranType	Part tran type (debit / credit)
intAcctNum	Interest Account Number (Account no. in which interest is getting credited.)
tranAmt	Transaction Amount
refAmt	Reference Type
tranDate	Transaction Date
bodDate	BOD Date
acctSolId	Sol ID Of Account
valueDate	Value Date of part tran.
initSolId	Init Sol Id

Output:

The output of the script is available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Script Output	Description
valueDate	Value Date of the Part tran.

Default Logic:

NA

System will continue with the original value date.

Typical Usage Scenario:

This script can be used to change the value date of a part transaction.

Sample Script:

Sample script `getValueDateForIntCalTran.sscr` is present in the sample scripts (samscripts) directory.

©Copyright Infosys Ltd.

Finacle Copyright

Modify SI Part Transaction Value Date

Script Name:

getPTranValueDateForSI.sscr

Description:

This script is used to do modify the SI part transaction value date based upon custom logic.

Inputs:

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS.INPUT. <Fieldname>

Script Input	Description
acid	Account Id
partTranType	SI part transaction
tranAmt	Transaction Amount
refNum	Reference amount
tranDate	Transaction Date
SIValueDateForPTran	SI part tran value date
tranParticular	Transaction particulars
tranRmks	Transaction remarks
rptCode	Report code
bodDate	BOD Date
initSolId	Init Sol ID
acctSolId	Account Sol ID
calledFor	This script is getting called from 2 places. To differentiate it, Introduced this flag whose Valid

Values are H-(When called for Header record) and D – (When called for Detail Record).

Output:

System dumps the entity along with this message in report for user reference in case entity escheatment fails due to custom logic.

Script Output	Description
SIValueDateForPTran	SI part tran value date
tranParticular	Transaction particulars
tranRmks	Transaction remarks
rptCode	Report code
refNum	Reference number

Default Logic:

NA

System will continue with the original value date.

Typical Usage Scenario:

This script can be used to change the value date of a part transaction.

Sample Script:

Sample script getPTranValueDateForSI.sscr is present in the sample scripts (samscripts) directory.

©Copyright Infosys Ltd.

Finacle Copyright

Modify Renewal Part Transaction Value Date

Script Name:

getValueDateForTDRenewal.sscr

Description:

This script is used to do modify the renewal part transaction value date based upon custom logic.

Inputs:

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS.INPUT. <Fieldname>

Script Input	Description
renAcid	Account Id which is getting renewed
partTranType	SI part transaction
tranAcid	Account on which part tran is created
tranAmt	Transaction Amount
refAmt	Reference amount
tranDate	Transaction Date
bodDate	BOD Date
valueDate	Value date of transaction
initSolId	Init Sol ID
acctSolId	Account Sol ID
tranParticular	Transaction particulars
tranRmks	Transaction remarks
rptCode	Report Code Of transaction
flowCode	Flow code of the transaction.

Output:

System dumps the entity along with this message in report for user reference in case entity escheatment fails due to custom logic.

Script Output	Description
valueDate	Value date of part tran
tranParticular	Transaction particulars
tranRmks	Transaction remarks
rptCode	Report code

Default Logic:

NA

System will continue with the original value date.

Typical Usage Scenario:

This script can be used to change the value date of a part transaction.

Sample Script:

Sample script `getValueDateForTDRenewal.sscr` is present in the sample scripts (samscripts) directory.

©Copyright Infosys Ltd.

Finacle Copyright

Modify Closure Part Transaction Value Date

Script Name:

getValueDateForTDClosure.sscr

Description:

This script is used to do modify the closure part transaction value date based upon custom logic.

Inputs:

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS.INPUT. <Fieldname>

Script Input	Description
clsrAcid	Account Id which is getting closed
partTranType	SI part transaction
tranAcid	Account on which transaction is created
tranAmt	Transaction Amount
refAmt	Reference amount
tranDate	Transaction Date
bodDate	BOD Date
valueDate	Value date
initSolId	Init Sol ID
acctSolId	Account Sol ID
tranParticular	Transaction particulars
tranRmks	Transaction remarks
rptCode	Tran report code
flowCode	Flow code of the transaction.

Output:

System dumps the entity along with this message in report for user reference in case entity escheatment fails due to custom logic.

Script Output	Description
valueDate	Value date of part tran
tranParticular	Transaction particulars
tranRmks	Transaction remarks
rptCode	Report code

Default Logic:

NA

System will continue with the original value date.

Typical Usage Scenario:

This script can be used to change the value date of a part transaction.

Sample Script:

Sample script `getValueDateForTDClosure.sscr` is present in the sample scripts (samscripts) directory.

©Copyright Infosys Ltd.

Demand Draft Events



Remittance of funds is one of the services offered by banks. Remittances are effected by banks using the Demand Drafts (For remittances across cities). As the issue (credit) and payment (debit) of Demand Drafts happen at different branches, reconciliation of these debit and credit credit entries is essential. Apart from issuing and paying the drafts, banks are also required to modify,rectify, reverse, revalidate, cancel the drafts. They may also have to issue duplicate drafts if the original is lost.

Finacle provides events to populate default values for a DD Transaction, upload DD status and charge calculation.

The different Demand Draft events are:

[Populate Issue Bank or Branch in HICTM Menu Option](#)

[Populate Payee Name in Additional Details Screen](#)

[Populate Issue Bank or Branch while Paying a Bankers Cheque](#)

[Populate Issue Bank or Branch in HDDMP Menu Option](#)

[DD Status Upload](#)

[Calculate Charges for DD Transactions](#)

[Memo Pad Upload](#)

[Stop Payment Upload](#)

[TDS Upload](#)

[Transfer Transaction Upload](#)

[ICV, IVS and TVS Upload](#)

DD Payment Upload



The DD Payment Uploads are:

[■ Calculate Charges for DD Transactions](#)

[■ Validate DD Record to be Uploaded](#)

©Copyright Infosys Ltd.

DSA Related Events



The different DSA related events are:

[Populate DSAM Upload Fields](#)

[Get the Data for DSA to Upload](#)

©Copyright Infosys Ltd.

EOT Events



EOT (End of Transaction) method is a distinct method of interest computation used by certain banks. Under this method the bank will charge interest from the customer if their account goes to debit balance during the day even if the intraday debit balance is squared off by the end of day through a credit transaction.

Three scripts are available to cater the bank's requirement.

- [Get Holiday Status for EOT Event](#)
- [To populate Transaction Codes for EOT Event](#)
- [Validation to Exempt Transaction for EOT Event](#)

©Copyright Infosys Ltd.

Get Holiday Status for EOT Event



Script Name:

getHolidayStatusForEOT.scr

Description:

This script is used to get the holiday string for all months between given start date and date.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the following manner:

BANCS.INPUT.<fieldName>

Script Input	Description
BANCS.INPUT.fromDate	Start Date of date range for which holiday data needs to fetched
BANCS.INPUT.toDate	End Date of date range for which holiday data needs to fetched

Output:

The Output of the script will be available in following repository fields:

BANCS.OUTPUT.<fieldName>

Script Output	Description
BANCS.OUTPUT.HLDYSTR_d	Holiday string for each of the months between from date and to date including that of from date and to date months. %d here is a count of months which should be incremented for each month.
	Month for which holiday script is fetched. %d here is a

BANCS.OUPUT.MONTH_d	count of months which should be incremented for each month
BANCS.OUPUT.YEAR_d	Year for which holiday script is fetched. %d here is a count of months which should be incremented for each month
BANCS.OUPUT.count	This is the count of number of months for which holiday string is being set in output
BANCS.OUPUT.errorMsg	Error message to be set in case of failure
BANCS.OUPUT.SuccessOrFailure	Flag to be set to S or F in case of Success Or Failure resp.

Default logic in case script is not present:

This script should be available to arrive at holiday status during interest calculation using EOT method.

Typical Usage Scenario:

This script is customized to determine holiday status for a given date range. Typically it would be used when holiday status is to be determined from custom table or reference SOL.

©Copyright Infosys Ltd.

To Populate Transaction Codes for EOT Event



Script Name:

populateTranCodesForEOT.scr

Description:

This script is used to populate transaction codes which is used for identifying clearing transaction and special transaction to exempt from End of Transaction interest.

Input:

Input not present

Output:

The Output of the script will be available in following repository fields:

BANCS.OUTPUT.<fieldName>

Script Output	Description
BANCS.OUTPUT.clgTranCode	Clearing Transaction code
BANCS.OUTPUT.sp1TranCode	Transaction code for special transactions to be exempted from interest

Default logic in case script is not present:

If script is not present, none of the transactions will be exempted from interest calculation using EOT method.

Validation to Exempt Transaction for EOT

Script Name:

valToExemptTranForEOT.scr

Description:

This script is used to check if transaction identified as special transaction has to be exempted from interest calculation by EOT method.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the following manner:

BANCS.INPUT.<fieldName>

Script Input	Description
BANCS.INPUT.AcctNum	Account Number
BANCS.INPUT.exemptTranFlg	Whether transaction is to be exempted as per system's default logic
BANCS.INPUT.amount	Transaction Amount
BANCS.INPUT.tranCode	Transaction code
BANCS.INPUT.openClrBal	Begin of day clear balance amount
BANCS.INPUT.openBookBal	Begin of day book balance amount

Output:

The Output of the script will be available in following repository fields:

BANCS.OUTPUT.<fieldName>

Script Output	Description
BANCS.OUTPUT.exemptTran	Whether to exclude this tran from interest calculation or not.

Default logic in case script is not present:

If script is not present, system will exempt the transactions identified as special transaction from interest calculation if EOD book balance is greater than zero.

©Copyright Infosys Ltd.

FAB Events



The FAB related events are:

[Customize Selection of Print Voucher Template](#)

[Get TC, Currency Sale and Purchase Charge Details in FAB](#)

©Copyright Infosys Ltd.

Facilitating Automated Tasks



The different events to facilitate Automated Tasks are:

[Automatic Verification of HACM Menu Option](#)

©Copyright Infosys Ltd.

Finacle Treasury Events



The different events of Finacle Treasury are:

[Finacle Treasury Cash Flows](#)

[Upload Finacle Treasury Transactions](#)

[Create Finacle Treasury](#)

©Copyright Infosys Ltd.

IBR Events

The different IBR events are:

[Customize Names of IBR files](#)

[Populate Default Values in HCFLSIBR Menu Option](#)

©Copyright Infosys Ltd.

Interest Related Events



The different Interest Related events are:

[Interpolation Script – Script for Arriving Rate of Interest Application](#)

[Commission Charge Back Process](#)

[Commission Booking Process](#)

[Commission Reconciliation Process](#)

[Script for RSI Recognize Suspended Interest Menu Option](#)

[Interest Calculation](#)

©Copyright Infosys Ltd.

Interest Calculation

The system must be able to manage and report the back-up withholding tax reported year to-date for a non-resident alien that changes their status from W9 to W8 prior to year end. A customer may change from W9 to W8 status at any time during the year. The system must be able to generate a 1099 tax withholding statement for the period during which the customer was W9 status. The system must not report a 1099 statement for the period when the customer is W8 status. A 1099 statement would be created for each customer account.

Hence the requirement is to identify an interest as W-8 interest or W-9 interest before update of INT_ADM table.

This can be achieved by providing a script hook can be called before INT_ADM insert, which will have all the tax details dumped into it, so that customization can maintain the INT_ADM data and put it in custom table to maintain traceability between tax certificate (W8 or W9) and tax entry.

Inputs Available in the Scripts

The Tax details that are dumped into the script will be available in repository BANCS, class INPARAM and with the field names mentioned below. One can access the inputs by referring to the fields in the following manner.

BANCS.INPARAM. <Fieldname>

Script Input	Description
A/c Id	The GAM foracid
Start date	Used to calculate the time period between Interest start date & end date
End date	Used to calculate the time period between Interest start date & end date

Withholding tax percentage	Withholding tax percent
Withholding Tax Floor limit	Floor limit for withholding tax
Withholding Tax Notice Received date	The Date on which the Notice for withholding tax is received
Withholding Tax Notice Period(Months)	This stores the Notice Period(Months) for Withholding Tax
Withholding Tax Notice Period(Days)	This field stores the Notice Period(Days) for Withholding Tax
Withholding Tax applicability	Withholding Tax applicable level for the account
Tax waiver Start date	The start date from which the withholding tax is waived
Tax waiver End date	The End date from which the withholding tax is waived
Tax waiver certificate number	Stores the Tax Certification number
Tax Certificate Submission date	Date of tax certificate submission
Tax Form Particular	Free text for storing any other description of tax waiver
Withholding Tax Category	Withholding Tax flag for this account
Withholding Tax Level	Withholding Tax applicable level for this account
Withholding Tax Borne by	Withholding Tax will be borne by whom
Tax amount	Tax Amount in home currency
CIF ID	Cif Id of the Customer
Record Type: Interest or Tax	It defines whether the record in the table is for interest or tax
INT_ADM key	It is the combination of : Acid, record serial number & bank Id
Tran Date	This is the transaction date

Tran Id	This is the system generated Transaction ID
Part tran serial number	It is the part tran serial number corresponding to the transaction number
Tax amount in home currency	Tax amount equivalent in the home currency
Tax currency code	This is the currency code In which tax is calculated

Output Expected

None

Default logic in case script is not present

INT_ADM Updates happens normally without executing the script and any dumping / population of the above fields into / from script.

Typical usage scenario(s)

For identifying one of the interests as W-8 interest or W-9 interest and updating a custom table whether the interest & tax is W-8 / W-9 status.

Sample Script

Sample script dumpTaxDetails.sscr is present in the Sample scripts (\$TBA_SAMPLE/samscripts) directory.

©Copyright Infosys Ltd.

For OD Debit and Credit Interest



Script Name:

outBndCallPostODInt.scr

Description:

This script is used to make the outbound call for OD Interest Calculation. The script outBndCallPostODInt.scr is present in TBA_SCRIPTS directory.

Inputs:

The defined input is available in the MTT repository, in the InputDetails class with the field names mentioned. You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Description
BANCS.INPUT.scr_entity_id	Acid of the Account
BANCS.INPUT.scr_int_amt	Cr/Dr Interest amount on the OD account
BANCS.INPUT.scr_penal_amt	Cr/Dr Penal amount on the OD account
BANCS.INPUT.scr_int_rate	Interest Rate of the OD account
BANCS.INPUT.scr_clr_bal_amt	Cr/Dr Balance amount of the OD account
BANCS.INPUT.scr_tran_id	Tran ID of the transaction
BANCS.INPUT.scr_tax_amt	Cr/Dr Tax amount of the OD account
BANCS.INPUT.scr_part_tran_srl_num	Part Tran Srl Num of the transaction
BANCS.INPUT.scr_tran_type	Tran Type of the transaction. Possible Value :- C (Credit) or D (Debit)

Output:

The output of the script is available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Description
BANCS.OUTPARAM.errorMesg	Error Message
BANCS.OUTPUT.successOrFailure	Success Or Failure - Status

Default Logic:

NA

Typical Usage Scenario:

This script is called to make the outbound call after creating transactions for interest calculation for OD accounts.

Example:

NA

©Copyright Infosys Ltd.

Scripts to call External Systems to release or reverse Interest Calculation



Script Name:

preCommitAndRollbackForAcctInt.scr

postCommitAndRollbackForAcctInt.scr

Description:

The pre script preCommitAndRollbackForAcctInt.scr and post script postCommitAndRollbackForAcctInt.scr are used to do a call to external system.

Inputs:

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS.INPUT.<Fieldname>

Pre Script

Script Input	Description
foracid_recs_str	Foracid values processed for interest calculation. The values will be dumped in a string with pipe separated.
crDrFlg_rec_str	Denotes the transaction type whether its credit or debit interest calculation.
tranid_recs_str	Transaction Id values generated during interest transaction. The values will be dumped in a string with pipe separated. In case of any failures the tran ID is not created a message will be dumped saying "No transaction created"
succFailFlg_recs_str	Flag values denoting if the particular interest transaction is failed or succeeded, the values will be dumped in a string with pipe separated
db_action	Denotes if the action is commit or rollback.

Post Script

Script Input	Description
foracid_recs_str	Foracid values processed for interest calculation. The values will be dumped in a string with pipe separated.
crDrFlg_rec_str	Denotes the transaction type whether its credit or debit interest calculation.
tranid_recs_str	Transaction Id values generated during interest transaction. The values will be dumped in a string with pipe separated. In case of any failures the tran ID is not created a message will be dumped saying "No transaction created"
succFailFlg_recs_str	Flag values denoting if the particular interest transaction is failed or succeeded, the values will be dumped in a string with pipe separated
db_action	Denotes if the action is commit or rollback.

Output:

There is no return of failure or success from scripts.

Default Logic:

If the script is not present then commit or rollback should happen as expected.

Typical Usage Scenario:

After the end of interest transaction processing a final commit or rollback will be issued for the selected records. The pre and post script will be called at this position before and after the commit or rollback, the script user hook can be used to make a call to an external system to release/reverse any process or transaction.

Sample Script:

Sample scripts preCommitAndRollbackForAcctInt.sscr and post script postCommitAndRollbackForAcctInt.sscr are present in

sample scripts directory (samscripts) directory.

©Copyright Infosys Ltd.

Finacle Copyright

Liquidity Management Related Events



The different events related to Liquidity Management are:

[Get individual interest amount for all participating accounts \(Notional Pooling case only\)](#)

[Script Hook for Dumping Account, Data centre and Bank level information](#)

[Script Hook for Dumping Transaction Details](#)

©Copyright Infosys Ltd.

Illegal Character Check for Pin Code Field Entered



Script Name:

The script valPinCode.scr is used to check whether Pin Code field entered contains valid special characters. Based on the allowed characters in the field, proper error is displayed to the calling function.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
pinCode	The pin code field through which pin code is accessed in script.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Valid Values are "S" or "F". If pin code is valid, then "S" will be returned. If Pin Code is invalid, then "F" will be returned.
ErrorMessage	If pin code is invalid, then proper error Message will be returned to the calling function, else empty string will be returned.

Default Logic:

In case script is not present, only alphanumeric, space, hash(#) and Hyphen(-) characters are allowed for Postal Code Field.

Typical Usage Scenario:

Script Hook is provided to allow other special characters for Postal Code Field.

Example:

NA

©Copyright Infosys Ltd.

Multilingual Based Events



The different Multilingual Based events are:

[Multilingual Number to Words Conversion](#)

©Copyright Infosys Ltd.

Mutual Funds Events



The different events related to Mutual Funds are:

[Calculate Commission](#)

[Calculate Base Price Out](#)

[Calculate Commission Based on Transaction Type](#)

[Create Mutual Fund Settlement Transaction](#)

[Define Mutual Funds Financial Transaction](#)

©Copyright Infosys Ltd.

Other Events

The Other events are:

- [CIF Core Interface Update Scripts](#)
- [Get Descriptions for HCVD Codes](#)
- [Get Descriptions for HHCVD codes](#)
- [Post Query of HHTDCS](#)
- [ETD To HTD Error Failure Capture](#)
- [EXEMOP for 24x7 Menu Access](#)
- [Get Lien Requester Details](#)
- [Get Participant Distribution Amount](#)
- [Get Maximum Number of Lines Required in the Passbook](#)
- [Copy the Values from Master to Placement Level](#)
- [Control Access to Menu Options](#)
- [Move Record to AED History](#)
- [HMRDSP – Multirepay Demand Satisfaction Process](#)
- [Return PDC Zone](#)
- [Truncate RTL Table](#)
- [Revolving OD Bill Generation](#)

- [Script Hook for Batch Freezing of Account](#)
- [Amount Calculation Script](#)
- [Change Record Format](#)
- [Transaction Rate for Forward Contract Number and SOL ID](#)
- [Decrypt a File](#)
- [Direct Debit Mandate](#)
- [Encryption of File](#)
- [Raise Exception while Modifying Account / Limit Node Attached to Expired Insurance Security](#)
- [User Hook for Connect24 \(GetContraAccountBal\)](#)
- [Amount Used for Calculating the Fee Charges for Different Events](#)
- [Script Hook for Inactive Dormant Batch program](#)
- [Memo Pad Upload](#)
- [Parsing Logic Script](#)
- [Script for Finding Stronger or Weaker Currency](#)
- [UIC Prepayment Loan Transaction](#)
- [Calculate the account pref interest rate](#)
- [Fetch Amortizatio Amount](#)
- [XML Upload of AED](#)
- [Derivation of Details for POIE](#)

- [Derivation of Paysys ID for IE](#)
- [Derivation of Sol ID for IE](#)
- [Getting Charge Event Id for IE](#)
- [Inward Credits for Message for IE](#)
- [Message Rerouting Logic of PAYSYS for IE](#)
- [Rerouting of Payment for IE](#)
- [Criteria Checking for incoming messages to be STP](#)
- [Validate the Extra Inter Entity](#)
- [Validations related to STP \(State through Processing\)](#)
- [Fetching the Value of Amount Field](#)
- [Populating 'Replacing String', From position' and 'To position](#)
- [Dumping the Login SOL and Entity \(bill\) SOL](#)
- [Script to Calculate Bucket Based on Rule Action](#)
- [Script to Calculate Schedule Based on Rule Action System](#)
- [Script to Calculate Schedule Based on Rule Action External](#)
- [Script to Change Status of Individual Saving Accounts to Skip Freeze](#)
- [Script to Raise Custom Exception for Total Contribution Cap Exceeded](#)
- [Script to Raise Custom Exception for Contribution Cap Exceeded](#)

[●Script to Raise Custom Exception for Current Year Contribution Restriction](#)

[●Script to Get Value of Reasonable Excuse Marker and Free Text Field](#)

[●Script for Offshore Hierarchy Logic](#)

[●Script for Onshore Hierarchy Logic](#)

[●Script to Open Zone for Autorepresentation](#)

[●Script to lodge Instrument](#)

[●Script to Find the type of External System](#)

[●Script to Identify UK & NON UK Country Codes](#)

[●Script to Segregate Header Details](#)

[●Script to Create FPID for FPS](#)

[●Script to Fetch Original PO for Recovery](#)

[●Script for Outward Transaction Recovery](#)

[●Script for Transaction Creation](#)

[●Script for Matching PO for Recovery Response](#)

[●Script for Creating FEE Transactions](#)

[●Script for Creating Remittance Transaction](#)

[●Script for EM Queue Transfer](#)

[●Script to Validate SFMS Message](#)

- [Script for Event Mapping for SFMS Message](#)
- [Script for Creating Customer Processing Transaction](#)
- [Script to Decide Charge Collection Requirement for Inward Auto Returns](#)
- [Script for Freezing ISA Accounts for Address Change](#)
- [Script for Validating PO CutOff Time.](#)
- [Script for Validating PO CutOff Time.](#)
- [Script for Bank Validation and Decision](#)
- [Script for Access Check Validation](#)
- [Script to Send Notification](#)
- [Script to Insert Notification Details](#)
- [Script to Check Additional Criterion for Pool Selection](#)
- [Script for Handling Other Account Level Tolerances During Pool Reassessment](#)
- [Script to Insert Notification Details](#)
- [Script to Insert Notification Details](#)
- [Script to Fetch PO of Original Message](#)
- [PO Black List Scan Script](#)
- [Script to Handle all the ISCD Validations](#)
- [Script to Map Input Mandate Fields to Advice Message](#)

- [Script to Transfer Details in Queue](#)
- [Script for Discretionary Limit Check](#)
- [RULE_CustomAllocRules Script](#)
- [RULE_CustomDecisionRules Script](#)
- [RE_ExeAddnlExtraCnd Script](#)
- [Script to Modify COTODParameters](#)
- [notifyCustomerForBCEM.sscr](#)
- [Script to Calculate APY](#)
- [Script for Issue Paying in Book](#)
- [Script to Build Code for Marking Instruments as Forced Suspence](#)
- [Script to Build Custom Logic](#)
- [Scripts for MBCD](#)
- [Scripts for MCTRD](#)
- [Scripts for GRCE](#)

To Override/Consider Exceptions During Transaction Processing



Script to override/consider exceptions during transaction processing:

The script paymentSample.scr must be present in TBA_SCRIPTS directory.

This scripthook is called for all the batch jobs (BJS framework) to override/consider the exceptions during transaction processing. This scripthook will override/consider exceptions based on the output of the scripthook, only when HEXCDM "Ignore Overriding events" is set as "Yes". For exceptions with "Ignore overriding events" as "No" will not override the exceptions irrespective of value set in paymentSample.scr

Input

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
IgnoreExcpnFlg	Indicates whether exception has to be ignored or not

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>



Field Name	Details
IgnoreExcpnFlg	Indicates whether exception has to be ignored or not

Typical Usage Scenario(s):

To override/consider exceptions during transaction in batch.

©Copyright Infosys Ltd.

Script to Calculate Bucket Based on Rule Action



This script **customRuleCondForCFA.scr** will be called when custom condition is available in the rule that is getting executed. The script calls the CFA_External.scr script or CFA_System.scr according to the rule action type passed from the calling source file.

Input:

Field Name	Details
BANCS.INPUT.ruleActionType	The rule action type has valid values as External or System.

Output:

This script does not have any particular output. The output of the called script is available to the user.

Default Logic:

This is a product script and hence is always present.

Typical Usage scenario:

This script will be called when rule action type is SYSTEM.

©Copyright Infosys Ltd.

Script to Calculate Schedule Based on Rule Action System



This script **CFA_External.scr** is used to calculate schedule based on rule action system.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
ruleId	Rule id for the rule set id(mentioned at acct or scheme level) from MRHT.
zoneCode	Zone code for which schedule needs to be created.
Solid	Solid in which zone lodged.
zoneDate	Zone lodged date.
setNum	Set number for which schedules needs to be created.
endInstr	Endorsed Instrument flag.
redInstr	Redeposit Instrument flag
doubtInCol	Doubt in collectability flag
emrgncyCond	Emergency condition flag
tranCode	Transaction Code entered for instrument
ociCrncyCode	Currency code of the instrument in the OCI.
instrmntAmt	Instrument amount
ociRcreTime	rcre time of the instrument lodged.
valueDate	Zone lodged date.

instrSrlNum	The serial number which uniquely identifies the instrument.
instrId	Instrument number of the instrument
instrSchdISrlNum	Schedule number assigned to the Schedule
instrLocType	Location of Instrument derived from script
depLocType	Deposit location of set.
bankCode	Bank code in which zone lodged.
brCode	Branch code for the bank.
tranValueDate	Transaction value date.
shdBalCode	Shadow balance code of the zone.
repCode	The clearing representative code
sortCode	The sort code on which the instrument is drawn
acctSolId	Sol id in which account lodged.
payingAcctId	This is the account id of the paying account.
futCrFlagAtTranPost	flag for future value dated transations.
issExtnCntr	The extension counter of the issue bank
issBankCode	The bank code from where the instrument is issued.
issBrCode	The branch code from where the instrument is issued.
extnCode	The extension code pertains to the reason why an instrument is extended.
extnNumOfDays	It gives the number of days by which the clearing time of the instument is extended.
Acid	Account id for which instrument lodged.
ocpCrncyCode	The account currency code.
partTranAmt	Amount associated with account.
acctCrncyCode	The account currency code.
ocpRcreTime	Date and time when the user has created the record for the first time.
partTranSrlNum	The part tran identifier.
MRHTMatchRuleCond	AND, OR value specifies if all or any of the rule conditions are satisfied for the payment respectively.

GAMSchmCode	Scheme code mentioned for the account at GAM level.
GAMAcctOpnDate	Account open date at GAM level.
ocpRecCount	Number of Accounts added for the set
ociRecCount	Number of instruments per account.
updOCTbl	Update indicator for OCASHT and OCASDT table.
Action	Action code for the schedule.

Below variables will be available according to the rule conditions. These are divided into two parts: Instrument and Deposit. The below variable which are started with I will be available when rule sub type is INSTRUMENT and the variables started with D will be available when rule sub type is DEPOSIT.

Values which are present in in Rules(Added using MPR menu) are dumped into the below variables.

ITCOValue	Value for transaction code
ITCONotInd	Not Indicator for the rule
ITCOCondOpr	Condition operator. Valid values Equal To or IN
ITCRValue	Value for transaction currency.
ITCRNotInd	Not Indicator for the rule
ITCRCondOpr	Condition operator. Valid values Equal To or IN
ITZValue	Value for time zone.
ITZNotInd	Not Indicator for the rule
ITZCondOpr	Condition operator. Valid values Equal To or IN
ITODFromTimeOfDeposit	From_time_of_deposit for Time Of Deposit
ITODToTimeOfDeposit	To_time_of_Deposit for Time OF Deposit.
ITODNotInd	Not Indicator for the rule
ITODCondOpr	Condition operator. Valid values Equal To, Greater than, Less than, Greater than equal to , Less than equal to or IN
IIAToAmt	To amount for Instrument amount
IIAFromAmt	From amount for Instrument amount
IIACrncyCode	Currency code for the amount.
IIANotInd	Not Indicator for the rule
	Condition operator. Valid values Equal To, Greater than, Less

IIACondOpr	than, Greater than equal to , Less than equal to or IN
ICUIValue	Value for Check On Us Indicator
ICUINotInd	Not Indicator for the rule
ICUICondOpr	Condition operator. Valid values IS
IILEValue	Value for Instrument location
IILENotInd	Not Indicator for the rule
IILECondOpr	Condition operator. Valid values Equal To or IN
IDLEValue	Value for Deposit Location
IDLENotInd	Not Indicator for the rule
IDLECondOpr	Condition operator. Valid values Equal To or IN
IEHIValue	Value for Endorsed Cheque Indicator
IEHINotInd	Not Indicator for the rule
IEHICondOpr	Condition operator. Valid values IS
INAIValue	Flag value for new account.
INAINotInd	Not Indicator for the rule
INAICondOpr	Condition operator. Valid values IS.
IREIValue	Redeposited Instrument Flag
IREINotInd	Not Indicator for the rule
IREICondOpr	Condition operator. Valid values IS
IDCIValue	Doubt in Collectability Indicator
IDCINotInd	Not Indicator for the rule
IDCICondOpr	Condition operator. Valid values IS
IECIValue	Emergency Condition Indicator
IECINotInd	Not Indicator for the rule
IECICondOpr	Condition operator. Valid values IS
scriptName	Name of script mentioned in rule
DTCRValue	Value for transaction currency.
DTCRNotInd	Not Indicator for the rule
DTCRCondOpr	Condition operator. Valid values Equal To or IN

DTZValue	Value for time zone.
DTZNotInd	Not Indicator for the rule
DTZCondOpr	Condition operator. Valid values Equal To or IN
DTODFromTimeOfDeposit	From_time_of_deposit for Time Of Deposit
DTODToTimeOfDeposit	To_time_of_deposit for Time Of Deposit
DTODNotInd	Not Indicator for the rule
DTODCondOpr	Condition operator. Valid values Equal To, Greater than, Less than, Greater than equal to , Less than equal to or IN
DDAtoAmt	Value for To deposit amount
DDAfromAmt	Value for From Deposit amount
DDANotInd	Not Indicator for the rule
DDACondOpr	Condition operator. Valid values Equal To, Greater than, Less than, Greater than equal to , Less than equal to or IN
DDLEValue	Value for Deposit Location
DDLENotInd	Not Indicator for the rule
DDLECondOpr	Condition operator. Valid values Equal To or IN
DNAIValue	New account Indicator.
DNAINotInd	Not Indicator for the rule
DNAICondOpr	Condition operator. Valid values IS
scriptName	Name of script mentioned at rule level.

Output:

The defined output is available in a repository called BANCS, in a class called OUTPUT with the field names mentioned. You can access the input by referring to the fields in the specified manner:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Valid Values are "S" or "F" If update in OCASHT and OCASDT is successful than return

	value is "S" else for failure "F" will be return.
scheduleId	The new value passed by user for bucket calculation.

Default Logic:

This is a product script, so should be present always

Typical usage scenario:

This script will be called when rule action type is SYSTEM.

©Copyright Infosys Ltd.

Script to Calculate Schedule Based on Rule Action External



This script **CFA_External.scr** is to calculate schedule based on rule action external.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
ruleId	Rule id for the rule set id(mentioned at acct or scheme level) from MRHT.
zoneCode	Zone code for which schedule needs to be created.
solid	Solid in which zone lodged.
zoneDate	Zone lodged date.
setNum	Set number for which schedules needs to be created.
endInstr	Endorsed Instrument flag.
redInstr	Redeposit Instrument flag
doubtInCol	Doubt in collectability flag
emrgncyCond	Emergency condition flag
tranCode	Transaction Code entered for instrument
ociCrncyCode	Currency code of the instrument in the OCI.
instrmntAmt	Instrument amount
ociRcreTime	rcre time of the instrument lodged.

valueDate	Zone lodged date.
instrSrlNum	The serial number which uniquely identifies the instrument.
instrId	Instrument number of the instrument
instrSchdISrlNum	Schedule number assigned to the Schedule
instrLocType	Location of Instrument derived from script
depLocType	Deposit location of set.
bankCode	Bank code in which zone lodged.
brCode	Branch code for the bank.
tranValueDate	Transaction value date.
shdBalCode	Shadow balance code of the zone.
repCode	The clearing representative code
sortCode	The sort code on which the instrument is drawn
acctSolId	Sol id in which account lodged.
payingAcctId	This is the account id of the paying account.
futCrFlagAtTranPost	flag for future value dated transations.
issExtnCntr	The extension counter of the issue bank
issBankCode	The bank code from where the instrument is issued.
issBrCode	The branch code from where the instrument is issued.
extnCode	The extension code pertains to the reason why an instrument is extended.
extnNumOfDays	It gives the number of days by which the clearing time of the instument is extended.
acid	Account id for which instrument lodged.
ocpCrncyCode	The account currency code.
partTranAmt	Amount associated with account.
acctCrncyCode	The account currency code.
	Date and time when the user has created the

ocpRcreTime	record for the first time.
partTranSrlNum	The part tran identifier.
MRHTMatchRuleCond	AND, OR value specifies if all or any of the rule conditions are satisfied for the payment respectively.
GAMSchmCode	Scheme code mentioned for the account at GAM level.
GAMAcctOpnDate	Account open date at GAM level.
ocpRecCount	Number of Accounts added for the set
ociRecCount	Number of instruments per account.
updOCTbl	Update indicator for OCASHT and OCASDT table.
action	Action code for the schedule.
Below variables will be available according to the rule conditions. These are divided into two parts: Instrument and Deposit. The below variable which are started with I will be available when rule sub type is INSTRUMENT and the variables started with D will be available when rule sub type is DEPOSIT. Values which are present in in Rules(Added using MPR menu) are dumped into the below variables.	
ITCOValue	Value for transaction code
ITCONotInd	Not Indicator for the rule
ITCOCondOpr	Condition operator. Valid values Equal To or IN
ITCRValue	Value for transaction currency.
ITCRNotInd	Not Indicator for the rule
ITCRCondOpr	Condition operator. Valid values Equal To or IN
ITZValue	Value for time zone.
ITZNotInd	Not Indicator for the rule
ITZCondOpr	Condition operator. Valid values Equal To or IN
ITODFromTimeOfDeposit	From_time_of_deposit for Time Of Deposit
ITODToTimeOfDeposit	To_time_of_Deposit for Time OF Deposit.

ITODNotInd	Not Indicator for the rule
ITODCondOpr	Condition operator. Valid values Equal To, Greater than, Less than, Greater than equal to , Less than equal to or IN
IIAToAmt	To amount for Instrument amount
IIAFromAmt	From amount for Instrument amount
IIACrncyCode	Currency code for the amount.
IIANotInd	Not Indicator for the rule
IIACondOpr	Condition operator. Valid values Equal To, Greater than, Less than, Greater than equal to , Less than equal to or IN
ICUIValue	Value for Check On Us Indicator
ICUINotInd	Not Indicator for the rule
ICUICondOpr	Condition operator. Valid values IS
IILEValue	Value for Instrument location
IILENotInd	Not Indicator for the rule
IILECondOpr	Condition operator. Valid values Equal To or IN
IDLEValue	Value for Deposit Location
IDLENotInd	Not Indicator for the rule
IDLECondOpr	Condition operator. Valid values Equal To or IN
IEHValue	Value for Endorsed Cheque Indicator
IEHNotInd	Not Indicator for the rule
IEHCondOpr	Condition operator. Valid values IS
INAIValue	Flag value for new account.
INAINotInd	Not Indicator for the rule
INAICondOpr	Condition operator. Valid values IS.
IREIValue	Redeposited Instrument Flag
IREINotInd	Not Indicator for the rule
IREICondOpr	Condition operator. Valid values IS

IDCIValue	Doubt in Collectability Indicator
IDCINotInd	Not Indicator for the rule
IDCICondOpr	Condition operator. Valid values IS
IECIValue	Emergency Condition Indicator
IECINotInd	Not Indicator for the rule
IECICondOpr	Condition operator. Valid values IS
scriptName	Name of script mentioned in rule
DTCRValue	Value for transaction currency.
DTCRNotInd	Not Indicator for the rule
DTCRCondOpr	Condition operator. Valid values Equal To or IN
DTZValue	Value for time zone.
DTZNotInd	Not Indicator for the rule
DTZCondOpr	Condition operator. Valid values Equal To or IN
DTODFromTimeOfDeposit	From_time_of_deposit for Time Of Deposit
DTODToTimeOfDeposit	To_time_of_deposit for Time Of Deposit
DTODNotInd	Not Indicator for the rule
DTODCondOpr	Condition operator. Valid values Equal To, Greater than, Less than, Greater than equal to , Less than equal to or IN
DDAToAmt	Value for To deposit amount
DDAFromAmt	Value for From Deposit amount
DDANotInd	Not Indicator for the rule
DDACondOpr	Condition operator. Valid values Equal To, Greater than, Less than, Greater than equal to , Less than equal to or IN
DDLEValue	Value for Deposit Location
DDLENotInd	Not Indicator for the rule
DDLECondOpr	Condition operator. Valid values Equal To or IN

DNAIValue	New account Indicator.
DNAINotInd	Not Indicator for the rule
DNAICondOpr	Condition operator. Valid values IS
scriptName	Name of script mentioned at rule level.

Output:

Script Input	Description
BANCS.OUTPUT .successOrFailure	Valid Values are "S" or "F" If update in OCASHT and OCASDT is successful than return value is "S" else for failure "F" will be return.

Default Logic:

This is a product script, so it must always be present.

Typical Usage scenario:

This script will be invoked when rule action type is EXTERNAL. The output of the script will calculate the schedule and insert into OCASHT and OCASDT table.

©Copyright Infosys Ltd.

Script to Calculate Bucket Based on Rule Action



Description:

This script is called when custom condition is available in the RULE that is getting executed. The script calls the CFA_External.scr script or CFA_System.scr according to the rule action type passed from the calling source file.

Input:

Script Input	Description
BANCS.INPUT.ruleActionType	The rule action type has valid values as External or System.

Output:

This script does not have any particular output. The output of the called script is available to the user.

Script Output	Description
BANCS.OUTPUT.exemptTran	Whether to exclude this tran from interest calculation or not.

Default logic:

This is a product script and so always present.

Typical Usage scenario:

This script is called when rule action type is SYSTEM.

©Copyright Infosys Ltd.

Script to Calculate Schedule Based on Rule Action System



Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input
ruleId
zoneCode
Solid
zoneDate
setNum
endInstr
redInstr
doubtInCol
emrgncyCond
tranCode
ociCrncyCode
instrmntAmt
ociRcreTime
valueDate
instrSrlNum
instrId
instrSchdlSrlNum

instrLocType
depLocType
bankCode
brCode
tranValueDate
shdBalCode
repCode
sortCode
acctSolId
payingAcctId
futCrFlagAtTranPost
issExtnCntr
issBankCode
issBrCode
extnCode
extnNumOfDays
Acid
ocpCrncyCode
partTranAmt
acctCrncyCode
ocpRcreTime
partTranSrlNum
MRHTMatchRuleCond
GAMSchmCode
GAMAcctOpnDate
ocpRecCount
ociRecCount
updOCTbl
Action

Below variables will be available according to the rule conditions. These are divided into two

Values which are present in in Rules(Added using MPR menu) are dumped into the below

ITCOValue
ITCONotInd
ITCOCondOpr
ITCRValue
ITCRNotInd
ITCRCondOpr
ITZValue
ITZNotInd
ITZCondOpr
ITODFromTimeOfDeposit
ITODToTimeOfDeposit
ITODNotInd
ITODCondOpr
IIAToAmt
IIAFromAmt
IIACrncyCode
IIANotInd
IIACondOpr
ICUIValue
ICUINotInd
ICUICondOpr
IILEValue
IILENotInd
IILECondOpr
IDLEValue
IDLENotInd
IDLECondOpr
IEHValue
IEHNotInd
IEHCondOpr

INAIValue
INAINotInd
INAICondOpr
IREIValue
IREINotInd
IREICondOpr
IDCIValue
IDCINotInd
IDCICondOpr
IECIValue
IECINotInd
IECICondOpr
scriptName
DTCRValue
DTCRNotInd
DTCRCondOpr
DTZValue
DTZNotInd
DTZCondOpr
DTODFromTimeOfDeposit
DTODToTimeOfDeposit
DTODNotInd
DTODCondOpr
DDAtoAmt
DDAfromAmt
DDANotInd
DDACondOpr
DDLEValue
DDLENotInd
DDLECondOpr
DNAIValue

DNAINotInd
DNAICondOpr
scriptName

Output:

The defined output is available in a repository called BANCS, in a class called OUTPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.OUTPUT.< fieldName>

Script Output	Description
successOrFailure	Valid Values are "S or "F If update in OCASHT and OCASDT is successful than return value is "S else for failure "F will be return.
scheduleId	The new value passed by user for bucket calculation.

Default logic:

This is a product script and so always present.

Typical Usage scenario:

This script is called when rule action type is SYSTEM.

©Copyright Infosys Ltd.

Script to Calculate Schedule Based on Rule Action External



Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input
ruleId
zoneCode
Solid
zoneDate
setNum
endInstr
redInstr
doubtInCol
emrgncyCond
tranCode
ociCrncyCode
instrmntAmt
ociRcreTime
valueDate
instrSrlNum
instrId
instrSchdlSrlNum

instrLocType
depLocType
bankCode
brCode
tranValueDate
shdBalCode
repCode
sortCode
acctSolId
payingAcctId
futCrFlagAtTranPost
issExtnCntr
issBankCode
issBrCode
extnCode
extnNumOfDays
Acid
ocpCrncyCode
partTranAmt
acctCrncyCode
ocpRcreTime
partTranSrlNum
MRHTMatchRuleCond
GAMSchmCode
GAMAcctOpnDate
ocpRecCount
ociRecCount
updOCTbl
Action

Below variables will be available according to the rule conditions. These are divided into two

Values which are present in in Rules(Added using MPR menu) are dumped into the below

ITCOValue
ITCONotInd
ITCOCondOpr
ITCRValue
ITCRNotInd
ITCRCondOpr
ITZValue
ITZNotInd
ITZCondOpr
ITODFromTimeOfDeposit
ITODToTimeOfDeposit
ITODNotInd
ITODCondOpr
IIAToAmt
IIAFromAmt
IIACrncyCode
IIANotInd
IIACondOpr
ICUIValue
ICUINotInd
ICUICondOpr
IILEValue
IILENotInd
IILECondOpr
IDLEValue
IDLENotInd
IDLECondOpr
IEHIValue
IEHINotInd
IEHICondOpr

INAIValue
INAINotInd
INAICondOpr
IREIValue
IREINotInd
IREICondOpr
IDCIValue
IDCINotInd
IDCICondOpr
IECIValue
IECINotInd
IECICondOpr
scriptName
DTCRValue
DTCRNotInd
DTCRCondOpr
DTZValue
DTZNotInd
DTZCondOpr
DTODFromTimeOfDeposit
DTODToTimeOfDeposit
DTODNotInd
DTODCondOpr
DDAtoAmt
DDAfromAmt
DDANotInd
DDACondOpr
DDLEValue
DDLENotInd
DDLECondOpr
DNAIValue

DNAInotInd
DNAICondOpr
scriptName

Output:

The defined output is available in a repository called BANCS, in a class called OUTPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.OUTPUT.< fieldName>

Script Output	Description
BANCS.OUTPUT .successOrFailure	Valid Values are "S or "F If update in OCASHT and OCASDT is successful than return value is "S else for failure "F will be return.

Default logic:

This is a product script and so always present.

Typical Usage scenario:

This script is invoked when rule action type is EXTERNAL. The output of the script calculates the schedule and inserts into OCASHT and OCASDT table.

©Copyright Infosys Ltd.

Script to do Release to Shadow Balance Operation on an Instrument



Description:

The script AutoSetReleaseForOCTM.scr must be present in TBA_SCRIPTS directory. This script is used to do Release to Shadow Balance Operation on an Instrument.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
release Flag	The autoSetRelease is to be done only for CFA(Check funds Availability) Enabled Instruments. This flags tells us whether the Instrument is CFA enabled or not.
clgZoneCode	The zone code of the clearing zone
clgZoneDate	The zone date of the clearing zone
setNum	The set num for which the instrument is lodged
releaseTranId	The tran ID created during Released to Shadow Balance

Output:

The script used to do Release to Shadow Balance Operation on an Instrument.

Default logic:

No default logic in the absence of the script.

Typical Usage scenario:

The script is used to do Release to Shadow Balance Operation on an Instrument.

©Copyright Infosys Ltd.

Finacle Copyright

Scripts for MBCD



The different scripts for MBCD are:

[Script to Process the Details in MBCD Menu](#)

[Script to Validate the Details in MBCD Menu](#)

©Copyright Infosys Ltd.

Scripts for MCTRD



The different scripts for MCTRD are:

[Script to Fetch Data for Modify and Inquire Modes in MCTRD Menu](#)

[Script to Default Populate Details for MCTRD Menu](#)

[Script to Populate the Details for ADD Mode in MCTRD Menu](#)

[Script to Validate the Details for Add/Modify Mode in MCTRD Menu](#)

[Script to Add the Details in MCTRD Menu](#)

[Script to Modify the Details MCTRD Menu](#)

©Copyright Infosys Ltd.

Scripts for GRCE



The different scripts for GRCE are:

[Script to Invoke Batch Job GRCE](#)

[Script to Set Register Information for Batch Job GRCE](#)

[Script to Get the List of Customers for the Batch GRCE](#)

[Script to Process Details of Each Customer for the Batch GRCE](#)

[Script to Generate Report for the Batch GRCE](#)

©Copyright Infosys Ltd.

Overdraft Events



The different Overdraft events are:

- [URODF – Upload Revolving Overdraft Fee](#)
- [MAN Tod Grant](#)
- [PROO/HODBLCOL - Pay Revolving Overdraft Online / Bill Collection of Revolving Overdraft](#)
- [HCOTA – Charge Off Transaction Account](#)
- [Grant for Informal TOD for Transaction from UNISER](#)
- [Modify Product Overdraft Limits Dates](#)
- [Grant for Informal TOD for Transaction for Debit Transaction after Checking the Informal Balance](#)

©Copyright Infosys Ltd.

URODF – Upload Revolving Overdraft Fee

Script Name:

The script `uploadRODFeeMTT.scr` should be present in `TBA_SCRIPTS` directory. This script is used to create the transaction when URODF upload is run.

Input:

The defined inputs are available in repository MTT, class `InputDetails` and with the field names mentioned below. You can access the inputs by referring the fields in the following manner.

MTT. `InputDetails`. `<Fieldname>`

Field Name	Details
rodAcct	The revolving overdraft account for which upload is done.
feeDrAcct	The fee debit account for the transaction.
pttCrAcct	The PTTM credit account for the transaction.
feeAmt	The transaction amount.
tranCrncy	The currency in which transaction is done.
capFlg	Capitalization flag
tranParticular	The particulars about transaction.
tranRptCode	The report code.
tranRmks	The transaction remarks.
eventId	The event ID of fees being uploaded.
eventType	The event type of fees being uploaded. It will be GCHRG.
chrgThruOfficeAcct	The flag which indicates whether charges are to be routed through office account or not.
TranId	The transaction ID.

cifld	The cif ID of the customer of ROD A/c.
--------------	--

Output:

BANCS.OUTPUT.successOrFailure: contains either “S” or “F”

BANCS.OUTPUT.tranId: contains the tranid of transaction

Default logic:

It is a mandatory script. Error is returned if script is not present.

Typical Usage Scenario:

You can create transaction for fee upload for revolving overdraft account.

Script Name:

The script numofRecordsInaTran.scr should be present in TBA_SCRIPTS directory. This script is used to decide the number of records in a single transaction when URODF upload is run. This is a sample script.

Input:

None

Output:

BANCS.OUTPUT.Records: contains the value of number of records for which a single transaction needs to be created.

Default logic:

A single transaction will be created for every 100 records.

Typical Usage Scenario:

You can decide on the number of uploaded records for which a single transaction would be created on upload of fee for revolving overdraft account.

Sample Scripts:

Sample script numofRecordsInaTran.sscr is present in the Sample scripts (samscripts) directory.

©Copyright Infosys Ltd.

MAN TOD Grant



Script Name:

The script MAN_TodGrant.scr must be present in TBA_SCRIPTS directory. This script will be used to decide whether TOD is to be granted or not based on number of times attempted.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.NoOfTimesAttempted	Indicates number of times attempted for execution.
BANCS.INPUT.ExecPaysysId	Identifies the paysysId used for execution.
BANCS.INPUT.DrAcct	Effective Account used for execution.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.GrantTODFlag	Sets TOD Flag.
BANCS.OUTPUT.DefaultPaysysId	PaysysId to be defaulted if TOD is granted.

Typical Usage Scenario:

This script is called when during mandate execution and grants TOD based on the number of times attempted.

©Copyright Infosys Ltd.

PROO / HODBLCOL - Pay Revolving Overdraft Online / Bill Collection of Revolving Overdraft



Script Name:

The script odbillcolltran.scr should be present in TBA_SCRIPTS directory. This script is used to create the transaction for PROO/HODBLCOL.

Input:

The new inputs variables are added and are available in MTT repository, class InputDetails and with the field names mentioned below. One can access the inputs by referring the fields in the following manner:

MTT. InputDetails. <Fieldname>

Field Name	Details
ODacctAcid	Overdraft account ID for which payment is being done.
ODcrncyCode	Currency code of overdraft account.
OPacctAcid	Operative account ID from where funds to be collected.
OPcrncyCode	Operative account's currency code.
collectionAmtFromOP	The amount to be collected from operative account.
collectionAmtCrncy	Currency in which amount to be collected.
intCollAmt	The interest amount to be collected.
intCrAcct	The interest credit account for the transaction.
feeCollAmt	The payment amount for fee.
feeCrAcct	The fee credit account for the transaction.
principalCollAmt	The payment amount for principal.

RateCode	Rate code for the transaction.
Rate	Rate for the transaction.
tranRemarks	The remarks entered by the user.
CalledFrom	To specify if this is called from PROO or HODBLCOL.

Output:

The output would be the tran ID.

Default logic:

It is a mandatory script. Error is returned if script is not present.

Typical Usage Scenario:

You can create bill collection transaction for revolving overdraft account with interest fee and principal part trans.

Script Name:

The script `getPymtSequenceForRod.scr` should be present in `TBA_SCRIPTS` directory. This script is used to decide the order in which the payment amount should be distributed when `PROO/HODBLCOL` is run. This is a sample script.

Input:

Field Name	Details
ODacctId	Revolving overdraft for which payment is being done.
ODcrncyCode	Currency code of overdraft account.
ODschmCode	Scheme code of revolving overdraft account.
ODcustId	Cust ID of revolving overdraft account.
ODsolId	Sol ID of revolving overdraft account.

Output:

BANCS.OUTPUT. pymtSequence: contains the order for adjustment of payment amount in different components.

Default logic:

The default order is interest, fee and principal.

Typical Usage Scenario:

You can decide the order for adjustment of payment amount in different components.

Sample Scripts:

Sample script getPymtSequenceForRod.sscr is present in the Sample scripts (samscripts) directory.

©Copyright Infosys Ltd.

HCOTA – Charge Off Transaction Account



Script Name:

The product script RODChargeOffMTT.scr present in TBA_SCRIPTS directory. This script is used to create the part trans during charge off ROD account in HCOTA.

Input:

The defined inputs are available in the MTT repository, class “InputDetails” and with the field names mentioned below. You can access the inputs by referring the fields in the following manner:

MTT.InputDetails. <Fieldname>

Field Name	Details
tranAcct	ROD account on which charge off is being done.
tranCrncy	Currency code of the ROD account.
chargeOffAcct	Charge off office account set in scheme.
chargeOffAcid	Acid for the charge off office account.
intDrAcct	Interest routed office account set in scheme.
intDrAcid	Acid of interest routed office account.
feeDrAcct	Fee routed office account set in scheme.
feeDrAcid	Acid for fee routed office account.
nonCapFeeAcct	Non capitalized fee office account set in scheme.
nonCapFeeAcid	Acid for non capitalized fee office account.
intSuspAcct	Interest suspense office account set in scheme.
intSuspAcctAcid	Acid of interest suspense account.
penalIntSuspAcct	Penal interest suspense account.

penalIntSuspAcctAcid	Acid for penal interest suspense account.
feeOutStandingAmt	Account balance of the fee routed office account.
prinTranAmt	Account balance of the ROD account.
intTranAmt	Total interest applied on the ROD account.
penalIntTranAmt	Total Penal interest applied on the ROD account.
bookTranAmt	Total booked amount.
penalBookTranAmt	Total penal booked amount.
ballnIntDrAcct	Account balance in the interest routed office account

Output:

NA

Default logic:

NA

Typical Usage Scenario:

You can use during Charge off of Revolving Overdraft Accounts.

Script Name:

NA

©Copyright Infosys Ltd.

Grant for Informal TOD for Transaction from UNISER



Script Name:

The script ChklfInfrmlTODAlwd.scr is used to check whether Informal TOD can be granted for any transaction through UNISER or not.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
Accounted	Contains the account id.
clrBalAfterTran	Contains the clear balance amount which is remaining after transaction.
effDrBalLimit	Contains the effective debit balance limit that is obtained from the function getEffDrBalLim which is calculated based on the parameter set at SRGPM.
todAmount	The excess amount for which TOD needs to be granted.
availBal	Contains the available balance.
tranAmount	Contains the transaction amount.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Contains the return value from the script. Valid Values are "S" or "F".
allowInformalBalFlg	Contains the value which decides whether TOD needs to be allowed or not.

Default Logic:

For any account, the debit transaction can be done, up to a limit of available balance plus debit balance limit, irrespective of lien placed on the account.

Typical Usage Scenario:

This script can be used, if lien amount and system reserved amount needs to be considered for any debit transaction on the account.

Example:

NA

©Copyright Infosys Ltd.

Modify Product Overdraft Limits Dates



Script Name:

The script ModifyProductODDates.scr is used to modify start date and expiry date of first tier and percolation required flag of account.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
Foracid	The account id for which the product overdraft limit is created.
limitAmount	Sanction limit amount granted.
calcStartDate	Calculated start date by system
calcExpiryDate	Calculated expiry date of the first product overdraft limit.
percolReqd	Percolation required flag.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
startDate	Contains start date of the first product overdraft limit returned from the script.
expiryDate	Contains expiry date of the first product overdraft limit returned

	from the script.
percolReqd	Contains percolation required flag returned from the script.

Default Logic:

In case this script is not present, system internally assumes that percolation required flag is YES. Applicable and expiry date will be followed as per setup details available in SUPOL.

Typical Usage Scenario:

Script Hook is provided to allow modification of start date, expiry date and percolation required flag.

Example:

NA

©Copyright Infosys Ltd.

Grant for Informal TOD for Transaction for Debit Transaction after Checking the Informal Balance



Script Name:

The script ChklfInfrmITODAlwd.sscr is used to check whether TOD can be given for any debit transaction after checking the informal balance. It must be present in TBA_SCRIPTS directory.

Input:

The defined inputs are available in repository CDCI, class Request and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

CDCI. Request.<Fieldname>

Field Name	Details
Accounted	Contains the Account id.
clrBalAfterTran	Contains the clear balance amount which is remaining after transaction.
effDrBalLimit	Contains the effective debit balance limit that is obtained from the function getEffDrBalLim, which is calculated based on the parameter set at SRGPM.
lienAmt	The sum of all the lien amount for the account.
availBal	Contains the available balance.
tranAmount	Contains the transaction amount.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Contains the return value from the script. Valid Values are "S" or "F".
allowInformalBalFlg	Contains the value which decides whether TOD needs to be allowed or not.

Default Logic:

For any account, the debit transaction can be done up to a limit of available.

Typical Usage Scenario:

This script can be used, if Debit balance limit, lien amount and system reserved amount needs to be considered for any debit transaction on the account.

Example:

NA

©Copyright Infosys Ltd.

Parse Events

The Parse events are:

[Parse the Input to Populate IMPARAM Class](#)

[Parsing Logic for Funds Verify Details](#)

[Other Scripts](#)

[Parsing Logic for HTTUM 711 Record](#)

©Copyright Infosys Ltd.

Finacle Copyright

Passbook Related Events

The Passbook Related events are:

[Passbook Printing](#)

©Copyright Infosys Ltd.

Past Due Details Maintenance



The events related to Past Due Details Maintenance are:

[Maintain Additional Details and Validate Option Code](#)

[Past Due Details Inquiry and Report Generation](#)

©Copyright Infosys Ltd.

Payment System Events

The events related to Payment System are:

- [Define Outward Swift Payment Process](#)
- [Derive Sol ID for the Message Based on Paysys ID](#)
- [Format Finacle Amount to Paysys Amount Format](#)
- [Format Finacle Date to Paysys Date Format](#)
- [Format Finacle Time to Paysys Time Format](#)
- [Format Swift Message for HPORDM Display](#)
- [Get Plugged Parties for Routing](#)
- [Get Plug Parties for Routing](#)
- [Get Reroute Paysys ID](#)
- [Get Routing Details from Outward Mapping Equation](#)
- [Get RTGS Inward Suspense Message Details](#)
- [Get RTGS UTR Number](#)
- [Get Swift Parameters Information](#)
- [Check Homogeneity of Message](#)
- [Map HPORDM for Rerouting](#)
- [Parse Swift Message](#)

- [Parsing Logic for PaySys Message](#)
- [Format SMH Message](#)
- [Convert Swift Format to SMH Format](#)
- [Rerouting Logic](#)
- [Format Paysys Amount to Finacle Format](#)
- [Format Paysys Date to Finacle Date Format](#)
- [Plug In Parties for Routing](#)
- [Calculate Payment Dates](#)
- [Define HPORDM Customer Payment Transaction](#)
- [Validate Payment Dates](#)
- [Validate HPORDM Message Details](#)
- [Define Insurance Transaction](#)
- [RTGS Creation](#)
- [Reroute HPORDM Entry For SWIFT](#)
- [Reroute RTGS Payment](#)
- [Reroute SWIFT Payment](#)
- [Format Inward RTGS Message](#)
- [Format Out Messages for RTGS](#)
- [Scan For RTGS Blacklist Customers](#)

- [Validate RTGS details](#)
- [Payment Order Charge Calculation](#)
- [PO Script for Data Population for NEFT & RTGS](#)
- [Select Parsing Script Based on the Paysys ID](#)
- [Upload a File for the Paysys ID NEFT](#)
- [Upload a File for the Paysys ID RTGS](#)
- [Getting Additional Details from the Incoming RTGS Message](#)
- [Upload a File for the Paysys ID SFMS](#)
- [Parse the Input Message Header and Footer Details](#)
- [Parse the Input Message Header and Footer Details in Finacle Internal Format](#)
- [Validates the Criteria of the HGUPSM](#)
- [Get the Name of the Script for Grouping and Ungrouping Payment Messages in HGUPSM](#)
- [Ungrouping the N02 NEFT Messages](#)
- [Transmit a File for the Paysys ID NEFT through HTRSWIFT](#)
- [Transmit a File for the Paysys ID RTGS](#)
- [Transmit a File for the Paysys ID SFMS](#)
- [To Parse the Input Message Details and Outputs the Formatted SFMS Message](#)
- [Deriving the Bank Code and Branch Code](#)

- [Deriving the Bank Details and Branch Details](#)
- [Derivation of Details for POIE](#)
- [Derivation of Paysys ID for IE](#)
- [Derivation of Sol ID for IE](#)
- [Getting Charge Event Id for IE](#)
- [Inward Credits for Message for IE](#)
- [Message Rerouting Logic of PAYSYS for IE](#)
- [Rerouting of Payment for IE](#)
- [Validate the Extra Inter Entity](#)
- [Link Network Directory](#)
- [BACS AED XML Upload Script](#)
- [BACS ahbx0005 Update Status Fields](#)
- [BACS Check Authorization Required For CP](#)
- [BACS Get Processing Date Script](#)
- [BACS Get Settlement Account For Contra Handling](#)
- [BACS Multi File Type Upload Script](#)
- [Update AED Custom fields for PO Creation during Interest Calculation](#)
- [Fetch Beneficiary's Address Field for PO creation](#)
- [Fetch DepartmentNumber Field for PO Creation](#)

- [Bank Validation and Decision](#)
- [BACS GenMultiOutFile Script](#)
- [Map Mandate Data To PORDM](#)
- [BACS Check Ach Holiday For PO](#)
- [BACS Check ACH Holiday For TD-SI Script](#)
- [SEPA-form Query For HGARFG/HGARFR](#)
- [SEPA-Generate Multi Out File For HGARFG](#)
- [SEPA-Update Status Fields for HGARFG/HGARFR](#)
- [SEPA-Settlement Date and Effective date validation for SEPA Credit and Direct Debits](#)
- [Event Mapping scripts for SFMS Message](#)
- [Format scripts for SFMS Message](#)
- [Mapping of Message Id from SWIFT to other Payment system](#)
- [Mapping of Message ID from Other Payment System Message ID to SWIFT](#)
- [Mapping for n series Messages to a Single Message](#)
- [Risk Limit Status Update Script](#)
- [Batch Limit Status Update Script](#)
- [Service Preference Serial Number Update](#)
- [AUTOREPRESENTMENT script](#)

- [Check for Autorepresentment](#)
- [Open Zone for Cheque Mode of Autorepresentment](#)
- [Script to Lodge Instruments](#)
- [Instrument Message Id](#)
- [Script to Validate Blacklisted Payments](#)
- [Auto Set Release For OCTM](#)
- [Profile Charge Transaction Creation Script](#)
- [Outward Clearing Data Upload](#)
- [Script to Generate Non Renewal Nidification](#)
- [Script to Generate Rescission Notification](#)
- [Script to Validate Other Bank Account](#)
- [Script to do Modules Check for BACS](#)
- [Script to Get Payment System ID](#)

©Copyright Infosys Ltd.

Link Network Directory

This script has the default logic for linking bics of same bank present in different network directories.

The script NDT_link.scr should be present in \$TBA_SCRIPTS directory.

Inputs Available in the Scripts

The defined inputs are available in repository PAYSYS. Two classes are created one for from entity and another for to entity, the class names are FromEntity and ToEntity respectively, INPUT will be given to the script with the field names mentioned below. The same set of field names will be present for both the entities. One can access the inputs by referring the fields in the following manner.

PAYSYS.FromEntity.<Fieldname> and PAYSYS.ToEntity.<Fieldname>

Script Input	Description
refKey	Primary key for the table. The unique key of the record in the upload file. If a record is added, then the following options have been provided for this field. a) User can enter a unique value b) User can form a unique value of this field by combining two, three fields c) For record which does not come with a key, the value will be generated from a sequence
bankId	Bank Id
fileSource	This defines the source from which the record was created. SWIFT, TARGET, CHAPS, CHIPS, FEDWIRE, BNM, RENTAS
bankCode	Bank code available in the directory, both this field and "dirBankCode" field will have the same value only.
fileType	This defines whether the record is manually added or uploaded
unqBankIdentifier	Unique Bank Identification Code of Network directory (bic)
secBankIdentifier	Secondary Bank Identification Code of Network Directory

repBankIdentifier	Representative Bank Identification Code of Network Directory
primaryRecflg	Y/N/NULL. Y- Whether the particular record is the primary record, N - If a record is linked with any primary record and NULL - If a record is not linked with any record
primaryRef	It holds the reference key of the record to which it is linked. If it is a linked record, then it should carry the ref_key of the Primary record. If it is a primary record, then this field will carry its own ref_key
dirBankcode	Bank code available in the directory
instituteName1	Name of the institute Part 1
instituteName2	Name of the institute Part 2
instituteName3	Name of the institute Part 3
branchInfo1	Name of the branch Part 1
branchInfo2	Name of the branch Part 2
address1	Address of the bank Part 1
address2	Address of the bank Part 2
address3	Address of the bank Part 3
address4	Address of the bank Part 4
locationName1	Location of the bank Part 1
locationName2	Location of the bank Part 2
locationName3	Location of the bank Part 3
zipCode	Zip code of the bank
countryName1	Country Name of the bank Part 1
countryName2	Country Name of the bank Part 2
countryCode	Country Code of the bank

Output Expected

The defined outputs are available in repository BANCS, class

OUTPUT and with the field names mentioned below. One can access the outputs by referring the fields in the following manner.

BANCS. OUTPUT. <Fieldname>

Script Input	Description
linkFlag	Y/N, if Y the records will be linked, if N the records will not be linked.
bankId	Bank Id
linkDesc	Will be dumped into the report file for reference.

Default logic in case script is not present

The script should be present if it is not present linking will not happen when LND menu is executed.

Typical usage scenario(s)

The script will be called to link bics of same bank present in different network directories, when the linking is done through LND batch job.

©Copyright Infosys Ltd.

BACS AED XML Upload Script



Script Name:

The script `BACS_aedXMLUpload.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to upload into AED for BACS format.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
<code>BANCS.INPUT.paysysid</code>	Paysys Id of the ACH Payment System
<code>BANCS.INPUT.organizationcode</code>	A Valid identifier for the originator of transaction
<code>BANCS.INPUT.payee name</code>	Name of the originator
<code>BANCS.INPUT. productcode</code>	Product of the originator or biller
<code>BANCS.INPUT. paymentamount</code>	The amount for which the transaction is created
<code>BANCS.INPUT. currency</code>	Transaction Currency
<code>BANCS.INPUT. returnamount</code>	The amount which is rejected
<code>BANCS.INPUT. debitdate</code>	Value date of the transaction
<code>BANCS.INPUT.settlementdate</code>	Settlement date of the transaction.
<code>BANCS.INPUT. duedate</code>	Due date of the transaction
<code>BANCS.INPUT. bankcode</code>	Bank Code of the payee name
<code>BANCS.INPUT. branchcode</code>	Branch Code of the payee name

BANCS.INPUT. rejectioncode	Rejection Code if transaction is made to rejected status
BANCS.INPUT. status	Status of the record. P - Processed, R - Rejected, S - Suspended, U - Under Processing, G - Direct Recall, B - To be recalled, C - Recalled , J - Unmatched Recal
BANCS.INPUT. returnactind	Indicates the returning of the record. Values are S -Success, B -Both, F -Failure, N -None
BANCS.INPUT. crdrind	Credit Debit indicator. Valid values are C - Credit, D - Debit.
BANCS.INPUT. inwardoroffus	Inward Outward Indicator. Valid values are I - Inward, O - Outward.
BANCS.INPUT. origoranswer	Status of the freshly uploaded record. Valid values are 0 - Fresh entry, 1 - return entry, 2 - Reject entry, 3 - Recall entry.
BANCS.INPUT. transactioncode	Transaction Code . Transaction Codes are defined in HRRCDM in the link tran_code. Mandatory Field
BANCS.INPUT. transactionid	Additional trace number
BANCS.INPUT. diasreferencenum	Additional trace number
BANCS.INPUT. filename	Return file name. Used for storing the return file name from which the transaction was created.
BANCS.INPUT. addproddata	Free text. Additional Information can be entered here
BANCS.INPUT. singlemultipliedrflag	Denotes whether single or multiple transactions for a batch ,Values are S - Single and M - Multiple
BANCS.INPUT. lienordebitflag	Denotes the transaction is direct debit or Lien ,Values are D – Debit and L - lien. Default value is D
BANCS.INPUT. batchid	Batch Id of the Uploaded File
BANCS.INPUT. dareferencenumber	Debit Authorization Reference Number.
BANCS.INPUT. origacct	Originator Account ID
BANCS.INPUT. headersrlnum	Header srl num of the batch record in AHD
BANCS.INPUT. achcorporateflag	ACH Corporate Flag
BANCS.INPUT. receiveracctdtls	This field stores the receiver account number entered by the user.This will be populated during upload only

BANCS.INPUT. autoreturnflag	Flag to indicate if auto return is enabled, Values are Y - Yes and N - No
BANCS.INPUT. custinfoflg	Flag whether to collect charge from instructed amt or not
BANCS.INPUT. receivername	Receiver name.
BANCS.INPUT. origaddr1	Address line 1 of the originator
BANCS.INPUT. origaddr2	Address line 2 of the originator
BANCS.INPUT. recvraddr	Additional information about receiver.
BANCS.INPUT. receiverid	Identification of the receiver. Mandatory field
BANCS.INPUT. RateCode	The rate code used for conversion between PAYSYS base currency and account currency.
BANCS.INPUT. Rate	The exchange rate used for conversion between PAYSYS base currency and account currency.
BANCS.INPUT. CollectChrgFromAmtFlag	Flag to collect charges from instructed amt or not
BANCS.INPUT. WaiveChargeFlag	Flag to check whether waive charges or not.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. EntrySrlNum	Finacle generated srl number in AED table.
BANCS.OUTPUT. PaysysId	Paysys Id of the ACH Payment System
BANCS.OUTPUT. HeaderSrlNum	Reference from header table -- Finacle generated srl number.
BANCS.OUTPUT. ReturnFileName	Return file name. Used for storing the return file name from which the transaction was created.
BANCS.OUTPUT.	Date on which return file is sent.

ReturnDate

BANCS.OUTPUT. OrigAcct	Originator Account ID
BANCS.OUTPUT. OrigId	A Valid identifier for the originator of transaction. For example Organisational Code associated with the Account can be used as the orig ID
BANCS.OUTPUT. OrigInfo1	Additional information about originator.
BANCS.OUTPUT. OrigInfo2	Additional information about originator.
BANCS.OUTPUT. OrigName	Name of the originator.
BANCS.OUTPUT. SrvCode	Product of the originator or biller.
BANCS.OUTPUT. RecvAcct	Receiver Account acid.
BANCS.OUTPUT. RecvId	Identification of the receiver.
BANCS.OUTPUT. RecvInfo1	Additional information about receiver.
BANCS.OUTPUT. RecvInfo2	Additional information about receiver.
BANCS.OUTPUT. RecvName	Receiver name.
BANCS.OUTPUT. TranAmt	The amount for which the transaction is created.
BANCS.OUTPUT. TranCrncy	Transaction Currency.
BANCS.OUTPUT. CommisionAmt	Commission amount for the transaction.
BANCS.OUTPUT. TotalAmt	Total amount is transaction amount plus commission amount.
BANCS.OUTPUT. OutwardCommision	Outward commission amount.
BANCS.OUTPUT.	The amount which is rejected.

RejectAmt

BANCS.OUTPUT. OtherAmt1	Additional amount Field.
BANCS.OUTPUT. OtherAmt2	Additional amount Field.
BANCS.OUTPUT. EffectiveDate	Value date of the transaction
BANCS.OUTPUT. SettlementDate	Settlement date of the transaction.
BANCS.OUTPUT. DueDate	Due date of the transaction
BANCS.OUTPUT. Date1	Additional Date Field.
BANCS.OUTPUT. Date2	Additional Date Field.
BANCS.OUTPUT. BankCode	Bank Code .
BANCS.OUTPUT. BranchCode	Branch Code.
BANCS.OUTPUT. SolId	Service Outlet Id of the Account
BANCS.OUTPUT. OrigCode	Originator Code. User Enterable
BANCS.OUTPUT. RejCode	Rejection Code.
BANCS.OUTPUT. RejDesc	Rejection Description -- reason for failure. Populated from ACH_PAYSYS_REASON_CODE_TABLE table for a given rejection code
BANCS.OUTPUT. EntryStatus	Status of the record. P - Processed, R - Rejected, S - Suspended, U - Under Processing,G - Direct Recall, B - To be recalled, C - Recalled , J - Unmatched Recall
BANCS.OUTPUT. ReturnStatus	Return Status. Valid values are R - Ready to Send, S - Sent , N – Not to be sent.
BANCS.OUTPUT. FailProcess	Indicates Failure Processing is Automatic or Manual/Suspense Processing. A -Automatic, M -Manual
BANCS.OUTPUT. status2	Additional status field which can be used for customization purposes

BANCS.OUTPUT. ReturnInd	Values are S -Success,B -Both,F -Failure, N -None
BANCS.OUTPUT. CrDrInd	Credit Debit indicator. Valid values are C - Credit, D - Debit.
BANCS.OUTPUT. InwOutwInd	Inward Outward Indicator Valid values are I - Inward, O - Outward.
BANCS.OUTPUT. FreshRetEntry	Entry type. Valid values are 0 - Fresh entry, 1 - return entry, 2 - Reject entry, 3 - Recall entry.
BANCS.OUTPUT. TranCode	Transaction Code .
BANCS.OUTPUT. CustTranId	Transaction Id of Customer.
BANCS.OUTPUT. CustTranDate	Customer transaction date.
BANCS.OUTPUT. SettTranId	Transaction Id for the settlement transaction
BANCS.OUTPUT. SettTranDate	Settlement transaction date.
BANCS.OUTPUT. TraceNum1	Additional trace number.
BANCS.OUTPUT. TraceNum2	Additional trace number.
BANCS.OUTPUT. TraceNum3	Additional trace number.
BANCS.OUTPUT. ApprovedBy	Id of user who approves.
BANCS.OUTPUT. ApproverCmnt	Comments by approver.
BANCS.OUTPUT. FreeCode1	Free code. Free Code 1 is maintained in RRCDM in reference type JB
BANCS.OUTPUT. FreeCode2	Free code. Free Code 2 is maintained in RRCDM in reference type JC
BANCS.OUTPUT. FreeCode3	Free code. Free Code 3 is maintained in RRCDM in reference type JD

BANCS.OUTPUT. FreeCode4	Free code. Free Code 4 is maintained in RRCDM in reference type JE
BANCS.OUTPUT. FreeCode5	Free code. Free Code 5 is maintained in RRCDM in reference type JF
BANCS.OUTPUT. FreeText1	Free text. Additional Information can be entered here
BANCS.OUTPUT. FreeText2	Free text. Additional Information can be entered here
BANCS.OUTPUT. FreeText3	Free text. Additional Information can be entered here
BANCS.OUTPUT. FreeText4	Free text. Additional Information can be entered here
BANCS.OUTPUT. FreeText5	Free text. Additional Information can be entered here
BANCS.OUTPUT. IntTranId	Transaction Id when the entry fails and needs suspense processing.
BANCS.OUTPUT. IntTranDate	Tran Date when the entry fails and needs suspense processing .
BANCS.OUTPUT. TxnStatus	Indicates the next status that the entry has to perform . C =Float-Customer,F =Customer-Float,O =Settlement-Float, S =Float-Settlement , X =Closed
BANCS.OUTPUT. SourceId	Source from where transaction is getting uploaded. For eg if it is created from HACHCOD it is populated as COD
BANCS.OUTPUT. SingleMultipleDRFlag	Denotes whether single or multiple transactions for a batch ,Values are S - Single and M - Multiple
BANCS.OUTPUT. LienorDebitFlag	Denotes the transaction is direct debit or Lien ,Values are D – Debit and L - lien. Default value is D
BANCS.OUTPUT. SystemId	Denotes the System if the account is Non Finacle account
BANCS.OUTPUT. OrigTranAcct	This field is the same as orig_acct. If Orig_acct is not a finacle account then it will populated as a internal office a/c , same will happen in case the entry is lodged from the other module
BANCS.OUTPUT. LienId	lien id for the A/c. This Lien placed on account as a result of this transaction. System Generated

BANCS.OUTPUT. BatchHdrSrlNum	Header srl num of the batch record in AHD
BANCS.OUTPUT. DAReferencenumber	Debit Authorization Reference Number. If the transaction is based on a debit authorization request then this refers to reference number of the same. Mapped to D BAT.da_ref_no
BANCS.OUTPUT. OrigSettlementDate	Originator settlement Date
BANCS.OUTPUT. AutoReturnFlag	Flag to indicate if auto return is enabled, Values are Y - Yes and N - No
BANCS.OUTPUT. RefundAcct	Refund account number for refund to other modules
BANCS.OUTPUT. CollectChrgFromAmtFlag	This flag indicates whether charges should be collected from the instructed amount or not. Values are Y - Yes and N - No
BANCS.OUTPUT. RateCode	The rate code used for conversion between PAYSYS base currency and account currency.
BANCS.OUTPUT. Rate	The exchange rate used for conversion between PAYSYS base currency and account currency.
BANCS.OUTPUT. EntityCreFlg	This indicates whether the record is verified or not. Values are Y -Yes and N - No.
BANCS.OUTPUT. RecvAcctDtIs	This field stores the receiver account number entered by the user.This will be populated during upload only
BANCS.OUTPUT. ChargeAcid	This field stores the Charge acid.
BANCS.OUTPUT. ChrgType	This field indicates the type of charge applicable to the instruction. For example: OUR, BEN, SHA etc.
BANCS.OUTPUT. ChrgEventId	Event Id of Charge Collection. Event Ids are defined and maintained in PTTM
BANCS.OUTPUT. ChrgRateCode	The rate code used for conversion between PAYSYS base currency and charge account currency.
BANCS.OUTPUT. ChrgRate	The exchange rate used for conversion between PAYSYS base currency and charge account currency.
BANCS.OUTPUT. OneShotFlg	This indicates whether the record should be sent in one shot or request mode. Values are Y - Yes and N - No.
BANCS.OUTPUT.	This indicates whether the processing in the other entity is

OtherEntityStatus	completed or not. Values are C - Completed, N - Not Completed and Null - For non Inter Entity cases
BANCS.OUTPUT. ChargeEventType	Event type of Charge Collection
BANCS.OUTPUT. UrgentFlg	This indicates whether the record should be processed instantly or later. Values are Y - Yes and N - No.
BANCS.OUTPUT. ReceiverBankId	This field will hold the bank id of the bank which has received this request in case of Inter Entity scenario. It will be null in case of initial outward message
BANCS.OUTPUT. SenderBankId	This field will hold the bank id of the bank which has sent this request in case of Inter Entity scenario. It will be null in case of initial outward message.
BANCS.OUTPUT. OrigAcctAddress1	Address line 1 of the originator
BANCS.OUTPUT. OrigAcctAddress2	Address line 2 of the originator
BANCS.OUTPUT. OrigAcctAddress3	Address line 3 of the originator
BANCS.OUTPUT. RespAcctAddress1	Address line 1 of the Respondant
BANCS.OUTPUT. RespAcctAddress2	Address line 2 of the Respondant
BANCS.OUTPUT. RespAcctAddress3	Address line 3 of the Respondant
BANCS.OUTPUT. WaiveChargeFlag	Flag to indicate waiver of charges, if set to Y no charges will be levied else charges will be calculated as per the setup
BANCS.OUTPUT. PurposeCode	Purpose Code.Code to indicate category purpose of credit transfer
BANCS.OUTPUT. OriginationCountry	Originator Country
BANCS.OUTPUT. RespondingCountry	Receiver Country
BANCS.OUTPUT. UltimateDebtorName	Name of the Originator Reference Party
BANCS.OUTPUT.	Address of the Originator Reference Party

UltimateDebtorAddress

**BANCS.OUTPUT.
UltimateDebtorCountry** Originator Reference Party Country

**BANCS.OUTPUT.
UltimateDebtorId** Originator Reference Party Id

**BANCS.OUTPUT.
UltimateCreditorName** Name of the Receiver Reference Party

**BANCS.OUTPUT.
UltimateCreditorAddress** Address of the Receiver Reference Party

**BANCS.OUTPUT.
UltimateCreditorCountry** Receiver Reference Party Country

**BANCS.OUTPUT.
UltimateCreditorId** Receiver Reference Party Id

**BANCS.OUTPUT.
EndToEndIdentification** End to End this reference is kept for the message

**BANCS.OUTPUT.
AutoRejectFlag** Flag to indicate if auto reject is enabled, Values are Y - Yes and N - No

**BANCS.OUTPUT.
Adviceld** Advice ID in case the this instruction is advised.

**BANCS.OUTPUT.
RecallDate** Date on which recall is done.

**BANCS.OUTPUT.
RecallInducedBy** Recall Induced indicator. Valid values are B - Bank, C - Customer.

**BANCS.OUTPUT.
RecallType** Type of recall. Valid values R-Record, F-File.

**BANCS.OUTPUT.
RecallChargeEventId** Charge event id for recall charges.

**BANCS.OUTPUT.
RecallChargeTranId** Transaction ID of charge collected for recall.

**BANCS.OUTPUT.
RecallChargeTranDate** Transaction Date on which charge collected for recall.

**BANCS.OUTPUT.
RecallTranId** Transaction ID for recall.

BANCS.OUTPUT. Transaction Date for recall.

RecallTranDate

**BANCS.OUTPUT.
RecallReasonCode**

Reason code for recall.

**BANCS.OUTPUT.
RecallRemarks**

Remarks for the recall.

**BANCS.OUTPUT.
RecallRequestId**

Request ID for the recall. For file recall it stores ACHFRR.srl_num.

**BANCS.OUTPUT.
SenderBic**

This is the bank identifier for the sender bank branch. This is generally referred to as Bank Identity code (BIC).

**BANCS.OUTPUT.
RecvBic**

This is the bank identifier for the receiver bank branch. This is generally referred to as Bank Identity code (BIC).

**BANCS.OUTPUT.
RejectTranId**

Transaction Id For rejected records.

**BANCS.OUTPUT.
RejectTranDate**

Rejection transaction date.

**BANCS.OUTPUT.
CompensationAmt**

Compensation Amount.

Default Logic:

This script must be present in **\$TBA_SCRIPTS** directory, If Implementation type in PAYSYS level is "BACS" then this script will be called.

Typical Usage Scenario:

This script is called when Implementation type in PAYSYS level is BACS.

Example:

©Copyright Infosys Ltd.

BACS ahbx0005 Update Status Fields



Script Name:

The script BACS_ahbx0005_updateStatusFields.scr present in TBA_SCRIPTS directory. This script will be used to update the status fields.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. ReturnFileName	Return file name. Used for storing the return file name from which the transaction was created.
BANCS.INPUT. ReturnDate	Date on which return file is sent.
BANCS.INPUT. OrigAcct	Originator Account ID
BANCS.INPUT. OrigTranAcct	Originator Account Acid.
BANCS.INPUT. OrigId	A Valid identifier for the originator of transaction. For example Organisational Code associated with the Account can be used as the orig ID
BANCS.INPUT. OrigInfo1	Additional information about originator.
BANCS.INPUT. OrigInfo2	Additional information about originator.
BANCS.INPUT. OrigName	Name of the originator.
BANCS.INPUT. SrvCode	Product of the originator or biller.
BANCS.INPUT. RecvAcid	Receiver Account acid.

BANCS.INPUT.RecvAcctDtls	Receiver Account Id.
BANCS.INPUT. RecvId	Identification of the receiver.
BANCS.INPUT. RecvInfo1	Additional information about receiver.
BANCS.INPUT. RecvInfo2	Additional information about receiver.
BANCS.INPUT. RecvName	Receiver name.
BANCS.INPUT. TranAmt	The amount for which the transaction is created.
BANCS.INPUT. TranCrncy	Transaction Currency.
BANCS.INPUT. CommisionAmt	Commission amount for the transaction.
BANCS.INPUT. TotalAmt	Total amount is transaction amount plus commission amount.
BANCS.INPUT. OutwardCommision	Outward commission amount.
BANCS.INPUT. RejectAmt	The amount which is rejected.
BANCS.INPUT. OtherAmt1	Additional amount Field.
BANCS.INPUT. OtherAmt2	Additional amount Field.
BANCS.INPUT. EffectiveDate	Value date of the transaction
BANCS.INPUT. SettlementDate	Settlement date of the transaction.
BANCS.INPUT. DueDate	Due date of the transaction
BANCS.INPUT. Date1	Additional Date Field.
BANCS.INPUT. Date2	Additional Date Field.
BANCS.INPUT. BankCode	Bank Code .
BANCS.INPUT. BranchCode	Branch Code.
BANCS.INPUT. SolId	Service Outlet Id of the Account
BANCS.INPUT. OrigCode	Originator Code. User Enterable
BANCS.INPUT. RejCode	Rejection Code.
BANCS.INPUT. RejDesc	Rejection Description -- reason for failure. Populated from ACH_PAYSYS_REASON_CODE_TABLE table for a given

rejection code

BANCS.INPUT. EntryStatus	Status of the record. P - Processed, R - Rejected, S - Suspended, U - Under Processing, G - Direct Recall, B - To be recalled, C - Recalled, J - Unmatched Recall
BANCS.INPUT. ReturnStatus	Return Status. Valid values are R - Ready to Send, S - Sent, N - Not to be sent.
BANCS.INPUT. FailProcess	Indicates Failure Processing is Automatic or Manual/Suspense Processing. A -Automatic, M -Manual
BANCS.INPUT. status2	Additional status field which can be used for customization purposes
BANCS.INPUT. ReturnInd	Values are S -Success, B -Both, F -Failure, N -None
BANCS.INPUT. CrDrInd	Credit Debit indicator. Valid values are C - Credit, D - Debit.
BANCS.INPUT. InwOutwInd	Inward Outward Indicator Valid values are I - Inward, O - Outward.
BANCS.INPUT. FreshRetEntry	Entry type. Valid values are 0 - Fresh entry, 1 - return entry, 2 - Reject entry, 3 - Recall entry.
BANCS.INPUT. TranCode	Transaction Code .
BANCS.INPUT. CustTranId	Transaction Id of Customer.
BANCS.INPUT. CustTranDate	Customer transaction date.
BANCS.INPUT. SettTranId	Transaction Id for the settlement transaction
BANCS.INPUT. SettTranDate	Settlement transaction date.
BANCS.INPUT. TraceNum1	Additional trace number.
BANCS.INPUT. TraceNum2	Additional trace number.
BANCS.INPUT. TraceNum3	Additional trace number.
BANCS.INPUT. ApprovedBy	Id of user who approves.
BANCS.INPUT. ApproverCmnt	Comments by approver.
BANCS.INPUT. FreeCode1	Free code. Free Code 1 is maintained in RRCDM in reference type JB
BANCS.INPUT. FreeCode2	Free code. Free Code 2 is maintained in RRCDM in

	reference type JC
BANCS.INPUT. FreeCode3	Free code. Free Code 3 is maintained in RRCDM in reference type JD
BANCS.INPUT. FreeCode4	Free code. Free Code 4 is maintained in RRCDM in reference type JE
BANCS.INPUT. FreeCode5	Free code. Free Code 5 is maintained in RRCDM in reference type JF
BANCS.INPUT. FreeText1	Free text. Additional Information can be entered here
BANCS.INPUT. FreeText2	Free text. Additional Information can be entered here
BANCS.INPUT. FreeText3	Free text. Additional Information can be entered here
BANCS.INPUT. FreeText4	Free text. Additional Information can be entered here
BANCS.INPUT. FreeText5	Free text. Additional Information can be entered here
BANCS.INPUT. TxnStatus	Indicates the next status that the entry has to perform . C =Float-Customer,F =Customer-Float,O =Settlement-Float, S =Float-Settlement , X =Closed
BANCS.INPUT. SourceId	Source from where transaction is getting uploaded. For eg if it is created from HACHCOD it is populated as COD
BANCS.INPUT. SingleMultipleDRFlag	Denotes whether single or multiple transactions for a batch ,Values are S - Single and M - Multiple
BANCS.INPUT. LienorDebitFlag	Denotes the transaction is direct debit or Lien ,Values are D – Debit and L - lien. Default value is D
BANCS.INPUT. OrigTranAcct	This field is the same as orig_acct. If Orig_acct is not a finacle account then it will populated as a internal office a/c , same will happen in case the entry is lodged from the other module
BANCS.INPUT. LienId	lien id for the A/c. This Lien placed on account as a result of this transaction. System Generated
BANCS.INPUT. BatchHdrSrlNum	Header srl num of the batch record in AHD
BANCS.INPUT. DAreferencenumber	Debit Authorization Reference Number. If the transaction is based on a debit authorization request then this refers to reference number of the same. Mapped to D BAT.da_ref_no
BANCS.INPUT. OrigSettlementDate	Originator settlement Date

BANCS.INPUT. AutoReturnFlag	Flag to indicate if auto return is enabled, Values are Y - Yes and N - No
BANCS.INPUT. RefundAcct	Refund account number for refund to other modules
BANCS.INPUT. CollectChrgFromAmtFlag	This flag indicates whether charges should be collected from the instructed amount or not. Values are Y - Yes and N - No
BANCS.INPUT. RateCode	The rate code used for conversion between PAYSYS base currency and account currency.
BANCS.INPUT. Rate	The exchange rate used for conversion between PAYSYS base currency and account currency.
BANCS.INPUT. EntityCreFlg	This indicates whether the record is verified or not. Values are Y -Yes and N - No.
BANCS.INPUT. RecvAcctDtIs	This field stores the receiver account number entered by the user.This will be populated during upload only
BANCS.INPUT. ChargeAcid	This field stores the Charge acid.
BANCS.INPUT. ChrgType	This field indicates the type of charge applicable to the instruction. For example: OUR, BEN, SHA etc.
BANCS.INPUT. ChrgEventId	Event Id of Charge Collection. Event Ids are defined and maintained in PTTM
BANCS.INPUT. ChrgRateCode	The rate code used for conversion between PAYSYS base currency and charge account currency.
BANCS.INPUT. ChrgRate	The exchange rate used for conversion between PAYSYS base currency and charge account currency.
BANCS.INPUT. OneShotFlg	This indicates whether the record should be sent in one shot or request mode. Values are Y - Yes and N - No.
BANCS.INPUT. OtherEntityStatus	This indicates whether the processing in the other entity is completed or not. Values are C - Completed, N - Not Completed and Null - For non Inter Entity cases
BANCS.INPUT. ChargeEventType	Event type of Charge Collection
BANCS.INPUT. UrgentFlg	This indicates whether the record should be processed instantly or later. Values are Y - Yes and N - No.
BANCS.INPUT. ReceiverBankId	This field will hold the bank id of the bank which has received this request in case of Inter Entity scenario. It will be null in case of intial outward message
BANCS.INPUT.	This field will hold the bank id of the bank which has sent this

SenderBankId	request in case of Inter Entity scenario. It will be null in case of initial outward message.
BANCS.INPUT. OrigAcctAddress1	Address line 1 of the originator
BANCS.INPUT. OrigAcctAddress2	Address line 2 of the originator
BANCS.INPUT. OrigAcctAddress3	Address line 3 of the originator
BANCS.INPUT. RespAcctAddress1	Address line 1 of the Respondant
BANCS.INPUT. RespAcctAddress2	Address line 2 of the Respondant
BANCS.INPUT. RespAcctAddress3	Address line 3 of the Respondant
BANCS.INPUT. WaiveChargeFlag	Flag to indicate waiver of charges, if set to Y no charges will be levied else charges will be calculated as per the setup
BANCS.INPUT. PurposeCode	Purpose Code.Code to indicate category purpose of credit transfer
BANCS.INPUT. OriginationCountry	Originator Country
BANCS.INPUT. RespondingCountry	Receiver Country
BANCS.INPUT. UltimateDebtorName	Name of the Originator Reference Party
BANCS.INPUT. UltimateDebtorAddress	Address of the Originator Reference Party
BANCS.INPUT. UltimateDebtorCountry	Originator Reference Party Country
BANCS.INPUT. UltimateDebtorId	Originator Reference Party Id
BANCS.INPUT. UltimateCreditorName	Name of the Receiver Reference Party
BANCS.INPUT. UltimateCreditorAddress	Address of the Receiver Reference Party

BANCS.INPUT. UltimateCreditorCountry	Receiver Reference Party Country
BANCS.INPUT. UltimateCreditorId	Receiver Reference Party Id
BANCS.INPUT. EndToEndIdentification	End to End this reference is kept for the message
BANCS.INPUT. AutoRejectFlag	Flag to indicate if auto reject is enabled, Values are Y - Yes and N - No
BANCS.INPUT. AdviceId	Advice ID in case the this instruction is advised.
BANCS.INPUT. RecallDate	Date on which recall is done.
BANCS.INPUT. RecallInducedBy	Recall Induced indicator. Valid values are B - Bank, C - Customer.
BANCS.INPUT. RecallType	Type of recall.Valid values R-Record, F-File.
BANCS.INPUT. RecallChargeEventId	Charge event id for recall charges.
BANCS.INPUT. RecallChargeTranId	Transaction ID of charge collected for recall.
BANCS.INPUT. RecallChargeTranDate	Transaction Date on which charge collected for recall.
BANCS.INPUT. RecallTranId	Transaction ID for recall.
BANCS.INPUT. RecallTranDate	Transaction Date for recall.
BANCS.INPUT. SenderBic	This is the bank identifier for the sender bank branch. This is generally referred to as Bank Identity code (BIC).
BANCS.INPUT. RecvBic	This is the bank identifier for the receiver bank branch. This is generally referred to as Bank Identity code (BIC).
BANCS.INPUT. CompensationAmt	Compensation Amount.
BANCS.INPUT. SelfId1	Select field
BANCS.INPUT. CSMInwRetFlg	CSM Inward Return Flag
BANCS.INPUT. CSMInwRejFlg	CSM Inward Reject Flag

BANCS.INPUT. IDPOutwCrFlg	IDP Outward Credit Flag
BANCS.INPUT. IDPInwRetFlg	IDP Inward Return Flag
BANCS.INPUT. IDPInwRejFlg	IDP Inward Reject Flag
BANCS.INPUT. IDPOutwDrFlg	IDP Outward Debit Flag
BANCS.INPUT. IDPOutwRecCrFlg	IDP Outward Record Credit Flag
BANCS.INPUT. IDPOutwRecDrFlg	IDP Outward Record Debit Flag
BANCS.INPUT. custInwRejFlg	Customer Inward Reject Flag
BANCS.INPUT. CSMOutwRecCrFlg	CSM Outward Record Credit Flag
BANCS.INPUT. CSMOutwRecDrFlg	CSM Outward Record Debit Flag
BANCS.INPUT. CSMOutwCrFlg	CSM Outward Credit Flag
BANCS.INPUT. CSMOutwDrFlg	CSM Outward Debit Flag
BANCS.INPUT. CSMInwCrRetFlg	CSM Inward Credit Return Flag
BANCS.INPUT. CSMInwDrRetFlg	CSM Inward Debit Return Flag
BANCS.INPUT. CSMInwRetCount	CSM Inward Return Count
BANCS.INPUT. CSMInwRejCount	CSM Inward Reject Count
BANCS.INPUT. IDPOutwCrCount	IDP Outward Credit Count
BANCS.INPUT. IDPInwRetCount	IDP Inward Return Count

BANCS.INPUT. IDPInwRejCount	IDP Inward Reject Count
BANCS.INPUT. IDPOutwDrCount	IDP outward Debit Count
BANCS.INPUT. IDPOutwRecCrCount	IDP Outward Record Credit Count
BANCS.INPUT. IDPOutwRecDrCount	IDP Outward Record Debit Count
BANCS.INPUT. custInwRejCount	Customer Inward Reject Count
BANCS.INPUT. CSMOutwRecCrCount	CSM Outward Record Credit Count
BANCS.INPUT. CSMOutwRecDrCount	CSM Outward Record Debit Count
BANCS.INPUT. CSMOutwCrCount	CSM Outward Credit Count
BANCS.INPUT. CSMOutwDrCount	CSM Outward Debit Count
BANCS.INPUT. CSMInwRetTotAmt	CSM Inward Return Total Amount
BANCS.INPUT. CSMInwRejTotAmt	CSM Inward Reject Total Amount
BANCS.INPUT. IDPOutwCrTotAmt	IDP Outward Credit Total Amount
BANCS.INPUT. IDPInwRetTotAmt	IDP inward Return total Amount
BANCS.INPUT. IDPInwRejTotAmt	IDP Inward Reject Toatal Amount
BANCS.INPUT. IDPOutwDrTotAmt	IDP Outward Debit Total Amount
BANCS.INPUT. IDPOutwRecCrTotAmt	IDP Outward Record Credit Total Amount
BANCS.INPUT. IDPOutwRecDrTotAmt	IDP Outward Record Debit Total Amount

BANCS.INPUT. custInwRejTotAmt	Customer Inward Reject Total Amount
BANCS.INPUT. CSMOutwRecCrTotAmt	CSM Outward Record Credit Total Amount
BANCS.INPUT. CSMOutwRecDrTotAmt	CSM Outward Record Debit Total Amount
BANCS.INPUT. CSMOutwCrTotAmt	CSM Outward Credit Total Amount
BANCS.INPUT. CSMOutwDrTotAmt	CSM Outward Debit Total Amount
BANCS.INPUT. fileType	File Type
BANCS.INPUT. FinFileFormat	Financial File Format
BANCS.INPUT. FileDestination	File Destination

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. ReturnFileName	Return file name. Used for storing the return file name from which the transaction was created.
BANCS. OUTPUT. ReturnDate	Date on which return file is sent.
BANCS. OUTPUT. OrigAcct	Originator Account ID
BANCS. OUTPUT. OrigTranAcct	Originator Account Acid.
BANCS. OUTPUT. OrigId	A Valid identifier for the originator of transaction. For example Organisational Code associated with the Account can be used as the orig ID
BANCS. OUTPUT.	Additional information about originator.

OrigInfo1

**BANCS. OUTPUT.
OrigInfo2** Additional information about originator.

**BANCS. OUTPUT.
OrigName** Name of the originator.

**BANCS. OUTPUT.
SrvCode** Product of the originator or biller.

**BANCS. OUTPUT.
RecvAcid** Receiver Account acid.

**BANCS.
OUTPUT.RecvAcctDtIs** Receiver Account Id.

BANCS. OUTPUT. RecvId Identification of the receiver.

**BANCS. OUTPUT.
RecvInfo1** Additional information about receiver.

**BANCS. OUTPUT.
RecvInfo2** Additional information about receiver.

**BANCS. OUTPUT.
RecvName** Receiver name.

**BANCS. OUTPUT.
TranAmt** The amount for which the transaction is created.

**BANCS. OUTPUT.
TranCrncy** Transaction Currency.

**BANCS. OUTPUT.
CommisionAmt** Commission amount for the transaction.

**BANCS. OUTPUT.
TotalAmt** Total amount is transaction amount plus commission amount.

**BANCS. OUTPUT.
OutwardCommision** Outward commission amount.

**BANCS. OUTPUT.
RejectAmt** The amount which is rejected.

**BANCS. OUTPUT.
OtherAmt1** Additional amount Field.

**BANCS. OUTPUT.
OtherAmt2** Additional amount Field.

BANCS. OUTPUT. EffectiveDate	Value date of the transaction
BANCS. OUTPUT. SettlementDate	Settlement date of the transaction.
BANCS. OUTPUT. DueDate	Due date of the transaction
BANCS. OUTPUT. Date1	Additional Date Field.
BANCS. OUTPUT. Date2	Additional Date Field.
BANCS. OUTPUT. BankCode	Bank Code .
BANCS. OUTPUT. BranchCode	Branch Code.
BANCS. OUTPUT. SolId	Service Outlet Id of the Account
BANCS. OUTPUT. OrigCode	Originator Code. User Enterable
BANCS. OUTPUT. RejCode	Rejection Code.
BANCS. OUTPUT. RejDesc	Rejection Description -- reason for failure. Populated from ACH_PAYSYS_REASON_CODE_TABLE table for a given rejection code
BANCS. OUTPUT. EntryStatus	Status of the record. P - Processed, R - Rejected, S - Suspended, U - Under Processing,G - Direct Recall, B - To be recalled, C - Recalled , J - Unmatched Recall
BANCS. OUTPUT. ReturnStatus	Return Status. Valid values are R - Ready to Send, S - Sent , N – Not to be sent.
BANCS. OUTPUT. FailProcess	Indicates Failure Processing is Automatic or Manual/Suspense Processing. A -Automatic, M -Manual
BANCS. OUTPUT. status2	Additional status field which can be used for customization purposes
BANCS. OUTPUT. ReturnInd	Values are S -Success,B -Both,F -Failure, N -None
BANCS. OUTPUT. CrDrInd	Credit Debit indicator. Valid values are C - Credit, D - Debit.
BANCS. OUTPUT.	Inward Outward Indicator Valid values are I - Inward, O -

InwOutwInd	Outward.
BANCS. OUTPUT. FreshRetEntry	Entry type. Valid values are 0 - Fresh entry, 1 - return entry, 2 - Reject entry, 3 - Recall entry.
BANCS. OUTPUT. TranCode	Transaction Code .
BANCS. OUTPUT. CustTranId	Transaction Id of Customer.
BANCS. OUTPUT. CustTranDate	Customer transaction date.
BANCS. OUTPUT. SettTranId	Transaction Id for the settlement transaction
BANCS. OUTPUT. SettTranDate	Settlement transaction date.
BANCS. OUTPUT. TraceNum1	Additional trace number.
BANCS. OUTPUT. TraceNum2	Additional trace number.
BANCS. OUTPUT. TraceNum3	Additional trace number.
BANCS. OUTPUT. ApprovedBy	Id of user who approves.
BANCS. OUTPUT. ApproverCmnt	Comments by approver.
BANCS. OUTPUT. FreeCode1	Free code. Free Code 1 is maintained in RRCDM in reference type JB
BANCS. OUTPUT. FreeCode2	Free code. Free Code 2 is maintained in RRCDM in reference type JC
BANCS. OUTPUT. FreeCode3	Free code. Free Code 3 is maintained in RRCDM in reference type JD
BANCS. OUTPUT. FreeCode4	Free code. Free Code 4 is maintained in RRCDM in reference type JE
BANCS. OUTPUT. FreeCode5	Free code. Free Code 5 is maintained in RRCDM in reference type JF
BANCS. OUTPUT.	

FreeText1	Free text. Additional Information can be entered here
BANCS. OUTPUT. FreeText2	Free text. Additional Information can be entered here
BANCS. OUTPUT. FreeText3	Free text. Additional Information can be entered here
BANCS. OUTPUT. FreeText4	Free text. Additional Information can be entered here
BANCS. OUTPUT. FreeText5	Free text. Additional Information can be entered here
BANCS. OUTPUT. TxnStatus	Indicates the next status that the entry has to perform . C =Float-Customer,F =Customer-Float,O =Settlement-Float, S =Float-Settlement , X =Closed
BANCS. OUTPUT. SourceId	Source from where transaction is getting uploaded. For eg if it is created from HACHCOD it is populated as COD
BANCS. OUTPUT. SingleMultipleDRFlag	Denotes whether single or multiple transactions for a batch ,Values are S - Single and M - Multiple
BANCS. OUTPUT. LienorDebitFlag	Denotes the transaction is direct debit or Lien ,Values are D – Debit and L - lien. Default value is D
BANCS. OUTPUT. OrigTranAcct	This field is the same as orig_acct. If Orig_acct is not a finacle account then it will populated as a internal office a/c , same will happen in case the entry is lodged from the other module
BANCS. OUTPUT. LienId	lien id for the A/c. This Lien placed on account as a result of this transaction. System Generated
BANCS. OUTPUT. BatchHdrSrlNum	Header srl num of the batch record in AHD
BANCS. OUTPUT. DAReferencenumber	Debit Authorization Reference Number. If the transaction is based on a debit authorization request then this refers to reference number of the same. Mapped to D BAT.da_ref_no
BANCS. OUTPUT. OrigSettlementDate	Originator settlement Date
BANCS. OUTPUT. AutoReturnFlag	Flag to indicate if auto return is enabled, Values are Y - Yes and N - No
BANCS. OUTPUT.	Refund account number for refund to other modules

RefundAcct

BANCS. OUTPUT. CollectChrgFromAmtFlag	This flag indicates whether charges should be collected from the instructed amount or not. Values are Y - Yes and N - No
BANCS. OUTPUT. RateCode	The rate code used for conversion between PAYSYS base currency and account currency.
BANCS. OUTPUT. Rate	The exchange rate used for conversion between PAYSYS base currency and account currency.
BANCS. OUTPUT. EntityCreFlg	This indicates whether the record is verified or not. Values are Y -Yes and N - No.
BANCS. OUTPUT. RecvAcctDtIs	This field stores the receiver account number entered by the user.This will be populated during upload only
BANCS. OUTPUT. ChargeAcid	This field stores the Charge acid.
BANCS. OUTPUT. ChrgType	This field indicates the type of charge applicable to the instruction. For example: OUR, BEN, SHA etc.
BANCS. OUTPUT. ChrgEventId	Event Id of Charge Collection. Event Ids are defined and maintained in PTTM
BANCS. OUTPUT. ChrgRateCode	The rate code used for conversion between PAYSYS base currency and charge account currency.
BANCS. OUTPUT. ChrgRate	The exchange rate used for conversion between PAYSYS base currency and charge account currency.
BANCS. OUTPUT. OneShotFlg	This indicates whether the record should be sent in one shot or request mode. Values are Y - Yes and N - No.
BANCS. OUTPUT. OtherEntityStatus	This indicates whether the processing in the other entity is completed or not. Values are C - Completed, N - Not Completed and Null - For non Inter Entity cases
BANCS. OUTPUT. ChargeEventType	Event type of Charge Collection
BANCS. OUTPUT. UrgentFlg	This indicates whether the record should be processed instantly or later. Values are Y - Yes and N - No.
BANCS. OUTPUT. ReceiverBankId	This field will hold the bank id of the bank which has received this request in case of Inter Entity scenario. It will be null in case of intial outward message
BANCS. OUTPUT. SenderBankId	This field will hold the bank id of the bank which has sent this request in case of Inter Entity scenario. It will be null in case of

initial outward message.

**BANCS. OUTPUT.
OrigAcctAddress1**

Address line 1 of the originator

**BANCS. OUTPUT.
OrigAcctAddress2**

Address line 2 of the originator

**BANCS. OUTPUT.
OrigAcctAddress3**

Address line 3 of the originator

**BANCS. OUTPUT.
RespAcctAddress1**

Address line 1 of the Respondant

**BANCS. OUTPUT.
RespAcctAddress2**

Address line 2 of the Respondant

**BANCS. OUTPUT.
RespAcctAddress3**

Address line 3 of the Respondant

**BANCS. OUTPUT.
WaiveChargeFlag**

Flag to indicate waiver of charges, if set to Y no charges will be levied else charges will be calculated as per the setup

**BANCS. OUTPUT.
PurposeCode**

Purpose Code.Code to indicate category purpose of credit transfer

**BANCS. OUTPUT.
OriginationCountry**

Originator Country

**BANCS. OUTPUT.
RespondingCountry**

Receiver Country

**BANCS. OUTPUT.
UltimateDebtorName**

Name of the Originator Reference Party

**BANCS. OUTPUT.
UltimateDebtorAddress**

Address of the Originator Reference Party

**BANCS. OUTPUT.
UltimateDebtorCountry**

Originator Reference Party Country

**BANCS. OUTPUT.
UltimateDebtorIdBANCS.
OUTPUT.
UltimateDebtorId**

Originator Reference Party Id

**BANCS. OUTPUT.
UltimateCreditorName**

Name of the Receiver Reference Party

**BANCS. OUTPUT.
UltimateCreditorAddress**

Address of the Receiver Reference Party

BANCS. OUTPUT. UltimateCreditorCountry	Receiver Reference Party Country
BANCS. OUTPUT. UltimateCreditorId	Receiver Reference Party Id
BANCS. OUTPUT. EndToEndIdentification	End to End this reference is kept for the message
BANCS. OUTPUT. AutoRejectFlag	Flag to indicate if auto reject is enabled, Values are Y - Yes and N - No
BANCS. OUTPUT. Adviceld	Advice ID in case the this instruction is advised.
BANCS. OUTPUT. RecallDate	Date on which recall is done.
BANCS. OUTPUT. RecallInducedBy	Recall Induced indicator. Valid values are B - Bank, C - Customer.
BANCS. OUTPUT. RecallType	Type of recall.Valid values R-Record, F-File.
BANCS. OUTPUT. RecallChargeEventId	Charge event id for recall charges.
BANCS. OUTPUT. RecallChargeTranId	Transaction ID of charge collected for recall.
BANCS. OUTPUT. RecallChargeTranDate	Transaction Date on which charge collected for recall.
BANCS. OUTPUT. RecallTranId	Transaction ID for recall.
BANCS. OUTPUT. RecallTranDate	Transaction Date for recall.
BANCS. OUTPUT. SenderBic	This is the bank identifier for the sender bank branch. This is generally referred to as Bank Identity code (BIC).
BANCS. OUTPUT. RecvBic	This is the bank identifier for the receiver bank branch. This is generally referred to as Bank Identity code (BIC).
BANCS. OUTPUT. CompensationAmt	Compensation Amount.
BANCS. OUTPUT. SelFld1	Select field

BANCS. OUTPUT. CSMInwRetFlg	CSM Inward Return Flag
BANCS. OUTPUT. CSMInwRejFlg	CSM Inward Reject Flag
BANCS. OUTPUT. IDPOutwCrFlg	IDP Outward Credit Flag
BANCS. OUTPUT. IDPInwRetFlg	IDP Inward Return Flag
BANCS. OUTPUT. IDPInwRejFlg	IDP Inward Reject Flag
BANCS. OUTPUT. IDPOutwDrFlg	IDP Outward Debit Flag
BANCS. OUTPUT. IDPOutwRecCrFlg	IDP Outward Record Credit Flag
BANCS. OUTPUT. IDPOutwRecDrFlg	IDP Outward Record Debit Flag
BANCS. OUTPUT. custInwRejFlg	Customer Inward Reject Flag
BANCS. OUTPUT. CSMOutwRecCrFlg	CSM Outward Record Credit Flag
BANCS. OUTPUT. CSMOutwRecDrFlg	CSM Outward Record Debit Flag
BANCS. OUTPUT. CSMOutwCrFlg	CSM Outward Credit Flag
BANCS. OUTPUT. CSMOutwDrFlg	CSM Outward Debit Flag
BANCS. OUTPUT. CSMInwCrRetFlg	CSM Inward Credit Return Flag
BANCS. OUTPUT. CSMInwDrRetFlg	CSM Inward Debit Return Flag
BANCS. OUTPUT. CSMInwRetCount	CSM Inward Return Count
BANCS. OUTPUT. CSMInwRejCount	CSM Inward Reject Count

BANCS. OUTPUT. IDPOutwCrCount	IDP Outward Credit Count
BANCS. OUTPUT. IDPInwRetCount	IDP Inward Return Count
BANCS. OUTPUT. IDPInwRejCount	IDP Inward Reject Count
BANCS. OUTPUT. IDPOutwDrCount	IDP outward Debit Count
BANCS. OUTPUT. IDPOutwRecCrCount	IDP Outward Record Credit Count
BANCS. OUTPUT. IDPOutwRecDrCount	IDP Outward Record Debit Count
BANCS. OUTPUT. custInwRejCount	Customer Inward Reject Count
BANCS. OUTPUT. CSMOutwRecCrCount	CSM Outward Record Credit Count
BANCS. OUTPUT. CSMOutwRecDrCount	CSM Outward Record Debit Count
BANCS. OUTPUT. CSMOutwCrCount	CSM Outward Credit Count
BANCS. OUTPUT. CSMOutwDrCount	CSM Outward Debit Count
BANCS. OUTPUT. CSMInwRetTotAmt	CSM Inward Return Total Amount
BANCS. OUTPUT. CSMInwRejTotAmt	CSM Inward Reject Total Amount
BANCS. OUTPUT. IDPOutwCrTotAmt	IDP Outward Credit Total Amount
BANCS. OUTPUT. IDPInwRetTotAmt	IDP inward Return total Amount
BANCS. OUTPUT. IDPInwRejTotAmt	IDP Inward Reject Toatal Amount
BANCS. OUTPUT. IDPOutwDrTotAmt	IDP Outward Debit Total Amount

BANCS. OUTPUT.
IDPOutwRecCrTotAmt IDP Outward Record Credit Total Amount

BANCS. OUTPUT.
IDPOutwRecDrTotAmt IDP Outward Record Debit Total Amount

BANCS. OUTPUT.
custInwRejTotAmt Customer Inward Reject Total Amount

BANCS. OUTPUT.
CSMOutwRecCrTotAmt CSM Outward Record Credit Total Amount

BANCS. OUTPUT.
CSMOutwRecDrTotAmt CSM Outward Record Debit Total Amount

BANCS. OUTPUT.
CSMOutwCrTotAmt CSM Outward Credit Total Amount

BANCS. OUTPUT.
CSMOutwDrTotAmt CSM Outward Debit Total Amount

BANCS. OUTPUT.
fileType File Type

BANCS. OUTPUT.
FinFileFormat Financial File Format

BANCS. OUTPUT.
FileDestination File Destination

BANCS. OUTPUT.
successOrFailure Success Failure field value

BANCS. OUTPUT.
errormesg Error Message

BANCS. OUTPUT.
RejectTranId Reject Tran Id

BANCS. OUTPUT.
RejectTranDate Reject Tran Date

BANCS. OUTPUT.
CompensationAmt Compensation Amount

BANCS. OUTPUT.
IntTranId Intermediate Tran Id

BANCS. OUTPUT.
IntTranDate Intermediate Tran date

Typical Usage Scenario:

This script is called when Implementation type in PAYSYS level is BACS. This script will be used to update the status fields.

Example:

NA

©Copyright Infosys Ltd.

BACS Check Authorization Required For CP



Script Name:

The script `BACS_checkAuthorizationRequiredforCP.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to check Authorization required for CP.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. IsAuthReqdFlg	Authorization Required Flag
BANCS.INPUT. OrigAcct	Originator Account
BANCS.INPUT. RecvAcctDtls	Receiver Account
BANCS.INPUT. SenderBic	Sender Bic
BANCS.INPUT. RecvBic	Receiver Bic

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. IsAuthReqdFlg	Authorization required Flag.

Typical Usage Scenario:

This script is called when Implement Type in PAYSYS Level is “BACS”. This script will be used to check authorization required for Customer Processing.

Example:

NA

©Copyright Infosys Ltd.

BACS Get Processing Date Script



Script Name:

The script `BACS_getProcessingDate.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to get the processing date in Julian Format.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT.settlementDate	Settlement date of the Record.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT.processingDate	Processing Date of the Every Record.

Typical Usage Scenario:

This script is called to convert the settlement date of every record to Processing date in Julian Format.

Example:

NA

©Copyright Infosys Ltd.

Finacle Copyright

BACS Get Settlement Account For Contra Handling

Script Name:

The script `BACS_getSettAcctForContra.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to get the settlement account for Contra Handling

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. Paysys_Id	Paysys ID of ACH Payment System.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT. contraDrAcct	Contra Debit Account.
BANCS.OUTPUT. contraCrAcct	Contra Credit Account.

Typical Usage Scenario:

This script is called when Contra Handling is done for BACS record. Final Settlement account will be derived for Contra Handling records based on the Paysys ID.

Example:

NA

©Copyright Infosys Ltd.

BACS Multi File Type Upload Script



Script Name:

The script `BACS_multiFileTypeUpload.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to get the XML Conversion required flag and also to get Upload Config file when user does not enter in the frontend.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. PaysysId	Paysys ID of ACH Payment System.
BANCS.INPUT. InputFileName	Input File name
BANCS.INPUT. configfilename	Upload Config File Name

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT. successOrFailure	Success or Failure

BANCS.OUTPUT. configfilename	Upload Config File Name
BANCS.OUTPUT. fileType	File Type(whether it is XML or FLAT)
BANCS.OUTPUT. IsAuthReqdFlg	Authorization required Flag.

Typical Usage Scenario:

This script is called to get the XML Conversion required flag and also to get Upload Config file when user does not enter in the frontend.

Example:

NA

©Copyright Infosys Ltd.

BACS Check ACH Holiday For TD-SI Script



Script Name:

The script BACS_checkAchHolidayForTDSI.scr must be present in \$TBA_SCRIPTS directory. This script will be used to get the settlement date by checking ACH Holiday for TD-SI changes. If derived settlement date is holiday, then next ACH working date will be derived.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.EffectiveDate	Effective Date (Processing Date).
BANCS.INPUT.PaysysId	Paysys Id of the ACH Payment System
BANCS.INPUT.LeadDays	Lead Days from HPAYSYS level

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

--	--

Field Name	Details
BANCS.OUTPUT. SettlementDate	Success or Failure

Typical Usage Scenario:

This script is called when implement type in HPAYSY level is “BACS”. When this script is not present in TBA_SCRIPTS directory, then it will be by passed.

Example:

NA

©Copyright Infosys Ltd.

Update AED Custom fields for PO Creation during Interest Calculation



Script Name:

The script INT_UpdateAEDCustomFields.scr must be present in TBA_SCRIPTS directory. This script will be used to update custom fields of AED table for Payment Order Creation during Interest Calculation

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. FreeCode1	Free Code 1
BANCS.INPUT. FreeCode2	Free Code 2
BANCS.INPUT. FreeCode3	Free Code 3
BANCS.INPUT. FreeCode4	Free Code 4
BANCS.INPUT. FreeCode5	Free Code 5
BANCS.INPUT. FreeText1	FreeText1
BANCS.INPUT. FreeText2	FreeText 2

**BANCS.INPUT.
FreeText3** FreeText 3

**BANCS.INPUT.
FreeText4** FreeText 4

**BANCS.INPUT.
FreeText5** FreeText 5

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS. OUTPUT. FreeCode1	Free Code 1
BANCS. OUTPUT. FreeCode2	Free Code 2
BANCS. OUTPUT. FreeCode3	Free Code 3
BANCS. OUTPUT. FreeCode4	Free Code 4
BANCS. OUTPUT. FreeCode5	Free Code 5
BANCS. OUTPUT. FreeText1	FreeText1
BANCS. OUTPUT FreeText2	FreeText 2
BANCS. OUTPUT. FreeText3	FreeText 3
BANCS. OUTPUT. FreeText4	FreeText 4
BANCS. OUTPUT. FreeText5	FreeText 5

Typical Usage Scenario:

This script will be used to update custom fields like Free code and free text fields in AED for Payment Order Creation during Interest Calculation.

Example:

NA

©Copyright Infosys Ltd.

BACS GenMultiOutFile Script



Script Name:

The script BACS_GenMultiOutFile.scr must be present in TBA_SCRIPTS directory. This script will be used to generate Mutli Out File.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.PaysysId	Paysys Id of ACH Payment System
BANCS.INPUT.toFileName	File Name
BANCS.INPUT.CSMOutwAdvAMENDFlg	CSM Outward Advice Amend Flag
BANCS.INPUT. CSMOutwAdvCNCLFlg	CSM Outward Advice Cancel Flag
BANCS.INPUT. CSMOutwAdvREINSFlg	CSM Outward Advice Reins Flag
BANCS.INPUT. CSMOutwAdvWAADVFlg	CSM Outward Advice WAADV Flag
BANCS.INPUT. CSMOutwAdvADDFlg	CSM Outward Advice Add Flag
BANCS.INPUT. pymtFlag1	Payment Flag1
BANCS.INPUT. CSMOutwAdvTRNSFFlg	CSM Outward Advice Transfer Flag
BANCS.INPUT. CSMOutwAdvTRMSGFlg	CSM Outward Advice Transfer Message Flag
BANCS.INPUT. pymtFlag2	Payment Flag2

BANCS.INPUT. succLstFile Success LST File

BANCS.INPUT. reposFile Repos File

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. successOrFailure	Success Or Failure Field value
BANCS.OUTPUT. errorMesg	Error Message Field value

Typical Usage Scenario:

This script is called when Implementation Type at PAYSYS Level is “BACS”

Example:

NA

©Copyright Infosys Ltd.

Map Mandate Data To PORDM



Script Name:

The script `MAN_MapMandatePORDM.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to map mandate data to PORDM structure.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT.deptNum	Department Number

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT.deptNum	Department Number.

Typical Usage Scenario:

This script is called when during mandate execution for Gross Type of payment system and populates department number required for PO creation from freeCode3 data in MMDMT table.

Example:

NA

©Copyright Infosys Ltd.

Finacle Copyright

BACS Check Ach Holiday For PO



Script Name:

The script BACS_checkAchHolidayForPO.scr must be present in TBA_SCRIPTS directory. This script is used to derive settlement date based on lead days and to check derive the next working date if it is a holiday.

Input:

The defined input is available in a repository called PAYSYS, in a class called PORD with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

PAYSYS.PORD.<fieldName>

Field Name	Details
PAYSYS.PORD. crExecutionDate	Indicates the credit execution date as entered by the user.
PAYSYS.PORD. paysysId	Identifies the paysysId.
PAYSYS.PORD. leadDays	Identifies the lead days set at paysys level.

Output:

The output of the script will be available in the specified repository fields:

PAYSYS.PORD.<fieldName>

Field Name	Details
PAYSYS.PORD. crExecutionDate	Indicates the modified credit execution date.

PAYSYS.PORD.
errorDesc

Indicates the error desc if any.

Typical Usage Scenario:

This script is called when Implement Type in PAYSYS Level is "BACS". This script will be used to check authorization required for Customer Processing.

Example:

NA

©Copyright Infosys Ltd.

SEPA-form Query For HGARFG/HGARFR

Script Name:

The script SEPA_ahbx0005_formQuery.scr must be present in \$TBA_SCRIPTS directory. This script will be used to form the query for HGARFG/HGARFR menus.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
BANCS.INPUT.BatchName	Batch name
BANCS.INPUT.FlgValue	Flag value(HGARFG – 'G')
BANCS.INPUT.PaysysId	Paysys Id
BANCS.INPUT.fileType	File Type(Financial – 'F' or Non-financial – 'N')
BANCS.INPUT.InputFileName	Input file name
BANCS.INPUT.Date	Return date
BANCS.INPUT.BODDate	BOD Date
BANCS.INPUT.FreeText1	Free text
BANCS.INPUT.SolId	SOL ID
BANCS.INPUT.ServiceSolId	Service Sol Id
BANCS.INPUT.InwOutwInd	Inward Outward Indicator
BANCS.INPUT.FileDestination	File destination(CSM – 'M ' or IDP – 'I ' or Customer – 'C')

BANCS.INPUT.FinFileFormat Financial file format(Unified – ‘U’ or Multiple – ‘M’)

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Script Input	Description
BANCS.OUTPUT.MainQry	The form query for HGARFG/HGARFR
BANCS.OUTPUT.successOrFailure	Success or Failure Indicator
BANCS.OUTPUT.errormesg	Error Message.

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is “SEPA”. This script will be used to form the query for HGARFG/HGARFR menus.

Example:

NA

©Copyright Infosys Ltd.

SEPA-Generate Multi Out File For HGARFG



Script Name:

The script SEPA_GenMultiOutFile.scr must be present in \$TBA_SCRIPTS directory. This script will be used to create Report for HGARFG when financial_file_format is Multiple for SEPA.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
BANCS.INPUT. <Mrt names>	MRT names (CSMIDPOutwCrMrt, CSMIDPOutwDrMrt, CSMIDPInwRetMrt, CSMIDPInwRejMrt, CSMIDPOutwRecCrMrt, CSMIDPOutwRecDrMrt, custInwRejMrt)
BANCS.INPUT. <Config file names>	Config file names (CSMIDPOutwCrCnfgFile, CSMIDPOutwDrCnfgFile, CSMIDPInwRetCnfgFile, CSMIDPInwRejCnfgFile, CSMIDPOutwRecCrCnfgFile, CSMIDPOutwRecDrCnfgFile, custInwRejCnfgFile)
BANCS.INPUT. <Flags>	Flags set in SEPA_updateStatusFields.sscr (CSMOUTWCRFLG, CSMOUTWDRFLG, CSMINWRETF LG, CSMINWREJFLG, CSMOUTWRECCRFLG, CSMOUTWRECDRFLG, IDPOUTWCRFLG, IDPOUTWDRFLG, IDPINWRETF LG, IDPINWREJFLG, IDPOUTWRECCRFLG, IDPOUTWRECDRFLG, CUSTINWREJFLG)
BANCS.INPUT. toFileName	Path where the file needs to be moved(aed_out_dir)

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Script Input	Description
BANCS.OUTPUT. errorMesg	Error Message.
BANCS.OUTPUT. successOrFailure	Success or Failure Indicator

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is “SEPA”. This script will be used to create Report for HGARFG when financial_file_format is Multiple for SEPA.

Example:

NA

©Copyright Infosys Ltd.

SEPA-Update Status Fields for HGARFG/HGARFR



Script Name:

The script SEPA_ahbx0005_updateStatusFields.scr must be present in \$TBA_SCRIPTS directory. This script will be used to update the status fields for HGARFG/HGARFR menus.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. BatchName	Criteria Batch name
BANCS.INPUT. SelFld3	selectFld[2]
BANCS.INPUT. SelFld2	selectFld[1]
BANCS.INPUT. SelFld1	selectFld[0]
BANCS.INPUT. TranId	Tran Id
BANCS.INPUT. TranDate	Tran Date
BANCS.INPUT. ReturnFileName	Return file name
BANCS.INPUT. ReturnDate	Return date
BANCS.INPUT. OrigAcct	Originator Account
BANCS.INPUT. OrigId	Originator Id
BANCS.INPUT. OrigInfo1	Orig Info 1

BANCS.INPUT. OrigInfo2	Orig Info 2
BANCS.INPUT. OrigName	Originator name
BANCS.INPUT.SrvCode	SRV Code
BANCS.INPUT.RecvAcct	Receiver account
BANCS.INPUT.RecvAcctDtls	Receiver account details
BANCS.INPUT.RecvId	Receiver Id
BANCS.INPUT.RecvInfo1	Receiver Info 1
BANCS.INPUT.RecvInfo2	Receiver Info 2
BANCS.INPUT.RecvName	Receiver name
BANCS.INPUT.RecvAcid	Receiver acid
BANCS.INPUT.TranAmt	Tran amount
BANCS.INPUT.TranCrncy	Tran currency
BANCS.INPUT.CommissionAmt	Commission amount
BANCS.INPUT.TotalAmt	Total amount
BANCS.INPUT.OutwardCommission	Outward commission
BANCS.INPUT.RejectAmt	Reject amount
BANCS.INPUT.OtherAmt1	other_amt1
BANCS.INPUT.OtherAmt2	other_amt2
BANCS.INPUT.EffectiveDate	Effective date
BANCS.INPUT.SettlementDate	Settlement date
BANCS.INPUT.OrigSettlementDate	orig_settlement_date
BANCS.INPUT.DueDate	due_date
BANCS.INPUT.Date1	date1
BANCS.INPUT.Date2	Date2
BANCS.INPUT.BankCode	bank_code
BANCS.INPUT.BranchCode	branch_code

BANCS.INPUT.Solid	SOL ID
BANCS.INPUT.OrigCode	Orig_code
BANCS.INPUT.RejCode	rejection_code
BANCS.INPUT.RejDesc	rejection_desc
BANCS.INPUT.EntryStatus	entry_status
BANCS.INPUT.ReturnStatus	return_status
BANCS.INPUT.FailProcess	fail_process
BANCS.INPUT.status2	status2
BANCS.INPUT.ReturnInd	return_ind
BANCS.INPUT.CrDrInd	cr_dr_ind
BANCS.INPUT.InwOutwInd	inw_outw_ind
BANCS.INPUT.FreshRetEntry	fresh_return_entry
BANCS.INPUT.TranCode	tran_code
BANCS.INPUT.CustTranId	cust_tran_id
BANCS.INPUT.CustTranDate	cust_tran_date
BANCS.INPUT.SettTranId	settlement_tran_id
BANCS.INPUT.SettTranDate	settlement_tran_date
BANCS.INPUT.TraceNum1	trace_num1
BANCS.INPUT.TraceNum2	trace_num2
BANCS.INPUT.TraceNum3	trace_num3
BANCS.INPUT.ApprovedBy	approved_by
BANCS.INPUT.ApproverCmnt	Approver comments
BANCS.INPUT.FreeCode1	free_code1
BANCS.INPUT.FreeCode2	free_code2
BANCS.INPUT.FreeCode3	free_code3
BANCS.INPUT.FreeCode4	free_code4

BANCS.INPUT.FreeCode5	free_code5
BANCS.INPUT.FreeText1	free_text1
BANCS.INPUT.FreeText2	free_text2
BANCS.INPUT.FreeText3	free_text3
BANCS.INPUT.FreeText4	free_text4
BANCS.INPUT.FreeText5	free_text5
BANCS.INPUT.TxnStatus	transaction_status
BANCS.INPUT.SourceId	source_id
BANCS.INPUT.<Flags>	Flags (CSMOUTWCRFLG, CSMINWRETFLG, CSMINWREJFLG, IDPOUTWCRFLG, IDPINWRETFLG, IDPINWREJFLG, IDPOUTWRECCRFLG, IDPOUTWRECDRFLG, IDPOUTWDRFLG, CUSTINWREJFLG)
BANCS.INPUT.<Counts>	Counts (CSMOUTWCRCOUNT, CSMINWRETCOUNT, CSMINWREJCOUNT, IDPOUTWCRCOUNT, IDPINWRETCOUNT, IDPINWREJCOUNT, IDPOUTWDRCOUNT, IDPOUTWRECCRCOUNT, IDPOUTWRECDRCOUNT, CUSTINWREJCOUNT)
BANCS.INPUT.<Amts>	Amounts (CSMOUTWCRTOTAMT, CSMINWRETTOTAMT, CSMINWREJTOTAMT, IDPOUTWCRTOTAMT, IDPINWRETTOTAMT, IDPINWREJTOTAMT, IDPOUTWDRTOTAMT, IDPOUTWRECCRTOTAMT, IDPOUTWRECDRTOTAMT, CUSTINWREJTOTAMT)
BANCS.INPUT.fileType	File Type('Financial' or 'Non-financial')
BANCS.INPUT.FileDestination	File Destination(CSM / IDP / Customer)
BANCS.INPUT.FinFileFormat	Financial File Format(Unified or Multiple)
BANCS.INPUT.CritInwOutwInd	Criteria Inward Outward Indicator
BANCS.INPUT.FlgValue	Flag Value(GARFG / GARFR)

BANCS.INPUT.SingleMultipleDRFlag	Single Multiple DR flag
BANCS.INPUT.LienorDebitFlag	Lein or debit flag
BANCS.INPUT.AutoReturnFlag	Auto return flag
BANCS.INPUT.CollectChrgFromAmtFlag	Collect charge from amount flag
BANCS.INPUT.LienId	Lein Id
BANCS.INPUT.BatchHdrSrlNum	Batch header srl number
BANCS.INPUT.DAReferencenumber	DA reference number
BANCS.INPUT.RefundAcct	Refund account
BANCS.INPUT.RateCode	Rate code
BANCS.INPUT.Rate	rate
BANCS.INPUT.ChrgAcct	Charge account
BANCS.INPUT.ChargeAcid	Charge acid
BANCS.INPUT.ChrgType	Charge type
BANCS.INPUT.ChrgEventId	Charge event type
BANCS.INPUT.ChrgRateCode	Charge rate code
BANCS.INPUT.ChrgRate	Charge rate
BANCS.INPUT.OrigAcctAddress1	Orig account address 1
BANCS.INPUT.OrigAcctAddress2	Orig account address 2
BANCS.INPUT.OrigAcctAddress3	Orig account address 3
BANCS.INPUT.RespAcctAddress1	Responding account address 1
BANCS.INPUT.RespAcctAddress2	Responding account address 2
BANCS.INPUT.RespAcctAddress3	Responding account address 3
BANCS.INPUT.ChargeEventType	Charge event type
BANCS.INPUT.OneShotFlg	One shot flag
BANCS.INPUT.UrgentFlg	Urgent flag
BANCS.INPUT.OtherEntityStatus	Other entity status

BANCS.INPUT.PurposeCode	Purpose code
BANCS.INPUT.OriginationCountry	Origination country
BANCS.INPUT.RespondingCountry	Responding country
BANCS.INPUT.UltimateDebtorName	Ultimate debtor name
BANCS.INPUT.UltimateDebtorAddress	Ultimate debtor address
BANCS.INPUT.UltimateDebtorCountry	Ultimate debtor country
BANCS.INPUT.UltimateDebtorId	Ultimate debtor Id
BANCS.INPUT.UltimateCreditorName	Ultimate creditor name
BANCS.INPUT.UltimateCreditorAddress	Ultimate creditor address
BANCS.INPUT.UltimateCreditorCountry	Ultimate creditor country
BANCS.INPUT.UltimateCreditorId	Ultimate creditor Id
BANCS.INPUT.EndToEndIdentification	End to end Identification
BANCS.INPUT.AutoRejectFlag	Auto reject flag
BANCS.INPUT.AdviceId	Advice Id
BANCS.INPUT.RecallDate	Recall date
BANCS.INPUT.RecallInducedBy	Recall induced by
BANCS.INPUT.RecallType	Recall type
BANCS.INPUT.RecallChargeEventId	Recall charge event Id
BANCS.INPUT.RecallChargeTranId	Recall charge tran Id
BANCS.INPUT.RecallChargeTranDate	Recall charge tran date
BANCS.INPUT.RecallTranId	Recall tran Id
BANCS.INPUT.RecallTranDate	Recall tran date
BANCS.INPUT.RecvBic	Receiver Bic
BANCS.INPUT.SenderBic	Sender Bic

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.ReturnFileName	Return file name
BANCS.OUTPUT.ReturnDate	Return date
BANCS.OUTPUT.OrigAcct	Originator Account
BANCS.OUTPUT.OrigId	Originator Id
BANCS.OUTPUT.OrigTranAcct	Originator Tran account
BANCS.OUTPUT.OrigInfo1	Orig Info 1
BANCS.OUTPUT.OrigInfo2	Orig Info 2
BANCS.OUTPUT.OrigName	Originator name
BANCS.OUTPUT.SrvCode	SRV Code
BANCS.OUTPUT.RecvAcct	Receiver account
BANCS.OUTPUT.RecvAcctDtls	Receiver account details
BANCS.OUTPUT.RecvId	Receiver Id
BANCS.OUTPUT.RecvInfo1	Receiver Info 1
BANCS.OUTPUT.RecvInfo2	Receiver Info 2
BANCS.OUTPUT.RecvName	Receiver name
BANCS.OUTPUT.RecvAcid	Receiver acid
BANCS.OUTPUT.TranAmt	Tran amount
BANCS.OUTPUT.TranCrncy	Tran currency
BANCS.OUTPUT.CommissionAmt	Commission amount
BANCS.OUTPUT.TotalAmt	Total amount
BANCS.OUTPUT.OutwardCommission	Outward commission
BANCS.OUTPUT.RejectAmt	Reject amount

BANCS.OUTPUT.OtherAmt1	other_amt1
BANCS.OUTPUT.OtherAmt2	other_amt2
BANCS.OUTPUT.EffectiveDate	Effective date
BANCS.OUTPUT.SettlementDate	Settlement date
BANCS.OUTPUT.OrigSettlementDate	orig_settlement_date
BANCS.OUTPUT.DueDate	due_date
BANCS.OUTPUT.Date1	date1
BANCS.OUTPUT.Date2	Date2
BANCS.OUTPUT.BankCode	bank_code
BANCS.OUTPUT.BranchCode	branch_code
BANCS.OUTPUT.Solid	SOL ID
BANCS.OUTPUT.OrigCode	Orig_code
BANCS.OUTPUT.RejCode	rejection_code
BANCS.OUTPUT.RejDesc	rejection_desc
BANCS.OUTPUT.EntryStatus	entry_status
BANCS.OUTPUT.ReturnStatus	return_status
BANCS.OUTPUT.FailProcess	fail_process
BANCS.OUTPUT.status2	status2
BANCS.OUTPUT.ReturnInd	return_ind
BANCS.OUTPUT.CrDrInd	cr_dr_ind
BANCS.OUTPUT.InwOutwInd	inw_outw_ind
BANCS.OUTPUT.FreshRetEntry	fresh_return_entry
BANCS.OUTPUT.TranCode	tran_code
BANCS.OUTPUT.CustTranId	cust_tran_id
BANCS.OUTPUT.CustTranDate	cust_tran_date
BANCS.OUTPUT.SettTranId	settlement_tran_id

BANCS.OUTPUT.SettTranDate	settlement_tran_date
BANCS.OUTPUT.TraceNum1	trace_num1
BANCS.OUTPUT.TraceNum2	trace_num2
BANCS.OUTPUT.TraceNum3	trace_num3
BANCS.OUTPUT.ApprovedBy	approved_by
BANCS.OUTPUT.ApproverCmnt	Approver comments
BANCS.OUTPUT.FreeCode1	free_code1
BANCS.OUTPUT.FreeCode2	free_code2
BANCS.OUTPUT.FreeCode3	free_code3
BANCS.OUTPUT.FreeCode4	free_code4
BANCS.OUTPUT.FreeCode5	free_code5
BANCS.OUTPUT.FreeText1	free_text1
BANCS.OUTPUT.FreeText2	free_text2
BANCS.OUTPUT.FreeText3	free_text3
BANCS.OUTPUT.FreeText4	free_text4
BANCS.OUTPUT.FreeText5	free_text5
BANCS.INPUT.TxnStatus	transaction_status
BANCS.OUTPUT.SourceId	source_id
BANCS.OUTPUT.SingleMultipleDRFlag	Single Multiple DR flag
BANCS.OUTPUT.LienorDebitFlag	Lein or debit flag
BANCS.OUTPUT.AutoReturnFlag	Auto return flag
BANCS.OUTPUT.CollectChrgFromAmtFlag	Collect charge from amount flag
BANCS.OUTPUT.SystemId	System Id
BANCS.OUTPUT.LienId	Lein Id
BANCS.OUTPUT.BatchHdrSrlNum	Batch header srl number
BANCS.OUTPUT.DAReferencenumber	DA reference number

BANCS.OUTPUT.RefundAcct	Refund account
BANCS.OUTPUT.RateCode	Rate code
BANCS.OUTPUT.Rate	rate
BANCS.OUTPUT.ChrgAcct	Charge account
BANCS.OUTPUT.ChargeAcid	Charge acid
BANCS.OUTPUT.ChrgType	Charge type
BANCS.OUTPUT.ChrgEventId	Charge event type
BANCS.OUTPUT.ChrgRateCode	Charge rate code
BANCS.OUTPUT.ChrgRate	Charge rate
BANCS.OUTPUT.OrigAcctAddress1	Orig account address 1
BANCS.OUTPUT.OrigAcctAddress2	Orig account address 2
BANCS.OUTPUT.OrigAcctAddress3	Orig account address 3
BANCS.OUTPUT.RespAcctAddress1	Responding account address 1
BANCS.OUTPUT.RespAcctAddress2	Responding account address 2
BANCS.OUTPUT.RespAcctAddress3	Responding account address 3
BANCS.OUTPUT.ChargeEventType	Charge event type
BANCS.OUTPUT.OneShotFlg	One shot flag
BANCS.OUTPUT.UrgentFlg	Urgent flag
BANCS.OUTPUT.OtherEntityStatus	Other entity status
BANCS.OUTPUT.PurposeCode	Purpose code
BANCS.OUTPUT.OriginationCountry	Origination country
BANCS.OUTPUT.RespondingCountry	Responding country
BANCS.OUTPUT.UltimateDebtorName	Ultimate debtor name
BANCS.OUTPUT.UltimateDebtorAddress	Ultimate debtor address
BANCS.OUTPUT.UltimateDebtorCountry	Ultimate debtor country
BANCS.OUTPUT.UltimateDebtorId	Ultimate debtor Id

BANCS.OUTPUT.UltimateCreditorName	Ultimate creditor name	
BANCS.OUTPUT.UltimateCreditorAddress	Ultimate creditor address	
BANCS.OUTPUT.UltimateCreditorCountry	Ultimate creditor country	
BANCS.OUTPUT.UltimateCreditorId	Ultimate creditor Id	
BANCS.OUTPUT.EndToEndIdentification	End to end Identification	
BANCS.OUTPUT.AutoRejectFlag	Auto reject flag	
BANCS.OUTPUT.AdviceId	Advice Id	
BANCS.OUTPUT.RecallDate	Recall date	
BANCS.OUTPUT.RecallInducedBy	Recall induced by	
BANCS.OUTPUT.RecallType	Recall type	
BANCS.OUTPUT.RecallChargeEventId	Recall charge event Id	
BANCS.OUTPUT.RecallChargeTranId	Recall charge tran Id	
BANCS.OUTPUT.RecallChargeTranDate	Recall charge tran date	
BANCS.OUTPUT.RecallTranId	Recall tran Id	
BANCS.OUTPUT.RecallTranDate	Recall tran date	
BANCS.OUTPUT.RecvBic	Receiver Bic	
BANCS.OUTPUT.SenderBic	Sender Bic	
BANCS.OUTPUT.RejectTranId	Reject Tran Id	
BANCS.OUTPUT.RejectTranDate	Reject tran Date	
BANCS.OUTPUT.CompensationAmt	Compensation amount	
BANCS.OUTPUT.<Flags>	Flags (CSMOUTWCRFLG, CSMINWRETFLG, CSMINWREJFLG, IDPOUTWCRFLG, IDPINWRETFLG, IDPINWREJFLG, IDPOUTWRECCRFLG, IDPOUTWRECDRFLG, IDPOUTWDRFLG, CUSTINWREJFLG)	
BANCS.OUTPUT.<Counts>	Counts (CSMOUTWCRCOUNT, CSMINWRETCOUNT, CSMINWREJCOUNT,	

IDPOUTWCRCOUNT, IDPINWRETCOUNT,
IDPINWREJCOUNT, IDPOUTWDRCOUNT,
IDPOUTWRECCRCOUNT,
IDPOUTWRECDRCOUNT,
CUSTINWREJCOUNT)

BANCS.OUTPUT.<Amts>

Amounts

(CSMOUTWCRTOTAMT,
CSMINWRETTOTAMT,
CSMINWREJTOTAMT,
IDPOUTWCRTOTAMT,
IDPINWRETTOTAMT, IDPINWREJTOTAMT,
IDPOUTWDRTOTAMT,
IDPOUTWRECCRTOTAMT,
IDPOUTWRECDRTOTAMT,
CUSTINWREJTOTAMT)

BANCS.OUTPUT. successOrFailure

Success or Failure Indicator

BANCS.OUTPUT.errormesg

Error Message.

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is “SEPA”. This script will be used to update the status fields for HGARFG/HGARFR menus.

Example:

NA

©Copyright Infosys Ltd.

SEPA-Settlement Date and Effective date validation for SEPA Credit and Direct Debits



Script Name:

The script SEPA_validateSettmntAndEffDate.scr must be present in \$TBA_SCRIPTS directory. This script will be used to do Settlement date and Effective date validation for SEPA Credit and Direct Debits.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
BANCS.INPUT.CrDrInd	Credit Debit Indicator
BANCS.INPUT.EffectiveDate	Effective date
BANCS.INPUT.SettlementDate	Settlement date
BANCS.INPUT.PaysysId	Paysys Id
BANCS.INPUT.SourceId	Source Id
BANCS.INPUT.InwOutwInd	Inward Outward Indicator
BANCS.INPUT.Trancode	Tran code
All AED table Dtls	All AED table details(not used)

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Script Input	Description
BANCS.OUTPUT. ErrorDesc	Error Message.
BANCS.OUTPUT. successOrFailure	Success or Failure Indicator

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is "SEPA". This script will be used to do Settlement date and Effective date validation for SEPA Credit and Direct Debits.

Example:

NA

©Copyright Infosys Ltd.

Fetch Department Number Field for PO Creation



Script Name:

The script `PO_getDepartmentNum.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to fetch DepartmentNumber for Payment Order Creation during Interest Calculation

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT.deptNum	Department Number

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT.deptNum	Department Number

Typical Usage Scenario:

This script will be used to customize Department Number to be passed for Payment Order Creation

Example:

NA

©Copyright Infosys Ltd.

Bank Validation and Decision

Script Name:

The script "BankValidationandDecision.scr" must be present in TBA_SCRIPTS directory. This script will be used to determine whether the Inward FPS Payment should be REJECTED, ACCEPTED or go to PENDING_USER_INTERVENTION.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. decisionFlag	The system decision based on validations done till now. The possible values are J – Rejected, Y – Accepted, I – User Intervention Required.
BANCS.INPUT. rejectionCode	The system decided Rejection Code. If the system has decided to reject the payment based on some internal validation, this code will give the reason for the same.
BANCS.INPUT. swSrlNum	The swift serial number of the message being currently processed. This is the key to the SMH table and this can be used any further data fetch that might be required on the same message.
BANCS.INPUT. BenefAcct	The account that will get credited because of this payment.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. decisionFlag	The final decision from the script. The system decision can get over-ridden from the script. The possible values are J – Rejected, Y – Accepted, I – User Intervention Required.
BANCS.OUTPUT. rejectionCode	The final rejection code from the script. This system decided rejection code can get over-ridden from the script.

Default Logic:

The default logic in the script is to accept system decision, if the decision is to ACCEPT or move the payment to UNSER_INTERVENTION status. But if the system decision is to REJECT, the script will check, if the reason for the same is because the beneficiary account has been frozen (Rejection Code = ACCFZ - BENEFICIARY ACCOUNT FROZEN or RAAFZ - RECEIVING AGENCY ACCOUNT FROZEN). If so, the system will change the decision to move the payment to USER_INTERVENTION and change the rejection code to AQUTD - QUALIFIED ACCEPTANCE. If the system has decided to reject the payment for any other reason, the payment will be rejected.

Typical Usage Scenario:

This script can be used to over-ride the system decision based on the bank's specific requirements. The decision could be based on certain scheme types of the beneficiary account.

Example:

NA

Event Mapping Scripts for SFMS Message



The Event Mapping scripts for SFMS messages are created to read, map and concatenate the repository values sent by the calling program and form the message.

These IFN Event Mapping scripts are similar to Swift Scripts that are MT Event Mapping scripts.

Event Mapping Scripts for SFMS and SWIFT are called in this fashion.

[<format_type> Event Mapping <msg_no>]. Format Type for SFMS is IFN and for SWIFT is MT.

Event Mapping script has to be called based on Implementation Type[i.e SWIFT or SFMS] format type and Msg No will be replaced to form a Event Mapping Script Name and that script will be executed.

All Event Mapping scripts for SFMS are in Norms with Swift Scripts.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
SendersReference	Senders Reference Number
NostroValueDate	Nostro Value Date
ValueDate	Value Date
CurrencyCode	Currency Code
Amount	Amount

OrderingCustomerName	Ordering Customer Details
OrderingCustomerAddress	Ordering Customer Details
OrderingCustomerCountryName	Ordering Customer Details
OrderingInstitutionBIC	Ordering Institution Details
OrderingInstitutionName	Ordering Institution Details
OrderingInstitutionAddress	Ordering Institution Details
IntermediaryInstitutionBIC	Intermediary Institution Details
IntermediaryInstitutionName	Intermediary Institution Details
IntermediaryInstitutionAddress	Intermediary Institution Details
InterMediaryPartyId	InterMediary Party Details
SendersCorrespondentBIC	Senders Correspondent Details
SendersCorrespondentLocation	Senders Correspondent Details
SendersCorrespondentName	Senders Correspondent Details
ReceiversCorrespondentBIC	Receivers Correspondent Details
ReceiversCorrespondentLocation	Receivers Correspondent Details
ReceiversCorrespondentName	Receivers Correspondent Details
AccountWithInstitutionBIC	Account With Institution Details
AccountWithInstitutionPartyId	Account With Institution Party Details
AccountWithInstitutionName	Account With Institution Details
AccountWithInstitutionAddress1	AccountWithInstitutionAddress1
BeneficiaryCustomerPartyId	Beneficiary Customer Party Details
.BeneficiaryCustomerAddress	.Beneficiary Customer Details
BeneficiaryCustomerCountryName	Beneficiary Customer Country Name
RemittanceInfo	Remittance Information
DetailsOfCharges	Details Of Charges
SenderToReceiverInfo	Sender To Receiver Information

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
out_mesg	The swift message which is in pipe separated format
SwiftMessage	The swift message which is in pipe separated format

Typical Usage Scenario(s):

The Event Mapping scripts are called on call of CreateSwiftMsg SRV from any menu or on navigating to Message Details Tab.

©Copyright Infosys Ltd.

Format Scripts for SFMS Message



This script IFN100msg.scr formats the IFN message from the message screen of IFN .Repositories that has been passed from the calling program. It is assumed that all the validations have been done before calling this script.

These Format IFN scripts are similar to Swift Scripts that are FormatMTscripts. Format Scripts for SFMS and SWIFT are called in this fashion [<format_type><msg_no>msg].Format Type for SFMS is IFN and for SWIFT is MT.

Format script has to be called based on Implementation Type[i.e SWIFT or SFMS] format type and Msg No will be replaced to form a Format Script Name and that script will be executed.

All Format scripts for SFMS are in Norms with Swift Scripts.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
Tag 32a1	Value Date
Tag 32a2	Currency Code
Tag 32a3	Amount
Tag 50	Ordering Customer
Tag59	Beneficiary Customer
Tag 52	Ordering Institution
Tag53	Sender's Correspondent.

Tag54	Receiver's Correspondent.
Tag56	Intermediary
Tag57	Account with Institution
Tag70	Details of Payment
Tag71A	Details of Charges
Tag72	Sender to Receiver Information
Tag20	Transaction Reference Number

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. swift_msg	Formatted Swift Message

Typical Usage Scenario(s):

The Format scripts are called when clicked on Accept button in Message Details tab. This script forms a pipe separated swift message which contains both tag and values.

©Copyright Infosys Ltd.

Mapping of Message ID from SWIFT to Other Payment System



In SWIFT and SFMS payment systems, most of the message IDs are used for similar purpose. There are certain message ID's which are used to send same message but their message ID's differ from one payment system to other.

Example: message ID 103 in SWIFT is similar to message ID 100 in SFMS

Message ID mapping script is written to reduce coding complexity. This script SWIFTToOtherPaySysMap.scr accepts paysys ID and message ID as input. paysys ID is the target to which message ID is mapped from SWIFT.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
PaysysIdForMap	Payment system type which requires mapping. i.e target Payment system type
SWIFTMsgNum	Message number used in SWIFT

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
MappedOtherPaysysMsgNum	Message number that is mapped to target Payment system type

Typical Usage Scenario(s):

This mapping script is called, when there is a need to map SWIFT message ID to other payment system message ID.

©Copyright Infosys Ltd.

Mapping of Message ID from Other Payment System Message ID to SWIFT



This script `OtherPaySysToSWIFTMap.scr` is similar to `SWIFTToOtherPaySysMap.scr`, but does reversal operation. Message ID mapping script is written to reduce coding complexity. This script accepts paysys ID and message ID as input. Here target paysys ID is always SWIFT, hence message ID mapping is done from other payment system to SWIFT equivalent message ID.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
OtherPaysysId	Payment system type other than SWIFT.
OtherPaysysMsgNum	Message number used in payment system other than SWIFT.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
MappedSWIFTMsgNum	Message number that is mapped to SWIFT Payment system type.

Typical Usage Scenario(s):

This mapping script is called, when there is a need to map other payment system message ID to SWIFT message ID.

©Copyright Infosys Ltd.

Mapping for n series Messages to a Single Message



This script is used to map the message ID of n series messages with the message ID for which Event mapping, validate and format scripts are available. For n series messages there is only one event mapping, validate and format script present.

Example:

For n92 series messages only scripts for message number 192 is available, hence other messages of n92 series must make use of these available scripts only.

MapNSeriesMsgNum.scr is written to reduce coding complexity and it is called only for n series messages. This script accepts paysys ID and message ID as input. Input message number will be mapped to a message number for which required scripts are available (i.e. event mapping, validate and format scripts).

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
paysysId	Payment system type
msgNum	Message number used in payment system.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
mappedMsgNum	Message number that is mapped to other Payment system type from SWIFT.

Typical Usage Scenario(s):

This mapping script for n series messages is called, when there is a need to map the message ID for which event mapping, validate and format scripts are present.

©Copyright Infosys Ltd.

Risk Limit Status Update Script



The script **riskLimitStatusUpdate.scr** must be present in TBA_SCRIPTS directory. This script will be used to update the Daily/File or Batch Limit Status.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.dailyPrefFlg	Daily Limit breach preference set at profile
BANCS.INPUT.filePrefFlg	File Limit breach preference set at profile
BANCS.INPUT.batchPrefFlg	Batch Limit breach preference set at profile
BANCS.INPUT.dailyBreachStatus	Daily Limit breached status
BANCS.INPUT.fileBreachStatus	File limit breached status
BANCS.INPUT.batchBreachStatus	Batch limit breached status
BANCS.INPUT.inputFileName	Input file name (uploaded file name)
BANCS.INPUT.fileId	File ID which was used during upload of the file
BANCS.INPUT.fileHdrSrlNum	Header serial number which was generated during upload process
BANCS.INPUT.duplicateField	Duplicate field consists of File ID and Input file name together makes unique combination.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.breachAction	The action which was taken on Record/File/Batch.
BANCS.OUTPUT.typeOfBreach	The type of breach which was occurred during upload process
BANCS.OUTPUT.successFailure	Success or Failure

Typical Usage Scenario(s):

This script is called, when Risk Limits are there and any limit breached (either Daily or File Limit breached).

According to limit breached and limit breach preference, status will be updated for all the records.

©Copyright Infosys Ltd.

Batch Limit Status Update Script



The script **batchLimitStatusUpdate.scr** must be present in TBA_SCRIPTS directory. This script will be used to update the Daily/File or Batch Limit status.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. batchPrefFlg	Batch Limit breach preference set at profile
BANCS.INPUT. batchHdrSrlNum	Batch Header serial number which is generated during upload.
BANCS.INPUT. batchBreachStatus	Batch Limit breached status which was done during upload process
BANCS.INPUT. riskLimitBreachPref	Risk Limit Breached Preference which is being updated during every breach process

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.successFailure	Success or Failure

Typical Usage Scenario(s):

This script is called when batch Limits are there and any batch limit is breached..

According to limit breached and limit breach preference, status will be updated for entire batch.

©Copyright Infosys Ltd.

Service Preference Serial Number Update



The script **updateSrvcPrefSrlNum.scr** must be present in TBA_SCRIPTS directory. This script will be used to update the Daily or File or Batch Limit status.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. batchHdrSrlNum	Batch Header serial number which is generated during upload.
BANCS.INPUT. srvcPrefSrlNum	Service Preference Serial number under which this batch is being uploaded

Output:

The output of the script will be available in the specified repository fields.

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.successFailure	Success or Failure

Typical Usage Scenario(s):

This script is called, when Batch Header Serial Number and Service Preference Serial Number will not be null. This service preference

serial number will be updated to all the records which are all belong to this batch Header serial number of AED table.

©Copyright Infosys Ltd.

Autorepresentment Script



The script **createACHInstForAutoRep.scr** is used to create an ACH instruction as a part of the autorepresentment process when the representment mode is set as ACH.

It must be present in TBA_SCRIPTS directory.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
OrigName	Originator Name
CrForAcid	Credit Foracid
CPP_RefCode	Ref Code
CPP_CrDrInd	Credit Debit Indicator
CPP_InOutInd	In Out Indicator
CrAcid	Credit Acid
CrCrncyCode	Credit Acct Currency Code
SolId	Sol Id
CrAcctName	Name of the Credit Acct Holder
CrShortName	Short Name of the Credit Acct Holder
InstrCrncyCode	Instrument Currency Code
InstrAmt	Instrument Amount
EffectiveDate	Effective Date
BankId	Bank Id

CPP_RepresMode	Mode of representment
CPP_Eligibility	Eligibility

Output:

This script creates an ACH instruction if the representment mode is set to ACH for a rejected instrument.

Typical Usage Scenario(s):

To decide, if the instrument is eligible for auto representment

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Check for Autorepresentation



The script checkForAutoRepresentation.scr is used to check if the reason codes of rejected instruments are a part of the applicable reason codes as a part of the Autorepresentation process.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
CPP_RejReasonCode1	Reject Reason Code 1
CPP_RejReasonCode2	Reject Reason Code 2
CPP_RejReasonCode3	Reject Reason Code 3
CPP_RejReasonCode4	Reject Reason Code 4
CPP_RejReasonCode5	Reject Reason Code 5
CPP_AutoRepReq	Boolean variable which indicates if Autorepresentation is required
CPP_ApplicableRejCode	The applicable reason Code.
CPP_RepresMode	The method of representment

Output:

To decide if the instrument is eligible for auto representment..

Sample Script:

Sample script mrdsp.sscr is present in the Sample scripts (samscripts)

directory.

Typical Usage Scenario(s):

To decide if the instrument is eligible for auto representment.

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Open Zone for Cheque Mode of Autorepresentation



This script is used to open a zone on a date calculated prior to calling the script. This is done as a part of the Auto-representation process when the mode of auto-representation is Cheque.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
ZoneCode	The Zone which has to be opened
EffectiveDate	The date on which the zone has to be opened
SolId	Service outlet ID
CPP_RepresMode	The method of representation

Output:

The script opens a zone on the effective date given as input.

Typical Usage Scenario(s):

To open a zone on a particular pre calculated date.

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Finacle Copyright

Script to Lodge Instruments



This script is used to lodge an instrument for a particular zone code - zone date combination.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
InstSrlNum	Instrument Serial Number
InstID	Instrument Number
BrCode	Branch Code
BankCode	Bank Code
BankName	Name of the bank
BrName	Name of the Branch
InstrAmt	Instrument Amount
InstrCrncyCode	The Currency Code of the Instrument
SolId	Service outlet id
SolDesc	Service outlet id description
ZoneCode	The Zone Code
EffectiveDate	Date for which the instrument is lodged
CrForAcid	Credit For Acid
CrAcid	Credit Acid
CrCrncyCode	Currency Code of the Credit Account
CrAcctName	Name of the Credit Account Holder

CrShortName	Short name of the Credit Account Holder
RptCode	Report Code

Output:

The script lodges the rejected instrument for a zone code – zone date combination.

Sample Script:

Sample script mrdsp.sscr is present in the Sample scripts (samscripts) directory.

Typical Usage Scenario(s):

To lodge a rejected instrument.

Default logic in Case Script is not Present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Instrument Message ID



The script **getFileNetSystemForImage.scr** must be present in TBA_SCRIPTS directory.

This script is used to decide if the scanned copy of an instrument for the corresponding instrument image ID has to be displayed or not.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
image ID	Instrument Image ID

Output:

The script decides if the instrument is eligible for Autorepresentation.

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Valid Values are "S" or "F" If script is executed successfully then "S" will be returned else "F" will be returned
fileNetSystem	Valid values are I.
IBMFileNetSystem	Valid values are 'Y' or 'N'. If IBMFileNetSystem is 'Y' it connects to FDMA

services. If IBMFileNetSystem is 'N' it doesnot connect to FDMA.
--

Typical Usage Scenario(s):

To display the scanned copy of an instrument image.

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Script to Validate Blacklisted Payments



The script **validatePymtWithOFAC.scr** must be present in TBA_SCRIPTS directory.

This script is used to validate blacklisted payments for PBPS and VBLPS menu

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
EntrySrlNum	Entry Serial Number
PaysysId	Paysys Id
HeaderSrlNum	Header Serial Number
ReturnFileName	Return File Name
ReturnDate	Return Date
OrigAcct	Originator Account Id
OrigId	Originator Id
OrigInfo1	Originator Information 1
OrigInfo2	Originator Information 2
OrigName	Originator Name
SrvCode	Srv Code
RecvAcct	Receiver Acct
RecvAcctDtls	Receiver Acct Details
RecvId	Receiver Id

RecvInfo1	Receiver Information 1
RecvInfo2	Receiver Information 2
RecvName	Receiver Name
RecvAcid	Receiver Acct Id
TranAmt	Transaction Amount
TranCrncy	Transaction Currency
CommisionAmt	Commission Amount
TotalAmt	Total Amount
OutwardCommision	Outward Commission
RejectAmt	Reject Amount
OtherAmt1	Other Amount 1
OtherAmt2	Other Amount 2
EffectiveDate	Effective Date
SettlementDate	SettlementDate
DueDate	Due Date
Date1	Date1
Date2	Date2
BankCode	Bank Code
BranchCode	Branch Code
Solld	Solld
OrigCode	Orig Code
RejCode	Rej Code
FailProcess	Fail Process
status2	Status 2
ReturnInd	Return Indicator
CrDrInd	Credit Debit Indicator
InwOutwInd	Inward Outward Indicator
FreshRetEntry	FreshRetEntry

TranCode	TranCode
CustTranId	CustTranId
CustTranDate	CustTranDate
SettTranId	SettTranId
SettTranDate	SettTranDate
TraceNum1	Trace Number1
TraceNum2	Trace Number2
TraceNum3	Trace Number3
ApprovedBy	ApprovedBy
ApproverCmnt	ApproverCmnt
FreeCode1	Free Code1
FreeCode2	Free Code2
FreeCode3	Free Code3
FreeCode4	Free Code4
FreeCode5	Free Code5
FreeText1	Free Text1
FreeText2	Free Text2
FreeText3	Free Text3
FreeText4	Free Text4
FreeText5	Free Text5
IntTranId	Int Transaction Id
IntTranDate	IntTransaction Date
TxnStatus	TxnStatus
SourceId	SourceId
SingleMultipleDRFlag	Single Multiple DR Flag
LienorDebitFlag	Lienor Debit Flag
SystemId	System Id
OrigTranAcct	Originator Transaction Account
LienId	Lien Id

BatchHdrSrlNum	Batch HeaderSrlNum
DAReferencenumber	DA Reference Number
OrigSettlementDate	Originator Settlement Date
AutoReturnFlag	AutoReturnFlag
RefundAcct	Refund Account
CollectChrgFromAmtFlag	Collect Charge From Amount Flag
RateCode	Rate Code
Rate	Rate

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Script Input	Description
BlackListStatus	The black list status
StatusDetails	The status details
BlackListRemarks	The back list remarks
successOrFailure	Valid Values are "S" or "F" If script is executed successfully then "S" will be returned else "F" will be returned

Sample Script:

Sample script mrdsp.sscr is present in the Sample scripts (samscripts) directory.

Typical Usage Scenario(s):

To check the blacklist status

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Finacle Copyright

Auto Set Release For OCTM

Infosys®



The script **AutoSetReleaseForOCTM.scr** must be present in TBA_SCRIPTS directory.

This script is used to do release to shadow balance operation on an instrument.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
release Flag	The autoSetRelease is to be done only for CFA(Check funds Availability) Enabled Instruments. This flags tells us whether the Instrument is CFA enabled or not.
clgZoneCode	The zone code of the clearing zone
clgZoneDate	The zone date of the clearing zone
setNum	The set num for which the instrument is lodged
releaseTranId	The tran id created during Released to Shadow Balance

Output:

The script used to do release to shadow balance operation on an instrument.

Sample Script:

Sample script AutoSetReleaseForOCTM.scr is present in the sample scripts (samscripts) directory.

Typical Usage Scenario(s):

To do release to shadow balance operation on an instrument.

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

Profile Charge Transaction Creation Script



The script **CPP_CreateChrgTran.scr** must be present in **TBA_SCRIPTS** directory. This script will be used to update the Daily/File or Batch Limit status.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
MTT.InputDetails.custId	Customer ID
MTT.InputDetails.remitCrncy	Remit Currency
MTT.InputDetails.DrAcct	Debit Account
MTT.InputDetails.DrAcctAcid	Debit account Acid
MTT.InputDetails.chargeAcct	Charge Account
MTT.InputDetails.chargeAcctAcid	Charge Account Acid
MTT.InputDetails.chargeEventId	Charge Event ID
MTT.InputDetails.chargeEventType	Charge Event Type
MTT.InputDetails.chargeRateCode	Charge rate Code
MTT.InputDetails.chargeRate	Charge Rate Rate

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.scriptError	Script Error
BANCS.OUTPUT.successOrFailure	Success or Failure

Typical Usage Scenario(s):

This script is called when Waive Charge Flag is NO and Default Charge account is not null during profile creation in MCPP menu option. This script will display all the transaction details which are required for transaction creation.

©Copyright Infosys Ltd.

Outward Clearing Data Upload



The script **doFileUploadChk.scr** must be present in TBA_SCRIPTS directory.

This script is used check to whether file upload is done for similar Zone Code, Zone Date or Zone Currency, MICR Indicator combination.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

One can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
UPLD_ZONE_CODE	Code of the zone for which the outward clearing data is to be uploaded
UPLD_ZONE_DATE	Date of the zone for which outward clearing data is to be uploaded
UPLD_CRNCY_CODE	Currency Code of the Zone
UPLD_MICR_FLG	Micr flag
UPLD_CHK_FLG	Upload check flag

Output:

The script decides, if file upload has been done for Similar Zone Code, Zone Date or Zone Crncy, MICR Flag combination

Sample Script:

Sample script doFileUploadChk.scr is present in the sample scripts

(samscripts) directory.

Typical Usage Scenario(s):

To decide, if file upload has been done for Similar Zone Code, Zone Date or Zone Crncy, MICR Flag combination

Default logic in case script is not present:

No default logic in the absence of the script.

©Copyright Infosys Ltd.

PDC Scripts



The PDC scripts are:

[Create Contingent Transaction](#)

[Fetch Zone Details for PDC](#)

©Copyright Infosys Ltd.

Referral Related Events



The Referral related events are:

[A](#) [Adding Custom Events in HREATM and HREALM](#)

[M](#) [Modifying Default Approval Process in Referral](#)

[R](#) [Referral Exceptions – Sending Exceptions for Custom Referral](#)

[G](#) [Get List of Exceptions to be Ignored](#)

[S](#) [Sending Exceptions for Custom Referral](#)

©Copyright Infosys Ltd.

Securitization Events



The different Securitization events are:

[Buyback Authorization Pool Transaction Script](#)

[Buyback Authorization Transaction Script](#)

[Credit Collection to Escrow Transaction Script](#)

[Credit Collection to SPV Transaction Script](#)

[Loans Waiver of Fee and Interest Transaction Script](#)

[Pool Authorization Transaction Script](#)

[Pool Selection Additional Criteria Script](#)

[Buyback Additional Selection Script](#)

[Credit Collection to SPV Amortization Transaction Script](#)

©Copyright Infosys Ltd.

SI Related Scripts



The SI related scripts are:

[Fetch Template](#)

[SI Amount Derivation](#)

[SI Execution](#)

[Distinguish Between Carry Forward SI and Regular SI](#)

©Copyright Infosys Ltd.

Pre Process Script for SI Execution



Script Name:

outBndCallPreSlEXEC.scr

Description:

This script is used as pre process script for SI execution. The script must be present in TBA_SCRIPTS directory.

Inputs:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned. You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Description
BANCS.INPUT. si_srl_num	SI serial number
BANCS.INPUT. si_partTranSrlNum	Denote part trans in each SI
BANCS.INPUT. si_amt	SI Part Tran Amount
BANCS.INPUT. si_acid	Part Tran Account Number
BANCS.INPUT. si_part_tran_type	Tran Type of the transaction. Possible Value :- C (Credit) or D (Debit)
BANCS.INPUT. si_event_type	This is event type defined for SI execution

Output:

The output of the script is available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

--	--

Field Name	Description
BANCS.OUTPARAM.errorMesg	Error Message
BANCS.OUTPUT.successOrFailure	Success Or Failure - Status

Default Logic:

NA

Typical Usage Scenario:

This script is used as pre process script for SI execution.

Example:

NA

©Copyright Infosys Ltd.

Post Process Script for SI Execution



Script Name:

outBndCallPostSlxec.scr

Description:

This script is used as post process script for SI execution. The script must be present in TBA_SCRIPTS directory.

Inputs:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned. You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Description
BANCS.INPUT. si_srl_num	SI serial number
BANCS.INPUT. si_partTranSrlNum	Denote part trans in each SI
BANCS.INPUT. si_amt	SI Part Tran Amount
BANCS.INPUT. si_acid	Part Tran Account Number
BANCS.INPUT. si_part_tran_type	Tran Type of the transaction. Possible Value :- C (Credit) or D (Debit)
BANCS.INPUT. si_event_type	This is event type defined for SI execution
BANCS.INPUT. si_status	This field contains the status of SI, such as whether its executed or any error or something else has occurred.

Output:

The output of the script is available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Description
BANCS.OUTPARAM.errorMesg	Error Message
BANCS.OUTPUT.successOrFailure	Success Or Failure - Status

Default Logic:

NA

Typical Usage Scenario:

This script is used as post process script for SI execution.

Example:

NA

©Copyright Infosys Ltd.

Scripts to call External Systems to Release or Reverse SIs



Script Name:

preCommitAndRollbackForSI.scr

postCommitAndRollbackForSI.scr

Description:

The pre script preCommitAndRollbackForSI.scr and post script postCommitAndRollbackForSI.scr are used to do a call to external system.

Inputs:

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS. INPUT. <Fieldname>

Pre Script

Script Input	Description
si_db_action	DB action whether to commit or rollback
si_db_position	Denotes the position from commit or rollback is called.
si_status	Status of SI.

Post Script

Script Input	Description
si_db_action	DB action whether to commit or rollback
si_db_position	Denotes the position from commit or rollback is called.
si_status	Status of SI.

Output:

The defined outputs are available in repository BANCS, class OUTPUT and with the field names mentioned below. One can access the outputs by referring the fields in the following manner.

BANCS. OUTPUT. <Fieldname>

Script Output	Description
successOrFailure	The return status of the script
errorMessage	The error message in case of failure

Default Logic:

If the script is not present then commit or rollback should happen as expected.

Typical Usage Scenario:

The pre and post script will be called for each commit or rollback happening in the process, the script user hook can be used to make a call to an external system to release/reverse any process or transaction.

Sample Script:

Sample scripts preCommitAndRollbackForSl.sscr and post script postCommitAndRollbackForSl.sscr are present in sample scripts directory (samscripts) directory.

©Copyright Infosys Ltd.

Swift Message Events

The Swift Message events are:

- [Script for MT110 Swift Message](#)
- [Script for MT111 Swift Message](#)
- [Script for MT192 Swift Message](#)
- [Generate Swift Message MT102](#)
- [Generate MT103 Swift Message](#)
- [Format MT110 Swift Message](#)
- [Generate MT110 Ungrouped Swift Message](#)
- [Generate Swift Message MT202](#)
- [Generate MT203 Swift Message](#)
- [Format MT100 Message](#)
- [Format MT102 Message](#)
- [Populate Swift Message MT102](#)
- [Form the MT103 Swift Message](#)
- [Format MT103 Message](#)
- [Form Date to Paysys Date Format](#)
- [Form MT110 Swift Message](#)

- [Format Swift Message MT110](#)
- [Form NT111 Swift Message](#)
- [Format MT111 Swift Message](#)
- [Format MT191 Message](#)
- [Form MT202 Swift Message](#)
- [Format MT202 Message](#)
- [Form MT400 Message](#)
- [Format MT400 Swift Message](#)
- [Form MT410 Swift Message](#)
- [Format MT410 Swift Message](#)
- [Form MT412 Message](#)
- [Format MT412 Swift Message](#)
- [Forma MT416 Swift Message](#)
- [Format MT416 Swift Message for the Given tags](#)
- [Form MT420 Message](#)
- [Format MT420 Swift Message](#)
- [Form MT422 Message](#)
- [Format MT422 Message](#)
- [Form MT430 Message](#)

- [Format MT430 Message](#)
- [Form MT495 Message](#)
- [Format MT495 Message](#)
- [Form MT496 Message](#)
- [MT643EventMapping](#)
- [MT644EventMapping](#)
- [MT645EventMapping](#)
- [MT646EventMapping](#)
- [Form MT700 Message](#)
- [Format MT700 Swift Message](#)
- [Format MT701 Message](#)
- [Format MT705 Swift Message](#)
- [Form MT707 Message](#)
- [Form MT707 Swift Message](#)
- [Format MT707 Swift Message for the Given Tags](#)
- [Form MT710 Swift Message](#)
- [Format MT710 Message](#)
- [Format MT711 Message](#)
- [Form MT720 Message](#)

- [Format MT720 Message](#)
- [Format MT721 Message](#)
- [Form MT730 Message](#)
- [Format MT730 Message](#)
- [Form Swift Message MT732](#)
- [Format the MT732 Swift Message](#)
- [Form MT734 Swift Message](#)
- [Format MT734 Swift Message](#)
- [Form MT740 Swift Message](#)
- [Format Swift Message MT740](#)
- [Form MT742 Swift Message](#)
- [Format MT742 Swift Message](#)
- [Form MT747 Swift Message](#)
- [Format MT747 Swift Message](#)
- [Form MT750 Message](#)
- [Format MT750 Message](#)
- [Form MT752 Swift Message](#)
- [Format MT752 Swift Message](#)
- [Form MT754 Swift Message](#)

[•Format MT754 Swift Message](#)

[•Form MT756 Swift Message](#)

[•Format MT756 Swift Message](#)

[•Generate MT760 Message](#)

[•Form MT760 Message](#)

[•Form MT767 Swift Message](#)

[•Format MT767 Message](#)

[•Form MT768 Message](#)

[•Form MT769 Message](#)

[•Form MT900 Message](#)

[•Form MT910 Message](#)

[•Format MT940 Swift Message](#)

[•Format MT942 Swift Message](#)

[•Format MT950 Swift Message](#)

[•Form MT999 Message](#)

[•Swift Message Events To Generate Non Renewal Notification via MT799 Swift Message](#)

[•To Generate Non Renewal Notification via MT799 Swift Message](#)

Swift Message Events To Generate Non Renewal Notification via MT799 Swift Message



This script is used to generate non renewal notification through MT799 Swift Message

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Description
dcRefNum	DC reference number
advBankAddr1	Advising bank address
advBankAddr2	Advising bank address
advBankAddr3	Advising bank address
issueBankAddr1	Issuing Bank Address
issueBankAddr2	Issuing Bank Address.
issueBankAddr3	Issuing Bank Address.
nextExpiryDate	DC Expiry date after renewal
ApplicantName	Name of the Applicant
ApplicantAddr1	Applicant's Address
ApplicantAddr2	Applicant's Address
ApplicantAddr3	Applicant's Address
BeneficiaryName	Name of the beneficiary
BeneficiaryAddr1	Beneficiary's address

BeneficiaryAddr1	Beneficiary's address
BeneficiaryAddr1	Beneficiary's address
inOutInd	Indicates whether DC is inward or outward
dcAvailValue	Unutilized amount
advisingBank	Advising bank name
advisingBranch	Advising branch name
issuingBank	Issuing bank name
issuingBranch	Issuing branch name
currExpiryDate	Expiry date of DC
bodDate	Current date

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Description
BANCS.OUTPUT.SwiftMessage	Returns swift message

Typical Usage Scenario(s):

This script is called from following menus

1. BGRUDC
2. ODCM
3. IDCM

This script is called when autoRenewNxtCycleFlg is set to NO and BOD date is greater than or equal to decision date and less than or equal to drop dead date in IDCM and ODCM menu option. This script forms non renewal notification payment message by in turn calling

script MT999EventMapping.scr. Narrative field of MT799 swift message will contain non renewal notification details.

©Copyright Infosys Ltd.

To Generate Non Renewal Notification via Infosys[®] MT799 Swift Message



This script is used to generate non renewal notification through MT799 Swift Message.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Description
dcRefNum	DC reference number
advBankAddr1	Advising bank address
advBankAddr2	Advising bank address
advBankAddr3	Advising bank address
issueBankAddr1	Issuing Bank Address
issueBankAddr2	Issuing Bank Address.
issueBankAddr3	Issuing Bank Address.
nextExpiryDate	DC Expiry date after renewal
ApplicantName	Name of the Applicant
ApplicantAddr1	Applicant's Address
ApplicantAddr2	Applicant's Address
ApplicantAddr3	Applicant's Address
BeneficiaryName	Name of the beneficiary
BeneficiaryAddr1	Beneficiary's address
BeneficiaryAddr1	Beneficiary's address

BeneficiaryAddr1	Beneficiary's address
inOutInd	Indicates whether DC is inward or outward
dcAvailValue	Unutilized amount
advisingBank	Advising bank name
advisingBranch	Advising branch name
issuingBank	Issuing bank name
issuingBranch	Issuing branch name
currExpiryDate	Expiry date of DC
bodDate	Current date

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Description
BANCS.OUTPUT.SwiftMessage	Returns swift message

Typical Usage Scenario(s):

This script is called during amendment and general modification in IDCM or ODCM menu option, if following conditions are met

- 1)Auto Renew Next Cycle Field's value is changed from No to Yes and Decision Date is less than BOD.
- 2) System has sent prior Non Renewal Notification for the Current Auto Renewal Cycle.

This script forms Rescission Notification message by calling script MT999EventMapping.scr. Narrative field of MT799 swift message will contain Rescission Notification details.

©Copyright Infosys Ltd.

Finacle Copyright

TDS Related Scripts

The TDS related scripts are:

■ [Get TDS Amount Deducted for the Account](#)

■ [TDS Shortfall Error or Warning](#)

■ [TDS Recovery Script](#)

■ [TDS Upload Related Scripts](#)

©Copyright Infosys Ltd.

Term Loan Events

The Term Loan events are:

- [Amortize Loan Account Charges](#)
- [Auto Reschedule Loan Accounts](#)
- [Discounted Loan - Upfront Interest Calculation Interest Adjustment](#)
- [Collect Fee for Recovery after Charge Off Transaction](#)
- [Create Transaction for Problem Loan Account Debt Consolidation](#)
- [Create Transaction for Commercial Loan Account Deferred Interest Waiver](#)
- [Draw Down Transaction Creation](#)
- [Loans Rescheduling and Fee Assessment](#)
- [Create Transaction for Loan Fee Assessment and Collection](#)
- [Create Transaction for Loan Account Fee Consolidation](#)
- [Create Transactions for Interest Waiver](#)
- [Loan Account Late Fee Assessment](#)
- [Recovery After Charge Off Transactions - Liability Collection](#)
- [Recovery After Charge Off Transactions - Liability Reversal](#)
- [Loan Account Charge Off](#)
- [Create Transactions for Loan Account Payoff](#)
- [Sample Script to Compute Notice Fees for Loan Account Prepayment](#)
- [Loan Charge Transaction](#)

[Loan Demand Satisfaction](#)

[Create Transactions for Loan Disbursements](#)

[Create Loan Fee Refund Transaction](#)

[Create Loan Payment Transaction](#)

[Loans Rescheduling Transaction](#)

[Create Transaction to Mark Account as Past Due](#)

[Calculate Loan Account Pre-payment Fee](#)

[Collect Reversal Fee for Recovery after Charge Off Transaction](#)

[Discounted Loan - Upfront Interest Calculation Rescheduling and Rephasement](#)

[Reverse Loan Account Charge Off Transaction](#)

[Past Due Transaction Reversal](#)

[Loan Payoff Transaction Script](#)

[Permitted Prepayment Amount for the Account](#)

[Calculation of Settlement Amount according to CCA \(Customer Credit Act\) Formula](#)

[UIC Prepayment Loan Transaction](#)

©Copyright Infosys Ltd.

Permitted Prepayment Amount for the Account



Script Name:

The script `getPermittedPrepayAmt.scr` is provided for customization to the Bank. This script is called, only if it exists. It calculates the remaining permitted prepayment amount for the account. It must be placed in `TBA_SCRIPTS` directory.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
<code>loanAmt</code>	Loan amount is the sanction limit for particular scheme.
<code>totalPaidAmt</code>	Total paid amount for the account.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
<code>remainingAmt</code>	This is the remaining calculated prepayment amount.

Default Logic:

If Script does not exist normal c functions will be called for calculation.

Typical Usage Scenario:

This script will be called during account inquiry (provided script exists) for HLNGI, HLPREPH, HLAUPY menu.

Example:

NA

©Copyright Infosys Ltd.

Calculation of Settlement Amount according to CCA (Customer Credit Act) Formula



Script Name:

The script LoanPayoffCCAFormula.scr is provided for calculation of settlement amount according to CCA (Customer Credit Account) formula. This script is called, only if the Cca Regulated Flag value is selected as 'Y' in the criteria page of HPAYOFF.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
InTenorInMonths	This field contains the loan tenor in months.
apr	This field contains the apr rate.
setlMntReqDate	The date on which the payoff is requested.
graceDays	This is the grace period set at scheme level.
extnPeriodMnth	This is the extension period set at scheme level.
extnPeriodDays	This is the extension period set at scheme level.
noOfDaysInYear	The number of days in a year set at scheme level.
disbRecCount	The number disbursements to the customer account.
DisbAmt	The disbursement amount.

DisbDate	The disbursement date related to DisbAmt amount.
collRecCount	The number of repayments made by customer.
RepymtAmt	The repayment amount.
RepymtDate	The repayment date related to RepymtAmt amount.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
settlemntDate	This is the settlement date arrived at after adding graceDays, extnPeriodMnths and extnPeriodDays.
settlementAmt	This is the settlement amount arrived at as per the CCA formula.
totalAmtPaidTillDate	This is the total amount paid by the customer till date.

Default Logic:

This script is mandatory in case the Cca Regulated flag is selected as “Y” in the HPAYOFF criteria screen.

Typical Usage Scenario:

This script will be called when the Cca Regulated flag is selected as “Y” in the criteria page of HPAYOFF for calculating the early settlement amount as per the CCA formula.

Example:

NA

Trade Finance Events

The Trade Finance events are:

[Determine Contingent Accounts in DCS and BGS](#)

[Define HIRM Inward Processing](#)

[Validate ACH History Details](#)

[Populate FBM details with Swift Message](#)

[Get the Currency Position](#)

[Populate HIRM details From Swift Message](#)

[Populate the Values for HIRM Service](#)

[Populate Default Values for 202 Message](#)

[Create Contingent Transactions](#)

[CreateWFItemforBM](#)

[Create Transaction for HECGCRPC Calculation](#)

[Euro Message Details](#)

[Validating Commodity for Disbursements](#)

[GMM Shipping Guarantee Details](#)

[Script for User Action \(User Additional Details\)](#)

[Check Customer Eligibility to Open RPC Account](#)

[Combined TC and Currency Processing in ORM](#)

Transaction Events

The types of Transaction events are:

[Finacle Transaction Creation Events](#)

[MTT Events](#)

The different Transaction events are:

[Account Lien Maintenance](#)

[Check and Display Account Balance](#)

[Check Part Transaction](#)

[Define Reversal Transaction](#)

[Define Transaction for Scheme Code Transfer](#)

[Define Transaction for SOL Transfer](#)

[Create Transaction for Suspense Account](#)

[Mask GL Subhead Transaction](#)

[Create Debit Authorisation Charge Transaction](#)

[Display Vostro Transfer Transaction](#)

[Fee Amortization](#)

[Clearing Transactions](#)

[Validate FTI Criteria](#)

[Get CYC Rate Codes from Scripts](#)

[Get GCT Home Currency Code and Rate Codes from Scripts](#)

[Instruments Regularization when Shadow Balance is Y](#)

[Script to Create Transactions for Advance Interest Type of Loan Accounts](#)

[Create Contingent Transaction for PDCs](#)

[Other Financial Transactions](#)

[Part Transaction Request Post](#)

[Define Insurance Financial Transaction](#)

[RPCTM Transaction Creation](#)

[DDSL - Draw Down Syndicated Loan](#)

[Transactions Through HTM](#)

[User Additional Detail Display](#)

[Utilization of Limits](#)

[Interest Reversal](#)

[Revocation](#)

[Script to Customize DTD Transaction Remarks](#)

[Notice Saver Debit Transaction](#)

[Foreign Bills Event Transactions Script](#)

[Creating a Transaction in Transaction Details Tab During Account Opening for TD Type of Accounts](#)

[Script for handling Customer Provisioning Transactions](#)

[Post Query for DTDI](#)

[Populate Transaction Source and Lien Resource Code](#)

[Transfer Transaction](#)

[Create Balancing Transaction during Download](#)

[Script Hook for Foreign Cheques Collection Transaction Creation](#)

[Customize DTD Transaction Remarks](#)

HTM – Validate Cheque Suspected To Exist

[Check HCRT PTran Reversal required](#)

[Check Charge PartTran For File Reversal](#)

[Statement Generation of those Accounts which had no Transactions in a Set Period](#)

[String Field Population before Posting of Transaction in DTD Table](#)

©Copyright Infosys Ltd.

Creation of Contingent Revaluation Transaction



The script **ContRevalTran.scr** is a product script provided for Contingent Revaluation and must be present in \$TBA_SCRIPTS folder.

The script will be used to create contingent revaluation transaction using input passed.

Input:

The defined input is available in a repository called MTT, in a class called TranDetails with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
MTT.TranDetails.TranDate	Transaction Date
MTT.TranDetails.TranType	Transaction Type
MTT.TranDetails.TranSubType	TranSubType
MTT.TranDetails.Remarks	Remarks
MTT.TranDetails.IgnoreExcp	IgnoreExcp
MTT.TranDetails.Consolidate	Consolidate
MTT.TranDetails.PrintAdviceInd	PrintAdviceInd
MTT.TranDetails.TranID	Transaction ID
MTT.PartTranDetails.RefAmount	RefAmount
MTT.PartTranDetails.Account	Account Number
MTT.PartTranDetails.RefCurrency	Ref Currency
MTT.PartTranDetails.TranCurrency	Transaction Currency

MTT.PartTranDetails.ValueDate	Value Date
MTT.PartTranDetails.ACPARTB2kId	AC PART B2k Id
MTT.PartTranDetails.ACPARTB2kType	ACPARTB2kType= "FBILL "
MTT.PartTranDetails.RateCode	Rate Code
MTT.PartTranDetails.Rate	Rate
MTT.PartTranDetails.Refnum	Reference number
MTT.PartTranDetails.ReportCode	Report Code
MTT.PartTranDetails.CustomerId	CustomerId
MTT.PartTranDetails.Particulars	Particulars
MTT.PartTranDetails.EntryUserId	Entry User Id
MTT.PartTranDetails.TreaRate	Treasury Rate
MTT.PartTranDetails.TreaRefNum	Treasury Reference Number
MTT.PartTranDetails.Consolidate	Consolidate flag
MTT.PartTranDetails.PTranBusinessType	PTranBusinessType="FBILL"
MTT.PartTranDetails.TranIdentifier	TranIdentifier = "FXBILLS"
MTT.ContingentDetails.TranMode	Tran Mode
MTT.ContingentDetails.EntityOperation	Entity Operation
MTT.ContingentDetails.EntityB2kId	Entity B2kId
MTT.ContingentDetails.EntityB2kType	Entity B2kType (FBILL\REMIT\DOCCR\BNKGR)
MTT.ContingentDetails.EntityNumber	Entity Number
MTT.ContingentDetails.EntitySolId	Entity SolId
MTT.ContingentDetails.EntityCurrency	Entity Currency
MTT.ContingentDetails.LiabDebitAcct	LiabDebitAcct
MTT.ContingentDetails.LiabCreditAcct	Liab Credit Acct
MTT.ContingentDetails.Amount	Amount(This amount should be in contingent Currency)
MTT.ContingentDetails.Currency	Currency(this currency will be contingent currency)
MTT.ContingentDetails.RateCode	Rate Code

MTT.ContingentDetails.Rate	Rate
MTT.ContingentDetails.EventAmount	Event Amount(This amount should be in entity currency)

Output:

Output not present

Sample Script:

The script is available in the \$TBA_SCRIPTS directory.

Default Logic:

If the script ContRevalTran.scr is not present then error message script [ContRevalTran.scr] does not exist thrown to the front-end Script.

Typical Usage Scenario(s):

This script will be called from the CXX sources.

©Copyright Infosys Ltd.

Commission Confirmation Transaction Creation



Script Name:

The script `mfTCommSettlementMTT.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to create the `mtt` financial transactions for confirmation of the commission id for trailer commission.

Input:

The defined input is available in a repository called `MTT`, in a class called `InputDetails` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

Field Name	Details
<code>MTT.InputDetails.TranType</code>	Transaction type will be transferred.
<code>MTT.InputDetails.TranSubType</code>	Transaction sub type will be bank induced.
<code>MTT.InputDetails.TranForacid</code>	Placeholders for respective payments. Income suspense PH and receivable suspense PH.
<code>MTT.InputDetails.DrCrInd</code>	Is the transaction debit or credit.
<code>MTT.InputDetails.TranAmt</code>	Confirmation amount for which the transaction is created.
<code>MTT.InputDetails.TranCrncy</code>	Currency for the transaction amount.
<code>MTT.InputDetails.RateApplied</code>	Rate applied (for future use).
<code>MTT.InputDetails.RateCodeApplied</code>	Rate Code applied (for future use).
<code>MTT.InputDetails.TranRemarks</code>	Commission Id.
<code>MTT.InputDetails.TranParticulars</code>	PH details + Fund Id + Commission id.
<code>MTT.InputDetails.ValueDate</code>	Date on which transaction got created.

MTT.InputDetails.TranEventType	MFTCC.
MTT.InputDetails.Remarks	Commission Id.

Output:

The output of the script will be available in the specified repository fields:

Field Name	Details
BANCS.OUTPUT.successOrFailure	Is the transaction creation success or failure.
BANCS.OUTPUT.scriptError	Error message if any which the bank wants to get in the report.

Default Logic:

NA

Typical Usage Scenario:

Script will get executed, if financial transactions are created during the confirmation, reversal or settlement events in the mutual fund trailer commission.

Example:

NA

©Copyright Infosys Ltd.

Foreign Bill Transactions



Script Name:

B2K_FxBillEventTransaction.scr

Description:

The script B2K_FxBillEventTransaction.scr is used to set up the MTT for foreign bill transaction. The script must be present in TBA_SCRIPTS directory.

Inputs:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned. You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Description
MTT.InputDetails.inwardOutwardInd	
MTT.InputDetails.entitySolId	
MTT.InputDetails.moduleId	
MTT.InputDetails.entityBillId	
MTT.InputDetails.billParamType	
MTT.InputDetails.homeCCY	
MTT.InputDetails.purchaseFlg	
MTT.InputDetails.remitType	
MTT.InputDetails.bpLiab	
MTT.InputDetails.delinkCrncy	
MTT.InputDetails.bpLiabCrncy	
MTT.InputDetails.billCrncy	
MTT.InputDetails.cifId	

MTT.InputDetails.operAcct	
MTT.InputDetails.chrgAcct	
MTT.InputDetails.rlzAcct	
MTT.InputDetails.purchAcct	
MTT.InputDetails.delinkAcct	
MTT.InputDetails.bpAcct	
MTT.InputDetails.nostroAcctNum	
MTT.InputDetails.eventAmt	
MTT.InputDetails.nostroAmt	
MTT.InputDetails.eefcRealAmt	
MTT.InputDetails.billAmt	
MTT.InputDetails.instrTotAmt	
MTT.InputDetails.valueDate	
MTT.InputDetails.bodDate	
MTT.InputDetails.dueDate	
MTT.InputDetails.delinkedDate	
MTT.InputDetails.eventRateCode	
MTT.InputDetails.notConvRateCode	
MTT.InputDetails.purposeOfRemit	
MTT.InputDetails.collFcChrg	
MTT.InputDetails.frgnBankChrgs	
MTT.InputDetails.chrgEventId	
MTT.InputDetails.consolidateFlg	
MTT.InputDetails.consolBacid	
MTT.InputDetails.currStatus	
MTT.InputDetails.billStatus	
MTT.InputDetails.tranId	
MTT.InputDetails.contAmt	
MTT.InputDetails.drCrFlg	

MTT.InputDetails.acctType	
MTT.InputDetails.TranAccount	
MTT.InputDetails.TranForacid	
MTT.InputDetails.schmCode	
MTT.InputDetails.isDDAcct	
MTT.InputDetails.DDBankCode	
MTT.InputDetails.DDBrCode	
MTT.InputDetails.DDPayeeName	
MTT.InputDetails.refCcy	
MTT.InputDetails.refAmt	
MTT.InputDetails.partyToCharge	
MTT.InputDetails.fwdCntrctSolld	
MTT.InputDetails.fwdCntrctNum	
MTT.InputDetails.refTranId	
MTT.InputDetails.refTranDate	
MTT.InputDetails.refPartTranSrlNum	
MTT.InputDetails.instrmntType	
MTT.InputDetails.instrmntAlpha	
MTT.InputDetails.instrmntNum	
MTT.InputDetails.instrmntDate	
MTT.InputDetails.treasRateCode	
MTT.InputDetails.treasRate	
MTT.InputDetails.rateCode	
MTT.InputDetails.rate	
MTT.InputDetails.tranAmt	
MTT.InputDetails.tranCcy	
MTT.InputDetails.tranPartCode	
MTT.InputDetails.tranPartcls	
MTT.InputDetails.valueDate	

MTT.InputDetails.rptCode	
MTT.InputDetails.schmCode	
MTT.InputDetails.isInland	

Output:

The output of the script is available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Description
BANCS.OUTPUT.successOrFailure	
BANCS.OUTPUT.scriptError	

Default Logic:

NA

Typical Usage Scenario:

NA

Example:

NA

©Copyright Infosys Ltd.

UCT– Create Upload Charge Transaction



The script createUpIChrgTran.scr should be present in TBA_SCRIPTS directory. This script is used to create charge transactions from external system uploaded through UCT menu.

Inputs Available in the Scripts

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS. INPUT. <Fieldname>

Script Input	Description
TranType	This field will be populated to MTT TranDetails structure
TranSubType	This field will be populated to MTT TranDetails structure
TranRemarks	This field will be populated to MTT TranDetails structure
ExceptionFlg	This field will be populated to MTT TranDetails structure
InitSolId	This field will be populated to MTT TranDetails structure
EventType	This field will be populated to MTT TranDetails structure
ChrgDrAccountId	This field will be populated to MTT PartTranDetails structure
ChrgCrAccountId	This field will be populated to MTT PartTranDetails structure
AccountId	This field will be populated to MTT PartTranDetails structure
ChargeAmount	This field will be populated to MTT PartTranDetails structure
DrCrInd	This field will be populated to MTT PartTranDetails structure
StartDate	This field will be populated to MTT PartTranDetails structure
EndDate	This field will be populated to MTT PartTranDetails structure
ChargeCrncy	This field will be populated to MTT PartTranDetails structure
RateCode	This field will be populated to MTT PartTranDetails structure

Particulars	This field will be populated to MTT PartTranDetails structure
TranParticularsCode	This field will be populated to MTT PartTranDetails structure
ValueDateDiff	This field will be populated to MTT PartTranDetails structure
EventId	This field will be populated to MTT ChargeDetails structure
DfltChrgCalcFlg	This field will be populated to MTT ChargeDetails structure
RelPricingRefNum	This field will be populated to MTT ChargeDetails structure
AmountWithoutDiscount	This field will be populated to MTT ChargeDetails structure
CifId	This field will be populated to MTT ChargeDetails structure
CompB2kId	This field will be populated to MTT ChargeDetails structure
CompB2kIdType	This field will be populated to MTT ChargeDetails structure
PTranBusType	This field will be populated to MTT ChargeDetails structure
ModifyFlg	This field will be populated to MTT ChargeDetails structure
LinkedChrgCrAcct	This field will be populated to MTT PartTranDetails structure
LinkedChrgRateCode	This field will be populated to MTT PartTranDetails structure
LinkedChrgCrncyCode	This field will be populated to MTT PartTranDetails structure
LinkedModifyFlg	This field will be populated to MTT PartTranDetails structure
LinkedPTranBusType	This field will be populated to MTT PartTranDetails structure

Output Expected

The defined outputs are available in repository BANCS, class OUTPUT and with the field names mentioned below. One can access the outputs by referring the fields in the following manner.

BANCS. OUTPUT. <Fieldname>

Script Input	Description
successOrFailure	Success or Failure Flag
scriptError	Populates the error message

Default logic in case script is not present

If the script is not present charge transaction will not be created through UCT menu.

Typical usage scenario(s)

This script will be called before inserting record to CXL table when charge from external system is being uploaded.

Sample Script

Since it is a product script no sample script present.

©Copyright Infosys Ltd.

Create Acct Closure Transaction while tran type is C or T



Script Name:

closureTran.scr

Description:

The script closureTran.scr should be present in TBA_SCRIPTS directory.

It can handle two additional transaction creation logic for revolving overdraft account closure if non capitalized fee and interest is routed through office account. Transaction type for closure event either CASH or TRANSFER

Inputs:

The following inputs were added to the MTT repository, class InputDetails and with the field names mentioned below.

Field Name	Description
feeCrAcct	Foracid to credit fee amount
feeCollAmt	Actual fee amount to be debited from ROD acct and credited to office account
intCrAcct	Foracid to credit interest amount
intCollAmt	Actual interest amount to be debited from ROD acct and credited to office account

Output:

It will define part tran separately for fees and interest amount based on the input parameters we pass.

Default Logic:

This is a product script, so should be present always.

Typical Usage Scenario:

This script will be called when operative accounts are closed with xferbalfg = 'Y' and transaction type is either T-transfer or C-cash.

Additional part-trans would be created for interest and fee amount if the account is of revolving OD type and interest or fees routed through office accounts.

Sample Script

Sample script *closureTran.scr* is present in the TBA_SCRIPTS directory.

©Copyright Infosys Ltd.

Create Acct Closure Transaction while tran type is B



Script Name:

closureTranForCashAndTransf.scr

Description:

The script closureTranForCashAndTransf.scr, should be present in TBA_SCRIPTS directory.

It can handle two additional transaction creation logic for revolving overdraft account closure if non capitalized fee and interest is routed through office account. Transaction type for closure event BOTH.

Inputs:

The following inputs were added to the MTT repository, class InputDetails and with the field names mentioned below.

Field Name	Description
feeCrAcct	Foracid to credit fee amount
feeCollAmt	Actual fee amount to be debited from ROD acct and credited to office account
intCrAcct	Foracid to credit interest amount
intCollAmt	Actual interest amount to be debited from ROD acct and credited to office account

Output:

It will define part tran separately for fees and interest amount based on the input parameters we pass.

Default Logic:

This is a product script, so should be present always.

Typical Usage Scenario:

This script will be called when operative accounts are closed with xferbalfg = 'Y' and transaction type is B-BOTH.

Additional part-trans would be created for interest and fee amount if the account is of revolving OD type and interest or fees routed through office accounts.

Sample Script

Sample script *closureTranForCashAndTransf.scr* is present in the TBA_SCRIPTS directory.

©Copyright Infosys Ltd.

Create Transaction for Transferring the Fee and Interest (outstanding amounts to target scheme from source scheme)



Script Name:

createSchemeTranForAccount.scr

Description:

The script createSchemeTranForAccount.scr should be present in TBA_SCRIPTS directory.

These scripts are used to create transactions for transferring the fee and interest outstanding amounts to target scheme from source scheme.

Inputs:

The defined inputs are available in repository MTT, class InputDetails and with the field names mentioned below. You can access the inputs by referring the fields in the following manner:

MTT.InputDetails.<Fieldname>

Field Name	Description
rodFeeSourceAcct	Foracid to credit fee amount
rodFeeTargetAcct	Foracid to debit fee amount
rodFeeTranAmt	Actual fee amount
rodFeeTranCrcncy	Fee currency
rodIntSourceAcct	Foracid to credit interest amount
rodIntTargetAcct	Foracid to debit interest amount
rodIntTranAmt	Actual interest amount
rodIntTranCrcncy	Interest currency

Output:

It will define part tran separately for fees and interest amount while we transfer account from one scheme to another scheme based on the input parameters we pass.

Default Logic:

This is a product script, so should be present always.

Typical Usage Scenario:

This script will be called when account is transferred from one scheme to another scheme.

Additional part-trans would be created for interest and fee amount if the account is of revolving OD type and interest or fees routed through office accounts.

Sample Script

Sample script *createSchemeTranForAccount.scr* is present in the TBA_SCRIPTS directory.

©Copyright Infosys Ltd.

Create Transaction for Transferring the Fee and Interest (outstanding amounts to target SOL from source SOL)



Script Name:

createsolxfrtran.scr

Description:

The script createsolxfrtran.scr should be present in TBA_SCRIPTS directory.

These scripts are used to create transactions for transferring the fee and interest outstanding amounts to target SOL from source SOL.

Inputs:

The defined inputs are available in repository MTT, class InputDetails and with the field names mentioned below. One can access the inputs by referring the fields in the following manner:

MTT.InputDetails..<Fieldname>

Field Name	Description
sourceRodIntAcct	Foracid to credit fee amount
targetRodIntAcct	Foracid to debit fee amount
rodIntTranAmt	Interest amount
rodIntTranCrcny	Interest currency
sourceRodFeeAcct	Foracid to credit fee amount
targetRodFeeAcct	Foracid to debit fee amount
rodFeeTranAmt	Fee amount
rodFeeTranCrcny	Fee currency

Output:

It will define part tran separately for fees and interest amount while we transfer account from one sol to another sol based on the input parameters we pass.

Default Logic:

This is a product script, so should be present always.

Typical Usage Scenario:

This script will be called when account is transferred from one sol to another SOL.

Additional part-trans would be created for interest and fee amount if the account is of revolving OD type and interest or fees routed through office accounts.

Sample Script

Sample script *createsolxfrtran.scr* is present in the TBA_SCRIPTS directory.

©Copyright Infosys Ltd.

Check HCRT PTran Reversal required



Script Name:

The script `checkHCRTPTTranRevReqd.scr` must be present in `TBA_SCRIPTS` directory. This script is used to identify the charge part trans and to decide whether to reverse it or not based in recall induced by set at paysys.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. partTranSrlNum	Indicates the Serial Number of the respective Part Tran.
BANCS.INPUT. tranId	Indicates the Transaction Id to be reversed.
BANCS.INPUT. tranAmt	Indicates the Amount to be reversed.
BANCS.INPUT. orgAcct	Indicates the Originator Account.
BANCS.INPUT. tranDate	Indicates the Date of Transaction.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT. ReversePTranFlg	Flag to identify whether the partTran is to be reversed or not.
BANCS.OUTPUT. IsChrgPartTran	Flag to identify whether the PartTran is a charge PartTran.

Typical Usage Scenario:

This script is used to check whether the part tran is charge part tran and whether it has to be reversed or not .

©Copyright Infosys Ltd.

Check Charge PartTran For File Reversal



Script Name:

The script checkChrgPartTranForFileReversal.scr must be present in TBA_SCRIPTS directory. This script will be used to decide whether the respective PartTran is a Charge PartTran.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. partTranSrlNum	Indicates Serial Number of the respective PartTran.
BANCS.INPUT. tranId	Identifies the paysysId used for execution.
BANCS.INPUT. tranAmt	Indicates the Amount to be reversed.
BANCS.INPUT. orgAcct	Indicates the Originator Account.
BANCS.INPUT. tranDate	Indicates the Date of Transaction.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>



Field Name	Details
BANCS.OUTPUT. ReversePTranFlg	Flag to identify whether the partTran is to be reversed or not.
BANCS.OUTPUT. IsChrgPartTran	Flag to identify whether the PartTran is a charge PartTran.

Typical Usage Scenario:

This script is used to check whether the part tran is charge part tran or not.

©Copyright Infosys Ltd.

Statement Generation of those Accounts which had no Transactions in a Set Period



Script Name:

A custom logic can be written in the script PSPAcctSkipCustomList.scr to force batch statement generation of only those accounts which had no transactions in a set period. The script must be present in TBA_SCRIPTS directory.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.foracid	Account ID.
BANCS.INPUT.low_tran_date	Statement Generation From Date.
BANCS.INPUT.high_tran_date	Statement Generation To Date.
BANCS.INPUT.last_tran_date	Last Transaction Date.
BANCS.INPUT.ps_last_prnt_time	Last statement Print time.
BANCS.INPUT.last_any_tran_date	Transaction date of latest transaction of any type.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT. acct_exists	The script hook will check that the account being processed does not exist in PSP_TMP and will pass a flag as 'Y' and 'N'.

Default logic:

In case script is not present, then HPSP will not check records in PSP_TMP table and will not have any impact on pass sheet printing.

Typical usage scenario(s) :

Script Hook is called to enable the processing based on CustomerListId

Example:

NA

©Copyright Infosys Ltd.

String Field Population before Posting of Transaction in DTD Table



Script Name:

A script hook, `prepareDtdGLSegmentString.scr` is provided to populate the string field before posting of transaction in DTD table. It must be placed in `TBA_SCRIPTS` directory.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Description
BANCS.INPUT.tranDate	The date on which the transaction was created.
BANCS.INPUT.tranId	The transaction identifier of the transaction. This is unique for a given day.
BANCS.INPUT.partTranSrINum	The identifier of the part transaction.
BANCS.INPUT.tranType	Indicates whether transaction type is CASH, CLEARING or TRANSFER.
BANCS.INPUT.tranSubType	Indicates whether it is Normal Payment, Normal Receipt, Customer Induced etc.
BANCS.INPUT.partTranType	Indicates whether the part transaction is Debit or Credit type.
BANCS.INPUT.glSubHeadCode	General ledger sub head of the account on which the part transaction is created.
BANCS.INPUT.acid	The account on which the part transaction is created.
BANCS.INPUT.valueDate	The date from which the transaction is effective.

BANCS.INPUT.tranAmt	The amount for which the transaction is created.
BANCS.INPUT.tranParticular	Field provided for entering particulars of transaction.
BANCS.INPUT.entryDate	The date on which the part transaction is entered.
BANCS.INPUT.pstdDate	The date on which the part transaction is posted.
BANCS.INPUT.vfdDate	The date on which the part transaction is verified.
BANCS.INPUT.rptCode	The report code of the report on which the transaction will get reflected.
BANCS.INPUT.refNum	The reference number of the part transaction.
BANCS.INPUT.instrmntType	The instrument type of the instrument which drives the transaction.
BANCS.INPUT.instrmntDate	The instrument date of the instrument.
BANCS.INPUT.instrmntNum	The instrument number of the instrument.
BANCS.INPUT.instrmntAlpha	The instrument alpha of the instrument.
BANCS.INPUT.tranRmks	Field for entering any remarks that the user wants to enter. This is an information for the bank for office purpose.
BANCS.INPUT.pstdFlg	Indicates whether the part transaction is already posted.
BANCS.INPUT.amtReservationInd	Indicates why the system has reserved the amount.
BANCS.INPUT.ReservationAmt	This is the amount reserved by the system which is not available for withdrawal.
BANCS.INPUT.custId	The customer to which the account belongs.
BANCS.INPUT.voucherPrintFlg	Whether voucher to be printed for the part transaction.
BANCS.INPUT.moduleId	The module which created the transaction for example, FFD, BILLS, FOREX.
BANCS.INPUT.brCode	The branch code of the originating or responding branch of transaction.
BANCS.INPUT.rateCode	The rate code from which the rate is derived.
BANCS.INPUT.rate	The conversion rate for the transaction involving multi currencies.

BANCS.INPUT.crncyCode	The currency code of the account for FCNR accounts
BANCS.INPUT.tranCrncyCode	The part transaction currency.
BANCS.INPUT.refCrncyCode	The transaction currency of the part transaction which initiates the transaction.
BANCS.INPUT.refAmt	The transaction amount of the initiating part transaction.
BANCS.INPUT.solld	The sol id of the account on which the part transaction is created.
BANCS.INPUT.bankCode	The bank code of the originating or responding branch of transaction.
BANCS.INPUT.treaRefNum	The reference number of the rate given by the treasury.
BANCS.INPUT.treaRate	The rate at which the treasury is willing to buy or sell the currency to the branch.
BANCS.INPUT.liftLienFlg	If this flag is set to Y, then based on LPT (lien part transaction table) lien will be lifted from the account.
BANCS.INPUT.proxyPostInd	It indicates whether proxy posting will be enabled. Valid value are P - normal post, Y - proxy post, B -both.
BANCS.INPUT.siSrINum	This is to identify the SI number due to which the particular part transaction is created.
BANCS.INPUT.siOrgExecDate	This is required to differentiate between the transactions created by the SI on the due date, and the transactions created by carried forward SIs.
BANCS.INPUT.prSrINum	This field along with serial_num identifies the source payment or receipt record of the part transaction.
BANCS.INPUT.serialNum	This field along with pr_srl_num identifies the source payment or receipt record of the part transaction.
BANCS.INPUT.delMemoPad	This field will indicate to the posting service that the memo pad associated to an account due to a part transaction has to be deleted.
BANCS.INPUT.uadModuleId	This is the key field of User Additional Detail table.
BANCS.INPUT.reversalDate	This is the date on which reversal of a proxy transaction happened.

BANCS.INPUT.reversalValueDate	This is the value date for reversal. It will be used in interest calculation.
BANCS.INPUT.pttmEventType	It stores the charge event identifier.
BANCS.INPUT.proxyAcid	This the acid which will be used at the time of reversal of proxy posted transaction.
BANCS.INPUT.todEntityType	It stores the Key field for Instant TOD (ITD Table) which is being granted during transaction.
BANCS.INPUT.todEntityId	It stores the Key field for Instant TOD (ITD Table) which is being granted during transaction.
BANCS.INPUT.dthInitSolId	It stores the intializing sol id of DTH.
BANCS.INPUT.regularizationAmt	This is the amount for which FFD has to be debited during FFD regularisation.
BANCS.INPUT.principalPortionAmt	It stores the principal portion in the transaction amount during TD part closure.
BANCS.INPUT.tfEntitySolId	Field added to enable centralization for trading account.
BANCS.INPUT.tranParticular2	Field provided for entering additional particulars of transaction in native language. This is the information for the customer for their information and goes to the customer with their statements.
BANCS.INPUT.tranParticularCode	This field will hold the transaction particular code.
BANCS.INPUT.trStatus	This is required to track whether FT processing is done for this transaction or not.
BANCS.INPUT.svsTranId	This field holds the SVS transaction id being generated after signature verification.
BANCS.INPUT.crncyHolChkDoneFlg	Indicates whether the currency holiday check has been done or not.
BANCS.INPUT.referralId	Referral Id which got generated during Referral submission.
BANCS.INPUT.partyCode	Code for capturing non customer id.
BANCS.INPUT.glDate	The gl date is the business date of the sol to which the acid of the prntransaction belongs.
BANCS.INPUT.bkdtTranFlg	Indicates whether the part transaction is back dated or not.

BANCS.INPUT.implCashPartTranFlg	Indicates whether the part transaction is Implicit Cash Part transaction or not.
BANCS.INPUT.ptranChrgExistsFlg	This flag will indicate whether charge part Transaction exists.
BANCS.INPUT.entryUserId	The user who has entered this part transaction.
BANCS.INPUT.pstdUserId	The user who has posted this part transaction.
BANCS.INPUT.vfdUserId	The user who has verified this part transaction.
BANCS.INPUT.tranCreMode	Indicates whether transaction creation is done in Online or Batch mode.
BANCS.INPUT.restrictModifyInd	This is an indicator which defines, what values can be modified after the transaction is created.
BANCS.INPUT.remarks	Field for entering any remarks that the user wants to enter. This is an information for the bank for office purpose.
BANCS.INPUT.pstFlg	Purchase Sale Flag.
BANCS.INPUT.deliveryChannelId	Delivery channel which created the transaction. For example, CDCI or FAB.
BANCS.INPUT.initSolId	Service Outlet identifier of the sol which initiated the transaction.
BANCS.INPUT.ignoreXcpnFlg	Whether the exceptions have to be ignored in batch mode. Valid Values are C - consider the exceptions and I - Ignore the exceptions.
BANCS.INPUT.b2kEventType	Event which created the transaction. For example, Outward Clearing, DDIssue, DDPayment.
BANCS.INPUT.referralEventType	Event type added to capture the event of a particular transaction under referral project.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
GLSegmentSring	The script hook will populate this string.

Default Logic:

If Script does not exist normal c functions will be called for calculation.

Typical Usage Scenario:

Script Hook is called from posting of transaction.

Example:

NA

©Copyright Infosys Ltd.

Loans Upload



The available Loan uploads are:

[Fee and Amortization Details Upload](#)

[Delinquency Details Upload](#)

[Document Details Upload](#)

[Loans Account Master Upload](#)

[Loans Additional Details Upload](#)

[Loans Transaction Upload](#)

[Principal Demand and Late Fee Upload](#)

[Schedule Balance Upload](#)

©Copyright Infosys Ltd.

Salary Upload Events



The Salary Upload events are:

[Bill Recovery during Salary Upload](#)

[Customize Input Values for Salary Upload](#)

[Salary Upload for Lien Processing](#)

©Copyright Infosys Ltd.

Validations for Uploading Debit Balance Limit



Script Name:

The script valDrBalLimUpl.scr is used to provide additional validations for uploading the debit balance limit for given account. Based on the validation present in script, proper message is returned back. It returns an error message, in case validation fails and It returns a success message, in case of successful validation.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
forAcid	The foracid for which the debit balance limit has to be uploaded.
drBalLimit	The debit balance limit to be uploaded.

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
successOrFailure	Valid Values are S /F. If the record clears the custom validation, then "S" will be returned. If the record does not clear the custom validation, then "F" will be

	returned.
errorMsg	If foracid and drBalLimit provided in upload file fails the custom validation provided in script, then a proper error message is returned from the script.
Remarks	If foracid and drBalLimit provided in upload file clears the custom validation provided in script, then remarks is returned from the script.

Default Logic:

In case script is not present, then debit balance limit will be uploaded only for valid accounts belonging to SB, CC, CA and OD scheme types and accounts which are not closed, that is when their acct_cls_flg field in GAM table is N. Only valid amount is allowed to be uploaded for debit balance limit.

Typical Usage Scenario:

Script Hook is provided for additional validations during upload.

Example:

NA

©Copyright Infosys Ltd.

Outward Clearing Data Upload Duplicate Check



Description:

The script doFileUploadChk.scr must be present in TBA_SCRIPTS directory.

This script is used to check whether file upload has been done for Similar Zone Code, Zone Date or Zone Currency, or MICR Flag combination.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
UPLD_ZONE_CODE	Code of the zone for which the outward clearing data is to be uploaded
UPLD_ZONE_DATE	Date of the zone for which outward clearing data is to be uploaded
UPLD_CRNCY_CODE	Currency Code of the Zone
UPLD_MICR_FLG	Micr flag
UPLD_CHK_FLG	Upload check flag

Output:

This script decides whether file upload has been done for Similar Zone Code, Zone Date, Zone Crncy, or MICR Flag combination.

Default logic:

No default logic in the absence of the script.

Typical Usage scenario:

The script is used to decide whether file upload has been done for Similar Zone Code, Zone Date, Zone Crncy, or MICR Flag combination.

©Copyright Infosys Ltd.

Validation Events

The Validation events are:

- [Customization of Validations](#)
- [Validate Customer Listing Criteria1](#)
- [Validate Customer Listing Criteria2](#)
- [Validate Beneficiary Account Details](#)
- [Validate BIC payment](#)
- [Check Whether the account is Finacle or Non-Finacle](#)
- [Check whether the DA account is finacle or N-n_finacle](#)
- [Validation of Limit Node Details](#)
- [Validate LSD Criteria](#)
- [Check for Menu Validity](#)
- [Validate Account Fields](#)
- [Validate NUM details](#)
- [Check Black List Status](#)
- [Check Cutoff Time status](#)
- [Check for Mandatory of HPTV Fields](#)
- [Validate HRRCDM Criteria](#)

- [Amount Calculation Script](#)
- [Validate the Number of Days for Months in General Calendar Mapping Maintenance](#)
- [Validate DD Payment Record to be Uploaded](#)
- [Validating HLNREV Menu Option Fields](#)
- [Validating HPULN Menu Option Fields](#)
- [Validating HPULNTH Menu Option Fields](#)
- [Validating HRLH Menu Option Fields](#)
- [Validation for Batch Deferment](#)
- METS/UEE – Maintain Escheatments/Upload For Escheatment
- [SCD Modulus Check For ACHODCL/ACHODRL](#)
- [SCD validation script for HACHODCL/HACHODRL](#)
- [validateMT202CV.scr](#)
- [SCD validation script for HACHORP](#)
- [BACS Validate ISCD MC For TD](#)
- [BACS Validate ISCD for TD](#)
- [BACS-Validate ISCD/MC for CMCMTM](#)
- [BACS-Validate ISCD/MC for CMMTRR](#)
- [BACS-Validate ISCD/MC for HGARFG/HGARFR](#)
- [BACS-validate ISCD for CMCMTM menu](#)

● [BACS-validate ISCD for CMMTRR menu](#)

● [BACS-validate ISCD for HGARFG/HGARFR menus](#)

● [NDT Sort Code Validation](#)

● [Commission ID Confirmation](#)

● [Validate SFMS Message](#)

● [RE_ValAddnlExtraCnd.scr](#)

©Copyright Infosys Ltd.

ISCD Modulus Check For ACHODCL/ACHODRL



Script Name:

BACS_validateISCDMCFForACHODCLRL.sscr:

This script performs ISCD Modulus Check Validations for the menu HACHODCL and HACHODRL. The script must be present in TBA_SCRIPTS directory.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. PaysysId	The Paysys Id
BANCS.INPUT. BicId	Bank Identifier Code (BIC)
BANCS.INPUT. RecvAcctDtIs	Receiver Account
BANCS.INPUT. AcctNumber	Receiver acct to be input to called script
BANCS.INPUT. SortCode	Receiver Bic to be input to called script

Output:

The output of the script will be available in the specified repository

fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.errorMessage	Internal repository field having the Error Message from called script.
BANCS.OUTPUT.ErrorDesc	Contains the error message to be dumped into cxx.
BANCS.OUTPUT.successOrFailure	Contains the value "S" for Success/"F" for Failure.
BANCS.OUTPUT.setupError	Contains Value "Y" if error is there in called script
BANCS.OUTPUT.setupErrorMsg	Contains Error message from called script.

Typical Usage Scenario:

This script is called when Implement Type in PAYSYS Level is "BACS". As It is a Sample script, It will be called only if it is present in TBA_SCRIPTS directory.

Default logic incase script is not present

If the script is not present, it won't get called and all validation will be bypassed.

Example:

1. NA

ISCD Validation Script for HACHODCL/HACHODRL



Script Name:

valISCDForACHODCLRL.sscr:

This script is called by “BACS_validateISCDMCFForACHODCLRL.sscr” for doing ISCD Validations.

The script must be present in TBA_SCRIPTS directory.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.AcctNumber	Receiver acct to be input from calling script
BANCS.INPUT.SortCode	Receiver Bic to be input from calling script

Output:

Field Name	Details
BANCS.OUTPUT.errorMessage	Contains Error Message.
BANCS.OUTPUT.successOrFailure	Contains the value “S” for Success/”F” for Failure.
BANCS.OUTPUT.STATUS	Value got from getValForISCD.sscr
BANCS.OUTPUT.TRANGROUPCODE	Contains Error message from called script.

Typical Usage Scenario:

This script is called from "BACS_validateISCDMCFForACHODCLRL.sscr", when Implement Type in PAYSYS Level is "BACS". As it is a Sample script, it will be called only if it is present in TBA_SCRIPTS directory.

Default logic incase script is not present

If the script is not present, An error message is passed to the calling script saying : "Validation Script [vallSCDForACHODCLRL.scr] does not exists".

Example:

1. NA

©Copyright Infosys Ltd.

ValidateMT202CV.scr



Script Name:

ValidateMT202CV.scr

This script performs 202CV Validations for the Paysys/TFIN/Loans modules .

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Script Input	Description
BANCS.INPUT. tag58a1	Beneficiary institution
BANCS.INPUT. tag211	Reference number
BANCS.INPUT. tagb50a1	Ordering customer
BANCS.INPUT. tag57a1	AWI details
BANCS.INPUT. tagb591	Beneficiary customer

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Script Input	Description
BANCS.OUTPUT.errorMessage	Internal repository field having the Error Message from called script.
BANCS.OUTPUT.failedFieldTag	Contains the field which was failed for validation
BANCS.OUTPUT.successOrFailure	Contains the value "S" for Success/"F" for Failure.

Typical Usage Scenario:

This script is called when the cover message is getting generated for the SWIFT paysys ID.

Default logic incase script is not present

If the script is not present, An error message is passed to the calling script saying : "Validation Script [ValidateMT202CV.scr] does not exists".

Example:

NA

©Copyright Infosys Ltd.

ISCD validation script for HACHORP



Script Name:

valISCDForACHORP.sscr:

This script is called by "SRV_ProcessAchRecForRepair_post_validate_data.sscr" for doing ISCD Validations.

The script must be present in TBA_SCRIPTS directory.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.AcctNumber	Receiver acct to be input from calling script
BANCS.INPUT.SortCode	Receiver Bic to be input from calling script

Output:

Field Name	Details
BANCS.OUTPUT.errorMessage	Contains Error Message.
BANCS.OUTPUT.successOrFailure	Contains the value "S" for Success/"F" for Failure.
BANCS.OUTPUT.STATUS	Value got from getValForISCD.sscr
BANCS.OUTPUT.TRANGROUPCODE	Contains Error message from called script.

Typical Usage Scenario:

This script is called from "SRV_ProcessAchRecForRepair_post_validate_data.sscr", when Implement Type in PAYSYS Level is "BACS". As it is a Sample script, it will be called only if it is present in TBA_SCRIPTS directory.

Default logic incase script is not present

If the script is not present, An error message is passed to the calling script saying : "Validation Script [vallSCDForACHORP.scr] does not exists".

Example:

NA

©Copyright Infosys Ltd.

BACS Validate ISCD MC For TD



Script Name:

The script `BACS_validateISCDMCFForTD.scr` must be present in `$TBA_SCRIPTS` directory. This script will be used to validate ISCD and modulus check for TD

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. PaysysId	Paysys ID of ACH Payment System.
BANCS.INPUT. BicId	Bank Identifier Code
BANCS.INPUT. RecvAcctDtIs	Receiver Account Details(IBAN Number).

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT. successOrFailure	Success or Failure
BANCS.OUTPUT. errorMessage	Error Message

BANCS.OUTPUT. Set Up Error Flag. Valid Values YES and NO
setupError

Typical Usage Scenario:

This script is called when implement type in HPAYSY level is “BACS”. When this script is not present in TBA_SCRIPTS directory, then it will be by passed.

Example:

NA

©Copyright Infosys Ltd.

BACS Validate ISCD for TD



Script Name:

The script `vallSCDForTD.scr` must be present in `$TBA_SCRIPTS` directory. This script will be used to handle all the ISCD validations for the menu TD Account Opening.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
BANCS.INPUT. PaysysId	Paysys ID of ACH Payment System.
BANCS.INPUT. BicId	Bank Identifier Code

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
BANCS.OUTPUT. successOrFailure	Success or Failure
BANCS.OUTPUT. errorMessage	Error Message

Typical Usage Scenario:

This script is called to handle all the ISCD validations for the menu TD Account Opening. If “vallSCDForTD.scr” does not exist, then it will give error saying “Validation Script [vallSCDForTD.scr] does not exist”. For validating ISCD for TD, vallSCDForTD.scr script must be present in TBA_SCRIPTS directory.

Example:

NA

©Copyright Infosys Ltd.

BACS-Validate ISCD/MC for CMCMTM



Script Name:

The script BACS_validateISCDMCFForCMCMTM.scr must be present in \$TBA_SCRIPTS directory. This script will be used to do the ISCD/MC for CMCMTM menu.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.PaysysId	Paysys Id
BANCS.INPUT.BicId	Receiver Bic Id
BANCS.INPUT.RecvAcctDtls	Receiver Account

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.errorMessage	Error Message.
BANCS.OUTPUT.successOrFailure	Success or Failure Indicator

BANCS.OUTPUT.setupError Setup Error Indicator

BANCS.OUTPUT.setupErrorMsg Setup Error Message

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is “BACS”. This script will be used to do the ISCD/MC validations for BACS.

Example:

NA

©Copyright Infosys Ltd.

BACS-Validate ISCD/MC for CMMTRR



Script Name:

The script BACS_validateISCDMCForCMMTRR.scr must be present in \$TBA_SCRIPTS directory. This script will be used to do the ISCD/MC for CMMTRR menu.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT.PaysysId	Paysys Id
BANCS.INPUT.BicId	Receiver Bic Id
BANCS.INPUT.RecvAcctDtls	Receiver Account

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.errorMessage	Error Message.
BANCS.OUTPUT.successOrFailure	Success or Failure Indicator

BANCS.OUTPUT.setupError Setup Error Indicator

BANCS.OUTPUT.setupErrorMsg Setup Error Message

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is “BACS”. This script will be used to do the ISCD/MC validations for BACS.

Example:

NA

©Copyright Infosys Ltd.

BACS-Validate ISCD/MC for HGARFG/HGARFR



Script Name:

The script BACS_validateISCDMCFORGARFGR.scr must be present in \$TBA_SCRIPTS directory. This script will be used to do the ISCD/MC for HGARFG/HGARFR menu.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
BANCS.INPUT. PaysysId	Paysys Id
BANCS.INPUT.BicId	Receiver Bic Id
BANCS.INPUT. RecvAcctDtls	Receiver Account
BANCS.INPUT.fileType	File Type
BANCS.INPUT.PurposeCode	Purpose Code
BANCS.INPUT.FlglValue	Flag Value

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
BANCS.OUTPUT.errorMessage	Error Message.
BANCS.OUTPUT.successOrFailure	Success or Failure Indicator
BANCS.OUTPUT.setupError	Setup Error Indicator
BANCS.OUTPUT.setupErrorMsg	Setup Error Message

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is "BACS". This script will be used to do the ISCD/MC validations for BACS.

Example:

NA

©Copyright Infosys Ltd.

BACS-validate ISCD for CMCMTM menu



Script Name:

The script `valISCDForCMCMTM.scr` must be present in `$TBA_SCRIPTS` directory. The script will handle all the ISCD validations for the menu CMCMTM.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
<code>BANCS.INPUT.menuParam</code>	CMCMTM

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
<code>BANCS.OUTPUT.errorMessage</code>	Error Message.
<code>BANCS.OUTPUT.successOrFailure</code>	Success or Failure Indicator
<code>BANCS.OUTPUT.STATUS</code>	Value got from <code>getValForISCD.scr</code>
<code>BANCS.OUTPUT.TRANGROUPCODE</code>	Value got from <code>getValForISCD.scr</code>
<code>BANCS.OUTPUT.TODDASO</code>	Value got from <code>getValForISCD.scr</code>

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is “BACS”. The script will handle all the ISCD validations for the menu CMCMTM.

Example:

NA

©Copyright Infosys Ltd.

BACS-validate ISCD for CMMTRR menu



Script Name:

The script `valISCDForCMMTRR.sscr` must be present in `TBA_SCRIPTS` directory. The script will handle all the ISCD validations for the menu CMMTRR.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
<code>BANCS.INPUT.menuParam</code>	CMMTRR

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
<code>BANCS.INPUT.menuParam</code>	Error Message.
<code>BANCS.OUTPUT. successOrFailure</code>	Success or Failure Indicator
<code>BANCS.OUTPUT.STATUS</code>	Value got from <code>getValForISCD.scr</code>
<code>BANCS.OUTPUT.TRANGROUPCODE</code>	Value got from <code>getValForISCD.scr</code>
<code>BANCS.OUTPUT.TODDASO</code>	Value got from <code>getValForISCD.scr</code>

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is “BACS”. The script will handle all the ISCD validations for the menu CMMTRR.

Example:

NA

©Copyright Infosys Ltd.

BACS-validate ISCD for HGARFG/HGARFR menus



Script Name:

The script `vallSCDForGARFGR.scr` must be present in `$TBA_SCRIPTS` directory. The script will handle all the ISCD validations for the menus HGARFG/HGARFR.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

`BANCS.INPUT.<fieldName>`

Field Name	Details
<code>BANCS.INPUT.menuParam</code>	GARFG/GARFR
<code>BANCS.INPUT.FigValue</code>	GARFG or GARFR
<code>BANCS.INPUT.fileType</code>	Financial or Non-financial
<code>BANCS.INPUT.CrDrInd</code>	Credit Debit Indicator
<code>BANCS.INPUT.adv_adviceType</code>	Advice Type
<code>BANCS.INPUT.adv_inwOwInd</code>	Inward outward Indicator

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

--	--

Field Name	Details
BANCS.OUTPUT. errorMessage	Error Message.
BANCS.OUTPUT. successOrFailure	Success or Failure Indicator
BANCS.OUTPUT.STATUS	Value got from getValForISCD.scr
BANCS.OUTPUT.TRANGROUPCODE	Value got from getValForISCD.scr
BANCS.OUTPUT.TODDASO	Value got from getValForISCD.scr

Typical Usage Scenario:

This script is called when Implement Type at PAYSYS Level is "BACS". The script will handle all the ISCD validations for the menus HGARFG/HGARFR.

Example:

NA

©Copyright Infosys Ltd.

NDT Sort Code Validation



Script Name:

The script `BACS_validateSortCode.sscr` is a sample script provided for BACS customization and should be present in `samscripts` directory. This script will be moved to `$TBA_SCRIPTS` folder as `BACS_validateSortCode.scr`.

The script will be used to carry out the NDT sort code validation for the `sort_code` and `paysys_id` passed to the script.

Input:

The defined inputs are available in repository `BANCS`, class `INPUT` and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

`BANCS.INPUT.<Fieldname>`

Field Name	Details
PaysysId	Paysys ID.
SortCode	Bank identifier field.

Output:

The output of the script will be available in the specified repository fields:

`BANCS.OUTPUT.<fieldName>`

Field Name	Details
successOrFailure	Returns the status, whether the script is success (S) or failure (F).
errorMessage	Appropriate error message.

Default Logic:

If the script BACS_validateSortCode.scr is not present, then the error “script [BACS_ValidateSortCode.scr] does not exist” is displayed to the front-end Script.

Typical Usage Scenario:

This script will be called from the CXX sources.

Example:

NA

©Copyright Infosys Ltd.

Commission ID Confirmation



Script Name:

The script `mftCConfirmation.scr` must be present in `TBA_SCRIPTS` directory. This script will be used to determine, if the commission id selected from the finacle DB is appropriate, as per any special requirements of the bank. If bank wants some customized validations to be done on commission id, then it can do that validation in this script.

Input:

The defined input is available in a repository called `BANCS`, in a class called `INPUT` with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

Field Name	Details
<code>BANCS.INPUT.fundHouseCode</code>	Fund house id mentioned in the upload file.
<code>BANCS.INPUT.fundId</code>	Fund Id mentioned in the upload file.
<code>BANCS.INPUT.paymentCode</code>	Payment code mentioned in the upload file.
<code>BANCS.INPUT.fromDate</code>	From date of the commission calculation mentioned in the upload file.
<code>BANCS.INPUT.toDate</code>	To date of the commission calculation mentioned in the upload file.
<code>BANCS.INPUT.grossAmt</code>	Gross amount for confirmation mentioned in the upload file.
<code>BANCS.INPUT.commCcy</code>	Currency of the commission amount paid mentioned in the upload file.
<code>BANCS.INPUT.aumAmt</code>	AUM amount mentioned in the upload file.
<code>BANCS.INPUT.commId</code>	Commission id selected from the finacle DB on the basis of upload file record.

Output:

The output of the script will be available in the specified repository fields:

Field Name	Details
BANCS.OUTPUT.commId	Commission id selected from the finacle DB on the basis of upload file record and which was dumped in the script.
BANCS.OUTPUT.errorMsg	Error message if any which the bank wants to get in the report.

Default Logic:

NA

Typical Usage Scenario:

Script will get executed for every commission id selected from the Finacle DB for the record mentioned in the upload file.

Example:

NA

©Copyright Infosys Ltd.

Validate SFMS Message



The validate scripts for SFMS messages are called to validate the message data and to ensure network validations.

These ValidateIFN scripts are similar to Swift Scripts that are ValidateMTscripts.

Validate Scripts for SFMS and SWIFT are called in following fashion :

[Validate<format_type><msg_no>].Format Type for SFMS is IFN and for SWIFT is MT

Validate script has to be called based on Implementation Type[i.e SWIFT or SFMS] format type and Msg No will be replaced to form a Validate Script Name and that script will be executed.

All validate scripts for SFMS are in norms with Swift scripts.

Input:

The defined input is available in a repository called BANCS, in a class called INPUT with the field names mentioned.

You can access the input by referring to the fields in the specified manner:

BANCS.INPUT.<fieldName>

Field Name	Details
Tag 32a1	Value Date
Tag 32a2	Currency Code
Tag 32a3	Amount
Tag 50	Ordering Customer
Tag59	Beneficiary Customer
Tag 52	Ordering Institution
Tag53	Sender's Correspondent.

Tag54	Receiver's Correspondent.
Tag56	Intermediary
Tag57	Account with Institution
Tag70	Details of Payment
Tag71A	Details of Charges
Tag72	Sender to Receiver Information
Tag20	Transaction Reference Number

Output:

The output of the script will be available in the specified repository fields:

BANCS.OUTPUT.<fieldName>

Field Name	Details
errorMessage	Gives the error description
failedFieldTag	Specifies Tag for which Validation Failed
successOrFailure	Returns success or failure.

Typical Usage Scenario(s):

The validate scripts are called when clicked on Accept or Validate button in Message Details tab. This script internally calls ValidateIFNTag.scr which validates tags that are common for all the SFMS messages.

©Copyright Infosys Ltd.

Validate PINCODE - Identify Illegal Character



Script Name:

valPinCode.scr

Description:

The script valPinCode.scr is used to check whether Pin Code field entered contains valid special characters. Based on the allowed characters in the field, proper error message is thrown to the calling function.

Inputs:

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. You can access the inputs by referring the fields in the following manner:

BANCS.INPUT.<Fieldname>

Field Name	Description
pinCode	The Pin Code field through which Pin code is Accessed in Script

Output:

Field Name	Description
successOrFailure	Valid Values are "S" or "F" If pin code is valid then "S" will be returned If Pin Code is invalid then "F".will be returned
ErrorMessage	If pin code is invalid then proper error Message will be returned to the calling function else empty string will be returned.

Default Logic:

In case script is not present, only alphanumeric, space, hash(#) and Hyphen(-) characters are allowed for Postal Code Field.

Typical Usage Scenario:

Script Hook is provided to allow other special characters for Postal Code Field.

Sample Script

valPinCode.scr

©Copyright Infosys Ltd.

Appendix

The fields in STDIN class in BANCS repository are:

Sl. No.	Field Name	Value Contained
1.	userId	The userid of the user who executed the script
2.	onlineOrBatch	Whether this script is being executed through a batch program or online ("O" or "B")
3.	userWorkClass	The workclass of the userid who executed the script from UPM
4.	menuOption	The menu option which called this script
5.	homeCrncyCode	The home currency of the data center from HSCFM
6.	homeCrncyAlias	The home currency alias
7.	CurrentBancsVersion	The Finacle version
8.	myBankCode	The bank code of the database
9.	myBrCod	The branch code of the SOL
10.	myExtCode	The Extension counter
11.	mySolId	The SOLID
12.	mySolAlias	The SOLALIAS
13.	mySolDesc	The description for the Sol as specified in HSCFM
14.	homeSolId	The Sol to which the User belongs
15.	homeSolAlias	The Home SOL Alias
16.	homeSolDesc	The Home Sol description as specified in HSCFM.
17.	dcAlias	The DC ALIAS

18.	SBString	The value of custoption for SBSTING
19.	CAString	The value of custoption for CASTING
20.	LLString	The value of custoption for LLSTING
21.	CCString	The value of custoption for CCSTING
22.	sysDate	The system date of the machine
23.	BODDate	The current BOD date of the SOL
24.	termClass	The terminal class from HTPM
25.	moduleIdentity	The module which is calling the Script
26.	TestFlg	Whether the script is being invoked in test mode. E.g through menu option "SCRIPT"
27.	WFflg	Whether the script is a workflow script
28.	ScriptName	The name of the script
29.	languageCode	This field contains the value of the language code of the user e.g. INFENG

See the Administrator module for HSCFM menu option details.

©Copyright Infosys Ltd.

autoReimburseClaim.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is added for getting the value 'No. Of Auto Claim Days'.

This script is added for getting the value 'No. Of Auto Claim Days'.

autoReimburseClaim.scr

NA

The following is the syntax for specifying the output fields:

BANCS.OUTPUT.Number = <Value>

The following are the details of the output field for the script:

Output Field	Description
Number	Obtaining the value for No. Of Auto Claim Days

NA

This script is added for getting the value 'No. Of Auto Claim Days'.

NA

checkPaySysIdForBPARC.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is added as part of the changes done for BPARC Menu option.

This script is added to check whether you have given the input for the Payment System ID as 'Swift'. If 'Swift' is given as input, then success is returned to you as an output. Else, failure is returned as an output.

checkPaySysIdForBPARC.scr

The following are the details of the input field for the script:

Input Field	Description
paysysId	Payment System ID entered by you.

The following are the details of the output field for the script:

Output Field	Description
successOrFailure	Success or Failure return value

NA

This script is added to check whether you have given the input for the Payment System ID as 'Swift'. If 'Swift' is given as input, then success is returned to you as an output. Else, failure is returned as an output.

NA

©Copyright Infosys Ltd.

Finacle Copyright

chkIfChnlEnbForInqAudit.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is used to check if validating channel is enabled for audit on Inquiries and Attempted Transaction.

Refer ticket - 656305

chkIfChnlEnbForInqAudit.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.channelId	Channel ID from where request is coming.
BANCS.INPUT.isChannelEnabled	Indicator to identify whether channel is enabled for audit on Inquiry and Attempted Transaction.

The following are the details of the output fields for the script:

Output Field	Description
BANCS.INPUT.isChannelEnabled	Indicator to identify whether channel is enabled for audit on Inquiry and Attempted Transaction.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is a Maha Transaction Template to create the transactions for contingent revaluation.

The following are the details of the input fields for the script:

Input Field	Description
MTT.TranDetails.TranDate	Transaction Date
MTT.TranDetails.TranType	Transaction Type
MTT.TranDetails.TranSubType	TranSubType
MTT.TranDetails.Remarks	Remarks
MTT.TranDetails.IgnoreExcp	IgnoreExcp
MTT.TranDetails.Consolidate	Consolidate
MTT.TranDetails.PrintAdviceInd	PrintAdviceInd
MTT.TranDetails.TranID	Transaction ID
MTT.PartTranDetails.RefAmount	RefAmount
MTT.PartTranDetails.Account	Account Number
MTT.PartTranDetails.RefCurrency	Ref Currency
MTT.PartTranDetails.TranCurrency	Transaction Currency
MTT.PartTranDetails.ValueDate	Value Date
MTT.PartTranDetails.ACPARTB2kId	AC PART B2k Id
MTT.PartTranDetails. ACPARTB2kType	ACPARTB2kType= "FBILL"
MTT.PartTranDetails. RateCode	Rate code
MTT.PartTranDetails. Rate	Rate
MTT.PartTranDetails. Refnum	Reference number

MTT.PartTranDetails. ReportCode	Report Code
MTT.PartTranDetails. CustomerId	CustomerId
MTT.PartTranDetails. Particulars	Particulars
MTT.PartTranDetails. EntryUserId	Entry User Id
MTT.PartTranDetails. TreaRate	Treasury Rate
MTT.PartTranDetails. TreaRefNum	Treasury Reference Number
MTT.PartTranDetails. Consolidate	Consolidate Flag
MTT.PartTranDetails. PTranBusinessType	PTranBusinessType="FBILL"
MTT.PartTranDetails. TranIdentifier	TranIdentifier = "FXBILLS"
MTT.ContingentDetails.CnTranMode	Tran Mode
MTT.ContingentDetails.CnEntityOperation	Entity Operation
MTT.ContingentDetails.CnEntityB2kId	Entity B2kId
MTT.ContingentDetails.CnEntityB2kType	Entity B2kType (FBILL\REMIT\DOCCR\BNKGR)
MTT.ContingentDetails.CnEntityNumber	Entity Number
MTT.ContingentDetails.CnEntitySolId	Entity SolId
MTT.ContingentDetails.CnEntityCurrency	Entity Currency
MTT.ContingentDetails.CnLiabDebitAcct	LiabDebitAcct
MTT.ContingentDetails.CnLiabCreditAcct	Liab Credit Acct
MTT.ContingentDetails.CnAmount	Amount(This amount should be in contingent Currency)
MTT.ContingentDetails.CnCurrency	Currency(this currency will be contingent currency)
MTT.ContingentDetails.CnRateCode	Rate Code
MTT.ContingentDetails.CnRate	Rate
MTT.ContingentDetails.CnEventAmount	Event Amount(This amount should be in entity currency)
MTT.ContingentDetails.CnEntityCurrency	Event Currency

getStmtNextPrintDate.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is used to set a user defined next statement generation date when HPSP is invoked for Pass Sheet Printing or Combined Statement Printing.

Refer ticket - 662407

getStmtNextPrintDate.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.acctNum	Account ID
BANCS.INPUT.masterAcctNum	Master account number
BANCS.INPUT.cifId	CIF ID
BANCS.INPUT.solId	SOL ID
BANCS.INPUT.schmType	Scheme Type
BANCS.INPUT.crncyCode	Currency code
BANCS.INPUT.psStatementCode	PS Statement Code
BANCS.INPUT.fromLastPrint	From Last Print
BANCS.INPUT.adhocFlg	Adhoc Flag
BANCS.INPUT.psFreqCalBase	PS Frequency calendar base
BANCS.INPUT.psFreqType	PS Frequency type
BANCS.INPUT.psFreqWeekNum	PS Frequency Week number
BANCS.INPUT.psFreqWeekDay	PS Frequency Week date

BANCS.INPUT.psFreqStartDd	PS Frequency start date
BANCS.INPUT.psFreqHldyStat	PS Frequency holiday status
BANCS.INPUT.psCsNextDueDate	PS Next due date

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.psCsNextDueDate	PS Next due date

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script hook is introduced if any change in tax calculation logic is required. They can introduce new logic in this script and can return successOrFailure as 'S' .

Introduced this script hook as a part of W-Tax enhancements.

getWTaxIslamic.scr

The following are the details of the input fields for the script:

Input Field	Description
Acid	This is the account for which w-tax is computed.
depositAmt	Deposit Amount of the given account ID.
depTenorDd	Deposit tenor (days) of the given account ID.
depTenorMm	Deposit tenor (months) of the given account ID.
profitAmt	Profit Amount for current processing.
profitAmtTillLastRun	Profit Amount paid for complete financial year.
wTaxPcnt	W-Tax Pcnt. from current maintenance.
wTaxFloorLimit	W-Tax Floor limit from current maintenance.
IncludeForTaxFlg	Include for Tax Flag from current maintenance, based on whose value w-tax floor limit will be considered for tax computation.
TaxAmtTillLastRun	Tax Amount paid for complete financial year.
wTaxAmt	Tax computed as per default logic through product.

Output

The following are the details of the output fields for the script:

Output Field	Description
wTaxAmt	WTax amount if changed after new logic.
successOrFailure	S if change in new logic else F.

Default Logic

By default the value of output will be same as input. If customization needs any change in calculation logic they can implement the new logic and pass the output to calling function.

If w-tax calculation logic is different from default product logic, new logic can be written here.

getWTaxIslamic.sscr

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script hook is introduced if any change in tax maintenance is required or if any slab level maintenance is required. A new logic can be introduced in this script and can return successOrFailure as 'S'.

Introduced as part of W-Tax enhancement.

getWTaxParametersIslamic.scr

The following are the details of the input fields for the script:

Input Field	Description
Acid	This is the account for which w-tax is computed
depositAmt	Deposit Amount of the given account ID.
depTenorDd	Deposit tenor (days) of the given account ID.
depTenorMm	Deposit tenor (months) of the given account ID.
profitAmt	Profit Amount for current processing.
profitAmtTillLastRun	Profit Amount paid for complete financial year.
periodStartDate	Period start date of current execution cycle.
periodEndDate	Period end date of current execution cycle.
wTaxPcnt	W-Tax Pcnt. from current maintenance.
wTaxFloorLimit	W-Tax Floor limit from current maintenance.
IncludeForTaxFlg	Include for Tax Flag from current maintenance, based on whose value w-tax floor limit is considered for tax computation.

The following are the details of the output fields for the script:

Output Field	Description
wTaxPcnt	W-Tax Pcnt if changed after new logic.
wTaxFloorLimit	W-Tax Floor limit if changed after new logic.
IncludeForTaxFlg	Include for Tax Flag if changed after new logic.
successOrFailure	"S" if change in new logic , else "F".

By default the value of output is same as input. If customization needs any change in maintenance they can implement the new logic and pass the output to calling function.

If w-tax setup must be an amount period slab maintenance, new logic can be written here.

getWTaxParametersIslamic.sscr

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from IN_SRV_FetchLienHistoryRecDtls_process_locale_data.scr for performing the locale data fetch for display in History mode.

IN_almHistDtls.scr

The following are the details of the input fields for the script:

Input Field	Description
histSrlNum	It is the serial number in Lien History Maintenance table.

The following are the details of the output fields for the script:

Output Field	Description
successOrFailure	To return success or failure.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from IN_SRV_FetchLienListRecDtls_process_locale_data.scr for performing the locale data fetch for display in List mode.

IN_almListDtls.scr

The following are the details of the input fields for the script:

Input Field	Description
acctAcid	The account ID upon which lien is marked.
ModuleType	The lien type. Specifies if ULIEN or not.
B2kId	The ALT table key.

The following are the details of the output fields for the script:

Output Field	Description
successOrFailure	To return success or failure.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called in HTDSIP (tdsiexp_link.js) to find the number of records in IN_WTC for the data present on screen. If there is at least one record, the explode button will be displayed.

IN_chkIfWeighted.scr

The following are the details of the input fields for the script:

Input Field	Description
acctId	'A/c. ID' present on screen
tdsCertNum	'Tax Certificate No.' present on screen
tranId	'Transaction ID' present on screen

The following are the details of the output fields for the script:

Output Field	Description
Count	The number of record present in IN_WTC table

The number of records in IN_WTC table with the account ID, transaction ID and TDS certificate number are found and passed as output.

HTDSIP Inquiry

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_DecreedReport_custval.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for validating the input fields in IN_DecreedReport.jasper

IN_DecreedReport_custval.scr

The following are the details of the input fields for the script:

Input Field	Description
As on date	As on date is set in the jasper.
SOL set ID	SOL set ID set in the jasper.

Inputs are obtained from the jasper file. Validations for inputs are handled in this script.

Automated report generation.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from jasper file IN_DecreedReport.jasper for generating the Decreeded accounts report.

IN_DecreedReport_defaultpop.scr

Context bank ID

The script is called from the jasper file and it populates the context bank id as a hidden input to the jasper.

©Copyright Infosys Ltd.

IN_DecreedReport.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for generating the Decreeded accounts report in HPR menu option.

IN_DecreedReport.scr

The following are the details of the input fields for the script:

Input Field	Description
As on date	As on date is set in the HBJSTM menu. This is passed as input to the procedure.
SOL set ID	SOL set ID is set in the HBJSTM menu. This is passed as input to the procedure.

NA

Inputs are obtained from the HBJSTM menu and procedure is called. Procedure returns the Ist file and this file is used to generate the Decreeded accounts report.

Automated report generation.

IN_FetchASBADataForHALMValidation.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script gets executed in Add or Copy from template modes of HALM and is called from the front end link file. The script fetches the scheme type, the ASBA Name setup at MGPS level and the IPO Institution name description from LRCDM. These values are used for front end validations.

IN_FetchASBADataForHALMValidation.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The account on which lien is marked.

The account ID on which lien is to be marked is passed as input to the script. The scheme type of the account, ASBA_Name value setup in MGPS and the LRCDM description for the IPO Institution name are fetched and passed to frontend.

The locale script is executed from the link file of HALM details page in Onload event. The script is called only in Add and Copy from template function modes.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Fetch SRV post process scripts in Modify or Cancel or Verify modes of HALM. The script includes the fetch logic of IPO Institution Name and IPO Application Number values from IN_ALT and populates it in the frontend variables.

IN_FetchHALMForASBA.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The account on which lien is marked.
Module Type	The lien type from HALM criteria page.

The following are the details of the output fields for the script:

Output Field	Description
IpoInsttnName	The IPO Institution name for the ASBA lien record.
IpoApplnNum	The IPO Application number for the ASBA lien record.

The records are taken one by one from the LienMaint link list. The lien reason code of each record is compared with the ASBA lien reason code. If it is ASBA lien, the IPO Institution Name and the IPO Application number values are fetched from the locale table IN_ALT and passed to the front end fields.

The locale script gets called on click of GO button from HALM criteria

page in Modify, Verify and Cancel modes.

©Copyright Infosys Ltd.

Finacle Copyright

IN_FetchLocaleDataForBills.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from script, IN_FetchLocaleDataForTfin.scr to fetch action code according to SRV called for BTPM menu.

IN_FetchLocaleDataForBills.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The Bill type for which the data needs to fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

Default Logic

The script is called from locale script to fetch action code based on the calling SRV for the script.

Typical Usage Scenario

The script is called from locale script, IN_FetchLocaleDataForTfin.scr.

Sample Script

NA

IN_FetchLocaleDataForFactoring.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from script, IN_FetchLocaleDataForTfin.scr to fetch action code according to SRV called for MFPS menu.

NA

IN_FetchLocaleDataForFactoring.scr

The following are the details of the input fields for the script:

Input Field	Description
Factoring Parameter Type	The Factoring parameter type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from locale script to fetch action code based on the calling SRV for the script.

The script is called from locale script, IN_FetchLocaleDataForTfin.scr.

NA

©Copyright Infosys Ltd.

Finacle Copyright

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from SRV scripts of BTPM and MFPS menu for different modes. This script has the logic to fetch locale data for different modes. It further calls the locale scripts to fetch action code based on the calling SRV for BTPM and MFPS menu.

IN_FetchLocaleDataForTfin.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type/Factoring Parameter Type	The Bill type or factoring parameter type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from SRV scripts of BTPM and MFPS menu. The script has the logic to process the locale data for these menu.

The script is called from SRV scripts of BTPM and MFPS menu for different modes.

NA

©Copyright Infosys Ltd.

Finacle Copyright

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from HGSPM menu option on click of Go button to fetch the values of locale fields. This script is called from various SRV script for different modes.

IN_FetchPandLRecoveryPHForGSPM.scr

This script is called to fetch the values of locale fields for various modes of HGSPM menu option.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from SRV scripts of HGSPM menu for different modes. This script is modified to implement the logic to fetch locale data for PCA scheme type.

IN_FetchPandLRecoveryPHForGSPM.scr

The following are the details of the input fields for the script:

Input Field	Description
Scheme Code	The scheme code for which locale data is to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from SRV scripts of GSPM menu. The script is modified to implement the logic to fetch the locale data.

The script is called from SRV scripts of HGSPM menu on click of GO button.

NA

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The script is used to fetch the debit account details from the IN_DSI table during the fetch operations of Modify, Cancel and Verify modes.

IN_fetchRDSI.scr

This script fetches the debit account id field from IN_DSI table and shows the field in the menus.

IN_submitRDSI.scr

The script is used to perform the table operations like add, modify, verify and cancel operations on the records present in the IN_DSI table.

IN_submitRDSI.scr

This script performs the database operations on the records present in IN_DSI table based on the mode selected by the user.

IN_FetchTranAcctSchmParamsForDelete_process

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HGSPM on click of Go button in Verify mode. The script calls the locale script IN_FetchPandLRecoveryPHForGSPM.scr for fetching the values of locale fields from IN_GSP table.

IN_FetchTranAcctSchmParamsForDelete_process_locale_data.scr

This script is called for fetch function from locale table in Cancel mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_GetWeightedAvgAmt.sscr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is used to modify the data being passed to the LST file in HTDSCALC menu. The default logic returns as many records as present in IN_WTC table. Using this, as many records are shown in the reports or certificates with the same format as present in the product. The script can be customized as required.

The file has to be renamed as .sscr and placed in the scripts directory.

IN_GetWeightedAvgAmt.sscr

The following are the details of the input fields for the script:

Input Field	Description
custId	cust_id from TDS table
SOL ID	sol_id from TDS table
tdsCertNum	Tds_cert_num from TDS table
tranDate	Tran_date from TDS table
inpMsg	The data being passed to the LST file for this record

The following are the details of the output fields for the script:

Output Field	Description
noOfRecords	The number of records passed back from the script hook
outMsg_0, outMsg_1, outMsg_2 etc	The data which is to be written to the LST file

If there are no records in IN_WTC table, LST data is passed back

without any change and is available in outMsg_0. If there are records, say 3, outMsg_0, outMsg_1, outMsg_2 are passed back. These have the interest amount, tax amount and tax rate from IN_WTC table. All other data is same as what was present in inpMsg.

This script is used when HTDSCALC reports/certificates should follow the same format as in the product, but with multiple records in case of weighted average calculation.

Yes

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for generating the Government Sponsored scheme report in HPR menu option.

IN_GovtSchmeReport.scr

The following are the details of the input fields for the script:

Input Field	Description
As on date	As on date is set in the HBJSTM menu. This is passed as input to the procedure.
SOL set ID	SOL set ID set in the HBJSTM menu. This is passed as input to the procedure.

Inputs are obtained from the HBJSTM menu and procedure is called. Procedure returns the 1st file and this file is used to generate the government sponsored scheme report.

Automated report generation.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for validating the input fields in IN_GovtSchmeReport.jasper

IN_GovtSchmeReport_custval.scr

The following are the details of the input fields for the script:

Input Field	Description
From date	From date is set in the jasper file.
To date	To date is set in the jasper file.
SOL set ID	SOL set ID set in the jasper file.
Government sponsored scheme	Government scheme is set in the jasper file.

NA

Inputs are obtained from the jasper file. Validations for inputs are handled in this script

Automated report generation.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from jasper file IN_GovtSchmeReport.jasper for generating the Government sponsored schemes report.

IN_GovtSchmeReport_defaultpop.scr

Context bank ID

The script is called from the jasper file and it populates the context bank id as a hidden input to the jasper.

©Copyright Infosys Ltd.

IN_GWK_VERIFY_post_process_data.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_KitBatchCall.scr

IN_GWK_VERIFY_post_process_data.scr

This script is called for post process of verify mode of newly added request number in GWK menu.

©Copyright Infosys Ltd.

IN_isKccAcctPastDue.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called in HSASCL. This script checks:

If passed account is KCC account

If KCC account, then checks whether it is NPA as per KCC logic.

If NPA, then modifies the system classification with best worst risk class from scheme set up.

IN_isKccAcctPastDue.scr

The following are the details of the input fields for the script:

Input Field	Description
Acid	Acid for the processed entity.
Schm Code	Scheme of the account.

The following are the details of the output fields for the script:

Output Field	Description
subClassSys	System Sub classification
mainClassSys	System Main Classification
successOrFailure	Success or failure

HSASCL

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_KCC_Report_custval.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for validating the input fields in IN_KCC_Report.jasper.

IN_KCC_Report_custval.scr

The following are the details of the input fields for the script:

Input Field	Description
From date	From date is set in the jasper file.
To date	To date is set in the jasper file.

Inputs are obtained from the jasper. Validations for inputs are handled in this script

©Copyright Infosys Ltd.

IN_KCC_Report_defaultpop.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from jasper file IN_KCC_Report.jasper for generating the KCC accounts report.

IN_KCC_Report_defaultpop.scr

Context bank ID

The script is called from the jasper file and it populates the context bank ID as a hidden input to the jasper.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for generating the suit filed accounts report in HPR menu.

IN_KCC_Report.scr

The following are the details of the input fields for the script:

Input Field	Description
From date	From date is set in the HBJSTM menu.
To date	To date is set in the HBJSTM menu.

Default Logic

Inputs are obtained from the HBJSTM menu and procedure is called. Procedure returns the 1st file and this file is used to generate the suit filed accounts report.

Typical Usage Scenario

Automated report generation.

IN_KitBatchCall.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ValidateKitRequest.scr as a batch job.

IN_KitBatchCall.scr

This script is called by IN_GWK_VERIFY_post_process_data.scr for verify mode of newly added request number in GWK menu.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script adds the core customer details in CCMG table.

IN_KitCustomerCoreLink.scr

This script is called by IN_OpenKitAccounts.scr in Verify mode for GWK menu.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls add kit related details in IN_WKD table.

IN_KitProcTbl.scr

This script is called by IN_OpenKitAccounts.scr in Verify mode for GWK menu.

©Copyright Infosys Ltd.

IN_KitReportGen.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release..

This script generates success and failure reports

IN_KitReportGen.scr

This script is called by IN_ValidateKitRequest.scr in Verify mode for GWK menu.

©Copyright Infosys Ltd.

IN_liftLienWithTransaction.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from cxx file to call the HTM service to revoke the lien and do the transaction for particular IPO Institution and IPO application number.

Added for UALRD menu.

IN_liftLienWithTransaction.scr

The following are the details of the input fields for the script:

Input Field	Description
debitForacid	It is the account from which transaction amount is to be debited.
schmCode	The scheme code of the account to be debited.
debitCrncyCode	Currency code of the debit account.
tranAmt	Amount for which the transaction is to be done.
ipoInstitutionName	Name of the Institute for which transaction is to be done.
applNumber	Application number for which transaction is to be done.
lienExpiryDate	Expiry date of the ASBA lien applied.
lienAmt	Amount for which lien is to be revoked.
b2kId	b2k ID for which the lien had to be revoked.
creditForacid	Office account that needs to be credited for the transaction.
creditCrncyCode	Currency code for the credit office account.

The following are the details of the output fields for the script:

Output Field	Description
successOrFailure	To return success or failure.

©Copyright Infosys Ltd.

IN_Loan_Disbursement.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for generating the suit filed accounts report in HPR menu.

IN_Loan_Disbursement.scr

The following are the details of the input fields for the script:

Input Field	Description
From date	From date is set in the HBJSTM menu.
To date	To Date is set in the HBJSTM menu.
State	State is set in the HBJSTM menu.

NA

Inputs are obtained from the HBJSTM menu and procedure is called. Procedure returns a text file which is used to generate the suit filed accounts report.

Automated report generation.

©Copyright Infosys Ltd.

IN_Loan_Disbursement_Report _custval.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for validating the input fields in IN_Loan_Disbursement_Report.jasper.

IN_Loan_Disbursement_Report_custval.scr

The following are the details of the input fields for the script:

Input Field	Description
From date	From date is set in the jasper file.
To date	To date is set in the jasper file.
State	State is set in the jasper file.

Inputs are obtained from the jasper. Validations for inputs are handled in this script

©Copyright Infosys Ltd.

IN_Loan_Disbursement_Report_defaultpop.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from jasper file IN_Loan_Disbursement_Report.jasper for generating the Loan Disbursement report.

IN_Loan_Disbursement_Report_defaultpop.scr

Context bank ID

The script is called from the jasper file and it populates the context bank ID as a hidden input to the jasper.

©Copyright Infosys Ltd.

IN_Minority_Report_Dist.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for generating the suit filed accounts report in HPR menu.

IN_Minority_Report_Dist.scr

The following are the details of the input fields for the script:

Input Field	Description
To date	To date is set in the HBJSTM menu.
SOL ID	SOL set ID set in the HBJSTM menu.

NA

Inputs are obtained from the HBJSTM menu and procedure is called. Procedure returns the text file and file is used to generate the suit filed accounts report.

Automated report generation.

©Copyright Infosys Ltd.

IN_Minority_Report_State.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for generating the suit filed accounts report in HPR menu.

NA

IN_Minority_Report_State.scr

The following are the details of the input fields for the script:

Input Field	Description
To date	To date is set in the HBJSTM menu.
SOL ID	SOL set ID is set in the HBJSTM menu.

Inputs are obtained from the HBJSTM menu and procedure is called. Procedure returns a text file and this file is used to generate the suit filed accounts report.

Automated report generation.

NA

IN_Minority_Report_State _custval.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for validating the input fields in IN_Minority_Report_State.jasper.

IN_Minority_Report_State _custval.scr

The following are the details of the input fields for the script:

Input Field	Description
To date	To date is set in the jasper file
SOL ID	SOL ID is set in the jasper file

Inputs are obtained from the jasper. Validations for inputs are handled in this script

NA

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from jasper file IN_Minority_Report_Dist.jasper for generating the Minority district report.

IN_Minority_Report_Dist_defaultpop.scr

Context bank ID

The script is called from the jasper file and it populates the context bank ID as a hidden input to the jasper.

NA

IN_Minority_Report_State_defaultpop.scr Infosys®



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from jasper file IN_Minority_Report_State.jasper for generating the Minority state report.

IN_Minority_Report_State_defaultpop.scr

Context bank ID

The script is called from the jasper file and it populates the context bank ID as a hidden input to the jasper.

©Copyright Infosys Ltd.

IN_Minority_Report_Dist _custval.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for validating the input fields in IN_Minority_Report_Dist.jasper.

IN_Minority_Report_Dist _custval.scr

The following are the details of the input fields for the script:

Input Field	Description
To date	To date is set in the jasper file.
SOL ID	SOL ID is set in the jasper file.

Inputs are obtained from the jasper. Validations for inputs are handled in this script.

©Copyright Infosys Ltd.

IN_MTDSEdet_fetch.scr (15AA - MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEgetData.scr

IN_MTDSEdet_fetch.scr

This script fetches the details based on criteria input for all modes except Inquire.

©Copyright Infosys Ltd.

IN_MTDSEdet_fetch_Inq.scr (15AA - MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEgetData.scr

IN_MTDSEdet_fetch_Inq.scr

This script fetches the details based on criteria input for Inquire mode.

©Copyright Infosys Ltd.

IN_MTDSEgetData.scr (15AA - MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called on click of 'Go' Button of criteria screen of MTDSE menu option.

IN_MTDSEgetData.scr

This script calls the Validate script and the script for fetching the data for the detail screen.

©Copyright Infosys Ltd.

IN_MTDSEsubmitData.scr (15AA - MTDSE Menu)

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called on click of 'Submit' button of Details Page.

IN_MTDSEsubmitData.scr

This script calls the scripts for validating and processing data. Scripts called are:

IN_MTDSEvalidateSubmit_Data.scr

IN_MTDSEsubmitForAddMode.scr

IN_MTDSEsubmitForMod.scr

IN_MTDSEsubmitForVerfy.scr

IN_MTDSEsubmitForCncl.scr

©Copyright Infosys Ltd.

IN_MTDSEsubmitForAddMode.scr (15AA -Infosys® MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEsubmitData.scr.

IN_MTDSEsubmitForAddMode.scr

This script submits the data on Add mode and adds a new record in IN_TECT table.

©Copyright Infosys Ltd.

IN_MTDSEsubmitForCncl.scr (15AA - MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEsubmitData.scr.

IN_MTDSEsubmitForCncl.scr

This script submits the data in Cancel mode and cancels the record of IN_TECT table. It deletes the modified values from genmod.

©Copyright Infosys Ltd.

IN_MTDSEsubmitForMod.scr (15AA - MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEsubmitData.scr.

IN_MTDSEsubmitForMod.scr

This script submits the data in Modify mode and modifies the record of IN_TECT table. It saves the modified values in genmod.

©Copyright Infosys Ltd.

IN_MTDSEsubmitForVerfy.scr (15AA - MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEsubmitData.scr.

IN_MTDSEsubmitForVerfy.scr

This script submits the data in Verify mode and verifies the record of IN_TECT table.

©Copyright Infosys Ltd.

IN_MTDSEvaluate_Data.scr (15AA - MTDSE Menu)



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEgetData.scr.

IN_MTDSEvaluate_Data.scr

This script validates the data of the criteria page.

©Copyright Infosys Ltd.

IN_MTDSEvaluateSubmit_Data.scr (15AA Infosys® - MTDSE Menu)

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called from IN_MTDSEsubmitData.scr.

IN_MTDSEvaluateSubmit_Data.scr

This script is used for validating the data on details page.

©Copyright Infosys Ltd.

IN_OpenKitAccounts.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script opens dummy account and calls IN_KitCustomerCoreLink.scr for customer core data insertion and IN_KitProcTbl.scr for table insertion

IN_OpenKitAccounts.scr

This script is called by IN_ValidateKitRequest.scr in Verify mode for GWK menu.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The script sets the function code and calls the IN_submitRDSI.scr and IN_fetchRDSI.scr correspondingly based on the mode the user selects using the menu.

IN_ProcessRDAcct.scr

This script sets the function codes and calls the scripts accordingly.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The script is used to create the Standing Instructions based on the RD account created and debit account ID entered. It derives the frequency and other required information for creating the Standing instructions. Finally, the standing Instructions gets created.

IN_processRDSI.scr

This script creates the Standing Instructions based on the details entered.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from IN_uploadDistSolDetails.scr for procTbl operations to IN_DSL table both insertion and modification.

IN_procTblIN_DSL.scr

The procTbl insert operation is applied if record is newly added else modify is applied.

The procTbl insert or modify operations are handled here.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

B2K_San_Acct_Derive is the script hook which is added as part of this enhancement.

IN_San_Acct_Derive.scd is the scd file having definition of the script hook.

IN_San_Acct_Derive.sscr is the script which takes inputs as mentioned in table below and return the acid as output. This is added for any future customization where the above mentioned fields are available in the script and a logic can be implemented in script to derive the acid. The HRMI product and localized code fetches the account number but the same can be over-written at customization stage for bank's specific requirements.

This is a sample script. During customization, the file should be renamed to extension scr and placed in scripts directory.

The ticket details are as follows:

Ticket Number : 661548

Tracker ID: 404954

IN_San_Acct_Derive.sscr

The following are the details of the input fields for the script:

Input Field	Description
presentingSortCode	Presenting Sort Code
draweeSortCode	Drawee Sort Code

clearingDate	Clearing Date
instrumentAmount	Instrument Amount
instrumentNum	Instrument Number
itemSeqNum	Item Sequence Number
tranCode	Transaction Code
micrAcctNum	MICR account number
acctNum	Acid

The following are the details of the output fields for the script:

Output Field	Description
account_num	Acid

No Default logic is provided. The same is written during customization for specific requirements.

The HRMI product and localized code fetches the account number but the same can be over-written at customization stage for bank's specific requirements.

The script IN_San_Acct_Derive.sscr is available in the \$TBA_SCRIPTS directory

©Copyright Infosys Ltd.

IN_SRV_AddFactParameter_validate_locale_data.s

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Add mode of MFPS menu. This script further calls the locale script to validate locale field for add mode.

IN_SRV_AddFactParameter_validate_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Add mode of MFPS menu. The script has the logic to validate new locale field.

The script is called on click of SUBMIT button to validate locale data for add mode of MFPS menu.

NA

IN_SRV_AddFactParameter_process_locale_data.s

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Add mode of MFPS menu. This script further calls the locale script to process locale field for add mode.

IN_SRV_AddFactParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Add mode of MFPS menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for add mode of MFPS menu.

NA

IN_SRV_AddFxBillParameter_process_locale_data

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Add mode of BTPM menu. This script further calls the locale script to process locale field for add mode.

IN_SRV_AddFxBillParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Add mode of BTPM menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for add mode of BTPM menu.

NA

IN_SRV_AddFxBillParameter_validate_locale_data

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Add mode of BTPM menu. This script further calls the locale script to validate locale field for add mode.

IN_SRV_AddFxBillParameter_validate_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Add mode of BTPM menu. The script has the logic to validate new locale field.

The script is called on click of SUBMIT button to validate locale data for add mode of BTPM menu.

NA

IN_SRV_AddLienOnAcct_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of Submit in Add mode. The script calls the locale script IN_ValidateHALMForASBA.scr for validating the values of locale fields IPO Institution Name and IPO Application No. and then calls the locale script IN_SubmitHALMForASBA for performing the IN_ALT and IN_ALH table operations.

IN_SRV_AddLienOnAcct_process_locale_data.scr

This script is called for performing validation and process function in Add mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_AddLienOnAcctAndVerify_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of Submit in Add mode when Auto verification is enabled. The script calls the locale script IN_ValidateHALMForASBA.scr for validating the values of locale fields IPO Institution Name and IPO Application No. and then calls the locale script IN_SubmitHALMForASBA for performing the IN_ALT and IN_ALH table operations.

IN_SRV_AddLienOnAcctAndVerify_process_locale_data.scr

This script is called for performing validation and process function in Add mode for HALM menu.

©Copyright Infosys Ltd.

IN_SRV_AddLoan and CLAcct Validate Scripts



Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale validate SRV script is called from HLAGSPM/HCLGSPM in add mode, on click of the submit button in details page. The script calls the locale script IN_validateLocalePH.scr and IN_validatePIFlg.scr for validating the NPA past due normal interest recovery place holder and past due penal interest recovery place holders and Penal Interest Accrual Past Due Flag respectively.

IN_SRV_AddLoanAcctSchmParams_validate_locale_data.scr

IN_SRV_AddCLAcctSchmParams_validate_locale_data.scr

IN_validateLocalePH.scr

IN_validatePIFlg.scr

Input Field	Description
genDtl.schm.schmCode	Scheme code to be verified or cancelled or deleted or undeleted
piIntAccrIPstDueFlg	Penal Interest Accrual Past Due Flag.
pstDueNrIntRvcyPcHdr	Past due normal interest recovery place holder.
pstDuePIIntRvcyPcHdr	Past due penal interest recovery place holders.

This script is called for validation during Add mode of HLAGSPM or HCLGSPM menu option.

IN_SRV_Add LoanAcctSchmParams and CLAcctSchmParams Scripts



Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HLAGSPM or HCLGSPM on click of the Submit button in details page. The script calls the locale script IN_LAGSPM_Add.scr for adding the NPA past due normal interest recovery place holder and past due penal interest recovery place holders.

*IN_SRV_AddLoanAcctSchmParams_process_locale_data.scr,
IN_SRV_AddCLAcctSchmParams_process_locale_data.scr*

IN_LAGSPM_Add.scr

Input Field	Description
genDtl.schm.schmCode	Scheme code to be added
piIntAccrIPstDueFlg	Penal Interest Accrual Past Due Flag
crncyCode	Currency code
pstDueNrIntRvcyPcHdr	Past due normal interest recovery place holder
pstDuePIIntRvcyPcHdr	Past due penal interest recovery place holders.

This script is called for performing Add mode of HLAGSPM or HCLGSPM menu option.

IN_SRV_AddTranAcctSchmParams_validate_local

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale SRV script called from the Add mode of HGSPM. The script further calls the script, IN_ValidatePandLRecoveryPHForGSPM.scr which includes validating the fields "Past Due Normal Interest Recovered Placeholder" and "Past Due Penal Interest Recovered Placeholder" entered from front end.

IN_SRV_AddTranAcctSchmParams_validate_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The Placeholder for Normal Interest recovery of past due accounts.
Past Due Penal Interest Recovered Placeholder	The Placeholder for Penal Interest recovery of past due accounts.

The locale script calls a script to validate the placeholders entered for interest recovery from front end.

The locale script gets called on click of Submit or Validate button from HGSPM details page in ADD mode.

IN_SRV and GSPM Scripts



Note:

This topic describes the enhancements delivered for 10.2.15 release.

The following scripts are available:

IN_SRV_AddTranAcctSchmParams_process_locale_data.scr

IN_SRV_AddTranAcctSchmParams_validate_locale_data.scr

IN_SRV_CancelTranAcctSchmParams_process_locale_data.scr

IN_SRV_DeleteTranAcctSchmParams_process_locale_data.scr

IN_SRV_FetchTranAcctSchmParamsForCancel_process_locale_data.scr

IN_SRV_FetchTranAcctSchmParamsForCopy_process_locale_data.scr

IN_SRV_FetchTranAcctSchmParamsForDelete_process_locale_data.scr

IN_SRV_FetchTranAcctSchmParamsForModify_process_locale_data.scr

IN_SRV_FetchTranAcctSchmParamsForUndelete_process_locale_data.scr

IN_SRV_FetchTranAcctSchmParamsForVerify_process_locale_data.scr

IN_SRV_InquireTranAcctSchmParams_process_locale_data.scr

IN_SRV_ModifyTranAcctSchmParams_process_locale_data.scr

IN_SRV_ModifyTranAcctSchmParams_validate_locale_data.scr

IN_SRV_UndeleteTranAcctSchmParams_process_locale_data.scr

IN_SRV_VerifyTranAcctSchmParams_process_locale_data.scr

IN_GSPM_AddKccData.scr

IN_GSPM_fetchKccData.scr

IN_GSPM_ModifyKccData.scr

IN_GSPM_ProcessKccData.scr

IN_GSPM_ValKccData.scr

IN_GSPMKccCheck.scr

The following are the details of the input fields for the script:

Input Field	Description
KccProductFlg	Kisan Credit Card is applicable for ODA scheme or not with values as Yes/No
CropInsuranceFlg	Crop Insurance applicable for the Kisan Credit Card scheme with values as NAIS/MNAIS
WbcisFlg	Optional Insurance applicable for Kisan Credit card scheme with values as Yes/No.

These scripts are used for the processing of HGSPM menu for Kisan Credit related fields for ODA schemes.

NA

©Copyright Infosys Ltd.

IN_SRV_AddTranAcctSchmParams_process_local

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Process SRV post process scripts in Add mode of HGSPM. The script further calls script, IN_SubmitPandLRecoveryPHForGSPM.scr which processes the values for new fields and adds the value to locale table, IN_GSP for a particular scheme code.

IN_SRV_AddTranAcctSchmParams_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The Placeholder for Normal Interest recovery of past due accounts.
Past Due Penal Interest Recovered Placeholder	The Placeholder for penal Interest recovery of past due accounts.

The values entered from the front end are stored in the table IN_GSP for a particular scheme code.

The locale script gets called on click of Submit from details page of HGSPM in Add function mode.

IN_SRV_CancelFxBillParameter_process_locale_d

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Cancel mode of BTM menu. This script further calls the locale script to process locale field for cancel mode.

IN_SRV_CancelFxBillParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Cancel mode of BTM menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for cancel mode of BTM menu.

NA

IN_SRV_CancelLienOnAcct_process_locale_data.s

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of Submit in Cancel mode. The script calls the locale script IN_SubmitHALMForASBA for performing the IN_ALT and IN_ALH table operations.

IN_SRV_CancelLienOnAcct_process_locale_data.scr

This script is called for performing process function in Cancel mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_CancelTDAcct_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ProcessRDAcct.scr script. This script gets called during the Cancel mode using HOAACVTD menu option.

IN_SRV_CancelTDAcct_process_locale_data.scr Input

This script calls IN_ProcessRDAcct.scr during Cancel mode for cancelling the record in IN_DSI table.

©Copyright Infosys Ltd.

IN_SRV_CancelTranAcctSchmParams_process_lo

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Process SRV post process scripts in Modify mode of HGSPM. The script further calls the script, IN_SubmitPandLRecoveryPHForGSPM.scr to process the values for new fields and verify the values in locale table, IN_GSP for a particular scheme code.

IN_SRV_CancelTranAcctSchmParams_process_locale_data.scr

This script is called for performing process function in Verify mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_CancelFactParameter_process_locale_data

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Cancel mode of MFPS menu. This script further calls the locale script to process locale field for cancel mode.

IN_SRV_CancelFactParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Cancel mode of MFPS menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for cancel mode of MFPS menu.

NA

IN_SRV_DeleteFxBillParameter_process_locale_da

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Delete mode of BTPM menu. This script further calls the locale script to process locale field for delete mode.

IN_SRV_DeleteFxBillParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Delete mode of BTPM menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for delete mode of BTPM menu.

NA

IN_SRV_DeleteFactParameter_process_locale_dat

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Delete mode of BTPM menu. This script further calls the locale script to process locale field for delete mode.

IN_SRV_DeleteFactParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Delete mode of MFPS menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for delete mode of MFPS menu.

NA

IN_SRV_DeleteTranAcctSchmParams_process_loc

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Process SRV post process scripts in Modify mode of HGSPM. The script further calls the script, IN_SubmitPandLRecoveryPHForGSPM.scr to process the values for new fields and delete the values in locale table, IN_GSP for a particular scheme code.

IN_SRV_DeleteTranAcctSchmParams_process_locale_data.scr

This script is called for performing process function in Modify mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchFactParmForCancel_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for cancel mode of MFPS menu. This script further calls the locale script to fetch locale field for cancel mode.

IN_SRV_FetchFactParmForCancel_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Factoring Parameter Type	The Factoring Parameter Type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for cancel mode of MFPS menu. The script has the logic for fetching new locale field.

The script is called on click of GO button for cancel mode of MFPS menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFactParmForCopy_process_locale_c

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Copy mode of MFPS menu. This script further calls the locale script to fetch locale field for various modes.

IN_SRV_FetchFactParmForCopy_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Factoring Parameter Type	The Factoring parameter type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Copy mode of MFPS menu. The script has the logic for fetching new locale field.

The script is called on click of SUBMIT button for copy mode of MFPS menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFactParmForDelete_process_locale_

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for Delete mode of MFPS menu. This script further calls the locale script to fetch locale data for delete mode.

IN_SRV_FetchFactParmForDelete_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Factoring Parameter Type	The Factoring parameter type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Delete mode of MFPS menu. The script has the logic for fetching new locale field.

The script is called on click of SUBMIT button for delete mode of MFPS menu.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchFactParmForInquire_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of Go button for Inquiry mode of MFPS menu. This script further calls the locale script to process locale data for inquiry mode.

NA

IN_SRV_FetchFactParmForInquire_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Factoring Parameter Type	The Factoring parameter type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for Inquire mode of MFPS menu. The script has the logic for processing new locale field.

The script is called on click of GO button for inquire mode of MFPS

menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFactParmForModify_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is the SRV script for modify mode of MFPS menu. It further calls the locale script to fetch the values for locale field in modify mode.

IN_SRV_FetchFactParmForModify_process_locale_data.scr

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called for modify mode of MFPS menu to fetch the value for locale field.

The script is called on the click of GO button for modify mode of MFPS menu.

NA

IN_SRV_FetchFactParmForVerify_process_locale_

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for Verify mode of MFPS menu. This script further calls the locale script to fetch locale field for verify mode.

IN_SRV_FetchFactParmForVerify_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Factoring Parameter Type	The Factoring parameter type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for Verify mode of MFPS menu. The script has the logic for fetching new locale field.

The script is called on click of GO button for verify mode of MFPS menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFxBillParamForCancel_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for cancel mode of BTPM menu. This script further calls the locale script to fetch locale field for cancel modes.

IN_SRV_FetchFxBillParamForCancel_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The Bill type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of Go button for cancel mode of BTPM menu. The script has the logic for fetching new locale field.

The script is called on click of Go button for cancel mode of BTPM menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFxBillParamForModify_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for Modify mode of BTPM menu. This script further calls the locale script to fetch locale field for modify mode.

IN_SRV_FetchFxBillParamForModify_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The Bill type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for Modify mode of BTPM menu. The script has the logic for fetching locale field.

The script is called on click of GO button for modify mode of BTPM menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFxBillParamForCopy_process_local

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of Submit button for Copy mode of BTPM menu. This script further calls the locale script to fetch locale field for various modes.

IN_SRV_FetchFxBillParamForCopy_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The Bill type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Copy mode of BTPM menu. The script has the logic for fetching new locale field.

The script is called on click of SUBMIT button for copy mode of BTPM menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFxBillParamForDelete_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for Delete mode of BTPM menu. This script further calls the locale script to fetch locale data for delete mode.

IN_SRV_FetchFxBillParamForDelete_process_locale_data.scr

The following is the syntax for specifying the input fields:

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The Bill type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Delete mode of BTPM menu. The script has the logic for fetching new locale field.

The script is called on click of SUBMIT button for delete mode of BTPM menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchFxBillParamForUndelete_process_Ic

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for Undelete mode of BTPM menu. This script further calls the locale script to fetch locale field for undelete mode.

NA

IN_SRV_FetchFxBillParamForUndelete_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The Bill type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for Undelete mode of BTPM

menu. The script has the logic for fetching new locale field.

The script is called on click of GO button for undelete mode of BTPM menu.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchLienDtlsForCncl_process_locale_da

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of GO in Cancel mode. The script calls the locale script IN_FetchHALMForASBA.scr for fetching the values of locale fields IPO Institution Name and IPO Application No. from IN_ALT table.

IN_SRV_FetchLienDtlsForCncl_process_locale_data.scr

This script is called for fetch function from locale table in Cancel mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchLienDtlsForVfy_process_locale_data

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of GO in Verify mode. The script calls the locale script IN_FetchHALMForASBA.scr for fetching the values of locale fields IPO Institution Name and IPO Application No. from IN_ALT table.

IN_SRV_FetchLienDtlsForVfy_process_locale_data.scr

This script is called for fetch function from locale table in Verify mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchLienDtIsOnAcForMod_process_loca

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of GO in Modify mode. The script calls the locale script IN_FetchHALMForASBA.scr for fetching the values of locale fields IPO Institution Name and IPO Application No. from IN_ALT table.

IN_SRV_FetchLienDtIsOnAcForMod_process_locale_data.scr

This script is called for fetch function from locale table in Modify mode for HALM menu.

©Copyright Infosys Ltd.

IN_SRV_FetchTDAcctOpenDtIForModify_process_

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ProcessRDAcct.scr. This script gets called during the fetch operation of Modify using HOAACMTD menu option.

IN_SRV_FetchTDAcctOpenDtIForModify_process_locale_data.scr

This script calls IN_ProcessRDAcct.scr during fetch for Modify mode for fetching the debit account ID field.

©Copyright Infosys Ltd.

IN_SRV_FetchTDAcctOpenDtIForVerify_process_lo

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ProcessRDAcct.scr. This script gets called during the fetch operation of Verify using HOAACVTD menu option.

IN_SRV_FetchTDAcctOpenDtIForVerify_process_locale_data.scr

This script calls IN_ProcessRDAcct.scr during fetch for Verify mode for fetching the debit account ID field.

©Copyright Infosys Ltd.

FetchTranAcctSchmParamsForModify_process_lo

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HGSPM on click of Go button in Modify mode. The script calls the locale script IN_FetchPandLRecoveryPHForGSPM.scr for fetching the values of locale fields from IN_GSP table.

IN_SRV_FetchTranAcctSchmParamsForModify_process_locale_data.sc

This script is called for fetch function from locale table in Modify mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchTranAcctSchmParamsForCancel_pr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HGSPM on click of Go button in Verify mode. The script calls the locale script IN_FetchPandLRecoveryPHForGSPM.scr for fetching the values of locale fields from IN_GSP table.

IN_SRV_FetchTranAcctSchmParamsForCancel_process_locale_data.sc

This script is called for fetch function from locale table in Cancel mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchTranAcctSchmParamsForVerify_pro

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HGSPM on click of Go button in Verify mode. The script calls the locale script IN_FetchPandLRecoveryPHForGSPM.scr for fetching the values of locale fields from IN_GSP table.

IN_SRV_FetchTranAcctSchmParamsForVerify_process_locale_data.scr

This script is called for fetch function from locale table in Verify mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchTranAcctSchmParamsForUndelete_

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HGSPM on click of Go button in Undelete mode. The script calls the locale script IN_FetchPandLRecoveryPHForGSPM.scr for fetching the values of locale fields from IN_GSP table.

IN_SRV_FetchTranAcctSchmParamsForUndelete_process_locale_data.

This script is called for fetch function from locale table in Undelete mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchTranAcctSchmParamsForCopy_proc

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HGSPM on click of Go button in Copy mode. The script calls the locale script IN_FetchPandLRecoveryPHForGSPM.scr for fetching the values of locale placeholders from IN_GSP table.

IN_SRV_FetchTranAcctSchmParamsForCopy_process_locale_data.scr

This script is called for fetch function from locale table in Copy mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_Fetch and Inquire Scripts

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HLAGSPM or HCLGSPM on click of the Submit button in details page. The script calls the locale script IN_LAGSPM_Fetch.scr for inquiring or verifying or deleting or undeleting or cancelling the NPA past due normal interest recovery place holder and past due penal interest recovery place holders.

IN_SRV_FetchCLAcctSchmParamsForCancel_process_locale_data.scr

IN_SRV_FetchLoanAcctSchmParamsForVerify_process_locale_data.scr

IN_SRV_FetchCLAcctSchmParamsForCopy_process_locale_data.scr

IN_SRV_FetchCLAcctSchmParamsForDelete_process_locale_data.scr

IN_SRV_FetchCLAcctSchmParamsForModify_process_locale_data.scr

IN_SRV_FetchLoanAcctSchmParamsForCancel_process_locale_data.scr

IN_SRV_FetchCLAcctSchmParamsForUndelete_process_locale_data.scr

IN_SRV_FetchCLAcctSchmParamsForVerify_process_locale_data.scr

IN_SRV_FetchLoanAcctSchmParamsForCopy_process_locale_data.scr

IN_SRV_FetchLoanAcctSchmParamsForDelete_process_locale_data.scr

IN_SRV_FetchLoanAcctSchmParamsForModify_process_locale_data.scr

IN_SRV_FetchLoanAcctSchmParamsForUndelete_process_locale_data.scr

IN_SRV_InquireCLAcctSchmParams_process_locale_data.scr

IN_SRV_InquireLoanAcctSchmParams_process_locale_data.scr

IN_LAGSPM_Fetch.scr

Input Field	Description
genDtl.schm.schmCode	Scheme code to be verified or cancelled or deleted or

	undeleted.
piIntAccrIPstDueFlg	Penal Interest Accrual Past Due Flag.
crncyCode	Currency code.
pstDueNrIntRvcyPcHdr	Past due normal interest recovery place holder
pstDuePIIntRvcyPcHdr	Past due penal interest recovery place holders.

This script is called to perform inquire or verify or delete or undelete or cancel mode of HLAGSPM or HCLGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_FetchFactParmForUndelete_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called on click of GO button for MFPS menu. It further calls the locale script which has the logic to fetch locale data for undelete mode.

IN_SRV_FetchFactParmForUndelete_process_locale_data.scr

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for Undelete mode of MFPS menu. It further calls the locale script to fetch locale data.

The script is called on click of GO button for Undelete mode of MFPS menu.

NA

IN_SRV_FetchFxBillParamForVerify_process_loca

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of GO button for Verify mode of BTPM menu. This script further calls the locale script to fetch locale field for verify mode.

IN_SRV_FetchFxBillParamForVerify_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The bill type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for Verify mode of BTPM menu. The script has the logic for fetching new locale field.

The script is called on click of GO button for verify mode of BTPM menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_FetchLienHistoryRecDtls_process_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of the explode button in details page in History mode. The script calls the locale script IN_almHistDtls.scr for display of the IPO Institution Name and IPO Application number values.

IN_SRV_FetchLienHistoryRecDtls_process_locale_data.scr

This is called for performing fetch of the locale data from IN_ALH in History mode, upon click of explode button.

©Copyright Infosys Ltd.

IN_SRV_FetchLienListRecDtls_process_locale_data

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of the explode button in details page in List mode. The script calls the locale script IN_almListDtls.scr for display of the IPO Institution Name and IPO Application number values.

IN_SRV_FetchLienListRecDtls_process_locale_data.scr

This script is called for performing fetch of the locale data from IN_ALT in List mode, upon click of explode button.

©Copyright Infosys Ltd.

IN_SRV_FetchTDAcctOpenDtIForCancel_process_

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ProcessRDAcct.scr. This script gets called during the fetch operation of Cancel using HOAACVTD menu option.

IN_SRV_FetchTDAcctOpenDtIForCancel_process_locale_data.scr

This script calls IN_ProcessRDAcct.scr during fetch for Cancel mode for fetching the account ID field.

©Copyright Infosys Ltd.

IN_SRV_InquireFxBillParameter_process_locale_d

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of Go button for Inquiry mode of BTPM menu. This script further calls the locale script to process locale data for inquiry mode.

IN_SRV_InquireFxBillParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Bill Type	The Bill type for which the data needs to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of GO button for Inquire mode of BTPM menu. The script has the logic for processing new locale field.

The script is called on click of GO button for inquire mode of BTPM menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_SRV_InquireLienDtls_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of GO in Inquire mode. The script calls the locale script IN_FetchHALMForASBA.scr for fetching the values of locale fields IPO Institution Name and IPO Application No. from IN_ALT table.

IN_SRV_InquireLienDtls_process_locale_data.scr

This script is called for fetch function from locale table in Inquire mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_InquireTranAcctSchmParams_process_lo

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HGSPM on click of Go button in Inquiry mode. The script calls the locale script IN_FetchPandLRecoveryPHForGSPM.scr for fetching the values of locale fields Nrml Int Rec Placeholder and Penal Int Rec Placeholder from IN_GSP table.

IN_SRV_InquireTranAcctSchmParams_process_locale_data.scr

This script is called for fetch function from locale table in Inquiry mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_ModifyFactParameter_validate_locale_dat

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Modify mode of MFPS menu. This script further calls the locale script to validate locale field for modify mode.

IN_SRV_ModifyFactParameter_validate_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Modify mode of MFPS menu. The script has the logic to validate new locale field.

The script is called on click of SUBMIT button to validate locale data for modify mode of MFPS menu.

NA

IN_SRV_ModifyFxBillParameter_process_locale_d

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Modify mode of BTPM menu. This script further calls the locale script to process locale field for modify mode.

IN_SRV_ModifyFxBillParameter_process_locale_data.scr Input

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Modify mode of BTPM menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for modify mode of BTPM menu.

NA

IN_SRV_ModifyFxBillParameter_validate_locale_data

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Modify mode of BTPM menu. This script further calls the locale script to validate locale field for modify mode.

IN_SRV_ModifyFxBillParameter_validate_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Modify mode of BTPM menu. The script has the logic to validate new locale field.

The script is called on click of SUBMIT button to validate locale data for modify mode of BTPM menu.

NA

IN_SRV_ModifyLienOnAcct_process_locale_data.s

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of Submit in Modify mode. The script calls the locale script IN_ValidateHALMForASBA.scr for validating the values of locale fields IPO Institution Name and IPO Application No. and then calls the locale script IN_SubmitHALMForASBA for performing the IN_ALT and IN_ALH table operations.

IN_SRV_ModifyLienOnAcct_process_locale_data.scr

This script is called for performing validation and process function in Modify mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_ModifyLienOnAcctAndVerify_process_loc

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of Submit in Modify mode when auto verification is enabled. The script calls the locale script IN_ValidateHALMForASBA.scr for validating the values of locale fields IPO Institution Name and IPO Application No. and then calls the locale script IN_SubmitHALMForASBA for performing the IN_ALT and IN_ALH table operations.

IN_SRV_ModifyLienOnAcctAndVerify_process_locale_data.scr

This script is called for performing validation and process function in Modify mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_Modify LoanAcctSchmParams and CLAcctSchmParams Scripts



Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HLAGSPM or HCLGSPM on click of the Submit button in details page. The script calls the locale script IN_LAGSPM_Modify.scr for modifying the NPA past due normal interest recovery place holder and past due penal interest recovery place holders.

IN_SRV_ModifyLoanAcctSchmParams_process_locale_data.scr,

IN_SRV_ModifyCLAcctSchmParams_process_locale_data.scr

IN_LAGSPM_Modify.scr

Input Field	Description
genDtl.schm.schmCode	Scheme code to be modified
piIntAccrIPstDueFlg	Penal Interest Accrual Past Due Flag
crncyCode	Currency code
pstDueNrIntRvcyPcHdr	Past due normal interest recovery place holder
pstDuePIIntRvcyPcHdr	Past due penal interest recovery place holders.

This script is called for performing Modify mode of HLAGSPM or HCLGSPM menu option

IN_SRV_Modify LoanAcct and CLAcct Validate Scripts



Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale validate SRV script is called from HLAGSPM or HCLGSPM in Modify mode, on click of the Submit button in details page. The script calls the locale script IN_validateLocalePH.scr and IN_validatePIFlg.scr for validating the NPA past due normal interest recovery place holder and past due penal interest recovery place holders and Penal Interest Accrual Past Due Flag respectively.

IN_SRV_ModifyLoanAcctSchmParams_validate_locale_data.scr

IN_SRV_ModifyCLAcctSchmParams_validate_locale_data.scr

IN_validateLocalePH.scr

IN_validatePIFlg.scr

Input Field	Description
genDtl.schm.schmCode	Scheme code to be verified or cancelled or deleted or undeleted.
piIntAccrIPstDueFlg	Penal Interest Accrual Past Due Flag.
pstDueNrIntRvcyPcHdr	Past due normal interest recovery place holder.
pstDuePIIntRvcyPcHdr	Past due penal interest recovery place holders.

This script is called for validation during Modify mode of HLAGSPM or HCLGSPM menu option.

IN_SRV_ModifyTDAcct_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ProcessRDAcct.scr script. This script gets called during the Modify mode using HOAACMTD menu option.

IN_SRV_ModifyTDAcct_process_locale_data.scr

This script calls IN_ProcessRDAcct.scr during Modify mode for modifying the record in IN_DSI table.

©Copyright Infosys Ltd.

IN_SRV_ModifyTDAcct_validate_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ValidateINDSI.scr. This script gets called during the modification of the account using HOAACMTD menu option.

IN_SRV_ModifyTDAcct_validate_locale_data.scr

This script calls IN_ValidateINDSI.scr which performs the validations during modify mode.

©Copyright Infosys Ltd.

IN_SRV_ModifyTranAcctSchmParams_process_lo

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Process SRV post process scripts in Modify mode of HGSPM. The script further calls the script, IN_SubmitPandLRecoveryPHForGSPM.scr to process the values for new fields and modify the values in locale table, IN_GSP for a particular scheme code.

IN_SRV_ModifyTranAcctSchmParams_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The Placeholder for Normal Interest recovery of past due accounts.
Past Due Penal Interest Recovered Placeholder	The Placeholder for Penal Interest recovery of past due accounts.

The values modified from the front end are stored in the table IN_GSP for a particular scheme code.

The locale script gets called on click of Submit from details page of HGSPM in Modify function mode.

IN_SRV_ModifyTranAcctSchmParams_validate_locale

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Modify mode of HGSPM. The script further calls the script, IN_ValidatePandLRecoveryPHForGSPM.scr which validates the fields "Past Due Normal Interest Recovered Placeholder" and "Past Due Penal Interest Recovered Placeholder" modified from front end.

IN_SRV_ModifyTranAcctSchmParams_validate_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The Placeholder for Normal Interest recovery of past due accounts.
Past Due Penal Interest Recovered Placeholder	The Placeholder for penal Interest recovery of past due accounts.

The locale script calls a script to validate the placeholders modified for interest recovery from front end.

The locale script gets called on click of Submit or Validate button from HGSPM details page in MODIFY mode.

IN_SRV_OpenTDAcct_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ProcessRDAcct.scr. This script gets called during the account opening using HOAACTD menu option.

IN_SRV_OpenTDAcct_process_locale_data.scr

This script calls the IN_ProcessRDAcct.scr which inserts a record into IN_DSI table.

©Copyright Infosys Ltd.

IN_SRV_OpenTDAcct_validate_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ValidateINDSI.scr. This script gets called during the account opening using HOAACTD menu option.

IN_SRV_OpenTDAcct_validate_locale_data.scr

This script calls IN_ValidateINDSI.scr which performs the validations during account opening.

©Copyright Infosys Ltd.

IN_SRV_UndeleteFactParameter_process_locale_c

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Undelete mode of MFPS menu. This script further calls the locale script to process locale field for modify mode.

IN_SRV_UndeleteFactParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Undelete mode of MFPS menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for undelete mode of MFPS menu.

IN_SRV_UndeleteFxBillParameter_process_locale_

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Undelete mode of BTM menu. This script further calls the locale script to process locale field for modify mode.

IN_SRV_UndeleteFxBillParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Undelete mode of BTM menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for undelete mode of BTM menu.

NA

IN_SRV_UndeleteTranAcctSchmParams_process_

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Process SRV post process scripts in Modify mode of HGSPM. The script further calls the script, IN_SubmitPandLRecoveryPHForGSPM.scr to process the values for new fields and undelete the values in locale table, IN_GSP for a particular scheme code.

IN_SRV_UndeleteTranAcctSchmParams_process_locale_data.scr

This script is called for performing process function in Undelete mode for HGSPM menu option.

©Copyright Infosys Ltd.

IN_SRV_Verify, Undelete, Cancel, Delete LoanAcct and CLAcct.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HLAGSPM or HCLGSPM on click of the Submit button in details page. The script calls the locale script IN_LAGSPM_VXDUMode.scr for verifying or deleting or undeleting or canceling the NPA past due normal interest recovery place holder and past due penal interest recovery place holders.

IN_SRV_VerifyLoanAcctSchmParams_process_locale_data.scr

IN_SRV_VerifyCLAcctSchmParams_process_locale_data.scr

IN_SRV_UndeleteLoanAcctSchmParams_process_locale_data.scr

IN_SRV_UndeleteCLAcctSchmParams_process_locale_data.scr

IN_SRV_CancelLoanAcctSchmParams_process_locale_data.scr

IN_SRV_CancelCLAcctSchmParams_process_locale_data.scr

IN_SRV_DeleteLoanAcctSchmParams_process_locale_data.scr

IN_SRV_DeleteCLAcctSchmParams_process_locale_data.scr

Input Field	Description
genDtl.schm.schmCode	Scheme code to be verified or cancelled or deleted or undeleted
piIntAccrIPstDueFlg	Penal Interest Accrual Past Due Flag
crncyCode	Currency code
pstDueNrIntRvcyPcHdr	Past due normal interest recovery place holder
pstDuePIIntRvcyPcHdr	Past due penal interest recovery place holders.

This script is called for performing verify or delete or undelete or cancel mode of HLAGSPM or HCLGSPM menu option.

©Copyright Infosys Ltd.

Finaacle Copyright

IN_SRV_VerifyFactParameter_process_locale_data

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Verify mode of MFPS menu. This script further calls the locale script to process locale field for modify mode.

IN_SRV_VerifyFactParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Verify mode of MFPS menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for verify mode of MFPS menu.

NA

IN_SRV_VerifyFxBillParameter_process_locale_da

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This SRV script is called on click of SUBMIT button for Verify mode of BTPM menu. This script further calls the locale script to process locale field for modify mode.

IN_SRV_VerifyFxBillParameter_process_locale_data.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called on click of SUBMIT button for Verify mode of BTPM menu. The script has the logic for processing new locale field.

The script is called on click of SUBMIT button for verify mode of BTPM menu.

NA

IN_SRV_VerifyLienOnAcct_process_locale_data.sc

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale post process SRV script is called from HALM on click of Submit in Verify mode. The script calls the locale script IN_SubmitHALMForASBA for performing the IN_ALT and IN_ALH table operations.

IN_SRV_VerifyLienOnAcct_process_locale_data.scr

This script is called for performing process function in Verify mode for HALM menu option.

©Copyright Infosys Ltd.

IN_SRV_VerifyTDAcct_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ProcessRDAcct.scr and IN_processRDSI.scr scripts. This script gets called during the Verify mode using HOAACVTD menu option.

IN_SRV_VerifyTDAcct_process_locale_data.scr

This script calls IN_ProcessRDAcct.scr during Verify mode for verifying the record in IN_DSI table and IN_processRDSI.scr for creating the Standing Instructions.

©Copyright Infosys Ltd.

IN_SRV_VerifyTDAcct_validate_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_ValidateINDSI.scr. This script gets called during the verification of the account using HOAACVTD menu option.

IN_SRV_VerifyTDAcct_validate_locale_data.scr

This script calls IN_ValidateINDSI.scr which performs the validations during verify.

IN_SRV_VerifyTranAcctSchmParams_process_loc

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Process SRV post process scripts in Modify mode of HGSPM. The script further calls the script, IN_SubmitPandLRecoveryPHForGSPM.scr to process the values for new fields and verify the values in locale table, IN_GSP for a particular scheme code.

IN_SRV_VerifyTranAcctSchmParams_process_locale_data.scr

This script is called for performing process function in Verify mode for HGSPM menu option.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from the SRV post process scripts in Add or Modify or Verify or Cancel or Copy from Template modes of HALM. The script performs the locale data updation and insertion into IN_ALT and IN_ALH using processing table.

IN_SubmitHALMForASBA.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The account on which lien is marked.
Lien Reason Code	The lien reason code of each MRH record from HALM details page.
IPO Institution Name	The IPO Institution name for the ASBA lien record.
Ipo Application Number	The IPO Application number for the ASBA lien record.

Processes each record in the link list one by one. If ASBA lien record, then performs the required proc table operation in IN_ALT depending on the function code (Add/Modify/Cancel/Verify). Also if the verification is successful, the record is inserted to Lien History table IN_ALH.

The locale script gets executed on click of Submit from details page of HALM in Add or Modify or Verify or Cancel or Copy from Template modes.

IN_SubmitLocaleDataForBills.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from SRV scripts of BTPM menu for different modes. This script has the logic to process locale data for various modes.

IN_SubmitLocaleDataForBills.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from SRV scripts of BTPM menu. The script has the logic to fetch the action code based on the calling SRV.

The script is called from locale script, IN_FetchLocaleDataForTfin.scr.

NA

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from various SRV scripts of MFPS menu for different modes. This script has the logic to process locale data for various modes.

IN_SubmitLocaleDataForFactoring.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from various SRV scripts of MFPS menu. The script has the logic to fetch the action code based on the calling SRV.

The script is called from locale script, IN_FetchLocaleDataForTfin.scr.

NA

IN_SubmitLocaleDataForTfin.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from SRV scripts of BTPM and MFPS menu for different modes. This script has the logic to process locale data for different modes. It further calls the locale scripts to fetch action code based on the calling SRV for BTPM and MFPS menu.

IN_SubmitLocaleDataForTfin.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from SRV scripts of BTPM and MFPS menu. The script has the logic to process the locale field data for these menu.

The script is called from SRV scripts of BTPM and MFPS menu for different modes.

NA

IN_SubmitPandLRecoveryPHForGSPM.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script is called from HGSPM menu option on click of Submit button. The script is called from different SRV scripts to submit the data to locale table, IN_GSP for different modes.

IN_SubmitPandLRecoveryPHForGSPM.scr

This script is called for submitting the data to locale table for different modes of HGSPM menu option.

©Copyright Infosys Ltd.

IN_SubmitPandLRecoveryPHForGSPM.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from SRV scripts of GSPM menu to process the locale data. This script is modified to add the processing for PCA scheme type.

IN_SubmitPandLRecoveryPHForGSPM.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from SRV scripts of GSPM menu. The script has been modified to add the logic to process locale data for PCA scheme type.

The script is called from locale script, IN_FetchLocaleDataForTfin.scr.

IN_Suit_Report.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for generating the suit filed accounts report in HPR menu.

IN_Suit_Report.scr

The following are the details of the input fields for the script:

Input Field	Description
As on date	As on date is set in the HBJSTM menu.
SOL Set ID	Sol set ID set in the HBJSTM menu.

NA

Inputs are obtained from the HBJSTM menu and procedure is called. Procedure returns the 1st file and this file is used to generate the suit filed accounts report.

Automated report generation.

©Copyright Infosys Ltd.

IN_Suit_Report_custval.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from HBJSTM menu for validating the input fields in IN_Suit_Report.jasper.

IN_Suit_Report_custval.scr

The following are the details of the input fields for the script:

Input Field	Description
As on date	As on date is set in the jasper file.
SOL set ID	SOL set ID set in the jasper file.

Inputs are obtained from the jasper. Validations for inputs are handled in this script

©Copyright Infosys Ltd.

IN_Suit_Report_defaultpop.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This locale script is called from jasper file IN_Suit_Report.jasper for generating the suit filed accounts report.

IN_Suit_Report_defaultpop.scr

Context bank ID

The script is called from the jasper file and it populates the context bank ID as a hidden input to the jasper.

NA

©Copyright Infosys Ltd.

IN_TDSInsert.scr (15AA)

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called to insert the data in IN_TDS table from txuu9407.cxx.

IN_TDSInsert.scr

The following are the details of the input fields for the script:

Input Field	Description
sol_id	SOL ID from TDS table.
cust_id	Customer ID from TDS table.
tds_cert_num	Tds_cert_num from TDS table.
tran_date	Transaction date from TDS table.
exmp_srl_num	Exmp_srl_num from IN_TECT table.

This script adds the record in IN_TDS table.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The script gets called from the verify post process of SB and CA accounts. This script activates the Welcome Kit generated accounts when the inactive account is modified for the first time through HACM.

IN_updateAcctOpnDateForWKIT.scr

This script gets called from the verify post process of SB and CA accounts. It checks whether the account is inactive. If the account is not activated, then it activates the account.

This script gets called from the Verify post process of HACM menu to activate the account through manual process.

©Copyright Infosys Ltd.

IN_uploadDistSolDetails.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script is used for uploading district code and name for a sol ID. The input required for uploading details must be given in the form of a text file, "IN_uploadDistSolDetails.txt". The text file should be placed in the cdc_logs. This enables bulk upload of data, each line in the text file is inserted to IN_DSL table if the entries are valid. In each record, first 8-spaces are meant for SOL ID, next 5 spaces for district code and next 50 spaces for district name. The data must be entered only at specified locations.

Based on the upload, success and failure reports are generated.

IN_uploadDistSolDetails.scr

The following are the details of the input fields for the script:

Input Field	Description
SOL ID	SOL ID occupies first 8 spaces (1 to 8) in each row of the test file.
District Code	District Code should be given from column 9 to 13 in each row of the test file.
District Name	District Code should be given from column 14 to 63 in each row of the test file.

The values entered in the test file will be added if not present in the table or modified if present for a valid SOL ID.

The locale script can be used for bulk upload of district details for a

SOL ID

©Copyright Infosys Ltd.

Finacle Copyright

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script called from the Process SRV post process scripts in Add or Modify or Copy from Template modes of HALM. The script includes the validations for IPO Institution Name and IPO Application Number values entered for each ASBA lien record. This script also validates all the setups required.

IN_ValidateHALMForASBA.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The account on which lien is marked.
Lien Reason Code	The lien reason code of each MRH record from HALM details page.
IPO Institution Name	The IPO Institution name for the ASBA lien record.
Ipo Application Number	The IPO Application number for the ASBA lien record.

Compares the lien reason code of each MRH record with ASBA lien reason code. If the record is ASBA lien, then the script validates the IPO Institution name and IPO application number values entered. It populates front end error in case of validation failure.

The locale script gets called on click of Submit from details page of HALM in Add and Modify function modes.

IN_ValidateINDSI.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

The script is used to perform the necessary validations required during the opening of Recurring Deposit for Standing Instructions.

IN_ValidateINDSI.scr

This script performs the validations required for creating the Standing Instructions during RD account opening.

©Copyright Infosys Ltd.

IN_ValidateKitRequest.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_OpenKitAccounts.scr for dummy account opening and IN_reportGen.scr for success and failure report generation.

IN_ValidateKitRequest.scr

This script is called by IN_KitBatchCall.scr as a batch script in Verify mode for GWK menu.

©Copyright Infosys Ltd.

IN_ValidateLocaleDataForTfin.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from SRV scripts of BTPM and MFPS menu for add and modify modes. This script has the logic to validate locale data for various modes.

IN_ValidateLocaleDataForTfin.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from add and modify SRV scripts of BTPM and MFPS menu. The script has the logic validate the locale field being added or modified.

The script is called from SRV scripts for add and modify mode to validate the locale field.

NA

IN_ValidatePandLRecoveryPHForGSPM.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The locale script is called from HGSPM menu option on click of the Submit button. The script validates the locale fields added.

IN_ValidatePandLRecoveryPHForGSPM.scr

This script is called for validating the locale fields for HGSPM in various modes.

©Copyright Infosys Ltd.

IN_ValidatePandLRecoveryPHForGSPM.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is called from SRV scripts of HGSPM menu to validate locale data for ADD and MODIFY modes. This script is modified to add the logic to add the validation for PCA scheme type.

IN_ValidatePandLRecoveryPHForGSPM.scr

The following are the details of the input fields for the script:

Input Field	Description
Past Due Normal Interest Recovered Placeholder	The locale field to add the placeholder value for recovery.

The script is called from SRV scripts of HGSPM menu to validate locale data. The code is added for PCA scheme type validation.

The script is called from SRV scripts of HGSPM menu.

NA

Scripts for Islamic Banking

IN_WeightedCalculationInsert.scr (15AA)

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This is called to insert the data in IN_WTC table from txuu9407.cxx.

IN_WeightedCalculationInsert.scr

The following are the details of the input fields for the script:

Input Field	Description
cust_id	Customer ID of the customer.
tran_id	Tran_id from TDS table.
Acid	acid from TDS table.
tds_cert_num	Tds_cert_num from TDS table.
int_amt	int_amt from TDS table.
tran_date	Tran_date from TDS table.
amt_tbl_code	Amt_tbl_code from IN_TECT or tds_tbl_code attached to CIF.
tds_crncy_code	Tds_Crncy_code from TDS table.
crncy_code	Crncy_code from TDS table.
int_tds_coll	Total interest for which TDS has been collected so far.
sol_id	The service outlet to which the account belongs to.

Input Field	Description
successOrFailure	To return success or failure.
errorMessage	Error message in case of failure.

This script calculates the TDS based on weighted method and adds the record in IN_WTC table.

©Copyright Infosys Ltd.

IN_welcomeKitAcctCustDtl.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script calls IN_welcomeKitInsertAcctDtl.scr and IN_welcomeKitInsertCustDtl.scr.

IN_welcomeKitAcctCustDtl.scr

All USPC fields defined in the Upload formats section.

successOrFailure and errorMessage

This script get inputs from IN_bbuu8076.cxx (USPC fields) and based on the procTbl insert or modify passes successOrFailure and errorMessage as output to IN_bbuu8076.cxx.

©Copyright Infosys Ltd.

IN_welcomeKitInsertAcctDtl.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is used for procTbl insert or modify to IN_ADA table.

IN_welcomeKitInsertAcctDtl.scr

Only meant for procTbl insert or modify to IN_ADA table.

©Copyright Infosys Ltd.

IN_welcomeKitInsertCustDtl.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is used for procTbl insert or modify to IN_KCD table.

IN_welcomeKitInsertCustDtl.scr

Only meant for procTbl insert or modify to IN_KCD table.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The script is used to activate the newly created accounts created for Welcome Kit. It collates the accounts and corresponding details. Processing was done record wise to activate the accounts. The success and failure reports are generated. The success report contains the list of accounts which got activated and the failure report contains the failed accounts along with the reason for its failure.

IN_WKITAccountActivation.scr

This script lists out the accounts and the corresponding details that required for activation. Processing was done account wise and it does the following steps to activate the account:

- Updates the nomination and joint holder details

- Unfreezing the account

- Changing the account open date to BOD date and

- Activates the account by setting the flag to Y in IN_ADA
ole. Success and Failure reports are generated accordingly.

This script is HBJSTM enabled so that it can be run periodically to activate the accounts.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is used for modifying different types of Account Closure Charges through HCACC menu.

modChrgAmt.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.compB2kld	This field specifies the account number on which the charges are imposed,
BANCS.INPUT.compB2kldType	This field specifies the entity type.
BANCS.INPUT.srlNum	Charge part transaction serial number.
BANCS.INPUT.chrgTranDate	Transaction date of the charge part transaction.
BANCS.INPUT.chrgTranId	Transaction ID of the Charge Collection.
BANCS.INPUT.parentTranSrlNum	Parent Transaction serial number for which the reversal has happened.
BANCS.INPUT.eventId	Event ID of Charge Collection.
BANCS.INPUT.eventType	Event Type of Charge Collection.
BANCS.INPUT.solId	Service Branch Sol ID.
BANCS.INPUT.systemCalcAmt	System calculated charge amount.
BANCS.INPUT.actualAmtColl	This field specifies the actual charge collected amount.
BANCS.INPUT.collCncyCode	Collection Currency Code.
BANCS.INPUT.tranParticular	Field provided for entering particulars of transaction.
BANCS.INPUT.tranRmks	Field for entering any remarks that the user wants to put.

BANCS.INPUT.chrgAcctAcid	This is the charge account Acid.
BANCS.INPUT.targetAcctAcid	This stores the acid for which the collection has happened.
BANCS.INPUT.chrgRptCode	Transaction Report Code.
BANCS.INPUT.rate1	Rate used for conversion between currencies using rate 1.
BANCS.INPUT.ptranBusType	Part Tran Business type.
BANCS.INPUT.consolDebitPtranFlg	Indicator to merge customer part transaction debit or not.
BANCS.INPUT.partTranType	Part transaction type, Credit or Debit.
BANCS.INPUT.parentTranId	Parent Transaction ID for which the reversal has happened.
BANCS.INPUT.parentTranDate	Parent Transaction date for which the reversal has happened.
BANCS.INPUT.chrgPartTranSrlNum	Part transaction serial number of the charge part transaction.
BANCS.INPUT.custId	Customer ID who is giving the charge.
BANCS.INPUT.rateCode1	Rate code used for Normal MC scenario.
BANCS.INPUT.modifyFlg	This is the modifiable indicator set up at the HPTTM level. This field specifies whether the charge amount can be modified or not.
BANCS.INPUT.amtWithoutDiscount	The output amount with no CLC (customer level discount) / CTG (channel level discount) effect.
BANCS.INPUT.amtAfterFirstLevelDiscount	The output amount after CLC / CTG effect based on GCT field channel_pref_bef_cust_pref. If this flag is Y, then this amount is after channel discount(CTG), else after customer level(CLC) discount.
BANCS.INPUT.channelId	Channel ID from where the transaction has happened.
BANCS.INPUT.amtBeforeAddtnIDisc	This is the amount left after Channel Level and Customer Level Discounts are applied to the actual Charge-Amount before considering additional discount.
BANCS.INPUT.contraPtranSrlNum	Serial number of entries in CXL made under a single charge transaction ID.

BANCS.INPUT.chrgReasonCode	This code indicates the reason for charge.
BANCS.INPUT.dfltChrgCalcFlg	Default charge calculated flag.
BANCS.INPUT.relPricingRefNum	Relationship pricing reference number.

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.outActAmtColl	This field specifies the actual charge collected amount.

©Copyright Infosys Ltd.

MT700EventMapping.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is modified as part of the changes done for Goods Purchased through Third Party agents.

For Wakala Murabaha Documentary Credit if Goods Purchase through Third Party is YES. Third party agent addresses fields in the SWIFT address explode are tagged to the field 50 of the MT 700 swift message. Else applicant address fields are tagged to the field 50 of the MT 700 swift message.

MT700EventMapping.scr

The following are the details of the input fields for the script:

Input Field	Description
GoodsPThruThirdAgent	Goods Purchased through Third Party agents flag
ThirdPartyName	Third Party Agent Name
ThirdPartyAddr1	Third Party Agent Address Field 1
ThirdPartyAddr2	Third Party Agent Address Field 2
ThirdPartyAddr3	Third Party Agent Address Field 3

NA

NA

The changes are used to populate field 50 of MT700 sift message with third party agent details or applicant details based on goods purchased through third party agent flag.

NA

©Copyright Infosys Ltd.

PurchaseAcptAdvice.scr



Note:

This topic describes the enhancements delivered for 10.2.15 release.

This script is written to generate message 799 to Generate Purchase Acceptance Advice for Shipping Guarantee or delivery order.

This script is written to generate message 799 to Generate Purchase Acceptance Advice for Shipping Guarantee or delivery order.

PurchaseAcptAdvice.scr

The following are the details of the input fields for the script:

Input Field	Description
bgSrlNum	Bank Guarantee serial number
billLadingNo	Bill lading no
billEqAmt	Bill equivalent amount
TransReference	Transaction reference
RelatedRefNum	Related reference number
Narrative	Narrative field

NA

NA

Used to generate message 799

NA

©Copyright Infosys Ltd.

Finacle Copyright

Scripts added for PPF Accounts and Special RD Enhancements



Note:

This topic describes the enhancements delivered for 10.2.15 release.

Script	Remarks
SSSCHMCODE_PostQry.scr	Added
USSAGSD_pre_gbsrv_invoke.scr	Reconciled from 10.5.2. New in 10.2.15. Added
IN_BRLISSAS_Transcr	Added
IN_SSALOAN_PostQry.scr	Added
IN_fetchPPFAcctDtls.scr	Added
IN_getCatAndSubcatParameter.scr	Added
IN_getPPFAcctDtls.scr	Added
IN_getPPFAcctTranAmt.scr	Added
IN_ppfAcctIntAccrual.scr	Added
calcInterestForSplRDPreClose.scr	Added
checkPSSeligibility.scr	Added
getMinBalValues.sscr	Added
RDUptInstallmentScript.scr	Added

©Copyright Infosys Ltd.

Finacle Copyright

Note:

This topic describes the enhancements delivered for 10.2.15 release.

DCEMCorrection_fcV10R2P14-V10R2P15.sql

This script is added as part of the Amendment of Reimbursement Bank Details.

```
Rem
*****

Rem          Source          : upd_DCEM.sql

Rem          Description      : Update DCEM for
new fields

Rem
*****

prompt Update DCEM with Data from DCMM

set serveroutput on size 100000
spool andLogFileName

DECLARE

    COMMIT_COUNTER          NUMBER;

    TOT_COMMIT_COUNTER      NUMBER;

-- The following cursor filters DCs which have
valid purchase reference:

-- number mapped
```

```

CURSOR    DC_CURSOR IS
SELECT    A.dc_ref_num,
          A.reimb_ind,
          A.reimb_applicable_rule,
          A.nostro_acct_num,
          A.dc_b2kid,
          A.sol_id,
          A.reimb_bank_code,
          A.reimb_branch_code,
          A.bank_id
FROM      TBAADM.DCMM A
WHERE     A.del_flg != 'Y'
ORDER BY A.dc_ref_num ASC;

BEGIN
--{
    COMMIT_COUNTER := 0;
    FOR DC_REC IN DC_CURSOR
    LOOP
        --{
            BEGIN
                UPDATE TBAADM.DCEM
                    SET reimb_ind =
DC REC.reimb ind,
```

```

                                reimb_applicable_rule =
DC_REC.reimb_applicable_rule,

                                nostro_acct_num =
DC_REC.nostro_acct_num,

                                reimb_bank_code =
DC_REC.reimb_bank_code,

                                reimb_branch_code =
DC_REC.reimb_branch_code

```

```

WHERE

```

```

    dc_b2kid = DC_REC.dc_b2kid

```

```

    AND bank_id = DC_REC.bank_id;

```

```

    COMMIT_COUNTER := COMMIT_COUNTER

```

```

+ 1;

```

```

EXCEPTION

```

```

    WHEN OTHERS THEN

```

```

        --{

```

```

                                DBMS_OUTPUT.PUT_LINE('Exce
occured for DC :' || DC_REC.dc_ref_num);

```

```

                                DBMS_OUTPUT.PUT_LINE('sol
id :' || DC_REC.sol_id);

```

```

        --}

```

```

    END;

```

```

    --}

```



```

END LOOP;

COMMIT;

        DBMS_OUTPUT.PUT_LINE('Total    Number    of
Accounts          corrected          : ' ||
to_char(COMMIT_COUNTER));
--}

END;

/

spool off

```

TFISetCorrection_fcV10R2P14-V10R2P15.sql

This script is added as part of the Generation of Purchase Acceptance Advice:

```

Rem
*****>

Rem Source      : TFISetCorrection_fcV10R2P14-V10R2P15.sql

Rem Description  : Migration of Murabaha SG or DO under collection
from 10.2.14 to 10.2.15,

Rem              a. Promise to Purchase Received   -   Yes

Rem              b. Promise to Purchase Date       -   Issue Date
of Guarantee

Rem              c. Promise to Purchase Ref No.    -   MIGRATION

Rem              d. Purchase Acceptance Advice.    -   Yes.

Rem
*****>

```

prompt updating records in TFISSET...

set serveroutput on size 100000

DECLARE

COMMIT_COUNTER NUMBER;

TOT_COMMIT_COUNTER NUMBER;

CURSOR BGM_CURSOR IS

SELECT B.bg_b2kid,B.issue_date,B.bg_srl_num,B.bank_id

FROM TBAADM.BGM B,

TBAADM.SGM S,

TBAADM.BGP P

WHERE P.bg_type = B.bg_type and P.bg_sub_type in ('S','R')

AND P.bank_id = B.bank_id AND P.bank_id = S.bank_id

AND S.bg_b2kid = B.bg_b2kid

AND S.dc_ref_num is null

AND B.bg_type in(

SELECT param_type

FROM TFISPT

WHERE ISLAMIC_FINANCING_TYPE ='M' AND entity_type

= 'BNKGR'

);

BEGIN

--{

COMMIT_COUNTER := 0;

TOT_COMMIT_COUNTER := 0;

FOR BGM_REC IN BGM_CURSOR

```

LOOP
--{
    BEGIN

        UPDATE TBAADM.TFISSET SET
        PROMISE_TO_PURCHASE_DATE = BGM_REC.issue_date,
        PROMISE_TO_PURCHASE_REFNO = 'MIGRATION',
        PROMISE_TO_PURCHASE_RCVD = 'Y',
        PURCHASE_ACCEPTANCE_ADVICE = 'Y'
        WHERE
        TFISSET.ENTITY_B2KTYPE = 'BNKGR'
        AND TFISSET.ENTITY_B2KID = BGM_REC.bg_b2kid
        AND TFISSET.BANK_ID = BGM_REC.bank_id;

        COMMIT_COUNTER := COMMIT_COUNTER + 1;
        TOT_COMMIT_COUNTER := TOT_COMMIT_COUNTER + 1;

    EXCEPTION

        WHEN OTHERS THEN
            --{
                DBMS_OUTPUT.PUT_LINE('Exception occurred for
                Guarantee Number : ' || BGM_REC.bg_srl_num);
            --}
        END;

        IF (MOD(COMMIT_COUNTER, 300) = 0) THEN
            --{
                DBMS_OUTPUT.PUT_LINE('Number of Guarantee Nos
                corrected till now : ' || to_char(COMMIT_COUNTER));
            --}
        END IF;
    END LOOP;

```

```

        COMMIT_COUNTER :=0;
        COMMIT;
    --}
    END IF;
--}
END LOOP;

COMMIT;

        DBMS_OUTPUT.PUT_LINE('Total Number of Guarantee Nos
corrected : ' || to_char(TOT_COMMIT_COUNTER));
--}
END;
/
spool off
upd_DCMM_fcV10R2P14_V10R2P15.sql
This script is added as part of the Auto reimbursement claim.

Rem
*****>
Rem    Source      : upd_DCMM_fcV10R2P14_V10R2P15.sql
Rem    Description  : Update script for DCMM table
Rem    From Version : Finacle 10.2.14
Rem    To Version   : Finacle 10.2.15
Rem
*****>

prompt Updating the table DCMM

update DC_MAST_MAIN_TABLE
SET autoreimb_claim_flg = 'N'

```

```

WHERE dc_reg_type in (SELECT reg_type
                      FROM DC_REGISTER_MAIN_TABLE
                      WHERE inw_out_dc_ind = 'I')
AND del_flg != 'Y'
AND date_clsd IS NULL
AND autoreimb_claim_flg IS NULL
/
commit

Rem *****
*****
END

```

alt_add_BGM.sql

```

prompt Adding columns in BGM:
Alter table BG_MASTER_TABLE add
(
coll_bank_code varchar(6 char),
coll_br_code varchar(6 char),
exp_party_code varchar(9 char)
)
/

```

upd_TFISSET_for_Promise_to_Purchase_fcV10R2P13-V10R2P14.sql

```

Rem *****
*****

Rem Source :
TFISSETCorrectionForPromPurchaseFlds.sql

Rem Description : Migration of Murabaha SG or DO under
collection from 10.2.14 to 10.2.15,

```

Rem a. Promise to Purchase Received - Yes
 Rem b. Promise to Purchase
 Date - Issue Date of Guarantee
 Rem c. Promise to Purchase Ref
 No. - MIGRATION
 Rem d. Purchase Acceptance
 Advice. - Yes.
 Rem
 *****>

prompt updating records in TFISSET...

set serveroutput on size 100000
 spool andLogFileName

DECLARE

COMMIT_COUNTER NUMBER;
 TOT_COMMIT_COUNTER NUMBER;

CURSOR BGM_CURSOR IS

SELECT B.bg_b2kid,B.issue_date,B.bg_srl_num,B.bank_id
 FROM TBAADM.BGM B,

TBAADM.SGM S,

TBAADM.BGP P

WHERE P.bg_type = B.bg_type and P.bg_sub_type in ('S','R')
 AND P.bank_id = B.bank_id AND P.bank_id = S.bank_id
 AND S.bg_b2kid = B.bg_b2kid
 AND S.dc_ref_num is null
 AND B.bg_type in(
 SELECT param_type

```
FROM TFISPT
WHERE ISLAMIC_FINANCING_TYPE = 'M' AND entity_type
= 'BNKGR'
);
```

```
BEGIN
```

```
--{
```

```
    COMMIT_COUNTER := 0;
```

```
    TOT_COMMIT_COUNTER := 0;
```

```
FOR BGM_REC IN BGM_CURSOR
```

```
LOOP
```

```
--{
```

```
    BEGIN
```

```
        UPDATE TBAADM.TFISSET SET
        PROMISE_TO_PURCHASE_DATE = BGM_REC.issue_date,
```

```
        PROMISE_TO_PURCHASE_REFNO = 'MIGRATION',
```

```
        PROMISE_TO_PURCHASE_RCVD = 'Y',
```

```
        PURCHASE_ACCEPTANCE_ADVICE = 'Y'
```

```
        WHERE
```

```
        TFISSET.ENTITY_B2KTYPE = 'BNKGR'
```

```
        AND TFISSET.ENTITY_B2KID = BGM_REC.bg_b2kid
```

```
        AND TFISSET.BANK_ID = BGM_REC.bank_id;
```

```
    COMMIT_COUNTER := COMMIT_COUNTER + 1;
```

```
    TOT_COMMIT_COUNTER := TOT_COMMIT_COUNTER + 1;
```

```
EXCEPTION
```

WHEN OTHERS THEN

--{

DBMS_OUTPUT.PUT_LINE('Exception occured for
Guarantee Number : ' || BGM_REC.bg_srl_num);

--}

END;

IF (MOD(COMMIT_COUNTER, 300) = 0) THEN

--{

DBMS_OUTPUT.PUT_LINE('Number of Guarantee Nos
corrected till now : ' || to_char(COMMIT_COUNTER));

COMMIT_COUNTER :=0;

COMMIT;

--}

END IF;

--}

END LOOP;

COMMIT;

DBMS_OUTPUT.PUT_LINE('Total Number of Guarantee Nos
corrected : ' || to_char(TOT_COMMIT_COUNTER));

--}

END;

/

spool off

©Copyright Infosys Ltd.

SRV_VerifyCAAcct_post_process_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The Verify post process of the CA account calls the IN_updateAcctOpnDateForWKIT.scr script to activate the inactive account.

SRV_VerifyCAAcct_post_process_data.scr

This script calls IN_updateAcctOpnDateForWKIT.scr to activate the inactive account.

©Copyright Infosys Ltd.

SRV_VerifySBAcct_post_process_data.scr

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The Verify post process of the Sb account calls the IN_updateAcctOpnDateForWKIT.scr script to activate the inactive account.

SRV_VerifySBAcct_post_process_data.scr

This script calls IN_updateAcctOpnDateForWKIT.scr to activate the inactive account.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The following scripts are available in this section.

SRV_AddCashTran_post_process_data.scr
SRV_AddXferTran_post_process_data.scr
SRV_DeleteTran_post_process_data.scr
SRV_FetchTranDtIsForCopy_post_process_data.scr
SRV_FetchTranDtIsForDelete_post_process_data.scr
SRV_FetchTranDtIsForModify_post_process_data.scr
SRV_FetchTranDtIsForPost_post_process_data.scr
SRV_FetchTranDtIsForVerify_post_process_data.scr
SRV_InquireTran_post_process_data.scr
SRV_ModifyAndPostCashTran_post_process_data.scr
SRV_ModifyCashTranForPTranPost_post_process_data.scr
SRV_ModifyCashTran_post_process_data.scr
SRV_PostTran_post_process_data.scr
SRV_VerifyTran_post_process_data.scr
SRV_AddAndPostXferTran_post_process_data.scr
SRV_AddAndPostCashTran_post_process_data.scr
SRV_AddCashTranForPTranPost_post_process_data.scr
SRV_AddXferTranForPTranPost_post_process_data.scr
SRV_ModifyXferTranForPTranPost_post_process_data.scr
IN_calculate_Repayment_OverDueDate.scr
IN_generate_KccDisbSrlNum.scr
IN_generate_KccRepaySrlNum.scr
IN_HTM_AddKccData.scr
IN_HTM_fetchKccData.scr
IN_HTM_Main_ProcessKccData.scr
IN_HTM_ModifyKccData.scr
IN_HTM_UpdateKccData.scr
IN_HTM_ValKccDataForFetch.scr

IN_HTM_ValKccData.scr
 IN_KccLocale_Insert_KDA.scr
 IN_KccLocale_Insert_KDT.scr
 IN_KccLocale_Insert_LDTD.scr
 IN_KccLocale_IsKccAcctId.scr
 IN_KccLocale_process_KDT.scr
 IN_KccLocale_process_LDTD.scr
 IN_KccLocale_Repay_Default.scr
 IN_KccLocale_Repay_Selective.scr
 IN_KCCADcheckData.scr
 IN_KCCADdeleteData.scr
 IN_KCCADgetData.scr
 IN_KCCADsubmitData.scr
 IN_KccLocale_fetchDisb_defaultData.scr
 IN_KccLocale_Validate_CropDetails.scr
 IN_KDTS.icfg
 in_kccad.xml
 in_kccadres.xml
 in_kccaddet.xml
 in_kccaddet.html
 in_kccadres.html
 in_fnModuleSearch.js
 in_tm.xml
 in_tmdet.xml
 in_tmdet.html
 IN_finbranch_combo.djs

Input Field	Description
kccCropCode	Kisan Credit Card crop code for which disbursement is done.
kccCropStateCode	Kisan credit card state code of the crop.
kccNumOfCropInYear	Number of crops in a year.
kccRepayDueDate	Repay due date of the disbursement for crop.
kccCropArea	Crop area of the kisan credit card crop.

kccCropInsuranceFlg	Insurance applicable for crop
kccWbcisAppFlg	Optional insurance applicable for crop
kccRepDisbSrlNum	Disbursement no against which repayment will be done.
kccRepCropCode	Crop code for which repayment is done.
kccDisbDate	Disbursement date.
kccRepDueDate	Repayment due date calculated during disbursement.
kccUnsettledAmt	Unsettled amount of the disbursement.
kccSettledAmt	Settled amount of the disbursement.
kccCursettledAmt	Current settled amount of the disbursement.

This script is called for performing Add/Modify/Verify/Delete/Post mode in HTM menu.

NA

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.15 release.

The following input variable is added to the existing script hook:

Input Field	Description
BANCS.INPUT.	

The following output variable is added to the existing scripting hook:

Output Field	Description
BANCS.OUTPUT.	

DCNonRenewalNotification.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is to generate message 799 for non-renewal notification.

Input Field	Description
BANCS.INPUT. TransReference	DC ref Number
BANCS.INPUT.RelatedRefNum	Bank Ref Number

Output Field	Description
BANCS.OUTPUT.SwiftMessage	Swift Message

This script is for non-renewal notification.

This script is used to generate message 799 for non-renewal notification.

©Copyright Infosys Ltd.

DCRescissionNotification.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is to generate message 799 for Rescission notification.

Input Field	Description
BANCS.INPUT.TransReference	DC ref Number
BANCS.INPUT.RelatedRefNum	Bank Ref Number

Output Field	Description
BANCS.OUTPUT.SwiftMessage	Swift Message

This script is for rescission notification.

This script is used to generate message 799 for rescission notification.

Scripts for Nigeria Localization

©Copyright Infosys Ltd.

getTransactionCodeDtls.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is provided to get customized user transaction code level details.

Refer Ticket: 680302

getTransactionCodeDtls.scr

Input Field	Description
BANCS.INPUT.userTranCode	User Transaction Code
BANCS.INPUT.sysTranCode	System Transaction Code
BANCS.INPUT.sysPartTranCode	System Part Transaction Code
BANCS.INPUT.userPartTranCode	User Part Transaction Code
BANCS.INPUT.ruleId	Rule Id
BANCS.INPUT.freeCode1	Free Code 1
BANCS.INPUT.freeCode2	Free Code 2
BANCS.INPUT.tranDate	Transaction Date
BANCS.INPUT.tranId	Transaction Id
BANCS.INPUT.partTranSrlNum	Part Tran Srl Num
BANCS.INPUT.tranType	Transaction Type
BANCS.INPUT.tranSubType	Transaction Sub Type
BANCS.INPUT.partTranType	Part Transaction Type
BANCS.INPUT.acid	Acid
BANCS.INPUT.valueDate	Value Date
BANCS.INPUT.tranParticular	Transaction Particulars
BANCS.INPUT.entryDate	Entry Date

BANCS.INPUT.initSolId	Init Sol Id
BANCS.INPUT.dtdTranRmks	DTD Transaction Remarks
BANCS.INPUT.dthRemarks	DTH Remarks
BANCS.INPUT.deliveryChannelId	Delivery Channel Id

Output Field	Description
BANCS.OUTPUT.userPartTranCode	User Part Transaction Code
BANCS.OUTPUT.tranParticular2	Transaction Particulars 2
BANCS.OUTPUT.tranParticularCode	Transaction Particular Code

©Copyright Infosys Ltd.

NG_AcotliqBatchInit.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called during BLCTAC menu for liquidation of account closure.

NA

NG_AcotliqBatchInit.scr

Input Field	Description
A/c ID	Account number

NA

NA

This script is called for liquidating cot accrual for the account specified.

NA

NG_AcotliqModifyLienAmt.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called to modify the accrued lien amount during BLCTAC menu.

NA

NG_AcotliqModifyLienAmt.scr

NA

NA

This script is called for modifying the lien accrued on the account.

NA

NG_AcotliqSubmit.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called during BLCTAC submit.

NA

NG_AcotliqSubmit.scr

©Copyright Infosys Ltd.

NG_AddIntProcessData.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called from 'NG_AddIntRateforPdts.scr' to process all the accounts for each individual and non-individual scheme codes.

NA

NG_AddIntProcessData.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The Account for which the batch has to be processed

The following are the details of the output fields for the script:

A failure report is generated listing the accounts failed and reason for failure.

It internally calls the ONS services (HINTTM service) to fetch existing interest details and modify them to additional interest rate, for additional interest pay for the month for the eligible accounts.

The locale script is called from NG_AddIntRateforPdts.scr on run of bonus interest batch.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_AddIntRateforPdts.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

NA

NG_AddIntRateforPdts.scr

The following are the details of the input fields for the script:

Input Field	Description
Individual schmcode	Individual scheme code for which minimum balance is to be maintained.
Non Individual scheme code	Non individual scheme code for which minimum balance is to be maintained.
Bonus percentage	Bonus percentage to be added to interest rate for those accounts who has maintained minimum balance and have no debit transaction for the month.

A failure report is generated listing the accounts failed and reason for failure.

Accounts under the scheme codes parameterized in MLPS are processed by the batch for ITC table record insertion.

The locale batch script is scheduled as a monthly batch at the end of month before interest application. It has the same frequency of that of interest application batch.

NA

©Copyright Infosys Ltd.

Finacle Copyright

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is used to activate the newly created accounts created in GBA. It will collate the accounts and corresponding details. Processing was done record wise to activate the accounts. The success and failure reports will be generated. The success report contains the list of accounts, which got activated, and the failure report contains the failed accounts along with the reason for its failure.

NA

NG_BA_AcctActivate.scr

NA

NA

This script lists out the accounts and the corresponding details required to activate. Processing is done account wise and does the following steps to activate the account.

1. Updates the nomination and joint holder details
2. Unfreezing the account
3. Changing the account open date to BOD date and
4. It activates the account by setting the flag to Y in NG_BAD table. Success and Failure reports are generated accordingly.

This script is HBJSTM enabled so that it can be run periodically to activate the accounts.

N/A

©Copyright Infosys Ltd.

NG_BUCTRCDInsertCOTDtl.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_BUCTRCDUpd.scr in BUCTRCD menu.

NA

NG_BUCTRCDInsertCOTDtl.scr

NA

NA

The script is called from NG_BUCTRCDUpd.scr in BUCTRCD menu.
This will do a table updation.

The script is called from NG_BUCTRCDUpd.scr in BUCTRCD menu.

NA

NG_BUCTRCDUpId.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_bbuu4002.cxx in BUCTRCD menu.

NA

NG_BUCTRCDUpId.scr

NA

NA

The script is called from NG_bbuu4002.cxx in BUCTRCD menu. This does a validation on record uploaded and calls a locale script NG_BUCTRCDInsertCOTDtl.scr.

The script is called from NG_bbuu4002.cxx in BUCTRCD menu.

NA

NG_bulkAcctCall.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script calls NG_bulkAcctProcess.scr as a batch job.

N/A

NG_bulkAcctCall.scr

N/A

N/A

N/A

This script is called from NG_GBA_VERIFY_post_process_data.scr for verify mode of newly added request number in GBA menu.

N/A

NG_bulkAcctCustCoreLink.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script adds the core customer details in CCMG table

N/A

NG_bulkAcctCustCoreLink.scr

N/A

N/A

N/A

This script is called by NG_bulkAcctOpen.scr in Verify mode for GBA menu.

N/A

NG_bulkAcctOpen.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script opens dummy account and calls NG_bulkAcctCustCoreLink.scr for customer core data insertion and NG_bulkAcctProcBCA.scr for table insertion.

N/A

NG_bulkAcctOpen.scr

N/A

N/A

N/A

This script is called by NG_bulkAcctProcess.scr in Verify mode for GBA menu.

N/A

NG_bulkAcctProcBCA.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script calls add kit related details in NG_BCA table.

N/A

NG_bulkAcctProcBCA.scr

N/A

N/A

N/A

This script is called by NG_bulkAcctOpen.scr in Verify mode for GBA menu.

N/A

NG_bulkAcctProcess.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script calls NG_bulkAcctOpen.scr for dummy account opening and NG_bulkAcctReportGen.scr for success and failure report generation.

N/A

NG_bulkAcctProcess.scr

N/A

N/A

N/A

This script is called by NG_bulkAcctCall.scr as a batch script in Verify mode for GBA menu.

N/A

NG_bulkAcctReportGen.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script generate success and failure reports.

N/A

NG_bulkAcctReportGen.scr

N/A

N/A

N/A

This script is called by NG_bulkAcctProcess.scr in Verify mode for GBA menu.

N/A

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_MCACTDsubmitForVerify.scr.

NA

NG_CCOTHTblopr.scr

NA

NA

The script is called from NG_MCACTDsubmitForVerify.scr. The history table updation, where old records after modification are stored is handled in this script.

The script is called from NG_MCACTDsubmitForVerify.scr.

NA

NG_CCOTMVerifyTblopr.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_MCACTDsubmitForVerify.scr.

NA

NG_CCOTMVerifyTblopr.scr

NA

NA

The script is called from NG_MCACTDsubmitForVerify.scr. The table updation required for verify of MCACTD menu is handled here.

The script is called from NG_MCACTDsubmitForVerify.scr.

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_MCACTDsubmitForVerify.scr.

NA

NG_CCOTRTblopr.scr

NA

NA

The script is called from NG_MCACTDsubmitForVerify.scr. The recalculation table is updated in this script.

The script is called from NG_MCACTDsubmitForVerify.scr.

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on GO in criteria page.

NA

NG_CHDTgetData.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The Account for which a cheque is been issued in CBT
Begin serial Num	A serial number is selected from the searcher in criteria page

The following are the details of the output fields for the script:

Output Field	Description
Begin Cheque Security No.	A unique security number for the cheque is maintained in this field
No Of leaves	Field is auto populated. Values are fetched from CBT table

Validates the acid and serial number and displays the details page with proper values. No of leaves field is auto populated. Values are fetched from CBT table

The locale script is called on click of Go in criteria page in Modify,

Inquire Verify and Cancel modes.

NA

©Copyright Infosys Ltd.

NG_CHDTsubmitData.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on SUBMIT from details page.

NA

NG_CHDTsubmitData.scr

The following are the details of the input fields for the script:

The following are the details of the input fields for the script:

Input Field	Description
A/c id	The Account for which a cheque is been issued in CBT
Begin serial Num	A serial number is selected from the searcher in criteria page
Begin Cheque Security No.	A unique security number for the cheque is maintained in this field
No. of leaves	Field is auto populated. Values are fetched from CBT table.

NA

On submit, locale table NG_CHDT is updated with appropriate values.

The locale script is called on click of SUBMIT in criteria page in add, Modify, Verify and Cancel modes.

NA

NG_CHDTaddData.scr

This locale script is called from NG_CHDTsubmitData.scr for add mode.

NG_CHDTcancelData.scr

This locale script is called from NG_CHDTsubmitData.scr for cancel mode.

NG_CHDTmodifyData.scr

This locale script is called from NG_CHDTsubmitData.scr for cancel mode.

NG_CHDTbIOpr.scr

This locale script is called from various table operation. FE and BE values are mapped here.

NG_CHDTpopulateCookie.scr

This locale script is called from populate the cookie for various table operations

NG_CHDTverifyData.scr

This locale script is called from NG_CHDTsubmitData.scr for verify mode.

NG_SRV_AddAndPostCashTran_validate_locale_data.scr

This locale script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on post of transactions in HTM and HCASHWD menu

NG_SRV_ModifyAndPostCashTran_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on post of transactions in HTM and HCASHWD menu

NG_SRV_AddCashTranForPTranPost_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on part Tran post of transactions in HTM and HCASHWD menu

NG_SRV_ModifyCashTranForPTranPost_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on part Tran post of transactions in HTM and HCASHWD menu

NG_SRV_AddCashTran_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on Save of transactions in HTM and HCASHWD menu

NG_SRV_ModifyCashTran_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on Save of transactions in HTM and HCASHWD menu

NG_SRV_AddAndPostXferTran_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on post of transactions in HXFER menu

NG_SRV_ModifyAndPostXferTran_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on post of transactions in HXFER menu

NG_SRV_AddXferTranForPTranPost_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on part Tran post of transactions in HXFER menu

NG_SRV_ModifyXferTranForPTranPost_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on part Tran post of transactions in HXFER menu

NG_SRV_AddXferTran_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on Save of transactions in HXFER menu

NG_SRV_ModifyXferTran_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on Save of transactions in HXFER menu

NG_SRV_FetchDataForDDMassIss_post_validate_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on Save of transactions in HDDMI menu

NG_SRV_FetchIcZoneDtlWithLock_validate_locale_data.scr

This script makes the security number mandatory and validates the combination of the Chq serial number and the security number. It is called on Save of transactions in HICTMO menu

NG_SRV_IssueChqBooks_validate_locale_data.scr

The script validates the begin cheque number and ensures not more than 8 digits are entered in HICHBA menu.

NG_CheckDigit.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script called during account opening with scheme for which NUBAN next number sequence is enabled.

NA

NG_CheckDigit.scr

The following are the details of the input fields for the script:

Input Field	Description
Next number	Next number sequence
Apply string	For apply string

The following are the details of the output fields for the script:

N/A

This script calculates Check Digit based on the input and returns NUBAN account number.

The locale script is called during account opening.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotAccrualRecalcBatch.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale scripts is called during recalculation of COT from COTRC batch scheduled at EOD before running COT accrual batch.

NA

NG_CotAccrualRecalcBatch.scr

NA

NA

The script checks if there any account eligible for recalculation of accrued COT. If it is available, the COT recalculation is done and lien, if applied, is removed and applied again.

This locale script is called during EOD batch job COTRC for recalculating the accrued COT if any SOL transfer or scheme transfer of account has happened.

NA

NG_cotAcctSolXfer.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script checks if any sol transfer has happened on bod date.

NA

NG_cotAcctSolXfer.scr

NA

NA

This script will be called for checking if account sol transfer has happened or not

This script will be called during recalculation and rebuild.

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called when an account is transferred from one scheme to another scheme.

NA

NG_cotAcctXfr.scr

NA

NA

NA

NA

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script called from COT liquidation, COT accrual, COT rebuild and COT recalculation. This script checks if transaction amount has crossed threshold limit.

NA

NG_CotDailyAccOnConcessnRate.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The Account on which cot is accrued/rebuild/recalculated/liquidated
COT Concession Code	The COT concession code set at scheme level
COT code	The COT code set at scheme level
COT Calc Type	The type of COT calculation set at account level

NA

If transaction amount has crossed the threshold limit then cot concession code is used for calculation.

The locale script is called during COT liquidation, COT accrual, COT rebuild and COT recalculation.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotDailyAccrual.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called during COTAC batch job run at EOD for calculating COT accrual for that day.

NA

NG_CotDailyAccrual.scr

NA

NA

COT eligible transaction is inserted into NG_COTRN through NG_CotDailyAccrualRecordFetch.scr. COT amount would be calculated on the transaction amount for the COT rate set at account level or at MLPS and updated in NG_CCOTT table. VAT amount is also calculated on the COT amount for the VAT rate set at MLPS.

Lien is marked for the sum of COT and vat amount.

The locale script is executed from COTAC batch job at EOD through HBJSTM.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotDailyAccrualRecordFetch.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called for fetching the COT applicable transactions.

NA

NG_CotDailyAccrualRecordFetch.scr

The following are the details of the input fields for the script:

Input Field	Description
Sol ID	The sol to which the user belongs
User ID	The application user id
Accrual date	The BOD date
Bank ID	The bank ID

NA

The transaction which are not of the tran sub type excluded at MLPS are considered for fetching the debit amount for each account and inserted into locale table NG_COTRN.

The locale script is executed during COT accrual batch job run at EOD (COTAC).

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotLiqDailyAccrualRecFetch.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called for fetching the COT applicable transactions.

NA

NG_CotLiqDailyAccrualRecFetch.scr

The following are the details of the input fields for the script:

Input Field	Description
Sol ID	The sol to which the user belongs
User ID	The application user id
Accrual date	The BOD date
Bank ID	The bank ID

NA

The transaction which are not of the tran sub type excluded at MLPS would be considered for fetching the debit amount for each account and inserted into locale table NG_COTRN.

The locale script gets executed during COT liquidation (BLCTAC)

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotMonthlyCollectnBatch.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called during COT application run at month end (COTAP).

This is run at SOL level. COT is applied and lien is removed with transaction created on VAT and COT placeholders set at MLPS.

NA

NG_CotMonthlyCollectnBatch.scr

Input Field	Description
SOL	The value SOL is passed in BJSTM to indicate that the script should be run SOL wise.

NA

NA

This script is called to apply the COT amount accrued and remove the lien placed on the account. BI transaction is created on COT and VAT placeholders by crediting those accounts and debiting the customer account.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotRebuildCorrectn.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called during BRCTD menu for rebuilding cot accrued in case of cot rate correction for a specific date range.

NA

NG_CotRebuildCorrectn.scr

Input Field	Description
Sol ID	The sol to which the user belongs
User ID	The application user ID
Bank ID	The bank ID

NA

This script checks for entry in NG_COTRA table if any account is there for cot rebuilding.

If records are there, it fetches the old COT rate and new COT rate for each account from NG_COTRA table and rebuild the accrued cot

This script is called during COT rebuild.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotRebuildForAcct.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The COT accrued is rebuild for the specified account for the date range mentioned.

NA

NG_CotRebuildForAcct.scr

Input Field	Description
A/c ID	Account for which cot rebuild needs to be run
User ID	The application user ID
Bank ID	The bank ID
From Date	Start date from which the cot rebuild should be run for
To Date	End date till which the cot rebuild should be run for

NA

This script checks if the specified account needs to be rebuild for cot accrual for the specified date range.

This script is called from BRCTD menu during cot rebuild at account level.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotRebuildForSet.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called during cot rebuild BRCTD menu at set id level.

NA

NG_CotRebuildForSet.scr

Input Field	Description
Set Id	Set Id for which cot rebuild needs to be run
User Id	The application user id
Bank Id	The bank id
From Date	Start date from which the cot rebuild should be run for
To Date	End date till which the cot rebuild should be run.

NA

The script rebuilds the accrued COT at set id level for the specified date range

This script is called from BRCTD menu for Set ID level.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotRebuildForSol.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called during cot rebuild BRCTD menu at sol id level.

NA

NG_CotRebuildForSol.scr

Input Field	Description
Sol Id	Sol Id for which cot rebuild needs to be run
User Id	The application user id
Bank Id	The bank id
From Date	Start date from which the cot rebuild should be run for
To Date	End date till which the cot rebuild should be run for.

NA

The script rebuilds the accrued COT at sol id level for the specified date range

This script is called from BRCTD menu for Sol ID level.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotRebuildInit.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called during BRCTD menu for rebuilding cot accrual charges.

NA

NG_CotRebuildInit.scr

Input Field	Description
Rebuild Level	Rebuild should be run at a/c level or sol level or set level or
A/c Id	The account id for which cot rebuild needs to be run
Sol Id	The sol id at which cot rebuild needs to be run
Set Id	The set id at which cot rebuild needs to be run
From date	The date from which cot rebuild should be run
To Date	The date till which cot rebuild should be run

NA

The script fetches MLPS data and COT accrual data from NG_CCOTT table and rebuilds the accrued COT amount for the specified input with the new cot rates.

This script is called during COT rebuild.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_CotRebuildNoLien.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called during COT rebuild from BRCTD menu when lien on COT is set as No at MLPS.

NA

NG_CotRebuildNoLien.scr

NA

NA

NA

This script is called during COT rebuild when lien on cot set up is No at MLPS level. It invokes NG_CotRebuildForAcct.scr if rebuild level is A/c Level and NG_CotRebuildForSol.scr if rebuild level is Sol. Level, NG_CotRebuildForSet.scr if rebuild level is Set Level.

NA

NG_CotRebuildSubmit.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called during click of submit at BRCTD menu.

NA

NG_CotRebuildSubmit.scr

NA

NA

It invokes NG_CotRebuildValidate.scr to validate the data passed and if rebuild is applicable.

If yes then it invokes NG_CotRebuildInit.scr

This script is called for performing process function in BRCTD menu.

NA

NG_CotRebuildValidate.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called from NG_CotRebuildSubmit.scr to validate data passed for rebuilding cot accrued.

NA

NG_CotRebuildValidate.scr

NA

NA

The script will validate for valid Account Id, cot applicable account ID, valid date range, valid sol id, set id. Appropriate error message is thrown in FE.

This script is called for validating the data passed in the menu BRCTD.

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called for doing the processing in case an account is transferred from one scheme to another.

NA

NG_cotSchmXfr.scr

NA

NA

NA

This script is called during cot recalculation or rebuild.

NA

NG_CotTableUpdates.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is a generic script called for all backend table operations.

NA.

NG_CotTableUpdates.scr

NA

The following are the details of the output fields for the script:

Output Field	Description
COTREP.COTCL.TableUpdSuccessOrFailure	To return success or failure.

This script calls proctbl to modify/insert/delete/verify any of the COT related tables.

NA

NA

NG_DCTSPgetdata.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale scripts is called on click of GO in criteria page of DCTSP menu.

NA

NG_DCTSPgetdata.scr

Input Field	Description
Function Code	Function Code(A/M/V/I/D)
Scheme Code	Scheme Code

Details page fields, Commission on turnover default code and Commission on turnover concession code in case of Modify/Verify/Inquiry/Delete mode

Output Field	Description
Commission on turnover default code	Commission on turnover default code
Commission on turnover concession code	Commission on turnover concession code

The script fetches the details in Modify/Verify/Inquiry/Delete mode. In Add mode, script checks if record already exists. Basic validations are handled.

The script is called on click of GO button in criteria page of DCTSP menu.

NA

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale scripts is called on click of Submit in criteria page of DCTSP menu.

NA

NG_DCTSPsubmitdata.scr

NA

NA

The processing logic on submit is handled in this script. The script does the procTbl updation based on the action passed.

The script is called on click of Submit button in details page of DCTSP menu.

NA

NG_defZeroCot.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_insertCCOTM.scr.

NA

NG_defZeroCot.scr

NA

NA

This script is called from NG_insertCCOTM.scr. The COT rate code population logic is handled here.

The script is called from NG_insertCCOTM.scr.

NA

NG_FetchRevandBnsMLPSdata.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

NA

NG_FetchRevandBnsMLPSdata.scr

The following are the details of the input fields for the script:

Input Field	Description
module	Module is L-Liability
Sub Module	Sub module is B-Bonus on Interest

The following are the details of the output fields for the script:

Output Field	Description
Individual schmcode	Individual scheme code for which minimum balance is to be maintained.
Non Individual scheme code	Non individual scheme code for which minimum balance is to be maintained.
Reversal rate code	Zero rate code
Bonus percentage	Bonus percentage to be added to interest rate for those accounts who has maintained minimum balance and have no debit transaction for the month.

Fetch the values parameterized in MLPS for module, Liability and sub module, B-Bonus on Interest.

The locale script is called from NG_AddIntRateforPdts.scr on run of bonus interest batch and NG_RevIntRateforPdts.scr on run of interest reversal batch.

NA

©Copyright Infosys Ltd.

NG_GBA_VERIFY_post_process_data.scr Infosys®



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script calls NG_bulkAcctCall.scr

N/A

NG_GBA_VERIFY_post_process_data.scr

N/A

N/A

N/A

This script is called for post process of verify mode of newly added request number in GBA menu.

N/A

NG_GenerateKYCNum.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called to generate the KYC ID when the user is non customer.

NA

NG_GenerateKYCNum.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c id	Sequence generated

The following are the details of the output fields for the script:

Output Field	Description
Begin Cheque Srl. No.	KYC ID is generated

NA

The locale script is called on click of accept in the explode button when the user is non-customer of the bank.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_getCOTForAcctOpen.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from
NG_SRV_FetchDfltODAcctDtls_post_process_data.scr/
NG_SRV_FetchDfltCAAcctDtls_post_process_data.scr/
NG_SRV_FetchDfltSBAcctDtls_post_process_data.scr.

NA

NG_getCOTForAcctOpen.scr

NA

NA

This script is called from
NG_SRV_FetchDfltODAcctDtls_post_process_data.scr/
NG_SRV_FetchDfltCAAcctDtls_post_process_data.scr/
NG_SRV_FetchDfltSBAcctDtls_post_process_data.scr. Fetch logic for
common parameters and basic validation is handled here.

The script is called from
NG_SRV_FetchDfltODAcctDtls_post_process_data.scr/
NG_SRV_FetchDfltCAAcctDtls_post_process_data.scr/
NG_SRV_FetchDfltSBAcctDtls_post_process_data.scr.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_GL_MovtBatch.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is to be scheduled as part of EODBOD operations and will transfer the general ledger subhead of SBA/CAA/ODA accounts based on the setup maintained in MSALGLSC menu.

NA

NG_GL_MovtBatch.scr

NA

NA

NA.

This script calls NG_msalglsr_procSGLM.scr for the actual data processing.

N/A

NG_GL_procAGL.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used to update the data eto NG_AGL table during GL transfer of accounts through NG_GL_MovtBatch.scr.

NA

NG_GL_procAGL.scr

NA

NA

NA.

This script is called from NG_GL_MovtBatch.scr

N/A

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script handles the SRV error or exceptions, if any, on calling the SRV for interest rate change and populates the error to the failure report.

NA

NA

©Copyright Infosys Ltd.

NG_insertCCOTM.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from
NG_SRV_VerifyCAAcct_pre_process_data.scr/
NG_SRV_VerifyODAcct_pre_process_data.scr/
NG_SRV_VerifySBAcct_pre_process_data.scr.

NA

NG_insertCCOTM.scr

NA

NA

This script is called from from
NG_SRV_VerifyCAAcct_pre_process_data.scr/
NG_SRV_VerifyODAcct_pre_process_data.scr/
NG_SRV_VerifySBAcct_pre_process_data.scr. The procTbl
operations are handled here.

The script is called from
NG_SRV_VerifyCAAcct_pre_process_data.scr/
NG_SRV_VerifyODAcct_pre_process_data.scr/
NG_SRV_VerifySBAcct_pre_process_data.scr.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_ListBeginSrlNum.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on click of the serial number searcher to show the correct values of the begin cheque serial number. These values are fetched from the CBT product table.

NA

NG_ListBeginSrlNum.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c id	The Account for which a cheque is been issued in CBT

The following are the details of the output fields for the script:

Output Field	Description
Begin Cheque Srl. No.	List of begin serial numbers issued for the cheque are listed out in the searcher

Records present in CBT table but not present in locale table are listed out.

The locale script gets called on click of serial number searcher in criteria page in Modify, Inquire Verify and Cancel modes.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_MarkLienOnCOTAccruedAmt.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called during cot accrual batch job to mark lien on the account.

NA

NG_MarkLienOnCOTAccruedAmt.scr

NA

NA

If lien were to be applied on the account SRV call for adding lien on account is called from this script.

This is called during cot accrual.

NA

NG_MCACTDfetch.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale scripts is called from NG_MCACTDgetdata.scr.

NA

NG_MCACTDfetch.scr

Input Field	Description
Function Code	Function Code(A/M/V/X)
A/c.ID	Account ID

Details page fields, COT calc type, Commission on turnover default code and Commission on turnover concession code, Effective date, Threshold Amount, Force debit flag in case of Modify/Verify /Cancel mode

Output Field	Description
Commission on turnover default code	Commission on turnover default code
Commission on turnover concession code	Commission on turnover concession code
COT Calc Type	Fixed , constant , covenant types
Effective date	Effective date
Threshold Amount	Threshold Amount
Force debit flag	Force debit flag, values Y/N

The script fetches the details in Modify/Verify/Cancel mode. In Add mode, script checks if record already exists.

This locale scripts is called from NG_MCACTDgetdata.scr.

NA

©Copyright Infosys Ltd.

NG_MCACTDgetdata.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on click of GO in criteria page of MCACTD menu.

NA

NG_MCACTDgetdata.scr

Input Field	Description
Function Code	Function Code(A/M/V/X)
A/c.ID	Account ID

Details page fields, COT calc type, Commission on turnover default code and Commission on turnover concession code, Effective date, Threshold Amount, Force debit flag in case of Modify/Verify /Cancel mode

Output Field	Description
Commission on turnover default code	Commission on turnover default code
Commission on turnover concession code	Commission on turnover concession code
COT Calc Type	Fixed , constant , covenant types
Effective date	Effective date
Threshold Amount	Threshold Amount
Force debit flag	Force debit flag, values Y/N

The script fetches the details in Modify/Verify/Cancel mode. In Add mode, script checks if record already exists. This script calls NG_MCACTDfetch.scr and NG_MCACTDvalidate_Data.scr

The script is called on click of GO button in criteria page of MCACTD menu.

NA

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of Submit button in details page of MCACTD menu.

NA

NG_MCACTDsubmitData.scr

NA

NA

This script is called on click of Submit button in details page of MCACTD menu. The processing logic for Add / Modify / Verify/cancel is handled here.

The script is called on click of Submit button in details page of MCACTD menu.

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on submit for verify. It is called from NG_MCACTDsubmitData.scr.

NA

NG_MCACTDsubmitForVerify.scr

NA

NA

The script is called on submit for verify. It is called from NG_MCACTDsubmitData.scr. The table processing for verification is handled here.

The script is called on submit for verify. It is called from NG_MCACTDsubmitData.scr.

NA

NG_MCACTDvalidate.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale scripts is called from NG_MCACTDsubmitData.scr.

NA

NG_MCACTDvalidate.scr

NA

NA

This script handles the validation before processing and table update.

This locale scripts are called from NG_MCACTDsubmitData.scr.

NA

NG_MCACTDvalidate_Data.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale scripts is called from NG_MCACTDgetdata.scr.

NA

NG_MCACTDvalidate_Data.scr

NA

NA

This script is a validation script for Add/Modify mode.

This locale scripts is called from NG_MCACTDgetdata.scr.

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is executed on click of Save/Post button in HTM/HCASHDEP/HCASHWD menu and is called from the front end link file ng_tmdet_locale_link.js. The script fetches the transaction type, Tran sub type, Tran amount, Tran currency and account related details. These values are used for front end validations. The validation is done based on the setup done in MCHP menu for that particular Account/CIF ID/Scheme/Set ID.

NA

NA

NA

If Tran amount exceeds the limit set in MCHP, then the transaction is charged on the extra amount with the rate specified in MCHP .For user confirmation, one confirmation alert pops up on click of post, stating the chargeable amount, charge amount and vat amount. You can accept or reject the transaction.

NG_MCHPchrgCollection.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script NG_MCHPchrgCollection.scr is called on click of POST in HTM/ HCASHDEP/ HCASHWD menu. In this script, charge collection takes place on the chargeable amount. The entry goes in NG_CHC for the corresponding account. Tran amount, Charge amount and VAT amount is updated in NG_CHC table.

For calculating Cash Lite limit, transactions made to all accounts of the customer are considered. However, for cash handling only the transactions made to that account is considered.

NA

NA

NA

NA

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script validate the frontend fields on the criteria page of MCHP menu. For Verify / Modify/Inquire/Delete function, it fetched the data from the database table NG_CHPT for the entered parameter to be displayed on details page.

NA

The following are the details of the input fields for the script:

Input Field	Description
Parameter Type	The parameter type A/S/C/T for which set up to be done
Parameter Value	The value for the given parameter type
Currency	This should be home currency

The following are the details of the output fields for the script:

Output Field	Description
Individual Credit Limit	Credit limit set for retail customer above which charge is applicable
Individual Credit Rate	Rate at which charge is applied on transaction amount above the limit
Corporate Credit Limit	Credit limit set for corporate customer above which charge is applicable
Corporate Credit Rate	Rate at which charge is applied on transaction amount above the limit
Vat Rate	Vat rate applicable on the chargeable amount
Transaction Narration	Remarks for the set up

Charge account placeholder	Office account for charge amount
Vat account placeholder	Office account for vat amount

The locale script is called on click of GO button from MCHP criteria page in Add/ Modify/ Verify/ Inquire/Delete modes.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on click of Submit button in MCHP menu. This will update the locale table NG_CHPT, will update the data corresponding to the entered parameter value.

NA

The following are the details of the input fields for the script:

Input Field	Description
Individual Credit Limit	Credit limit set for retail customer above which charge is applicable
Individual Credit Rate	Rate at which charge is applied on transaction amount above the limit
Corporate Credit Limit	Credit limit set for corporate customer above which charge is applicable
Corporate Credit Rate	Rate at which charge is applied on transaction amount above the limit
Charge account Placeholder	Office account for chargeable amount
Vat account Placeholder	Office account for Vat amount

NA

The locale script gets executed on click of Submit from details page of MCHP menu in Add/Modify/Verify/Delete modes. This script will internally call following scripts according to the mode.

Add Mode: NG_MCHPsubmitForAddMode.scr

Modify Mode: NG_MCHPsubmitForModifyMode.scr

Verify Mode: NG_MCHPsubmitForVerifyMode.scr

Delete Mode: NG_MCHPsubmitForDeleteMode.scr

After the processing of data, record is updated in locale table NG_CHPT.

In case multiple parameter are set, system will start checking the limit and charges based on SET ID, In flow if system get limit/charge set up for ACCOUNT ID it will take that limit/charges and will do charge calculation and CIF set level setup is not checked. CIF ID or SCHEME CODE (in sequence) set up is checked only when no set up done for account id. So the priority is Account > CIF > Scheme > SET.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script called on click of Submit on the details page of MCHP menu. It validates the fields on the details page and throws proper error if validation fails.

NA

The following are the details of the input fields for the script:

Input Field	Description
Individual Credit Rate	Individual credit Rate at which charge will be applied on transaction amount above the limit
Corporate Credit Rate	Corporate Credit Rate at which charge will be applied on transaction amount above the limit
Charge account Placeholder	Office account for chargeable amount
Vat account Placeholder	Office account for Vat amount

NA

The locale script is called on click of Submit from details page of MCHP menu in Add and Modify function modes.

NA

©Copyright Infosys Ltd.

Finacle Copyright

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script gets executed on click of Save/Post button in HTM menu and is called from the front end link file ng_tmdet_locale_link.js. The script fetches the transaction type, Tran sub type, Tran amount, Tran currency and account related details. These values are used for front end validations. The validation is done based on the setup done in MCPR menu for that particular Account/CIF ID/Scheme/Set Id.

NA

NA

NA

If Tran amount exceed the limit set in MCPR, then the transaction is charged on the extra amount with the rate specified in MCPR .For user confirmation one confirmation alert is pop up on click of post, stating the chargeable amount, charge amount and vat amount. User can accept or reject the transaction.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script NG_MCPRchrgCollection.scr is called on click of POST in HTM/ HCASHDEP/ HCASHWD menu. In this script charge collection takes place on the chargeable amount. The entry goes in NG_CXTT for the corresponding CIF ID and account. Charge amount and VAT amount are updated in NG_CXTT table. The locale table NG_CASHL are updated with srl number, tran_type, tran_subtype for the corresponding CIF ID.

For calculating CashLite limit, transactions made to all accounts of the customer are considered.

NA

NA

NA

NA

NA

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script validate the frontend fields on the criteria page of MCPR menu. For Verify / Modify/Inquire/Delete function it fetched the data from the database table NG_CLPT for the entered parameter to be displayed on details page.

NA

The following are the details of the input fields for the script:

Input Field	Description
Parameter Type	The parameter type A/S/C/T for which set up to be done
Parameter Value	The value for the given parameter type.
Currency	This should be home currency.

The following are the details of the output fields for the script:

Output Field	Description
Individual Credit Limit	Credit limit set for retail customer above which charge is applicable
Individual Credit Rate	Rate at which charge is applied on transaction amount above the limit
Individual Debit Limit	Debit limit set for retail customer above which charge is applicable
Individual Debit Rate	Rate at which charge is applied on transaction amount above the limit
Corporate Credit Limit	Credit limit set for corporate customer above which charge is applicable
Corporate Credit Rate	Rate at which charge is applied on transaction amount

	above the limit
Corporate Debit Limit	Debit limit set for corporate customer above which charge is applicable
Corporate Debit Rate	Rate at which charge is applied on transaction amount above the limit
Vat Rate	Vat rate applicable on the chargeable amount
Transaction Narration	Remarks for the set up
Charge account placeholder	Office account for charge amount
Vat account placeholder	Office account for vat amount

The locale script is called on click of GO button from MCPR criteria page in Add/ Modify/ Verify/ Inquire/Delete modes.

©Copyright Infosys Ltd.

NG_MCPRgetSumAmount.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called from NG_MCPRchrgCollection.scr. This script gets the total sum amount from DTD for a particular customer. This total sum amount is used in limit validation in charge collection.

NA

NA

NA

NA

NA

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on click of Submit button in MCPR menu. This updates the locale table NG_CLPT, which updates the data corresponding to the specified parameter value.

NA

The following are the details of the input fields for the script:

Input Field	Description
Individual Credit Limit	Credit limit set for retail customer above which charge is applicable
Individual Credit Rate	Rate at which charge is applied on transaction amount above the limit
Individual Debit Limit	Debit limit set for retail customer above which charge is applicable
Individual Debit Rate	Rate at which charge is applied on transaction amount above the limit
Corporate Credit Limit	Credit limit set for corporate customer above which charge is applicable
Corporate Credit Rate	Rate at which charge is applied on transaction amount above the limit
Corporate Debit Limit	Debit limit set for corporate customer above which charge is applicable
Corporate Debit Rate	Rate at which charge is applied on transaction amount above the limit
Charge account Placeholder	Office account for chargeable amount
Vat account Placeholder	Office account for Vat amount

NA

The locale script gets executed on click of Submit from details page of MCPR menu in Add/Modify/Verify/Delete modes. This script will internally call following scripts according to the mode.

Add Mode: NG_MCPRsubmitForAddMode.scr

Modify Mode: NG_MCPRsubmitForModifyMode.scr

Verify Mode: NG_MCPRsubmitForVerifyMode.scr

Delete Mode: NG_MCPRsubmitForDeleteMode.scr

After the processing of data, record will be updated in locale table NG_CLPT.

In case multiple parameter are set, system will start checking the limit and charges based on SET ID, In flow if system get limit/charge set up for ACCOUNT ID it will take that limit/charges and will do charge calculation and CIF set level setup is not checked. CIF ID or SCHEME CODE (in sequence) set up is checked only when no set up done for account id. So the priority is Account > CIF > Scheme > SET.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script called on click of Submit on the details page of MCPR menu. It validates the fields on the details page and throws proper error if validation fails.

NA

The following are the details of the input fields for the script:

Input Field	Description
Individual Credit Rate	Individual credit Rate at which charge is applied on transaction amount above the limit
Individual Debit Rate	Individual Debit Rate at which charge is applied on transaction amount above the limit.
Corporate Credit Rate	Corporate Credit Rate at which charge is applied on transaction amount above the limit
Corporate Debit Rate	Corporate Debit Rate at which charge is applied on transaction amount above the limit
Charge account Placeholder	Office account for chargeable amount
Vat account Placeholder	Office account for Vat amount

NA

The locale script gets called on click of Submit from details page of

MCPR menu in Add and Modify function modes.

NA

©Copyright Infosys Ltd.

NG_msalglsch_Fetch.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called on clicking 'Go' button in criteria page of MSALGLSC menu. It validates the data specified and the data to be shown in the details page is fetched from database.

NA

NG_msalglsch_Fetch.scr

NA

NA

NA.

This script calls NG_msalglsch_procSGLM.scr for the actual data processing

N/A

NG_msalgisc_procSGLM.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used to update the data entered in MSALGLSC menu to the database and to fetch the data from database.

NA

NG_msalgisc_procSGLM.scr

NA

NA

NA

This script is called from NG_msalgisc_Fetch.scr and NG_msalgisc_Submit.scr

N/A

NG_msalgisc_Submit.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called on clicking 'Submit' button in details page of MSALGLSC menu. It validates the data entered and if data is valid, commits it to the database.

NA

NG_msalgisc_Submit.scr

NA

NA

NA.

This script calls NG_msalgisc_procSGLM.scr for the actual data processing

N/A

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on Post/Save in details page of HTM/ HCASHWD/ HCASHDEP/ HXFER.

NA

NG_NFIUAdditionalDtlsAdd.scr

The following are the details of the input fields for the script:

Input Field	Description
Tran id	The Tran ID for which the data has to be inserted
Tran Date	The tran date on which tran id is generated

The following are the details of the output fields for the script:

Output Field	Description
Begin Cheque Security No.	Fields entered in the explode screen should be inserted in the table

Validates the transaction amount if it crosses the threshold limit set at MLPS level then an error message is thrown to specify the additional details.

Transaction amount if it crosses the threshold limit set at MLPS level then an error message is thrown to specify the additional details.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_NFIUAddtionalDtIsFetch.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This locale script is called on click of explode button from details page in modify/verify/inquire/delete modes in the details page.

NA

NG_NFIUAddtionalDtIsFetch.scr

The following are the details of the input fields for the script:

Input Field	Description
Tran id	The Tran ID for which the data has to be inserted
Tran Date	The tran date on which tran id is generated

NA

On click of explode button from details page in modify/verify/inquire/delete modes in the details page. Locale table appropriate values are fetched from NG_NFIU.

This locale script is called on click of explode button from details page in modify/verify/inquire/delete modes in the details page.

NA

NG_NFIUAddtionalDtlsModify.scr

This locale script is called for MODIFY mode.

NG_SRV_AddAndPostCashTran_post_process_data.scr

This locale script calls the add script to add the additional details specified in the explode screen in HTM, HCASHDEP and HCASHWD menu

NG_SRV_AddAndPostXferTran_post_process_data.scr

This locale script calls the add script to add the additional details specified in the explode screen in HXFER menu

NG_SRV_AddCashTran_post_process_data.scr

This locale script calls the add script to add the additional details specified in the explode screen in HTM, HCASHDEP and HCASHWD menu when clicked on SAVE

NG_SRV_AddXferTran_post_process_data.scr

This locale script calls the add script to add the additional details specified in the explode screen in HXFER menu when clicked on SAVE.

NG_SRV_ModifyAndPostCashTran_post_process_data.scr

This locale script calls the modify script to add/modify the additional details specified in the explode screen in HTM, HCASHDEP and HCASHWD menu

NG_SRV_ModifyAndPostXferTran_post_process_data.scr

This locale script calls the add script to add/modify the additional details specified in the explode screen in HXFER menu.

NG_SRV_ModifyCashTran_post_process_locale_data.scr

This locale script calls the modify script to add/modify the additional details specified in the explode screen in HTM, HCASHDEP and HCASHWD menu when clicked on SAVE

NG_SRV_ModifyXferTran_post_process_data.scr

This locale script calls the add script to add/modify the additional details specified in the explode screen in HXFER menu when clicked on SAVE.

©Copyright Infosys Ltd.

NG_passSheetAdhocCall.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script called from the mrt file for duplicate pass sheet print.

NA

NG_passSheetAdhocCall.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c number	The Account for which pass sheet is being printed
Page Number	How many pages are there in pass sheet

The following are the details of the output fields for the script:

N/A

This script calls NG_passSheetAdhocTran.scr for charge collection.

The locale script is called when duplicate pass sheet print happens for NG locale

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_passSheetAdhocTran.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script called from the NG_passSheetAdhocCall.scr for duplicate pass sheet print charges collection.

NA

NG_passSheetAdhocTran.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c number	The Account for which pass sheet is being printed
Page Number	How many pages are there in pass sheet

The following are the details of the output fields for the script:

N/A

This script collects charges from the customer account and performs respective credits in bank office account and vat office account.

The locale script is called when duplicate pass sheet print happens for NG locale

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_RevandBnsLocTblInsert.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

NA

NG_RevandBnsLocTblInsert.scr

The following are the details of the input fields for the script:

Input Field	Description
tablename	Common script to insert data to local table. Provide the table name into which data is to be inserted.
Action code	Pass the action code as 'A'

©Copyright Infosys Ltd.

NG_RevIntProcessData.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is called from ' NG_AddIntRateforPdts.scr' to process all the accounts for each individual and non individual scheme codes.

NA

NG_RevIntProcessData.scr

The following are the details of the input fields for the script:

Input Field	Description
A/c ID	The Account for which the batch has to be processed

The following are the details of the output fields for the script:

A failure report is generated listing the accounts failed and reason for failure.

It internally calls the ONS services (HINTTM service) to fetch existing interest details and modify them to ZERO interest rate, for not applying any interest for the identified accounts below minimum account balance.

The locale script is called from NG_AddIntRateforPdts.scr on run of bonus interest batch.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_RevIntRateforPdts.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

NA

NG_RevIntRateforPdts.scr

The following are the details of the input fields for the script:

Input Field	Description
Individual schmcode	Individual scheme code for which minimum balance is to be maintained.
Non Individual scheme code	Non individual scheme code for which minimum balance is to be maintained.
Reversal rate code	Zero rate code

A failure report is generated listing the accounts failed and reason for failure.

The locale batch script is scheduled as a monthly batch at the end of month before interest application. It will have the same frequency of that of interest application batch.

Accounts under the scheme codes parameterized in MLPS are processed by the batch for ITC table record insertion.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_SRV_AddAndPostCashTran_process_locale_c

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called on click of POST in HTM/HCASHDEP/HCASHWD menu. It is internally called NG_MCPRchrgCollection.scr for Charge collection for the given transaction.

NA

NA

NA

NA

NG_SRV_AddAndPostCashTran_process_locale_c

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called on click of POST in HTM/HCASHDEP/HCASHWD menu. It is internally called NG_MCHPchrgCollection.scr for charge collection for the given transaction.

NA

NA

NA

NA

NG_SRV_AddLienOnAcct_validate_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of SUBMIT button in HALM menu.

NA

NG_SRV_AddLienOnAcct_validate_locale_data.scr

NA

NA

The script is called on click of SUBMIT button in HALM menu. This script calls the locale validation script for lien.

The script is called on click of SUBMIT button in HALM menu.

NA

NG_SRV_FetchDfltCAAcctDtls_post_process_data

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of GO button HOAACCA menu.

NA

NG_SRV_FetchDfltCAAcctDtls_post_process_data.scr

NA

NA

The script gets on click of GO button HOAACCA menu. This script will in turn call NG_getCOTForAcctOpen.scr for getting the MLPS data and basic validation.

The script is called on click of GO button HOAACCA menu.

NA

NG_SRV_FetchDfltODAcctDtls_post_process_data

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of GO button HOAACOD menu.

NA

NG_SRV_FetchDfltODAcctDtls_post_process_data.scr

NA

NA

The script gets on click of GO button HOAACOD menu. This script will in turn call NG_getCOTForAcctOpen.scr for getting the MLPS data and basic validation.

The script is called on click of GO button HOAACOD menu.

NA

NG_SRV_FetchDfltSBAcctDtls_post_process_data

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of GO button HOAACSB menu.

NA

NG_SRV_FetchDfltSBAcctDtls_post_process_data.scr

NA

NA

The script is called on click of GO button HOAACSB menu. This script in turn calls NG_getCOTForAcctOpen.scr for getting the MLPS data and basic validation.

The script is called on click of GO button HOAACSB menu.

NA

NG_SRV_FetchOperAcctDtIForClosure_validate_d

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of GO button in HCAAC menu.

NA

NG_SRV_FetchOperAcctDtIForClosure_validate_data.scr

NA

NA

The script is called on click of GO button in HCAAC menu. This script calls the locale validation script to check the liquidation has happened on account before closure if any pending.

The script is called on click of GO button in HCAAC menu.

NA

NG_SRV_ModifyAndPostCashTran_process_locale

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called on click of POST in HTM/HCASHDEP/HCASHWD menu. It is internally called NG_MCHPchrgCollection.scr for charge collection for the given transaction.

NA

NA

NA

NA

NG_SRV_ModifyAndPostCashTran_process_locale

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called on click of POST in HTM/HCASHDEP/HCASHWD menu. It is internally called NG_MCPRchrgCollection.scr for Charge collection for the given transaction.

NA

NA

NA

NA

NG_SRV_ModifyLienOnAcct_validate_locale_data.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of SUBMIT button in HALM menu.

NA

NG_SRV_ModifyLienOnAcct_validate_locale_data.scr

NA

NA

The script is called on click of SUBMIT button in HALM menu. This script calls the locale validation script for lien.

The script is called on click of SUBMIT button in HALM menu.

NA

NG_SRV_PostTran_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called on click of POST in HTM/HCASHDEP/HCASHWD menu. It is internally called NG_MCHPchrgCollection.scr for charge collection for the given transaction.

NA

NA

NA

NA

NG_SRV_PostTran_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The locale script is called on click of POST in HTM/HCASHDEP/HCASHWD menu. It is internally called NG_MCPRchrgCollection.scr for Charge collection for the given transaction.

NA

NA

NA

NA

NG_SRV_VerifyCAAcct_pre_process_data.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of Submit button of HOAACVCA menu.

NA

NG_SRV_VerifyCAAcct_pre_process_data.scr

NA

NA

The script is called on click of Submit button of HOAACVCA menu. This script in turn calls NG_insertCCOTM.scr for inserting the record into locale table.

The script is called on click of Submit button of HOAACVCA menu.

NA

NG_SRV_VerifyCAAcct_process_locale_data.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The Verify post process of the CA account calls NG_updateAcctOpnDateForBA.scr script to activate the inactive account.

NA

NG_SRV_VerifyCAAcct_process_locale_data.scr

NA

NA

NA.

This script calls NG_updateAcctOpnDateForBA.scr to activate the inactive account.

N/A

NG_SRV_VerifyODAcct_pre_process_data.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of Submit button of HOAACVOD menu.

NA

NG_SRV_VerifyODAcct_pre_process_data.scr

NA

NA

The script is called on click of Submit button of HOAACVOD menu. This script in turn calls NG_insertCCOTM.scr for inserting the record into locale table.

The script is called on click of Submit button of HOAACVOD menu.

NA

NG_SRV_VerifySBAcct_pre_process_data.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called on click of Submit button of HOAACVSB menu.

NA

NG_SRV_VerifySBAcct_pre_process_data.scr

NA

NA

The script is called on click of Submit button of HOAACVSB menu. This script in turn calls NG_insertCCOTM.scr for inserting the record into locale table.

The script gets on click of Submit button of HOAACVSB menu.

NA

NG_UACDInsertAcctDtl.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used for data insert or modify to NG_BAD table.

N/A

NG_UACDInsertAcctDtl.scr

N/A

N/A

N/A

Only meant for data insert or modify to NG_BAD table.

N/A

©Copyright Infosys Ltd.

NG_UACDInsertCustDtl.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used for procTbl insert or modify to NG_BCD table.

N/A

NG_UACDInsertCustDtl.scr

N/A

N/A

N/A

Only meant for data insert or modify to NG_BCD table.

N/A

NG_UACDUpld.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script calls NG_UACDInsertAcctDtl.scr and NG_UACDInsertCustDtl.scr.

N/A

NG_UACDUpld.scr

All USPC fields defined in the section 3.5.1

successOrFailure and errorMessage

N/A

This script gets inputs from NG_bbuu4001.cxx (USPC fields) and based on the procTbl insert or modify, passes successOrFailure and errorMessage as output to NG_bbuu4001.cxx.

N/A

NG_updateAcctOpnDateForBA.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script gets called from the verify post process of SB, CA and OD accounts. This script activates the Welcome Kit generated accounts when the inactive account is modified for the first time through HACM.

NA

NG_updateAcctOpnDateForBA.scr

NA

NA

This script gets called from the verify post process of SB, CA and OD accounts. It checks whether the account has been activated. If the account is not activated then it activates the account.

This script is called from the Verify post process of HACM menu to activate the account through manual process.

N/A

NG_validateAcctDtlForClosure.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_SRV_FetchOperAcctDtlForClosure_validate_data.scr in HCAAC menu.

NA

NG_SRV_FetchOperAcctDtlForClosure_validate_data.scr

NA

NA

The script is called from NG_SRV_FetchOperAcctDtlForClosure_validate_data.scr in HCAAC menu. This script does validation to check the liquidation has happened on account before closure if any pending.

The script is called from NG_SRV_FetchOperAcctDtlForClosure_validate_data.scr in HCAAC menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

NG_validateCOTForAcct.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from NG_insertCCOTM.scr.

NA

NG_validateCOTForAcct.scr

NA

NA

This script is called from NG_insertCCOTM.scr. Fetch logic for common parameters and basic validation is handled here.

The script is called from NG_insertCCOTM.scr.

NA

NG_validateCOTLien.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

The script is called from
NG_SRV_ModifyLienOnAcct_validate_locale_data.scr

/ NG_SRV_AddLienOnAcct_validate_locale_data.scr for HALM
menu.

NA

NG_validateCOTLien.scr

NA

NA

The script is called from
NG_SRV_ModifyLienOnAcct_validate_locale_data.scr

/ NG_SRV_AddLienOnAcct_validate_locale_data.scr for HALM
menu. Validation for lien reason code check with that of COT is
handled here.

The script is called from
NG_SRV_ModifyLienOnAcct_validate_locale_data.scr

/ NG_SRV_AddLienOnAcct_validate_locale_data.scr for HALM
menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

Sample Scripts Added



Note:

This topic describes the enhancements delivered for 10.2.16 release.

Core

©Copyright Infosys Ltd.

Sample Scripts Modified



Note:

This topic describes the enhancements delivered for 10.2.16 release.

Core

Srl. No.	Script	Remarks
1	AcctClosureStampDuty.sscr	Modified for Transaction Code SER
2	BOTC_Trans.sscr	Modified for Transaction Code SER
3	CDTranParticulars.sscr	Modified for Transaction Code SER
4	ecsOutRetTransaction.sscr	Modified for Transaction Code SER
5	FxAdditionalTran.sscr	Modified for Transaction Code SER
6	FxBillContingent.sscr	Modified for Transaction Code SER
7	FxBillLodge.sscr	Modified for Transaction Code SER
8	LoanDmdSatisfy.sscr	Modified for Transaction Code SER
9	mrdsp.sscr	Modified for Transaction Code SER
10	MTTScrForProvTran.sscr	Modified for Transaction Code SER
11	pdcCollection.sscr	Modified for Transaction Code SER
12	psCreateReversalTran.sscr	Modified for Transaction Code SER

13	recoverTds.sscr	Modified for Transaction Code SER
14	salRecoveryBillTran.sscr	Modified for Transaction Code SER
15	tdintcalc.sscr	Modified for Transaction Code SER

©Copyright Infosys Ltd.

Scripts for APND menu



Note:

This topic describes the enhancements delivered for 10.2.16 release.

NG_APND_FetchDetails.scr

This script is called on click of Go of 'APND' menu to validate and fetch the data for the Pin number entered.

NG_APND_SubmitDetails.scr

This script is called on click of Submit of 'APND' menu to carry out inter sol transaction.

©Copyright Infosys Ltd.

Scripts for CTLM menu



Note:

This topic describes the enhancements delivered for 10.2.16 release.

NG_CTLM_ValidateDetails.scr

This script is called to validate the data for the payment number specified.

NG_CTLM_SubmitDetails.scr

This script is called on click of Submit of 'CTLM' menu to carry out receiver side transaction based on collect type specified.

©Copyright Infosys Ltd.

Scripts for ILMT menu



Note:

This topic describes the enhancements delivered for 10.2.16 release.

NG_PopAmtOnchange.scr

The following are the details of the input fields for the script:

Input Field	Description
Amount	Amount entered in criteria page of ILMT menu
Collect type	Collect Type selected in criteria page of ILMT menu
Amount Inclusive of Charge	Amount Inclusive of Charge selected in criteria page of ILMT menu

Auto populates the **Amt Payable** field in criteria of ILMT menu based on selection of collect type and amt inclusive flag.

Auto populates the **Amt Payable** field in criteria of ILMT menu based on selection of collect type and amt inclusive flag.

NG_CompChrgAmt.scr

This script is called from ' NG_PopAmtOnchange.scr' to compute the different charges payable based on collect type.

NG_FetchMLPSdataforLMT.scr

This is a common script to fetch MLPS data for LMT for module G and sub module 'LMT'. The cot charge and cot placeholder will be derived from MLPS data stored for COT enhancement for module 'L' and sub module 'COT'.

NG_ILMT_CompTotAmt.scr

This script is called from ' NG_CompChrgAmt.scr ' to compute the total amount payable based on collect type and amount inclusive flag

NG_ILMT_FetchTblVal.scr

This script is called to populate the computational field values in details page in all modes other than add based on serial number and also to populate amount payable to receiver in all modes.

NG_ILMT_FetchChqDet.scr

This script is called to populate the instrument number, instrument type and security number entered for the HTM transaction done to debit sender account and credit fund transfer account for collect type as cheque.

NG_ILMT_FetchForAdd.scr

This script is called on click of Go to populate the sender details based on sender account id entered in criteria and also to populate the different charges(commission amount,demand draft commission amount,vat amount, service charge) in details page.

NG_ILMT_ValidateData.scr

This script is called to validate the criteria details. This script is called from ' NG_ILMT_FetchForAdd.scr '

NG_ILMT_ValSndrAcctDetails.scr

This script is called from ' NG_ILMT_ValidateData.scr' to validate the sender details if sender account id is entered.

NG_ILMT_SubmitData.scr

This script is called on click of "Submit" in all modes of ILMT menu.

NG_ILMT_SubmitForAdd.scr

This script is called on Submit in add mode of ILMT menu.

NG_ILMT_ValDataonSubmit.scr

This script is called to validate the details page data of ILMT menu.

NG_ILMT_SubmitDataForAllmodes.scr

This script is called on click of submit of Verify/Cancel/modify mode.

NG_ILMT_FetchDetails.scr

This script is called on click of 'Go' in Modify/Inquire/Verify/Cancel mode to populate the details page data for the serial number entered.

NG_ILMT_GetTableDetails.scr

This is a common script called to fetch the table values from LMT table for the serial number.

NG_ILMT_HandleTxn.scr

This script carries out the sender side transactions based on the collect type and transfer type selected.

NG_ILMT_HandleSRVErrors.scr

This script handles the SRV errors and exceptions encountered on execution.

Scripts for MPND menu

Note:

This topic describes the enhancements delivered for 10.2.16 release.

NG_mpndGetData.scr

This script is called on click of Go of 'MPND' menu.

NG_mpndSubmit.scr

This script is called on click of Submit of 'MPND' menu for blocking and activating specified PIN number.

©Copyright Infosys Ltd.

Scripts for RLPN menu



Note:

This topic describes the enhancements delivered for 10.2.16 release.

NG_rlpn.scr

This script is called on click of Submit of 'MPND' menu for retrieving the lost pin number for the specified Serial number.

©Copyright Infosys Ltd.

Scripts for RPN menu



Note:

This topic describes the enhancements delivered for 10.2.16 release.

NG_rpn.scr

This script is called on click of Submit of 'MPND' menu for retrieving the payment number for the specified PIN number.

©Copyright Infosys Ltd.

Scripts Hooks Added



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This section discusses the various scripts and scripts hooks added due to enhancements in the release.

Scripts for Core

©Copyright Infosys Ltd.

Scripts Modified

Note:

This topic describes the enhancements delivered for 10.2.16 release.

Core

Srl. No.	Script	Remarks
1	ACCBAL_PostQry.scr	Modified for Transaction Code SER
2	accrdPenalIntTran.scr	Modified for Transaction Code SER
3	ACH_CreateChrgTran.scr	Modified for Transaction Code SER
4	achCreateReturnTran.scr	Modified for Transaction Code SER
5	achLACollectionProcessing.scr	Modified for Transaction Code SER
6	achProcessSuspTran.scr	Modified for Transaction Code SER
7	AmortizationTran.scr	Modified for Transaction Code SER
8	AutoReshdITranScript.scr	Modified for Transaction Code SER
9	B2K_bgContLiabScript.scr	Modified for Transaction Code SER
10	B2K_ContingentTran.scr	Modified for Transaction Code SER
11	B2K_FxBillEventTransaction.scr	Modified for Transaction Code SER
12	B2K_MarginTransactionScript.scr	Modified for Transaction Code SER
13	B2K_ReversalTran.scr	Modified for Transaction Code SER
14	BesaniXferTransaction.scr	Modified for Transaction

		Code SER
15	bgDefChrgCollTran.scr	Modified for Transaction Code SER
16	bgInvocationEventTran.scr	Modified for Transaction Code SER
17	bonusCalc.scr	Modified for Transaction Code SER
18	buybackAuthPcTran.scr	Modified for Transaction Code SER
19	buybackAuthTran.scr	Modified for Transaction Code SER
20	cashwdtax.scr	Modified for Transaction Code SER
21	cashwdtaxCTD.scr	Modified for Transaction Code SER
22	ChargeOffMTT.scr	Modified for Transaction Code SER
23	chargeReversal.scr	Modified for Transaction Code SER
24	chargeReversalMod.scr	Modified for Transaction Code SER
25	clCrystalsnTranCreation.scr	Modified for Transaction Code SER
26	ClCustPayTranCreation.scr	Modified for Transaction Code SER
27	CLDrawDown.scr	Modified for Transaction Code SER
28	closureTran.scr	Modified for Transaction Code SER
29	closureTranForCashAndTransf.scr	Modified for Transaction Code SER
30	ClupayTranCreation.scr	Modified for Transaction Code SER
31	CollToEscrow.scr	Modified for Transaction Code SER
32	CollToSPV.scr	Modified for Transaction Code SER

33	CollToSPVAmort.scr	Modified for Transaction Code SER
34	createAchorpTran.scr	Modified for Transaction Code SER
35	createAchReturnTran.scr	Modified for Transaction Code SER
36	CreateDSACommissionTran.scr	Modified for Transaction Code SER
37	CreateFCCTran.scr	Modified for Transaction Code SER
38	CreateInwardSWIFTPaymtTran.scr	Modified for Transaction Code SER
39	CreateOutwardSWIFTPaymtTran.scr	Modified for Transaction Code SER
40	CreatePymtlnwSuspTran.scr	Modified for Transaction Code SER
41	CreateReversalTran.scr	Modified for Transaction Code SER
42	createSchemeTranForAccount.scr	Modified for Transaction Code SER
43	createsolxfrtran.scr	Modified for Transaction Code SER
44	createUpIChrgTran.scr	Modified for Transaction Code SER
45	CreditTranProcForPastDueAcct.scr	Modified for Transaction Code SER
46	CustProvisionTran.scr	Modified for Transaction Code SER
47	custTranCreation.scr	Modified for Transaction Code SER
48	DA_CreateChrgTran.scr	Modified for Transaction Code SER
49	ddpupl.scr	Modified for Transaction Code SER
50	ddupload.scr	Modified for Transaction Code SER
51	dduploadchrg.scr	Modified for Transaction

		Code SER
52	DebtTransfer.scr	Modified for Transaction Code SER
53	DELCHDTL_PostQry.scr	Modified for Transaction Code SER
54	dspVostroTransferTran.scr	Modified for Transaction Code SER
55	ecgcmmt.scr	Modified for Transaction Code SER
56	ecsBulkTransaction.scr	Modified for Transaction Code SER
57	ecsInwBulkTransaction.scr	Modified for Transaction Code SER
58	ecsInwRetProcessing.scr	Modified for Transaction Code SER
59	EntityFeeCollectionMTT.scr	Modified for Transaction Code SER
60	fee_amortization.scr	Modified for Transaction Code SER
61	fileRecallTranCreation.scr	Modified for Transaction Code SER
62	FWCDeliveryTran.scr	Modified for Transaction Code SER
63	fxBillAccept.scr	Modified for Transaction Code SER
64	InterestReversal.scr	Modified for Transaction Code SER
65	intRvrslTranCreation.scr	Modified for Transaction Code SER
66	LaChargeTransaction.scr	Modified for Transaction Code SER
67	LAFeeRefundMTT.scr	Modified for Transaction Code SER
68	LAFeeTransferMTT.scr	Modified for Transaction Code SER
69	LaPayTranCreation.scr	Modified for Transaction Code SER

70	LARebatePaymentMTT.scr	Modified for Transaction Code SER
71	LaSPayTranCreation.scr	Modified for Transaction Code SER
72	LaUPayTranCreation.scr	Modified for Transaction Code SER
73	LAwaiveInterestMTT.scr	Modified for Transaction Code SER
74	LimitContTran.scr	Modified for Transaction Code SER
75	LoanAdvIntAdj.scr	Modified for Transaction Code SER
76	LoanNonAccrueTran.scr	Modified for Transaction Code SER
77	LoanPayoffTran.scr	Modified for Transaction Code SER
78	LoanRecoverytran.scr	Modified for Transaction Code SER
79	LoanReschedulingTran.scr	Modified for Transaction Code SER
80	LoanReshdlReversalTran.scr	Modified for Transaction Code SER
81	LoanReverseNonAccrueTran.scr	Modified for Transaction Code SER
82	LoanRevRecovery.scr	Modified for Transaction Code SER
83	LoanRolloverAdvIntTran.scr	Modified for Transaction Code SER
84	LoanUICPrePay.scr	Modified for Transaction Code SER
85	mttZakatDeduction.scr	Modified for Transaction Code SER
86	odbillcolltran.scr	Modified for Transaction Code SER
87	odlatefeetran.scr	Modified for Transaction Code SER
88	OpPDCCChrgTranCreation.scr	Modified for Transaction Code SER

89	parseTTUM711.scr	Modified for Transaction Code SER
90	PckgAcctMaintCharge.scr	Modified for Transaction Code SER
91	PO_CreatePORDTran.scr	Modified for Transaction Code SER
92	poolAcctProfitDist.scr	Modified for Transaction Code SER
93	poolauthtran.scr	Modified for Transaction Code SER
94	poolInvst.scr	Modified for Transaction Code SER
95	poolInvstClosure.scr	Modified for Transaction Code SER
96	poolInvstCls.scr	Modified for Transaction Code SER
97	poolIPIProfitDist.scr	Modified for Transaction Code SER
98	PoolProfitAccrual.scr	Modified for Transaction Code SER
99	poolProfitCalc.scr	Modified for Transaction Code SER
100	poolRecon.scr	Modified for Transaction Code SER
101	profitBooking.scr	Modified for Transaction Code SER
102	psuploadSLIPS.scr	Modified for Transaction Code SER
103	PurchaseSaleCommMTT.scr	Modified for Transaction Code SER
104	recallTranCreation.scr	Modified for Transaction Code SER
105	RecdIntIncomeRecoveryTran.scr	Modified for Transaction Code SER
106	ReverseChargeOffMTT.scr	Modified for Transaction Code SER

107	ReverseTaChargeOffMTT.scr	Modified for Transaction Code SER
108	ReverseXferTransaction.scr	Modified for Transaction Code SER
109	Revocation.scr	Modified for Transaction Code SER
110	rpctmTranCreation.scr	Modified for Transaction Code SER
111	RTGS_InSuspProcCustPymtTran.scr	Modified for Transaction Code SER
112	RTGS_InSuspProcInterBankTran.scr	Modified for Transaction Code SER
113	RTGS_ProcessInTran.scr	Modified for Transaction Code SER
114	rtgsCustPaymentReversalTran.scr	Modified for Transaction Code SER
115	rtgsCustPaymentTran.scr	Modified for Transaction Code SER
116	rtgsIntBankPaymentRvrslTran.scr	Modified for Transaction Code SER
117	rtgsInterBankPaymentTran.scr	Modified for Transaction Code SER
118	rtgsOwnAcctTransferTran.scr	Modified for Transaction Code SER
119	salPay.scr	Modified for Transaction Code SER
120	settlementProcess.scr	Modified for Transaction Code SER
121	subsidyCollection.scr	Modified for Transaction Code SER
122	subsidyDmdClm.scr	Modified for Transaction Code SER
123	swapChrgColl.scr	Modified for Transaction Code SER
124	SynDrawDownTran.scr	Modified for Transaction Code SER
125	TaChargeOffMTT.scr	Modified for Transaction

		Code SER
126	TDacctOpenTran.scr	Modified for Transaction Code SER
127	TDSuploadTranCreation.scr	Modified for Transaction Code SER
128	tfcChrgCollection.scr	Modified for Transaction Code SER
129	tracerChargeColl.scr	Modified for Transaction Code SER
130	TranAcctRecoverytran.scr	Modified for Transaction Code SER
131	TranAcctRevRecovery.scr	Modified for Transaction Code SER
132	TransferReversal.scr	Modified for Transaction Code SER
133	Ttumupload.scr	Modified for Transaction Code SER
134	TUAcctOpenTran.scr	Modified for Transaction Code SER
135	XferTransaction.scr	Modified for Transaction Code SER
136	OpPDCContTranCreation.scr	Modified for Transaction Code SER
137	createFWCForwardRevalTran.scr	Modified for Transaction Code SER
138	B2K_FactContingentTran.scr	Modified for Transaction Code SER
139	B2K_IslamicPurEventTransaction.scr	Modified for Transaction Code SER
140	FactMarkPastDue.scr	Modified for Transaction Code SER
141	FactRetransferPastDue.scr	Modified for Transaction Code SER
142	LADisbAdjMarginDebit.scr	Modified for Transaction Code SER
143	LADisbursementMTTExtn.scr	Modified for Transaction Code SER

144	PremPayTran.scr	Modified for Transaction Code SER
145	TradeAssetRecovMTT.scr	Modified for Transaction Code SER
146	TradeAssetReverseRecovMTT.scr	Modified for Transaction Code SER
147	LIPRFTTranCreation.scr	Modified for Transaction Code SER
148	MurabahaBulkPurchaseTran.scr	Modified for Transaction Code SER
149	RepossessIjarahAcctMTT.scr	Modified for Transaction Code SER
150	acctBooking.scr	Modified for Transaction Code SER
151	createIRRTran.scr	Modified for Transaction Code SER
152	islamicPoolProfitCalc.scr	Modified for Transaction Code SER
153	islamicProfitSimulation.scr	Modified for Transaction Code SER
154	AssetImpDepMTT.scr	Modified for Transaction Code SER
155	DepreciationTran.scr	Modified for Transaction Code SER
156	LSAmortBatchMTT.scr	Modified for Transaction Code SER
157	LSAssetDisposalMTT.scr	Modified for Transaction Code SER
158	LSPaymentBatchMTT.scr	Modified for Transaction Code SER
159	LSPaymentOnlineMTT.scr	Modified for Transaction Code SER
160	LeasePayoffTran.scr	Modified for Transaction Code SER
161	MDADeprAmtMTT.scr	Modified for Transaction Code SER
162	MasAssetIDPayMTT.scr	Modified for Transaction

		Code SER
163	insuranceTranMTT.scr	Modified for Transaction Code SER
164	repossessionTranMTT.scr	Modified for Transaction Code SER
165	unearnedIncomeTransaction.scr	Modified for Transaction Code SER
166	AmortizationOfAFRMTT.scr	Modified for Transaction Code SER
167	DepreciationMTT.scr	Modified for Transaction Code SER
168	IslFreqBasedPrftDist.scr	Modified for Transaction Code SER
169	IslamicDepoitsClsTran.scr	Modified for Transaction Code SER
170	IslamicFreqBasedProfitDist.scr	Modified for Transaction Code SER
171	IslamicOperClsTran.scr	Modified for Transaction Code SER
172	IslamicPreClsTran.scr	Modified for Transaction Code SER
173	MurabahaPurchaseTran.scr	Modified for Transaction Code SER
174	MurabahaReversal.scr	Modified for Transaction Code SER
175	MurabahaReversalOfBulkPurchaseTran.scr	Modified for Transaction Code SER
176	MurabahaSaleTran.scr	Modified for Transaction Code SER
177	collAdjstmntTran.scr	Modified for Transaction Code SER
178	minAgeTranForMudarabah.scr	Modified for Transaction Code SER
179	murabahaProfitPayout.scr	Modified for Transaction Code SER
180	profitPayout.scr	Modified for Transaction Code SER

181	tacsp.scr	Modified for Transaction Code SER
182	wakProfDist.scr	Modified for Transaction Code SER
183	TradeAssetChargeOffMTT.scr	Modified for Transaction Code SER
184	LADisbursementMTT.scr	Modified for Transaction Code SER

©Copyright Infosys Ltd.

SPTC_PostQry.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used to get the system part transaction code description.

Input Field	Description
BANCS.INPUT.part_tran_mmsg_id	Part Transaction Message Id/Code

Output Field	Description
BANCS.OUTPUT.sys_part_tran_desc	System Part Transaction Code Description

This script should be available to get the system part transaction code description.

This script is used in the searcher of system part transaction code.

©Copyright Infosys Ltd.

STC_PostQry.scr



Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used to get the system transaction code description.

Input Field	Description
BANCS.INPUT.tran_mmsg_id	Transaction Message Id/Code

Output Field	Description
BANCS.OUTPUT.sys_tran_code_desc	System Transaction Code Description

This script should be available to get the system transaction code description.

This script is used in the searcher of system transaction code.

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used to get the system transaction/part transaction code for display in searcher in HTM menu.

Input Field	Description
BANCS.INPUT. systemTranCode	System Transaction Code
BANCS.INPUT.systemPartTranCode	System Part Transaction Code

Output Field	Description
BANCS.OUTPUT. system_tran_code	System Transaction Code for Listing
BANCS.OUTPUT.system_part_tran_code	System Part Transaction Code for Listing

This script should be available to display the system transaction/part transaction code in the searcher list.

This script is used in the searcher in HTM menu.

UTCMAIN_PostQry.scr

Note:

This topic describes the enhancements delivered for 10.2.16 release.

This script is used to get the system transaction code for display in searcher in HTM menu.

Input Field	Description
BANCS.INPUT. systemTranCode	System Transaction Code

Output Field	Description
BANCS.OUTPUT. system_tran_code	System Transaction Code for Listing

This script should be available to display the system transaction code in the searcher list.

This script is used in the searcher in HTM menu.

©Copyright Infosys Ltd.

createExtraPartTransactionForAdvEI.scr (Advance EI)



NA

createExtraPartTransactionForAdvEI.scr

NA

NA

The script is used to call the script ExtraPartTransactionForAdvEI.scr to create extra part transaction for advance EI amount.

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

createSchemeTransactionForAccount.scr (Advance EI)

Reference

NA

Script Name

createSchemeTransactionForAccount.scr

Input

NA

Output

NA

Default Logic

The script calls IN_postXferTransactionForAdvEI.scr for transaction creation.

Typical Usage Scenario

This script is called in India localization, for advance EI transaction creation.

Sample Script

NA

©Copyright Infosys Ltd.

NA

createsolxfrtransaction.scr

NA

NA

The script calls IN_postXferTransactionForAdvEI.scr for transactionsaction creation.

This script is called in India localization, for advance EI transactionsaction creation.

NA

©Copyright Infosys Ltd.

EDPRealizOptionalResponse.scr



This script is used for customization / generation of optional responses in EDPMS reports for Bill Realization

This is added for the ticket 693694.

EDPRealizOptionalResponse.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.FIRCNumber	FIRC Number, in case the payment realized in different AD Code
BANCS.INPUT.accountNumber	Account Number to which payment was received for the invoice
BANCS.INPUT.bankingChargesAmt	Amount charged by bank for realization
BANCS.INPUT.FOBAmtIC	Equivalent FOB Amount in Invoice Currency Code
BANCS.INPUT.freightAmtIC	Equivalent Freight Amount in Invoice Currency Code
BANCS.INPUT.insuranceAmtIC	Equivalent Insurance Amount in Invoice Currency Code
BANCS.INPUT.commissionAmtIC	Equivalent Commission Amount in Invoice Currency Code
BANCS.INPUT.packagingChargesAmtIC	Equivalent Packaging Amount in Invoice Currency Code
BANCS.INPUT.deductionAmtIC	Equivalent Deduction Amount in Invoice Currency Code
BANCS.INPUT.discountAmtIC	Equivalent Discount Amount in Invoice Currency Code
BANCS.INPUT.finFOBAmtIC	Equivalent FOB Amount in Invoice Currency Code from Finacle product table

BANCS.INPUT.finfreightAmtIC	Equivalent Freight Amount in Invoice Currency Code from existing Finacle product table
BANCS.INPUT.fininsuranceAmtIC	Equivalent Insurance Amount in Invoice Currency Code from Existing finacle product table
BANCS.INPUT.fincommissionAmtIC	Equivalent Commission Amount in Invoice Currency Code from finacle table
BANCS.INPUT.finpackagingChargesAmtIC	Equivalent Packaging Amount in Invoice Currency Code from existing Finacle product table
BANCS.INPUT.findeductionAmtIC	Equivalent Deduction Amount in Invoice Currency Code from existing Finacle product table
BANCS.INPUT.findiscountAmtIC	Equivalent Discount Amount in Invoice Currency Code from existing Finacle product table
BANCS.INPUT.finfreightAmtCCY	freight Amt Currency code
BANCS.INPUT.finfreightAmtRate	Freight Amt Rate
BANCS.INPUT.finfreightAmtRateCode	freight Amt rate code.
BANCS.INPUT.fininsuranceAmtCCY	insurance Amt currency code
BANCS.INPUT.fininsuranceAmtRate	insurance Amt Rate
BANCS.INPUT.fininsuranceAmtRateCode	Insurance Amt Rate code
BANCS.INPUT.realizationAmtCCY	realization Amt currency code
BANCS.INPUT.invoiceAmtCCY	invoice amt currency code
BANCS.INPUT.convRate	conversion rate
BANCS.INPUT.convRateCode	conversion rate code

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.FIRCADCCode	AD Code at which actual realization occurred
BANCS.OUTPUT.FOBAMt	Actual FOB Amount in Realized Currency Code
BANCS.OUTPUT.FOBAMtIC	Equivalent FOB Amount in Invoice Currency

	Code
BANCS.OUTPUT.freightAmt	Actual Freight Amount in Realized Currency Code
BANCS.OUTPUT.freightAmtIC	Equivalent Freight Amount in Invoice Currency Code
BANCS.OUTPUT.insuranceAmt	Actual Insurance Amount in Realized Currency Code
BANCS.OUTPUT.insuranceAmtIC	Equivalent Insurance Amount in Invoice Currency Code
BANCS.OUTPUT.commissionAmt	Actual Commission Amount in Realized Currency Code
BANCS.OUTPUT.commissionAmtIC	Equivalent Commission Amount in Invoice Currency Code
BANCS.OUTPUT.packagingChargesAmt	Actual Packaging Amount in Realized Currency Code
BANCS.OUTPUT.packagingChargesAmtIC	Equivalent Packaging Amount in Invoice Currency Code
BANCS.OUTPUT.deductionAmt	Actual Deduction Amount in Realized Currency Code
BANCS.OUTPUT.deductionAmtIC	Equivalent Deduction Amount in Invoice Currency Code
BANCS.OUTPUT.discountAmt	Actual Discount Amount in Realized Currency Code
BANCS.OUTPUT.discountAmtIC	Equivalent Discount Amount in Invoice Currency Code

BANCS.OUTPUT.FIRCADCCode defaulted as Null. To be customized if required.

All output amounts default mapped to input amounts in invoice currency.

Example:

BANCS.OUTPUT.FOBAmtIC = BANCS.INPUT.FOBAmtIC

BANCS.OUTPUT.freightAmtIC = BANCS.INPUT.freightAmtIC

So on.

Sample conversion of freight amount from invoice currency to freight amount currency handled.

Based on this example any further currency conversion of various amounts required to be customized as per Bank's requirement for optional response.

Freight amount rate, insurance rate and conversion rate are 3 rates available as inputs in the script for such conversions. Any different rate to be considered must be derived in script based on custom logic only.

Used for generating the optional responses of EDPMS reports for Bill realization event.

©Copyright Infosys Ltd.

errorLogIntoDB.scr



This script takes input from the MRT file and update the BFDt table with corresponding keys.

errorLogIntoDB.scr

The following are the details of the input fields for the script:

Input Field	Description
recordKey	Holds the key value of failure record
errorCode	Holds the error code of the failure record
errorMsg	Holds the error message of the failure record
exeName	Holds the exe name of the failure record

©Copyright Infosys Ltd.

ExtraPartTransactionForAdvEI.scr (Advance EI)



NA

ExtraPartTransactionForAdvEI.scr

NA

NA

The script is used to call to create the extra part transaction for advance EI amount.

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

GetRefAmtForAdvEI.scr (Advance EI)



NA

GetRefAmtForAdvEI.scr

NA

NA

The script is used to get the ref amount after add or subtract the advance EI amount.

This script is called in India localization, for HLADISB.

NA

Scripts for Core

©Copyright Infosys Ltd.

GetRefAmtForAdvEILoans.scr (Advance EI)



NA

GetRefAmtForAdvEILoans.scr

NA

NA

The script is used to call the script GetRefAmtForAdvEI.scr to get the ref amount.

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_AcctReliefDataUpload.scr (DPD Freeze)



This script is called to upload the relief period details to IN_RPD table

NA

IN_AcctReliefDataUpload.scr

The following is the syntax for specifying the input fields:

NA

NA

This script is called to upload the relief period details to IN_RPD table

Is called during the upload menu URPDA.

NA

©Copyright Infosys Ltd.

IN_AcctReliefDataValidate.scr (DPD Freeze)



This script is called to validate the relief period details during upload

NA

IN_AcctReliefDataValidate.scr

The following is the syntax for specifying the input fields:

NA

NA

This script is called to validate the relief period details during upload.

Is called during the upload menu URPDA.

NA

©Copyright Infosys Ltd.

IN_AddMTTLAAddnIDtls.scr (NEFT and RTGS)



This script is called to populate the LA additional details required for creating a transactionsaction on Loan account.

NA

IN_AddMTTLAAddnIDtls.scr

NA

NA

This script is called to populate the LA additional details required for creating a transactionsaction on Loan account.

Is called during creation of Loan account transactionsaction through NEFT/RTGS payment.

NA

©Copyright Infosys Ltd.

IN_addPODetails.scr (UTR and DD No)



This script adds locale data for the menu HPORDM

NA

NA

NA

This script adds locale data for the menu HPORDM

Post process script that is called during addition

NA

©Copyright Infosys Ltd.

IN_Advance_EI_Fetch.scr (Advance EI)



NA

IN_Advance_EI_Fetch.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.mopId	The menu id of the corresponding menu
BANCS.INPUT.acctNo	The account no given at the account level
BANCS.INPUT.schmCodeLoc	The scheme code entered during account opening
BANCS.INPUT.currCodeLoc	The corresponding currency of the scheme code

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.advanceEIColl	The advance EI collection indicator set at the scheme level

This script gets the value of advance EI collection set at the scheme level for the corresponding scheme from the IN_LLSP table

This script is called in India localization from HOAACL/HOAACMLA.

NA

IN_AdvanceEI_FetchForLNGI.scr (Advance EI)



NA

IN_AdvanceEI_FetchForLNGI.scr

None

None

This script handles the fetch of Advance EI of the parameters of Advance EI for LNGI menu.

This script is called in India localization from script:

IN_SRV_FetchLaGenDetails_process_locale_data.scr

NA

©Copyright Infosys Ltd.

NA

IN_advanceEI_validate.scr

None

None

This script handles the validation of Advance EI of the parameters of Advance EI at the upload level

This script is called in India localization from source IN_lauu9500.cxx

NA

©Copyright Infosys Ltd.

IN_advanceEiVal.scr (Advance EI)



NA

IN_advanceEiVal.scr

None

None

This script handles the validations of Advance EI of the parameters of Advance EI at the account level.

This script is called in India localization from script:

IN_SRV_ModifyLAAcct_validate_data.scr

IN_SRV_OpenLaAcct_validate_data.scr

NA

©Copyright Infosys Ltd.

IN_BGNPAFR_ListGet.scr (NPA Forms report)



This script is used for handle the criteria query for BGNPAFR menu.

NA

IN_BGNPAFR_ListGet.scr

NA

NA

Records which are needed for processing is fetched here based on the inputs from the criteria fields of BGNPAFR menu.

Is called once the BCFG menu BGNPAFR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPAFR_RecordProcess.scr (NPA Forms report)



This script is used for handle the each eligible NPA records for BGNPAFR menu.

NA

IN_BGNPAFR_RecordProcess.scr

NA

NA

Each eligible NPA Records are processed here which forms the 1st file for the BGNPAFR menu report.

Is called once the BCFG menu BGNPAFR is invoked.

NA

©Copyright Infosys Ltd.

IN_bgnpafr.scr (NPA Forms report)

Infosys®



This script is called from the COM file for the BGNPAFR menu and performs the rest of the processing

NA

IN_bgnpafr.scr

NA

NA

This script is called from the COM file for the BGNPAFR menu and performs the rest of the processing.

Is called once the BCFG menu BGNPAFR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPAFR_SetRegisterInfo.scr (NPA Forms report)



This script is used to set the repository values needed for BGNPAFR menu.

NA

IN_BGNPAFR_SetRegisterInfo.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.arg_4

CUSTOM.BATCH.arg_5

CUSTOM.BATCH.arg_6

CUSTOM.BATCH.arg_7

CUSTOM.BATCH.arg_8

The following are the details of the input fields for the script:

Input Field	Description
CUSTOM.BATCH.arg_4	From date in criteria
CUSTOM.BATCH.arg_5	To date
CUSTOM.BATCH.arg_6	Sol Set Id
CUSTOM.BATCH.arg_7	Report format [PDF,XLX, TXT]
CUSTOM.BATCH.arg_8	Report type[Substandard, Doubtful1, Doubtful2, Doubtful3, Loss]

All the inputs in the criteria fields of BGNPAFR menu are accessed in this script and populated in the CUSTOM.BATCH repository.

Is called once the BCFG menu BGNPAFR is invoked.

NA

IN_BGNPAFR_PostProcessing.scr (NPA Forms report)

This script is used for handle the report formation using LST file and jasper files for BGNPAFR menu.

NA

IN_BGNPAFR_PostProcessing.scr

NA

NA

Report formation happens here based on the LST file formed and jasper files.

Is called once the BCFG menu BGNPAFR is invoked.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_bgnpafrReadInput.scr (NPA Forms report)



This script is used for handle input fields from DAT file for BGNPAFR menu.

NA

IN_bgnpafrReadInput.scr

NA

Input fields from the DAT file is processed here for the BGNPAFR menu report.

Is called once the BCFG menu BGNPAFR is invoked.

NA

©Copyright Infosys Ltd.

IN_bgnparr.scr (NPA Recovery report)

Infosys®



This script is called from the COM file for the BGNPAFR menu and performs the rest of the processing

NA

IN_bgnparr.scr

The following is the syntax for specifying the input fields:

NA

The following are the details of the output fields for the script:

NA

This script is called from the COM file for the BGNPARR menu and performs the rest of the processing.

Is called once the BCFG menu BGNPARR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPARR_ListGet.scr (NPA Recovery report)

This script is used for handle the criteria query for BGNPAFR menu

NA

IN_BGNPARR_ListGet.scr

The following is the syntax for specifying the input fields:

NA

The following are the details of the output fields for the script:

NA

Records which are needed for processing is fetched here based on the inputs from the criteria fields of BGNPARR menu.

Is called once the BCFG menu BGNPARR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPARR_PostProcessing.scr (NPA Recovery report)



This script is used for handle the report formation using LST file and jasper files for BGNPARR menu

NA

IN_BGNPARR_PostProcessing.scr

The following is the syntax for specifying the input fields:

NA

NA

Report formation happens here based on the LST file formed and jasper files.

Is called once the BCFG menu BGNPARR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPARR_RecordProcess.scr (NPA Recovery report)



This script is used for handle the each eligible NPA records for BGNPARR menu

NA

IN_BGNPARR_RecordProcess.scr

The following is the syntax for specifying the input fields:

NA

NA

Each eligible NPA Records are processed here which forms the 1st file for the BGNPAFR menu report.

Is called once the BCFG menu BGNPARR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPARR_SetRegisterInfo.scr (NPA Recovery report)



This script is used to set the repository values needed for BGNPARR menu

NA

IN_BGNPARR_SetRegisterInfo.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.arg_4

CUSTOM.BATCH.arg_5

CUSTOM.BATCH.arg_6

CUSTOM.BATCH.arg_7

CUSTOM.BATCH.arg_8

The following are the details of the input fields for the script:

Input Field	Description
CUSTOM.BATCH.arg_4	From date in criteria
CUSTOM.BATCH.arg_5	To date
CUSTOM.BATCH.arg_6	SOL Set ID
CUSTOM.BATCH.arg_7	Report format [PDF,XLX, TXT]
CUSTOM.BATCH.arg_8	Report type[Substandard, Doubtful1, Doubtful2, Doubtful3, Loss]

All the inputs in the criteria fields of BGNPARR menu are accessed in this script and populated in the CUSTOM.BATCH repository.

Is called once the BCFG menu BGNPAFR is invoked.

NA

©Copyright Infosys Ltd.

IN_bgnparrReadInput.scr (NPA Recovery report)

This script is used for handle input fields from DAT file for BGNPARR menu

NA

IN_bgnparrReadInput.scr

The following is the syntax for specifying the input fields:

NA

NA

Input fields from the DAT file is processed here for the BGNPARR menu report.

Is called once the BCFG menu BGNPARR is invoked.

NA

©Copyright Infosys Ltd.

IN_bgpnpsar.scr (PSL/NON PSL report)

Infosys®



This script is called from the COM file for the BGPNPSAR menu and performs the rest of the processing

NA

IN_bgpnpsar.scr

NA

NA

This script is called from the COM file for the BGPNPSAR menu and performs the rest of the processing.

Is called once the BCFG menu BGPNPSAR is invoked.

©Copyright Infosys Ltd.

IN_BGNPNSAR_ListGet.scr (PSL/NON PSL report)



This script is used for handle the criteria query for BGNPAFR menu

NA

IN_BGNPNSAR_ListGet.scr

The following is the syntax for specifying the input fields:

NA

The following are the details of the output fields for the script:

NA

Records which are needed for processing is fetched here based on the inputs from the criteria fields of B BGNPNSAR menu.

Is called once the BCFG menu BGNPNSAR is invoked.

NA

IN_BGNPSAR_PostProcessing.scr (PSL/NON PSL report)



This script is used for handle the report formation using LST file and jasper files for BGNPAFR menu

NA

IN_BGNPSAR_PostProcessing.scr

The following is the syntax for specifying the input fields:

NA

NA

Report formation happens here based on the LST file formed and jasper files.

Is called once the BCFG menu BGNPSAR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPSAR_RecordProcess.scr (PSL/NON PSL report)



This script is used for handle the each eligible NPA records for BGNPSAR menu

NA

IN_BGNPSAR_RecordProcess.scr

The following is the syntax for specifying the input fields:

NA

NA

Each eligible NPA Records are processed here which forms the 1st file for the BGNPSAR menu report.

Is called once the BCFG menu BGNPSAR is invoked.

NA

©Copyright Infosys Ltd.

IN_BGNPNSAR_SetRegisterInfo.scr (PSL/NON PSL report)



This script is used to set the repository values needed for BGNPAFR menu

NA

IN_ BGNPNSAR_SetRegisterInfo.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.arg_4

CUSTOM.BATCH.arg_6

CUSTOM.BATCH.arg_7

The following are the details of the input fields for the script:

Input Field	Description
CUSTOM.BATCH.arg_4	To date in criteria
CUSTOM.BATCH.arg_6	Sol Set ID
CUSTOM.BATCH.arg_7	Report format [PDF,XLX, TXT]

All the inputs in the criteria fields of BGNPNSAR menu are accessed in this script and populated in the CUSTOM.BATCH repository.

Is called once the BCFG menu BGNPNSAR is invoked.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_bgpnpsarReadInput.scr (PSL/NON PSL report)



This script is used for handle input fields from DAT file for BGNPNSAR menu

NA

IN_bgpnpsarReadInput.scr

The following is the syntax for specifying the input fields:

NA

NA

Input fields from the DAT file is processed here for the BGNPAFR menu report.

Is called once the BCFG menu BGNPNSAR is invoked.

NA

©Copyright Infosys Ltd.

IN_calcNPAREcoveryForLoan.scr (NPA Recovery report)



This script is called to calculate the outstanding amount in loan accounts

NA

IN_calcNPAREcoveryForLoan.scr

The following is the syntax for specifying the input fields:

NA

NA

This script is called to calculate the outstanding amount in loan accounts.

Is called once the BCFG menu BGNPARR is invoked.

NA

©Copyright Infosys Ltd.

IN_calcNPAREcoveryForOD.scr (NPA Recovery report)



This script is called to calculate the outstanding amount in Non loan accounts

NA

IN_calcNPAREcoveryForOD.scr

The following is the syntax for specifying the input fields:

NA

NA

This script is called to calculate the outstanding amount in Non loan accounts.

Is called once the BCFG menu BGNPARR is invoked.

NA

©Copyright Infosys Ltd.

IN_calculateDPD.scr (DPD Freeze)



This script is called to calculate the DPD value by considering the relief period details.

NA

IN_calculateDPD.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.AcctId

BANCS.INPUT.StartDate

BANCS.INPUT.EndDate

BANCS.INPUT.CurrentDpd

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.AcctId	Account ID for which the DPD value should be calculated.
BANCS.INPUT.StartDate	This start date is the oldest outstanding demand date for the account.
BANCS.INPUT.EndDate	End date is the BOD date.
BANCS.INPUT.CurrentDpd	Original DPD Value.

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.NewDPDValue	Calculated New DPD value by considering the relief period.

This script is called to calculate the DPD value by considering the relief period details.

Is called during HSASCL.

NA

©Copyright Infosys Ltd.

IN_checkAdvEiTransactionReqdForSCHM.scr (Advance EI)

NA

IN_checkAdvEiTransactionReqdForSCHM.scr

NA

NA

The script returns an indicator which indicates whether transactionsaction creation is needed during scheme transactionsfer.

This script is called in India localization, for advance EI transactionsaction creation.

NA

IN_checkAdvEiTransactionReqdForSOL.scr (Advance EI)

NA

IN_checkAdvEiTransactionReqdForSOL.scr

NA

NA

The script returns an indicator which indicates whether transactionsaction creation is needed during Sol transactionsfer.

This script is called in India localization, for advance EI transactionsaction creation.

NA

Finacle Copyright

IN_chkForMatTDAcct.scr - Part closure after maturity - HCAACTD menu

NA

IN_chkForMatTDAcct.scr

The following are the details of the input fields for the script:

Input Field	Description
Account ID	Account ID which needs to be checked, that whether it is matured or not.

The following are the details of the output fields for the script:

Output Field	Description
Maturity Date	Maturity date of the account ID passed as input.
Deposit amount	Initial deposit amount of the account ID passed.

The script returns the maturity date and principal amount of the account ID that is passed.

This script is called in India localization, on load of the criteria page in HCAACTD.

NA

IN_dtlsCapForNC.scr (NonCust - HTM menu)



NA

IN_dtlsCapForNC.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.srl_num	Part transaction Serial Number

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.visited	Checks whether the explode screen has been visited or not.
BANCS.OUTPUT.dtls_cap	Checks whether the details have been recorded or not.

Additional Details Recorded for NonCustomer - Y/N

This script is called in India localization, from different cxx files to check whether additional details have been recorded or not.

NA

IN_fetchAdvanceEIPopup.scr (Advance EI)



NA

IN_fetchAdvanceEIPopup.scr

NA

NA

The file fetches the advance EI details. The fetched details is shown in popup message displayed in the menus

This script is called in India localization, to display the popup messages for advance EI.

NA

©Copyright Infosys Ltd.

IN_fetchNonCustDetails.scr (NonCust - HTM menu)



NA

IN_fetchNonCustDetails.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.transactionconductorId	Conductor ID for which the details are to be fetched.

The following are the details of the output fields for the script:

Output Field	Description
Explode Fields	Sets the Explode values.

This script fetches the details of the non customer and displays on explode.

This script is called in India localization, to fetch non customer details.

NA

IN_fetchNonCustDtIsForCopy.scr (NonCust - HORM)



NA

IN_fetchNonCustDtIsForCopy.scr

None

None

This script computes the value of transaction ID and transaction date from FAE table based upon the remittance Id and then will finally compute the drop down: "Transactions for Non Customer" from transaction ID and transaction date in IN_LDTD table.

This script is called in India localization from script, SRV_FetchORDtIsForCopy_pre_process_data.scr

NA

©Copyright Infosys Ltd.

IN_FITL_WCDL_Accts_Fetch.scr (Linkage of FITL and WCTL accounts to Loan accounts)



This script is used for fetching the FITL and WCTL accounts in HLNGI and HCLNGI menu.

NA

IN_FITL_WCDL_Accts_Fetch.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.acctId

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.acctId	Account ID for which FITL and WCTL accounts should be fetched.

The following are the details of the output fields for the script:

Output Field	Description
LinkedFITLAcctId	Linked FITL A/c. ID
LinkedWCDLAcctId	Linked WCTL A/c. ID

The account ID passes through all the validations and wherever it fails the error is thrown at that point in HLNGI and HCLNGI.

HLNGI and HCLNGI Inquire menu.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_FITL_WCDL_Add.scr (Auto Loans-HLADISB menu)



NA

IN_FITL_WCDL_Add.scr

NA

NA

The script is used to add the margin account details and linked FITL and WCTL accounts during HOAACL.

This script is called when click on submit in HOAACL.

NA

©Copyright Infosys Ltd.

IN_FITL_WCDL_Add.scr (Advance EI)



NA

IN_FITL_WCDL_Add.scr

None

None

This script handles the addition of Advance EI of the parameters of Advance EI at the account level from IN_LAM table.

This script is called in India localization from script:

IN_SRV_OpenLaAcct_process_locale_data.scr

NA

©Copyright Infosys Ltd.

IN_FITL_WCDL_Add.scr (Linkage of FITL and WCTL accounts to Loan accounts)



This script is used for verifying and cancelling the FITL and WCTL accounts in HACMLA and HACMCL menu.

NA

IN_FITL_WCDL_Add.scr

The following is the syntax for specifying the input fields:

acctCommonInfo.acctGeneralInfo.acctBasic.acid

INLOC.DATA.funcCode

The following are the details of the input fields for the script:

Input Field	Description
acctCommonInfo.acctGeneralInfo.acctBasic.acid	Account id for which FITL and WCTL accounts should be fetched.
INLOC.DATA.funcCode	FuncCode is used to set the type of action in proctable.
ONS.LOCIN.linkedFITLAcct	Linked FITL A/c. ID
ONS.LOCIN.linkedWCDLAcct	Linked WCTL A/c ID

The account ID passes through all the validations and wherever it fails the error is thrown at that point in HACMLA and HACMCL and stores the data in IN_LAM table.

HOAACLA and HOAACCL open mode, this script is called on click of

SUBMIT in Details screen.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_FITL_WCDL_Fetch.scr (Linkage of FITL and WCTL accounts to Loan accounts)



This script is used for fetching the FITL and WCTL accounts in HACMLA and HACMCL menu.

NA

IN_FITL_WCDL_Fetch.scr

The following is the syntax for specifying the input fields:

acctCommonInfo.acctGeneralInfo.acctBasic.acid
INLOC.DATA.funcCode

The following are the details of the input fields for the script:

Input Field	Description
acctCommonInfo.acctGeneralInfo.acctBasic.acid	Account id for which FITL and WCTL accounts should be fetched.
INLOC.DATA.funcCode	FuncCode is used to set the type of action in proctable.

The following are the details of the output fields for the script:

Output Field	Description
LinkedFITLAcctId	Linked FITL A/c. ID
LinkedWCDLAcctId	Linked WCTL A/c. ID

The account id passes through all the validations and wherever it fails

the error is thrown at that point in HACMLA and HACMCL.

HACMLA and HACMCL inquire, modify, verify and cancel mode, this script is called on click of GO in criteria screen.

NA

©Copyright Infosys Ltd.

IN_FITL_WCDL_Fetch.scr (Auto Loans-HLADISB menu)



NA

IN_FITL_WCDL_Fetch.scr

NA

NA

The script is used to fetch the margin account details and linked FITL and WCTL

accounts during HOAACMLA, HOAACVLA and HACMLA.

This script is called when click on Go in the criteria page of HOAACMLA, HOAACVLA and

HACMLA.

NA

NA

IN_FITL_WCDL_Fetch.scr

None

None

This script handles the logic for fetch of Advance EI of the parameters of Advance EI at the account level from IN_LAM table.

This script is called in India localization from script:

IN_SRV_FetchLAAcctDtIForMaintCancel_process_locale_data.scr

IN_SRV_FetchLAAcctDtIForMaintVerify_process_locale_data.scr

IN_SRV_FetchLAAcctDtIForModify_process_locale_data.scr

IN_SRV_InquireLAAcct_process_locale_data.scr

NA

IN_FITL_WCDL_Modify.scr (Linkage of FITL and WCTL accounts to Loan accounts)



This script is used for verifying and cancelling the FITL and WCTL accounts in HACMLA and HACMCL menu.

NA

IN_FITL_WCDL_Modify.scr

The following is the syntax for specifying the input fields:

acctCommonInfo.acctGeneralInfo.acctBasic.acid

INLOC.DATA.funcCode

The following are the details of the input fields for the script:

Input Field	Description
acctCommonInfo.acctGeneralInfo.acctBasic.acid	Account id for which FITL and WCTL accounts should be fetched.
INLOC.DATA.funcCode	FuncCode is used to set the type of action in proctable.

The account ID passes through all the validations and wherever it fails the error is thrown at that point in HACMLA and HACMCL and stores the data in IN_LAM table.

HACMLA and HACMCL modify mode, this script is called on click of SUBMIT in Details screen.

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_FITL_WCDL_Modify.scr (Auto Loans- HLADISB menu)



NA

IN_FITL_WCDL_Modify.scr

NA

NA

The script is used to add or modify the margin account details and linked FITL and WCTL accounts during HOAACMLA and HACMLA.

This script is called when click on submit in HOAACMLA and HACMLA.

NA

©Copyright Infosys Ltd.

NA

IN_FITL_WCDL_Modify.scr

None

None

This script handles the modification of Advance EI of the parameters of Advance EI at the account level from IN_LAM table

This script is called in India localization from script:

IN_SRV_ModifyLAAcct_process_locale_data.scr

NA

IN_FITL_WCDL_VXDUMode.scr (Linkage of FITL and WCTL accounts to Loan accounts)



This script is used for verifying and cancelling the FITL and WCTL accounts in HACMLA and HACMCL menu.

NA

IN_FITL_WCDL_VXDUMode.scr

The following is the syntax for specifying the input fields:

acctCommonInfo.acctGeneralInfo.acctBasic.acid

INLOC.DATA.funcCode

The following are the details of the input fields for the script:

Input Field	Description
acctCommonInfo.acctGeneralInfo.acctBasic.acid	Account ID for which FITL and WCTL accounts should be fetched.
INLOC.DATA.funcCode	FuncCode is used to set the type of action in proctable.
ONS.LOCIN.linkedFITLAcct	Linked FITL A/c. ID
ONS.LOCIN.linkedWCDLAcct	Linked WCTL A/c ID

The account ID passes through all the validations and wherever it fails the error is thrown at that point in HACMLA and HACMCL and stores the data in IN_LAM table

HACMLA and HACMCLverify and cancel mode, this script is called on click of SUBMIT in Details screen.

NA

©Copyright Infosys Ltd.

IN_getAdvEiDetailsForSolXFER.scr (Advance EI)



NA

IN_getAdvEiDetailsForSolXFER.scr

NA

NA

The script fetches advance EI details and sets the variables that are required for transactionsaction creation.

This script is called in India localization, for advance EI transactionsaction creation.

NA

©Copyright Infosys Ltd.

IN_getAdvEiDetailsForClosure.scr (Advance EI)



NA

IN_getAdvEiDetailsForClosure.scr

NA

NA

The script fetches advance EI details required during account closure.

This script is called in India localization, for account closure.

NA

©Copyright Infosys Ltd.

IN_getAdvEiDetailsForSchmXFER.scr (Advance EI)

NA

IN_getAdvEiDetailsForSchmXFER.scr

NA

NA

The script fetches advance EI details and sets the variables that are required for transactionsaction creation.

This script is called in India localization, for advance EI transactionsaction creation.

NA

IN_getAdvEiDetails.scr (Advance EI)



NA

IN_getAdvEiDetails.scr

NA

NA

The script contains logic for fetching the advance EI details. The fetched details is shown in the reports of Batch menus

This script is called in India localization, to display the advance EI details in Batch reports.

NA

©Copyright Infosys Ltd.

IN_getConductorIdForCopy.scr (NonCust - HTM menu)



NA

IN_getConductorIdForCopy.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.transactionId	Transaction ID
BANCS.INPUT.transactionDate	Transaction Date
BANCS.INPUT.srlNum	Part transaction serial number

The following are the details of the output fields for the script:

Output Field	Description
Conductor ID	Conductor ID for the part transaction.

The Value of: Transactionsaction Conductor ID.

This script is called in India localization in copy mode to fetch the conductor Id for each part transaction.

NA

IN_getNonCustIndForMod.scr (NonCust)

NA

IN_getNonCustIndForMod.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.transactionId	Transaction Id
BANCS.INPUT.transactionDate	Transaction Date
BANCS.INPUT.partTransactionSrlNum	Part Transaction Serial number.

The following are the details of the output fields for the script:

Output Field	Description
IND.LOC.non_cust_ind	Non Cust Indicator for modes other than Add.

This script computes the value of the drop down: "Transactionsaction for Non Customer" from the values in IN_LDTD.

This script is called in India localization, from HTM/HCASHDEP/HDDMI/HDDXMI/HORM link files

NA

IN_GetMarginDetails.scr (Auto Loans- HLADISB menu)



NA

IN_GetMarginDetails.scr

NA

NA

The script used to fetch the margin details for auto loans.

This script is called in India localization to fetch the margin details like product type, margin

Money amount, margin money accounting flag and so on.

NA

©Copyright Infosys Ltd.

IN_getNonCustDtIsForCopy.scr (NonCust - HORM)



NA

IN_getNonCustDtIsForCopy.scr

The following are the details of the input fields for the script:

Input Field	Description
IND.LOC.non_cust_ind	Transactionsaction For Non-Customer Indicator from the IND.LOC repository.
IND.LOC.cond_id	Conductor ID from IND.LOC repository.

The following are the details of the output fields for the script:

Output Field	Description
nonCustInd	Value of : Transactionsaction for Non Customer
conductorId	Value of : Transactionsaction Conductor Id

This script gets the value of the drop down: "Transactionsaction for Non Customer" and "Conductor ID" from the Repository.

This script is called in India localization HORM Event Details tab.

NA

IN_getNonCustInd.scr (NonCust)



NA

IN_getNonCustInd.scr

The following are the details of the input fields for the script:

Input Field	Description
ONS.LOCIN.nonCustTransactionInd	Transactionsaction For Non-Customer Indicator from ONS.LOCIN repository.

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.non_Cust_Ind	Value of : Transactionsaction for Non Customer

This script gets the value of the drop down: "Transactionsaction for Non Customer" from the Repository.

This script is called in India localization from HTM/HCASHDEP/HDDMI/HDDXMI/HORM locale SRVs.

NA

IN_getNonCustIndForORM.scr (NonCust - HORM menu)



NA

IN_getNonCustIndForORM.scr

The following are the details of the input fields for the script:

Input Field	Description
IND.LOC.non_cust_ind	Transactionsaction For Non-Customer Indicator from the IND.LOC repository.

The following are the details of the output fields for the script:

Output Field	Description
nonCustInd	Value of : Transactionsaction for Non Customer

This script gets the value of the drop down: "Transactionsaction for Non Customer" from the Repository.

This script is called in India localization from HORM Event Details page.

NA

IN_GetRefAmtForAutoLoans.scr (Auto Loans- HLADISB menu)



NA

IN_GetRefAmtForAutoLoans.scr

NA

NA

The script is used to add the margin money amount to the credit amount to balance the part

Transactionsaction.

This script is called when click on Accept in details page and click on submit in final

Page of HLADISB.

NA

©Copyright Infosys Ltd.

IN_getSchmType.scr (NonCust - HTM menu)



NA

IN_getSchmType.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.foracid	Foracid for which scheme is to be determined.

The following are the details of the output fields for the script:

Output Field	Description
IND.LOC.schm_type	Scheme Type for the foracid passed.

This script gets the scheme type for the account ID.

This script is called in India localization, and is called from link files of HTM/HCASHDEP.

NA

IN_GetSchmType.scr (NEFT and RTGS)



This script fetches the scheme type of an account.

NA

IN_GetSchmType.scr

BANCS.INPUT.laAcct

BANCS.OUTPUT.schm_type

This script fetches the scheme type of an account.

Is called to get the scheme type of an account at multiple places.

NA

©Copyright Infosys Ltd.

IN_GetTransactionDtlsFromIN_LAM.scr (Auto Loans- HLADISB menu)



NA

IN_GetTransactionDtlsFromIN_LAM.scr

NA

NA

The script is used to get the transactionsaction details from IN_LAM for part transactionsaction creation.

This script getting called when click on Accept in details page and click on submit in final

Page of HLADISB only in disbursement mode.

NA

©Copyright Infosys Ltd.

IN_HTM_AddNonCustData.scr (NonCust - HTM menu)



NA

IN_HTM_AddNonCustData.scr

The following are the details of the input fields for the script:

Input Field	Description
INTMNC.NONCUS	INTMNC.NONCUS repository which has all values which needs to be inserted in Database.

The following are the details of the output fields for the script:

Output Field	Description
SuccessOrFailure	Success or Failure.

This script adds the record into the DB.

Called from IN_HTM_Main_ProcessNonCustData.scr

NA

©Copyright Infosys Ltd.

IN_HTM_fetchNonCustData.scr (NonCust - HTM menu)



NA

IN_HTM_fetchNonCustData.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.fetchCode	Fetch Code passed.

The following are the details of the output fields for the script:

Output Field	Description
SuccessOrFailure	Success or Failure.

This script is used to fetch Non Customer details.

This script is called in India localization, from all Fetch sRVs.

NA

IN_HTM_Main_ProcessNonCustData.scr (NonCust - HTM menu)



NA

IN_HTM_Main_ProcessNonCustData.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.funcCode	Function code passed through HTM.
BANCS.INPUT.postTransaction	Post the transactionsaction Yes or No.
BANCS.INPUT.mainCode	Main Code for the database.

The following are the details of the output fields for the script:

Output Field	Description
SuccessOrFailure	Success or Failure

This script sets the Repositories and calls the scripts for further processing based on function codes.

This script is called in India localization, in all SRVs
post_process_data.scr

NA

IN_HTM_ModifyNonCustData.scr (NonCust - HTM menu)



NA

IN_HTM_ModifyNonCustData.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.mainCode	Fetch code used for Proc table.

The following are the details of the output fields for the script:

Output Field	Description
SuccessOrFailure	Success or failure

This script modifies the data in IN_COND

This script is called in India localization, and modifies the data in database.

NA

IN_HTM_ValNonCustData.scr (NonCust - HTM menu)



NA

IN_HTM_ValNonCustData.scr

The following are the details of the input fields for the script:

Input Field	Description
INTMNC.NONCUS	INTMNC.NONCUS repository which has all values which needs to be validated.

The following are the details of the output fields for the script:

Output Field	Description
SuccessOrFailure	Success or Failure

This script validates the data recorded through Explode.

This script is called in India localization, for validating non cust details.

NA

IN_InsertReliefDetailsForCrtstalizedAcct.scr (DPD Freeze)

This script is called to copy the relief period details from parent account to child account Reference

NA

IN_IRAC_AcctStatus.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.acctransactionk

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.acctransactionk	The rank of the account for which status is derived based on set up in MLPS menu.

BANCS.OUTPUT.acctStatus

Rank of the account such as STANDARD or SUB STANDARD or LOSS.

This script is called to derive the status of the account based on the system classification of account

Is called during HASPROV/HSASCL for IRAC provisioning.

NA

IN_IRAC_NPA_limitCollAmt.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.AcctId

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.AcctId	Account ID for which provisioning is processed.

BANCS.OUTPUT.limitCrncy

BANCS.OUTPUT.LiabValue

Limit currency and total limit amount value applicable as security for account.

The script is used to calculate Limit based collateral value for Account.

Is called during HASPROV/HSASCL for IRAC provisioning.

NA

IN_IRAC_SUBSTANDARD_CHECK.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.principalOutstanding

BANCS.INPUT.effDepositSec

BANCS.INPUT.effSecuProvPcnt

BANCS.INPUT.effUnsecProvPcnt

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.principalOutstanding	Principal outstanding amount of account for which provisioning is processed.
BANCS.INPUT.effDepositSec	Net collaterals attached with account.
BANCS.INPUT.effSecuProvPcnt	Secured provision percent maintained in HAPPM menu.
BANCS.INPUT.effUnsecProvPcnt	Unsecured provision percent maintained in HAPPM menu.

BANCS.OUTPUT.secudPcnt

BANCS.OUTPUT.unSecudPcnt

The script is used to check if the collateral is less than 10% of total principal outstanding then secured and unsecured provision percent is increased by 10%.

Is called during HASPROV/HSASCL for IRAC NPA provisioning.

NA

IN_IRAC_prinOS_OP.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.AcctId

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.AcctId	ODA account which is getting processed for IRAC provisioning.

BANCS.OUTPUT.prinAmtValue

The script is used calculate clear balance for ODA account considering normal booked interest and interest in suspense account.

Is called during HASPROV/HSASCL for IRAC NPA provisioning.

NA

IN_UAPD_SetRegisterInfo.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.report_to

CUSTOM.BATCH.sol_set_id

The following are the details of the input fields for the script:

Input Field	Description
CUSTOM.BATCH.report_to	Report to field on frontend screen in UAPD menu
CUSTOM.BATCH.sol_set_id	SOL set field on frontend screen in UAPD menu

CUSTOM.BATCH.schm_code	Scheme code on frontend screen in UAPD menu
CUSTOM.BATCH.crncy_code	Currency code on frontend screen in UAPD menu
CUSTOM.BATCH.acct_from	From Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.acct_to	To Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.trial_mode	Trial mode as Yes or No on UAPD menu.
CUSTOM.BATCH.inp_file_name	Input file name on screen of UAPD menu
CUSTOM.BATCH.prvsn_amt	Provision amount on screen of UAPD menu

NA

The SetRegisterInfo script should be used to set the register (meta-data, enable/disabling driver provided features) info the custom batch job.

UAPD custom batch job menu for Provisioning.

NA

IN_UAPD_RecordProcess.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.report_to

CUSTOM.BATCH.sol_set_id

The following are the details of the input fields for the script:

Input Field	Description
CUSTOM.BATCH.report_to	Report to field on frontend screen in UAPD menu

CUSTOM.BATCH.sol_set_id	Sol set field on frontend screen in UAPD menu
CUSTOM.BATCH.schm_code	Scheme code on frontend screen in UAPD menu
CUSTOM.BATCH.crncy_code	Currency code on frontend screen in UAPD menu
CUSTOM.BATCH.acct_from	From Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.acct_to	To Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.trial_mode	Trial mode as Yes or No on UAPD menu.
CUSTOM.BATCH.inp_file_name	Input file name on screen of UAPD menu
CUSTOM.BATCH.prvsn_amt	Provision amount on screen of UAPD menu

NA

For processing of selected records for the custom batch job.

UAPD custom batch job menu for Provisioning.

NA

IN_UAPD_ListGet.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.report_to

CUSTOM.BATCH.sol_set_id

The following are the details of the input fields for the script:

Input Field	Description
CUSTOM.BATCH.report_to	Report to field on frontend screen in UAPD menu

CUSTOM.BATCH.sol_set_id	Sol set field on frontend screen in UAPD menu
CUSTOM.BATCH.schm_code	Scheme code on frontend screen in UAPD menu
CUSTOM.BATCH.crncy_code	Currency code on frontend screen in UAPD menu
CUSTOM.BATCH.acct_from	From Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.acct_to	To Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.trial_mode	Trial mode as Yes or No on UAPD menu.
CUSTOM.BATCH.inp_file_name	Input file name on screen of UAPD menu
CUSTOM.BATCH.prvsn_amt	Provision amount on screen of UAPD menu

NA

For processing of selected records for the custom batch job.

UAPD custom batch job menu for Provisioning.

NA

IN_uapdReadInput.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.report_to

CUSTOM.BATCH.sol_set_id

The following are the details of the input fields for the script:

Input Field	Description
CUSTOM.BATCH.report_to	Report to field on frontend screen in UAPD menu
CUSTOM.BATCH.sol_set_id	Sol set field on frontend screen in UAPD menu

CUSTOM.BATCH.schm_code	Scheme code on frontend screen in UAPD menu
CUSTOM.BATCH.crncy_code	Currency code on frontend screen in UAPD menu
CUSTOM.BATCH.acct_from	From Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.acct_to	To Account ID field on frontend screen in UAPD menu
CUSTOM.BATCH.trial_mode	Trial mode as Yes or No on UAPD menu.
CUSTOM.BATCH.inp_file_name	Input file name on screen of UAPD menu
CUSTOM.BATCH.prvsn_amt	Provision amount on screen of UAPD menu

NA

For processing of selected records for the custom batch job.

UAPD custom batch job menu for Provisioning.

NA

IN_getPrincipalOSAmt.scr

The following is the syntax for specifying the input fields:

CUSTOM.BATCH.schm_type

CUSTOM.BATCH.acid

The following are the details of the input fields for the script:

Field Name	Description
CUSTOM.BATCH.schm_type	Scheme type of account getting processed for provisioning in UAPD menu
CUSTOM.BATCH.acid	account getting processed for provisioning in UAPD

INREP.IRAC.serialNum
INREP.IRAC.adHocProvisionedAmt
INREP.IRAC.netNPV
INREP.IRAC.netColl
INREP.IRAC.iasProvisionedAmt
INREP.IRAC.disclasProvisionedAmt
INREP.IRAC.provisionedAmt

For processing of selected records for the custom batch job.

UAPD custom batch job menu for Provisioning.

NA

IN_UAPD_PostProcessing.scr

The following is the syntax for specifying the input fields:

INREP.IRAC.successLst
INREP.IRAC.failureLst

The following are the details of the input fields for the script:

Input Field	Description
INREP.IRAC.successLst	Success LST file to process report.

INREP.IRAC.failureLst	Failure LST file to process report.
-----------------------	-------------------------------------

NA

For report processing of selected records for the custom batch job.

UAPD custom batch job menu for Provisioning.

NA

IN_CheckKCCRtransaction_HCRT.scr

The following is the syntax for specifying the input fields:

USREP.KCCR.transactionId

USREP.KCCR.transactionDate

The following are the details of the input fields for the script:

Input Field	Description
USREP.KCCR.transactionId	Transaction ID for reversal or marked to be a reversed.
USREP.KCCR.transactionDate	Transaction Date of Transaction ID.

NA

For checking if the transactionsaction ID is for a kisan credit card account.

HCRT Reversal of transactionsaction of KCC (ODA) account.

NA

IN_HCRT_Locale_process_LDTD.scr

The following is the syntax for specifying the input fields:

INTMREP.KCCT.transactionDate

INTMREP.KCCT.transactionId

INTMREP.KCCT.partTransactionSrlNum

The following are the details of the input fields for the script:

Input Field	Description
INTMREP.KCCT.transactionId	Transaction ID for reversal or marked to be a reversed.
INTMREP.KCCT.transactionDate	Transaction Date of Transaction Id.

NA

For process and marking KCC transaction ID as Reversed in IN_LDTD table.

HCRT Reversal of transactionsaction of KCC (ODA) account.

NA

IN_HCRT_update_IN_LDTD_MarkRev.scr

The following is the syntax for specifying the input fields:

INTMREP.KCCT.foracid

INTMREP.KCCT.acid

INTMREP.KCCT.transactionDate

INTMREP.KCCT.transactionId

INTMREP.KCCT.partTransactionSrlNum

The following are the details of the input fields for the script:

Input Field	Description
INTMREP.KCCT.transactionId	Transaction ID for reversal or marked to be a reversed.
INTMREP.KCCT.transactionDate	Transaction Date of Transaction ID.

NA

For process and marking KCC transaction ID as Reversed in IN_LDSTD table.

HCRT Reversal of transactionsaction of KCC (ODA) account.

NA

SRV_MarkRevTransaction_post_process_data.scr

The following is the syntax for specifying the input fields:

INTMREP.KCCT.foracid

INTMREP.KCCT.acid

INTMREP.KCCT.transactionDate

INTMREP.KCCT.transactionId

INTMREP.KCCT.partTransactionSrlNum

The following are the details of the input fields for the script:

Input Field	Description
INTMREP.KCCT.transactionId	Transaction ID for reversal or marked to be a reversed.
INTMREP.KCCT.transactionDate	Transaction Date of Transaction ID.

NA

For process and marking KCC transaction id as Reversed in IN_LD TD table.

HCRT Reversal of transactionsaction of KCC (ODA) account.

NA

SRV_RevTransaction_post_process_data.scr

The following is the syntax for specifying the input fields:

INTMREP.KCCT.foracid

INTMREP.KCCT.acid

INTMREP.KCCT.transactionDate

INTMREP.KCCT.transactionId

INTMREP.KCCT.partTransactionSrINum

The following are the details of the input fields for the script:

Input Field	Description
INTMREP.KCCT.transactionId	Transaction ID for reversal or marked to be a reversed.
INTMREP.KCCT.transactionDate	Transaction Date of Transaction Id.

NA

For process and marking KCC transaction ID as Reversed in IN_LDSTD table.

HCRT Reversal of transactionsaction of KCC (ODA) account.

NA

SRV_FetchDataForTransactionRev_validate_data.scr

The following is the syntax for specifying the input fields:

USREP.KCCR.transactionId

USREP.KCCR.transactionDate

The following are the details of the input fields for the script:

Input Field	Description
USREP.KCCR.transactionId	Transaction ID for reversal or marked to be a reversed.
USREP.KCCR.transactionDate	Transaction Date of Transaction ID.

For process and marking KCC transactionsaction ID as Reversed in IN_LDSTD table.

Validation for HCRT Reversal of transactionsaction of KCC (ODA) account.

NA

IN_processKCCForHRSI.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.AcctId

USREP.KCCR.transactionDate

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.AcctId	Account ID on HRSI criteria page.
BANCS.INPUT.lastDate	Int recognized till date of account or date in which account was marked as past due.

NA

For process of KCC ODA account where only KCC Other type of transactionsactions is recognized as income.

HRSI menu processing for KCC ODA accounts.

NA

IN_getAddtlPeriodForCIF.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.acctId

BANCS.INPUT.custId

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.acctId	Account ID for Subvention.
BANCS.INPUT.custId	Customer ID of the KCC account.

Additional Period applicable for customer for subvention.

BANCS.OUTPUT.period

For Subvention processing of KCC account.

BGSNR menu processing for KCC ODA accounts subvention processing.

NA

IN_getAddtlPeriodForCIF.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.acctId

BANCS.INPUT.custId

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.acctId	Account ID for Subvention.
BANCS.INPUT.custId	Customer ID of the KCC account.

Additional Period applicable for customer for subvention.

BANCS.OUTPUT.period

For Subvention processing of KCC account.

BGSNR menu processing for KCC ODA accounts subvention processing.

NA

IN_getNoOfKCCAccounts.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.cifId

BANCS.INPUT.toDate

BANCS.INPUT.prodConcept

BANCS.INPUT.prodGroup

BANCS.INPUT.schmCode

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.cifId	CIF ID of Account ID for Subvention.
BANCS.INPUT.toDate	Date on criteria page of BGSNR menu.

NA

For Subvention processing of KCC account in BGSNR menu.

BGSNR menu processing for KCC ODA accounts subvention processing.

NA

©Copyright Infosys Ltd.

IN_InsertReliefDetailsForCrtstalizedAcct.scr (DPD Freeze)

This script is called to copy the relief period details from parent account to child account Reference

NA

IN_InsertReliefDetailsForCrtstalizedAcct.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.ParentAcct

BANCS.INPUT.ChildAcct

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.ParentAcct	The account from which we need to copy the relief period details.
BANCS.INPUT.ChildAcct	The account to which we need to copy the relief period details...

NA

This script is called to copy the relief period details from parent account to child account.

Is called during crystallization (HCRY).

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_isAcctUnderReliefEligibleForPercolation.scr (DPD Freeze)

This script is called to check whether the account is eligible for percolation or not.

NA

IN_isAcctUnderReliefEligibleForPercolation.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.AcctId

BANCS.INPUT.BodDate

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.AcctId	Account ID for which the DPD value should be calculated.
BANCS.INPUT.BodDate	Passing the BOD date as the input.

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.PercFlg	This flag indicates whether the account is eligible for percolation or not. Valid values are 'F' or 'S'

This script is called to check whether the account is eligible for

percolation or not.

Is called during HSASCL.

NA

©Copyright Infosys Ltd.

IN_LAGSPM_Add.scr (Advance EI)



NA

IN_LAGSPM_Add.scr

None

None

This script inserts the scheme level parameters of Advance EI values into IN_LLSP table.

This script is called in India localization from script IN_SRV_AddLoanAcctSchmParams_process_locale_data.scr

NA

©Copyright Infosys Ltd.

NA

IN_LAGSPM_Fetch.scr

None

None

This script fetches the scheme level parameters of Advance EI values entered in the IN_LLSP table for different modes.

This script is called in India localization from script:

J_SRV_FetchLoanAcctSchmParamsForCancel_process_locale_data.s

J_SRV_FetchLoanAcctSchmParamsForCopy_process_locale_data.scr

J_SRV_FetchLoanAcctSchmParamsForDelete_process_locale_data.sc

J_SRV_FetchLoanAcctSchmParamsForModify_process_locale_data.s

J_SRV_FetchLoanAcctSchmParamsForUndelete_process_locale_data

J_SRV_FetchLoanAcctSchmParamsForVerify_process_locale_data.sc

IN_SRV_InquireLoanAcctSchmParams_process_locale_data.scr

NA

©Copyright Infosys Ltd.

IN_LAGSPM_Modify.scr (Advance EI)



NA

IN_LAGSPM_Modify.scr

None

None

This script modifies the scheme level parameters of Advance EI values entered in the IN_LLSP table.

This script is called in India localization from script IN_SRV_ModifyLoanAcctSchmParams_process_locale_data.scr

NA

©Copyright Infosys Ltd.

NA

IN_LAGSPM_VXDUMode.scr

None

None

This script handles the verify, cancel, delete, undelete operations of the scheme level parameters of Advance EI values entered in the IN_LLSP table.

This script is called in India localization from script:

IN_SRV_CancelLoanAcctSchmParams_process_locale_data.scr

IN_SRV_DeleteLoanAcctSchmParams_process_locale_data.scr

IN_SRV_UndeleteLoanAcctSchmParams_process_locale_data.scr

IN_SRV_VerifyLoanAcctSchmParams_process_locale_data.scr

NA

IN_LAGSPMLLSPFetch.scr (Advance EI)



NA

IN_LAGSPMLLSPFetch.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.in_schmCode	The scheme code name that is entered at the scheme level
BANCS.INPUT.in_crncyCode	The corresponding currency of the scheme code

The following are the details of the output fields for the script:

Output Field	Description
BANCS.OUTPUT.count	The number of records present in the ADT table for the scheme
BANCS.OUTPUT.advanceEIPH	The advance EI place holder for the corresponding scheme and currency.

This script gets the value of count from the ADT table and the corresponding advance EI placeholder for the IN_LLSP table

This script is called in India localization from HLAGSPM.

NA

IN_LAGSPMVal.scr (Advance EI)



NA

IN_LAGSPMVal.scr

None

None

This script handles the validations of Advance EI of the parameters of Advance EI at the scheme level

This script is called in India localization from script:

IN_SRV_AddLoanAcctSchmParams_post_process_data.scr

IN_SRV_ModifyLoanAcctSchmParams_post_process_data.scr

NA

©Copyright Infosys Ltd.

IN_LAGSPMValidate.scr (Auto Loans- HLADISB menu)



NA

IN_LAGSPMValidate.scr

NA

NA

The script is used validate whether the scheme modification is verified or not. Based on that the locale fields are disabled.

This script is called in the page on load of scheme details page in HLADISB.

NA

©Copyright Infosys Ltd.

IN_LAMFetchMarginDetails.scr (Auto Loans- HLADISB menu)



NA

IN_LAMFetchMarginDetails.scr

NA

NA

The script is used to fetch the margin account details for auto loans.
Transactionsaction.

This script is called when page on load of loan details tab in
HOAACLA, HOAACMLA,
HACMLA.

NA

©Copyright Infosys Ltd.

IN_LAMValidateData.scr (Auto Loans-HLADISB menu)



NA

IN_LAMValidateData.scr

NA

NA

The script is used to validate the locale fields which are added newly in loan details tab in

HOAACL, HOAACML, HACML.

This script is called when click on submit in HOAACL, HOAACML, HACML

NA

©Copyright Infosys Ltd.

IN_laupld_add.scr (Auto Loans- HLADISB menu)



NA

IN_laupld_add.scr

NA

NA

The script is used to insert the margin account details and linked FITL and WCTL

accounts in IN_LAM table in HLAUPLD.

This script is called when click on submit for master details upload.

NA

©Copyright Infosys Ltd.

IN_laupld_add.scr (Advance EI)



NA

IN_laupld_add.scr

None

None

This script handles the addition of Advance EI of the parameters of Advance EI at the upload level

This script is called in India localization from source IN_laau9500.cxx

NA

©Copyright Infosys Ltd.

IN_laupld_add.scr (Linkage of FITL and WCTL accounts to Loan accounts)



This script is used for add the FITL and WCTL accounts in HLAUPLD menu.

NA

IN_laupld_add.scr Input

The following is the syntax for specifying the input fields:

BANCS.INPUT.acid

BANCS.INPUT.LinkedFITLAcct

BANCS.INPUT.LinkedWCDLAcct

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.acid	Account ID for which FITL and WCTL accounts should be fetched.
BANCS.INPUT.LinkedFITLAcct	Linked FITL A/c. ID
BANCS.INPUT.LinkedWCDLAcct	Linked WCTL A/c ID
BANCS.INPUT.refNo	
BANCS.INPUT.transactionid	
BANCS.INPUT.transactiondate	
BANCS.INPUT.partTransactionSrIno	

The following are the details of the output fields for the script:

Output Field	Description
--------------	-------------

BANCS.OUTPUT.successOrFailure	Valid values : S of F
BANCS.OUTPUT.errorMessage	Error message is occurred.

The account ID passes through all the validations and wherever it fails the error is thrown at that point in HLAUPLD and stores the data in IN_LAM table.

HLAUPLD open mode, this script is called on click of SUBMIT in Details screen.

NA

©Copyright Infosys Ltd.

IN_LoanAcctValidate.scr (NEFT and RTGS)



This script performs loan account validations for NEFT and RTGS transactions.

NA

IN_LoanAcctValidate.scr

BANCS.INPUT.laAcct

NA

This script performs loan account validations for NEFT and RTGS transactions.

Is called to validate loan account while performing NEFT and RTGS transactions.

NA

©Copyright Infosys Ltd.

IN_MarginPartTransactionForAutoLoans.scr (Auto Loans- HLADISB menu)

NA

IN_MarginPartTransactionForAutoLoans.scr

NA

NA

The script is used to create the margin part transactionsaction if margin money amount is there.

This script is getting called when click on Accept in details page and click on submit in final

Page in HLADISB.

Sample

NA

IN_modifyPODetails.scr (UTR and DD No)



This script modifies locale data for the menu HPORDM

NA

NA

NA

This script modifies locale data for the menu HPORDM

Post process script that is called during modification

NA

©Copyright Infosys Ltd.

IN_panprOutstandingAmtForLoanAcct.scr (PSL/NON PSL report)

This script is called from the record process script file for calculating outstanding amount for loan accounts in the BGNPNSAR menu

NA

IN_panprOutstandingAmtForLoanAcct.scr

The following is the syntax for specifying the input fields:

NA

NA

This script calculates the outstanding amount for the loan accounts and returns the value.

Is called once the BCFG menu BGNPNSAR is invoked.

NA

©Copyright Infosys Ltd.

IN_postXferTransactionForAdvEI.scr (Advance EI)



NA

IN_postXferTransactionForAdvEI.scr

NA

NA

The script contains the logic for creating the transactionsaction during SOL/Scheme transactionsfer.

This script is called in India localization, for advance EI transactionsaction creation.

NA

©Copyright Infosys Ltd.

IN_RELIEFReadInput.scr (DPD Freeze)



This script is called to read the details from flat file.

NA

IN_RELIEFReadInput.scr

NA

NA

This script is called to read the details from flat file.

Is called during the upload menu URPDA.

NA

©Copyright Infosys Ltd.

IN_reposUpdForPost.scr (NonCust - HTM menu)



NA

IN_reposUpdForPost.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.srl_num	Part transaction serial Number
BANCS.INPUT.fin_amt	Final Amount that has to be updated in IN_COND for the conductor.
BANCS.INPUT.fin_date	Final Date that has to be updated in IN_COND for the conductor.
BANCS.INPUT.fin_ccy	Final CCY that has to be updated in IN_COND for the conductor.
BANCS.INPUT.cond_id	Conductor Id for which the details has to be updated.

The following are the details of the output fields for the script:

Output Field	Description
successOrFailure	Success or Failure

This script sets the value of transaction date, transaction amount and transaction CCY in repository for Post mode.

This script is called in India localization, from IN_ftnap065.cxx

NA

©Copyright Infosys Ltd.

Finacle Copyright

IN_setNonCustInd.scr (NonCust - HTM menu)



NA

IN_setNonCustInd.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.transactionForNonCust	This sets the value of drop down into the repository.

The following are the details of the output fields for the script:

Output Field	Description
IND.LOC.transactionForNC	Non Cust Indicator is set in Repository.

This script sets the value of the drop down: "Transactionsaction for Non Customer" into the Repository.

This script is called in India localization, from Link files.

NA

IN_setNonCustIndForORM.scr (NonCust - HORM menu)



NA

IN_setNonCustIndForORM.scr

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.nonCustTransactionInd	Transactionsaction For Non-Customer Indicator given on Event details page of HORM.

None.

This script sets the value of the drop down: "Transactionsaction for Non Customer" into the Repository.

This script is called in India localization from HORM Event Details page.

NA

IN_SRV_AddLoanAcctSchmParams_post_process (Advance EI)

NA

IN_SRV_AddLoanAcctSchmParams_post_process_data.scr

NA

NA

The script internally calls IN_LAGSPMVal.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

IN_SRV_AddLoanAcctSchmParams_post_process (Auto Loans- HLADISB menu)

NA

IN_SRV_AddLoanAcctSchmParams_post_process_data.scr

NA

NA

The script is used to call the locale script validateAutoLoans.scr during HLAGSPM.

This script is called when click on submit in HLAGSPM in add mode.

NA

IN_SRV_AddPymtOrderMaintDtls_process_locale_ (UTR and DD No)

This script adds locale data for the menu HPORDM

NA

NA

NA

This script adds locale data for the menu HPORDM

Post process script that is called during addition

NA

©Copyright Infosys Ltd.

IN_SRV_CancelCLAcct_process_locale_data.scr (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls INFITL_WCDL_VXDUMode.scr

NA

IN_SRV_CancelCLAcct_process_locale_data.scr,

NA

NA

NA

This script is called for process function in Cancel mode of HACMCL.

NA

IN_SRV_CancelLAAcct_process_locale_data.scr (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls INFITL_WCDL_VXDUMode.scr

NA

IN_SRV_CancelLAAcct_process_locale_data.scr

NA

NA

NA

This script is called for process function in Cancel mode of HACMLA.

NA

IN_SRV_DeletePymtOrderMaintDtls_process_local (UTR and DD No)

This script deletes locale data for the menu HPORDM

NA

NA

NA

This script deletes locale data for the menu HPORDM

Post process script that is called during deletion

NA

©Copyright Infosys Ltd.

IN_SRV_DisbLoanAcct_pre_process_data.scr (Advance EI)

NA

IN_SRV_DisbLoanAcct_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_DisbLoanAcct_pre_process_data.scr (Auto Loans- HLADISB menu)

NA

IN_SRV_DisbLoanAcct_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization, on click on Accept in disbursement details page.

NA

IN_SRV_DisbursedTransactionFetch_pre_process_ - Auto Loans- HLADISB menu

NA

IN_SRV_DisbursedTransactionFetch_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization, on click on Accept in disbursement details page.

NA

IN_SRV_DisbursedTransactionFetchForRvsl_pre_pi - Auto Loans- HLADISB menu

NA

IN_SRV_DisbursedTransactionFetchForRvsl_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization in fetch of disbursement reversal.

NA

IN_SRV_DisbursedTransactionFetch_pre_process_ (Advance EI)

NA

IN_SRV_DisbursedTransactionFetch_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_DisbursedTransactionFetchForRvsl_pre_pi (Advance EI)

NA

IN_SRV_DisbursedTransactionFetchForRvsl_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchCLAcctDtIForMaintCancel_process_ (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_FetchCLAcctDtIForMaintCancel_process_locale_data.scr

NA

NA

NA

This script is called for process function in Cancel mode HACMCL.

NA

IN_SRV_FetchCLAcctDtIForMaintVerify_process_I (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_FetchCLAcctDtIForMaintVerify_process_locale_data.scr,

NA

NA

NA

This script is called for process function in verify mode of HACMCL.

NA

IN_SRV_FetchCLAcctDtIForModify_process_locale (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_FetchCLAcctDtIForModify_process_locale_data.scr,

NA

NA

NA

This script is called for process function modify mode of HACMCL.

NA

IN_SRV_FetchLAAcctDtIForMaintCancel_process_ (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_FetchLAAcctDtIForMaintCancel_process_locale_data.scr

NA

NA

NA

This script is called for process function in Cancel of HACMCL.

NA

IN_SRV_FetchLAAcctDtIForMaintVerify_process_I (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_FetchLAAcctDtIForMaintVerify_process_locale_data.scr

NA

NA

NA

This script is called for process function in verify of HACMLA.

NA

IN_SRV_FetchLAAcctDtIForModify_process_locale (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_FetchLAAcctDtIForModify_process_locale_data.scr

NA

NA

NA

This script is called for process function in modify mode of HACMLA.

NA

IN_SRV_FetchLADisbData_pre_process_data.scr - Auto Loans- HLADISB menu

NA

IN_SRV_FetchLADisbData_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization, on click on Go in criteria page.

NA

IN_SRV_FetchLADisbDataForRvsl_pre_process_data (Auto Loans- HLADISB menu)

NA

IN_SRV_FetchLADisbDataForRvsl_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization in fetch of disbursement reversal.

NA

IN_SRV_FetchLADisbDataForVfy_pre_process_data - Auto Loans- HLADISB menu

NA

IN_SRV_FetchLADisbDataForVfy_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization in verification of disbursement.

NA

IN_SRV_FetchLADisbDataForXcl_pre_process_data (Auto Loans- HLADISB menu)

NA

IN_SRV_FetchLADisbDataForXcl_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization in fetch of disbursement for cancel mode.

NA

IN_SRV_FetchLADisbData_pre_process_data.scr (Advance EI)

NA

IN_SRV_FetchLADisbData_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchLADisbDataForRvsl_pre_process_data (Advance EI)

NA

IN_SRV_FetchLADisbDataForRvsl_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchLADisbDataForVfy_pre_process_data (Advance EI)

NA

IN_SRV_FetchLADisbDataForVfy_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchLADisbDataForXcl_pre_process_data (Advance EI)

NA

IN_SRV_FetchLADisbDataForXcl_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchLaGenDetails_process_locale_data.scr (Advance EI)

NA

IN_SRV_FetchLaGenDetails_process_locale_data.scr

NA

NA

The script internally calls IN_AdvanceEI_FetchForLNGI.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

IN_SRV_FetchPymtOrderMaintDtIsForCopy_proce: (UTR and DD No)

This script fetches locale data for the menu HPORDM

NA

NA

NA

This script fetches locale data for the menu HPORDM

Post process script that is called during fetch operation

NA

©Copyright Infosys Ltd.

IN_SRV_FetchPymtOrderMaintDtlsForModify_proc (UTR and DD No)

This script fetches locale data for the menu HPORDM

NA

NA

NA

This script fetches locale data for the menu HPORDM

Post process script that is called during fetch operation

NA

©Copyright Infosys Ltd.

IN_SRV_FetchPymtOrderMaintDtIsForVerify_proce (UTR and DD No)

This script fetches locale data for the menu HPORDM

NA

NA

NA

This script fetches locale data for the menu HPORDM

Post process script that is called during fetch operation

NA

©Copyright Infosys Ltd.

IN_SRV_FetchPymtOrderMaintDtIsForDelete_proc (UTR and DD No)

This script fetches locale data for the menu HPORDM

NA

NA

NA

This script fetches locale data for the menu HPORDM

Post process script that is called during fetch operation

NA

©Copyright Infosys Ltd.

IN_SRV_InquirePymtOrderMaintDtls_process_loca (UTR and DD No)

This script inquires locale data for the menu HPORDM

NA

NA

NA

This script inquires locale data for the menu HPORDM

Post process script that is called during Inquiry

NA

©Copyright Infosys Ltd.

IN_SRV_InquireCLAcct_process_locale_data.scr (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_InquireCLAcct_process_locale_data.scr

NA

NA

NA

This script is called for process function in Inquire of HACMCL.

NA

IN_SRV_InquireLAAcct_process_locale_data.scr (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN_FITL_WCDL_Fetch.scr

NA

IN_SRV_InquireLAAcct_process_locale_data.scr

NA

NA

NA

This script is called for process function in Inquire of HACMLA.

NA

IN_SRV_InsertDisbData_pre_process_data.scr (Advance EI)

NA

IN_SRV_InsertDisbData_pre_process_data.scr

NA

NA

The script is used to fetch the advance EI details

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

IN_SRV_InsertDisbData_pre_process_data.scr - Auto Loans- HLADISB menu

NA

IN_SRV_InsertDisbData_pre_process_data.scr

NA

NA

The script calls the IN_ IN_GetMarginDetails.scr to fetch the margin details for auto loans.

This script is called in India localization, on click of submit in disbursement.

NA

IN_SRV_ModifyCLAcct_process_locale_data.scr, (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN FITL_WCDL_Modify.scr

NA

IN_SRV_ModifyCLAcct_process_locale_data.scr

NA

NA

NA

This script is called for process function in modify mode of HACMCL.

NA

IN_SRV_ModifyLAAcct_process_locale_data.scr (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN FITL_WCDL_Modify.scr

NA

IN_SRV_ModifyLAAcct_process_locale_data.scr

NA

NA

NA

This script is called for process function in modify mode of HACMLA.

NA

IN_SRV_ModifyLoanAcctSchmParams_post_proce (Auto Loans- HLADISB menu)

NA

IN_SRV_ModifyLoanAcctSchmParams_post_process_data.scr

NA

NA

The script is used to call the locale script validateAutoLoans.scr during HLAGSPM.

This script is called when click on submit in HLAGSPM in modify mode.

NA

IN_SRV_ModifyLAAcct_validate_data.scr (Advance EI)



NA

IN_SRV_ModifyLAAcct_validate_data.scr

NA

NA

The script internally calls IN_advanceEiVal.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

IN_SRV_ModifyLoanAcctSchmParams_post_proce (Advance EI)

NA

IN_SRV_ModifyLoanAcctSchmParams_post_process_data.scr

NA

NA

The script internally calls IN_ LAGSPMVal.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

IN_SRV_ModifyPymtOrderMaintDtls_process_loca (UTR and DD No)

This script modifies locale data for the menu HPORDM

NA

NA

NA

This script modifies locale data for the menu HPORDM

Post process script that is called during verification

NA

©Copyright Infosys Ltd.

IN_SRV_OpenCLAcct_process_locale_data.scr (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN FITL_WCDL_Add.scr

NA

IN_SRV_OpenCLAcct_process_locale_data.scr Input

NA

NA

NA

This script is called for process function in opening mode of
HOAACCL

NA

IN_SRV_OpenLaAcct_process_locale_data.scr (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls IN FITL_WCDL_Add.scr

NA

IN_SRV_OpenLaAcct_process_locale_data.scr

NA

NA

NA

This script is called for process function in opening mode of
HOAACLA

NA

IN_SRV_OpenLaAcct_validate_data.scr (Advance EI)



NA

IN_SRV_OpenLaAcct_validate_data.scr

NA

NA

The script internally calls IN_advanceEiVal.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

IN_SRV_VerifyCLAcct_process_locale_data.scr (HACMCL- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls INFITL_WCDL_VXDUMode.scr

NA

IN_SRV_VerifyCLAcct_process_locale_data.scr

NA

NA

NA

This script is called for process function in verify mode of HACMCL.

NA

IN_SRV_VerifyLAAcct_process_locale_data.scr (HACMLA- Linkage of FITL and WCTL accounts to Loan accounts)

This script calls INFITL_WCDL_VXDUMode.scr

NA

IN_SRV_VerifyLAAcct_process_locale_data.scr

NA

N/A

NA

This script is called for process function in verify mode of HACMLA.

NA

IN_SRV_VerifyPymtOrderMaintDtls_process_locale (UTR and DD No)

This script verifies locale data for the menu HPORDM

NA

NA

NA

This script verifies locale data for the menu HPORDM

Post process script that is called during verification

NA

©Copyright Infosys Ltd.

IN_SRV_XferAcctBtwnSchms_validate_locale_data (Advance EI)

NA

IN_SRV_XferAcctBtwnSchms_validate_locale_data.scr

NA

NA

The script calls IN_validateXFERSchmForAdvEi.scr which contains validations that has to be done during scheme transactionsfer

This script is called in India localization, to perform validations.

NA

IN_SRV_XferAcctBtwnSol_validate_locale_data.sc (Advance EI)

NA

IN_SRV_XferAcctBtwnSol_validate_locale_data.scr

NA

NA

The script calls IN_validateXFERSolForAdvEi.scr which contains validations that has to be done during Sol transactionsfer.

This script is called in India localization, to perform validations.

NA

IN_UploadReliefDetails.scr (DPD Freeze) Infosys®



This script is called during upload of relief period details through URPDA.

NA

IN_UploadReliefDetails.scr

NA

NA

This script is called during upload of relief period details through URPDA.

Is called during the upload menu URPDA.

NA

©Copyright Infosys Ltd.

IN_UploadReliefDtIsjLimo.scr (DPD Freeze)



This script is called during relief period details upload using URPDA.

NA

IN_UploadReliefDtIsjLimo.scr

NA

NA

This script is called during relief period details upload using URPDA.

Is called during the upload menu URPDA.

NA

©Copyright Infosys Ltd.

IN_UploadReliefDtIsLstDmp.scr (DPD Freeze)



This script is called to dump the relief period details to the report.

NA

IN_UploadReliefDtIsLstDmp.scr

NA

NA

This script is called to dump the relief period details to the report.

Is called during the upload menu URPDA.

NA

©Copyright Infosys Ltd.

IN_UploadReliefDtIsReport.scr (DPD Freeze)



This script is called to dump the relief period details to the report

NA

IN_UploadReliefDtIsReport.scr

NA

NA

This script is called to dump the relief period details to the report.

Is called during the upload menu URPDA.

NA

©Copyright Infosys Ltd.

IN_validateAcidType.scr (Linkage of FITL and WCTL accounts to Loan accounts)



This script is used for validating the FITL and WCTL accounts in HACMLA and HACMCL menu.

NA

IN_validateAcidType.scr

The following is the syntax for specifying the input fields:

BANCS.INPUT.AcctId

BANCS.INPUT.foracid

BANCS.INPUT.acctFlg

The following are the details of the input fields for the script:

Input Field	Description
BANCS.INPUT.AcctId	Account ID for which FITL and WCTL accounts should undergo validations for.
BANCS.INPUT.foracid	Passing original loan accounts to identify the accounts IN_LAM
BANCS.INPUT.acctFlg	Flag to identify if the account is FITL or WCTL account

The account ID passes through all the validations and wherever it fails the error is thrown at that point in HACMLA and HACMCL and stores the data in IN_LAM table.

HACMLA and HACMCL modify mode, this script is called on click of SUBMIT/Validate in Details screen.

NA

©Copyright Infosys Ltd.

IN_validateAutoLoans.scr (Auto Loans- HLADISB menu)



NA

IN_validateAutoLoans.scr

NA

NA

The script is used to validate the basic scheme validation in HLADISB.

This script is called when click on submit in modify mode of HLADISB.

NA

©Copyright Infosys Ltd.

IN_ValidateSchm.scr (NEFT and RTGS)

Infosys®



This script performs loan account validations for NEFT and RTGS transactions.

NA

IN_LoanAcctValidate.scr

NA

This script performs loan account validations for NEFT and RTGS transactions.

Is called to validate loan account while performing NEFT and RTGS transactions.

NA

©Copyright Infosys Ltd.

IN_validateTransaction.scr (Auto Loans- HLADISB menu)



NA

IN_validateTransaction.scr

NA

NA

The script is used to validate the transaction details which are entered during HOAACLA, HOAACMLA and HACMLA.

This script is called when we move out of the tab, or click on validate or click on submit in

HOAACLA, HOAACMLA and HACMLA.

NA

IN_validateXFERSchmForAdvEi.scr (Advance EI)



NA

IN_validateXFERSchmForAdvEi.scr

NA

NA

The script performs necessary validations during account being transactionsferred to another Scheme.

This script is called in India localization, to perform validations.

NA

©Copyright Infosys Ltd.

IN_validateXFERSolForAdvEi.scr (Advance EI)



NA

IN_validateXFERSolForAdvEi.scr

NA

NA

The script performs necessary validations during account being transactionsferred to another SOL.

This script is called in India localization, to perform validations.

NA

©Copyright Infosys Ltd.

IN_valMarginDetails.scr (Auto Loans- HLADISB menu)



NA

IN_valMarginDetails.scr

NA

NA

The script to validate the margin details for auto loans.

This script is called on click on Go in criteria page of HLADISB menu and validates the margin details.

NA

©Copyright Infosys Ltd.

IN_vrfyDelPODetails.scr (UTR and DD No)



This script verifies locale data for the menu HPORDM

NA

NA

NA

This script verifies locale data for the menu HPORDM

Post process script that is called during verification

NA

©Copyright Infosys Ltd.

NA

LADisbursementMTT.scr

NA

NA

The script is used to create the part transactionsaction for HLADISB

This script is called in India localization, for HLADISB.

NA

©Copyright Infosys Ltd.

SRV_AddAndPostCashTransaction_post_process_ (NonCust - HTM menu)

NA

SRV_AddAndPostCashTransaction_post_process_data.scr

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr.

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_AddCashTransaction_post_process_data.scr (NonCust - HTM menu)

NA

SRV_AddCashTransaction_post_process_data.scr

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr.

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_AddCashTransactionForPTransactionPost_p (NonCust - HTM menu)

NA

SRV_AddCashTransactionForPTransactionPost_post_process_data.scr

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr.

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_FetchTransactionDtlsForCopy_post_process (NonCust - HTM menu)

NA

SRV_FetchTransactionDtlsForCopy_post_process_data.scr

NA

NA

The script internally calls IN_HTM_fetchNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_FetchTransactionDtlsForDelete_post_proces (NonCust - HTM menu)

NA

SRV_FetchTransactionDtlsForDelete_post_process_data.scr

NA

NA

The script internally calls IN_HTM_fetchNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_FetchTransactionDtlsForVerify_post_process (NonCust - HTM menu)

NA

SRV_FetchTransactionDtlsForVerify_post_process_data.scr

NA

NA

The script internally calls IN_HTM_fetchNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_FetchORDtlsForCopy_pre_process_data.scr (NonCust - HORM menu)

NA

SRV_FetchORDtlsForCopy_pre_process_data.scr

None

None

This script calls the script IN_fetchNonCustDtlsForCopy.scr.

This script is called in India localization for copy mode in HORM menu.

NA

SRV_FetchTransactionDtlsForPost_post_process_ (NonCust - HTM menu)

NA

SRV_FetchTransactionDtlsForPost_post_process_data.scr

NA

NA

The script internally calls IN_HTM_fetchNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_FetchTransactionDtlsForModify_post_proces (NonCust - HTM menu)

NA

SRV_FetchTransactionDtlsForModify_post_process_data.scr

NA

NA

The script internally calls IN_HTM_fetchNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_InquireTransaction_post_process_data.scr (NonCust - HTM menu)

NA

SRV_InquireTransaction_post_process_data.scr

NA

NA

The script internally calls IN_HTM_fetchNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_ModifyAndPostCashTransaction_post_proce (NonCust - HTM menu)

NA

SRV_ModifyAndPostCashTransaction_post_process_data.scr

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_ModifyCashTransaction_post_process_data.scr (NonCust - HTM menu)

NA

SRV_ModifyCashTransaction_post_process_data.scr

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_ModifyCashTransactionForPTransactionPost (NonCust - HTM menu)

NA

SRV_ModifyCashTransactionForPTransactionPost_post_process_data.s

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_ModifyLAAcct_validate_data.scr (Auto Loans- HLADISB menu)



NA

SRV_ModifyLAAcct_validate_data.scr

NA

NA

The script is used to call the locale script LAMValidateData.scr and validate the locale fields during HOAACMLA and HACMLA.

This script is called when click on submit in HOAACMLA and HACMLA.

NA

©Copyright Infosys Ltd.

SRV_OpenLaAcct_validate_data.scr (AutoInfosys® Loans- HLADISB menu)

NA

SRV_OpenLaAcct_validate_data.scr

NA

NA

The script is used to call the locale script LAMValidateData.scr and validate the locale fields during HOAACL.

This script is called when click on submit in HOAACL.

NA

©Copyright Infosys Ltd.

SRV_PostTransaction_post_process_data.scr (NonCust - HTM menu)

NA

SRV_PostTransaction_post_process_data.scr

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr

This script is called in India localization, as post processing.

NA

©Copyright Infosys Ltd.

SRV_VerifyTransaction_post_process_data.scr (NonCust - HTM menu)

NA

SRV_VerifyTransaction_post_process_data.scr

NA

NA

The script internally calls IN_HTM_Main_ProcessNonCustData.scr

This script is called in India localization, as post processing.

NA

Note:

This topic describes the enhancements delivered for 10.2.18 release.

Following scripts and script hooks are added:

Input Field	Description
insertIntoDCT.scr	Finacle script to insert DCT record, upon generation of account statement of archived data using the retrieval menu - GASAT.
insertIntoPQT.scr	Finacle script to insert PQT record, upon generation of report of archived data using any of the reporting retrieval menus - GASAT & GRAAR.
Optim_rep_print.scr	Finacle script which is called post generation of retrieval report, which in turn calls the above two Finacle scripts - insertIntoDCT.scr and insertIntoPQT.scr.
prePreprocessing.scr	Finacle script hook which gets called (if the script is placed/present in the pre-defined scripts path) before starting pre-processing job (PPA menu). Pre-processing job will proceed even if this script is not present.
postPreprocessing.scr	Finacle script hook which gets called (if the script is placed/present in the pre-defined scripts path) post successful completion of pre-processing (PPA menu). Pre-processing job will continue/complete even if this script is not present.

©Copyright Infosys Ltd.

Finacle Copyright

Note:

This topic describes the enhancements delivered for 10.2.18 release.

This is the sample script which can be used by the customization code to handle the logic of average of minimum balance calculation, considering actual run days in a month and averaging for a quarter and to have monthly check for balance eligibility.

Firestone ticket id - 761133

getCustomAvgOfMinBal.scr

The following is the syntax for specifying the input fields:

Input Field	Description
BANCS.INPUT.numberOfMonth	Number of months applicable for the account in the PD cycle for avg. of min. bal. calculation.
BANCS.INPUT.minBalThreshold	Minimum balance threshold from scheme level setup.
BANCS.INPUT.monthStartDate1	Start date of month#1
BANCS.INPUT.monthEndDate1	End date of month#1
BANCS.INPUT.monthlyMinBal1	Minimum balance for month#1
BANCS.INPUT.monthStartDate2	Start date of month#2
BANCS.INPUT.monthEndDate2	End date of month#2
BANCS.INPUT.monthlyMinBal2	Minimum balance for month#2
BANCS.INPUT.monthStartDate3	Start date of month#3
BANCS.INPUT.monthEndDate3	End date of month#3
BANCS.INPUT.monthlyMinBal3	Minimum balance for month#3

The following is the syntax for specifying the output fields:

Output Field	Description
BANCS.OUTPUT.weightedBalance	Weighted balance for profit rate fetch.
BANCS.OUTPUT.averageBalance	Balance for profit calculation.

If the custom script is not available, balance calculation is done by the existing product logic.

This sample script logic is used only when it is present and it has to receive the number months, threshold balance, start and end dates of each month and minimum balance for each month in an iteration and then to calculate and return the weighted balance for profit rate fetch and average balance for profit calculation as outputs.

/finacle/fincore/v10.22BT1D27/sourcebay/base/common/sample/samsr

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.18 release.

This is a sample script which can be used to customize the product fetched MPST profit rate with custom profit rate from the script, for calculating broken period profit for pre-closed Mudarabah TU accounts during pool level distribution.

Firestone ticket ID: 761136

getCustomBrokenPeriodProfitRate.scr

The following is the syntax for specifying the input fields:

Input Field	Description
BANCS.INPUT.acctId	Account Id
BANCS.INPUT.acctCrncyCode	Account Currency Code
BANCS.INPUT.poolCode	Pool Code
BANCS.INPUT.profitShareCode	Profit Share Code/MPST Code

The following is the syntax for specifying the output fields:

Output Field	Description
BANCS.OUTPUT.customProfitRate	Profit rate output from customization logic to be used for actual broken period profit calculation for pre-closed TU accounts.

If the script does not exist in the system, the product fetched profit rate is used to calculate the profit rate.

This sample script is called only when it is present in the system and whenever pool level distribution for pre-closed TU accounts is done. This custom profit rate will override the actual profit rate fetched by the system for broken period profit calculation.

```
/finacle/fincore/v10.22BT1D27/sourcebay/base/common/sample/samsr  
getCustomBrokenPeriodProfitRate.sscr
```

©Copyright Infosys Ltd.

Note:

This topic describes the enhancements delivered for 10.2.18 release.

This is a sample script which can be used to customize the product calculated simple daily multiplier of (number of days in profit distribution cycle)/(number of days in year) in calculation of profit rate and profit amount.

Firestone ticket ID: 760357

getMudCustPeriodCalc.scr

The following is the syntax for specifying the input fields:

Input Field	Description																
BANCS.INPUT.entityId	acid- in case of account based calculation; pool code- in case of pool based calculation																
BANCS.INPUT.entityType	Type of the entity.A- Account,P- Pool code.																
BANCS.INPUT.eventType	The event in which the calculation is used. <table border="1"> <tr> <th>SCENARIO</th><th>EVENT TYPE</th></tr> <tr> <td>CPRMP3</td><td>CPRMP</td></tr> <tr> <td>CPILP</td><td>CPILP</td></tr> <tr> <td>SPILS</td><td>SPILS</td></tr> <tr> <td>DPPA normal profit</td><td>DPPNP</td></tr> <tr> <td>DPPA preferential profit</td><td>DPPPP</td></tr> <tr> <td>HCAAC normal profit</td><td>CSINP (i.e. CASA indicative normal profit)</td></tr> <tr> <td>HCAAC preferential profit</td><td>CSIPP (i.e. CASA indicative preferential profit)</td></tr> </table>	SCENARIO	EVENT TYPE	CPRMP3	CPRMP	CPILP	CPILP	SPILS	SPILS	DPPA normal profit	DPPNP	DPPA preferential profit	DPPPP	HCAAC normal profit	CSINP (i.e. CASA indicative normal profit)	HCAAC preferential profit	CSIPP (i.e. CASA indicative preferential profit)
SCENARIO	EVENT TYPE																
CPRMP3	CPRMP																
CPILP	CPILP																
SPILS	SPILS																
DPPA normal profit	DPPNP																
DPPA preferential profit	DPPPP																
HCAAC normal profit	CSINP (i.e. CASA indicative normal profit)																
HCAAC preferential profit	CSIPP (i.e. CASA indicative preferential profit)																

	HCAACTD normal profit	TUCNP (i.e. TU closure normal profit)
	HCAACTD preferential profit	TUCPP (i.e. TU closure normal profit)
	APA booked amount	APABA
BANCS.INPUT.profitShareCode	Calculation start date.	
BANCS.INPUT.endDate	Calculation end date.	
BANCS.INPUT.prodCalcValue	Product calculated multiplier of (number of days in profit distribution cycle)/(number of days in year)	

The following is the syntax for specifying the output fields:

Output Field	Description
BANCS.OUTPUT.customCalcValue	The custom multiplier value to be used in case of any different period calculation scenario.

This sample script is called only when its event is present and whenever profit calculation for distribution is done. It is called just before the calculation and the output of the script is then used as a custom multiplier.

GPRPD_output.scr



Note:

This topic describes the enhancements delivered for 10.2.18 release.

GPRPD_output.scr has been modified for preferential profit details.

©Copyright Infosys Ltd.

Scripts Deleted

Note:

This topic describes the enhancements delivered for 10.2.18 release.

Following Finacle scripts and com/shell scripts are deleted:

Input Field	Description
killPreproc.com	Shell script to kill the running transaction pre-processing batch job.
terminatePreproc.scr	Finacle script, which is called from pre-processing menu (PPA), to kill the running transaction pre-processing batch job.

DSACOMM – Validate Event Types for Discounting



The script `isDiscountingApplicable.scr` should be present in `TBA_SCRIPTS` directory. This script is used for validation of event types that are applicable for discounting.

Inputs Available in the Scripts

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS. INPUT. <Fieldname>

Script Input	Description
eventType	This gives us the event type to be validated to check if it is applicable for discounting or not.

Output Expected

The defined outputs are available in repository BANCS, class OUTPUT and with the field names mentioned below. One can access the outputs by referring the fields in the following manner.

BANCS. OUTPUT. <Fieldname>

Script Input	Description
isDiscountingApplicable	If the event is applicable for discounting this flag will be set to 'Y' else 'N'

Default logic in case script is not present

If the script is not present validation of events to check if it is applicable for discounting will not be done.

Typical usage scenario(s)

This script will be called before calling the discounting logic in charge routines.

Sample Script

Since it is a product script no sample script present.

©Copyright Infosys Ltd.

UCT – Validate Events for Uploading Charge Transactions



The script `validateEvents.scr` should be present in `TBA_SCRIPTS` directory. This script is used to validate the charge transactions from external system being uploaded through UCT menu.

Inputs Available in the Scripts

The defined inputs are available in repository BANCS, class INPUT and with the field names mentioned below. One can access the inputs by referring the fields in the following manner.

BANCS. INPUT. <Fieldname>

Script Input	Description
AccountId	Account id on which the charges are computed
StartDate	Populates the error message
EndDate	Start Date for batch charges
EventType	Type of Event for which charges are being uploaded

Output Expected

The defined outputs are available in repository BANCS, class OUTPUT and with the field names mentioned below. One can access the outputs by referring the fields in the following manner.

BANCS. OUTPUT. <Fieldname>

Script Input	Description
successOrFailure	Success or Failure flag
ErrorMesg	Populates the error message
StartDate	Start Date for batch charges

EndDate

End Date for batch charges

Default logic in case script is not present

If the script is not present validations required on the charge transaction to be uploaded will not be performed.

Typical usage scenario(s)

This script will be called before inserting record to CXL table when charge from external system is being uploaded.

Sample Script

Since it is a product script no sample script present.

©Copyright Infosys Ltd.

About Infosys Finacle

Finacle is the industry-leading digital banking solution suite from EdgeVerve Systems, a wholly owned product subsidiary of Infosys. Finacle helps traditional and emerging financial institutions drive truly digital transformation to achieve frictionless customer experiences, larger ecosystem play, insights-driven interactions and ubiquitous automation. Today, banks in over 100 countries rely on Finacle to service more than a billion consumers and 1.3 billion accounts.

Finacle solutions address the core banking, omnichannel banking, payments, treasury, origination, liquidity management, Islamic banking, wealth management, analytics, artificial intelligence, and blockchain requirements of financial institutions to drive business excellence. An assessment of the top 1250 banks in the world reveals that institutions powered by the Finacle Core Banking solution, on average, enjoy 7.2% points lower costs-to-income ratio than others.



For more information, contact finacle@edgeverve.com

www.finacle.com

©2019 EdgeVerve Systems Limited, a wholly owned subsidiary of Infosys, Bangalore, India. All Rights Reserved. This documentation is the sole property of EdgeVerve Systems Limited ("EdgeVerve"). EdgeVerve believes the information in this document or page is accurate as of its publication date; such information is subject to change without notice. EdgeVerve acknowledges the proprietary rights of other companies to the trademarks, product names and such other intellectual property rights mentioned in this document. This document is not for general distribution and is meant for use solely by the person or entity that it has been specifically issued to and can be used for the sole purpose it is intended to be used for as communicated by EdgeVerve in writing. Except as expressly permitted by EdgeVerve in writing, neither this documentation nor any part of it may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, printing, photocopying, recording or otherwise, without the prior written permission of EdgeVerve and/ or any named intellectual property rights holders under this document.