

# Joint Optimization of Trajectory Planning and Task Scheduling in Heterogeneous Multi-UAV System

Rejoy Chakraborty

Dept. of Computer Science and Engineering, Indian Institute of Science, Ropar

## Abstract

The use of unmanned aerial vehicles (UAV) as a new sensing paradigm is emerging for surveillance and tracking applications, especially in the infrastructure less environment. One such application of UAVs is in the construction industry where currently prevalent manual progress tracking results in schedule delays and cost overruns. In this paper, we develop a heterogeneous multi-UAV framework for progress tracking of large construction sites. The proposed framework consists of Edge UAV which coordinates the data relay of the visual sensor equipped Inspection UAVs (I UAV s) to the cloud. Our framework jointly takes into consideration the trajectory optimization of the Edge UAV and the stability of system queues. In particular, we develop a Distance and Access Latency Aware Trajectory (DLAT) optimization that generates a fair access schedule for I UAV s. In addition, a Lyapunov based online optimization ensures the system stability of the average queue backlogs for data offloading tasks. Through a message based mechanism, the coordination between the set of I UAV s and Edge UAV is ensured without any dependence on any central entity or message broadcasts. The performance of our proposed framework with joint optimization algorithm is validated by extensive simulation results in different parameter settings.

**Keywords:** Path Planning, Task Scheduling, Data Offloading, Construction Site Monitoring, Unmanned Aerial Vehicles (UAVs), Lyapunov Optimization

## 1 Introduction

The unmanned aerial vehicle (UAV) based solutions are emerging in various domains such as wireless sensing[1], payload delivery[2], precision agriculture [3], help and rescue operations [4], etc. Moreover, with the current trend of automation, sensing and information exchange in Industry 4.0, UAV based applications are also finding their place in the construction industry especially for resource tracking and progress monitoring using aerial imagery. Such solutions are helpful in infrastructure-less large construction sites as they provide ease of deployment, quick access to the ground-truth data and higher reachability and coverage [5]. Further, the autonomous or semi-autonomous UAV based solutions could facilitate progress monitoring, building inspections (for cracks or other defects), safety inspections (to find any environmental hazards) and many more construction-specific audits automatically. The UAV based visual monitoring of under-construction projects also allows simultaneous observability of ground-truth data by different collaborating entities. Availability of such data

and information helps in timely assessments that could reduce schedule delays, cost overruns, resource wastage and financial losses which are not uncommon in construction projects.

A plausible solution to address the aforementioned challenges could be a Mobile Edge Computing (MEC) [6] based heterogeneous multi-UAV framework. Such a framework along with the prior geometric knowledge available about the construction site as gathered from a Building Information Model (BIM)[7] could help create an effective multi-UAV based visual monitoring system for construction sites. As for any constrained environment, the optimization of computational resources is central to develop a solution. The integration of UAVs and MEC into a single framework could facilitate that with efficient data collection/processing from the UAV based dynamic sensors in infrastructure-less environments [8]. In addition, an MEC based framework can help to perform partial computation offloading wherein a part of data is processed by the UAVs while the rest gets offloaded to the cloud.

An MEC based UAV framework is not new and the deployment of the UAVs as base stations or edge servers is widely studied [9, 10]. These studies reflect on the flexibility in deployment of UAV based edge computing components. However, there is a problem of buffer overflow of UAVs due to the limited on-board processing and the shared bandwidth to transfer data to the cloud which leads to instability in the system. In addition, the dynamic nature of such systems with varying data traffic and continuous movement of UAVs makes it difficult to stabilize or control the system in a deterministic manner. Researchers have used online Lyapunov optimization[11] to address such system instabilities. Lyapunov optimization considers the stability of the system with time varying data and optimizes time averages of system utility and queue backlogs.

In this paper, we address the challenges of deploying a heterogeneous multi-UAV system for construction site monitoring by the joint optimization of UAV trajectory planning and data offloading task scheduling. The proposed framework employs two types of UAVs viz. Inspection UAVs I UAV s and Mobile Edge UAVs (Edge UAV ). While the former is deployed as visual sensors to collect visual data from different locations of the site, the latter interacts and collects data from I UAV s, and offloads the same to the cloud. The core objective of the framework is to minimize the total energy consumption of the system while considering the data queue backlogs of I UAVs and Edge UAV and also jointly optimizing the trajectory of the Edge UAV in accordance with the trajectories of I UAV s

having minimum access latency and travel distance. The online resource management such as transmission power and processor frequency of the Edge UAV is evolved using Lyapunov optimization (as in [12]).

The rest of the paper is organised as follows: Section 2 presents the proposed heterogeneous multi-UAV framework for construction site monitoring. The overall system objective is discussed in Sections 3. Sections 4 and 5 discuss the trajectory optimization and Lyapunov based system stability, respectively. The simulation setup has been presented in Section 6. Section 7 discusses the results gathered from the experiments while Section 8 concludes the paper.

## 2 Heterogeneous Multi-UAV Framework

Figure depicts the overall multi-UAV framework with all its components. The system consists of two heterogeneous UAVs i.e. a set of Inspection UAVs I UAV = I\_UAV1, I\_UAV2, I\_UAV3, ....., I\_UAVN and a MobileEdge UAV (Edge UAV). I UAV s are smaller in size and are more agile. They collect visual data from a set of Point of Interests (PoIs) denoted as  $L = l_1, l_2, l_3, \dots, l_k$  across the construction site. As the construction sites are infrastructure-less environments, there are limited Access Points (AP) available for connectivity to the cloud. Further, the I UAV s possess limited connectivity range that makes it difficult for them to transfer data to cloud directly. In addition, the I UAV s move in the 3D Cartesian coordinate system. The Edge UAV, which is larger in size and possesses higher computational capabilities, coordinates with the I UAV s to relay the data (after partially processing the same) to the cloud. Edge\_UAV always maintains a constant height and thus its trajectory lies in an horizontal plane.

The communication between I UAV and Edge UAV (A2A channel) has limited range and bandwidth. We have assumed the achievable data transmission rate of the I UAVi in a given time slot as  $d_i^{off}(t)$ . Further, The height of the Edge UAV is  $h$  which is dependent on coverage range  $r$  and line of sight (LoS) loss caused due to environmental effects [13].

The A2A channel power gain  $\zeta$  from I UAV to Edge UAV can be given as:

$$\zeta = g_0 \left( \frac{dis_0}{dis_t} \right)^\theta \quad (1)$$

where  $g_0$  is the path loss constant,  $dis_0$  is the reference distance,  $dis_t$  distance between the UAVs, and  $\theta$  is the path loss exponent.

### 2.1 Data collection and offloading

Each PoI ( $li$ ) is a tuple  $(\langle di, \psi \rangle)$  where  $di$  specifies the amount of data (images) to be collected and  $\psi_i$  denotes the coordinates of the site locations in 3D space. The sequence of PoIs to be visited is provided to I UAV s and same is also shared with the Edge UAV. During the traversal along the sequence of PoIs, the limited buffer may make the I UAV wait at some PoIs along the trajectory until it offloads the data to the Edge UAV.

The Edge UAV can communicate with one of the I UAVi in a time slot. The data gathered by each of the

I UAVi in a time slot  $t$  is denoted by  $A_i(t)$ .  $Q_i(t)$  represents the queue of the I UAVi and  $d_i^{off}(t)$  denotes the amount of data offloaded to the Edge UAV by the I UAVi in time-slot  $t$ . The recursive equation to update the  $Q_i(t)$  is as follows:

$$Q_i(t+1) = \max\{Q_i(t) - d_i^{off}(t), 0\} + A_i(t) \quad (2)$$

The Edge UAV accepts data from the selected I UAVi in the time-slot  $t$  in its queue  $L(t)$ . The following equation updates  $L(t)$  recursively:

$$L(t+1) = \max\{L(t) - c(t) - d_{edge}^{off}(t), 0\} + A_{edge}(t) \quad (3)$$

where  $A_{edge}(t)$  is the data arrived from the selected I UAVi in time-slot  $t$ ,  $c(t)$  is the data processed by the Edge UAV in time-slot  $t$ , and  $d$  of  $f$  edge( $t$ ) is the number of bits offloaded to the cloud in time-slot  $t$ .

## 3 System Objective

### 3.0.1 Transition energy of Edge\_UAV

### 3.1 Communication energy of Edge\_UAV

### 3.2 Communication energy of I\_UAV

[14]

## 4 Distance and Latency Aware Trajectory

## 5 Lyapunov Optimization based System Stability

[15]

## 6 Experimentation

Hello

## 7 Results and Discussions

## 8 Conclusion

UAV based applications for progress monitoring and resource tracking are emerging in construction industry. Constructions projects have minimal infrastructure for capture and offloading of ground-truth data. This paper presents a heterogeneous multi-UAV based framework for end-to-end data collection and offloading using a distance and latency aware trajectory optimization. The Lyapunov optimization approach is used to ensure the stability of the system in terms of expected system queue backlogs by breaking the system optimization problem into two sub-problems. The simulation results show that the access latency of our proposed (DLAT + Lyapunov) approach performs better than other baseline approaches. Moreover, the analysis of system parameter  $V$  has shown a trade-off between the queue stability and the system utility.

## References

- [1] Mohammad Mozaffari, Walid Saad, Mehdi Bennis, Young-Han Nam, and Mérouane Debbah. A tutorial on uavs for wireless networks: Applications, challenges, and open problems. *IEEE communications surveys & tutorials*, 21(3):2334–2360, 2019.
- [2] Fabio Ruggiero, Vincenzo Lippiello, and Anibal Ollero. Aerial manipulation: A literature review. *IEEE Robotics and Automation Letters*, 3(3):1957–1964, 2018.
- [3] Achilles D Boursianis, Maria S Papadopoulou, Panagiotis Diamantoulakis, Aglaia Liopa-Tsakalidi, Pantelis Barouchas, George Salahas, George Karagiannidis, Shaohua Wan, and Sotirios K Goudos. Internet of things (iot) and agricultural unmanned aerial vehicles (uavs) in smart farming: A comprehensive review. *Internet of Things*, page 100187, 2020.
- [4] Sonia Waharte and Niki Trigoni. Supporting search and rescue operations with uavs. In *2010 International Conference on Emerging Security Technologies*, pages 142–147. IEEE, 2010.
- [5] Hesam Hamledari, Shakiba Davari, Seyed Omid Sajedi, Pouya Zangeneh, Brenda McCabe, and Martin Fischer. Uav mission planning using swarm intelligence and 4d bims in support of vision-based construction progress monitoring and as-built modeling. In *Construction Research Congress 2018*, pages 43–53, 2018.
- [6] Yuyi Mao, Changsheng You, Jun Zhang, Kaibin Huang, and Khaled B Letaief. A survey on mobile edge computing: The communication perspective. *IEEE Communications Surveys & Tutorials*, 19(4):2322–2358, 2017.
- [7] Mani Golparvar-Fard, Feniosky Peña-Mora, and Silvio Savarese. Integrated sequential as-built and as-planned representation with d 4 ar tools in support of decision-making tasks in the aec/fm industry. *Journal of Construction Engineering and Management*, 137(12):1099–1116, 2011.
- [8] VanDung Nguyen, Tran Trong Khanh, Pham Van Nam, Ngo Thien Thu, Choong Seon Hong, and Eui-Nam Huh. Towards flying mobile edge computing. In *2020 International Conference on Information Networking (ICOIN)*, pages 723–725. IEEE, 2020.
- [9] Shuo Wan, Jiaxun Lu, Pingyi Fan, and Khaled B Letaief. Towards big data processing in iot: Path planning and resource management of uav base stations in mobile-edge computing system. *IEEE Internet of Things Journal*, 2019.
- [10] Nasir Abbas, Yan Zhang, Amir Taherkordi, and Tor Skeie. Mobile edge computing: A survey. *IEEE Internet of Things Journal*, 5(1):450–465, 2017.
- [11] Michael Neely. *Stochastic network optimization with application to communication and queueing systems*. Morgan & Claypool Publishers, 2010.
- [12] Jiao Zhang, Li Zhou, Qi Tang, Edith C-H Ngai, Xiping Hu, Haitao Zhao, and Jibo Wei. Stochastic computation offloading and trajectory scheduling for uav-assisted mobile edge computing. *IEEE Internet of Things Journal*, 6(2):3688–3699, 2018.
- [13] Akram Al-Hourani, Sithamparanathan Kandeepan, and Simon Lardner. Optimal lap altitude for maximum coverage. *IEEE Wireless Communications Letters*, 3(6):569–572, 2014.
- [14] Jiaxun Lu, Shuo Wan, Xuhong Chen, Zhengchuan Chen, Pingyi Fan, and Khaled Ben Letaief. Beyond empirical models: Pattern formation driven placement of uav base stations. *IEEE Transactions on Wireless Communications*, 17(6):3641–3655, 2018.
- [15] Michael J. Neely. *Network Optimization: Notes and Exercises*, 2018.