



Decimation: A sampling rate decriaser is shown below. We shall confine our attention to a decrease by an integer factor M (e.g. $M=3$)



The output signal $y(m)$ is obtained by taking every M th sample of the input signal. If $M=3$, we should just take every third sample of $x(n)$ to form the desired signal $y(m)$.

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Example: $x[n] = \{1, \cancel{4}, \cancel{7}, 5, \cancel{6}, -8, \cancel{2}, -3, 2\}$

↓ Down sample by (2)

$y[m] = \{1, 4, 5, -8, -3\}$


The output signal $y[n]$ is obtained by taking every M^{th} sample of the input signal. If $M = 3$, we should just take every third sample of $x[n]$ to form the desired signal $y[m]$.

Obviously, it only makes sense to reduce the sampling rate if the information content of the signal we wish to preserve is band limited to $\frac{f_s}{6}$; half the desired sampling rate since the spectral components above this frequency will be aliased into frequencies below $\frac{f_s}{6}$ according to the sampling rule.

ELEC3104


Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



The diagram below shows a block representations of a times M decimator.

The signal $x(n)$ is first passed through a lowpass filter that attenuates the band from $\{f_s/2\}/M$ to $f_s/2$ to prevent aliasing.




ELEC3104


Digital Signal
Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW





Example:




ELEC3104 Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Should we use ~~IIR~~ or ~~FIR~~ for the lowpass filtering required? ✓ ✓

Using an IIR filter in this case has an obvious shortcoming. We cannot take advantage of the fact that we only have to compute every Nth output, since previous outputs are required to compute the Mth output. Thus no saving is realised.




On the other hand, using an FIR filter, in this case implies that we can do our computations at the rate of f_s/M . Thus, using an FIR filter in the decimation process will lead to a significantly lower computation rate.

Another advantage of using an FIR filter is the fact that we can easily design linear phase filters and is desirable in many applications.

ELEC3104


Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Interpolation

- The process of interpolation involves a sampling rate increase




- The sequence $x(n)$ was derived by sampling $x(t)$ at a sampling rate f_s and we want to obtain a sequence $y(n)$ that approximates as closely as possible the sequence that would have been obtained had we sampled $x(t)$ at the rate Lf_s .
- Interpolation involves inserting between any samples $x(n)$ and $x(n-1)$ and additional $L-1$ samples.

ELEC3104

Digital Signal
Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Interpolation Examples

$$x[n] = \{1, 2, 4, 3, -5, 6, -7, 2, 4, 3\}$$

↑
2

$$y[m] = \{1, 0, 2, 0, 4, 0, 3, 0, -5, 0, 6, 0, -7, 0, 2, 0, 4, 0, 3, 0\}$$

$$x[n] = \{1, 2, 4, 3, -5, 6, -7, 2, 4, 3\}$$


↑
3

$$y[m] = \{1, 0, 0, 2, 0, 0, 4, 0, 0, 3, 0, 0, -5, 0, 0, 6, 0, 0, -7, 0, 0, 2, 0, 0, 4, 0, 0, 3, 0, 0\}$$



ELEC3104

**Digital Signal
Processing**

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Interpolation Example




Sampling frequency of $y(m) = 4f_s$; Signals must be band limited


ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Interpolation Example




Sampling frequency of $y(m) = 4f_s$; Signals must be band limited


ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW




Interpolator



ELEC3104


Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Example: Decimation of $x[n] = \{2, 6, 4, 2, 6, 8, 4, 2, 4, 4\}$

$\downarrow M=2$



$$h[n] = \{1/2, 1/2\}$$

$$h[0] = 1/2, h[1] = 1/2$$

$$p[n] = x[n] * h[n] = \{4, 5, 3, 4, 7, 6, 3, 3, 4, 2\}$$


$\downarrow 2$

$$y[n] = \{4, 3, 7, 3, 4\}$$


ELEC3104

Digital Signal
Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW




Example: Decimation of $x[n] = \{2, 6, 4, 2, 6, 8, 4, 2, 4, 4\}$




ELEC3104
Digital Signal
Processing

Professor E. Ambikairajah
 School of Electrical Engineering
 and Telecommunications
 UNSW



Example: Linear interpolation of $x[n] = \{1, 3, 5, 3, 7\}$



$\rightarrow x[n] = \{1, 3, 5, 3, 7\}$
 $p[n] = \{1, 0, 3, 0, 5, 0, 3, 0, 7, 0\}$ (insert zeros)


$\rightarrow h[n] = \left\{ \frac{1}{2}, 1, \frac{1}{2} \right\}$


$y[n] = p[n] * h[n] = \{1, 2, 3, 4, 5, 4, 3, 5, 7, 3.5\}$

ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW





- What should be the cut-off frequency of the digital lowpass filter?
- What should be the value of f_s' ?

ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



ELEC3004





Figure below shows that the sampling frequency change is achieved by first interpolating the data by L and then decimating by M .




The two Digital Lowpass Filters, $h1(m)$ and $h2(m)$ can be combined into a single filter since they are in cascade and have a common sampling frequency


If $M > L$ the resulting operation is a decimation process by M/L
 If $M < L$ the resulting operation is an interpolation

ELEC3104
Digital Signal Processing

Professor E. Ambikairajah
 School of Electrical Engineering
 and Telecommunications
 UNSW



Summary: Sampling Rate Conversion by Non-Integer Factors



The lowpass filter that we require is the one that has a cut-off frequency:

$$\theta_c = \min\left(\frac{\pi}{L}, \frac{\pi}{M}\right)$$

ELEC3104

Digital Signal
Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



ELEC3004




Decimation by 2

$$\begin{aligned}
 Y(z) &= \frac{1}{2} [X(z^2) + X(-z^2)] \\
 Y(\theta) &= \frac{1}{2} [X(e^{j\frac{\theta}{2}}) + X(-e^{j\frac{\theta}{2}})] \\
 &= \frac{1}{2} [X(e^{j\frac{\theta}{2}}) + X(e^{j(\frac{\theta}{2} - \pi)})] \\
 &= \frac{1}{2} [X(\frac{\theta}{2}) + X(\frac{\theta}{2} - \pi)]
 \end{aligned}$$

Aliasing term

Aliasing term




Stretch $X(\theta)$ by a factor 2 to obtain $X(\theta/2)$


The spectrum is stretched by a factor 2

ELEC3104
Digital Signal Processing


Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Decimation by 2




Case 2



$$Y(\theta) = \frac{1}{2} \left[X\left(\frac{\theta}{2}\right) + X\left(\frac{\theta}{2} - \pi\right) \right]$$


No Aliasing ✓




ELEC3104

Digital Signal
Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW






Solution


Note: By using a lowpass filter $H(\theta)$, we can eliminate the images and extract the original spectrum $X(\theta)$.


$V(\theta)$ is a compressed version of $W(\theta)$



ELEC3104 Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW






ELEC3104


Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Example: $x(t)$ is the input signal for the system shown below. The analogue signal $x(t)$ has the spectrum $X(f)$ given by:

$$X(f) = \begin{cases} 1 & 0.9\text{kHz} \leq f \leq 1.1\text{kHz} \\ 1 & -1.1\text{kHz} \leq f \leq -0.9\text{kHz} \\ 0 & \text{elsewhere} \end{cases}$$




$H(\theta)$ is an ideal lowpass filter (gain=10) with cut-off frequency $f_c = 125$ Hz. Sketch, one above another, $|X(\theta)|$, $|P(\theta)|$, $|V(\theta)|$, $|Y(\theta)|$ against θ .


Note: $P(\theta) = \frac{1}{2}[X(\theta + \theta_0) + X(\theta - \theta_0)]$

ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW





Time Domain

Frequency Domain

$x(n) \cos(\theta_0 n)$

$\checkmark \frac{1}{2} [X(\theta - \theta_0) + X(\theta + \theta_0)]$

$x(n) \sin(\theta_0 n)$

$\frac{1}{2j} [X(\theta - \theta_0) - X(\theta + \theta_0)]$

$x(n) e^{-jn\theta_0}$


$X(\theta + \theta_0)$



ELEC3104


Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



$$f_s = \frac{1}{T} = 2.5 \text{ kHz}; \quad \theta_0 = 2\pi \cdot 10^3 (0.410 \cdot 10^{-3}) = 0.8\pi; \quad \theta_c = 2\pi (125 / (2.5 \cdot 10^3)) = 0.1\pi$$


Solution



ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW




Example:

$x(n]$ is the input signal for the system shown below.

If $x(n] = 0.5 \delta(n+1) + \delta(n) + 0.5 \delta(n-1)$, Show that

$$S(\theta) = \begin{cases} 1/2 & 10\pi/4 \leq \theta \leq 11\pi/4 \\ 1/2 & -11\pi/4 \leq \theta \leq -10\pi/4 \\ 0 & \text{elsewhere} \end{cases}$$



$$G(\theta) = \begin{cases} 1 & 0 \leq |\theta| \leq \frac{\pi}{4} \\ 0 & \frac{\pi}{4} < |\theta| \leq \pi \end{cases}$$


$$H(\theta) = \begin{cases} 1 & 0 \leq |\theta| \leq \frac{\pi}{7} \\ 0 & \frac{\pi}{7} < |\theta| \leq \frac{\pi}{2} \end{cases}$$




ELEC3104

**Digital Signal
Processing**

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW





$$x(n) = \frac{1}{2} \delta(n+1) + \delta(n) + \frac{1}{2} \delta(n-1) \Rightarrow X(z) = \frac{1}{2} z^{+1} + 1 + \frac{1}{2} z^{-1}$$

$$X(\theta) = \frac{1}{2} e^{j\theta} + 1 + \frac{1}{2} e^{-j\theta} = 1 + \cos(\theta) \quad -\pi \leq \theta \leq \pi$$

$$A(\theta) = 1 + \cos(2\theta)$$


$$B(\theta) = \frac{1}{2} \{A(\theta - \theta_1) + A(\theta + \theta_1)\} = \frac{1}{2} \left\{ 1 + A \cos 2\left(\theta - \frac{\pi}{4}\right) + 1 + A \cos 2\left(\theta + \frac{\pi}{4}\right) \right\}$$

$$= 1$$


$$D(\theta) = B(\theta) \cdot G(\theta) = \begin{cases} 1 & -\pi/4 \leq \theta \leq \pi/4 \\ 0 & \text{elsewhere} \end{cases}$$

ELEC3104 Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW



Solution.....



$$R(\theta) = \underline{E(\theta)} \cdot \underline{H(\theta)} = \underline{D(7\theta)} \cdot \underline{H(\theta)} \quad \{H(\theta) = 1\}$$

$$= \begin{cases} D(7\theta) & -\pi/7 \leq \theta \leq \pi/7 \\ 0 & \text{elsewhere} \end{cases}$$

$$R(\theta) = \begin{cases} 1 & -\pi/4 \leq \theta \leq \pi/4 \\ 0 & \pi/4 \leq |\theta| \leq \pi \end{cases} = \begin{cases} 1 & -\pi/28 \leq \theta \leq \pi/28 \\ 0 & \pi/28 \leq |\theta| \leq \pi \end{cases}$$

$$H(\theta) = \begin{cases} 1 & 0 \leq \theta \leq \frac{\pi}{7} \\ 0 & \frac{\pi}{7} < |\theta| \leq \pi \end{cases}$$


$$G(\theta) = \begin{cases} 1 & 0 \leq \theta \leq \frac{\pi}{4} \\ 0 & \frac{\pi}{4} < |\theta| \leq \pi \end{cases}$$




ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW




Solution....



$$\begin{aligned}
 S(\theta) &= \frac{1}{2} \left\{ R(\theta - \theta_2) + R(\theta + \theta_2) \right\} \\
 &= \frac{1}{2} \left\{ R\left(\theta - \frac{3\pi}{4}\right) + R\left(\theta + \frac{3\pi}{4}\right) \right\} \\
 &= \frac{1}{2} \quad -\pi/28 \leq \theta - \frac{3\pi}{4} \leq \pi/28 \\
 S(\theta) &= \frac{1}{2} \quad -\pi/28 \leq \theta + \frac{3\pi}{4} \leq \pi/28 \\
 &= 0 \quad \text{elsewhere}
 \end{aligned}$$

$$\theta_2 = \frac{3\pi}{4}$$

$$\begin{aligned}
 S(\theta) &= \frac{1}{2} \quad 10\pi/14 \leq \theta \leq 11\pi/14 \\
 S(\theta) &= \frac{1}{2} \quad -11\pi/14 \leq \theta \leq -10\pi/14 \\
 &= 0 \quad \text{elsewhere}
 \end{aligned}$$



ELEC3104

Digital Signal Processing

Professor E. Ambikairajah
School of Electrical Engineering
and Telecommunications
UNSW

