| Series | Model | Initial_height_m | Hydraulic_lift_m | Max_height_wit | H2_mm | Total_length_m | Net_weight_kg | Gross_weight_k | Package_cm | Product_page |
|---|---|---|---|---|---|---|---|---|---|---|
| Up-down | HJP 150-300 | 130 | 80 | 310–320 | | 420 | 15 | 34 | 61 × 28 × 34 | https://reliancetrenchless.com/products/point-repair-jack |
| Up-down | HJP 300-600 | 180 | 100 | 610–620 | | 420 | 24 | 43 | 66 × 36 × 34 | https://reliancetrenchless.com/products/point-repair-jack |
| Duck-billed | DHJ 300 | | | 310–320 | 250 | 650 | 38 | 48 | 76 × 36 × 43 | https://reliancetrenchless.com/products/point-repair-jack |
| Duck-billed | DHJ 400 | | | 410–420 | 300 | 700 | 58 | 69 | 91 × 46 × 48 | https://reliancetrenchless.com/products/point-repair-jack |
| Duck-billed | DHJ 500 | | | 510–520 | 380 | 760 | 62 | 73 | 94 × 51 × 50 | https://reliancetrenchless.com/products/point-repair-jack |

**Facts only from reliancetrenchless.com — confirm with Reliance before ordering.**

Point-Repair Jack Model Range | Reliance Trenchless

Source of truth:
https://reliancetrenchless.com/products/point-repair-jack
Contact: https://reliancetrenchless.com/contact · sales@reliancetrenchless.com

How to use: Select Up-down (HJP) or Duck-billed (DHJ) by pipe diameter and defect geometry. Page states suitability for HDPE/PVC/glass sand-filled/steel-belt and not for PE/concrete — confirm pipe material with Reliance (brochure wording is inconsistent on PE vs HDPE). Accessories: hydraulic tube 2×40 m; hydraulic pump listed without size.
Do not confuse with: Not pipe repair packers; not Instant-Lock sleeves.

Confirm dimensions, materials, operating limits, inspection documents, availability and delivery terms with Reliance for each project.