

## 07 - Lexical Analysis

Dr. Robert Lowe

Division of Mathematics and Computer Science  
Maryville College

# Outline

- 1 Lexical Analysis
- 2 Regular Expressions
- 3 Tokenization
- 4 L++

# Outline

- 1 Lexical Analysis
- 2 Regular Expressions
- 3 Tokenization
- 4 L++

# Lexical Analysis Tasks

- The lexical analyzer, or **lexer**, processes the micro-syntax of a language.

# Lexical Analysis Tasks

- The lexical analyzer, or **lexer**, processes the micro-syntax of a language.
- The lexer converts sequences of terminals into **lexemes**.

# Lexical Analysis Tasks

- The lexical analyzer, or **lexer**, processes the micro-syntax of a language.
- The lexer converts sequences of terminals into **lexemes**.
- A lexeme is the basic building block of a language.

# Lexical Analysis Tasks

- The lexical analyzer, or **lexer**, processes the micro-syntax of a language.
- The lexer converts sequences of terminals into **lexemes**.
- A lexeme is the basic building block of a language.
- The lexer has two basic layers/tasks:

# Lexical Analysis Tasks

- The lexical analyzer, or **lexer**, processes the micro-syntax of a language.
- The lexer converts sequences of terminals into **lexemes**.
- A lexeme is the basic building block of a language.
- The lexer has two basic layers/tasks:
  - 1 Scanner



# Lexical Analysis Tasks

- The lexical analyzer, or **lexer**, processes the micro-syntax of a language.
- The lexer converts sequences of terminals into **lexemes**.
- A lexeme is the basic building block of a language.
- The lexer has two basic layers/tasks:
  - 1 Scanner
  - 2 Screener

# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.

# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.
- Recall that regular grammars consist of these productions:  
 $A \rightarrow a$  and  $A \rightarrow aB$

# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.
- Recall that regular grammars consist of these productions:  
 $A \rightarrow a$  and  $A \rightarrow aB$
- These productions are the **lexemes** of a language.

# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.
- Recall that regular grammars consist of these productions:  
 $A \rightarrow a$  and  $A \rightarrow aB$
- These productions are the **lexemes** of a language.
- Example lexemes include:

# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.
- Recall that regular grammars consist of these productions:  
 $A \rightarrow a$  and  $A \rightarrow aB$
- These productions are the **lexemes** of a language.
- Example lexemes include:
  - Literals

# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.
- Recall that regular grammars consist of these productions:  
 $A \rightarrow a$  and  $A \rightarrow aB$
- These productions are the **lexemes** of a language.
- Example lexemes include:
  - Literals
  - Identifiers

# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.
- Recall that regular grammars consist of these productions:  
 $A \rightarrow a$  and  $A \rightarrow aB$
- These productions are the **lexemes** of a language.
- Example lexemes include:
  - Literals
  - Identifiers
  - Keywords



# Analyzing the Micro-Syntax

- The micro-syntax of a language is the portion of the language which is expressible as a regular grammar.
- Recall that regular grammars consist of these productions:  
 $A \rightarrow a$  and  $A \rightarrow aB$
- These productions are the **lexemes** of a language.
- Example lexemes include:
  - Literals
  - Identifiers
  - Keywords
- It is possible to use recursive descent for this, but this would be overkill for a lexer!

# Scanning

- In the scanning layer, the lexer consumes sequences of characters and transforms them into the productions of the micro-syntax.

# Scanning

- In the scanning layer, the lexer consumes sequences of characters and transforms them into the productions of the micro-syntax.
- Scanning can be implemented as recursive descent, but this is not necessary.

# Scanning

- In the scanning layer, the lexer consumes sequences of characters and transforms them into the productions of the micro-syntax.
- Scanning can be implemented as recursive descent, but this is not necessary.
- Scanning is typically implemented as a simple state machine.

# Scanning

- In the scanning layer, the lexer consumes sequences of characters and transforms them into the productions of the micro-syntax.
- Scanning can be implemented as recursive descent, but this is not necessary.
- Scanning is typically implemented as a simple state machine.
- This is also known as “regular expression parsing”, because the language processed by the lexer is a regular grammar.

# Screening

- Screening is the layer which excludes improper characters or sequences of characters.

# Screening

- Screening is the layer which excludes improper characters or sequences of characters.
- Usually, screening is done as an exclusionary sort of process.

# Screening

- Screening is the layer which excludes improper characters or sequences of characters.
- Usually, screening is done as an exclusionary sort of process.
- Sometimes screened characters are skipped (for example, unneeded whitespace or comments).



# Screening

- Screening is the layer which excludes improper characters or sequences of characters.
- Usually, screening is done as an exclusionary sort of process.
- Sometimes screened characters are skipped (for example, unneeded whitespace or comments).
- If something does not match the rules of the lexer's language, it is flagged as an invalid sequence.

# The Lexer Interface

- A global variable `symbol`

# The Lexer Interface

- A global variable `symbol`
- **procedure** `next_symbol`

# The Lexer Interface

- A global variable `symbol`
- **procedure** `next_symbol`
  - This is where most of the lexer exists.

# The Lexer Interface

- A global variable `symbol`
- **procedure** `next_symbol`
  - This is where most of the lexer exists.
  - Includes the state machine that consumes the input stream.

# The Lexer Interface

- A global variable `symbol`
- **procedure** `next_symbol`
  - This is where most of the lexer exists.
  - Includes the state machine that consumes the input stream.
  - Rather than producing single characters, this procedure will process as many characters as needed for the regular productions of the language.

# The Lexer Interface

- A global variable `symbol`
- **procedure** `next_symbol`
  - This is where most of the lexer exists.
  - Includes the state machine that consumes the input stream.
  - Rather than producing single characters, this procedure will process as many characters as needed for the regular productions of the language.
- The remaining two procedures provide convenience for matching symbols.

# The Lexer Interface

- A global variable `symbol`
- **procedure** `next_symbol`
  - This is where most of the lexer exists.
  - Includes the state machine that consumes the input stream.
  - Rather than producing single characters, this procedure will process as many characters as needed for the regular productions of the language.
- The remaining two procedures provide convenience for matching symbols.
  - **procedure** `mustbe(s)`



# The Lexer Interface

- A global variable `symbol`
- **procedure** `next_symbol`
  - This is where most of the lexer exists.
  - Includes the state machine that consumes the input stream.
  - Rather than producing single characters, this procedure will process as many characters as needed for the regular productions of the language.
- The remaining two procedures provide convenience for matching symbols.
  - **procedure** `mustbe(s)`
  - **procedure** `have(s)`

# Outline

- 1 Lexical Analysis
- 2 Regular Expressions
- 3 Tokenization
- 4 L++

# Simple Regular Expression Syntax

- **grouping** ( . . . )

# Simple Regular Expression Syntax

- **grouping** ( . . . )
- **boolean or** a | b

# Simple Regular Expression Syntax

- **grouping** ( . . . )
- **boolean or** a | b
- **wildcard** .

# Simple Regular Expression Syntax

- **grouping** ( . . . )
- **boolean or** a | b
- **wildcard** .
- **quantifiers** Quantifiers follow a symbol or a group and specify how many occurrences match.

# Simple Regular Expression Syntax

- **grouping** ( . . . )
- **boolean or** a | b
- **wildcard** .
- **quantifiers** Quantifiers follow a symbol or a group and specify how many occurrences match.
  - \*: zero or more

# Simple Regular Expression Syntax

- **grouping** ( . . . )
- **boolean or** a | b
- **wildcard** .
- **quantifiers** Quantifiers follow a symbol or a group and specify how many occurrences match.
  - \*: zero or more
  - +: one or more



# Simple Regular Expression Syntax

- **grouping** ( . . . )
- **boolean or** a | b
- **wildcard** .
- **quantifiers** Quantifiers follow a symbol or a group and specify how many occurrences match.
  - \*: zero or more
  - +: one or more
  - ?: exactly zero or one

# Simple Regular Expression Syntax

- **grouping** ( . . . )
- **boolean or** a | b
- **wildcard** .
- **quantifiers** Quantifiers follow a symbol or a group and specify how many occurrences match.
  - \*: zero or more
  - +: one or more
  - ?: exactly zero or one
- **escaping literals** The special characters in regular expressions can all be escaped in the usual way.  
\\ (, \\), \\|, \\., \\\*, \\\*, \\\*, \\?, \\

# Regular Expressions and DFA's

- A regular expression is equivalent to a deterministic finite automaton (DFA).

# Regular Expressions and DFA's


- A regular expression is equivalent to a deterministic finite automaton (DFA).
- A DFA is a graph where states are represented by vertices.

# Regular Expressions and DFA's


- A regular expression is equivalent to a deterministic finite automaton (DFA).
- A DFA is a graph where states are represented by vertices.
- Edges show transitions from each state for a given character or set of characters.

# Regular Expressions and DFA's

- A regular expression is equivalent to a deterministic finite automaton (DFA).
- A DFA is a graph where states are represented by vertices.
- Edges show transitions from each state for a given character or set of characters.
- For example: `aa.*b+` becomes the DFA:




# Coding a DFA



- A DFA can be readily converted into code.


# Coding a DFA



- A DFA can be readily converted into code.
- First, we need an enumeration for the states.




# Coding a DFA




- A DFA can be readily converted into code.
- First, we need an enumeration for the states.
- Then we set the initial state.

# Coding a DFA




- A DFA can be readily converted into code.
- First, we need an enumeration for the states.
- Then we set the initial state.
- Next, we write a loop that will scan the input.

# Coding a DFA



- A DFA can be readily converted into code.
- First, we need an enumeration for the states.
- Then we set the initial state.
- Next, we write a loop that will scan the input.
- Within the loop, we add `if` statements to transition the state. Any invalid transition returns an error.

# Coding a DFA



- A DFA can be readily converted into code.
- First, we need an enumeration for the states.
- Then we set the initial state.
- Next, we write a loop that will scan the input.
- Within the loop, we add `if` statements to transition the state. Any invalid transition returns an error.
- **Activity:** Let's code the above DFA!

# Outline

- 1 Lexical Analysis
- 2 Regular Expressions
- 3 Tokenization
- 4 L++

# Tokens

- A **token** is a sequence of characters with meaning. (A token is equivalent to a lexeme.)

# Tokens

- A **token** is a sequence of characters with meaning. (A token is equivalent to a lexeme.)
- One approach in C++ would be to represent a token using an enumeration:

```
enum Token_Type {INVALID_TOK, OPERATOR_TOK,  
                INTEGER_TOK, LPAREN_TOK,  
                RPAREN_TOK, EOF_TOK};
```

# Tokens

- A **token** is a sequence of characters with meaning. (A token is equivalent to a lexeme.)
- One approach in C++ would be to represent a token using an enumeration:

```
enum Token_Type {INVALID_TOK, OPERATOR_TOK,  
                INTEGER_TOK, LPAREN_TOK,  
                RPAREN_TOK, EOF_TOK};
```

- We often need to store some additional information about a token:

```
struct Token {  
    Token_Type type;  
    string text;  
};
```



# Identifying Tokens

- Tokens are typically represented by implementing the DFA which represents the regular grammar of the lexer.

# Identifying Tokens

- Tokens are typically represented by implementing the DFA which represents the regular grammar of the lexer.
- The basic strategy is this:

# Identifying Tokens

- Tokens are typically represented by implementing the DFA which represents the regular grammar of the lexer.
- The basic strategy is this:
  - 1 Set the state to the start state.

# Identifying Tokens

- Tokens are typically represented by implementing the DFA which represents the regular grammar of the lexer.
- The basic strategy is this:
  - 1 Set the state to the start state.
  - 2 Peek at the next character and transition to an appropriate state.

# Identifying Tokens

- Tokens are typically represented by implementing the DFA which represents the regular grammar of the lexer.
- The basic strategy is this:
  - 1 Set the state to the start state.
  - 2 Peek at the next character and transition to an appropriate state.
  - 3 Continue following transitions until the production ends.

# Identifying Tokens

- Tokens are typically represented by implementing the DFA which represents the regular grammar of the lexer.
- The basic strategy is this:
  - 1 Set the state to the start state.
  - 2 Peek at the next character and transition to an appropriate state.
  - 3 Continue following transitions until the production ends.
  - 4 Emit the token indicated by the current state.

# Tokenizing a String

- The global `symbol` variable should be a `Token` structure.

# Tokenizing a String

- The global `symbol` variable should be a `Token` structure.
- Each call to `next_symbol` should perform the DFA on the stream.



# Tokenizing a String

- The global `symbol` variable should be a `Token` structure.
- Each call to `next_symbol` should perform the DFA on the stream.
- `symbol` is set to the emitted token.

# Outline

- 1 Lexical Analysis
- 2 Regular Expressions
- 3 Tokenization
- 4 L++

# The Grammar of L++

$\langle \text{program} \rangle ::= \langle \text{expression} \rangle$

$\langle \text{expression} \rangle ::= \langle \text{term} \rangle \langle \text{expression-tail} \rangle$

$\langle \text{expression-tail} \rangle ::= \lambda \mid '+' \langle \text{term} \rangle \langle \text{expression-tail} \rangle$

$\langle \text{term} \rangle ::= \langle \text{factor} \rangle \langle \text{term-tail} \rangle$

$\langle \text{term-tail} \rangle ::= \lambda \mid '**' \langle \text{factor} \rangle \langle \text{term-tail} \rangle$

$\langle \text{factor} \rangle ::= \langle \text{integer} \rangle \mid '(' \langle \text{expression} \rangle ')'$

$\langle \text{integer} \rangle ::= \langle \text{unit} \rangle \mid \langle \text{unit} \rangle \langle \text{integer} \rangle$

$\langle \text{unit} \rangle ::= '0' \mid '1' \mid '2' \mid '3' \mid '4' \mid '5' \mid '6' \mid '7' \mid '8' \mid '9'$

# Regular Expressions of L++

● `integer := (0|1|2|3|4|5|6|7|8|9)+`

# Regular Expressions of L++

- `integer := (0|1|2|3|4|5|6|7|8|9)+`
- `operator := +|*`

# Regular Expressions of L++

- `integer := (0|1|2|3|4|5|6|7|8|9)+`
- `operator := +|*`
- `lparen := \"`

# Regular Expressions of L++

- `integer := (0|1|2|3|4|5|6|7|8|9)+`
- `operator := +|*`
- `lparen := \(`
- `rparen := \)`

# Regular Expressions of L++

- `integer := (0|1|2|3|4|5|6|7|8|9)+`
- `operator := +|*`
- `lparen := \(`
- `rparen := \)`
- `invalid := anything else.`



# L++ DFA

