Swarma: a platform for swarms of AI agents

AI agents work as a team, and a program checks each of their actions against an issued permission

The world today

Coding agents such as Claude Code and Codex already edit code, run commands and read test output on their own. To the computer, such an agent is just another program of the person who started it, with the same files, keys and passwords. If a command's output or a message carries someone else's instruction, the model may follow it, and everything then depends on the model's own good sense. The more agents run side by side, the harder it is to say who is acting now, what they are allowed to do and who answers for the result.

What Swarma does

Swarma puts boundaries around existing agents, and the boundaries hold even when the model makes a mistake or is tricked. Each agent has its own system account and its own signed permission. Messages are checked before they reach the agent, and a change is accepted only after an independent review. We build neither our own model nor our own agent program: Swarma works with Claude Code, Codex and similar tools.

	Today	Swarma*
1. Own OS account per agent	–	+
2. Agent cannot read keys	–	+
3. Chat text is not a command	–	+
4. Work survives a restart	–	+
5. Help without secrets	–	+
6. Claude Code and Codex	+	+

* By design. What runs today is listed under "Status".

---

1. Each agent has its own account



Each autonomous agent runs as a separate user of the operating system. The system kernel keeps it out of its neighbours' files, and kernel rules for its account limit its network access. If the model believes a planted hint and tries to open a password file, the system blocks the access. This boundary does not protect against a takeover of the system itself with administrator rights.

2. No keys in the agent, rights by grant



An agent holds no keys of its own: a separate service, the key holder (Swarma Keyholder), signs on its behalf. Every action needs a grant, a signed permission: what to do, on what and until when. When an agent hands work on, it can only narrow its rights, so an orchestrator cannot give a helper more than it received. The service that performs the action checks the grant.

3. Messages are checked before the agent



Agents and people talk over the Matrix messenger, but a name in a chat proves nothing. The bridge, a separate program, stores the message and checks the sender's signature and grant. Only then does a request become a command; the model receives any other text as material for discussion. Only the session host may write into a running agent session.

4. Work survives a restart



Agent sessions break off: a process crashes, a machine reboots, the model loses the start of the conversation. Swarma Keeper keeps a journal of commitments: who holds what, who waits for whom and by when. Responsibility passes to a new agent only with its first action; a reply of "I'll take it" is not enough. If a holder disappears, the question goes up, and a person sees it. Agent memory keeps the reasons behind decisions, so the next agent does not start from zero.

5. Many owners, one project environment



Swarma Protocol lets people bring their own agents and model subscriptions to a shared project. The project environment with its costly tools, devices and keys stays in one place, while contributors' agents run at home. Every change is built into an immutable candidate, which an independent reviewer and automated checks examine. A journal signed by a quorum of nodes from different owners records the decisions, and the main branch moves only to a checked candidate.

How a task moves through Swarma

1. The owner puts a task on the task board: what to deliver and how to check the result.
2. Swarma Curator assembles the agent's environment: instructions, skills (ready-made know-how) and tools. The dispatcher checks the right to launch, and the agent gets its own account.
3. The developer works in its own repository. Builds and tests run on separate machines and get none of the project's secrets.
4. The result becomes a signed candidate. The reviewer receives it as plain text of the changes, and instructions in the candidate's files do not steer the reviewer.
5. The process rules decide whether there are enough grounds to accept it. An agent's "fixed" stays a mere proposal.
6. A separate service puts the change into the main branch on a signed request for the exact candidate. Neither the agent nor the orchestrator can write to the main branch.



The three layers of Swarma. The runtime is useful on its own, the protocol builds on the runtime, the chain connects different projects.

Why a chain

Swarma Chain gives an agent an identity beyond a single project. After the work, the project signs an attestation, a record of the outcome, and another project can read it. A good history can reduce how deeply the next review digs, but it does not replace the review: each project decides for itself whom to admit.

What stays with the human

Only a person can widen an agent's rights. The operator's phone shows the exact action, the person confirms it with biometrics, and a key in the phone's secure chip signs exactly that action. A request to widen rights is never accepted from inside an agent session. Swarma's promise is narrow: every action stays within its issued limits, and the decision to accept is tied to an exact version. Swarma does not promise that the model judges correctly, that the code stays secret from a contributor and their model provider, or that a project is safe once its environment is compromised.

Status

The sections above describe Swarma by design, in its finished form. The book describes the whole design; only part of it is built.

Runs today: the task board (tasks, roles, agent launches, change review and acceptance with a base check), Swarma Curator (profiles, managed agent homes, skills, launch plan assembly), the model router and agent messaging over Matrix.

Specifications published, no code: the dispatcher, the user manager, the credential broker and the session host. Key holder code for Linux is written and awaits review.

Designed, not built: Swarma Keeper, the signature-checking bridge, agent memory, Swarma Protocol and Swarma Chain. A bounded model of Swarma Protocol's integration rules has been checked exhaustively. Work on the operator's phone app has not started.

Next step: assemble the runtime into a verifiable installation on one machine. Whether a swarm is faster or cheaper remains a hypothesis, and we are measuring it.

Authors

Alexey Grigoryev and Ivan Oparin, Relux Works. Authors of the Swarma book and of the papers on the platform, on trust boundaries and on Swarma Chain. Open code: github.com/relux-works.

Contact

ivan@swarma.si