n, m, i, j Index variables for meta-lists

num, numZero, numOne Numeric literals

nat

hex Bit vector literal, specified by C-style hex number bin Bit vector literal, specified by C-style binary number

string String literals

regexp Regular expresions, as a string literal

real number literal

value

 $egin{array}{lll} x, \ y, \ z & & \mbox{identifier} \\ ix & & \mbox{infix identifier} \\ \end{array}$

q Index variables for meta-lists

 $\begin{array}{ll} \overrightarrow{ctor} & \text{Constructor} \\ x, \ y, \ z, \ x, \ f, \ ka & \text{Identifier} \\ bit & \text{Bit} \end{array}$

 $\begin{array}{ccc} u & & & \text{Mutable Variables} \\ \beta & & & \text{Base type variables} \end{array}$

 $tid \hspace{35mm} \textbf{Type ID}$

```
l
                                                source location
               ::=
annot
               ::=
                                                kinded IDs: Type, Int, and Order variables
kid
                     'x
kind
                                                base kind
               ::=
                                                  kind of types
                     Type
                                                  kind of natural number size expressions
                     Int
                                                  kind of vector order specifications
                     Order
                     Bool
                                                  kind of constraints
                                                numeric expression, of kind Int
nexp
                     id
                                                  abbreviation identifier
                                                  variable
                     kid
                                                  constant
                     num
                     id(nexp_1, \ldots, nexp_n)
                                                  app
                     nexp_1 * nexp_2
                                                  product
                                                  sum
                     nexp_1 + nexp_2
                     nexp_1 - nexp_2
                                                  subtraction
                     2 \uparrow nexp
                                                  exponential
                                                  unary negation
                     -nexp
                                            S
                     (nexp)
                                           Μ
                     nexp_1 + ... + nexp_n
                                                vector order specifications, of kind Order
order
                     kid
                                                  variable
                     inc
                                                  increasing
                     \operatorname{dec}
                                                  decreasing
                                           S
                     (order)
base\_effect
                                                effect
                                                  read register
                     rreg
                                                  write register
                     wreg
                                                  read memory
                     rmem
                                                  read memory and tag
                     rmemt
                     wmem
                                                  write memory
                                                  signal effective address for writing memory
                     wmea
                                                  determine if a store-exclusive (ARM) is going to succeed
                     exmem
                                                   write memory, sending only value
                     wmv
                                                  write memory, sending only value and tag
                     wmvt
                     barr
                                                  memory barrier
                                                  dynamic footprint
                     depend
                     undef
                                                  undefined-instruction exception
                                                  unspecified values
                     unspec
                     nondet
                                                  nondeterminism, from nondet
```

		escape config		potential exception configuration option
effect	::= 	$\{\mathit{base_effect}_1,,\mathit{base_effect}_n\}$ pure	М	effect set sugar for empty effect set
typ	::=			type expressions, of kind Type
		$\begin{array}{l} id \\ kid \\ (typ_1, \dots, typ_n) \rightarrow typ_2 \textbf{effect} effect \\ typ_1 \leftrightarrow typ_2 \textbf{effect} effect \\ (typ_1, \dots, typ_n) \\ id(typ_arg_1, \dots, typ_arg_n) \\ (typ) \\ \{kinded_id_1 \dots kinded_id_n, n_constraint.typ\} \\ typ_{exp} \\ typ_{lexp} \\ typ_{pat} \\ \textbf{sigma} (typ) \end{array}$	S M M M	defined type type variable Function (first-order only) Mapping Tuple type constructor application
typ_arg	::=			type constructor arguments of
		$nexp$ typ $order$ $n_constraint$		
$n_constraint,\ ncons$::= 	$nexp \equiv nexp'$ $nexp \geq nexp'$ $nexp \leq nexp'$ $nexp \leq nexp'$ $nexp < nexp'$ $nexp! = nexp'$ $kid \ IN \{num_1,, num_n\}$ $n_constraint \land n_constraint'$ $n_constraint n_constraint'$ $id(typ_arg_0,, typ_arg_n)$ kid $true$ $false$		constraint over kind Int
$kinded_id$::= 	$kind \ kid$ kid	S	optionally kind-annotated idea kind-annotated variable
$quant_item$::=			kinded identifier or Int constr

optionally kinded identifier

 $kinded_id$

```
n\_constraint
                                                                   constraint
                         kinded\_id_0 \dots kinded\_id_n
typquant
                                                                 type quantifiers and constraints
                   ::=
                         \forall quant\_item_1, ..., quant\_item_n.
                                                                   empty
typschm
                                                                 type scheme
                         typquant typ
type\_def
                   ::=
                         type\_def\_aux
type\_def\_aux
                                                                 type definition body
                   ::=
                         type id typquant = typ_arg
                                                                   type abbreviation
                         typedef id = \mathbf{const} \mathbf{struct} typquant\{typ_1 id_1; ...; typ_n id_n;^?\}
                                                                   struct type definition
                         typedef id = const union typquant\{type\_union_1; ...; type\_union_n;^?\}
                                                                   tagged union type definition
                         typedef id = \text{enumerate} \{id_1; ...; id_n; ?\}
                                                                   enumeration type definition
                         bitfield id: typ = \{id_1: index\_range_1, ..., id_n: index\_range_n\}
                                                                   register mutable bitfield type definition
type\_union
                                                                 type union constructors
                   ::=
                         typ id
index\_range
                                                                 index specification, for bitfields in register types
                                                                   single index
                         nexp
                                                                   index range
                         nexp_1..nexp_2
                         index\_range_1, index\_range_2
                                                                   concatenation of index ranges
lit
                                                                 literal constant
                   ::=
                         ()
                         bitzero
                         bitone
                         true
                         false
                                                                   natural number constant
                         num
                         hex
                                                                   bit vector constant, C-style
                         bin
                                                                   bit vector constant, C-style
                         string_1
                                                                   string constant
                         undefined
                                                                   undefined-value constant
                         real
                                                                 optional semi-colon
                   ::=
```

```
::=
typ\_pat
                                                                                                          type pattern
                                      kid
                                      id(typ\_pat_1, ..., typ\_pat_n)
                                                                                                          pattern
pat
                                      lit
                                                                                                             literal constant pa
                                                                                                             wildcard
                                      pat_1|pat_2
                                                                                                             pattern disjunctio
                                      \sim pat
                                                                                                             pattern negation
                                      (pat \mathbf{as} id)
                                                                                                             named pattern
                                      (typ)pat
                                                                                                             typed pattern
                                                                                                             identifier
                                      id
                                      pat\ typ\_pat
                                                                                                             bind pattern to ty
                                                                                                             union constructor
                                      id(pat_1, ..., pat_n)
                                      [pat_1, \ldots, pat_n]
                                                                                                             vector pattern
                                                                                                             concatenated vect
                                      pat_1@...@pat_n
                                      (pat_1, \ldots, pat_n)
                                                                                                             tuple pattern
                                      [||pat_1, \dots, pat_n||]
                                                                                                             list pattern
                                                                                                     S
                                      (pat)
                                                                                                             Cons patterns
                                      pat_1 :: pat_2
                                      pat_1 \uparrow \uparrow \dots \uparrow \uparrow pat_n
                                                                                                             string append pat
loop
                                ::=
                                      while
                                      until
internal\_loop\_measure
                                ::=
                                                                                                          internal syntax for a
                                      termination_measure \{exp\}
                                ::=
                                                                                                          expression
exp
                                      \{exp_1; \ldots; exp_n\}
                                                                                                             sequential block
                                      id
                                                                                                             identifier
                                      lit
                                                                                                             literal constant
                                      (typ)exp
                                                                                                             cast
                                      id(exp_1, ..., exp_n)
                                                                                                             function application
                                      exp_1 id exp_2
                                                                                                             infix function app
                                      (exp_1, \ldots, exp_n)
                                                                                                             tuple
                                                                                                             conditional
                                      if exp_1 then exp_2 else exp_3
                                      loop\ internal\_loop\_measure\ exp_1\ exp_2
                                      foreach (id from exp_1 to exp_2 by exp_3 in order) exp_4
                                                                                                             for loop
                                      [exp_1, \ldots, exp_n]
                                                                                                             vector (indexed fr
                                      exp[exp']
                                                                                                             vector access
                                       exp[exp_1..exp_2]
                                                                                                             subvector extracti
                                      [exp  with exp_1 = exp_2]
                                                                                                             vector functional
                                      [exp \mathbf{with} exp_1..exp_2 = exp_3]
                                                                                                             vector subrange u
                                       exp_1@exp_2
                                                                                                             vector concatenata
                                      [|exp_1, ..., exp_n|]
                                                                                                             list
                                                                                                             cons
                                       exp_1 :: exp_2
```

```
struct \{fexp_0, \dots, fexp_n\}
                                                                        struct
                         \{exp \mathbf{with} fexp_0, \dots, fexp_n\}
                                                                        functional update of struct
                                                                        field projection from struct
                         exp.id
                                                                        pattern matching
                         \mathbf{match}\ exp\{pexp_1, \dots, pexp_n\}
                         letbind \ \mathbf{in} \ exp
                                                                        let expression
                                                                        imperative assignment
                         lexp = exp
                         sizeof nexp
                                                                        the value of nexp at run time
                         {f return}\; exp
                                                                        return exp from current function
                                                                        halt all current execution
                         exit exp
                         \mathbf{ref}\ id
                         throw exp
                         try exp catch \{pexp_1, ..., pexp_n\}
                         \mathbf{assert}\left(exp,exp'\right)
                                                                        halt with error message exp' when not exp. exp
                                                                 S
                         (exp)
                         \mathbf{var} \ lexp = exp \ \mathbf{in} \ exp'
                                                                        This is an internal node for compilation that de
                         \mathbf{let} \ pat = exp \ \mathbf{in} \ exp'
                                                                        This is an internal node, used to distinguised so
                         \mathbf{return\_int}\,(\mathit{exp})
                                                                        For internal use to embed into monad definition
                                                                        For internal use in interpreter to wrap pre-evalu
                         value
                         constraint n_constraint
                                                                     lvalue expression
lexp
                  ::=
                         id
                                                                        identifier
                         deref exp
                         id(exp_1, ..., exp_n)
                                                                        memory or register write via function call
                         (typ)id
                         (lexp_0, ..., lexp_n)
                                                                        multiple (non-memory) assignment
                         lexp_1@\dots@lexp_n
                                                                        vector concatenation L-exp
                         lexp[exp]
                                                                        vector element
                         lexp[exp_1..exp_2]
                                                                        subvector
                                                                        struct field
                         lexp.id
fexp
                                                                     field expression
                         id = exp
opt\_default
                                                                     optional default value for indexed vector expressio
                  ::=
                         ; default = exp
                                                                     pattern match
pexp
                         pat \rightarrow exp
                         pat when exp_1 \rightarrow exp
tannot\_opt
                                                                     optional type annotation for functions
                         typquant\ typ
                                                                     optional recursive annotation for functions
rec\_opt
                                                                        non-recursive
                                                                        recursive without termination measure
                         rec
```

```
\{pat \rightarrow exp\}
                                                              recursive with termination measure
effect\_opt
                                                           optional effect annotation for functions
                  ::=
                                                              no effect annotation
                         \mathbf{effect}\ \mathit{effect}
pexp\_funcl
                  ::=
                         pat = exp
                         (pat \mathbf{when} exp_1) = exp
funcl
                  ::=
                                                           function clause
                         id pexp\_funcl
                                                           function definition
fundef
                  ::=
                         function rec\_opt\ tannot\_opt\ effect\_opt\ funcl_1 and ... and funcl_n
                                                           Mapping pattern. Mostly the same as normal patterns but of
mpat
                  ::=
                         lit
                         id
                         id(mpat_1, ..., mpat_n)
                         [mpat_1, ..., mpat_n]
                         mpat_1@\dots@mpat_n
                         (mpat_1, \ldots, mpat_n)
                         [||mpat_1, \ldots, mpat_n||]
                                                       S
                         (mpat)
                         mpat_1::mpat_2
                         mpat_1 \uparrow \uparrow \dots \uparrow \uparrow mpat_n
                         mpat: typ
                         mpat as id
                  ::=
mpexp
                         mpat
                         mpat when exp
                                                           mapping clause (bidirectional pattern-match)
mapcl
                  ::=
                         \mathit{mpexp}_1 \leftrightarrow \mathit{mpexp}_2
                         mpexp \Rightarrow exp
                         mpexp \mapsto exp
                                                           mapping definition (bidirectional pattern-match function)
mapdef
                  ::=
                         mapping id \ tannot\_opt = \{mapcl_1, ..., mapcl_n\}
letbind
                                                           let binding
                  ::=
                         \mathbf{let} \ pat = exp
                                                              let, implicit type (pat must be total)
val\_spec
                  ::=
                         val\_spec\_aux
```

val_spec_aux	::= 	val typschm id val cast typschm id val extern typschm id val extern typschm id = string	S S S	value type specification specify the type of an upcoming definiti specify the type of an external function specify the type of a function from Lem
$default_spec$::=	${\bf default\ Order}\ order$		default kinding or typing assumption
$scattered_def$::=	$egin{align*} \mathbf{scattered function} \ rec_opt \ tannot_opt \ \end{bmatrix}$ function clause $funcl$ $\mathbf{scattered typedef} \ id = \mathbf{const union} \ id \ \mathbf{member} \ type_union \ \end{bmatrix}$ $\mathbf{scattered mapping} \ id : tannot_opt \ \mathbf{mapping clause} \ id = mapcl \ \mathbf{end} \ id \ \end{bmatrix}$		scattered function definition header scattered function definition clause
reg_id	::=	id		
$alias_spec$::=	$egin{aligned} reg_id.id \ reg_id[exp] \ reg_id[expexp'] \ reg_id: reg_id' \end{aligned}$		register alias expression forms
dec_spec	::= 	register effect effect' $typ \ id$ register configuration $id : typ = exp$ register alias $id = alias_spec$ register alias $typ \ id = alias_spec$		register declarations
prec	::= 	infix infixl infixr		
$loop_measure$::=	loop exp		
def	::=	$type_def$ $fundef$		top-level definition type definition function definition

```
mapdef
                                                                                                         mapping definition
                letbind
                                                                                                         value definition
                val\_spec
                                                                                                         top-level type cons
                fix prec num id
                                                                                                         fixity declaration
                overload id[id_1; ...; id_n]
                                                                                                         operator overload s
                default\_spec
                                                                                                         default kind and ty
                scattered\_def
                                                                                                         scattered function
                termination_measure id pat = exp
                                                                                                         separate termination
                termination_measure id\ loop\_measure_1, ..., loop\_measure_n
                                                                                                         separate termination
                dec\_spec
                                                                                                         register declaration
                fundef_1 ... fundef_n
                                                                                                         internal representa
                \$string_1 string_2 l
                                                                                                         compiler directive
defs
                                                                                                      definition sequence
          ::=
                def_1 \dots def_n
                                                                                                      Constraint logic grou
rv
          ::=
                num
                true
                {\bf false}
                ()
                bitstr
                (rv_1, rv_2)
                ctor tid rv
                \dot{ctor}\ tid\ b\ rv
                \mathbf{usort}\, rv
                                                                                                      RCL valuation
i
          ::=
                \epsilon
                x \to rv, i
b
          ::=
                                                                                                      Base Type
                int
                bool
                                                                                                         Type ID
                tid
                unit
                                                                                                         Bit vectors
                bvec
                b_1 * b_2
                bapp tid b
                                                                                       Μ
                |\tau|_b
                b_1[b_2/\beta]
                                                                                       Μ
                                                                                                      Refined Type
                \{x:b|\phi\}
                                                                                       bind x in \phi
                x:b[\phi]
                                                                                       bind x in \phi
                \tau[v/x]
                                                                                       Μ
                \tau[b/\beta]
                                                                                       Μ
```

S

 (τ)

```
\boldsymbol{A}
                                                                                              Dependent Function Type
           ::=
                  x:b[\phi] \to \tau
                                                                                              Expressions for constraints
ce
           ::=
                                                                                                  Value
                  v
                                                                                                  Addition
                  ce_1 + ce_2
                  va1 \leq va2
                                                                                                  Less than or equl
                  \mathbf{fst}\,ce
                                                                                                  Project first part of pair
                  \mathbf{snd}\,ce
                                                                                                  Project second part of pair
                  len ce
                                                                                                  Length of vector
                  ce_1@ce_2
                                                                                                  Bit vector concat
                  ce[v/x]
                                                                             Μ
                                                                                                  Substitution
                                                                             S
                  (ce)
                                                                                              Literals
                                                                                                  Numeric literal
                  n
                  {f T}
                                                                                                  true boolean literal
                  \mathbf{F}
                                                                                                  false boolean literal
                  ()
                                                                                                  Unit value
                   bin
                                                                                                  Bit vector
                                                                                              Values
                                                                                                  Immutable variable
                  \boldsymbol{x}
                  l
                                                                             Μ
                                                                                                  Substitution
                  v_1[v_2/x]
                  (v)
                                                                             S
                  (v_1,v_2)
                                                                                                  Value pair
                  \dot{ctor} tid v
                                                                                                  Data constructor
                  \dot{ctor} tid[b]v
                                                                                                  Data constructor for polymorphic ty
def
                                                                                              Definitions
            | \operatorname{val} f: (x:b[\phi]) \to \tau
                                                                             bind x in \tau
                                                                             bind x in \phi
                  \operatorname{val} \forall \beta. f : (x : b[\phi]) \to \tau
                                                                             bind x in \tau
                                                                             bind x in \phi
                  function f(x) = s
                                                                             bind x in s
                  function f(x) = s
                                                                             bind x in s
                  union tid = \{ctor_1 : \tau_1, ..., ctor_n : \tau_n\}
union tid = \forall \beta. \{ctor_1 : \tau_1, ..., ctor_n : \tau_n\}
                                                                                              Program
           ::=
p
                  def_1; ...; def_n; ; s
Γ
                                                                                               Variable type context
                                                                                                  Empty context
                  x:b[\phi]
                  \Gamma, x : b[\phi]
                                                                             S
```

```
\mathbf{effect}
{\bf consistent\_increase}
consistent\_decrease
                                        Identifier
(\,\mathbf{operator}\,x)\\\mathbf{bool}
                                           remove infix status
```

id

S

```
S
               \mathbf{not}
                                       S
               atom
                                       S
               real
                                       S
               string
                                       S
               bitvector
                                       S
               bit
                                       S
               unit
                                       S
               exception
                                       S
               int
                                       S
               list
                                       S
               vector
                                       S
               register
                                       S
               range
               range
               atom\_bool
               add\_range
               {\bf split\_vector}
               vector\_append
               vector\_access
               {\bf vector\_update}
               vector_subrange
               \mathbf{fst}
               \mathbf{snd}
               len
               +
               \leq
E
        ::=
               E, id: typ
                                       Μ
               E_{exp}
                                       Μ
               E_{pat}
               E_{pexp}
                                       Μ
M
               M, kid \rightarrow ce
                                            Expressions
        ::=
                                               Value
               v
                                               Mutable Variable
               u
                                               Function Application
               fv
                                               Polymorphic Function Application
                                               Addition
               v_1 + v_2
                                               Less than or equal
               v_1 \leq v_2
               v_1 = v_2
                                               Project first part of pair
               \mathbf{fst} v
               \operatorname{\mathbf{snd}} v
                                               Project second part of pair
               \mathbf{len}\,e
               v_1@v_2
```

```
split v_1 v_2
                                                                                                        Split vector
                                                                                 S
                 (e)
                 e[v/x]
                                                                                 Μ
                                                                                                        Substitution
                 eqand v_1 v_2 v_3
                                                                                                     Statement
                 \mathbf{let}\, x = e\, \mathbf{in}\, s
                                                                                 \mathsf{bind}\;x\;\mathsf{in}\;s
                                                                                                        Let binding
                 let x : \tau = s_1 in s_2
                                                                                 bind x in s_2
                                                                                                        Let binding with type annotation
                 if v then s_1 else s_2
                                                                                                        If-then-else
                                                                                                        Substitution
                                                                                 Μ
                 match v of c\dot{tor}_1 x_1 \Rightarrow s_1, \dots, c\dot{tor}_n x_n \Rightarrow s_n
                                                                                                        Match statement
                 \mathbf{var}\,u:\tau:=v\,\mathbf{in}\,s
                                                                                 \mathsf{bind}\; u \; \mathsf{in}\; s
                                                                                                        Declaration and scoping of mutable
                                                                                                        Assignment to mutable variable
                 u := v
                 while (s_1) do \{s_2\}
                                                                                                        While loop
                                                                                                        Statement sequence
                 s_1; s_2
                 abort
                 \mathbf{assert}\,\phi\,\mathbf{in}\,s
                                                                                 S
                 (s)
                                                                                 S
                 \{s\}
                 s[b/\beta]
                                                                                 Μ
                 L[s]
                                                                                 Μ
                 L[[s]]
                                                                                 Μ
                 switch x\{lp_1 \Rightarrow s_1 | \dots | lp_n \Rightarrow s_n\}
                                                                                 Μ
                 unpack x into x_1, \ldots, x_n in s
                                                                                 Μ
                                                                                                     Small context
                 x : \tau
                 \gamma_1, \gamma_2
L
         ::=
                \mathbf{let}\,x=e\,\mathbf{in}\,L
                let x : \tau = s_1 in ___
                L_1[L_2] 
 L_1 + \dots + L_n
                                                                                 Μ
                                                                                 Μ
                                                                                 S
                                                                                                    Literals for patterns. Augmenting wit
lp
         ::=
                 l
                                                                                                     Pattern branch
                 pat_1 ... pat_n \Rightarrow exp
(\pi)
                                                                                                        patterns and associated term varial
                                                                                 S
```

```
Π
                                                                                                                           Pattern matrix
                               \pi_1, \ldots, \pi_n
                               \pi, \Pi
                                                                                                                           Refinement Constraints - Quntifier fr
                               \perp
                               \phi_1 \wedge \phi_2
                               ce_1 = ce_2
                               ce_1 \le ce_2
                                                                                                                   S
                               (\phi)
                               \phi[v/x]
                                                                                                                   Μ
                               \phi_1 \Longrightarrow \phi_2
                               \phi_1 \wedge ... \wedge \phi_n
                               \phi[ce/x]
                               \phi[ce_1/x_1 \dots ce_n/x_n]
mut
                      ::=
                               mutable
                               immutable
formula
                               judgement
                              formula_1 .. formula_n
                               x:b[\phi]\in\Gamma
                               u:\tau\in\Delta
                               union tid = \{ctor_1 : \tau_1, ..., ctor_n : \tau_n\} \in \Theta
                               union tid = \forall \beta. \{ctor_1 : \tau_1, ..., ctor_n : \tau_n\} \in \Theta
                               x \in \text{dom}(\Gamma)
                               \mathbf{val}\, f: (x:b[\phi]) \to \tau \,\not\in\, \Phi
                               \operatorname{val} f: (x:b[\phi]) \to \tau \in \Phi
                               \operatorname{val} \forall \beta. f : (x : b[\phi]) \to \tau \in \Phi
                               function f(x) = s \notin \Phi
                               function f(x) = s \in \Phi
                               f \in \text{dom}(\Phi)
                               u \in \mathrm{dom}(\Delta)
                               tid \notin \Phi
                               \dot{ctor} \notin \Phi
                               f \notin \Phi
                               f \notin \mathrm{dom}(\Phi)
                               u \notin \mathrm{dom}(\delta)
                               u\notin\mathrm{dom}(\Delta)
                               x \notin \text{dom}(\Gamma)
                               tid \notin dom(\Theta)
                               distinct ctor_1 \dots ctor_n
                               \overrightarrow{ctor}_1 \dots \overrightarrow{ctor}_n \not\in \Theta
                               v_1 + v_2 = v
                               v_1 \le v_2 = v
```

```
\mathbf{len}\,v_1=v_2
v_1@v_2 = v_3
v_1 = \mathbf{split} \, v_2 \, v_3
f x = e
x_1 = x_2
x_1 \neq x_2
x\#e
x\#\Gamma
x \, \mathbf{fresh}
v = \delta(u)
\delta' = \delta[u \mapsto v]
\delta = u_1 \to v_1, \dots, u_n \to v_n
\Delta = u_1 : \tau_1, \dots, u_n : \tau_n
\beta \in B
\forall i.\Theta; \Gamma \vdash i \wedge i \models \Gamma \longrightarrow i \models \phi
rv = i(x)
rv = rv_1 + rv_2
rv = rv_1 \le rv_2
rv = rv_1@rv_2
rv = \operatorname{len} rv'
rv = (rv_1 = rv_2)
rv = rv_1 \lor rv_2
rv = rv_1 \wedge rv_2
rv = rv_1 \Longrightarrow rv_2
rv = \sim rv_1
id \sim x
id \sim u
E \vdash id \leadsto ctor, tid
id \sim tid
lp \not\in lp_1 \dots lp_n
id \in E.mutable
id \in E.immutable
id \in E.enum
id \in E.ctor
id/mut: typ \in E
id/\mathbf{register}: typ \in E
id/\mathbf{enum}: typ \in E
id/mut \notin E
\mathbf{fresh}\,x
fresh x_1 \dots x_n
num = is\_constant ce
quant\_item_1, \dots, quant\_item_n \leadsto kinded\_id_1 \dots kinded\_id_m, n\_constraint
b \in \{ \mathbf{int}, \mathbf{bool} \}
is\_ctor b
b=(b_1,\ldots,b_n)
fresh x_1 \dots x_n
pat_1 ... pat_n = duplicate pat b_1 ... b_m
kind_1 = kind_2
kind_1 \neq kind_2
kid = ka
```

```
M' = M, ce, kinded_{-}id_1 ... kinded_{-}id_m
                                     is\_kid\_map M', b, ce, kinded\_id_1 .. kinded\_id_m
                                     ce = M(kid)
                                     id_1 \dots id_n \leadsto f
                                     E \vdash \mathbf{inst\_of}\ id(exp_1, ..., exp_n) \leadsto x; L
                                     L_5 = \mathbf{let} \, x_4 = \mathbf{update\_vector\_range} \, x \, x_1 \, x_2 \, x_3 \, \mathbf{in} \, \_
rcl
                            ::=
                                     [l] \sim rv
                                     i[v] \sim rv
                                     i[ce] \sim rv
                                     i\llbracket\phi\rrbracket\sim rv
                                     i \models \phi
                                     i \models \Gamma
                                     \Theta \vdash_{wf} rv : b
                                     \Theta; \Gamma \vdash i
                                     \Theta; B; \Gamma \models \phi
wf\_check
                            ::=
                                     \vdash_{wf} \Theta
                                                                                                                                          Wellformedness for type def
                                     \Theta; B \vdash_{wf} b
                                                                                                                                          Wellformedness for base-typ
                                     \Theta \vdash_{wf} \Phi
                                                                                                                                          Wellformedness for function
                                     \Theta; B \vdash_{wf} \Gamma
                                                                                                                                          Wellformedness for immutal
                                     \Theta; B; \Gamma \vdash_{wf} \Delta
                                                                                                                                          Wellformedness for mutable
                                     \Theta; B; \Gamma \vdash_{wf} v : b
                                                                                                                                          WF for values
                                     \Theta; \Phi; B; \Gamma; \Delta \vdash_{wf} e : b
                                                                                                                                          WF for expressions
                                     \Theta; B; \Gamma \vdash_{wf} \phi
                                                                                                                                          WF for constraints
                                     \Theta; B; \Gamma \vdash_{wf} \tau
                                                                                                                                          WF for types
                                     \Theta; \Phi; B; \Gamma; \Delta \vdash_{wf} s : b
                                                                                                                                          WF for statements
extension
                                     \Theta; B \vdash \Gamma_1 \sqsubseteq \Gamma_2
                                                                                                                                          \Gamma_2 is an extension of \Gamma_1
                                     \Theta; B; \Gamma \vdash \Delta_2 \sqsubseteq \Delta_1
                                                                                                                                          \Delta_1 is an extension of \Delta_2
subtype\_anf
                                     \Theta; B; \Gamma \vdash \tau_1 \lessapprox \tau_2
                                                                                                                                          Subtyping
typing
                                     \vdash l \Rightarrow \tau
                                                                                                                                          Type synthesis for literals.
                                     \Theta; B; \Gamma \vdash v \Rightarrow \tau
                                                                                                                                          Type synthesis. Infer that t
                                     \Theta; B; \Gamma \vdash v \leq \tau
                                                                                                                                          Check that type of v is \tau
                                     \Theta; \Phi; B; \Gamma; \Delta \vdash e \Rightarrow \tau
                                                                                                                                          Infer that type of e is \tau
                                     \Theta; \Phi; B; \Gamma; \Delta \vdash e \leq \tau
                                                                                                                                          Check that type of e is \tau
                                     \Theta; \Phi; B; \Gamma; \Delta \vdash s \leq \tau
                                                                                                                                          Check that type of s is \tau
                                     \Theta_1; \Phi_1 \vdash def_1 ... def_n \leadsto \Theta_2; \Phi_2
                                     \vdash p
                                     \Theta \vdash \Delta \sim \delta
                                     \Theta; \Phi; \Delta \vdash (\delta, s) \leq \tau
                                                                                                                                          Program state typing judger
```

```
reduction
                                        ::=
                                                 \Phi \vdash \langle \delta, s_1 \rangle \rightarrow \langle \delta', s_2 \rangle
                                                                                                                                                           One step reduction
                                                  \Phi \vdash \langle \delta_1, s_1 \rangle \xrightarrow{*} \langle \delta_2, s_2 \rangle
                                                                                                                                                           Multi-step reduction
check_config
                                        ::=
                                                  \Theta \vdash \delta \sim \Delta
                                                  \Theta; \Phi; \Delta \vdash (\delta, s) \leq \tau
record
                                        ::=
                                                  E \vdash \mathbf{pack\_record} \ \tau \ x \ id_1 = x_1 \dots id_n = x_n \leadsto L
                                                  E \vdash \mathbf{unpack\_field} \ \tau \ x \ x' \ id \leadsto L
                                                  E \vdash \mathbf{update\_record} \ \tau \ x \ x' \ id_1 = x_1 \dots id_n = x_n \leadsto L
wf_{-}l
                                        ::=
                                          \Theta; \Phi; B; \Gamma; \Delta \vdash_{wf} L : \gamma
                                                                                                                                                           WF for let-context
convert\_typ
                                        ::=
                                                  typquant \rightsquigarrow kinded\_id_1 ... kinded\_id_m, n\_constraint
                                                  E \vdash typ \leadsto \tau
                                                  E; M \vdash typ\_arg \leadsto \phi
                                                  E; M \vdash typ\_arg \leadsto ce
                                                  E; M \vdash typ; ce \leadsto b; \phi
                                                  E; M \vdash n\_constraint \leadsto \phi
                                                  E; M \vdash nexp \leadsto ce
convert\_exp
                                                  lit \leadsto lp
                                                  lit \leadsto l
                                                  E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                                  E \vdash exp : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x; L : \tau
                                                  E \vdash exp: typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s: \tau
                                                  E \vdash \Pi : b_1/x_1 ... b_n/x_n \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau
                                                                                                                                                           Convert match branch
pattern\_expansion
                                        ::=
                                                  E \vdash x_1; x_2; pat_1, \dots, pat_n \leadsto L; x_3
                                                  E \vdash \Pi \leadsto \Pi_1; lp_1 || ... || \Pi_n; lp_n
                                                  E \vdash \Pi \leadsto \Pi_1; \dot{ctor}_1 b_1 x_1 || ... || \Pi_n; \dot{ctor}_n b_n x_n
                                                  E \vdash \Pi : b \leadsto \Pi'; b_1/x_1 ... b_n/x_n
convert\_defs
                                                  E \vdash funcl_1 \text{ and } ... \text{ and } funcl_n \leadsto \Theta; \Phi; \Delta \vdash def
                                                  E \vdash def \leadsto \Theta; \Phi; \Delta \vdash def_1, ..., def_n
                                                  E \vdash def_1 ... def_n \leadsto \Theta; \Phi \vdash def_1 ... def_m
judgement
                                                  rcl
                                                  wf\_check
                                                  extension
                                                  subtype\_anf
```

```
typing
                          reduction
                          check\_config
                          record
                          wf_{-}l
                          convert\_typ
                          convert\_exp
                          pattern\_expansion
                          convert\_defs
user\_syntax
                          n
                          num
                          nat
                          hex
                          bin
                          string
                          regexp
                          real
                          value
                          \boldsymbol{x}
                          ix
                          \dot{\mathop{ctor}^q}
                          \boldsymbol{x}
                          bit
                          u
                          β
                          tid
                          l
                          annot
                          kid
                          kind
                          nexp
                          order
                          base\_ef\!fect
                          effect
                          typ
                          typ\_arg
                          n\_constraint
                          kinded\_id
                          quant\_item
                          typquant
                          typschm
                          type\_def
                          type\_def\_aux
                          type\_union
                          index\_range
                          lit
                          ;?
```

```
typ\_pat
pat
loop
internal\_loop\_measure
exp
lexp
fexp
opt\_default
pexp
tannot\_opt
rec\_opt
\mathit{effect\_opt}
pexp\_funcl
funcl
fundef
mpat
mpexp
mapcl
mapdef
letbind
val\_spec
val\_spec\_aux
default\_spec
scattered\_def
reg\_id
alias\_spec
dec\_spec
prec
loop\_measure
def
defs
rv
i
b
\tau
A
ce
l
v
def
p
Γ
Φ
\Delta
Θ
B
\pi
\delta
terminals
id
```

 $egin{array}{c|c} E \ M \ & e \ & s \ & \gamma \ & L \ & lp \ & \pi \ & \Pi \ & \phi \ & mut \ & formula \end{array}$

1 Syntax

The syntax ...

2 MiniSail type system

2.1 Refinement constraint logic

 $[\![l]\!] \sim rv$

 $i[\![v]\!] \sim rv$

$$\frac{\llbracket l \rrbracket \sim rv}{i \llbracket l \rrbracket \sim rv} \quad \text{EVAL_V_LIT}$$

$$\frac{rv = i(x)}{i \llbracket x \rrbracket \sim rv} \quad \text{EVAL_V_VAR}$$

$$\frac{i \llbracket v_1 \rrbracket \sim rv_1}{i \llbracket v_2 \rrbracket \sim rv_2} \quad \text{EVAL_V_PAIR}$$

$$\frac{i \llbracket v_1 \rrbracket \sim rv}{i \llbracket (v_1, v_2) \rrbracket \sim (rv_1, rv_2)} \quad \text{EVAL_V_PAIR}$$

$$\frac{i \llbracket v \rrbracket \sim rv}{i \llbracket ctor\ tid\ v \rrbracket \sim ctor\ tid\ rv} \quad \text{EVAL_V_CONS}$$

$$\frac{i \llbracket v \rrbracket \sim rv}{i \llbracket ctor\ tid \llbracket b \rrbracket v \rrbracket \sim ctor\ tid\ b rv} \quad \text{EVAL_V_CONSP}$$

 $i \llbracket ce \rrbracket \sim rv$

$$\frac{i\llbracket v\rrbracket \sim rv}{i\llbracket v\rrbracket \sim rv} \quad \text{EVAL_CE_VAL}$$

$$\frac{i\llbracket v_1\rrbracket \sim rv_1}{i\llbracket v_2\rrbracket \sim rv_2}$$

$$\frac{rv = rv_1 + rv_2}{i\llbracket v_1 + v_2\rrbracket \sim rv} \quad \text{EVAL_CE_PLUS}$$

$$\frac{i\llbracket v_1\rrbracket \sim rv_1}{i\llbracket v_2\rrbracket \sim rv_2}$$

$$\frac{rv = rv_1 \leq rv_2}{i\llbracket va1 \leq va2\rrbracket \sim rv} \quad \text{EVAL_CE_LEQ}$$

$$\frac{i\llbracket v_1\rrbracket \sim rv_1}{i\llbracket fst\left(v_1,v_2\right)\rrbracket \sim rv_1} \quad \text{EVAL_CE_SND}$$

$$\frac{i\llbracket v_2\rrbracket \sim rv_2}{i\llbracket snd\left(v_1,v_2\right)\rrbracket \sim rv_2} \quad \text{EVAL_CE_SND}$$

$$\frac{i\llbracket v_1\rrbracket \sim rv_1}{i\llbracket v_2\rrbracket \sim rv_2} \quad \text{EVAL_CE_SND}$$

$$\frac{i\llbracket v_1\rrbracket \sim rv_1}{i\llbracket v_2\rrbracket \sim rv_2} \quad \text{EVAL_CE_SND}$$

$$\frac{i\llbracket v_1\rrbracket \sim rv_1}{i\llbracket v_2\rrbracket \sim rv_2} \quad \text{EVAL_CE_CONCAT}$$

$$\frac{i\llbracket v_1\rrbracket \sim rv'}{i\llbracket v_1\rrbracket \sim rv'} \quad \text{EVAL_CE_CONCAT}$$

$$\frac{i\llbracket v\rrbracket \sim rv'}{i\llbracket v_1\rrbracket \sim rv} \quad \text{EVAL_CE_LEN}$$

 $i[\![\phi]\!] \sim rv$

$$i \llbracket ce_1 \rrbracket \sim rv_1$$

$$i \llbracket ce_2 \rrbracket \sim rv_2$$

$$rv = (rv_1 = rv_2)$$

$$i \llbracket ce_1 = ce_2 \rrbracket \sim rv$$

$$i \llbracket \phi_1 \rrbracket \sim rv_1$$

$$i \llbracket \phi_2 \rrbracket \sim rv_2$$

$$rv = rv_1 \wedge rv_2$$

$$i \llbracket \phi_1 \wedge \phi_2 \rrbracket \sim rv$$

$$i \llbracket \phi_1 \rrbracket \sim rv'$$

$$rv = \sim rv'$$

$$i \llbracket \phi_1 \rrbracket \sim rv$$

$$i \llbracket \phi_1 \rrbracket \sim rv$$

$$i \llbracket \phi_2 \rrbracket \sim rv$$

$$rv = rv_1 \implies rv_2$$

 $i \models \phi$

$$\frac{i\llbracket\phi\rrbracket \sim \mathbf{true}}{i \models \phi} \quad \text{SATIS_CA_CA}$$

 $i \models \Gamma$

$$\begin{aligned} & \overline{i \models \cdot} & \text{SATIS_G_NIL} \\ & i \models \Gamma \\ & i \models \phi \\ & \overline{i \models \Gamma, x : b[\phi]} & \text{SATIS_G_CONS} \end{aligned}$$

 $\Theta \vdash_{wf} rv : b$

$$\overline{\Theta \vdash_{wf} \mathit{num} : \mathbf{int}} \quad \text{WF_RCL_V_INT}$$

$$\overline{\Theta \vdash_{wf} \mathbf{true} : \mathbf{bool}} \quad \text{WF_RCL_V_TRUE}$$

$$\Theta \vdash_{wf} \mathbf{false} : \mathbf{bool}$$
 WF_RCL_V_FALSE

$$\Theta \vdash_{wf} () : \mathbf{unit}$$
 WF_RCL_V_UNIT

$$\overline{\Theta \vdash_{wf} \mathbf{bitstr} : \mathbf{bvec}} \quad \text{WF_RCL_V_BVEC}$$

$$\frac{\Theta \vdash_{wf} rv_1 : b_1}{\Theta \vdash_{wf} rv_2 : b_2} \frac{}{\Theta \vdash_{wf} (rv_1, rv_2) : b_1 * b_2} \quad \text{WF_RCL_V_PAIR}$$

$$\frac{\Theta \vdash_{wf} rv : b}{\mathbf{union} \ tid = \{ \overrightarrow{ctor_i} : \tau_i^{\ i} \} \in \Theta} \\ \frac{\Theta \vdash_{wf} \overrightarrow{ctor_j} \ tid \ rv : tid}{\Theta \vdash_{wf} \overrightarrow{ctor_j} \ tid \ rv : tid} \quad \text{WF_RCL_V_CONS}$$

$$\begin{array}{c} \Theta \vdash_{wf} rv : |\tau_{j}|_{b}[b_{2}/\beta] \\ \underline{ \begin{array}{c} \mathbf{union} \ tid = \forall \, \beta. \{ \, \overrightarrow{ctor_{i}} : \tau_{i}^{\ i} \, \} \, \in \, \Theta \\ \\ \Theta \vdash_{wf} \overrightarrow{ctor_{j}} \ tid \, b_{2} \ rv : \mathbf{bapp} \ tid \, b_{2} \end{array} } \quad \text{WF_RCL_V_CONSP}$$

$$\overline{\Theta \vdash_{wf} \mathbf{usort} \, rv : \beta} \quad \text{WF_RCL_V_BOXED}$$

 $\Theta; \Gamma \vdash i$

$$\begin{aligned} & \overline{\Theta; \cdot \vdash i} \quad \text{WF_VAL_EMPTY} \\ & rv = i(x) \\ & \underline{\Theta \vdash_{wf} rv : b} \\ & \underline{\Theta; \Gamma, x : b[\phi] \vdash i} \quad \text{WF_VAL_CONS} \end{aligned}$$

 $\Theta; B; \Gamma \models \phi$

$$\frac{\Theta; B; \Gamma \vdash_{wf} \phi}{\forall i.\Theta; \Gamma \vdash i \land i \models \Gamma \longrightarrow i \models \phi}$$
$$\Theta; B; \Gamma \models \phi$$
 VALID_VALID

2.2 Wellformedness

 $\vdash_{wf} \Theta$ Wellformedness for type definition context

 $\Theta; B \vdash_{wf} b$ Wellformedness for base-type

$$\frac{\vdash_{wf}\Theta}{\Theta;B\vdash_{wf}\mathbf{bool}} \quad \text{WF_B_BOOL}$$

$$\frac{\vdash_{wf}\Theta}{\Theta;B\vdash_{wf}\mathbf{int}} \quad \text{WF_B_INT}$$

$$\frac{\vdash_{wf}\Theta}{\Theta;B\vdash_{wf}\mathbf{unit}} \quad \text{WF_B_UNIT}$$

$$\frac{\vdash_{wf}\Theta}{\Theta;B\vdash_{wf}\mathbf{bvec}} \quad \text{WF_B_BVEC}$$

$$\frac{\Theta;B\vdash_{wf}b_1}{\Theta;B\vdash_{wf}b_2} \quad \text{WF_B_PAIR}$$

$$\frac{\Theta;B\vdash_{wf}b_2}{\Theta;B\vdash_{wf}b_1*b_2} \quad \text{WF_B_PAIR}$$

$$\frac{\vdash_{wf}\Theta}{\mathbf{union}\,tid} = \{ctor_1:\tau_1,...,ctor_n:\tau_n\} \in \Theta$$

$$\frac{\Theta;B\vdash_{wf}tid}{\Theta;B\vdash_{wf}\beta} \quad \text{WF_B_BVR}$$

 $\Theta \vdash_{wf} \Phi$ Wellformedness for function definition context

$$\begin{split} f \not\in \mathrm{dom}(\Phi) \\ \Theta; \cdot, \beta \vdash_{wf} b \\ \Theta; \cdot, \beta \vdash_{wf} x : b[\phi] \\ \Theta; \cdot, \beta; x : b[\phi] \vdash_{wf} \tau \\ \hline \Theta \vdash_{wf} \Phi, \mathbf{val} \, \forall \, \beta.f : (x : b[\phi]) \to \tau \end{split} \quad \text{WF_P_VALSPEC_POLY} \\ f \not\in \mathrm{dom}(\Phi) \\ \Theta; \cdot \vdash_{wf} b \\ \Theta; \cdot \vdash_{wf} x : b[\phi] \\ \hline \Theta; \cdot \vdash_{wf} x : b[\phi] \vdash_{wf} \tau \\ \hline \Theta \vdash_{wf} \Phi, \mathbf{val} \, f : (x : b[\phi]) \to \tau \end{split} \quad \text{WF_P_VALSPEC} \\ \frac{\vdash_{wf} \Theta}{\Theta \vdash_{wf}} \Phi, \mathbf{val} \, f : (x : b[\phi]) \to \tau \end{split}$$

 $\Theta; B \vdash_{wf} \Gamma$ Wellformedness for immutable variable context

$$\frac{\vdash_{wf} \Theta}{\Theta; B \vdash_{wf} \cdot} \quad \text{WF_G_EMPTY}$$

$$\begin{split} \Theta; B \vdash_{wf} \Gamma \\ \Theta; B \vdash_{wf} b \\ \Theta; B; \Gamma, x : b[\top] \vdash_{wf} \phi \\ \underline{x \notin \text{dom}(\Gamma)} \\ \Theta; B \vdash_{wf} \Gamma, x : b[\phi] \end{split} \quad \text{WF-G-CONS} \\ \Theta; B \vdash_{wf} \Gamma \\ \Theta; B \vdash_{wf} b \\ \underline{x \notin \text{dom}(\Gamma)} \\ \Theta; B \vdash_{wf} \Gamma, x : b[\top] \end{split} \quad \text{WF-G-CONS-TRUE} \\ \Theta; B \vdash_{wf} \Gamma \\ \Theta; B \vdash_{wf} b \\ \underline{x \notin \text{dom}(\Gamma)} \\ \Theta; B \vdash_{wf} b \\ \underline{x \notin \text{dom}(\Gamma)} \\ \Theta; B \vdash_{wf} b \\ \underline{x \notin \text{dom}(\Gamma)} \\ \Theta; B \vdash_{wf} \Gamma, x : b[\bot] \end{split}$$

$\Theta; B; \Gamma \vdash_{wf} \Delta$ Wellformedness for mutable variable context

$$\begin{split} &\frac{\Theta; B \vdash_{wf} \Gamma}{\Theta; B; \Gamma \vdash_{wf} \cdot} \quad \text{WF_D_EMPTY} \\ &\frac{\Theta; B; \Gamma \vdash_{wf} \Delta}{\Theta; B; \Gamma \vdash_{wf} \tau} \\ &\frac{u \notin \text{dom}(\Delta)}{\Theta; B; \Gamma \vdash_{wf} \Delta, u : \tau} \quad \text{WF_D_CONS} \end{split}$$

$\Theta; B; \Gamma \vdash_{wf} v : b$ WF for values

$$\begin{array}{c} \Theta; B \vdash_{wf} \Gamma \\ \hline x:b[\phi] \in \Gamma \\ \hline \Theta; B; \Gamma \vdash_{wf} x:b \end{array} \quad \text{WF-V-VAR} \\ \hline \frac{\Theta; B \vdash_{wf} \Gamma}{\Theta; B; \Gamma \vdash_{wf} n: \mathbf{int}} \quad \text{WF-V-NUM} \\ \hline \frac{\Theta; B \vdash_{wf} \Gamma}{\Theta; B; \Gamma \vdash_{wf} \mathbf{T}: \mathbf{bool}} \quad \text{WF-V-TRUE} \\ \hline \frac{\Theta; B \vdash_{wf} \Gamma}{\Theta; B; \Gamma \vdash_{wf} \mathbf{F}: \mathbf{bool}} \quad \text{WF-V-FALSE} \\ \hline \frac{\Theta; B \vdash_{wf} \Gamma}{\Theta; B; \Gamma \vdash_{wf} (): \mathbf{unit}} \quad \text{WF-V-UNIT} \\ \hline \frac{\Theta; B \vdash_{wf} \Gamma}{\Theta; B; \Gamma \vdash_{wf} (): \mathbf{tid}} \quad \text{WF-V-CONS} \\ \hline \frac{\Theta; B \vdash_{wf} \tau: [\tau_j]_b}{\Phi; B; \Gamma \vdash_{wf} \tau c tor_j t t d v: t i d} \quad \text{WF-V-CONS} \\ \hline \Theta; B; \Gamma \vdash_{wf} v: [\tau_j]_b [b_2/\beta] \\ \Theta; B \vdash_{wf} b_2 \\ \hline \mathbf{union} \ t i d = \forall \beta. \{ \overrightarrow{ctor_i}: \tau_i^{\ i} \} \in \Theta \\ \hline \Theta; B; \Gamma \vdash_{wf} c tor_j t i d [b_2] v: \mathbf{bapp} \ t i d \ b_2 \\ \hline \Theta; B; \Gamma \vdash_{wf} v_1: b_1 \\ \Theta; B; \Gamma \vdash_{wf} v_2: b_2 \\ \hline \Theta; B; \Gamma \vdash_{wf} (v_1, v_2): b_1 * b_2 \\ \hline \Theta; B; \Gamma \vdash_{wf} (v_1, v_2): b_1 * b_2 \\ \hline \end{array} \quad \text{WF-V-PAIR} \\ \hline \end{array}$$

$$\begin{array}{c} \Theta; \Phi; B; \Gamma; \Delta \vdash_{wf} e : b \\ \\ \Theta; B; \Gamma \vdash_{wf} \Delta \\ \Theta \vdash_{wf} \Phi \\ \Theta; B; \Gamma \vdash_{wf} v : b \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \Phi \vdash_{wf} \Phi \\ \Theta; B; \Gamma \vdash_{wf} \Delta \\ \Theta \vdash_{wf} \Phi \\ \Theta; B; \Gamma \vdash_{wf} \Delta \\ \Theta \vdash_{wf} \Phi \\ \Theta; B; \Gamma \vdash_{wf} v : b_1[b_2/\beta] \\ \hline val \forall \beta, f : (x : b[d]) \rightarrow \tau \in \Phi \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} v : b_1[b_2/\beta] \\ \hline val \forall \beta, f : (x : b_1[d]) \rightarrow \tau \in \Phi \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \Phi \\ \Theta; B; \Gamma \vdash_{wf} \Phi \\ \Theta; B; \Gamma \vdash_{wf} \Phi \\ \Theta; B; \Gamma \vdash_{wf} \Phi : int \\ \hline \Theta; B; \Gamma \vdash_{wf} \psi_1 : int \\ \Theta; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_2 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; B; \Gamma \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi; F \vdash_{wf} \psi_3 : int \\ \hline \Theta; \Phi;$$

WF_E_SPLIT

 $\Theta; B; \Gamma \vdash_{wf} v_2 : \mathbf{bvec}$

 $\overline{\Theta; \Phi; B; \Gamma; \Delta \vdash_{wf} \mathbf{split} v_1 v_2 : \mathbf{bvec} * \mathbf{bvec}}$

$$\begin{array}{c} \Theta;\mathcal{B};\Gamma\vdash_{wf}\Delta\\ u:\tau\in\Delta\\ \overline{\Theta};\mathcal{B};\Gamma;\Delta\vdash_{wf}u:|\tau|_b \end{array} \\ \hline \text{WF for constraints} \\ \\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\Rightarrow\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_2\Rightarrow\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\Rightarrow\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_2\Rightarrow\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\Rightarrow\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_2\Rightarrow\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_1\Rightarrow\phi_2\\ \Theta;\mathcal{B};\Gamma\vdash_{wf}\phi_2\Rightarrow\phi_2\\ \Theta;$$

 $\Theta \vdash_{wf} \Phi$

$$\begin{array}{l} & \underset{\Theta;B;\Gamma \vdash_{wf} \text{ } : \text{ } i \text{ } i}{\text{d} i \text{ } i \text{ }$$

2.3

$$\begin{array}{c|c} \Theta; B; \Gamma \vdash \tau_1 \lessapprox \tau_2 \end{array} \quad \text{Subtyping} \\ & \begin{array}{c|c} \Theta; B; \Gamma \vdash_{wf} \{z_1 : b | \phi_1\} \\ \Theta; B; \Gamma \vdash_{wf} \{z_2 : b | \phi_2\} \\ \hline \Theta; B; \Gamma, z_3 : b[\phi_1[z_3/z_1]] \models \phi_2[z_3/z_1] \\ \hline \Theta; B; \Gamma \vdash \{z_1 : b | \phi_1\} \lessapprox \{z_2 : b | \phi_2\} \end{array} \quad \text{SUBTYPE_ANF_SUBTYPE}$$

2.4 Typing

 $\vdash l \Rightarrow \tau$ Type synthesis for literals. Infer that type of l is τ

$$\begin{array}{c} \vdash ()\Rightarrow \{z: \mathbf{unit}|z=()\} \\ \hline \vdash \mathbf{T}\Rightarrow \{z: \mathbf{bool}|z=\mathbf{T}\} \\ \hline \vdash \mathbf{F}\Rightarrow \{z: \mathbf{bool}|z=\mathbf{F}\} \\ \hline \vdash \mathbf{F}\Rightarrow \{z: \mathbf{int}|z=n\} \\ \hline \vdash \mathbf{F}\Rightarrow \{z: \mathbf{$$

```
z_3 \# \Gamma
                                                      \Theta \vdash_{wf} \Phi
                                                      \Theta; B; \Gamma \vdash_{wf} \Delta
                                                      \Theta; B; \Gamma \vdash v_1 \Rightarrow \{z_1 : \mathbf{int} | \phi_1\}
                                                      \Theta; B; \Gamma \vdash v_2 \Rightarrow \{z_2 : \mathbf{int} | \phi_2\}
                                                                                                                                                    INFER_E_ANF_LEQ
                         \Theta; \Phi; B; \Gamma; \Delta \vdash v_1 \leq v_2 \Rightarrow \{z_3 : \mathbf{bool} | z_3 = va1 \leq va2\}
                                                        \Theta \vdash_{wf} \Phi
                                                        \Theta; B; \Gamma \vdash_{wf} \Delta
                                                        \operatorname{val} f: (x:b[\phi]) \to \tau \in \Phi
                                                     \frac{\Theta; B; \Gamma \vdash v \leq \{z: b | \phi\}}{\Theta; \Phi; B; \Gamma; \Delta \vdash f \, v \Rightarrow \tau[v/x]} \quad \text{INFER\_E\_ANF\_APP}
                                             \Theta \vdash_{wf} \Phi
                                             \Theta; B; \Gamma \vdash_{wf} \Delta
                                             \operatorname{val} \forall \beta. f : (x : b[\phi]) \to \tau \in \Phi
                                             \Theta; B; \Gamma \vdash v \le \{z : b[b_2/\beta] | \phi\}
                                                                                                                            INFER_E_ANF_APP_POLY
                                     \Theta; \Phi; B; \Gamma; \Delta \vdash f[b_2]v \Rightarrow \tau[b_2/\beta][v/x]
                                                      z\#\Gamma
                                                      \Theta \vdash_{wf} \Phi
                                                      \Theta; B; \Gamma \vdash_{wf} \Delta
                                                      \Theta; B; \Gamma \vdash v \Rightarrow \{z : b_1 * b_2 | \phi\}
                                        \overline{\Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{fst} \, v \Rightarrow \{z : b_1 | z = \mathbf{fst} \, v\}} \quad \text{INFER\_E\_ANF\_FST}
                                                      z\#\Gamma
                                                      \Theta \vdash_{wf} \Phi
                                                      \Theta; B; \Gamma \vdash_{wf} \Delta
                                                      \Theta; B; \Gamma \vdash v \Rightarrow \{z : b_1 * b_2 | \phi\}
                                                                                                                                         INFER_E_ANF_SND
                                      \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{snd} \ v \Rightarrow \{z : b_2 | z = \mathbf{snd} \ v\}
                                               z\#\Gamma
                                               \Theta \vdash_{wf} \Phi
                                               \Theta; B; \Gamma \vdash_{wf} \Delta
                                               \Theta; B; \Gamma \vdash v_1 \Rightarrow \{z_1 : \mathbf{bvec} | \phi_1\}
                                               \Theta; B; \Gamma \vdash v_2 \Rightarrow \{z_2 : \mathbf{bvec} | \phi_2\}
                                                                                                                                       INFER_E_ANF_CONCAT
                            \Theta; \Phi; B; \Gamma; \overline{\Delta \vdash v_1@v_2} \Rightarrow \{z : \mathbf{bvec} | z = v_1@v_2\}
                                                 z\#\Gamma
                                                  \Theta \vdash_{wf} \Phi
                                                  \Theta; B; \Gamma \vdash_{wf} \Delta
                                                  \Theta; B; \Gamma \vdash v_1 \Rightarrow \{z_1 : \mathbf{int} | \phi_1\}
                                                 \Theta; B; \Gamma \vdash v_2 \Rightarrow \{z_2 : \mathbf{bvec} | \phi_2\}
                                                                                                                                                                            INFER_E_ANF_SPLIT
\Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{split} \ v_1 \ v_2 \Rightarrow \{z : \mathbf{bvec} | v_2 = \mathbf{fst} \ z @ \mathbf{snd} \ z \land v_1 = \mathbf{len} \ (\mathbf{fst} \ z) \}
                                                       z\#\Gamma
                                                       \Theta \vdash_{wf} \Phi
                                                       \Theta; B; \Gamma \vdash_{wf} \Delta
                                                       \Theta; B; \Gamma \vdash v \Rightarrow \{z : \mathbf{bvec} | \phi\}
                                                                                                                                       INFER_E_ANF_LEN
                                      \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{snd} v \Rightarrow \{z : b_2 | z = \mathbf{len} v\}
                                                                   \Theta \vdash_{wf} \Phi
                                                                   \Theta; B; \Gamma \vdash_{wf} \Delta
                                                                   u: \tau \in \Delta
                                                           \overline{\Theta;\Phi;B;\Gamma;\Delta\vdash u\Rightarrow\tau}\quad \text{INFER\_E\_ANF\_MVAR}
```

```
\Theta; \Phi; B; \Gamma; \Delta \vdash e < \tau Check that type of e is \tau
                                             \Theta; \Phi; B; \Gamma; \Delta \vdash e \Rightarrow \{z_2 : b | \phi_2\}
                                            \Theta; B; \Gamma \vdash \{z_2 : b | \phi_2\} \lessapprox \{z_1 : b | \phi_1\} CHECK_E_ANF_EXPR
                                                 \Theta; \Phi; B; \Gamma; \Delta \vdash e < \{z_1 : b | \phi_1\}
\Theta; \Phi; B; \Gamma; \Delta \vdash s \leq \tau
                                                       Check that type of s is \tau
                                                                         \Theta \vdash_{wf} \Phi
                                                                         \Theta; B; \Gamma \vdash_{wf} \Delta
                                                                  \frac{\Theta; B; \Gamma \vdash v \leq \tau}{\Theta; \Phi; B; \Gamma; \Delta \vdash v \leq \tau} \quad \text{CHECK\_S\_VAL}
                                                           u \notin \text{dom}(\Delta)
                                                           \Theta; B; \Gamma \vdash v \leq \tau
                                                           \Theta; \Phi; B; \Gamma; \Delta, u : \tau \vdash s \leq \tau_2
                                               \overline{\Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{var} \, u : \tau := v \, \mathbf{in} \, s \leq \tau_2} \quad \text{CHECK\_S\_VAR}
                                                                     \Theta \vdash_{wf} \Phi
                                                                     \Theta; B; \Gamma \vdash_{wf} \Delta
                                                                     u: \tau \in \Delta
                                                                     \Theta; B; \Gamma \vdash v \leq \tau
                                                                                                                                       CHECK_S_ASSIGN
                                            \overline{\Theta; \Phi; B; \Gamma; \Delta \vdash u := v \leq \{z : \mathbf{unit} | \top\}}
                                        \Theta; B; \Gamma \vdash v \Rightarrow \{z : \mathbf{bool} | \phi_1 \}
                                       \Theta; \Phi; B; \Gamma; \Delta \vdash s_1 \leq \{z_1 : b | v = \mathbf{T} \Longrightarrow \phi[z_1/z]\}
                                       \Theta; \Phi; B; \Gamma; \Delta \vdash s_2 \leq \{z_2 : b | v = \mathbf{F} \Longrightarrow \phi[z_2/z]\}
                                                                                                                                                       CHECK_S_IF
                                         \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{if} \ v \ \mathbf{then} \ s_1 \ \mathbf{else} \ s_2 \le \{z : b | \phi\}
                                                    x\#\Gamma
                                                    \Theta; \Phi; B; \Gamma; \Delta \vdash e \Rightarrow \{z : b | \phi\}
                                                    \frac{\Theta; \Phi; B; \Gamma, x : b[\phi[x/z]]; \Delta \vdash s \leq \tau}{\Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{let} \ x = e \ \mathbf{in} \ s \leq \tau} \quad \text{CHECK\_S\_LET}
                                                 \frac{\Theta; \Phi; B; \Gamma, x : \mathbf{bool}[\phi]; \Delta \vdash s \leq \tau}{\Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{assert} \ \phi \ \mathbf{in} \ s \leq \tau} \quad \text{Check\_s\_assert}
                                                  x\#\Gamma
                                                  \Theta; \Phi; B; \Gamma; \Delta \vdash s_1 \leq \{z : b | \phi\}
                                    \frac{\Theta;\Phi;B;\Gamma,x:b[\phi[x/z]];\Delta\vdash s_2\leq\tau}{\Theta;\Phi;B;\Gamma;\Delta\vdash\mathbf{let}\ x:\{z:b|\phi\}=s_1\ \mathbf{in}\ s_2\leq\tau}
                                                                                                                                                   CHECK_S_LET2
                      union tid = \{ \overrightarrow{ctor_i} : \{z_i : b_i | \phi_i \}^i \} \in \Theta
                      \Theta; B; \Gamma \vdash v \Rightarrow \{z : tid | \phi\}
                      \Theta; \Phi; B; \Gamma, x_i : b_i[v = \underline{ctor}_i \ tid \ x_i \land \phi_i[x_i/z_i]]; \Delta \vdash s_i \leq \tau^{i} CHECK_S_MATCH
                                   \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{match} \ v \ \mathbf{of} \ \overline{ctor_i \ x_i \Rightarrow s_i}^i < \tau
                                                  \Theta; \Phi; B; \Gamma; \Delta \vdash s_1 \leq \{z : \mathbf{bool} | \top \}
                                                  \Theta; \Phi; B; \Gamma; \Delta \vdash s_2 \leq \{z : \mathbf{unit} | \top\}
                                                                                                                                                     CHECK_S_WHILE
                                \Theta; \Phi; B; \Gamma; \Delta \vdash while (s_1) do \{s_2\} \leq \{z : \mathbf{unit} | \top \}
                                                     \Theta; \Phi; B; \Gamma; \Delta \vdash s_1 \leq \{z : \mathbf{unit} | \top\}
                                                    \Theta; \Phi; B; \Gamma; \Delta \vdash s_2 \leq \tau
                                                                                                                             — CHECK_S_SEQ
                                                              \Theta; \Phi; B; \Gamma; \Delta \vdash s_1; s_2 < \tau
```

 $\Theta; \Phi; \Delta \vdash (\delta, s) \leq \tau$ Program state typing judgement

$$\begin{array}{l} \Theta \vdash \Delta \sim \delta \\ \Theta ; \Phi ; \cdot ; \cdot ; \Delta \vdash s \leq \tau \\ \hline \Theta ; \Phi ; \Delta \vdash (\delta, s) < \tau \end{array} \quad \text{CHECK_REDEX_STMT}$$

2.5 Operational semantics

$$\frac{\Phi \vdash \langle \delta, s_1 \rangle \to \langle \delta', s_2 \rangle}{\Phi \vdash \langle \delta, \mathbf{if} \, \mathbf{T} \, \mathbf{then} \, s_1 \, \mathbf{else} \, s_2 \rangle \to \langle \delta, s_1 \rangle} \quad \text{REDUCE_IF_TRUE}$$

$$\frac{\Phi \vdash \langle \delta, \mathbf{if} \, \mathbf{F} \, \mathbf{then} \, s_1 \, \mathbf{else} \, s_2 \rangle \to \langle \delta, s_2 \rangle}{\Phi \vdash \langle \delta, \mathbf{let} \, x = v \, \mathbf{in} \, s \rangle \to \langle \delta, s[v/x] \rangle} \quad \text{REDUCE_IF_VALUE}$$

```
\frac{v_1 + v_2 = v}{\Phi \vdash \langle \delta, \mathbf{let} \ x = v_1 + v_2 \mathbf{in} \ s \rangle \rightarrow \langle \delta, \mathbf{let} \ x = v \mathbf{in} \ s \rangle}
                                                                                                                                                                                              REDUCE_LET_PLUS
                                             \frac{v_1 \le v_2 = v}{\Phi \vdash \langle \delta, \mathbf{let} \ x = v_1 \le v_2 \mathbf{in} \ s \rangle \rightarrow \langle \delta, \mathbf{let} \ x = v \mathbf{in} \ s \rangle}
                                                                                                                                                                                                REDUCE_LET_LEQ
                                                                             \operatorname{val} f: (x:b[\phi]) \to \tau \in \Phi
                                                                             function f(x) = s_1 \in \Phi
                          \overline{\Phi \vdash \langle \delta, \mathbf{let} \ y = f \ v \ \mathbf{in} \ s_2 \rangle \rightarrow \langle \delta, \mathbf{let} \ y : \tau[v/x] = s_1[v/x] \ \mathbf{in} \ s_2 \rangle}
                                                                                                                                                                                                                  REDUCE_LET_APP
                                                                   \operatorname{val} \forall \beta. f : (x : b[\phi]) \to \tau \in \Phi
                                                                   function f(x) = s_1 \in \Phi
\overline{\Phi \vdash \langle \delta, \mathbf{let} \ y = f[b_1]v \ \mathbf{in} \ s_2 \rangle \rightarrow \langle \delta, \mathbf{let} \ y : \tau[v/x][b_1/\beta] = s_1[v/x][b_1/\beta] \ \mathbf{in} \ s_2 \rangle}
                                                                                                                                                                                                      REDUCE_LET_FST
                                       \overline{\Phi \vdash \langle \delta, \mathbf{let} \, x = \mathbf{fst} \, (v_1, v_2) \, \mathbf{in} \, s \rangle} \rightarrow \langle \delta, \mathbf{let} \, x = v_1 \, \mathbf{in} \, s \rangle
                                                                                                                                                                                                       REDUCE_LET_SND
                                      \overline{\Phi \vdash \langle \delta, \mathbf{let} \ x = \mathbf{snd} \ (v_1, v_2) \mathbf{in} \ s \rangle \rightarrow \langle \delta, \mathbf{let} \ x = v_2 \mathbf{in} \ s \rangle}
                                       \frac{v_1@v_2=v_3}{\Phi \vdash \langle \delta, \mathbf{let} \ x=v_1@v_2 \mathbf{in} \ s \rangle \to \langle \delta, \mathbf{let} \ x=v_3 \mathbf{in} \ s \rangle}
                                                                                                                                                                                         REDUCE_LET_CONCAT
                                                                                       v_1 = \mathbf{split} \, v_2 \, v_3
                                     \frac{1}{\Phi \vdash \langle \delta, \mathbf{let} \ x = \mathbf{split} \ v_2 \ v_3 \ \mathbf{in} \ s \rangle \rightarrow \langle \delta, \mathbf{let} \ x = v_1 \ \mathbf{in} \ s \rangle}
                                                                                                                                                                                                   REDUCE_LET_SPLIT
                                              \frac{\operatorname{len} v_1 = v_2}{\Phi \vdash \langle \delta, \operatorname{let} x = \operatorname{len} v_1 \operatorname{in} s \rangle \rightarrow \langle \delta, \operatorname{let} x = v_2 \operatorname{in} s \rangle}
                                                                                                                                                                                               REDUCE_LET_LEN
                                                   \frac{v = \delta(u)}{\Phi \vdash \langle \delta, \mathbf{let} \ x = u \ \mathbf{in} \ s \rangle \rightarrow \langle \delta, \mathbf{let} \ x = v \ \mathbf{in} \ s \rangle}
                                                                                                                                                                                    REDUCE\_LET\_MVAR
                                                 \frac{u \notin \mathrm{dom}(\delta)}{\Phi \vdash \langle \delta, \mathbf{var}\, u : \tau := v \, \mathbf{in} \, s \rangle \to \langle \delta[u \mapsto v], s \rangle} \quad \text{REDUCE\_MVAR\_DECL}
                                                                       \frac{\delta' = \delta[u \mapsto v]}{\Phi \vdash \langle \delta, u := v \rangle \to \langle \delta', () \rangle} \quad \text{REDUCE\_MVAR\_ASSIGN}
                                                                                   \frac{\Phi \vdash \langle \delta, s_1 \rangle \to \langle \delta', s_3 \rangle}{\Phi \vdash \langle \delta, s_1; s \rangle \to \langle \delta', s_3; s \rangle} \quad \text{REDUCE\_SEQ1}
                                                                                         \overline{\Phi \vdash \langle \delta, (); s \rangle \rightarrow \langle \delta, s \rangle} \quad \text{REDUCE\_SEQ2}
                                                                                                                                                                                  REDUCE_LET2_VAL
                                                    \overline{\Phi \vdash \langle \delta, \mathbf{let} \ x : \tau = v \ \mathbf{in} \ s_2 \rangle \rightarrow \langle \delta, s_2[v/x] \rangle}
                              \frac{\Phi \vdash \langle \delta, s_1 \rangle \to \langle \delta', s_3 \rangle}{\Phi \vdash \langle \delta, \mathbf{let} \ x : \tau = s_1 \ \mathbf{in} \ s_2 \rangle \to \langle \delta', \mathbf{let} \ x : \tau = s_3 \ \mathbf{in} \ s_2 \rangle}
                                                                                                                                                                                                                    REDUCE_MATCH

\overline{\Phi \vdash \langle \delta, \mathbf{match} \, (ctor_j \, tid \, v) \, \mathbf{of} \, \overline{ctor_i \, x_i \Rightarrow s_i}^i \rangle} \rightarrow \langle \delta, s_i [v/x_i] \rangle

                                                                                                                                                                                                                                                                                                                   REDUC
\overline{\Phi \vdash \langle \delta, \mathbf{while}\,(s_1)\,\mathbf{do}\,\{s_2\}\rangle \rightarrow \langle \delta, \mathbf{let}\,\,x: \{z: \mathbf{bool}|\top\} = s_1\,\,\mathbf{in}\,\,\mathbf{if}\,x\,\mathbf{then}\,(s_2; \mathbf{while}\,(s_1)\,\mathbf{do}\,\{s_2\})\,\mathbf{else}\,()\rangle}
                                                                                                                                                                     REDUCE_ASSERT1
                                                                       \overline{\Phi \vdash \langle \delta, \mathbf{assert} \, \phi \, \mathbf{in} \, v \rangle \rightarrow \langle \delta, v \rangle}
                                                   \frac{\Phi \vdash \langle \delta, s_1 \rangle \to \langle \delta', s_2 \rangle}{\Phi \vdash \langle \delta, \mathbf{assert} \ \phi \ \mathbf{in} \ s_1 \rangle \to \langle \delta', \mathbf{assert} \ \phi \ \mathbf{in} \ s_2 \rangle} \quad \text{REDUCE\_ASSERT2}
```

$$\begin{array}{c} \Phi \vdash \langle \delta_1, s_1 \rangle \xrightarrow{*} \langle \delta_2, s_2 \rangle & \text{Multi-step reduction} \\ \\ \hline \frac{\Phi \vdash \langle \delta_1, s_1 \rangle \rightarrow \langle \delta_2, s_2 \rangle}{\Phi \vdash \langle \delta_1, s_1 \rangle \xrightarrow{*} \langle \delta_2, s_2 \rangle} & \text{REDUCE_MANY_SINGLE_STEP} \\ \\ \frac{\Phi \vdash \langle \delta_1, s_1 \rangle \rightarrow \langle \delta_2, s_2 \rangle}{\Phi \vdash \langle \delta_2, s_2 \rangle \xrightarrow{*} \langle \delta_3, s_3 \rangle} & \text{REDUCE_MANY_MANY_STEP} \end{array}$$

2.6 Machine configuration check

$$\Theta \vdash \delta \sim \Delta$$

$$\begin{split} & \overline{\Theta \vdash \cdot \sim} \cdot \\ & u \notin \mathrm{dom}(\Delta) \\ & \Theta \vdash \delta \sim \Delta \\ & \Theta; \cdot; \cdot \vdash v \leq \tau \\ & \overline{\Theta \vdash \delta[u \mapsto v] \sim \Delta, u : \tau} \end{split} \quad \text{CHECK_STORE_CONS}$$

$$\Theta; \Phi; \Delta \vdash (\delta, s) \le \tau$$

$$\begin{array}{ll} \Theta \vdash \delta \sim \Delta \\ \Theta ; \Phi ; \cdot ; \cdot ; \Delta \vdash s \leq \tau \\ \Theta ; \Phi ; \Delta \vdash (\delta , s) \leq \tau \end{array} \quad \text{CHECK_CONFIG_CONFIG}$$

$$E \vdash \mathbf{pack_record} \ \tau \ x \ id_1 = x_1 \dots id_n = x_n \leadsto L$$

$$\boxed{E \vdash \mathbf{unpack_field} \, \tau \, x \, x' \, id \rightsquigarrow L}$$

$$\boxed{E \vdash \mathbf{update_record} \ \tau \ x' \ id_1 = x_1 \dots id_n = x_n \leadsto L}$$

$$\Theta; \Phi; B; \Gamma; \Delta \vdash_{wf} L : \gamma$$
 WF for let-context

$$\begin{split} \frac{\Theta;\Phi;B;\Gamma;\Delta\vdash_{wf}e:b}{\Theta;\Phi;B;\Gamma;\Delta\vdash_{wf}\mathbf{let}\,x=e\,\mathbf{in}\,{}_{-}:x:\{z:b|\phi\}} &\quad \text{WF_LCTX_LET} \\ \frac{\Theta;\Phi;B;\Gamma;\Delta\vdash_{wf}s:b}{\Theta;B;\Gamma\vdash_{wf}\tau} \\ \frac{\Theta;\Phi;B;\Gamma\vdash_{wf}\tau}{\Theta;\Phi;B;\Gamma;\Delta\vdash_{wf}\mathbf{let}\,x:\tau=s\,\,\mathbf{in}\,\,{}_{-}:x:\{z:b|\phi\}} &\quad \text{WF_LCTX_LET2} \end{split}$$

3 Sail to MiniSail-ANF conversion

3.1 Converting types

 $typquant \leadsto kinded_id_1 ... kinded_id_m, n_constraint$

Normalise type quant. Pull out all of the constraints and put them at the end $E \vdash typ \leadsto \tau$

Convert Sail type to MiniSail type. First form is that we normalise bringing out any exisentials to the top level.

$$\frac{E; \epsilon \vdash typ; z \leadsto b; \phi}{E \vdash typ \leadsto \{z : b|\phi\}} \quad \text{TYP_CONV}$$

Extract MiniSail base type and constraint from Sail type.

$$\overline{E;M \vdash int;ce \leadsto int;\top} \quad \text{CTA_INT}$$

$$E;M \vdash typ_arg \leadsto ce'$$

$$\overline{E;M \vdash atom(typ_arg);ce \leadsto int;ce = ce'} \quad \text{CTA_ATOM_INT}$$

$$\overline{E;M \vdash bool;ce \leadsto bool;\top} \quad \text{CTA_BOOL}$$

$$E;M \vdash typ_arg \leadsto \phi$$

$$\overline{E;M \vdash typ_arg_1 \leadsto ce_1}$$

$$E;M \vdash typ_arg_1 \leadsto ce_1$$

$$E;M \vdash typ_arg_2 \leadsto ce_2$$

$$\overline{E;M \vdash typ_arg_1, typ_arg_2);ce \leadsto int;ce_1 \le ce \land ce \le ce_2} \quad \text{CTA_RANGE}$$

$$M' = M, ce, kinded_id_1 ... kinded_id_m$$

$$E;M' \vdash typ;ce \leadsto b;\phi$$

$$E;M' \vdash n_constraint \leadsto \phi'$$

$$\overline{E;M \vdash \{kinded_id_1 ... kinded_id_m, n_constraint.typ\};ce \leadsto b;\phi \land \phi'} \quad \text{CTA_EXIST}$$

$$E;M \vdash typ; \mathbf{fst} ce \leadsto b;\phi$$

$$E;M \vdash (typ_1, ..., typ_n); \mathbf{snd} ce \leadsto b';\phi'$$

$$\overline{E;M \vdash (typ_1, ..., typ_n);ce \leadsto b * b';\phi \land \phi'} \quad \text{CTA_TUPLE}$$

$$E;M \vdash n_constraint \leadsto \phi$$

Convert Sail constraint to MiniSail constraint.

$$\begin{split} E; M \vdash nexp_1 \leadsto ce_1 \\ E; M \vdash nexp_2 \leadsto ce_2 \\ \hline E; M \vdash nexp_1 \equiv nexp_2 \leadsto ce_1 = ce_2 \end{split} \quad \text{CONVERT_C_EQUAL}$$

$$E; M \vdash nexp \leadsto ce$$

Convert Sail constraint expression to MiniSail constraint expression.

$$\frac{ce = M(kid)}{E; M \vdash kid \leadsto ce} \quad \text{NEXP_CEA_VAR}$$

$$E; M \vdash nexp_1 \leadsto ce_1$$

$$E; M \vdash nexp_2 \leadsto ce_2$$

$$E; M \vdash nexp_2 + nexp_1 \leadsto ce_1 + ce_2$$

$$\text{NEXP_CEA_ADD}$$

```
3.2
           Converting expressions
lit \leadsto lp
 lit \leadsto l
                                                                           \frac{}{num \leadsto n} CL_NUM
  E \leadsto \Theta; \Phi; B; \Gamma; \Delta
 E \vdash exp : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x; L : \tau
                                                                    \operatorname{fresh} x
                                                                    lit \leadsto l
                                                                     E \vdash typ \leadsto \tau
                                                                    E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                    E \vdash lit : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x; \mathbf{let} \ x = l \ \mathbf{in} = : \tau
                                                      id/\mathbf{immutable}: id \in E
                                                      id \sim x
                                                      E \vdash typ \leadsto \tau
                                                      E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                                                                                                            CE_IMMUTABLE
                                   \overline{E \vdash id : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/x : \tau \vdash x; \_ : \tau}
                                                                 \mathbf{fresh}\,x
                                                                 id/\mathbf{enum}: typ \in E
                                                                 E \vdash id \leadsto ctor, tid
                                                                 E \vdash typ \leadsto \tau
                                                                 E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                      E \vdash id : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/x : \tau \vdash x; \mathbf{let} \ x = ctor \ tid \ () \ \mathbf{in} = : \tau
                                                          \mathbf{fresh}\,x
                                                          id/\mathbf{mutable}: typ \in E
                                                          id \sim u
                                                          E \vdash typ \leadsto \tau
                                                          E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                                                                                                                           CE\_MUTABLE
                          E \vdash id : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/x : \tau \vdash x; \mathbf{let} \ x = u \ \mathbf{in} \ \_: \tau
                                                          \operatorname{fresh} x
                                                           id/\mathbf{register}: typ \in E
                                                          id \sim u
                                                           E \vdash typ \leadsto \tau
                                                           E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                                                                                                                          CE\_REGISTER
                          \overline{E \vdash id : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/x : \tau \vdash x; \mathbf{let} \ x = u \ \mathbf{in} \ \_: \tau}
```

 $E_{exp} \vdash exp : \operatorname{typ}_{exp} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1$

 $E_2 \vdash (exp_1, \dots, exp_n) : typ \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2/\gamma_2 \vdash x_2; L_2 : \tau_2$

 $E \leadsto \Theta; \Phi; B; \Gamma; \Delta$

 $E \vdash typ \leadsto \tau$

 $\overline{E \vdash (exp, exp_1, ..., exp_n) : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma'_1, \gamma'_2, x : \tau \vdash x; L_1[L_2[\mathbf{let} \ x = (x', x'') \ \mathbf{in} \ _]] : \tau}$

 CE_TUPLE

```
\operatorname{fresh} x
        E_{(exp_1,...,exp_n)} \vdash (exp_1,...,exp_n) : \operatorname{typ}_{(exp_1,...,exp_n)} \leadsto \Theta'; \Phi'; B'; \Gamma'; \Delta'/\gamma' \vdash x'; L : \tau'
        E \leadsto \Theta; \Phi; B; \Gamma; \Delta
        E \vdash typ \leadsto \tau
        E \vdash \mathbf{inst\_of}\ id(exp_1, ..., exp_n) \leadsto x''; L''
\overline{E \vdash id(exp_1, ..., exp_n) : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma', x : \tau \vdash x; L''[L[\mathbf{let} \ x = f(x'', x') \ \mathbf{in} \ \_]] : \tau}
      \operatorname{fresh} x
      E_{(exp_1,...,exp_n)} \vdash (exp_1,...,exp_n) : \operatorname{typ}_{(exp_1,...,exp_n)} \leadsto \Theta'; \Phi'; B'; \Gamma'; \Delta' / \gamma' \vdash x'; L : \tau'
      E \leadsto \Theta; \Phi; B; \Gamma; \Delta
      E \vdash id \leadsto ctor, tid
      E \vdash typ \leadsto \tau
                                                                                                                                                                                               CE_CTOR
 E \vdash id(exp_1, ..., exp_n) : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma', x : \tau \vdash x; L[\mathbf{let} \ x = ctor \ tid \ x' \ \mathbf{in} \ \_] : \tau
                               E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1
                               E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2/\gamma_2 \vdash x_2; L_2 : \tau_2
                               E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                               E \vdash typ \leadsto \tau
                                                                                                                                                                                                 CE\_PLUS
\overline{E \vdash exp_1 + exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma_1, \gamma_2, x : \tau \vdash x; L_1[L_2[\mathbf{let} \ x = x_1 + x_2 \ \mathbf{in} \ \_]] : \tau}
                                E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1
                                E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2/\gamma_2 \vdash x_2; L_2 : \tau_2
                                E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                E \vdash typ \leadsto \tau
                                                                                                                                                                                                    CE_LEQ
E \vdash exp_1 \leq exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \overline{\Delta/\gamma_1, \gamma_2, x : \tau \vdash x; L_1[L_2[\mathbf{let} \ x = x_1 \leq x_2 \ \mathbf{in} \ \_]] : \tau_1}
                                E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1
                                E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                E \vdash typ \leadsto \tau
                                                                                                                                                                                      CE_LEN
             E \vdash \mathbf{len}(exp_1) : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma_1, x : \tau \vdash x; L_1[\mathbf{let} \ x = \mathbf{len} \ x_1 \ \mathbf{in} \ \_] : \tau
                           fresh x
                           E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_2; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1
                           E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2/\gamma_2 \vdash x_2; L_2 : \tau_2
                           E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                           E \vdash typ \leadsto \tau
                                                                                                                                                                                          CE_CONCAT
E \vdash exp_1@exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \overline{\Delta/\gamma_1, \gamma_2, x : \tau} \vdash x; L_1[L_2[\mathbf{let} \ x = x_1@x_2 \ \mathbf{in} \ \_]] : \tau
                                \mathbf{fresh}\,x
                                E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1
                                E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                E \vdash typ \leadsto \tau
              E \vdash \mathbf{fst}(exp_1) : typ \longrightarrow \Theta; \Phi; B; \Gamma; \Delta/\gamma_1, x : \tau \vdash x; L_1[\mathbf{let} \ x = \mathbf{fst} \ x_1 \ \mathbf{in} \ \_] : \tau_1
                                E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1
                                E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                E \vdash typ \leadsto \tau
                                                                                                                                                                                        CE\_SND
            E \vdash \mathbf{snd}(exp_1) : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma_1, x : \tau \vdash \overline{x; L_1[\mathbf{let} \ x = \mathbf{snd} \ x_1 \ \mathbf{in} \ \_]} : \tau
```

```
\operatorname{fresh} x
                                         \overline{E \vdash exp_i : typ_i \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x_i; L_i : \tau_i}^{i \in 1...n}
                                         E \vdash typ \leadsto \tau
                                         E \vdash \mathbf{pack\_record} \ \tau \ x \ \overline{id_i = x_i}^{i \in 1...n} \leadsto L
                                                                                                                                                                                                                   CE_RECORD
   \overline{E \vdash \mathbf{struct} \left\{ \overline{id_i = exp_i}^{i \in 1...n} \right\} : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x; (L_1 + ... + L_n)[L] : \tau}
                                                     \mathbf{fresh}\,x
                                                     E \vdash exp: typ' \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x'; L:\tau'
                                                      E \vdash typ \leadsto \tau
                                                \frac{E \vdash \mathbf{unpack\_field} \ \tau \ x \ x' \ id \leadsto L'}{E \vdash exp. id : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x; L[L'] : \tau}
                                        \operatorname{fresh} x
                                       \frac{E \vdash exp: typ' \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x'; L: \tau'}{E \vdash exp_i: typ_i \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x_i; L_i: \tau_i} {}^{i \in 0...n}
                                        E \vdash typ \leadsto \tau
                                        E \vdash \mathbf{update\_record} \ \tau \ x \ x' \ \overline{id_i = x_i}^{i \in 0...n} \ \leadsto L'
                                                                                                                                                                                                            - CE_RECORD_UPDATE
\overline{E \vdash \{exp \text{ with } \overline{id_i = exp_i}^{i \in 0...n}\} : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma \vdash x; (L_0 + ... + L_n)[L'] : \tau}
                                       \mathbf{fresh}\,x
                                       E \vdash \mathbf{if} \ exp_1 \ \mathbf{then} \ exp_2 \ \mathbf{else} \ exp_3 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau
            \overline{E \vdash \mathbf{if} \ exp_1 \mathbf{then} \ exp_2 \mathbf{else} \ exp_3 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\epsilon \vdash x; \mathbf{let} \ x : \tau = s \ \mathbf{in} \ \_ : \tau}
                          \mathbf{fresh}\,x
\frac{E \vdash \mathbf{match} \ exp\{pat_1 \to exp_1, ..., pat_n \to exp_n\} : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau}{E \vdash \mathbf{match} \ exp\{pat_1 \to exp_1, ..., pat_n \to exp_n\} : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta/\epsilon \vdash x; \mathbf{let} \ x : \tau = s \ \mathbf{in} \ \_ : \tau}
   E \vdash exp : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau
                                       id \sim x
                                        E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L : \tau_1
                                        E \vdash typ \leadsto \tau
                                      \frac{E \vdash (pat \Rightarrow exp_2) : |\tau_1|_b/x \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s_2 : \tau'}{E \vdash \mathbf{let} \ pat = exp_1 \ \mathbf{in} \ exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[s_2] : \tau}
                                       id \sim u
                                       E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L : \tau'
                                       E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; E_2; \Gamma_2; \Delta_2 \vdash s_2 : \tau
                                       E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                       E \vdash typ \leadsto \tau
                                       id/\mathbf{mutable} \notin E
                \overline{E \vdash \mathbf{var} \ id = exp_1 \ \mathbf{in} \ exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[\mathbf{var} \ u : \tau := x_1 \ \mathbf{in} \ s_2] : \tau}
                                      E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L : \tau_1
                                      E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2 \vdash s_2 : \tau
                                      E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                      E \vdash typ \leadsto \tau
                                      E \vdash typ' \leadsto \tau'
```

 $\overline{E \vdash \mathbf{var}\,(typ')id = exp_1\,\mathbf{in}\,exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[\mathbf{var}\,u : \tau' := x_1\,\mathbf{in}\,s_2] : \tau}$

 CS_CAST

```
id \sim u
                              E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L : \tau'
                              E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2 \vdash s_2 : \tau
                              E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                              E \vdash typ \leadsto \tau
                              id/\mathbf{mutable}: typ' \in E
                                                                                                                                                                      CS_ASSIGN
                    E \vdash \mathbf{var} \ id = exp_1 \ \mathbf{in} \ exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[u := x_1; s_2] : \tau
      id_1 \sim u
      E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_3; L[\operatorname{let} x_2 = u \operatorname{in} \_] : \tau'
      E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2 \vdash s_2 : \tau
      E \leadsto \Theta; \Phi; B; \Gamma; \Delta
      E \vdash \mathbf{update\_record} \ \tau \ x_1 \ x_2 \ id_2 = x_3 \leadsto L'
                                                                                                                                                                         CS_FIELD_ASSIGN
     E \vdash \mathbf{var} \ id_1.id_2 = exp_1 \ \mathbf{in} \ exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[L'[u := x_1; s_2]] : \tau
                               id \sim u
                               E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L : \tau'
                               E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2 \vdash s_2 : \tau
                               E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                               E \vdash typ \leadsto \tau
                               id/\mathbf{register}: typ' \in E
                                                                                                                                                                             CS_DEREF
              E \vdash \mathbf{varderef}\ id = exp_1\ \mathbf{in}\ \overline{exp_2: typ} \leadsto \Theta; \Phi; \overline{B}; \Gamma; \Delta \vdash L[u := x_1; s_2] : \tau
                                             E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x_1; L_1 : \tau_1
                                             E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2/\gamma_2 \vdash x_2; L_2 : \tau_2
                                             E_{exp_3} \vdash exp_3 : \operatorname{typ}_{exp_3} \leadsto \Theta_3; \Phi_3; B_3; \Gamma_3; \Delta_3/\gamma_3 \vdash x_3; L_3 : \tau_3
                                             E_{exp_4} \vdash exp_4 : \operatorname{typ}_{exp_4} \leadsto \Theta_4; \Phi_4; B_4; \Gamma_4; \Delta_4 \vdash s_4 : \tau
                                             E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                             E \vdash typ \leadsto \tau
                                             L_4 = \mathbf{let} \, x = u \, \mathbf{in}_{--}
                                             L_5 = \mathbf{let} \, x_4 = \mathbf{update\_vector\_range} \, x \, x_1 \, x_2 \, x_3 \, \mathbf{in} \, \_
                                                                                                                                                                                                                            CS_VECT
E \vdash \mathbf{var} \ id[exp_1..exp_2] = exp_3 \ \mathbf{in} \ exp_4 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash (L_1 + L_2 + L_3 + L_4 + L_5)[u := x_4; s_4] : \tau
                                            E \vdash exp : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau
                                            E \leadsto \Theta : \Phi : B : \Gamma : \Delta
                                            E \vdash typ \leadsto \tau
                                                                                                                                CS_BLOCK_SINGLE
                                         E \vdash \{exp\} : tup \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau
                                E \vdash exp : \operatorname{typ}_{exp} \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau
                                E \vdash \{exp_1; ...; exp_n\} : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s' : \tau'
                                E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                E \vdash typ \leadsto \tau
                                                                                                                                                     CS_BLOCK_CONS
                        \overline{E \vdash \{exp; exp_1; ...; exp_n\} : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s; s' : \tau'}
                                     E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1/\gamma_1 \vdash x; L : \tau'
                                     E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2 \vdash s_2 : \tau_2
                                     E_{exp_3} \vdash exp_2 : \operatorname{typ}_{exp_3} \leadsto \Theta_3; \Phi_3; B_3; \Gamma_3; \Delta_3 \vdash s_3 : \tau_3
                                     E \leadsto \Theta; \Phi; B; \Gamma; \Delta
                                     E \vdash typ \leadsto \tau
                                                                                                                                                                                          CS_IF
            E \vdash \mathbf{if} \ exp_1 \mathbf{then} \ exp_2 \mathbf{else} \ exp_3 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[\mathbf{if} \ x \mathbf{then} \ s_2 \mathbf{else} \ s_3] : \tau
                    E_{\mathit{exp}} \vdash \mathit{exp} : \mathsf{typ}_{\mathit{exp}} \leadsto \Theta; \Phi; B; \Gamma; \Delta/\gamma_1 \vdash x; L : \tau'
                     E \vdash (pat_1 \Rightarrow exp_1), \dots, (pat_n \Rightarrow exp_n) : b/x \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau'
                                                                                                                                                                                  CS\_MATCH
        E \vdash \mathbf{match} \; exp\{pat_1 \rightarrow exp_1, \, ..\,, pat_n \rightarrow exp_n\} : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[s] : \tau
```

```
E \vdash \operatorname{typ}_{exp_1} \leadsto \{z : b | \phi\}
                                            E_{exp_1} \vdash exp_1 : \operatorname{typ}_{exp_1} \leadsto \Theta_1; \Phi_1; B_1; \Gamma_1; \Delta_1 \vdash s_1 : \tau_1
E_{exp_2} \vdash exp_2 : \operatorname{typ}_{exp_2} \leadsto \Theta_2; \Phi_2; B_2; \Gamma_2; \Delta_2 \vdash s_2 : \tau_2
                                                                                                                                                                                                                                      CS_WHILE
        E \vdash \mathbf{while} \ exp_1 \ exp_2 : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{while} \ (s_1) \ \mathbf{do} \ \{\mathbf{assert} \ \phi \ \mathbf{in} \ s_2\} : \tau
                                                 \frac{E_{exp} \vdash exp : \operatorname{typ}_{exp} \leadsto \Theta; \Phi; B; \Gamma; \Delta / \gamma \vdash x; L : \tau}{E \vdash exp : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash L[x] : \tau}
E \vdash \Pi : b_1/x_1 ... b_n/x_n \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau
                                                                                                                                      Convert match branches
                                                             \frac{E \vdash exp : typ \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau}{E \vdash \Rightarrow exp, \Pi : \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau} \quad \text{CB\_EMPTY}
                                                 \frac{E \vdash \Pi : \mathbf{unit}/x \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau}{E \vdash () \Rightarrow exp, \Pi : \mathbf{unit}/x \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau} \quad \text{CB\_UNIT}
                                      b \in \{ \mathbf{int}, \mathbf{bool} \}
                                      E \vdash \Pi \leadsto \Pi_1; lp_1 || ... || \Pi_n; lp_n
                                      E \vdash \Pi_i : b_1/x_1 ... b_m/x_m \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s_i : \tau^{i \in 1...n}
         E \vdash \Pi : b/x \, b_1/\overline{x_1 \dots b_m/x_m} \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{switch} \, x \{ \, \overline{lp_i \Rightarrow s_i}^{\, i \in 1..n} \, \} : \tau
                                  E \vdash \Pi \leadsto \Pi_1; \overrightarrow{ctor}_1 \ b_1' \ x_1' || \ldots || \Pi_n; \overrightarrow{ctor}_n \ b_n' \ x_n'
                                  E \vdash \Pi_i : b_1'/x_1' \ b_1/x_1 \dots b_m/x_m \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s_i : \tau^{i \in 1 \dots n}
                                                                                                                                                                                                                                           CB_CTOR
    E \vdash \Pi : tid/x \, b_1/x_1 \dots b_m/x_m \xrightarrow{\leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{match} \, x \, \mathbf{of} \, \overline{ctor_i \, x_i' \Rightarrow s_i}^{i \in 1..n} : \tau
                              b = (b'_1, \ldots, b'_n)
                              E \vdash \Pi : b \leadsto \Pi'; b'_1/x'_1 \dots b'_n/x'_n
       \frac{E \vdash \Pi' : b'_1/x'_1 \dots b'_n/x'_n \ b_1/x_1 \dots b_m/x_m \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau}{E \vdash \Pi : b/x \ b_1/x_1 \dots b_m/x_m \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash \mathbf{unpack} \ x \ \mathbf{into} \ x'_1, \dots, x'_n \ \mathbf{in} \ s : \tau}
                                                                                                                                                                                                                                      CB_TUPLE
```

3.3 Convert patterns

```
lit \leadsto l
                                                           l \not\in lp_1 \dots lp_m
                                                           E \vdash \Pi \leadsto \Pi_1; lp_1 || ... || \Pi_m; lp_m
                                                                                                                                                                         PHG_LIT2
             \overline{E \vdash (lit\ pat_1 ... pat_n \Rightarrow exp), \Pi \leadsto (pat_1 ... pat_n \Rightarrow exp); l||\Pi_1; lp_1||...||\Pi_m; lp_m||}
                                  E \vdash (\_pat_1 ... pat_n \Rightarrow exp), \Pi \leadsto (pat_1 ... pat_n \Rightarrow exp); \bot
                                                                                                                                                      PHG_VAR
                                 \overline{E \vdash (id \ pat_1 ... pat_n \Rightarrow exp), \Pi \leadsto (pat_1 ... pat_n \Rightarrow exp); id}
   E \vdash \Pi \leadsto \Pi_1; \dot{ctor}_1 b_1 x_1 || ... || \Pi_n; \dot{ctor}_n b_n x_n
                                                                              \overline{E \vdash \leadsto} PHC_EMPTY
                                           E \vdash id \leadsto \dot{ctor}, tid
                                           E \vdash \Pi \leadsto \Pi_1; \dot{ctor}_1 b_1 x_1 || ... || \Pi_n; \dot{ctor}_n b_n x_n
                                                                                                                                                                             PHC_CTOR
       \overline{E \vdash id(pat'_1, ..., pat'_m) \ pat_1 ... pat_n \Rightarrow exp, \Pi \leadsto \Pi_1; ctor_1 \ b_1 \ x_1 || ... || \Pi_n; ctor_n \ b_n \ x_n}
                                            E \vdash \Pi \leadsto \Pi_1; \dot{ctor}_1 b_1 x_1 || ... || \Pi_n; \dot{ctor}_n b_n x_n
                       E \vdash id \ pat_1 ... pat_n \Rightarrow exp, \Pi \leadsto \Pi_1; \overrightarrow{ctor_1} \ b_1 \ x_1 || ... || \Pi_n; \overrightarrow{ctor_n} \ b_n \ x_n
   E \vdash \Pi : b \leadsto \Pi'; b_1/x_1 \dots b_n/x_n
                                                                          \overline{E \vdash : b \leadsto}; PHT_EMPTY
                                                                               fresh x_1 \dots x_n
                                                                               b = (b_1, \ldots, b_n)
E \vdash (pat_1, ..., pat_n) \ pat_1' ... \ pat_m' \Rightarrow exp, \Pi : b \leadsto pat_1 ... \ pat_n \ pat_1' ... \ pat_m' \Rightarrow exp, \Pi ; b_1/x_1 ... b_n/x_n
                                                                                                                                                                                                PHT_TUPLE
                                                      fresh x_1 \dots x_n
                                                      b = (b_1, ..., b_n)
       pat_{1}'' ... pat_{n}'' = \mathbf{duplicate}_{-}b_{1} ... b_{n} 
 E \vdash_{-} pat_{1}' ... pat_{m}' \Rightarrow exp, \Pi : b \leadsto pat_{1}'' ... pat_{n}'' pat_{1}' ... pat_{m}' \Rightarrow exp, \Pi ; b_{1}/x_{1} ... b_{n}/x_{n} 
                                                      fresh x_1 \dots x_n
                                                      b = (b_1, ..., b_n)
      \frac{pat_1'' ... pat_n'' = \mathbf{duplicate} \ id \ b_1 ... b_n}{E \vdash id \ pat_1' ... pat_m' \Rightarrow exp, \Pi : b \leadsto pat_1'' ... pat_n'' \ pat_1'' ... pat_m' \Rightarrow exp, \Pi ; b_1/x_1 ... b_n/x_n}
                                                                                                                                                                                PHT_VAR
     E \vdash funcl_1 \text{ and } ... \text{ and } funcl_n \leadsto \Theta; \Phi; \Delta \vdash def
                    id_1 \dots id_n \leadsto f
      \frac{E \vdash (pat_1 \Rightarrow exp_1), \, \dots, (pat_n \Rightarrow exp_n) : b/x \leadsto \Theta; \Phi; B; \Gamma; \Delta \vdash s : \tau}{E \vdash id_1 \; pat_1 = exp_1 \; \mathbf{and} \; \dots \; \mathbf{and} \; id_n \; pat_n = exp_n \leadsto \Theta; \Phi; \Delta \vdash \mathbf{function} \; f(x) = s}
                                                                                                                                                                            CFL_FUNCL
   E \vdash def \leadsto \Theta; \Phi; \Delta \vdash def_1, ..., def_n
                                                              E; \epsilon \vdash (typ_1, \dots, typ_n); \mathbf{snd} \ x \leadsto b; \phi
                                                              E; \epsilon \vdash typ; z \leadsto b_2; \phi_2
                                                                                                                                                                                                          CDEF_FUNSPI
\overline{E \vdash \mathbf{val}\ (typ_1, \dots, typ_n) \to typ_2\ \mathbf{effect}\ effect\ id \leadsto \Theta; \Phi; \Delta \vdash \mathbf{val}\ f: (x: \mathbf{unit} * b[\phi]) \to \{z: b_2 | \phi_2\}}
                                                        typquant \rightsquigarrow kinded\_id_1 ... kinded\_id_m, n\_constraint
                                                       is_kid_map M, b, fst x, kinded_id_1 ... kinded_id_m
                                                        E; M \vdash n\_constraint \leadsto \phi
                                                        E; M \vdash (typ_1, ..., typ_n); \mathbf{snd} \ x \leadsto b_1; \phi_1
                                                        E; M \vdash typ; z \leadsto b_2; \phi_2
                                                                                                                                                                                                                         CDEF.
E \vdash \mathbf{val} \ typquant \ (\overline{typ_i}^{i \in 1...n}) \rightarrow typ \ \mathbf{effect} \ effect \ id \leadsto \Theta; \Phi; \Delta \vdash \mathbf{val} \ f : (x : b * b_1[\phi \land \phi_1]) \rightarrow \{z : b_2|\phi_2\}
```

```
E \vdash id_1 \leadsto ctor_1, tid \quad \dots \quad E \vdash id_n \leadsto ctor_n, tid
                                                      E \vdash typ_1 \leadsto \tau_1 \quad \dots \quad E \vdash typ_n \leadsto \tau_n
\overline{E \vdash \mathbf{typedef}\ id = \mathbf{const}\ \mathbf{union}\ \{typ_1\ id_1;\ \dots; typ_n\ id_n\ ;^?\} \leadsto \Theta; \Phi; \Delta \vdash \mathbf{union}\ tid = \{\overrightarrow{ctor}_1: \tau_1,\ \dots, \overrightarrow{ctor}_n: \tau_n\}}
                                                                                E \vdash id_1 \leadsto c\dot{tor}_1, tid \quad \dots \quad E \vdash id_n \leadsto c\dot{tor}_n, tid
                                                                                typquant \rightsquigarrow kinded\_id_1 ... kinded\_id_m, n\_constraint
                                                                                is\_kid\_map\ M, b, fst\ x, kinded\_id_1... kinded\_id_m
                                                                                E; M \vdash n\_constraint \leadsto \phi
                                                                                E; M \vdash typ_1; \mathbf{snd} \ z \leadsto b_1; \phi_1 \quad \dots \quad E; M \vdash typ_1; \mathbf{snd} \ z \leadsto b_n; \phi_n
E \vdash id_1 \leadsto ctor_1, tid \quad \dots \quad E \vdash id_n \leadsto ctor_n, tid
\overline{E \vdash \mathbf{typedef}\ id = \mathbf{enumerate}\ \{id_1; \ \dots; id_n; ?\}} \leadsto \Theta; \Phi; \Delta \vdash \mathbf{union}\ tid = \{ctor_1: \{z: \mathbf{unit} | \top\}, \ \dots, ctor_n: \{z: \mathbf{unit} | \top\}\}
                               E \vdash funcl_1 \text{ and } ... \text{ and } funcl_n \leadsto \Theta; \Phi; \Delta \vdash def
       \overline{E \vdash \mathbf{function} \ rec\_opt \ effect\_opt \ funcl_1 \ \mathbf{and} \ ... \ \mathbf{and} \ funcl_n \leadsto \Theta; \Delta \vdash def}
                                        E \vdash \mathbf{val} \ typguant \ typ \ id \leadsto \Theta; \Phi; \Delta \vdash de \ f_1
                                        E \vdash funcl_1 \text{ and } ... \text{ and } funcl_n \leadsto \Theta; \Phi; \Delta \vdash def_2
                                                                                                                                                                   CDEF_FUNDEF_SP
\overline{E \vdash \mathbf{function}} \ rec\_opt \ typquant \ typ \ effect\_opt \ funcl_1 \ \mathbf{and} \ ... \ \mathbf{and} \ funcl_n \leadsto \Theta; \Phi; \Delta \vdash def_1, def_2
                                                           E \vdash typ \leadsto \tau
                                                                                                                    CDEF_REGISTER
                         \overline{E \vdash \mathbf{register} \ effect \ effect' \ typ \ id \leadsto \Theta; \Phi; \Delta, u : \tau \vdash}
```

 $id \sim tid$

 $E \vdash \overline{def_1 .. def_n \leadsto \Theta; \Phi \vdash def_1 .. def_m}$

$$\frac{E \vdash def \leadsto \Theta; \Phi \vdash def}{E \vdash def \ def_1 \dots def_n \leadsto \Theta; \Phi \vdash def \ def_1 \dots def_n} \quad \text{CDEFS_CONS}$$

Definition rules: 234 good 0 bad Definition rule clauses: 756 good 0 bad