
Model-Based Shape Optimization of Deformable Linear Objects via Robotic Manipulation

Research Practice – Proposed Project Structure

Remy Tribout · Technical University of Munich · May 23, 2026

This document outlines the proposed scope and structure of the Research Practice project, to establish a common basis for discussion and supervision.

Project Objective

- Study model-based methods for optimizing the shape of deformable linear objects under robotic manipulation.
- Define the optimization problem in terms of target shape, boundary actuation, robot end-effector pose, computation time, and final shape accuracy.
- Analyze the trade-off between physically accurate rod models and faster simplified or reduced-order modeling approaches.

Baseline Rod Modeling and Shape Optimization

- Use Cosserat rod modeling as the main theoretical baseline for DLO deformation.
- Formulate the shape optimization objective with elastic energy and target-shape error terms.
- Study numerical convergence, initialization sensitivity, and the possible need for continuation strategies.

Integration of the MATLAB Toolbox

- Investigate how the provided MATLAB toolbox for efficient simulation of flexible multibody systems can be included in the project.
- Focus on its geometrically exact beam formulation, structure-preserving variational time integration, and reduced deformation coordinates.
- Evaluate whether this modeling framework can speed up the shape optimization pipeline compared with the baseline rod optimization model.

Simplified Model for Initialization

- Study whether a simplified DLO model can provide a fast approximate shape or end-effector pose.
- Use the simplified result as a warm start for a higher-fidelity optimization model.
- Assess whether this reduces computation time while preserving the final shape accuracy.

Robotic Manipulation Interface

- Relate the optimized DLO boundary conditions or tip pose to a robot end-effector command.
- Keep the project focused on model-based shape optimization, while maintaining a clear connection to robotic manipulation.

Evaluation Criteria

The different modeling and optimization approaches will be compared according to:

- computation time;
- convergence behavior;
- final shape error with respect to the target shape;
- robustness with respect to initialization and target complexity;
- suitability for integration in a robotic manipulation pipeline.

References

- [1] A. Artinian et al., *Optimal Cosserat-based deformation control for robotic manipulation of linear objects*, IEEE AIM, 2023.
- [2] A. Artinian et al., *Closed-Loop Shape Control of Deformable Linear Objects Based on Cosserat Model*, IEEE RA-L, 2024.
- [3] A. Govoni et al., *Performance Analysis of a Mass-Spring-Damper DLO Model in Robotic Simulation Frameworks*, arXiv, 2025.
- [4] K. Almaghout et al., *Robotic co-manipulation of deformable linear objects for large deformation tasks*, Robotics and Autonomous Systems, 2024.
- [5] F. Surmont, D. Coache et al., *Geometrically exact static 3D Cosserat rods problem solved using a shooting method*, International Journal of Non-Linear Mechanics, 2020.
- [6] Y. Yu, H. Yang, J. Tan, X. Wang, *A Hybrid Force-Position Strategy for Shape Control of Deformable Linear Objects With Graph Attention Networks*, 2023.
- [7] C. Alessi et al., *Rod models in continuum and soft robot control: a review*, SAGE Journals, 2024.
- [8] M. Herrmann and P. Kotyczka, *Relative-Kinematic Formulation of Geometrically Exact Beam Dynamics Based on Lie Group Variational Integrators*, Computer Methods in Applied Mechanics and Engineering, 2024.
- [9] L. Pfeiffer, *Model-Based State Estimation and Control of Continuum Manipulators: Design and Experimental Evaluation*, Master's Thesis, TUM, 2025.