

Query Execution

Remy Wang

May 2026

Review how projection and filter work in relational algebra.

The first interesting operation is group by-aggregate.

We can implement it by first sorting, then summing over adjacent elements.

x	y
1	1
1	2
1	3
2	1
2	2

Because the table is sorted by x, each group is together, and we can sum over them.

A popular sorting algorithm is merge sort. Let's review. The key step in merge sort is merging two sorted lists.

A: **1**, 3, 5

B: **2**, 4, 6

out:

A: 1, **3**, 5

B: **2**, 4, 6

out: 1

A: 1, **3**, 5

B: 2, **4**, 6

out: 1, 2

A: 1, 3, **5**

B: 2, **4**, 6

out: 1, 2, 3

A: 1, 3, **5**

B: 2, 4, **6**

out: 1, 2, 3, 4

A: 1, 3, 5

B: 2, 4, **6**

out: 1, 2, 3, 4, 5

A: 1, 3, 5

B: 2, 4, 6

out: 1, 2, 3, 4, 5, 6

Using the merge operation, we can then implement sort recursively:

1. Break the input into two parts
2. Recursively sort each part
3. Merge them together

input:

[3, 1, 4, 1, 5, 9, 2, 6]

split:

[3, 1, 4, 1] [5, 9, 2, 6]

split:

[3, 1] [4, 1] [5, 9] [2, 6]

split:

[3] [1] [4] [1] [5] [9] [2] [6]

merge:

[1, 3] [1, 4] [5, 9] [2, 6]

merge:

[1, 1, 3, 4] [2, 5, 6, 9]

merge:

[1, 1, 2, 3, 4, 5, 6, 9]

Sorting can also be used to implement join.

A: **1**, 3, 5, 7

B: **2**, 3, 5, 6

out:

A: 1, **3**, 5, 7

B: **2**, 3, 5, 6

out:

A: 1, **3**, 5, 7

B: 2, **3**, 5, 6

out:

A: 1, 3, **5**, 7

B: 2, 3, **5**, 6

out: 3

A: 1, 3, 5, **7**

B: 2, 3, 5, **6**

out: 3, 5

A: 1, 3, 5, **7**

B: 2, 3, 5, 6

out: 3, 5

What if there are duplicates?

A: (3, a), (3, b), (5, c)

B: (3, x), (3, y), (5, z)

(letters distinguish rows with the same key)

Naively advancing both pointers on a match:

out: (3, a, x), (3, b, y), (5, c, z)

But we want *all* matching pairs — there should be 5.

When keys match, output the cross product of the *runs* of equal keys on both sides.

run in A: (3, a), (3, b)

run in B: (3, x), (3, y)

out: (3, a, x), (3, a, y), (3, b, x), (3, b, y)

Then advance past both runs.

A: (3, a), (3, b), **(5, c)**

B: (3, x), (3, y), **(5, z)**

out: ..., (5, c, z)

We can also implement group-by with a *map* (dictionary in Python).

For example, to group by *x* and sum over *y*:

```
d = {}
```

```
for (x, y) in t:
    if x not in d:
        d[x] = y
    else:
        d[x] += y
```

