

BELDAM CROSSLEY LIMITED

P.O. Box 2141, Lostock Lane Industrial Estate, Lostock Lane, Lostock, Bolton BL6 4BL. England. Tel: +44 (1204) 675700 Fax: +44 (1204) 675701 ISO 14001, 9001 Approved.

PRODUCT REFERENCE	PILOTPACK 3480	PRODUCT DATA SHEET NUMBER	650	
PRODUCT DESCRIPTION	PILOTPACK 3480 is a crossplait multi-filament packing, fully impregnated with PTFE. It is specially treated with graphite for excellent dissipation and further treated with lubricants for initial bedding-in. This packing style was previously referred to as IMP 75.			
	It is listed by the United Kingdom Water Fittings Byelaw Scheme Ref: 0409509.			
MATERIALS OF CONSTRUCTION	PTFE FILAMENT GRAPHITE LUBRICANTS			
COLOUR	BLACK			
TYPICAL PROPERTIES	TEMPERATURE RANGE	-200°C TO + 280°C		
	MAXIMUM PRESSURE	200	200 Bar	
	pH RANGE	1-1	1-14	
	MAXIMUM SPEED	20m	20ms ⁻¹	
	SUITABLE MEDIA		Mild acids and alkalis, water, steam, oils, effluent, paper stock, sludge and solvents	
SIZE RANGE	3 - 25 mm Larger sizes or specific lengths available on request.			
TYPICAL APPLICATIONS	Valves, pumps and mixers. Industries include paper, water, refineries and chemical.			
NOTE	This copy as dated supersedes all previous copies. We reserve the right to make changes to the product and datasheet without prior notification. As the application &/or conditions of use of this product are beyond BCL'S control, users should therefore satisfy themselves it is suitable for the intended purpose. Liability to users will only extend to the invoice value of the goods supplied, in respect of the above information.			
AUTHORISED BY: M. NICHOLAS.		ATE: 02.11.2004		