








		Algorithm	Brief description	Examples of usage
Traditional Machine Learning	Supervised Learning	SVM-based methods Support Vector Machines; One-class SVM; etc. 	Find a hyperplane that best separates instances of distinct classes, maximizing the distance from the decision boundary to the closest data points.	Guan <i>et al.</i> (2018) Collier <i>et al.</i> (2019) Nulsen <i>et al.</i> (2021)
		Regression-based methods Logistic regression 	Combine input values linearly using coefficient values (<i>i.e.</i> , weights), transforming the predictions into the range 0 and 1 using a sigmoid function.	Davoli <i>et al.</i> (2013) Gnad <i>et al.</i> (2015) Park <i>et al.</i> (2017)
		Tree-based methods Decision trees; Random Forests; Gradient Boosting Machines; etc. 	Recursively splits a training sample using the most informative feature to separate classes. Often, multiple trees are combined into ensembles.	Zhou <i>et al.</i> (2018) Jiang <i>et al.</i> (2019) Colaprico <i>et al.</i> (2020)
		Neural Network Artificial Neural Network 	Comprised of interconnected node layers (input, hidden, and output layers). Each node connects to another with an associated weight that is adjusted during training.	Althubaiti <i>et al.</i> (2019)
		Probabilistic Methods Naïve Bayes 	Use probability distributions to represent uncertainty about data and apply basic rules of probability theory to estimate posterior probabilities for a set of classes.	Wang <i>et al.</i> (2018)
		Other Techniques Decision Table; LWL; AdaBoost; Bayesian Factor; Regression Model 	Techniques that combine more than one learning strategy to improve classification performance, and thus do not fit in the previous categories defined.	Fu <i>et al.</i> (2012) U <i>et al.</i> (2014) Wang <i>et al.</i> (2020)
	Unsupervised Learning	Clustering K-means 	Groups instances into clusters based on their similarities so that instances in the same cluster should be more similar than those in different clusters.	Manolakos <i>et al.</i> (2014)
		Dimensionality Reduction Subspace learning 	Reduces the number of dimensions of the feature space (<i>i.e.</i> , inputs) by projecting the data into a lower dimensional space that captures the essence of data.	Xi <i>et al.</i> (2019)
Deep Learning		Convolutional Neural Network 	Particular implementation of artificial neural networks that process structured arrays of data and perform feature extraction from data through convolutional layers.	Tavanaei <i>et al.</i> (2017) Agajanianet <i>et al.</i> (2019) Luo <i>et al.</i> (2019)
		Graph Neural Network 	Class of neural networks designed to operate directly on data structured as graphs, capturing the dependence of graphs via message passing between the nodes.	Schulte-Sasse <i>et al.</i> (2019)