
QML for detecting AMR from EHR

Nihal Anand 
nihal@utdallas.edu
The University of Texas
at Dallas

Thanh Dat 
M1461015@cgu.edu.tw
Chang Gung University

Renata Wong 
D000019113@cgu.edu.tw
Chang Gung University

August 2026

ABSTRACT

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magnam aliquam quaerat voluptatem. Ut enim aequae doleamus animo, cum corpore dolemus, fieri tamen permagna accessio potest, si aliquod aeternum et infinitum impendere malum nobis opinemur. Quod idem licet transferre in voluptatem, ut postea variari voluptas distinguere possit.

Keywords First keyword · Second keyword · etc.

1 Introduction

Electronic Health Records (EHRs) have been used in the past to train machine learning (ML) models to predict the presence of antimicrobial-resistant bacteria. [1] While traditional testing is effective, it can also require a significant amount of time and expense. [2] As EHRs are available for the vast majority of patients for little to no additional cost, being able to predict which patients may be at higher risk for developing antimicrobial resistance from only EHRs is a problem of significant interest. In this study, we use the Antibiotic Resistance Microbiology Dataset Mass General Brigham (ARMD-MGB) dataset for EHRs to train quantum machine learning (QML) models to predict the presence of antimicrobial-resistant bacteria, obtaining Shapley values for each model and comparing the results to a classical machine learning (CML) baseline. This dataset has been used to predict antimicrobial resistance using CML methods, [3] but not yet for Shapley value analysis or QML. Other research has demonstrated the effectiveness of QML for detecting antimicrobial resistance from urine samples, [4] but even that cost may be too high or inaccessible in some areas, prompting investigation of the effectiveness of QML when using EHRs.

It is an active problem in the literature around the efficacy of QML to learn in which domains it is most useful. [5] We contribute to this literature by comparing performance to a baseline classical model, with separate models for each antibiotic, allowing us to create a fine-grained picture of how the quantum models perform in relation to the

classical models.

Applying Shapley values to QML models has some precedent in other applications in medicine, [6] but it is of special interest in application to detecting antimicrobial resistance from EHRs. Because EHRs contain several significant social factors, identifying which features of the model had the most impact on the model prediction has serious implications for disease prevention, as it allow public health policy makers to identify communities or areas that may be most at risk, or enable doctors to provide more support to patients in those communities. [7]

2 Methods

Several features were extracted from the raw dataset. They are Area Deprivation Index (ADI), Age, Gender, time (days) since last nursing home visit, time (days) since last dose of antibiotic, most recent procedure, time (days) since most recent procedure, the type of ward the patient was seen in, and a list of all comorbidities each patient had. This totalled 520 features. These features were chosen to train models that could be effective given minimally expensive information, not requiring microbiology testing or body sample collection. The dataset was then segregated by antibiotic, and only those antibiotics with subjects between 4500 and 15000 subjects were used (for a total of 9 antibiotics), balancing generalizability and size so training could be completed in a reasonable amount of time.




Figure 1: End-to-end data processing, resampling, and dual-architecture modeling pipeline.

We used a Histogram-based Gradient Boosting Classifier (HistGB) from the scikit-learn package to serve as our classical baseline. It is based on the Gradient Boosting Classifier, which was chosen because of its high accuracy and performance on similar datasets in the medical field. [8] The Histogram-based version of the model was chosen for its performance on large datasets. [9]

While the classical model could run on the full set of 520 features, the quantum model could not. So, PCA from the scikit-learn package was used to reduce the number of features being used by the quantum circuit. The vast majority of the 520 features (508) were the comorbidities of each patient, so these were reduced by PCA to 12 features, for a total of 20 features. A standard list of comorbidity groupings was not used, in order to identify latent correlations within our specific dataset without any potential bias from existing groupings.

Because the data was severely imbalanced on our target with varying imbalance for each antibiotic, we also implemented undersampling and SMOTENC oversampling using the

imbalanced-learn package to balance the dataset, training different models for each situation. In total, for the classical models we had 6 models for each antibiotic (raw, oversampled, and undersampled for 521 and 20 features) and for the quantum models we had 3 (raw, oversampled, and undersampled).

We used a Variational Quantum Circuit (VQC) implemented using the qiskit-machine-learning package. We used the Aer Sampler in statevector mode with GPU acceleration for the sampler. We used the EfficientSU2 circuit from qiskit for the feature map with 1 repetition, such that 4 features were mapped to a qubit. The EfficientSU2 circuit was constructed with full entanglement. We used the RealAmplitudes circuit from qiskit for the ansatz with 3 repetitions to maximize expressibility without increasing circuit depth too much. We used COBYLA from qiskit-machine-learning for the optimizer with 100 maximum iterations.

From each model we gathered its accuracy score, a confusion matrix, Area Under the Receiver Operating Characteristic Curve (AUROC), and Precision-Recall Area Under the Curve (PRAUC). SHAP values were also calculated for each model.

3 Results

4 Discussion

5 Conclusion

Bibliography

- [1] Z. Almalki, A. Althagafi, and S. Al-Shareef, “Predicting Antimicrobial Resistance Using Machine Learning on Electronic Health Records: A Comparative Study of Ensemble Models,” p. , Sep. 2025, doi: 10.21203/rs.3.rs-7529240/v1.
- [2] I. Gajic *et al.*, “Antimicrobial Susceptibility Testing: A Comprehensive Review of Currently Used Methods,” *Antibiotics*, vol. 11, no. 4, 2022, doi: 10.3390/antibiotics11040427.
- [3] X. Liu *et al.*, “Patient-specific antibiotic susceptibility ranking for empirical treatment of gram-negative bloodstream infection: a retrospective clinical decision-support and transportability study,” p. , May 2026. doi: 10.21203/rs.3.rs-9854692/v1.
- [4] K. Rhrissorrakrai *et al.*, “Data complexity signature predicts quantum projected learning benefit for antibiotic resistance.” [Online]. Available: <https://arxiv.org/abs/2601.15483>
- [5] M. Cerezo, G. Verdon, H.-Y. Huang, L. Cincio, and P. J. Coles, “Challenges and opportunities in quantum machine learning,” *Nature Computational Science*, vol. 2, pp. 567–576, 2022, [Online]. Available: <https://api.semanticscholar.org/CorpusID:252323115>
- [6] X. Huang *et al.*, “An integrated strategy based on radiomics and Quantum Machine Learning: Diagnosis and clinical interpretation of pulmonary ground-glass nodules,” *BMC Medical Imaging*, vol. 25, no. 1, Jul. 2025, doi: 10.1186/s12880-025-01813-y.

- [7] M. Cavallaro, E. Moran, B. Collyer, N. D. McCarthy, C. Green, and M. J. Keeling, "Informing antimicrobial stewardship with explainable AI," *medRxiv*, 2022, doi: 10.1101/2022.08.12.22278678.
- [8] X. Huang *et al.*, "An integrated strategy based on radiomics and Quantum Machine Learning: Diagnosis and clinical interpretation of pulmonary ground-glass nodules," *BMC Medical Imaging*, vol. 25, no. 1, Jul. 2025, doi: 10.1186/s12880-025-01813-y.
- [9] M. Saied, S. Guirguis, and M. Madbouly, "A comparative study of using boosting-based machine learning algorithms for IOT network intrusion detection," *International Journal of Computational Intelligence Systems*, vol. 16, no. 1, Nov. 2023, doi: 10.1007/s44196-023-00355-x.