

Advanced Trigonometry Calculator 2.1.8

Bilingual User Guide

Guia de Utilizador Bilingue

English / Portugues (Portugal)

Contents / Indice

English

1. What ATC is
2. What ATC is not
3. Quick Start
4. Input basics
5. Interactive prompt
6. Angle mode
7. Precision
8. Constants and previous answers
9. Arithmetic
10. Trigonometry
11. Hyperbolic functions
12. Logarithms
13. Complex numbers
14. Automatic multiplication
15. Variables
16. Matrices
17. Statistics and probability
18. DSP
19. Polynomial tools
20. Equation solving
21. Solver
22. Function study
23. Graph
24. Guided calculation modules
25. Financial, geometry, physics and unit conversion recipes
26. Time commands
27. Sorting
28. TXT processing and command bridge
29. Scripting
30. User functions
31. Settings and environment commands
32. File and folder commands
33. Export prompts
34. Verbose resolution
35. Cookbook / Recipes
36. Recipes / Usage profiles
37. Best practices
38. Practical troubleshooting
39. Documentation and test coverage

Portugues (Portugal)

1. O que é o ATC
2. O que o ATC não é
3. Quick Start
4. Bases de input
5. Prompt interativo
6. Modo angular
7. Precisao
8. Constantes e respostas anteriores
9. Aritmética
10. Trigonometria
11. Funcoes hiperbolicas
12. Logaritmos
13. Numeros complexos
14. Multiplicacao automática
15. Variáveis
16. Matrizes
17. Estatística e probabilidade
18. DSP
19. Polinomios
20. Resolucao de equacoes
21. Solver
22. Estudo de funções
23. Grafico
24. Modulos guiados
25. Receitas por area
26. Tempo
27. Ordenacao
28. TXT processing e command bridge
29. Scripting
30. Funcoes do utilizador
31. Settings e ambiente
32. Ficheiros e pastas
33. Exportacao
34. Verbose resolution
35. Cookbook / Receitas
36. Perfis de utilização
37. Boas práticas
38. Resolucao de problemas
39. Documentação e testes

English

ATC 2.1.8 User Guide

Advanced Trigonometry Calculator Full User Guide

Version: ATC 2.1.8 Language: English Author: Renato Alexandre dos Santos Freitas

This guide is the expanded repository user guide for Advanced Trigonometry Calculator (ATC). It is based on the existing online user guide, the current 2.1.8 documentation, and the automated regression coverage available in this repository.

1. What ATC is

ATC is a free, open-source Windows command-line mathematical application. It is designed for fast local mathematical work through typed commands and expressions.

Typical use cases:

- quick scientific calculations;
- trigonometry and inverse trigonometry;
- complex-number calculations;
- matrix work;
- statistics and probability;
- DSP helpers;
- polynomial simplification;
- equation solving and systems of equations;
- reusable variables and expressions;
- guided interactive calculation modules;
- TXT-file based command workflows.

2. What ATC is not

ATC deliberately focuses on practical command-driven mathematical computation instead of trying to be a universal CAS.

- ATC is not a full general-purpose CAS like Mathematica, Maple, SageMath, or SymPy.

- ATC is not designed to symbolically prove arbitrary mathematical theorems.

- ATC is not intended to replace domain-specific professional engineering validation tools.

- ATC focuses on numeric computation, command-driven workflows, educational use, implemented symbolic/numeric hybrid features, and fast local execution.

- Some symbolic behavior exists, but only where explicitly supported and tested.

3. Quick Start

ATC is a free, open-source Windows command-line mathematical application. It evaluates typed mathematical expressions, documented commands and guided workflows. It is best understood as a practical local calculator, not as a universal symbolic CAS.

Open ATC by launching `atc.exe` from the built Release folder or through the installed ATC shortcut/launcher when available. The prompt accepts one command or expression per line.

First commands to try:

```
2+2
sin(pi/2)
mode
solve equation(x^2-5*x+6)
solver(x+2)
create matrix(foo\2\2\3)
see variables
exit
```

Basic reading rules:

- `_` is used by ATC as a negative marker in many documented command forms and outputs, for example `_5` means `-5`.
- `#0`, `#1`, and later indexes refer to previous results in the current session.
- A direct expression is evaluated immediately, such as `2+2`.
- A command starts a named ATC action, such as `mode` or `solve equation(...)`.
- A guided module opens an interactive workflow, such as ``financial calculations or unit conversions``.

Recommended first workflow:

```
mode
2+2
sin(pi/2)
solve equation(x^2-5*x+6)
verbose resolution(1)
sin(pi/6)
verbose resolution(0)
```

If a result matters, confirm the angle mode and precision mode before relying on it.

4. Input basics

ATC expressions are typed directly at the prompt.

```
2+3*4
sqrt(9)
sin(pi/2)
log(100)
```

Stable example outputs:

```
#0=14
#1=3
#2=1
#3=2
```

ATC uses `_` as a negative marker in many documented inputs and outputs:

```
_6+2
```

Expected result:

```
#0=-4
```

Scientific notation uses uppercase E:

```
1E3
1E-3
```

5. Interactive prompt

ATC 2.1.8 includes a custom prompt editor:

- Tab completes documented commands, mathematical functions, aliases and user

functions;

- repeated Tab cycles possible completions;
- Up and Down navigate command history;
- Left, Right, Home, End, Delete and Backspace edit the current

input line.

This improves speed while keeping calculation semantics in the normal ATC parser.

6. Angle mode

Use:

mode

The menu offers:

```
radian -> 1
degree -> 2
gradian -> 3
```

Examples:

```
sin(pi/2)
sin(30)
```

Use `sin(pi/2)` in radian mode and `sin(30)` in degree mode.

7. Precision

ATC 2.1.8 supports:

- double
- Boost `mp_float`

Persisted precision mode:

```
higherprecision(1)
higherprecision(0)
```

The setting is applied after restarting ATC.

Useful precision commands:

```
dp15dppi
dp50dppi
dp50dpe
dp50dppmaxprecpi
```

Stable high-precision examples:

```
dp50dppi
3.14159265358979323846264338327950288419716939937511
```

```
dp50dpe
2.71828182845904523536028747135266249775724709369996
```

`maxprec` is useful when a single expression needs higher precision without changing the persisted precision mode.

8. Constants and previous answers

Common constants:

```
pi
e
i
INF
__INF
true
false
```

Previous result references use ATC result indexes, for example:

```
#0
```

#1

Use this to build calculations step by step.

9. Arithmetic

Examples:

```
2+3*4
(2+3)*4
8/4
2^10
5!
abs(_7)
100rest(3)
100quotient(3)
rtD4D(16)
```

Stable expected outputs include:

```
2+3*4      -> 14
(2+3)*4    -> 20
2^10       -> 1024
5!         -> 120
abs(_7)    -> 7
rtD4D(16)  -> 2
```

10. Trigonometry

Examples:

```
sin(pi/2)
cos(0)
tan(pi/4)
sec(0)
cosec(pi/2)
cotan(pi/4)
asin(1)
acos(1)
atan(1)
acosec(1)
asec(1)
acotan(1)
```

When using degree mode:

```
mode
sin(30)
```

Expected:

```
#n=0.5
```

11. Hyperbolic functions

Examples:

```
sinh(0)
cosh(0)
tanh(0)
sech(0)
cosech(1)
cotanh(1)
asinh(0)
acosh(1)
atanh(0)
asech(1)
acosech(1)
acotanh(2)
```

These are useful for scientific and engineering formulas involving hyperbolic relationships.

12. Logarithms

Examples:

```
log(100)
ln(e)
logb2b(8)
```

Expected:

```
log(100)  -> 2
ln(e)     -> 1
logb2b(8) -> 3
```

13. Complex numbers

ATC supports complex values with `i`.

Examples:

```
2i
3(2i)
sin(30+30i)
asin(sin(30+30i))
```

Complex-number behavior depends on the selected angle mode for trigonometric functions.

14. Automatic multiplication

ATC can infer multiplication in documented forms.

Examples:

```
2pi
pi2
2e
2(3+4)
(1+1)(2+3)
2sin(pi/2)
sin(pi/2)2
2i
3(2i)
```

With variables:

```
x=4
2x
x(4)
(4)x
xpi
pix
xe
xsin(pi/2)
```

When a variable name exists exactly, ATC should prefer the existing variable over splitting it into implied products.

15. Variables

Examples:

```
data=5
data+1
energy=10
energy+1
```

ATC 2.1.8 accepts broader variable names than older parser versions while preserving reserved function and constant names.

Useful commands:

```
see variables
renamed variables
eliminate variables
see results
eliminate results
```

16. Matrices

Create a matrix:


```
create matrix(foo\2\2\3)
```

Matrix helpers:

```
min(foo)
max(foo)
avg(foo)
linsnum(foo)
colsum(foo)
getlins(foo)
getcols(foo)
```

Matrix arithmetic:

```
foo+foo
foo-foo
foo*foo
foo^2
foo^T
foo^R
foo/2
2*foo
```

Use matrices for tabular numeric workflows, linear algebra helpers and repeated numeric data.

17. Statistics and probability

List helpers:

```
min(3\_1\2)
max(3\_1\2)
avg(2\4\6)
```

Expected:

```
min(3\_1\2) -> -1
max(3\_1\2) -> 3
avg(2\4\6) -> 4
```

Gaussian/probability helpers:

```
gerror(0)
gerrorc(0)
gerrorinv(0)
gerrorcinv(1)
qfunc(0)
qfuncinv(0.5)
```

Guided module:

```
statistics calculations
```

Use the guided module for menu-based workflows such as variance and standard deviation where available.

18. DSP

Signal helpers:

```
sinc(0)
sinc(1)
fft(1\0\0\0)
fft(1\2\3)
ifft(1\0\0\0)
ifft(1\1\1\1)
```

Use these commands for compact signal-processing experiments and educational checks.

19. Polynomial tools

Simplify supported polynomial forms:

```
simplify polynomial(x)
simplify polynomial(x+1)
simplify polynomial(x+x+1)
simplify polynomial(x^2-5*x+6)
simplify polynomial((x-2)*(x-3))
simplify polynomial((x+1)*(x+1))
```

```
simplify polynomial((x-1)^2)
simplify polynomial((x+2)*(x-2))
simplify polynomial((x+2i)*(x-2i))
simplify polynomial(((x-5)(x+2))/(x-5))
```

Convert roots to a polynomial:

```
roots to polynomial(2\3)
roots to polynomial(2\7\12)
roots to polynomial(6.5i\_6.5i)
roots to polynomial(1+2i\1-2i)
roots to polynomial(0\1\2)
```

Stable example:

```
roots to polynomial(2\3)
(1+0i)x^2+(-5+0i)x^1+(6+0i)
```

20. Equation solving

Quadratic command:

```
solve quadratic equation(1\_5\6)
solve quadratic equation(1\_2\1)
solve quadratic equation(1\2\5)
```

Systems:

```
solve equations system(1\1\5;1\_1\1)
```

Polynomial equations:

```
solve equation(x+2)
solve equation(x^2-5*x+6)
solve equation(x^7-12)
solve equation(1\2\3\4\5)
solve equation((x-1)(x-2))
solve equation(((x-5)(x+2))/(x-5))
solve equation(x^25-100)
```

Stable examples:

```
solve equation(x+2)
x1=-2

solve equation(x^2-5*x+6)
x1=3
x2=2
```

21. Solver

The solver (. . .) command supports numerical solving paths and selected fast-path normalizations. ATC 2.1.8 validates each candidate against the original expression before returning it. A solution may be real or complex. If the earlier solver path does not produce a valid root, a general numerical fallback is attempted.

Examples:

```
solver(sin(x)-0.5)
solver(0.5-sin(x))
solver(cos(x)-cos(60))
solver(tan(x)-tan(45))
solver(asin(sin(30))-x)
solver(qfunc(x)-qfunc(0.34233))
solver(x^2-12x-9)
solver(x+2)
solver(((x-5)(x+2))/(x-5))
solver((x-e+pii)(x-e-pii))
solver(x^2-2)
solver(x^2+1)
solver(x^2-2i)
solver(x^2+22)
```

The last four examples cover validated real and complex polynomial roots. When no candidate satisfies the original expression, ATC reports:

```
ATC was unable to find a valid solution.
```

Angle-mode behavior matters for trigonometric solver examples. In degree mode, `solver(sin(x)-0.5)` is expected to return a degree-based solution.

22. Function study

Examples:

```
function study(x+1)
function study(x^2)
function study(x^2-4)
function study(_x^2)
function study(1/(x-1))
function study((x^2-1)/(x-1))
function study((1-x^2)/(x^2-4))
function study(x/(x^2-9))
function study((x+1)/(x^2+1))
```

Function study reports items such as domain, intercepts, asymptotes, symmetries, sign, monotony, concavity and codomain where supported.

23. Graph

Examples:

```
graph settings
graph(x)
graph(x;_2\2\1)
```

Graph behavior is console-based. Automated tests cover deterministic smoke paths and settings mutation; full visual inspection is still best done manually.

24. Guided calculation modules

ATC includes guided menus for:

```
triangles rectangles solver
arithmetic matrix solver
financial calculations
geometry calculations
statistics calculations
physics calculations
unit conversions
microeconomics calculations
```

These modules prompt for values and options. They are useful when the user prefers guided input over a single compact expression.

25. Financial, geometry, physics and unit conversion recipes

Finance:

```
financial calculations
100*15/100
```

Geometry:

```
geometry calculations
```

Physics:

```
physics calculations
```

Unit conversion:

```
unit conversions
```

Microeconomics:

```
microeconomics calculations
```

For guided menus, exact output depends on the selected options and entered values.

26. Time commands

Examples:

```
time
calendar(2026)
day of week(y2026m6d20)
day of week(d20m6y2026)
time difference calculations
actual time response
```

Interactive or continuously running tools include stopwatch, timer, big timer, clock and big clock variants. Use them manually when real time or opened windows are involved.

27. Sorting

Numeric sorting:

```
ascending order(3\1\2)
descending order(3\1\2)
ascending order(_3\1\_2\0)
descending order(_3\1\_2\0)
```

ASCII sorting:

```
ascii order
inverse ascii order
```

Some sorting commands can export reports.

28. TXT processing and command bridge

Core TXT commands:

```
predefine txt
solve txt
solve txt(name)
open txt("C:\Temp\file.txt")
to solve
enable txt detector
eliminate strings
atc from cmd
atc over cmd
auto solve txt
```

Typical flow:

1. Create a TXT file with one ATC command per line.
2. Run `predefine txt` and provide the path.
3. Run `solve txt`.
4. ATC creates an `_answers.txt` response file.

Example TXT input:

```
2+2
sqrt(9)
solver(x-2)
solve equation((x-1)(x-2))
simplify polynomial((x+1)(x-1))
2++
2+3
```

ATC should keep processing after an invalid line and report the syntax error for that line.

29. Scripting

The online guide documents scripting helpers such as:

```
print(...)
get(...)
sprintf(...)
while
for
if
else
switch
case
cls()
break
return
```

```
replace
replace by index
count occurrences
delete x occurrences
is contained
calc
is equal
get positive value
is to write
is variable
is contained variable
is contained by index
strlen
```

Use scripting for repeatable command workflows. Keep scripts small and test them with known values before using them on larger calculations.

30. User functions

User functions live under the ATC user-functions folder. Autocomplete can suggest available user functions as `atc_<name>(` completions.

Use user functions when an expression should be reused by name.

31. Settings and environment commands

Common commands:

```
current settings
verbose resolution
verbose resolution(1)
verbose resolution(0)
numerical systems
si prefixes
actual time response
dimensions
window
about
auto adjust window
enable atc intro
disable atc intro
clean history
clean
exit
```

Use `current settings` to inspect persisted configuration.

32. File and folder commands

ATC manages folders such as:

- ATC data folder;
- Scripts examples;
- Source code;
- Strings;
- To solve;
- User functions.

Commands may open Explorer, Notepad or external viewers. In automated testing, these actions are mocked; in normal use they open real windows.

33. Export prompts

Some commands ask:

```
Export result? (Yes -> 1 \ No -> 0)
```

Use:

1

to export, or:

0

to skip export.

34. Verbose resolution

Enable:

```
verbose resolution(1)
```

Disable:

```
verbose resolution(0)
```

Verbose mode explains calculation processing. It is useful for learning and debugging, but normal calculations are quieter with verbose mode disabled.

35. Cookbook / Recipes

Online project documentation:

- [ATC Cookbook](#)

It contains practical workflows for scientific calculations, trigonometry, polynomial solving, matrices, statistics, DSP, TXT processing, verbose resolution and guided modules.

36. Recipes / Usage profiles

Engineering

```
solve equation(x^2-5*x+6)
create matrix(foo\2\2\3)
foo^2
unit conversions
physics calculations
```

Education

```
2+3*4
sin(pi/2)
mode
geometry calculations
function study(x^2)
```

DSP

```
sinc(0)
fft(1\0\0\0)
ifft(1\1\1\1)
sin(pi/2)+cos(0)
```

Statistics

```
avg(2\4\6)
min(3\_1\2)
max(3\_1\2)
statistics calculations
qfunc(0)
```

Finance

```
financial calculations
100*15/100
```

37. Best practices

Online project documentation:

- [ATC Best Practices](#)

Use it for reliable day-to-day workflows: start with small expressions, confirm angle mode, validate parentheses, choose the right solver path, use TXT files for repeatable batches and avoid undocumented behavior.

38. Practical troubleshooting

If an expression fails:

- check parentheses balance;
- check angle mode;
- check whether `_` is needed for negative input;
- check whether the command is interactive;
- simplify the expression and test smaller pieces;
- use `verbose resolution(1)` for a more detailed trace;
- confirm whether the feature is documented and covered by regression tests.

39. Documentation and test coverage

Online project documentation:

- [Testing](#)

Current validated regression result:

```
All: 376 passed, 0 failed
SolverComplex: 14 passed, 0 failed
Txt: 15 passed, 0 failed
Settings: 7 passed, 0 failed
```

This guide should evolve with the tests and the documented behavior of ATC 2.1.8.

Portugues (Portugal)

Guia de Utilizador do ATC 2.1.8

Guia Completo de Utilizador do Advanced Trigonometry Calculator

Versão: ATC 2.1.8 Idioma: Português de Portugal Autor: Renato Alexandre dos Santos Freitas

Este é o guia de utilizador expandido do Advanced Trigonometry Calculator (ATC). Foi construído a partir do guia online existente, da documentação 2.1.8 atual e da cobertura automatizada de regressão deste repositório.

1. O que é o ATC

O ATC é uma aplicação matemática gratuita, open source e de linha de comandos para Windows. Foi desenhada para trabalho matemático local rápido através de comandos e expressões textuais.

Casos típicos:

- cálculos científicos rápidos;
- trigonometria e trigonometria inversa;
- números complexos;
- matrizes;
- estatística e probabilidade;
- funções DSP;
- simplificação polinomial;
- resolução de equações e sistemas;
- variáveis e expressões reutilizáveis;
- módulos interativos guiados;
- processamento de ficheiros TXT.

2. O que o ATC não é

O ATC foca-se deliberadamente em computação matemática prática orientada por comandos, em vez de tentar ser um CAS universal.

- O ATC não é um CAS geral completo como Mathematica, Maple, SageMath ou SymPy.

- O ATC não foi desenhado para provar teoremas matemáticos arbitrários.

- O ATC não substitui ferramentas profissionais de validação específicas de engenharia.

- O ATC foca-se em cálculo numérico, fluxos por comandos, uso educativo, funcionalidades híbridas simbólicas/numéricas implementadas e execução local rápida.

- Existe comportamento simbólico apenas onde está explicitamente suportado e testado.

3. Quick Start

O ATC é uma aplicação matemática de linha de comandos para Windows, gratuita e open-source. Avalia expressões matemáticas, comandos documentados e workflows guiados. Deve ser entendido como uma calculadora local prática, não como um CAS simbólico universal.

Abrir o ATC executando `atc.exe` a partir da pasta Release criada pelo build ou através do atalho/launcher instalado quando existir. O prompt aceita um comando ou expressão por linha.

Primeiros comandos a experimentar:

```
2+2
sin(pi/2)
mode
solve equation(x^2-5*x+6)
solver(x+2)
create matrix(foo\2\2\3)
see variables
exit
```

Regras básicas de leitura:

- `_` é usado pelo ATC como marcador de negativo em várias formas documentadas e outputs; por exemplo `_5` significa `-5`.
- `#0`, `#1` e índices seguintes referem resultados anteriores da sessão atual.
- Uma expressão direta é avaliada de imediato, por exemplo `2+2`.
- Um comando inicia uma ação ATC, por exemplo `mode` ou `solve equation(...)`.
- Um módulo guiado abre um workflow interativo, por exemplo ``financial calculations` ou `unit conversions``.

Workflow inicial recomendado:

```
mode
2+2
sin(pi/2)
solve equation(x^2-5*x+6)
verbose resolution(1)
sin(pi/6)
verbose resolution(0)
```

Quando um resultado é importante, confirmar primeiro o modo angular e o modo de precisão.

4. Bases de input

As expressões são escritas diretamente no prompt.

```
2+3*4
sqrt(9)
sin(pi/2)
log(100)
```

Outputs estáveis:

```
#0=14
#1=3
#2=1
#3=2
```

O ATC usa `_` como marcador negativo em muitos inputs e outputs documentados:

```
_6+2
```

Resultado esperado:

```
#0=-4
```

Notação científica usa E maiúsculo:

```
1E3
1E-3
```

5. Prompt interativo

O ATC 2.1.8 inclui editor de linha:

- Tab completa comandos, funções matemáticas, aliases e funções do utilizador;
- Tab repetido alterna entre complementos possíveis;
- Up e Down navegam no histórico;
- Left, Right, Home, End, Delete e Backspace editam a linha atual.

6. Modo angular

Use:

```
mode
```

Opcoes:

```
radian -> 1
degree -> 2
gradian -> 3
```

Exemplos:

```
sin(pi/2)
sin(30)
```

Use $\sin(\pi/2)$ em radianos e $\sin(30)$ em graus.

7. Precisão

O ATC 2.1.8 suporta:

- double
- Boost mp_float

Alternancia persistente:

```
higherprecision(1)
higherprecision(0)
```

A definição é aplicada após reiniciar o ATC.

Comandos uteis:

```
dp15dppi
dp50dppi
dp50dpe
dp50dpmxprecpi
```

Exemplos validados:

```
dp50dppi
3.14159265358979323846264338327950288419716939937511
```

```
dp50dpe
2.71828182845904523536028747135266249775724709369996
```

maxprec permite usar mais precisão numa expressão sem alterar o modo persistente.

8. Constantes e respostas anteriores

Constantes comuns:

```
pi
e
i
INF
-INF
true
false
```

Resultados anteriores:

```
#0
#1
```

9. Aritmética

Exemplos:

```
2+3*4
(2+3)*4
8/4
2^10
5!
abs(_7)
100rest(3)
100quotient(3)
rtD4D(16)
```

Resultados esperados:

```
2+3*4      -> 14
(2+3)*4    -> 20
2^10       -> 1024
5!         -> 120
abs(_7)    -> 7
rtD4D(16)  -> 2
```

10. Trigonometria

```
sin(pi/2)
cos(0)
tan(pi/4)
sec(0)
cosec(pi/2)
cotan(pi/4)
asin(1)
acos(1)
atan(1)
acosec(1)
asec(1)
acotan(1)
```

Em modo grau:

```
mode
sin(30)
```

Resultado esperado:

```
#n=0.5
```

11. Funcoes hiperbolicas

```
sinh(0)
cosh(0)
tanh(0)
sech(0)
cosech(1)
cotanh(1)
asinh(0)
acosh(1)
atanh(0)
asech(1)
acosech(1)
acotanh(2)
```

12. Logaritmos

```
log(100)
ln(e)
logb2b(8)
```

Resultados esperados:

```
log(100)  -> 2
ln(e)     -> 1
logb2b(8) -> 3
```

13. Numeros complexos

```
2i
3(2i)
sin(30+30i)
asin(sin(30+30i))
```

O modo angular influencia funções trigonométricas com argumentos complexos.

14. Multiplicacao automática

```
2pi
pi2
2e
2(3+4)
(1+1)(2+3)
2sin(pi/2)
sin(pi/2)2
2i
3(2i)
```

Com variáveis:

```
x=4
2x
x(4)
(4)x
xpi
pix
xe
xsin(pi/2)
```

Quando existe uma variavel com nome exato, o ATC deve preferir essa variavel em vez de dividir o nome em produtos implicitos.

15. Variáveis

```
data=5
data+1
energy=10
energy+1
```

Comandos uteis:

```
see variables
renamed variables
eliminate variables
see results
eliminate results
```

16. Matrizes

Criar matriz:

```
create matrix(foo\2\2\3)
```

Helpers:

```
min(foo)
max(foo)
avg(foo)
linsnum(foo)
colsnum(foo)
getlins(foo)
getcols(foo)
```

Operacoes:

```
foo+foo
foo-foo
foo*foo
foo^2
foo^T
foo^R
foo/2
```

```
2*foo
```

17. Estatística e probabilidade

```
min(3\1\2)
max(3\1\2)
avg(2\4\6)
```

Resultados:

```
min(3\1\2) -> -1
max(3\1\2) -> 3
avg(2\4\6) -> 4
```

Helpers gaussianos/probabilidade:

```
gerror(0)
gerrorc(0)
gerrorinv(0)
gerrorcinv(1)
qfunc(0)
qfuncinv(0.5)
```

Módulo guiado:

```
statistics calculations
```

18. DSP

```
sinc(0)
sinc(1)
fft(1\0\0\0)
fft(1\2\3)
ifft(1\0\0\0)
ifft(1\1\1\1)
```

19. Polinomios

Simplificacao:

```
simplify polynomial(x)
simplify polynomial(x+1)
simplify polynomial(x+x+1)
simplify polynomial(x^2-5*x+6)
simplify polynomial((x-2)*(x-3))
simplify polynomial((x+1)*(x+1))
simplify polynomial((x-1)^2)
simplify polynomial((x+2)*(x-2))
simplify polynomial((x+2i)*(x-2i))
simplify polynomial(((x-5)(x+2))/(x-5))
```

Raizes para polinómio:

```
roots to polynomial(2\3)
roots to polynomial(2\7\12)
roots to polynomial(6.5i\_6.5i)
roots to polynomial(1+2i\1-2i)
roots to polynomial(0\1\2)
```

Exemplo:

```
roots to polynomial(2\3)
(1+0i)x^2+(-5+0i)x^1+(6+0i)
```

20. Resolucao de equacoes

Quadraticas:

```
solve quadratic equation(1\_5\6)
solve quadratic equation(1\_2\1)
solve quadratic equation(1\2\5)
```

Sistemas:

```
solve equations system(1\1\5;1\_1\1)
```

Equacoes polinomiais:

```

solve equation(x+2)
solve equation(x^2-5*x+6)
solve equation(x^7-12)
solve equation(1\2\3\4\5)
solve equation((x-1)(x-2))
solve equation(((x-5)(x+2))/(x-5))
solve equation(x^25-100)

```

Exemplos:

```

solve equation(x+2)
x1=-2

solve equation(x^2-5*x+6)
x1=3
x2=2

```

21. Solver

O comando `solver( . . . )` suporta caminhos de resolução numérica e normalizações rápidas seleccionadas. O ATC 2.1.8 valida cada candidato na expressão original antes de o devolver. Uma solução pode ser real ou complexa. Se o caminho anterior do `solver` não produzir uma raiz válida, é tentado um fallback numérico geral.

```

solver(sin(x)-0.5)
solver(0.5-sin(x))
solver(cos(x)-cos(60))
solver(tan(x)-tan(45))
solver(asin(sin(30))-x)
solver(qfunc(x)-qfunc(0.34233))
solver(x^2-12x-9)
solver(x+2)
solver(((x-5)(x+2))/(x-5))
solver((x-e+pii)(x-e-pii))
solver(x^2-2)
solver(x^2+1)
solver(x^2-2i)
solver(x^2+22)

```

Os últimos quatro exemplos cobrem raízes polinomiais reais e complexas validadas. Quando nenhum candidato satisfaz a expressão original, o ATC apresenta:

```
ATC was unable to find a valid solution.
```

O modo angular é importante nos exemplos trigonométricos.

22. Estudo de funções

```

function study(x+1)
function study(x^2)
function study(x^2-4)
function study(_x^2)
function study(1/(x-1))
function study((x^2-1)/(x-1))
function study((1-x^2)/(x^2-4))
function study(x/(x^2-9))
function study((x+1)/(x^2+1))

```

O estudo pode apresentar domínio, zeros, assintotas, simetrias, sinal, monotonia, concavidade e contradomínio quando suportado.

23. Grafico

```

graph settings
graph(x)
graph(x;_2\2\1)

```

O gráfico é renderizado na consola. A validação visual completa continua a ser mais adequada manualmente.

24. Modulos guiados

```

triangles rectangles solver
arithmetic matrix solver
financial calculations

```

```
geometry calculations
statistics calculations
physics calculations
unit conversions
microeconomics calculations
```

Estes módulos pedem valores e opções ao utilizador.

25. Receitas por area

Finanças:

```
financial calculations
100*15/100
```

Geometria:

```
geometry calculations
```

Física:

```
physics calculations
```

Conversoes:

```
unit conversions
```

Microeconomia:

```
microeconomics calculations
```

26. Tempo

```
time
calendar(2026)
day of week(y2026m6d20)
day of week(d20m6y2026)
time difference calculations
actual time response
```

Ferramentas como stopwatch, timer, big timer, clock e big clock devem ser usadas manualmente quando envolvem tempo real ou janelas abertas.

27. Ordenacao

```
ascending order(3\1\2)
descending order(3\1\2)
ascending order(_3\1\_2\0)
descending order(_3\1\_2\0)
ascii order
inverse ascii order
```

28. TXT processing e command bridge

```
predefine txt
solve txt
solve txt(name)
open txt("C:\Temp\file.txt")
to solve
enable txt detector
eliminate strings
atc from cmd
atc over cmd
auto solve txt
```

Fluxo tipico:

1. Criar um TXT com um comando ATC por linha. 2. Executar `predefine txt` e indicar o caminho. 3. Executar `solve txt`. 4. O ATC cria um ficheiro `_answers.txt`.

Exemplo de TXT:

```
2+2
sqrt(9)
solver(x-2)
solve equation((x-1)(x-2))
```

```
simplify polynomial((x+1)(x-1))
2++
2+3
```

O ATC deve continuar após uma linha inválida e reportar o erro dessa linha.

29. Scripting

O guia online documenta helpers como:

```
print(...)
get(...)
sprintf(...)
while
for
if
else
switch
case
cls()
break
return
replace
replace by index
count occurrences
delete x occurrences
is contained
calc
is equal
get positive value
is to write
is variable
is contained variable
is contained by index
strlen
```

Use scripting para fluxos repetíveis e teste scripts pequenos antes de os usar em cálculos maiores.

30. Funcoes do utilizador

As funções do utilizador vivem na pasta `User functions`. O autocomplete pode sugerir funções como `atc_<nome>()`.

31. Settings e ambiente

```
current settings
verbose resolution
verbose resolution(1)
verbose resolution(0)
numerical systems
si prefixes
actual time response
dimensions
window
about
auto adjust window
enable atc intro
disable atc intro
clean history
clean
exit
```

32. Ficheiros e pastas

O ATC gere pastas como:

- pasta de dados ATC;
- Scripts examples;
- Source code;
- Strings;
- To solve;

- User functions.

Alguns comandos abrem Explorer, Notepad ou visualizadores externos.

33. Exportacao

Alguns comandos perguntam:

```
Export result? (Yes -> 1 \ No -> 0)
```

Use 1 para exportar ou 0 para ignorar.

34. Verbose resolution

```
verbose resolution(1)  
verbose resolution(0)
```

O modo verbose ajuda a aprender e depurar, mas o uso normal e mais limpo com verbose desligado.

35. Cookbook / Receitas

Documentação online do projeto:

- [Cookbook do ATC](#)

Inclui workflows praticos para cálculo científico, trigonometria, polinómios, matrizes, estatística, DSP, TXT processing, verbose resolution e módulos guiados.

36. Perfis de utilização

Engenharia:

```
solve equation(x^2-5*x+6)  
create matrix(foo\2\2\3)  
foo^2  
unit conversions  
physics calculations
```

Educação:

```
2+3*4  
sin(pi/2)  
mode  
geometry calculations  
function study(x^2)
```

DSP:

```
sinc(0)  
fft(1\0\0\0)  
ifft(1\1\1\1)  
sin(pi/2)+cos(0)
```

Estatística:

```
avg(2\4\6)  
min(3\_1\2)  
max(3\_1\2)  
statistics calculations  
qfunc(0)
```

Finanças:

```
financial calculations  
100*15/100
```

37. Boas práticas

Documentação online do projeto:

- [Boas práticas do ATC](#)

Usar para workflows fiáveis: começar por expressões pequenas, confirmar modo angular, validar parenteses, escolher o solver certo, usar TXT para lotes reprodutíveis e evitar comportamento não documentado.

38. Resolucao de problemas

Se uma expressão falhar:

- verificar parenteses;
- verificar modo angular;
- confirmar se deve usar `_` para negativo;
- confirmar se o comando e interativo;
- testar partes menores da expressão;
- usar `verbose resolution(1);`
- confirmar se a funcionalidade esta documentada e coberta por testes.

39. Documentação e testes

Documentação online do projeto:

- [Testes](#)

Resultado atual validado:

```
All: 376 passed, 0 failed
SolverComplex: 14 passed, 0 failed
Txt: 15 passed, 0 failed
Settings: 7 passed, 0 failed
```

Este guia deve evoluir com os testes e com o comportamento documentado do ATC 2.1.8.