



ANDROID STATIC ANALYSIS REPORT



 appgroffe (1.0.0)


File Name: app-release.apk

Package Name: com.example.appgroffe

Scan Date: May 5, 2025, 7:29 p.m.

App Security Score: 45/100 (MEDIUM RISK)

Grade:



FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
2	4	2	1	0

FILE INFORMATION

File Name: app-release.apk

Size: 18.09MB

MD5: aae7fd58e2df6a7799c52c36e267faea

SHA1: 7c7910a5dab322f22943eda1980203aacdce348c

SHA256: 8041fee3fda7edb9593d0206ca7f3fa385264bc2e7745ea75ee852d6f7168149

APP INFORMATION

App Name: appgroffe

Package Name: com.example.appgroffe

Main Activity: com.example.appgroffe.MainActivity

Target SDK: 35

Min SDK: 21

Max SDK:

Android Version Name: 1.0.0

Android Version Code: 1

APP COMPONENTS

Activities: 1
Services: 0
Receivers: 1
Providers: 1
Exported Activities: 0
Exported Services: 0
Exported Receivers: 1
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: True
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=Android Debug, O=Android, C=US
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2025-03-12 22:08:56+00:00
Valid To: 2055-03-05 22:08:56+00:00
Issuer: CN=Android Debug, O=Android, C=US
Serial Number: 0x1
Hash Algorithm: sha256
md5: b329c247df7ffd9c00f9b777e175b5e7
sha1: 29116f8f4ad942baf37b31f206a68e4256974ad8
sha256: a504c6bd36efd8eec57959867543397ec9039bfc8c6febe72751fd0e01fe56a
sha512: 43677a816f8844184d0cbc8f90d8dc25ae39831507eabe422496a3d5566078dcd0e57578eba47b434fa979378274ff1f46f3cc339c66180db419cf3858d5fc50
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 8f99748fc12ee412010d99cfb4ffb8f650ae108ef164b96c8eb09536d3dbe77a
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
com.example.appgroffe.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Compiler	r8 without marker (suspicious)

NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

CERTIFICATE ANALYSIS

HIGH: 1 | WARNING: 1 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

TITLE	SEVERITY	DESCRIPTION
Application vulnerable to Janus Vulnerability	warning	Application is signed with v1 signature scheme, making it vulnerable to Janus vulnerability on Android 5.0-8.0, if signed only with v1 signature scheme. Applications running on Android 5.0-7.0 signed with v1, and v2/v3 scheme is also vulnerable.
Application signed with debug certificate	high	Application signed with a debug certificate. Production application must not be shipped with a debug certificate.

Q MANIFEST ANALYSIS

HIGH: 1 | WARNING: 2 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version Android 5.0-5.0.2, [minSdk=21]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup] flag is missing.	warning	The flag [android:allowBackup] should be set to false. By default it is set to true and allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 0 | WARNING: 1 | INFO: 2 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
----	-------	----------	-----------	-------

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	a/a.java c0/a0.java c0/e.java c0/f0.java c0/i.java c0/k0.java c0/l.java c0/n.java c0/p.java c0/w.java com/example/appgroffe/MainActivity.java d0/c.java d0/e.java e0/b.java e0/g.java g0/f.java g1/u.java io/flutter/embedding/engine/FlutterJNI.java io/flutter/embedding/engine/renderer/FlutterRenderer\$I mageTextureRegistryEntry.java io/flutter/embedding/engine/renderer/f.java io/flutter/plugin/editing/f.java io/flutter/plugin/editing/k.java io/flutter/plugin/platform/q.java io/flutter/view/AccessibilityViewEmbedder.java io/flutter/view/k.java j0/a.java j0/j.java k/e.java k/g.java k/j.java k/k.java k/o.java k0/a.java o0/a.java r/e.java s/c.java u/s.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	The App uses an insecure Random Number Generator.	warning	CWE: CWE 330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	x/l.java a1/a.java a1/b.java a1/c.java b1/a.java m/g.java
3	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	io/flutter/plugin/editing/c.java k/e.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----	--------------	-------	-------	---------	---------	------------------

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	armeabi-v7a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	armeabi-v7a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	armeabi-v7a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk', '__vsprintf_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	armeabi-v7a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00014	Read file into a stream and put it into a JSON object	file	g1/u.java
00013	Read file and put it into a stream	file	g1/u.java m/c.java m/n.java o0/a.java
00004	Get filename and put it to JSON object	file collection	g1/u.java
00022	Open a file from given absolute path of the file	file	a0/c.java g0/c.java
00209	Get pixels from the latest rendered image	collection	c0/l.java
00210	Copy pixels from the latest rendered image into a Bitmap	collection	c0/l.java
00161	Perform accessibility service action on accessibility node info	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java io/flutter/view/j.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	0/25	
Other Common Permissions	0/44	

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
dartbug.com	ok	IP: 216.239.36.21 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.w3.org	ok	IP: 104.18.23.19 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
developer.android.com	ok	IP: 209.85.145.101 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
api.flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 140.82.112.3 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
docs.flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.unicode.org	ok	IP: 64.182.27.164 Country: United States of America Region: Texas City: Dallas Latitude: 32.814899 Longitude: -96.879204 View: Google Map

EMAILS

EMAIL	FILE
appro@openssl.org	lib/arm64-v8a/libflutter.so

EMAIL	FILE
storationinformation@149124995.fromserial _invocationmirror@0150898._withtype _link@15069316.fromrawpat _uri@0150898.notsimple _growablelist@0150898.withcapaci _future@5048458.immediate _directory@15069316.fromrawpat _list@0150898.of _assertionerror@0150898._create _growablelist@0150898._ofother _bytebuffer@8027147._new _typeerror@0150898._create _growablelist@0150898._ofarray _growablelist@0150898._literal _growablelist@0150898._ofefficie _growablelist@0150898._ofgrowabl ngstreamsubscription@5048458.zoned _double@0150898.fromintege _growablelist@0150898._literal3 _growablelist@0150898.of _hashcollisionnode@201137193.fromcollis _growablelist@0150898._literal2 _uri@0150898.file _list@0150898._ofefficie _growablelist@0150898.generate _list@0150898._ofother _growablelist@0150898._literal5 _timer@1026248.periodic _list@0150898.generate _growablelist@0150898._literal4 _list@0150898._ofarray _uri@0150898.directory _list@0150898._ofgrowabl _growablelist@0150898._literal1 _file@15069316.fromrawpat _compressednode@201137193.single _timer@1026248._internal _list@0150898.empty	lib/armeabi-v7a/libapp.so

_future@5048458.immediatee	
EMAIL	FILE
appro@openssl.org	lib/x86_64/libflutter.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libflutter.so

EMAIL	FILE
storationinformation@149124995.fromserial _invocationmirror@0150898._withtype _link@15069316.fromrawpat _uri@0150898.notsimple _growablelist@0150898.withcapaci _future@5048458.immediate _directory@15069316.fromrawpat _list@0150898.of _assertionerror@0150898._create _growablelist@0150898._ofother _bytebuffer@8027147._new _typeerror@0150898._create _growablelist@0150898._ofarray _growablelist@0150898._literal _growablelist@0150898._ofefficie _growablelist@0150898._ofgrowabl ngstreamsubscription@5048458.zoned _double@0150898.fromintege _growablelist@0150898._literal3 _growablelist@0150898.of _hashcollisionnode@201137193.fromcollis _growablelist@0150898._literal2 _uri@0150898.file _list@0150898._ofefficie _growablelist@0150898.generate _list@0150898._ofother _growablelist@0150898._literal5 _timer@1026248.periodic _list@0150898.generate _growablelist@0150898._literal4 _list@0150898._ofarray _uri@0150898.directory _list@0150898._ofgrowabl _growablelist@0150898._literal1 _file@15069316.fromrawpat _compressednode@201137193.single _timer@1026248._internal _list@0150898.empty	apktool_out/lib/armeabi-v7a/libapp.so

_future@5048458.immediatee	
EMAIL	FILE
appro@openssl.org	apktool_out/lib/x86_64/libflutter.so

SCAN LOGS

Timestamp	Event	Error
2025-05-05 19:29:38	Generating Hashes	OK
2025-05-05 19:29:38	Extracting APK	OK
2025-05-05 19:29:38	Unzipping	OK
2025-05-05 19:29:39	Parsing APK with androguard	OK
2025-05-05 19:29:39	Extracting APK features using aapt/aapt2	OK
2025-05-05 19:29:39	Getting Hardcoded Certificates/Keystores	OK
2025-05-05 19:29:41	Parsing AndroidManifest.xml	OK
2025-05-05 19:29:41	Extracting Manifest Data	OK

2025-05-05 19:29:41	Manifest Analysis Started	OK
2025-05-05 19:29:41	Performing Static Analysis on: appgroffe (com.example.appgroffe)	OK
2025-05-05 19:29:41	Fetching Details from Play Store: com.example.appgroffe	OK
2025-05-05 19:29:41	Checking for Malware Permissions	OK
2025-05-05 19:29:41	Fetching icon path	OK
2025-05-05 19:29:41	Library Binary Analysis Started	OK
2025-05-05 19:29:41	Analyzing lib/arm64-v8a/libflutter.so	OK
2025-05-05 19:29:41	Analyzing lib/arm64-v8a/libapp.so	OK
2025-05-05 19:29:41	Analyzing lib/armeabi-v7a/libflutter.so	OK
2025-05-05 19:29:41	Analyzing lib/armeabi-v7a/libapp.so	OK
2025-05-05 19:29:41	Analyzing lib/x86_64/libflutter.so	OK

2025-05-05 19:29:41	Analyzing lib/x86_64/libapp.so	OK
2025-05-05 19:29:41	Analyzing apktool_out/lib/arm64-v8a/libflutter.so	OK
2025-05-05 19:29:41	Analyzing apktool_out/lib/arm64-v8a/libapp.so	OK
2025-05-05 19:29:41	Analyzing apktool_out/lib/armeabi-v7a/libflutter.so	OK
2025-05-05 19:29:42	Analyzing apktool_out/lib/armeabi-v7a/libapp.so	OK
2025-05-05 19:29:42	Analyzing apktool_out/lib/x86_64/libflutter.so	OK
2025-05-05 19:29:42	Analyzing apktool_out/lib/x86_64/libapp.so	OK
2025-05-05 19:29:42	Reading Code Signing Certificate	OK
2025-05-05 19:29:42	Running APKID 2.1.5	OK
2025-05-05 19:29:45	Updating Trackers Database....	OK
2025-05-05 19:29:45	Detecting Trackers	OK

2025-05-05 19:29:45	Decompiling APK to Java with JADX	OK
2025-05-05 19:29:52	Converting DEX to Smali	OK
2025-05-05 19:29:52	Code Analysis Started on - java_source	OK
2025-05-05 19:29:52	Android SBOM Analysis Completed	OK
2025-05-05 19:29:54	Android SAST Completed	OK
2025-05-05 19:29:54	Android API Analysis Started	OK
2025-05-05 19:29:55	Android API Analysis Completed	OK
2025-05-05 19:29:55	Android Permission Mapping Started	OK
2025-05-05 19:29:55	Android Permission Mapping Completed	OK
2025-05-05 19:29:55	Android Behaviour Analysis Started	OK
2025-05-05 19:29:57	Android Behaviour Analysis Completed	OK

2025-05-05 19:29:57	Extracting Emails and URLs from Source Code	OK
2025-05-05 19:29:57	Email and URL Extraction Completed	OK
2025-05-05 19:29:57	Extracting String data from APK	OK
2025-05-05 19:29:57	Extracting String data from SO	OK
2025-05-05 19:29:57	Extracting String data from Code	OK
2025-05-05 19:29:57	Extracting String values and entropies from Code	OK
2025-05-05 19:29:57	Performing Malware check on extracted domains	OK
2025-05-05 19:29:58	Saving to Database	OK

Report Generated by - MobSF v4.3.3

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2025 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).